



US 20110158787A1

(19) **United States**

(12) **Patent Application Publication**
Thacker, II

(10) **Pub. No.: US 2011/0158787 A1**

(43) **Pub. Date: Jun. 30, 2011**

(54) **WIND TURBINE**

(52) **U.S. Cl. 415/1; 415/213.1**

(76) **Inventor: Andrew Carlton Thacker, II,**
Lakewood, CO (US)

(57) **ABSTRACT**

(21) **Appl. No.: 13/039,951**

(22) **Filed: Mar. 3, 2011**


Related U.S. Application Data

(60) **Provisional application No. 61/314,104, filed on Mar. 15, 2010.**

Publication Classification

(51) **Int. Cl.**
F01D 25/28 (2006.01)

Wind turbine systems and methods are provided. The wind turbine system includes a plurality of coaxial, counter-rotating turbine assemblies. First and second shroud assemblies define a generally spherical volume containing the first and second turbine assemblies. The first and second shroud assemblies each include a shroud member that can selectively shield or expose portions of the respective turbine assemblies to the wind by changing the rotational position of the shroud members about the system axis. The turbine assemblies are interconnected to a generator for the production of electrical power.






FIG.1




FIG.2




FIG.3




FIG.4




FIG. 5




FIG. 6A




FIG. 6B




FIG.6C




FIG.7A




FIG. 7B




FIG.7C




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 8D




FIG.9A




FIG. 9B




FIG. 10




FIG. 11A




FIG. 11B




FIG. 12A




FIG. 12B




FIG. 13A




FIG. 13B




FIG. 14A




FIG. 14B




FIG. 15A




FIG. 15B




FIG. 16A




FIG. 16B




FIG.17

WIND TURBINE

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of U.S. Provisional Patent Application Ser. No. 61/314,104, filed Mar. 15, 2010, the entire disclosure of which is hereby incorporated herein by reference. This application is related to U.S. Application Ser. No. _____, filed _____, entitled "WIND TURBINE CONTROL", and identified as Attorney Docket No. 6228-2, the entire disclosure of which is hereby incorporated herein by reference.

FIELD

[0002] The present invention is directed to wind turbine systems and methods. More particularly, the present invention relates to wind turbine systems and methods that utilize counter-rotating turbine assemblies.

BACKGROUND

[0003] Several decades of development have focused on harnessing the power of the wind to turn water and grist mills, and since the invention by Westinghouse in the late 1800's, to produce electrical power. Many types of designs have been proffered, however, they have been focused almost entirely on horizontal turbines with blades, sails or propellers to convert the kinetic energy of wind into a force to drive various types of electrical generators, including alternating current (AC), direct current (DC) and 3-phase current for storing and using power as the demand presents itself or to provide power directly into the public and private utility grids for distribution from substations to homes, offices, hotels, casinos, cities and municipalities, industrial and other energy dependent user applications.

[0004] The past 20 years has seen a much greater emphasis on renewable energy sources as alternatives to fossil fuel power plants burning coal, natural gas, fuel oil or nuclear fuels to produce steam to power large scale electrical generators to reduce the impact of carbon compounds upon the Earth's atmosphere. These efforts have primarily been directed to large scale utility grids and the emphasis has been on large scale production systems (wind farms) greater than 1 megawatt that are geographically concentrated in remote locations where wind is available. It is now common to see systems greater than 4 megawatts in one tower. The systems developed can cost multi-million dollars each. The systems can be highly complex, enormous in size and scale and number in the tens of thousands in North America and worldwide. Towers of 200-400 feet in height are common on prairies and savannas, along our coastal regions, and even offshore in shallow ocean waters. It was thought that these systems would have an enormous impact in offsetting the use of carbon based fuels and provide a cheap source of unlimited power.

[0005] Unfortunately, this has not been the case and large utilities are now rethinking their use of these systems due to several inherent problems with the design and deployment of the systems. Among the problems impacting these systems are variations in wind speeds over the sweep of the propellers (60 ft-450 ft), ground turbulence that causes prop dithering and imbalance, and gusting winds that apply uneven forces and torquing of the drive axles which have resulted in expensive and time consuming repairs of system mechanical drive

trains and transmissions which cannot respond quickly to these changing dynamic loads. Other problems include overheating of the turbines resulting in transmission system and hydraulic system fires, wind loads that have caused complete system failure and total collapse of the towers, flickering light patterns disturbing cattle and other livestock, and complaints from people living near the turbines with regard to noise, bird kills, and flickering light patterns in their home windows. Recently complaints have been lodged by the Federal Aviation Administration and the United States AeroSpace Command regarding interference with air traffic control radar and guidance systems both on the ground and airborne caused by large scale wind farms.

[0006] Additionally, significant losses in electrical energy are incurred due to long distance transmission from the wind farm sites to the utility substations which has resulted in low utilization of wind power and has reduced the effectiveness and reliability of the power generated. System shut down in gusty and turbulent wind conditions has resulted in "spiking" in the utility grid, creating inefficiency. The system loads can be unpredictable and unreliable. In many cases, wind energy is not used due to these problems and the utility industry is rethinking its investment and deployment strategy.

[0007] On a smaller scale, wind turbine systems have been developed for generating power at or near the point of use. However, such systems have typically had only modest power generation capabilities, thereby limiting their application to the useful generation of power. For example, such systems have been utilized for low power applications, such as charging batteries and direct current (DC) applications. As a result, deployment of such systems has typically been limited to remote locations, where electrical power may otherwise be unavailable, as opposed to being deployed as an alternate energy source where grid power is otherwise available. Therefore, the use of wind generated electrical power at or near the point of use, on a scale at which the sale of electricity to an electric utility during times when the wind generated power is not entirely consumed at the location, has been limited.

SUMMARY

[0008] The present invention is directed to solving these and other problems and disadvantages of the prior art. In accordance with embodiments of the present invention, a wind turbine system having first and second turbine assemblies is provided. The first and second turbine assemblies are configured to rotate about a first axis, in opposite directions, in the presence of a suitable wind. In addition, first and second shroud assemblies are associated with the first and second wind turbine assemblies respectively. The first and second shroud assemblies extend around the outer circumference of the corresponding first and second turbine assemblies. In addition, the shroud assemblies include shroud members that extend around some portion of the outer circumference of the respective turbine assembly.

[0009] In accordance with further embodiments of the present invention, the first turbine assembly is interconnected to a first drive shaft having an axis of rotation that is coincident with the first axis of the system. In addition, the second turbine assembly is interconnected to a second drive shaft that has an axis of rotation that also is coincident with the first axis of the system. Moreover, at least a portion of the second drive shaft can be received by and rotate within the first drive shaft. The first and second drive shafts are part of a drive train

assembly that can operate to transfer wind energy from the turbine assemblies to a generator.

[0010] A wind turbine system in accordance with embodiments of the present invention can include a base member to which the turbine assemblies and the shroud assemblies are interconnected, either directly or through other components. For example, the first shroud assembly can be interconnected to the base member, and the second shroud assembly can in turn be interconnected to the first shroud assembly. Moreover, the first shroud assembly can be selectively positioned by rotating the first shroud assembly about the first axis of the system and relative to the base member. In accordance with further embodiments of the present invention, the second shroud assembly can be selectively positioned by rotating the second shroud assembly about the first axis of the system relative to the base member and the first shroud assembly. In accordance with still further embodiments of the present invention, the first and second shroud assemblies can comprise a support structure that at least partially supports one or both of the turbine assemblies. In addition, the first drive shaft of the first wind turbine assembly can be rotatably interconnected to the base member. The second drive shaft of the second wind turbine assembly can also be rotatably interconnected to the base member. In addition, bearings can rotatably interconnect the first and second drive shafts. In accordance with still other embodiments, one or both of the first and second drive shafts can be interconnected to a support structure comprising one or both of the shroud assemblies.

[0011] Methods in accordance with embodiments of the present invention include providing counter-rotating turbine assemblies. The turbine assemblies are selectively exposed to the wind through operation of shroud assemblies. More particularly, the shroud assemblies are rotated about a first axis of the system to expose a portion of a corresponding wind turbine assembly to the wind, while shielding another portion of that wind turbine assembly from the wind. The shroud assemblies can thus be used to control the exposure of the turbine assemblies to the wind so that the turbine assemblies are driven in a desired direction and to control the force of the wind on the turbine assemblies. In addition, the shroud assemblies can be positioned to entirely or substantially shield the turbine assemblies, for example where the generation of power is not desired, or to protect the wind turbine system from extremely strong winds.

[0012] Additional features and advantages of embodiments of the present invention will become more readily apparent from the following description, particularly when taken together with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] FIG. 1 depicts a wind turbine system in accordance with embodiments of the present invention in an exemplary operating environment;

[0014] FIG. 2 is a block diagram depicting components of a wind turbine system in accordance with embodiments of the present invention;

[0015] FIG. 3 is a front view in elevation of a wind turbine system in accordance with embodiments of the present invention;

[0016] FIG. 4 is a perspective view of a wind turbine system in accordance with embodiments of the present invention;

[0017] FIG. 5 is a perspective view of wind turbine system support structure components in accordance with embodiments of the present invention;

[0018] FIG. 6A is a top perspective view of a first turbine assembly in accordance with embodiments of the present invention;

[0019] FIG. 6B is a top plan view of a first turbine assembly in accordance with embodiments of the present invention;

[0020] FIG. 6C is a view in elevation of a first turbine assembly in accordance with embodiments of the present invention;

[0021] FIG. 7A is a top perspective view of a second turbine assembly in accordance with embodiments of the present invention;

[0022] FIG. 7B is a top plan view of a second turbine assembly in accordance with embodiments of the present invention;

[0023] FIG. 7C is a view in elevation of a second turbine assembly in accordance with embodiments of the present invention;

[0024] FIG. 8A is a front perspective view of a turbine assembly blade in accordance with embodiments of the present invention;

[0025] FIG. 8B is a side elevation of a turbine assembly blade in accordance with embodiments of the present invention;

[0026] FIG. 8C is a first end view of a turbine assembly blade in accordance with embodiments of the present invention;

[0027] FIG. 8D is a second end view of a turbine assembly blade in accordance with embodiments of the present invention;

[0028] FIG. 9A depicts a portion of a turbine assembly in accordance with embodiments of the present invention;

[0029] FIG. 9B is a plan view of a turbine assembly with a blade that has been displaced in accordance with embodiments of the present invention;

[0030] FIG. 10 is a cross-section of a compliance unit in accordance with embodiments of the present invention;

[0031] FIG. 11A depicts a wind turbine system in accordance with embodiments of the present invention, and illustrates shroud member positions in an exemplary operating environment;

[0032] FIG. 11B depicts the shroud member positions of FIG. 11A in plan view;

[0033] FIG. 12A depicts a wind turbine system in accordance with embodiments of the present invention, and illustrates shroud member positions in another operating environment;

[0034] FIG. 12B depicts the shroud member positions of FIG. 12A in plan view;

[0035] FIG. 13A depicts a wind turbine system in accordance with embodiments of the present invention, and illustrates shroud member positions in another operating environment;

[0036] FIG. 13B depicts the shroud member positions of FIG. 13A in plan view;

[0037] FIG. 14A depicts a wind turbine system in accordance with embodiments of the present invention, and illustrates shroud member positions in another operating environment;

[0038] FIG. 14B depicts the shroud member positions of FIG. 14A in plan view;

[0039] FIG. 15A depicts a wind turbine system in accordance with embodiments of the present invention, and illustrates shroud member positions in another operating environment;

[0040] FIG. 15B depicts the shroud member positions of FIG. 15A in plan view;

[0041] FIG. 16A depicts a wind turbine system in accordance with embodiments of the present invention, and illustrates shroud member positions in another operating environment;

[0042] FIG. 16B depicts the shroud member positions of FIG. 16A in plan view; and

[0043] FIG. 17 is a flowchart depicting aspects of the operation of a wind turbine system 104 in accordance with embodiments of the present invention, and in particular operation while the wind turbine system 104 is in a power generation mode.

DETAILED DESCRIPTION

[0044] FIG. 1 depicts a wind turbine system 104 in accordance with embodiments of the present invention, in an exemplary operating environment. In particular, the wind turbine system 104 is shown mounted to a platform 108. In this example, the platform 108 comprises a tall building, and the wind turbine system 104 is mounted to the roof of that building 108. However, a wind turbine system 104 in accordance with embodiments of the present invention can be associated with any type of platform 108. Therefore, examples of suitable platforms 108 to which a wind turbine system 104 as disclosed herein can be mounted include, in addition to tall buildings such as skyscrapers, mid-rise buildings, warehouses, big box retail stores, residences, towers, storage tanks, bridges or platforms. In addition, although depicted in an upright vertical orientation in the example of FIG. 1, a wind turbine system 104 can be mounted in alternate orientations. For example, a wind turbine system 104 can be mounted in a horizontal orientation, for instance to the side of a platform 108 comprising a building or tower. As another example, a wind turbine system 104 in accordance with embodiments of the present invention can be mounted in an upside down vertical orientation, for example to the underside of a bridge.

[0045] FIG. 2 is a block diagram depicting components of a wind turbine system 104 in accordance with embodiments of the present invention. In general, the wind turbine system 104 can include a number of shroud assemblies 204. For instance, a wind turbine system 104 can include a first shroud assembly 204a and a second shroud assembly 204b. In general, each shroud assembly 204 is associated with and can at least partially define a volume containing a turbine assembly 208. Accordingly, a wind turbine system 104 can include a first turbine assembly 208a and a second turbine assembly 208b. The turbine assemblies 208 can be coupled to an electrical generator 212 by a drive train assembly 216. Although referred to herein as a generator 212, the component of the wind turbine system 104 used to generate electricity may comprise a motor operated as an electrical generator. As an example, and without limitation, the generator 212 may comprise a 60 Hz 3 phase permanent magnet generator. Moreover, the drive train assembly 216 can include drive shafts that interconnect the turbine assemblies 208 to an input shaft of the generator 212 via a clutch. In accordance with embodiments of the present invention, the generator 212 can comprise any electrical generator. The wind turbine system 104 can also include a shroud control system 220. The shroud control system 220 can comprise motors, sensors, and controllers or processors for determining and controlling the position of the shroud assemblies 204.

[0046] FIG. 3 depicts a wind turbine system 104 in accordance with embodiments of the present invention in elevation. In this exemplary embodiment, the wind turbine system 104 is mounted to a base member 304 that is in turn mounted to the platform 108. In this embodiment, the base member 304 includes a bottom plate or first end surface 308 and a top plate or second end surface 312. Although the terms top and bottom are used throughout the specification for ease of description, it should be appreciated that the wind turbine system 104 can be oriented such that the bottom surface is above the top surface, or is at the same elevation or average elevation above the ground as the top surface, depending on the orientation of the wind turbine system 104. Accordingly, as used herein, a bottom surface, member or other element refers to an instance of the associated component or assembly that is more proximal to the platform 108 or the base member 304 than is a top component or assembly. The bottom plate or first end surface 308 can comprise a first circular end surface, while the top plate or second end surface 312 can comprise a second circular end surface. In this particular embodiment, the base member 304 includes an intermediate section 316 having a diameter that is less than the diameter of the first circular end surface 308 and the second circular end surface 316. Accordingly, the base member 304 can have a profile that is tapered in the center.

[0047] The first shroud assembly 204a is mounted to the base member 304 via a first circular track or peripheral bearing assembly 320. The first peripheral bearing assembly 320 allows the first shroud assembly 204a to be rotated relative to the base member 304 about a first or system axis 324. A first central bearing assembly 328 can also be provided to rotatably interconnect the first shroud assembly 204a to the base member 304 and/or a first drive shaft 332. The second shroud assembly 204b is interconnected to the first shroud assembly 204a via a second circular track or equatorial bearing assembly 336. The equatorial bearing assembly 336 allows the second shroud assembly 204b to be rotated about the system axis 324 relative to the base member 304, and relative to an independently of the first shroud assembly 204a. A second central bearing assembly 340 can also be provided to rotatably interconnect the second shroud assembly 204b to a second drive shaft 344. Sensors comprising position encoders can be associated with or incorporated into some or all of the bearing assemblies 320, 328, 336 and 340, to provide information to a controller of the shroud control system 220 regarding the positions of the shroud assemblies 204 about the system axis 324.

[0048] Each of the shroud assemblies 204 includes a shroud member 348. In particular, a first shroud member 348a associated with the first shroud assembly 204a generally extends between the first peripheral bearing assembly 320 and the hemispherical bearing assembly 336. In accordance with at least some embodiments, the first shroud member 348a is mounted to the first shroud assembly 204a via the first peripheral bearing assembly 320 and the equatorial bearing assembly 336, and thus can be rotated relative to the system or central axis 124 and the first shroud assembly 204a by moving the shroud member 348a along the bearing assemblies 320 and 336. In addition, the first shroud member 348a is generally hemispherical in that it extends for about one half the outer circumference of the first shroud assembly 204a. The second shroud assembly 348b generally extends between the hemispherical bearing 336 to or near a top extent of the wind turbine system 104. In accordance with at least some

embodiments, the second shroud member **348b** is mounted to the second shroud assembly **204b** via a second peripheral bearing assembly **322** and the equatorial bearing assembly **336**, and can be rotated relative to the central axis **124** and the second shroud assembly **204b** by moving the shroud member **348b** along the bearing assembly **322** and **336**. The second shroud member **358b** is generally hemispherical in that it extends around about one half the outer circumference of the second shroud assembly **204b**. In addition, the shroud assemblies **204** together define a shape that is generally spherical.

[0049] The shroud assemblies **204** also generally describe a partially enclosed volume comprising a housing for the turbine assemblies **208**. In particular, the first shroud assembly **204a** partially encloses the first turbine assembly **208a**. Similarly, the second shroud assembly **204b** partially encloses the second turbine assembly **208b**. The rotational locations about the system axis **324** that are enclosed by the shroud members **348** of the shroud assemblies **204** are controlled to provide a desired operational state of the wind turbine system **104**, as described elsewhere herein. Moreover, positioning of the shroud assemblies **204** can be effected through the actuation of motors, such as stepper motors, associated with or incorporated into some or all of the bearings **320**, **328**, **336**, and **340**. In addition, embodiments of the present invention include turbine assemblies **208** that each comprise a plurality of airfoils or blades **352** having a first surface **804** and a second surface **808**. Moreover, the blades **352** of the first turbine assembly **208a** are oriented to rotate that assembly **208a** in a first direction about the system axis **324**, while the blades **352** of the second turbine assembly **208b** are oriented to rotate that assembly **208b** in a second direction about the system axis **324**. In accordance with embodiments of the present invention, the first turbine assembly **208a** may have a first number of blades **352**, and the second turbine assembly **208b** may have a second, different number of blades **352**. Accordingly, the turbine assemblies **208** are asynchronous in operation. Each of the blades **352** of the first turbine assembly **208a** can be interconnected to the first drive shaft **332** by a blade support structure **356**. Similarly, each of the blades **352** of the second turbine assembly **208b** can be interconnected to the second drive shaft **344** by a blade support structure **356**. The blade support structure **356** can include one or more struts, although other configurations are possible.

[0050] FIG. 4 is a perspective view of a wind turbine system **104** in accordance with embodiments of the present invention. More particularly, FIG. 4 illustrates the relationship of a wind turbine system **104** to a prevailing wind **404** and flow paths through the wind turbine system **104** under exemplary operating conditions. In FIG. 4, the shroud assemblies **204** are shown positioned such that about a 90° section or arc of each of the turbine assemblies **208** is exposed to face the wind **404**. Moreover, the shroud assemblies **204** are positioned so that the wind is incident on the first side or surface **804** of the blades **352** of the turbine assemblies **208**, and to allow the wind **404** to apply a generally tangential force on the turbine assemblies **208** such that the turbine assemblies **208** rotate in opposite directions about the system axis **324**. Thus, in this example, the resulting exposure of the turbine assemblies **208** to the incident wind **404** causes the first turbine assembly **208b** to be rotated in a clockwise direction about the system axis **324**, and causes the second turbine assembly **208b** to be rotated in a counter-clockwise direction, when the wind turbine system **104** is viewed from above. In addition, the wind turbine system **104** provides a stepper or dual compressor

effect with respect to at least some of the incident wind **404**. In particular, the blades **352** of the first turbine assembly **208a** generally direct at least some of the wind incident thereon upwards through the wind turbine system **104**, to the second turbine assembly **204b**. Therefore, in addition to the wind **404** that is directly incident on the blades **352** of the second turbine assembly **208b**, at least some wind that was incident on the blades **352** of the first turbine assembly **204a** is available to also act on the blades **352** of the second turbine assembly **208b**.

[0051] As can be appreciated by one of skill in the art after consideration of the present disclosure, the counter-rotation of the first **208a** and second **208b** turbine assemblies results in a small or even zero torsional force on an associated platform **108**. In addition, the counter-rotating turbine assemblies **208** can provide reduced vibration characteristics as compared to systems that do not employ counter rotating turbine assemblies or elements that are asynchronous due to having differing numbers of blades or airfoils. For example, the first turbine assembly **208a** may have a larger number of blades than the second turbine assembly **208b**. In addition, the flow paths of the wind **404** through the turbine assemblies **208** and the movement of the turbine assemblies **208** in a direction that is generally away from the incident wind **404** can provide a safer environment for birds and other wildlife.

[0052] FIG. 5 is a perspective view of components of a support structure **504** of a wind turbine system in accordance with embodiments of the present invention. In addition, FIG. 5 illustrates the generally spherical volume or truncated spherical volume defined by the shroud assemblies **204**. The support structure **504** can include the base member **304**, the first shroud assembly **204a**, and the second shroud assembly **204b**. Additional details of embodiments of the shroud assemblies **204** are also illustrated. In particular, it can be seen that each shroud assembly **204** includes an equatorial support member **508**. Moreover, the equatorial support member **508a** of the first shroud assembly **204a** is interconnected to the equatorial support member **508b** of the second shroud assembly **204b** by the equatorial bearing assembly **336**. As discussed elsewhere herein, the equatorial bearing assembly **336** allows the rotational position of the second shroud assembly **204b** to be changed relative to the first shroud assembly **204a** and the base member **304**. In accordance with further embodiments of the present invention, each shroud assembly **204** can include a number of longitudinal support members **510**. For example, each shroud assembly **204** can include four longitudinal support members **510** spaced at 90° intervals. Moreover, each shroud assembly **204** can include radial members **514** that extend between the equatorial support member **508** and a center ring **518** of the associated shroud assembly **204**. It can also be seen that, at least in some embodiments of the disclosed invention, the support for the second shroud assembly **204b** can be entirely or primarily provided by the first shroud assembly **204a**.

[0053] In addition to an equatorial support member **508** and longitudinal support members **510**, each shroud assembly **204** can include a web structure **512**. In general, the web structure **512** provides support for a corresponding shroud assembly **204**, at an end of that shroud assembly **204** opposite the equatorial support member **508**, and also provides support for longitudinal support members **510** that extend between the web structure **512** and the equatorial support member **508**. The web structure **512a** associated with the first shroud assembly **204a** can also include or can be proximate to a

portion of the peripheral bearing assembly 320 associated with the first shroud assembly 204a, and/or the central bearing assembly 328. The web structure 512b associated with the second shroud assembly 204b can function to provide additional support for the second shroud member 348b. In addition, the second web structure 512b can include or be associated with a portion of the bearing assembly 340. FIG. 5 also illustrates an access panel 516 in the base member 304. The access panel 516 can be used to access the generator 212 and/or other wind turbine system 104 components housed within the base member 304. In accordance with other embodiments of the present invention, the shroud members 348 can be rotated around the central axis 324 relative to the associated shroud assembly 204 support members and structures. For example, each shroud member 348 can be mounted to the remainder of the wind turbine system 104 by the equatorial bearing assembly 336 and by end bearings 518 interconnected to the web structure 512 of the associated shroud assembly 204.

[0054] FIGS. 6A-6C illustrate top perspective, top plan, and elevation views respectively of a first turbine assembly 208a in accordance with embodiments of the present invention. As previously noted, the first turbine assembly 208a includes a plurality of airfoils or blades 352. In this example, eight blades 352 are shown. However, this is not a requirement, and the number of blades 352 in a particular embodiment will depend on the design of the individual airfoils 352 and other considerations. For instance, it is desirable to maintain a spacing between blades 352 that is sufficient to allow the individual blades 352 to operate efficiently. In particular, a blade 352 can function as a lifting body through at least some portion of the rotation of the turbine assembly 208. For example, with an associated shroud assembly 204 positioned so that the turbine assembly 208 can extract a maximum amount of energy from the wind, a blade 352 will act as a lifting body as it comes from behind the shroud member 348 and enters the air flow or wind, and for some additional degrees of rotation of the turbine assembly 208. Therefore, it is desirable to maintain a spacing between blades 352 that is large enough to allow each blade 352 to generate lift without being negatively impacted by turbulence from adjacent blades 352. Moreover, the blades 352 can be spaced such that as the angle of attack of a blade 352 increases and the blade 352 begins to spill wind, that spilled wind is directed towards and impacts a downwind blade 352. In addition, once the blade 352 has advanced to a point that the blade 352 is more normal to the wind, it is beneficial to maintain spacing between the blades 352 that is large enough to allow the wind to impact the blade 352 unimpeded or relatively unimpeded by the next blade 352. As can be appreciated by one of skill in the art, in selecting the number of blades 352 to include in a turbine assembly 208, the benefits of maintaining space between blades 352 is generally balanced against the additional force that can be extracted from wind of a given velocity by having a larger number of blades 352 exposed to the wind at a particular moment in time.

[0055] Each blade 352 in the illustrated example is interconnected to the first drive shaft 332 by a support structure 356 comprising a plurality of support struts 604. From the views in FIGS. 6A-6C, it can be appreciated that the blades 352 are shaped to be effective to rotate the first drive shaft 335 when a portion of the wind turbine assembly 208 is exposed to an incident wind with a component that is generally tangential to an outer circumference of the turbine assembly

208a. In particular, the blades 352 of the first wind turbine assembly 208a are configured to rotate the first drive shaft 335 in a clockwise direction, when the first wind turbine assembly 204a is viewed from above, and when exposed to such an incident wind. In addition, the blades 352 can be configured to direct at least some wind incident on the blades 352 in an end to end (e.g., a bottom to top) direction. Moreover, the outer edges 812 can be contoured so that the overall profile of the blade portion of the first turbine assembly 208a is hemispherical or hemispherical-like.

[0056] FIGS. 7A-7C illustrate a second turbine assembly 208b in accordance with embodiments of the present invention in top perspective, top plan and elevation views respectively. Similar to the first turbine assembly 208a, the second turbine assembly 208b includes a plurality of airfoils or blades 352. The blades 352 of the second turbine assembly 208b are interconnected to the second drive shaft 344 by a support structure 356. In the illustrated example, the support structure 356 includes a plurality of support struts 604 associated with each blade 352. In this embodiment, the blades 352 are configured to rotate the second drive shaft 344 in a counterclockwise direction when the second turbine assembly 208b is viewed from above, in the presence of an incident wind having a component that is generally tangential to an outer circumference of the turbine assembly 208a. In addition, it can be appreciated that the blades 352 are configured to impart a rotational force to the second drive shaft 344 in a counterclockwise direction in response to an updraft of wind (or a bottom to top flow generally parallel to the system axis 324), such as may be provided by a first turbine assembly 208a in a wind turbine system 104 configured as illustrated in, for example, FIGS. 3 and 4. It can also be appreciated that at least a portion of the wind incident on the second turbine assembly 208b, either tangentially or as an updraft, can be exhausted in an upward direction (or in a direction generally parallel to the system axis 324). The outer edges 812 of the blades 352 can be contoured so that the overall profile of the blade portion of the second turbine assembly 208b is hemispherical or hemispherical-like.

[0057] In the example first turbine assembly 208a of FIGS. 6A-6C, seven blades 352 are shown, while in the example second turbine assembly 208b of FIGS. 7A-7C, six blades 352 are shown. The number of blades 352 in the turbine assemblies 208 of a particular embodiment of a wind turbine system 104 in accordance with the present invention will vary depending on the particular application and design considerations for example as described above in connection with the first turbine assembly 208a. In accordance with at least some embodiments of the present invention, the first 208a and second 208b turbine assemblies each have a different number of blades 352. In accordance with still further embodiments, the first turbine assembly 208a has a larger number of blades 352 than the second turbine assembly 208b. By so configuring the wind turbine system 104, vibration and noise produced during operation of the wind turbine system 104 can be reduced as compared to embodiments in which the first 208a and second 208b turbine assemblies have the same number of blades 352.

[0058] FIGS. 8A-8D provide different views of a blade 352 of a turbine assembly 204 in accordance with embodiments of the present invention. In particular, FIG. 8A is a perspective view, FIG. 8B is a side elevation, FIG. 8C is a first plan view, and FIG. 8D is a second plan view of an exemplary blade 352 in accordance with embodiments of the present invention.

The blade **352** includes a first surface **804** that is cupped or profiled to capture wind incident on that surface **804**. In addition or as an alternative to trapping wind like a bucket, the blades **352** can comprise lifting bodies. Therefore, a wind turbine system **104** can comprise both impulse turbine and reaction turbine operating principles. In operation, a wind turbine system **104** in accordance with embodiments of the present invention generally positions the shroud members **348** such that the wind is allowed to be incident on the first surface **804** of the turbine assembly **208** blades **352**. In addition, each blade **352** has a second surface **808** that is relatively streamlined such that, to the extent the blade **352** travels in a direction away from the first side **804** and towards the second side **808** of the blade **352**, any air in front of the blade **352** during such movement is easily displaced. Accordingly, the blades **352** may be profiled such that the turbine assembly **208** including such blades **352** is rotated in one particular direction in the presence of a wind with a component that is tangential to the outer circumference of the turbine assembly **208**.

[0059] In addition, the shape and/or contour of a blade **352** can be compound complex geometry and/or asymmetric geometry. For instance, the width **W** of the blade **352** can be different at different points along the length **L** of the blade **352**. In addition, an outer side edge or leading edge **812** of the blade **352** can be curved, to define the generally hemispherical shape of a turbine assembly **208** including the blade **352**. The blade **352** also includes an inner side edge or trailing edge **816** that, together with the outer side edge **812**, defines the width of the blade **352**. For example, and as shown in FIG. **8A**, the side edges **812** and **816** can define a blade **352** with a width **W** that generally decreases from a base edge or end **820** of the blade **352** to the tapered or narrowed edge or end **824** of the blade **352**. Moreover, the first surface **804** may curve from the base edge **820** to the tapered edge **824**. For example, the curve may be generally inwardly from the base edge **820** to the tapered edge **824**.

[0060] In addition to various curves and changes in dimension along the length **L** of the blade **352** when considered in a front view (see generally FIG. **8A**), the blade **352** can also vary in the depth **D** of the cup or concave surface (or alternatively the height of the concave back surface **808**). This depth **D** may vary with position along the length **L** of the blade **352**. For example, moving from the base edge **820**, the depth **D** can increase as the distance from the base edge **820** along the length **L** increases. After reaching a maximum point proximate the base edge **820**, the depth **D** may gradually decrease as the distance from the base edge **820** along the length **L** decreases, until a minimum depth **D** proximate the tapered edge **824** is reached.

[0061] After consideration of FIGS. **8A-8D**, it can be appreciated that the blade **352** may be contoured so as to provide a lifting body or airfoil. Therefore, wind flowing across the blade **352** will produce lift, at least within some range of angles of attack. Accordingly, the blades **352** may comprise airfoils or lifting bodies. Moreover, lift generated by the blades **352** of a turbine assembly **208** will result in a force in a direction that tends to rotate the associated turbine assembly **208**. In addition, wind incident on the first surface **804** of a blade **352** is generally captured by the blade **352**, to promote a transfer of energy from that wind to, for example, a turbine assembly **208** that includes the blade **352**. Moreover, the blade **352** generally moves in a direction away from the wind. As a result, turbine assemblies **208** incorporating the

blades **352** can comprise a combination of impulse turbine and reaction turbine operating characteristics.

[0062] FIG. **9A** is an illustration of a portion of a turbine assembly **208** in accordance with embodiments of the present invention. In particular, portions of a drive shaft **332** or **344** and of a blade support structure **356** are illustrated. The blade support structure **356** is shown as including a plurality of struts **604**. Each of the struts **604** can be interconnected to the drive shaft **332** or **344** via a hinge plate **906** and a compliance unit or structure **908**. Each hinge plate **906** is interconnected to the associated drive shaft **332** or **344** via a hinge **910**. The compliance unit **908**, together with the hinge plate **906**, provide a mechanism by which an airfoil **352** can move relative to the interconnected drive shaft **332** or **344** when the force of the wind on the blade **352** is especially strong. Accordingly, high forces, for example from gusting winds or sudden increases in wind velocity, can be absorbed by the wind turbine system **104** in a controlled manner.

[0063] FIG. **9B** illustrates a turbine assembly **208** in plan view, with a blade **352a** that has been temporarily displaced by a gust of incident wind **404**. In particular, the radial spacing of the displaced blade **352a** with respect to the preceding blade **352b** has been increased, while the radial spacing between the displaced blade **352a** and a following blade **352c** has decreased. This change in radial spacing is a result of the struts **604** of the support structure **356** associated with the first blade **352a** transmitting a force to the compliance unit **908** that is greater than some threshold amount. Such a situation may occur, for example, where the incident wind **404** momentarily gusts. Accordingly, excess wind or a sudden increase in force imparted to a blade **352** can be absorbed. In particular, the blade **352** is allowed to open, dumping wind while absorbing force by moving against the compliance unit **908**. With reference again to FIG. **9A**, it can be appreciated that, as the radial position of the blade **352** with respect to the drive shaft **332** or **344** changes, the compliance unit **908** is compressed, and the hinge plate **906** pivots about the hinge **910** with respect to each strut **604** included in the support structure **356**.

[0064] In accordance with further embodiments of the present invention, the compliance unit **908** can function as both a spring and a damper. More particularly, as depicted in FIG. **10**, the compliance unit **908** can include a housing **1002** and a shaft member **1004** with a first end **1008** that, in an assembled state, is interconnected to a strut **604**. The second end of the shaft **1004** comprises a plunger or piston **1012**. The piston **1012** travels within a fluid **1014** that fills the interior chamber **1016** of the compliance unit. The interior chamber **1016** can be separated from the ambient environment by first **1020** and second **1024** seals. An equalization plate **1028** having a plurality of holes **1032** formed therein divides the fluid filled chamber **1016** into first **1036** and second **1040** sub chambers, with the holes **1032** allowing for communication of the fluid **1014** between the first **1036** and second **1040** sub chambers. The equalization plate **1028** can travel along at least some of the length of the fluid filled chamber **1016**. In addition, a resilient member **1044**, such as a spring or the like, can be provided within the second sub chamber **1040**. The resilient member **1044** biases the shaft **1004** towards a fully extended position. An inlet **1048**, and a relief fitting **1052** can be provided on the housing **1002** to allow for communication with the fluid filled chamber **1016**. Moreover, various sensors **1056** can be provided, for example to monitor internal forces,

operating temperatures, the position of the piston **1012** within the chamber **1016**, and/or other operating parameters.

[0065] In operation, a force applied at the first end **1008** of the shaft **1004**, for example from a gust of wind acting on a blade **352** supported at least in part by a strut **604** interconnected to the shaft **1004**, will tend to push the piston **1012** against the resilient member **1044**. When the force applied through the shaft **1004** to the resilient member **1044** is great enough, the shaft will compress the resilient member **1044**, allowing the radial position of the associated blade **352** to change with respect to the associated shaft **332** or **344**. In addition, the piston **1032** and the equalization plate **1028** dampen movement of the shaft **1004** with respect to the housing **1002**. Accordingly, the rate at which the radial position of the blade **352** associated with the compliance unit **908** can change is restricted. As the blade **352** continues its rotation away from the incident wind **404** (see FIG. 9B), the force on the blade **352** will lessen. Once the force transmitted by the blade **352** to the shaft **1004** is less than the countering force of the resilient member **1044**, the strut **1004** will be pushed back against the strut **604**, and the blade **352** will return to its normal radial position with respect to the associated drive shaft **332** or **344**. As can be appreciated by one of skill in the art after consideration of the present disclosure, the rate at which the shaft **1004** moves relative to the housing **1002** is limited by the damping effect provided by the flow of the fluid **1014** in the chamber **1016** through the holes **1032** in the equalization plate **1028**. As can be appreciated by one of skill in the art after consideration of the present disclosure, different configurations of compliance units **908** can be used to absorb sudden increases in the force imparted to a blade **352** by the incident wind. For example, separate, instead of integrated, spring and damper units can be utilized. As a further example, a compliance unit **908** can be arranged such that an associated spring operates in tension rather than compression. In accordance with still other embodiments, compliance can be provided by the support structure **356**, for example through the provision of flexible struts **604**.

[0066] FIGS. 11A-11B illustrate shroud member **348** positions relative to the wind **404**, while the wind turbine system **104** is in a power generation mode, and while the wind **404** is incident on the wind turbine system **104** from a first direction. More particularly FIG. 11A is a view in elevation of a wind turbine system **104** in a power generation mode, with the wind traveling in a direction that is directly into the page. The configuration of the shrouds **348** illustrated in FIG. 11A is depicted in a top plan view in FIG. 11B. In this configuration, the wind turbine system **104** can draw a maximum amount of available energy from the incident wind **404**. In particular, one quadrant or about 90° of a first area **1104a** in a first hemisphere of the wind turbine system **104** is uncovered, thus exposing the first turbine assembly **208a** (see, e.g., FIG. 2) to the wind **404**. Similarly, a second area **1104b** in a second hemisphere of the wind turbine system **104** is unshielded by the second shroud **348b**, exposing a portion of the second turbine assembly **208b** (see, e.g., FIG. 2) to the incident wind **404**. As can be appreciated by one of skill in the art after consideration of the disclosure provided herein, by thus exposing the turbine assemblies **208** to the incident wind **404**, at least a first component of that incident wind **404** is tangential to the first turbine assembly **208a**, and at least a second component of the incident wind **404** is tangential to the second turbine assembly **208b**. Moreover, by exposing the turbine assemblies **208** to the wind at opposed quadrants of the

wind turbine system **104**, the turbine assemblies **208** will tend to rotate in opposite directions. Moreover, the configuration exposes a first side **804** of the turbine assembly blades **352** to the incident wind **404**, while shielding the second side **808** of the blades **352**, promoting the efficient rotation of the turbine assemblies **208**.

[0067] In FIGS. 12A and 12B, a wind turbine system **104** in a maximum power generation mode is again illustrated in elevation (FIG. 12A) and top plan (FIG. 12B) views. However, in these views, the direction of the incident wind **404** has shifted by about 15° as compared to the conditions depicted in FIGS. 11A and 11B. In response to this shift in the direction of the wind **404**, the rotational position of the shroud members **348** has changed. In particular, the shrouds **348** have been rotated about the system axis **324**, to maintain an exposure to the turbine assemblies **208** that maximizes the energy transferred from the incident wind **404** to the wind turbine system **104**. Therefore, while the same or about the same area **1104a** and **1104b** is exposed to the incident wind **404** (i.e., the areas **1104a** and **1104b** are the same as the example in FIGS. 11A and 11B when considered from a view taken along the wind direction), the absolute orientation of the shroud members **348** relative to the central axis **324** is shifted to track the change in wind **404** direction.

[0068] FIGS. 13A and 13B depict an exemplary shroud member **348** configuration while the wind turbine system **104** is in a power generation mode, in the presence of a relatively strong incident wind **404**. With respect to FIG. 13A, the wind is traveling in a direction that is directly into the page. In this configuration, the areas **1104a** and **1104b** of exposure of the turbine assemblies **204** has been reduced. That is, more of the area of the wind turbine assemblies **204** is shielded by the shroud members **348**. Accordingly, the amount of wind **404** incident on the turbine assemblies **204** is reduced, thereby reducing the amount of energy transferred from the wind **404** by the wind turbine system **104** as compared to a configuration in which the exposed areas **1104a** and **1104b** are larger. The exposed area **1104a** and **1104b** can be further decreased if the velocity of the incident wind **404** increases. Similarly, in response to a decrease in the incident wind speed **404**, the exposed areas **1104a** and **1104b** can be increased, until the velocity of the incident wind **404** has decreased to below some threshold amount, at which point the maximum power configuration depicted in FIGS. 11A, 11B, 12A and 12B is reached. Accordingly, the wind turbine system **104** can be selectively powered and depowered.

[0069] While operating in the power generation mode in the presence of strong incident wind, in addition to reducing the exposed areas **1104a** and **1104b**, the rotational positions of the shroud members **348** can be altered to track changes in the direction of the incident wind **404**. An example of a change in the position of the shroud members **348** due to a change in direction of a strong incident wind **404**, as compared to the direction of the strong incident wind depicted in FIGS. 13A and 13B, is depicted in FIGS. 14A and 14B. In particular, while the areas **1104a** and **1104b** of exposed turbine assembly **208** remains depowered, the orientation of those areas has been shifted to track the change in the direction of the wind **404**.

[0070] FIGS. 15A and 15B illustrate shroud member **348** positions relative to the wind **404** while the wind turbine system **104** is in an idle mode. More particularly, FIG. 15A is a view in elevation of a wind turbine system **104** in an idle mode, with the wind traveling in a direction that is directly

into the page. The configuration of the shrouds **348** illustrated in FIG. **15A** is depicted in top plan view in FIG. **15B**. In this configuration, the turbine assemblies **208** are completely or substantially shielded from the incident wind **404**. This idle mode is generally entered when power generation is not desired or when the incident wind **404** velocity is too high for safe and reliable operation of the wind turbine system **104**.

[0071] FIGS. **16A** and **16B** illustrate the shroud member **348** positions in the idle mode, but in the presence of a wind shift of about 75° as compared to the wind direction and the configuration illustrated in FIGS. **15A** and **15B**. In particular, in order to track the shift in wind **404** direction, the shroud assemblies **204** are positioned to place the respective shroud members **308** such that the turbine assemblies **208** remain shielded from the wind **404**. Therefore, it can be appreciated that, even in an idle mode, the position of the shroud members **348** about the system axis **324** can continue to be varied with changes in wind **404** direction.

[0072] FIG. **17** is a flowchart depicting aspects of the operation of a wind turbine system **104** in accordance with embodiments of the present invention, and in particular operation while the wind turbine system **104** is in a power generation mode. Initially, after entering the power generation mode, the wind direction and velocity is determined (step **1704**). The shroud members **348** are then positioned to expose the turbine assemblies **208** to the wind (step **1708**). More particularly, a first shroud assembly **204a** shroud member **348a** can be positioned to uncover a first quadrant or other portion of a first turbine assembly **208**, such that the wind is incident on the first surface **804** of the blades **352** within that quadrant. Similarly, a second shroud member **204b** can be positioned by rotating the second shroud member **348b** such that the wind is incident on a first surface **804** of some of the blades **352** of the second turbine assembly **208b** within a quadrant of the second turbine assembly. By thus exposing some of the blades **352** of the turbine assemblies **208** to the wind, those turbine assemblies **208** will begin to rotate relative to the central axis **324** of the wind turbine assembly **104**.

[0073] A determination may then be made as to whether the incident wind **404** has gusted or otherwise suddenly increased (step **1710**). If the wind **404** has suddenly increased, the energy imparted to a blade **352** that is receiving a force from the wind **404** in excess of a predetermined amount is absorbed by the compliance units **908** included in the affected blade's **352** support structure **356** (step **1712**). In particular, when the force on the blade **352** is sufficiently high, e.g., greater than a predetermined amount, the shaft **1004** of the compliance unit **908** is compressed against the resilient member **1044**. As can be appreciated by one of skill in the art after consideration of the present disclosure, the ability to absorb forces on the turbine assembly blades **352** caused by high winds protects the wind turbine system **100** components. In addition, the compliance units **908** protect the system **100** components from damage due to high winds, and in particular to sudden gusts or changes in wind speed, where the change in wind speed occurs too quickly to address through adjusting the shroud assemblies **204** to reduce the area of the turbine assemblies **208** exposed to the wind. At step **1714**, a determination may be made as to whether the force of the wind causing the blade **352** to compress the associated compliance unit or units **908** has been removed. If the force has not yet been removed, the gust or increased wind continues to be absorbed by the compliance units **908**. If the force of the gust or sudden increase in wind has been removed, the blade **352**

is returned to its normal position (step **1716**). In accordance with embodiments of the present invention, the blade **352** is returned to its normal position relative to the associated shaft **332**, **344** in a measured manner. In particular, the force of the resilient member **1044** returns the shaft **1004** to its normal, fully extended position, while the movement of the piston **1012** through the fluid **1016**, and the movement of the fluid **1016** through the holes **1032** of the equalization plate **1028** controls the rate at which the strut **1004** is returned to the extended position. As can be appreciated by one of skill in the art after consideration of the present disclosure, the blade **352** will be returned to its normal position relative to the associated shaft **332**, **344** when the speed of the incident wind **404** has decreased by a sufficient amount, and/or when the blade has, through the rotation of the associated turbine assembly **208**, rotated out of the wind.

[0074] At step **1720**, a determination may be made as to whether an actionable change in either the wind velocity or the wind direction has been observed. If an actionable change in wind velocity or direction has been observed, the position of the shroud members **348** can be changed (step **1724**). For instance, if the direction of the wind has changed by at least some minimum number of degrees, the shroud assemblies **204** can be rotated about the system axis **324** in the same direction such that the exposure of the first **208a** and second **208b** turbine assemblies to the wind remains equal or substantially equal. As an example, and without limitation, an actionable change can occur when the wind direction is more than 5° to either side of being equally incident on the shroud members **358**. In response to a change in wind velocity, the shroud assemblies **204a** and **204b** can be rotated in opposite directions about the system axis **324** to change the exposure of the turbine assemblies **208** to the wind. Moreover, the rotational position of the shroud assemblies **204** can be changed in response to a combination of a change in the direction and a change in the velocity of the wind.

[0075] At step **1728**, a determination may be made as to whether the power generation mode is to be continued. If power generation is to be continued, the process may return to step **1710**. If the power generation mode is to be discontinued, the process may end.

[0076] As disclosed herein, a wind turbine system **104** in accordance with embodiments of the present invention includes counter-rotating turbine assemblies **208**. In at least some embodiments, a first turbine assembly **208a** includes a plurality of airfoils or blades that spin in a direction that is opposite the direction of spin of the second turbine assembly **208b**, thus substantially canceling out the inertia or twisting motion that would otherwise be induced by the force of turning the turbine assemblies **208** in only one direction. In addition, the geometry of the first turbine assembly **208a** blades **352** forces the incident wind **404** to not only turn the turbine assembly **204a**, but in addition to direct excess wind load upward into the second turbine assembly **208b**, thus acting similar to a two stage compressor and providing additional kinetic energy to move the second turbine assembly **208b**. In addition, the blades **352** of the first turbine assembly **208a** can be the mirror image of the blades **352** of the second turbine assembly **208b** and can comprise lifting bodies. The number of blades included in the first turbine assembly **208a** is generally different than the number of blades **352** included in the second turbine assembly **208b**. As examples, from 5 to 13 blades **352** can be included any one turbine assembly **208**.

[0077] The blades **352** may be made from a variety of different materials such as but not limited to metals, composites, plastics, combinations thereof, and the like. For example, the materials can include an ALUCOBOND™ composite material (an aluminum composite material that includes two sheets of aluminum thermo bonded to a polyethylene core), carbon composites, aluminum, galvanized metals, plastics or similar lightweight materials. The blades **352** may incorporate any of a number of different geometries and may comprise turbine blades, lifting bodies, airfoils, sails, and the like. In an exemplary configuration, the blades **352** can comprise a cambered surface that extends from about 10% to about 20% or higher from the side edges **812** and **816** of the blade **352**. As a particular example, the cambered surface can extend about 12%. In addition, an airfoil **352** can incorporate a curve when considered in a front elevation view.

[0078] The shroud members **358** can comprise hemispherical aero shells. The shroud assemblies **204** incorporating the shroud members **358** can be formed from various materials. Suitable materials include ALCUBOND™ composite material, carbon composites, sheet metal, sheet screens, aluminum, plastics, or the like.

[0079] Exemplary generators **212** include three phase induction generators at various outputs, depending on the size and intended use of the wind turbine system **104**. Exemplary power outputs include 60 KW, 120 KW, 200 KW, 500 KW and 700 KW production capacities. As can be appreciated by one of skill in the art after consideration of the present disclosure, a generator **212** can provide output power to an inverter system, for distribution of electricity into an electrical power bus or transformers of the user and the public utility grid. Accordingly, 60 Hz alternating current power can be provided by the wind turbine system **104**, for use at the location of the wind turbine system **104**, and/or for distribution by the public utility grid.

[0080] In an exemplary configuration, the turbine assemblies **208** have a radius from about 3 feet for a relatively small system to about 20 feet for a relatively large (e.g., 500 KW) system. The height of the overall wind turbine system **104** can range from about 14 feet for a small (e.g., 60 KW) system to about 50 feet for a large system. In one exemplary embodiment, an individual blade **352** has a total area of greater than **54** square feet, as determined by Euler's formula as known one of ordinary skill in the art, for converting wind power into work power based on surface area presented to the wind stream.

[0081] The operating revolutions per minute (RPM) of the turbine assemblies **208** can range from about 0 RPM to about 5,000 RPM and greater. For example, a wind turbine system **104** in accordance with embodiments of the present invention can be controlled to maintain rotation of the turbine assemblies **208** between about 3,000 RPM to about 6,500 RPM.

[0082] The foregoing discussion of the invention has been presented for purposes of illustration and description. Further, the description is not intended to limit the invention to the form disclosed herein. Consequently, variations and modifications commensurate with the above teachings, within the skill or knowledge of the relevant art, are within the scope of the present invention. The embodiments described hereinabove are further intended to explain the best mode presently known of practicing the invention and to enable others skilled in the art to utilize the invention in such or in other embodiments and with various modifications required by the particular application or use of the invention. It is

intended that the appended claims be construed to include alternative embodiments to the extent permitted by the prior art.

What is claimed is:

1. A wind turbine system, comprising:
 - a base member;
 - a first turbine assembly, wherein the first turbine assembly is interconnected to the base member, and wherein the first turbine assembly is rotatable about a first axis;
 - a second turbine assembly, wherein the second turbine assembly is interconnected to the base member, and wherein the second turbine assembly is rotatable about the first axis;
 - a first shroud assembly, including:
 - a first shroud member, wherein the first shroud assembly is interconnected to the base member, and wherein the first shroud member extends at least partially around an outer circumference of the first turbine assembly;
 - a second shroud assembly, including:
 - a second shroud member, wherein the second shroud assembly is interconnected to the base member, and wherein the second shroud member extends at least partially around an outer circumference of the first turbine assembly.
2. The system of claim 1, wherein the first turbine assembly includes a first plurality of blades, wherein the second turbine assembly includes a second plurality of blades, and wherein the number of blades included in the first plurality of blades is different than the number of blades included in the second plurality of blades.
3. The system of claim 2, further comprising:
 - a plurality of blade support structures, wherein each blade in the first plurality of blades and each blade in the second plurality of blades is associated with a support structure, each support structure including a compliance member, wherein in response to a force greater than a first predetermined amount, a radial position of a blade relative to an associated drive shaft is changed.
4. The system of claim 1, wherein in a first operational mode the first turbine assembly is configured to spin in a first direction around the first axis, and wherein in the first operational mode the second turbine is configured to spin in a second direction around the first axis.
5. The system of claim 1, wherein the first shroud member extends around at least one half of the outer circumference of the first turbine assembly, and wherein the second shroud member extends around at least one half of the outer circumference of the second turbine assembly.
6. The system of claim 1, wherein the first and second shroud assemblies are rotatable about the first axis.
7. The system of claim 1, further comprising:
 - a generator, wherein the generator includes an input shaft;
 - a drive train assembly interconnected to the input shaft of the generator, the drive train assembly including:
 - a first drive shaft, wherein the first turbine assembly is interconnected to the first drive shaft;
 - a second drive shaft, wherein the second turbine assembly is interconnected to the second drive shaft.
8. The system of claim 1, wherein the base member includes:
 - a first circular end surface having a first diameter;
 - a second circular end surface having a second diameter;

a medial section having a third diameter, wherein the third diameter is smaller than the first diameter, and wherein the third diameter is smaller than the second diameter.

9. The system of claim **1**, wherein the first shroud assembly defines a first exposed area of the first turbine assembly.

10. The system of claim **9**, wherein the second shroud assembly defines a second exposed area of the second turbine assembly.

11. A method for providing a wind turbine system, comprising:

interconnecting a first turbine assembly to a base member, wherein the first turbine assembly is located about a first axis;

interconnecting a second turbine assembly to the base member, wherein the second turbine assembly is located about the first axis;

selectively shielding a first portion of the first turbine assembly from a wind using a first shroud assembly, wherein the first shroud assembly partially shields at least a portion of the first turbine assembly, and wherein the first shroud assembly is located about the first axis;

selectively shielding a first portion of the second turbine assembly from the wind using a second shroud assembly, wherein the second shroud assembly partially shields at least a portion of the second turbine assembly, and wherein the second shroud assembly is located about the first axis.

12. The method of claim **11**, further comprising:

in a first operational mode:

selectively exposing a second portion of the first turbine assembly to the wind, wherein the first turbine assembly is rotated about the first axis in a first direction;

selectively exposing a second portion of the second turbine assembly to the wind, wherein the second turbine assembly is rotated about the first axis in a second direction.

13. The method of claim **12**, further comprising:

detecting a shift in the wind of at least a first predetermined amount;

changing a rotational position of the first shroud assembly about the first axis and changing a rotational position of the second shroud assembly about the second axis.

14. The method of claim **12**, further comprising:

driving a generator using the first second and turbine assemblies.

15. The method of claim **12**, further comprising:

experiencing a sudden increase in a force imparted to a blade of at least one of the first and second turbine assemblies;

in response to the force being at least a first predetermined amount, changing a radial position of the blade relative to other blades of the at least one of the first and second turbine assemblies.

16. The method of claim **15**, further comprising:

in response to the force from the wind on the blade dropping below the first predetermined amount, returning the blade to a normal position relative to the other blades in the at least one of the first and second turbine assemblies.

17. A wind turbine system, comprising:

a base member;

a generator interconnected to the base member;

a first shroud assembly interconnected to the base member, the first shroud assembly including a first shroud member, wherein the first shroud member can be rotated about a system axis to change a location of the first shroud member about the system axis;

a second shroud assembly interconnected to the second shroud assembly, the second shroud assembly including a second shroud member, wherein the second shroud member can be rotated about the system axis to change a location of the second shroud member about the system axis, and wherein the first and second shroud assemblies define a volume;

a first turbine assembly interconnected to the generator, wherein the first turbine assembly is located in the volume defined by the first and second shroud assemblies, and wherein the first shroud member partially encloses the volume in at least a first area adjacent the first turbine assembly;

a second turbine assembly interconnected to the generator, wherein the second turbine assembly is located in the volume defined by the first and second shroud assemblies, and wherein the second shroud member partially encloses the volume in at least a second area adjacent the second turbine assembly.

18. The system of claim **17**, further comprising:

a controller, including a processor and at least a first sensor, wherein the controller is operable to control the location of the first and second shield members about the system axis in response to information from the at least a first sensor.

19. The system of claim **17**, further comprising:

a plurality of blades,

wherein the first turbine assembly includes a first plurality of blades;

wherein the second turbine assembly includes a second plurality of blades.

20. The system of claim **17**, wherein at least a first flow path is defined by the first shroud, wherein the first flow path intersects the first turbine assembly, and wherein the first flow path also intersects the second turbine assembly.

* * * * *