

US 20110253046A1

(19) **United States**(12) **Patent Application Publication**
Dalton et al.(10) **Pub. No.: US 2011/0253046 A1**(43) **Pub. Date: Oct. 20, 2011**(54) **APPARATUS FOR PROVIDING UNIFORM
GAS DELIVERY TO A REACTOR****Publication Classification**(51) **Int. Cl.**
C23C 16/455 (2006.01)(52) **U.S. Cl.** **118/715**(57) **ABSTRACT**

A gas distribution system for a reactor having at least two distinct gas source orifice arrays displaced from one another along an axis defined by a gas flow direction from the gas source orifice arrays towards a work-piece deposition surface such that at least a lower one of the gas source orifice arrays is located between a higher one of the gas source orifice arrays and the work-piece deposition surface. Orifices in the higher one of the gas source orifice arrays may be spaced an average of 0.2-0.8 times a distance between the higher one of the gas source orifice arrays and the work-piece deposition surface, while orifices in the lower one of the gas source orifice arrays may be spaced an average of 0.1-0.4 times a distance between the higher one of the gas source orifice array and the work-piece deposition surface.

(76) Inventors: **Jeremie J. Dalton**, San Jose, CA (US); **M. Ziaul Karim**, San Jose, CA (US); **Ana R. Londergan**, Santa Clara, CA (US)(21) Appl. No.: **13/168,792**(22) Filed: **Jun. 24, 2011****Related U.S. Application Data**

(60) Continuation of application No. 12/553,917, filed on Sep. 3, 2009, now Pat. No. 7,981,472, which is a division of application No. 11/278,700, filed on Apr. 5, 2006, now abandoned.




Fig. 2




Fig. 3




Fig. 4




Fig. 5

APPARATUS FOR PROVIDING UNIFORM GAS DELIVERY TO A REACTOR

RELATED APPLICATIONS

[0001] This CONTINUATION of co-pending U.S. application Ser. No. 12/553,917, filed 3 Sep. 2009, which is a DIVISIONAL of U.S. patent application Ser. No. 11/278,700, filed 5 Apr. 2006, now abandoned, both of which are incorporated herein by reference.

FIELD OF THE INVENTION

[0002] The present invention relates to a gas distribution system for an atomic layer deposition or chemical vapor deposition processing system in which a vapor phase precursor is transported from an upstream source to a reaction space above a substrate.

BACKGROUND

[0003] The chemical deposition of thin solid films from gaseous (vapor-phase) chemical precursors onto solid substrates is of great interest in many areas including semiconductor fabrication, magnetic data storage, nanotechnology and others. In particular, atomic layer deposition (ALD) and chemical vapor deposition (CVD) processes are commonly used to deposit both dielectric and metal films onto semiconductor substrates. Increasingly, these applications require that the deposited film meet strict standards for thickness uniformity across the substrate and repeatability in such thicknesses over multiple substrates, while at the same time the process equipment is required to provide high film deposition rates so as not to present a bottleneck in the overall fabrication process.

[0004] In order for CVD and ALD equipment to meet such requirements, the flux of vapor precursors to the substrate must be tightly controlled and shaped. Often, there can be multiple gaseous precursors that must react to form the desired film and all must be delivered to the substrate in a precise and controllable manner. In some cases, it is advantageous to mix these multiple precursors together prior to introducing them into the reactor chamber. In other cases, it is preferable to maintain the precursors isolated from one another until they come into contact with the substrate so as to prevent any unwanted premature reactions.

[0005] Generally, uniform precursor flow into the reaction chamber is attempted by providing a flat plate with many small holes in between the gas-source and the substrate (a so-called showerhead). An early description of a device for providing such axial-symmetric gas flow towards a substrate is provided in U.S. Pat. No. 4,798,165 of deBoer et al. The diffusion plate or showerhead can have separate zones such that sonic holes are used for introducing one precursor and other holes are used for introducing the other precursor. In this way the precursors are kept separate so that no mixing occurs prior to the precursors entering the reaction space adjacent to the substrate.

[0006] One such showerhead is described in U.S. Published Patent Application 2006-0021703 of Salvador P. Umotoy. In this design, the showerhead faceplate has a number of gas passageways to provide a plurality of gases to the process region without commingling of those gases. A gas distribution manifold assembly is coupled so as to provide the different gasses to the various gas holes in the faceplate.

[0007] Another design for maintaining gases in separate passageways until they exit the distribution plate into the process region is described in U.S. Pat. No. 5,595,606. This showerhead includes a multiple block stack that ostensibly maintains two gases in separate passageways until they exit the distribution plate into the process region.

[0008] While showerheads of the sort described above purport to maintain separation of the various gases used in the ALD and CVD the present inventors have observed that if the relative flow rates of the different precursors flowing through adjacent holes are not well designed, recirculation can occur along the showerhead faceplate between the holes. FIG. 1 illustrates this condition. Shown in the diagram is a cut away view of a showerhead apparatus **10** having two individual gas manifolds generally indicated at **12** and **14**. The upper manifold **12** includes gas passageways **16a** and **16b**, which provide means for the gas in manifold **12** to exit via holes **18a** and **18b** in the faceplate **20** of showerhead **10**. Similarly, the lower manifold **14** includes gas passageways **22a** and **22b**, which provide means for the gas in manifold **14** to exit via holes **24a** and **24b** in faceplate **20**.

[0009] As shown, recirculation of the different precursor gases has been known to occur along the showerhead faceplate **20** between the holes associated with the different manifolds **12** and **14**. This undesired mixing of the precursors can cause unwanted reactions therebetween and reduce film uniformity on substrates in proximity thereto. Furthermore, when multiple zones are present within a single showerhead the spacing between the outlet holes of different zones becomes constrained by the number and size of holes required for flow uniformity.

[0010] Another problem with such showerhead designs is that it is difficult or impossible to maintain a difference in temperature between the two precursors because they both flow through the same solid plate **26** before reaching the faceplate **20**. In many cases, it would be desirable to maintain precursors at different temperatures until they react at the substrate surface.

[0011] What is needed, therefore, is a gas distribution system that overcomes these limitations of conventional showerheads.

SUMMARY OF THE INVENTION

[0012] One embodiment of the present invention provides a gas distribution system for a reactor having at least two distinct gas source orifice arrays displaced from one another along an axis defined by a gas flow direction from the gas source orifice arrays towards a work-piece deposition surface such that at least a lower one of the gas source orifice arrays is located between an upper one of the gas source orifice arrays and the work-piece deposition surface. The precise distance from the upper gas source orifice array (or the lower gas source orifice array) to the work-piece deposition surface depends on a number of factors, including the shape of the individual orifices in each of the arrays and the gas flow rates for each array. In general, the orifice arrays are positioned within the reactor such that a relatively uniform deposition over the work-piece surface can be achieved using the necessary gases and flow rates for the particular layer to be deposited. In addition to the distance from the work-piece surface, the spacing between individual orifices of each array will affect the nature and quality of the deposited layer. Hence, orifices in the upper one of the gas source orifice arrays may be spaced an average of 0.2-0.8 times a distance between the

higher one of the gas source orifice arrays and the work-piece deposition surface, while orifices in the lower one of the gas source orifice arrays may be spaced an average of 0.1-2 times a distance between the higher one of the gas source orifice arrays and the work-piece deposition surface.

[0013] The higher one of the gas source orifice arrays may be a planar showerhead having a generally uniform distribution of orifices across its faceplate. The lower one of the gas source orifice arrays may include one or more conduits distributed axi-symmetrically with respect to a radius of the planar showerhead. For example, the lower one of the gas source orifice arrays may include a number of spoke conduits leading from an axially centered feed conduit, and each spoke conduit including a number of individual orifices spaced an average of 0.1-2 times a distance between the higher one of the gas source orifice arrays and the work-piece deposition surface.

[0014] A further embodiment of the present invention provides for introducing gases into a reactor by flowing a purge gas from a first gas source orifice array disposed a first distance from a surface of a work-piece along an axis defined by gas flow from the first gas source orifice array to the surface of the work-piece while flowing a first reactive precursor into the reactor from a second gas source orifice array separate from the first gas source orifice array and disposed at a second distance from the surface of a work-piece along the axis defined by gas flow, said second distance being between said first distance. At an appropriate time, the flow of the first reactive precursor from the second gas source array may be stopped and the purge gas then flowed into the reactor from one or more of the first gas source orifice array and the second gas source orifice array. When unused portions of the first reactive precursor have been evacuated from the reactor, a second reactive precursor may be flowed into the reactor through the first gas source orifice array while flowing the purge gas into the reactor through the second gas source orifice array. Thereafter, the flow of the second reactive precursor from the first gas source array may be stopped, and unused portions of the second reactive precursor evacuated while flowing the purge gas into the reactor from one or more of the first gas source orifice array and the second gas source orifice array. This cycle may be repeated as needed to form a film on a substrate within the reactor.

[0015] Notwithstanding its applicability to ALD processes such as those described above, the invention is also useful in CVD and/or pulsed-CVD operations as discussed further below.

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] The present invention is illustrated by way of example, and not limitation, in the figures of the accompanying drawings, in which:

[0017] FIG. 1 shows an example of undesired gas recirculation and mixing which can occur when a conventional showerhead having gas passageways with exit holes in a single plane is used;

[0018] FIG. 2 shows an example of a showerhead configured in accordance with an embodiment of the present invention so as to prevent or reduce such undesired gas recirculation and mixing by displacing gas passageway exit holes into separate planes displaced from one another along an axis defined by the gas injection axis;

[0019] FIG. 3 shows an example of a showerhead configured in accordance with an embodiment of the present inven-

tion in which a radial spoke gas injection conduit is displaced beneath a planar gas distribution plate; and

[0020] FIG. 4 shows an example of an ALD reactor having with a gas distribution system configured in accordance with an embodiment of the present invention; and

[0021] FIG. 5 illustrates a variation of the ALD system shown in FIG. 4 in which multiple wafers are processed in a single reactor.

DETAILED DESCRIPTION

[0022] Described herein are gas distribution systems for ALD, CVD and/or other processing systems in which vapor phase precursors or other gases (e.g., inert carrier gases) are transported from upstream sources to a reaction space above a substrate. Unlike such distribution systems of the past, the present distribution systems are composed of two or more physically separated gas source orifices. That is, embodiments of the present invention provide gas source orifices at different displacements from a surface of a substrate along an axis of the gas pathway from the orifices to that surface. Viewed differently, the gas source orifices (which may be supplied by a common manifold configured to provide gases or precursors separately to each orifice) are separated from one another along an axis defining a path for the gasses to travel between the orifices and the substrate.

[0023] Embodiments of the present invention provide both physical and thermal separation of reactive precursors until they come into close proximity to the substrate. This not only avoids undesired reactions along the faceplate of the showerhead, it also permits the individual precursors to be delivered at their individual optimum temperatures. Furthermore, systems configured in accordance with the present invention provide manufacturers greater flexibility in designing gas flow manifolds for each precursor, independent from the geometrical constraints of the other.

[0024] Turning now to FIG. 2, an example of a gas distribution system 28 configured in accordance with an embodiment of the present invention is illustrated. Note that although this illustration depicts a gas distribution system with two manifolds (or gas source orifice arrays as they are sometimes termed herein), the present invention is not limited to such systems. Any number of such manifolds can be used. In some cases, the gas distributions systems will have multiple gas orifices disposed in a single plane (such as is the case for the system illustrated in FIG. 1) and in addition will have other gas orifices disposed in a different plane (as described below). In other cases, three or more such orifice arrays separately disposed from one another along an axis of gas injection may be provided. Thus, the depiction of a system employing two such arrays displaced from one another is meant only to illustrate the concepts embodied in the present invention and should not be viewed as limiting the scope of the invention to such arrangements.

[0025] FIG. 2 then is a cut away view of a gas distribution system 28 having two individual gas manifolds generally indicated at 30 and 32. The upper manifold 30 includes gas passageways 34a-34d, which provide means for the gas in manifold 30 to exit via holes 36a-36d in the faceplate 38 of a distribution plate 40. The lower manifold 32 includes a generally cylindrical gas passageway 40, which provide means for the gas in manifold 32 to exit via holes 44a-44c.

[0026] Of course, the individual manifolds are not limited to these illustrated configurations and, in general, any convenient configurations may be used to achieve desired gas dis-

tribution profiles within a reaction space proximate to a substrate. Thus, planar, curved, corrugated, cylindrical or other manifolds/distribution devices may be employed. For example, the faceplate **38** of upper manifold **30** need not be a flat (or relatively flat) surface as is shown in the illustration. Instead, faceplate **38** may have a corrugated or even saw tooth profile. Further, regardless of whether the faceplate **38** is flat or not, it need not necessarily be planar. Instead, various embodiments of the present invention may find particular application for a curved (e.g., relatively concave or relatively convex) faceplate **38**.

[0027] The lower manifold **32** may itself be something other than a cylindrical gas passageway. For example, the lower manifold may be a relatively planar diffuser plate. Alternatively, the lower manifold **32** may be a series of radially projecting cylinders resembling the spokes of a bicycle wheel (as is shown in later figures and described further below). In some cases the individual spoke-like orifice arrays may be of different lengths and/or diameters and arranged so as to provide a desired gas flow to a substrate. The spoke-like arrays may be independent of one another or may be coupled to one another via azimuthally-oriented or chord-like members and/or gas source orifice arrays.

[0028] In some cases the distance between the lower manifold **32** and the upper manifold **30** may be adjustable. For example, the lower manifold **32** may be suspended beneath the upper manifold **30** by one or more telescoping (e.g., pneumatic or hydraulic) supports which operate under the control of a controller so as to set the lower manifold at a desired distance from the faceplate **38** of the upper manifold **30**. Alternatively, the supports or other means of adjusting the separation distance between the manifolds may be manually configurable. Different CVD and/or ALD processes may require such different spacings between the manifolds in order to achieve desired deposition characteristics on substrates.

[0029] Whether adjustable or not, the optimal distance between the upper and lower manifolds may be dependent on the characteristics of the individual orifices present therein. Hence, to accommodate a wide variety of applications, the present invention encompasses the use of different types of orifices in either or both of the manifolds. Some orifices may be substantially cylindrical in cross-section, while others may be more funnel-like in cross-section so as to provide a wider dispersal of the gas exiting the orifice than might otherwise be achieved using orifices having a cylindrical cross-section. So too may the number of holes in each individual manifold be adjusted to provide a desired gas distribution profile at the surface of the work-piece undergoing processing. Different arrangements of orifice types and numbers in different radial areas of either or both of the manifolds may provide for relatively uniform deposition rates across an entire surface of a substrate. Individual orifices may be circular, rectangular, square, triangular, etc., in transverse section.

[0030] While these various arrangements of orifices of different types are not critical to the present invention, the overall goal of providing a gas delivery system configured to achieve substantially uniform deposition across an entire substrate surface while avoiding undesired cross-mixing of precursor gases should not be overlooked. In the case of a lower manifold having radial, spoke-like orifice arrays for gas distribution, reduced spacing between individual orifices would imply having more spokes in the entire array. This may not necessarily be desirable in that a wider spacing with fewer

individual orifices would provide fewer opportunities for undesired mixing of precursor gases along the arms of the lower gas distribution array and, hence, reduced overall formation of contaminant particles.

[0031] As shown in FIG. 2, manifold **32** is displaced from manifold **30** along an axis (Z) in the direction of gas injection from the respective holes of each manifold. Hence, the recirculation of the different precursor gases from the different manifolds does not lead to any undesired mixing of the precursors along the faceplate **38** of distribution plate **40**. This improves the film deposition characteristics of systems employing system **28** over those which make use of conventional showerheads.

[0032] FIG. 3 shows an isometric view of the gas distribution system **28**. The upper manifold is composed of a relatively flat distribution plate **40** with multiple through-holes **36** in faceplate **38** to allow precursor vapors and purge gases to enter the reactor (not shown). The lower manifold **32** is configured as an array of radial tubes **48** joined to a central inlet **50**. The tubes **48** have a series of outlet holes (not shown in detail in this drawing) to provide for uniform delivery of precursor and purge gases. The tubes **48** may be organized as one or more conduits distributed axi-symmetrically with respect to a radius of the planar distribution plate **40**.

[0033] FIG. 4 illustrates an example of an ALD reactor **52** having a gas distribution system configured in accordance with an embodiment of the present invention. In this cut away view, a wafer **54** is placed on a susceptor **56** (which may be vertically movable along the Z axis and may also include a heater) beneath the gas distribution system **28**. The gas distribution system **28** may be part of a lid assembly for reactor **52** or may be separate therefrom. As indicated above, the gas distribution system includes an upper manifold **30**, which is configured to receive precursor A from an upstream source, and a lower manifold **32**, which is configured to receive precursor B from a separate upstream source. Each of the manifold may also be configured to receive purge gasses. Manifold **30** distributes precursor A towards substrate **54** through holes (not shown in this view) in the faceplate **38**, while manifold **32** distributes precursor B towards substrate **54** through holes (also not shown in this view) in radial arms **48**. The radial arms are fed via central inlet **50**. Manifold **32** is displaced below the faceplate **38** of manifold **30** along the axis of gas injection towards the substrate **54** (the Z axis) by a distance "d".

[0034] FIG. 5 illustrates a variation of the above-described system in which multiple wafers or other substrates **60** are accommodated in a single reactor **52**. The wafers **60** may be supported on a linear array **56'**. Alternatively, the wafers may be placed in a radial array that resembles a carousel. Accordingly, the wafers **60** could be aligned along radial directions with respect to the center of a circular supporting element. A multi-wafer reactor of this type may be used where backside depositions can be tolerated (or otherwise compensated for) and may improve overall throughput. Similarly, reactors such as reactor **52** may be configured for use in stand-alone tools or in multi-single wafer tools or in cluster tools.

[0035] Importantly, the lower manifold **48** need not have a radial spoke configuration as depicted in the illustration. In some cases the lower manifold may be a point source (i.e., a gas orifice having a substantially circular or other cross-section). Alternatively, the lower manifold **48** could be a planar (or relatively planar) source, a source having a concave cross-section, or a radial spoke configuration with spokes of

varying lengths. Further, the lower manifold **48** may be relatively smaller or larger than as depicted in the illustration. That is, the lower manifold **48** may have a diameter equal to or greater than the substrate **54** or, the lower manifold may have a diameter smaller than that of the substrate, as shown.

[0036] Moreover, precursor B need not necessarily be fed to the lower manifold **32** via a single, central supply line. Instead, some configurations may have precursor B being fed to the orifice array through a lateral line or other, non central axial-symmetric feed line or lines. The details of such gas feed lines from an external gas supply source are not critical to the present invention.

[0037] In one embodiment of the present invention, the faceplate **38** of manifold **30** is located a distance "L" from the surface of substrate **54** on which deposition is to occur. In practice, "L" will be an average distance of an intended plane defined by the faceplate **38** from the surface of the substrate **54** and individual distances of any point on the faceplate **38** will reside at a distance $L \pm \delta 1$ a from said surface, owing to nonuniformities in the faceplate surface and the surface of the substrate **54**. Preferably, the holes in faceplate **38** through which precursor A gases will be introduced to reactor **52** will spaced an average of 0.2-0.8 times $L \pm \delta 1$ from one another. In further embodiments, the holes in manifold **32** may be spaced an average of 0.1-2 times $L \pm \delta 1$ from one another. Note that this latter spacing may be achieved through selected positioning of the various radial arms **48** of manifold **32**.

[0038] Further, the distance from the lower manifold **32** to the surface of the substrate **54** will be some fraction of L. In various embodiments of the invention this distance may be 0.3-0.9*L, and in one embodiment that was reduced to practice was 0.7 L. Typically, L will be approximately one inch.

[0039] During a typical ALD process in which the present gas distribution assembly would be used, manifold **30** will be flowing purge gas while manifold **32** is flowing reactive precursor B. In the next step of the process both manifolds **30** and **32** will flow purge gas to assist in removing any unreacted precursor from the reactor **52**. Unused precursors and purge gases are exhausted from reactor **52** via a pumping arrangement (not shown). Next, precursor A will be introduced through manifold **30** and purge gas will flow through manifold **32**. Finally, both manifolds **30** and **32** will flow purge gas to assist in removing any unreacted precursor. The flows of precursor and purge gas may be alternated in this fashion throughout the deposition process to allow the substrate **54** to be sequentially exposed to each of the precursors without allowing the precursors to mix in the gas phase.

[0040] The above-described process allows for uniform delivery of precursor vapor by introducing one of the reactant species through a flat plate with a plurality of through-holes while the second reactant species is introduced through a set of conduits radiating outward from a centrally located inlet. The conduits are situated such that they are between the flat plate and the substrate. This provides delivery of both reactants while maintaining thermal and physical isolation between the chemicals.

[0041] In some ALD processes, one of the ALD half-reactions will be soft saturating while the other is not. In such cases it may be desirable to introduce the precursor associated with the soft saturating half reaction through the upper manifold. For example, the precursor associated with the soft saturating reaction may require more uniform distribution, as may be achieved through introduction via the upper, relatively planar gas orifice array. In contrast, the precursor asso-

ciated with the strongly saturating half-reaction in the ALD process may be relatively insensitive to distribution via a nonuniform gas orifice array such as the lower manifold. This may not always be the case, however, inasmuch as relative gas flow rates must also be taken into consideration.

[0042] In addition to ALD processes, the present invention may be used in connection with CVD and/or pulsed-CVD processes. In a typical CVD process both manifold **30** and manifold **32** may be flowing purge gases and/or reactive precursors (potentially with respective carrier gases). When a desired deposition has been achieved, the flow of reactive precursors will be stopped and either or both manifolds **30** and **32** may flow purge gas to assist in removing any remaining precursors from the reactor **52**.

[0043] In a pulsed-CVD process a first precursor and carrier gas may be introduced continually through manifold **30** and the second precursor introduced in a pulsed fashion through the lower manifold **32**. Preferably, the precursor introduced via the lower manifold will be the one which has a dominant surface reaction during the CVD. As before, once the desired deposition has been achieved, the unused precursors and purge gases are exhausted from reactor **52** while flowing purge gas through one or both of the manifolds.

[0044] In further embodiments, the two manifolds may be operated so as to variously flow reactive precursors, precursors and carrier gases, and/or purge gas at various times in an ALD, CVD or other process so as to achieve a desired deposition on a substrate within the reactor. For example, while a precursor is introduced via the upper manifold (with or without a carrier gas), the lower manifold may be used to introduce a second precursor (with or without its own carrier gas) or purge gas and vice-versa.

[0045] Thus, a gas distribution system composed of distinct, physically separated source orifices to supply precursor vapors and inert gases to a substrate has been described. The distinct gas sources are oriented such that one orifice is located between the substrate and the other orifice. This prevents gas recirculation that is often observed with conventional showerheads, when the precursor vapors and inert gases are injected through adjacent orifices, and prevents premature reactions that are often observed when the precursors and purge gases are introduced through a single orifice. Stated differently, in contrast to conventional showerheads gas distribution systems configured in accordance with the present invention do not provide a recirculation zone between the outlet entices of the separate gas manifolds. This improves purging and can minimize gas-phase mixing and turbulence, both of which can lead to unwanted film deposition or particle formation.

[0046] It should be apparent from the preceding discussion that the use of separate gas source orifices that are not constrained to a single flat-plate allows much more freedom in designing the size and shape of each precursor manifold. When both precursor manifolds are constrained to have their outlet orifices in the same horizontal plane as in a conventional showerhead, the designer may not be able to achieve optimal flow uniformity for both precursors. At a minimum, the designer may have to resort to complex manifold and gas flow passages to achieve uniform flow. However, when separating the precursor manifolds into distinct orifices that are not in the same plane, in accordance with the present invention, it is much easier to obtain gas flow uniformity with simple gas flow passages. Of course, although the present invention was discussed with reference to certain illustrated

embodiments, these examples should not be used to limit the broader scope of the invention as set forth in the following claims.

What is claimed is:

1. An apparatus, comprising
a reactor chamber;

gas source arrays disposed within the reactor chamber, the
gas source arrays having:

(i) a first gas source orifice array disposed a first distance
from a surface of a work-piece within the reactor
chamber along an axis defined by gas flow towards the
surface of the work-piece, and

(ii) a second gas source orifice array separate from and
not fluidly coupled to the first gas source orifice array,
the second gas source orifice array disposed at a sec-
ond distance from the surface of a work-piece along
the axis defined by gas flow towards the surface of the
work-piece, said second distance being less than said
first distance; and

vacuum means coupled to evacuate gasses from the reactor
chamber,

wherein, the first and second gas source orifice arrays are
fluidly coupled to:

(i) flow, during a first time interval, a purge gas into the
reactor chamber from the first gas source orifice array
while flowing a first reactive precursor into the reactor
chamber from the second gas source orifice array;

(ii) flow, during a second time interval, the purge gas into
the reactor chamber from both the first and second gas
source orifice arrays while evacuating the reactor
chamber;

(iii) flow, during a third time interval, a second reactive
precursor into the reactor chamber from the first gas
source orifice array while flowing the purge gas into
the reactor chamber from the second gas source ori-
fice array; and

(iv) flow, during a fourth time interval, the purge gas into
the reactor chamber from both the first and second gas
source orifice array While evacuating the reactor.

* * * * *