


COOLING UNIT

Filed July 31, 1933

2 Sheets-Sheet 1









INVENTOR
William M. Stewart
White, Prost. Fleher Lothrop
ATTORNEYS

COOLING UNIT

Filed July 31, 1933

2 Sheets-Sheet 2





UNITED STATES PATENT OFFICE

2,011,881

COOLING UNIT

William M. Stewart, San Francisco, Calif. Application July 31, 1933, Serial No. 682,997

11 Claims. (CI. 62-91.5)

My invention relates to means for controlling and reducing the temperature of enclosures and is especially concerned with means for utilizing a solid, gas-emanating refrigerant, such as solid carbon-dioxide or the like, for controlling the temperature within an enclosure such as a cooling chamber.

An object of my invention is to provide means for cooling an enclosure with a substantially ex10 act regulation of temperature.

Another object of my invention is to provide a cooling unit which is sufficiently light and compact to be readily portable.

Another object of my invention is to provide a cooling unit which is economical of refrigerant.

A further object of my invention is to provide a simple and inexpensive cooling unit primarily designed for use with a solid, gas-emanating refrigerant.

An additional object of my invention is, in general, to improve cooling units.

The foregoing and other objects are attained in the embodiment of the invention shown in the drawings, in which—

Figure 1 is a cross-section on a longitudinal plane of a cooling unit constructed in accordance with my invention.

Figure 2 is a cross-section the plane of which is indicated by the line 2—2 of Figure 1.

Figure 3 is a view, partly in section, showing in elevation a cooling unit installation in accordance with my invention.

Figure 4 is a side elevation of the cooling unit shown in Figure 1 with the addition of an air-circulating fan.

Figure 5 is a bottom view of the structure shown in Figure 4.

The cooling unit of my invention is susceptible of a wide range of variation, not only in matters of construction but also in environmental conditions. One valuable use is in connection with railway express car cooling, as indicated in my co-pending application entitled "Compartment car", filed July 31, 1933, with Serial No. 45 682,996. The range of usefulness, however, is so great that I have chosen for illustration herein a typical cooling unit suitable for all-around usage.

This unit, as illustrated, has proved particu50 larly successful in connection with cooling produce containers on motor trucks, and comprises
a housing 6 which is generally rectangular and is
approximately square in transverse cross-section. The housing is made up of a plurality of
enclosing walls generally fabricated of a suitable

insulating material 7. That is, a top wall 8 is comprised of insulating material 7 sheathed on both surfaces, for example by an outer, preferably metallic covering 9 and an inner metallic lining 11. Comparably, the housing incorporates a bottom wall 12 including insulating material 7 confined between an inner lining 13 and an outer shell 14. An end wall 16 is similarly fabricated of an outer shell 17 and an inner shell 18 lying on opposite sides of the insulating material 7. 10 The opposite end of the housing is sealed by a closure 21 comprising a door structure including insulating material 22, an outer shell 23 and an inner lining 24. The door 21 is preferably tapered to form a tight seal with its jamb 26 and 15 is preferably mounted on hinges 27 and provided with a suitable latch 28 to maintain the door in closed position.

The spacing of the various walls is such as to provide a chamber 28 therein for the accommo- 20 dation of a solid, gas-emanating refrigerant, usually in the form of blocks 29 and 31. Customarily, solid carbon-dioxide is utilized as the refrigerant. This material has the property of giving off carbon-dioxide gas at suitable tem- 25 peratures. This gas is considerably heavier than air and naturally tends to drop if unconfined. I preferably take advantage of such characteristic in practising my invention. To this end the standard size blocks of refrigerant 29 and 31 are 30 somewhat smaller than the internal dimensions of the chamber 28, so that gas emanating from the refrigerant tends naturally to flow downwardly in the direction of the arrows 32 through a passage 33 between the blocks 31 and the in- 35 terior shell 24 of the door 21.

Preferably forming part of the housing 6, but thermally isolated from the chamber 28, is a conduit 34. This conduit is defined by the outer shell 14 of the wall 12 and by a suitably corrugated plate 36 which is customarily of metal and provides a heat exchange surface between the material within the conduit 34 and the exterior air. The plate 36, while illustrated herein as corrugated, can be flat or of any suitable configuration in order to comply with the desired heat exchange characteristics.

To establish communication between the conduit 34 and the chamber 28 I provide an outlet duct 37 which pierces the bottom wall 12 and is 50 of generally rectangular shape and of relatively large cross-sectional area. Gas flowing in the path indicated by the arrows 32 continues through the duct, as indicated by the arrows 38, and flows through the conduit 34 as indicated by the arrows 55

In order to prevent blocking of the duct 38 by shifting of the refrigerant blocks 29 and 31, I preferably provide suitable guards or spacers 41 on the door 21, so that when the door is closed the 5 blocks 29 and 31 are precluded from sliding over and blocking the duct 38.

I preferably provide means to control the flow to the duct 38, and therefore on the plate 36 I provide a threaded boss 42 within which is screwed a threaded shaft 43 carrying a suitable manipulating handle 44. A valve plate 46 is mounted on the shaft 43 and can be tightly pressed against the duct 38 or can be removed therefrom in order to regulate the passage of gas therethrough. Adjacent the boss 42 I provide a sump 47 with a grainpipe 48 and a closure cap 49 for the drainage of moisture. While solid carbon-dioxide itself is moisture-free, nevertheless certain atmospheric moisture enters the chamber 28 whenever the door 21 is opened, and after a period of time such moisture collects within the sump 47 and is discharged through the pipe 48 upon removal of the cap 49.

Gas which travels from the duct 38 into the con-25 duit 34 is in neat absorbing relationship to external air on the opposite side of the plate 36 and absorbs heat from such external air at a relatively rapid rate. The absorption of heat causes the gas in the conduit 34 to be of less density than the gas emanating from the blocks 29 and 31 and flowing through the duct 38. Being of less density, the relatively warm gas in the conduit 34 travels in the direction of the arrows 51 and flows in a generally upward direction, in accordance with the arrows 52, through a passageway 54 to an inlet duct 56 piercing the end wall 16. The passage 54 is partially formed by a closure 57 customarily fabricated of sheet metal and fitting on the end of the housing 6. The duct 56 is very much of the character of the duct 38 but is located adjacent the uppermost portion of the chamber 28, so that the relatively light, warmed gas can return in a favorable location. Gas which returns through the duct 56, as indicated by the arrow 58, is quickly reduced in temperature by thermal proximity to the refrigerant blocks 29 and 31 and quickly recycles in the path of the arrows 32 and 39 as previously described.

In the mentioned fashion there is provided convection circulation in a closed cycle, with heat absorption through the conduit 36 and return of the warmed gases to the relatively cold chamber 28. The pressure existing in the circuit is substantially atmospheric and, in order to maintain such pressure and to provide for the escape of gas which is relatively high in temperature and which is no longer useful, I provide an outlet pipe 59 at substantially the highest thermal point in the cycle. The pipe 59 opens into the upper portion of the duct 54 and, while most of the warm gas adjacent the duct 56 is sufficiently cooled by the refrigerant blocks 29 and 31 to enter the duct 56 and recycle, certain of the gas which is too high in temperature is not sufficiently cooled and 65 flows out through the discharge pipe 59 which communicates with the atmosphere.

In order that flow through the duct 56 will not be blocked by the refrigerant cubes 29 and 31, I provide suitable spacers 61 on the end wall 16, so 70 that the duct 56 affords a free passage for the returning gas. In accordance with my invention. however, I desire to vary or restrict the circulation of the gas in order to adjust the temperature within the conduit 34 so that the desired cooling 75 rate can be obtained. To this end I preferably

restrict the entrance of duct 56 by a valve 62 which can be operated in a suitable fashion. Ordinarily, the valve 62 is operated in response to the temperature of the returning gas within the passage 54. To this end the plate 62 is mounted on a bimetallic strip 63 or other suitable thermostat which is anchored as at 64 on the casing 57.

In order to control the temperature at which the thermostat 63 is especially responsive, I provide a cross-shaft 66 which projects from the 10 casing 57 and carries a manual operating handle 68 or other suitable actuating device. Mounted on the shaft 66 is an eccentric 69 adapted to abut the strip 63 and thus govern the position of the plate 62 and the temperatures at which the plate 15 62 is especially effective. By suitably manipulating the handle 68 the maximum rate of flow of the refrigerant can be governed. The temperature within the space or enclosure cooled by the cooling unit of my invention is held within very 20close limits by the thermostat. I have found from extensive practice that a device constructed with approximately the proportions shown, especially with the insulation in the walls 8 and the door 22 somewhat thicker than the insulation 25 in the walls 16 and 12 adjacent the heat exchange members 34 and 57, provides a suitable range of operating temperatures.

While the unit as shown in Figures 1 and 2 is suitable for general installation, when the cooling 30 unit is installed within an insulated chamber I prefer to provide certain modifications. As illustrated in Figure 3, the cooling unit, generally designated 101, is disposed within an insulated chamber 102 having walls 103 formed of an outer 35 shell 104 and an inner shell 106. Generally, the space between the inner and outer walls is filled with any standard heat-insulating material 107. In accordance with my invention, the outlet pipe 108 for spent gases from the cooling unit 101, is 40 tapped through the inner wall 106 to discharge into the insulation material 107 between the inner and outer walls 106 and 104, respectively. Such discharged gas is usually still lower in temperature than the temperature obtaining within 45 the compartment 102, while carbon-dioxide gas itself is a good heat insulation material. The gas discharged into the space between the walls 104 and 106 is compelled to pass completely around the chamber 102 to discharge from an 50 outlet pipe 109 into the atmosphere, the direction of circulation being indicated by the arrows 111. A baffle 112 prevents short-circuiting of the gas between the pipes 108 and 109.

While under most conditions of operation the 55 natural, exterior circulation past the heat exchange surface 36 is ample, nevertheless under certain circumstances I desire to accelerate such air flow and thereby obtain an enhanced rate of heat exchange. To this end I preferably mount a 60 fan of any suitable character on the cooling unit itself. As illustrated in Figures 4 and 5, a cooling unit 121 is provided with a heat exchange surface 122 of corrugated contour. The unit includes a casing 123 to which a suitable motor 124 65 is mechanically attached. The motor 124 is part of a blower having a scroll housing 126 to which an air inlet 127 leads and from which an air outlet 128 discharges. The direction of discharge of 70 the outlet 128 is such as to cause a current of air induced to flow through the inlet 127 to spread out and flow along the corrugated surface 122, thereby providing an accelerated heat transfer through the surface.

I claim:

1. A cooling unit comprising a housing of heat insulating material having a chamber therein for containing a solid gas-emanating refrigerant, a 5 heat conducting wall disposed in spaced relation to said housing and forming a conduit having an exposed heat-exchanging surface along one side of said chamber, a duct establishing communication between the lower part of said chamber and said conduit, a second duct establishing communication between said conduit and the upper part of said chamber, and thermostatic means disposed within one of said ducts responsive to the temperature of the gas circulating in said 15 conduit for controlling the flow of gas therethrough.

2. A cooling unit comprising a heat insulated housing having a chamber therein for containing a solid gas-emanating refrigerant, a metallic 20 partition having an exposed heat absorbing surface arranged in spaced relation along the bottom of said housing, a plurality of ducts piercing said heat insulated housing for establishing communication for a convection circulation of gas between said housing and said metallic partition, and thermostatic means responsive to the temperature of the circulating gas for controlling the rate of heat absorption of said metallic partition.

3. A self contained cooling unit for refrigerating purposes comprising a housing of heat insulating material having a chamber therein for holding a solid gas-emanating refrigerant, a corrugated metallic wall disposed in spaced relation along the bottom of said housing and forming a conduit having an exposed heat-exchanging surface, a plurality of ducts extending through the heat insulating material forming said housing for establishing communication for a convection circulation and recirculation of gas through said chamber and between said housing and said corrugated metallic wall, and thermostatic means in said conduit for controlling the rate of the circulation of said gas.

4. A cooling unit comprising a heat insulated 45 housing having a chamber therein for containing a solid gas-emanating refrigerant, a metallic partition having an exposed heat absorbing surface arranged in spaced relation along the bottom of said housing, inlet and outlet ducts piercing said heat insulated housing for establishing communication for a convection circulation of gas between said housing and said metallic partition, a manually controlled valve in said outlet duct, and a thermostatically controlled valve responsive to the temperature of the circulating gas in said inlet duct, said valves being operable to control the rate of heat absorption of said metallic partition.

5. A cooling unit comprising a housing of heat insulating material having a chamber therein for containing a solid gas-emanating refrigerant, a conduit having an exposed heat-exchanging surface arranged outside of and below said housing, a duct in the bottom of said chamber establishing communication between said chamber and said conduit, a door adjacent said duct for the introduction of the solid gas-emanating refrigerant, and means carried by said door for holding said solid gas-emanating refrigerant clear of said duct without interfering with the free flow of gas therethrough.

6. A self contained solid carbon dioxide refrigerating unit comprising a housing of heat insulating material having a chamber for holding a 75 quantity of solid carbon dioxide, means forming

a conduit having heat-exchanging properties through which the gas emanating from said solid carbon dioxide may circulate and recirculate by convection, and thermostatic means within said conduit responsive to the temperature of the cir- 5 culating gas for controlling the recirculation of gas therethrough.

7. A self contained cooling unit for refrigerating purposes comprising a housing of heat insulating material having a chamber for holding 10 a solid gas-emanating refrigerant, means forming a conduit having heat-exchanging properties through which the gas emanating from said solid refrigerant may circulate by convection, thermostatic means within said conduit for controlling 15 the circulation of gas therethrough, and means for regulating the range of said thermostatic means during operation whereby the rate of gas emanation from said solid refrigerant may be determined at any time irrespective of the external 20

temperature. 8. A solidified carbon dioxide refrigerating unit comprising a housing of heat insulating material having a chamber therein for containing a quantity of solid carbon dioxide, a heat conducting wall disposed in spaced relation with said housing and forming an exposed heat-exchanging surface below said chamber, means establishing communication between the interior of said chamber and the inside of said heat conducting wall for a closed-cycle convection circulation of the gas emanating from said solid carbon dioxide, and thermostatic means responsive to the temperature variations of the circulating gas for controlling the flow thereof and thereby the rate 35 of sublimation of said solid carbon dioxide independently of the temperature external to said exposed heat-exchanging surface.

9. A solidified carbon dioxide refrigerating unit comprising a housing of heat insulating material 40 having a chamber therein for containing a solid carbon dioxide, a heat conducting wall disposed in spaced relation with said housing and forming a conduit for a closed-cycle circulation of carbon dioxide gas having an exposed heat-exchanging 45 surface arranged below said chamber, means for establishing communication between said chamber and said conduit to permit a circulation of gas evolved from said solid carbon dioxide, and a thermostatically controlled valve responsive to 50 the temperature within said conduit for controlling the circulation of the gas therethrough, whereby the rate of gas emanation from said solid carbon dioxide will be determined by the heat absorbed by the gas from said heat-ex- 55 changing surface.

10. A solidified gas refrigerating unit comprising a housing of heat insulating material having a chamber therein for containing a solid gasemanating refrigerant, a conduit having an ex- 60 posed heat-exchanging surface arranged outside of and below said housing, a duct establishing a path for gas evolved from said solid refrigerant extending from the lower part of said chamber to said conduit, a second duct establishing a path 65 from said conduit to the upper part of said chamber, said ducts cooperating with said chamber and said conduit to provide a closed-cycle circulation of the gas emanating from said solid refrigerant, and a thermostatically controlled 70 valve responsive to the temperature of the circulating gas for controlling the recirculation thereof and thereby the rate of sublimation of said solid refrigerant independently of the temperature external to said housing.

11. A cooling unit comprising a heat insulated housing having a chamber therein for containing a solid gas-emanating refrigerant, a metallic partition having an exposed heat absorbing surface arranged in spaced relation along the bottom of said housing, inlet and outlet ducts piercing said heat insulated housing for establishing communication for a convection circulation and recirculation of gas between said housing and said metallic partition, a manually controlled valve in said outlet duct for controlling the discharge of gas from

said chamber, and a thermostatically controlled valve responsive to the temperature of the gas circulating between said housing and said metallic partition, said manually controlled valve being operable to control the rate of circulation of said 5 gas from said chamber and said thermostatically controlled valve being operable to control the rate of recirculation of said gas, whereby the heat absorption ability of said metallic partition will be determined.

WILLIAM M. STEWART.

DISCLAIMER

2,011,881.—William M. Stewart, San Francisco, Calif. Cooling Unit. Patent dated August 20, 1935. Disclaimer filed July 22, 1939, by the assignee, Controlled Refrigerants Company Ltd.

Hereby enters this disclaimer to wit: any interpretation of claim 1 that will include a structure wherein the thermostatic means is not located in a duct remote from the exposed heat-exchanging surface and is not controlled in its automatic operation solely by temperature changes of the gas circulating through the duct in which the thermostatic means is located.

[Official Gazette August 22, 1939.]