

US 20120017495A1

(19) **United States**

(12) **Patent Application Publication**
Traynor et al.

(10) **Pub. No.: US 2012/0017495 A1**

(43) **Pub. Date: Jan. 26, 2012**

(54) **METHODS FOR DEOXYGENATING
BIOMASS-DERIVED PYROLYSIS OILS**

(52) **U.S. Cl. 44/401; 44/388**

(75) **Inventors:** **Thomas Traynor**, Buffalo Grove,
IL (US); **Timothy A. Brandvold**,
Arlington Heights, IL (US);
Jennifer F. Abrahamian, Chicago,
IL (US)

(57) **ABSTRACT**

Methods for deoxygenating treated biomass-derived pyrolysis oil are provided. The treated biomass-derived pyrolysis oil is exposed to a catalyst having a neutral catalyst support such as a non-alumina metal oxide support, a theta alumina support, or both. The non-alumina metal oxide support may be a titanium oxide (TiO₂) support, a silicon oxide support, a zirconia oxide (ZrO₂) support, a niobium oxide (Nb₂O₅) support, or a support having a mixture of non-alumina metal oxides. The catalyst may include a noble metal or a Group VIII non-noble metal and a Group VIB non-noble metal on the neutral catalyst support. The treated biomass-derived pyrolysis oil is introduced into a hydroprocessing reactor in the presence of the catalyst under hydroprocessing conditions to produce low oxygen biomass-derived pyrolysis oil.


(73) **Assignee:** **UOP LLC**, Des Plaines, IL (US)

(21) **Appl. No.:** **12/843,625**

(22) **Filed:** **Jul. 26, 2010**

Publication Classification

(51) **Int. Cl.**
C10L 1/19 (2006.01)






FIG. 1




FIG. 2




FIG. 3

COMBINATION (%)	Ni	Co	Mo	W	Rd	Rh	Au	Pd
Ni Mo	0.5-3-5		5-15-20					
Co Mo		0.5-3-5	5-15-20					
Ni Co Mo	0.1-1-5	0.5-3-5	5-15-20					
Ni W	0.5-3-5			5-15-20				
Co W		0.5-3-5		5-15-20				
Ni Co W	0.1-1-5	0.5-3-5		5-15-20				
Rd					0.1-0.5-5			
Rh						0.1-1-5		
Au							0.1-1-5	
Pd								0.1-1-5

FIG. 4

COMBINATION (%)	SUPPORT A	SUPPORT B	SUPPORT C	SUPPORT D
Ni Mo	TiO ₂	ZrO ₂	THETA ALUMINA	Nb ₂ O ₅
Co Mo	TiO ₂	ZrO ₂	THETA ALUMINA	Nb ₂ O ₅
Ni Co Mo	TiO ₂	ZrO ₂	THETA ALUMINA	Nb ₂ O ₅
Ni W	TiO ₂	ZrO ₂	THETA ALUMINA	Nb ₂ O ₅
Co W	TiO ₂	ZrO ₂	THETA ALUMINA	Nb ₂ O ₅
Ni Co W	TiO ₂	ZrO ₂	THETA ALUMINA	Nb ₂ O ₅
Rd	TiO ₂	ZrO ₂	THETA ALUMINA	Nb ₂ O ₅
Rh	TiO ₂	ZrO ₂	THETA ALUMINA	Nb ₂ O ₅
Au	TiO ₂	ZrO ₂	THETA ALUMINA	Nb ₂ O ₅
Pd	TiO ₂	ZrO ₂	THETA ALUMINA	Nb ₂ O ₅

FIG. 5

METHODS FOR DEOXYGENATING BIOMASS-DERIVED PYROLYSIS OILS

FIELD OF THE INVENTION

[0001] The present invention generally relates to methods for producing biofuels, and more particularly relates to methods for deoxygenating biomass-derived pyrolysis oils.

DESCRIPTION OF RELATED ART

[0002] Fast pyrolysis is a process during which organic carbonaceous biomass feedstock, i.e., “biomass”, such as wood waste, agricultural waste, etc., is rapidly heated to between about 300° C. to about 900° C. in the absence of air using a pyrolysis reactor. Under these conditions, solid and gaseous pyrolysis products are produced. A condensable portion (vapors) of the gaseous pyrolysis products is condensed into biomass-derived pyrolysis oil. Biomass-derived pyrolysis oil can be burned directly as fuel for certain boiler and furnace applications, and can also serve as a potential feedstock in catalytic processes for the production of fuels in petroleum refineries. Biomass-derived pyrolysis oil has the potential to replace up to 60% of transportation fuels, thereby reducing the dependency on conventional petroleum and reducing its environmental impact.

[0003] However, biomass-derived pyrolysis oil is a complex, highly oxygenated organic liquid having properties that currently limit its utilization as a biofuel. For example, biomass-derived pyrolysis oil has high acidity and a low energy density attributable in large part to oxygenated hydrocarbons in the oil, which undergo secondary reactions during storage. “Oxygenated hydrocarbons” as used herein are organic compounds containing hydrogen, carbon, and oxygen. Such oxygenated hydrocarbons in the biomass-derived pyrolysis oil include carboxylic acids, phenols, cresols, aldehydes, etc. Conventional biomass-derived pyrolysis oil comprises about 30% by weight oxygen from these oxygenated hydrocarbons.

[0004] Conversion of biomass-derived pyrolysis oil into biofuels and chemicals requires full or partial deoxygenation of the biomass-derived pyrolysis oil. Such deoxygenation may proceed via two main routes, namely the elimination of either water or CO₂. Unfortunately, deoxygenating biomass-derived pyrolysis oil leads to rapid plugging or fouling in a hydroprocessing reactor caused by the formation of solids from the biomass-derived pyrolysis oil. Particulates in the oil settle on the processing catalysts causing catalytic bed fouling thereby reducing activity of the catalyst and causing build up in the hydroprocessing reactor. It is believed that this plugging is caused by an acid catalyzed polymerization of the biomass-derived pyrolysis oil that creates either a glassy brown polymer or powdery brown char, which limit run duration and processability of the biomass-derived pyrolysis oil.

[0005] Accordingly, it is desirable to provide methods for deoxygenating biomass-derived pyrolysis oils. In addition, it is also desirable to deoxygenate biomass-derived pyrolysis oils without plugging of the reactor thereby improving processability of biomass-derived pyrolysis oil and increasing run duration. Furthermore, other desirable features and characteristics of the present invention will become apparent from the subsequent detailed description of the invention and the

appended claims, taken in conjunction with the accompanying drawings and this background of the invention.

SUMMARY OF THE INVENTION

[0006] Methods are provided for deoxygenating treated biomass-derived pyrolysis oil. In accordance with one exemplary embodiment, the method comprises exposing the treated biomass-derived pyrolysis oil to a catalyst having a neutral catalyst support.

[0007] Methods are provided for deoxygenating treated biomass-derived pyrolysis oil in accordance with yet another exemplary embodiment of the present invention. The method comprises the steps of providing a catalyst comprising a metal on a carbon support, a non-alumina metal oxide support, a theta alumina support, or a combination thereof. The treated biomass-derived pyrolysis oil is introduced into a hydroprocessing reactor in the presence of the catalyst under hydroprocessing conditions to produce low oxygen biomass-derived pyrolysis oil.

[0008] Methods are provided for deoxygenating treated biomass-derived pyrolysis oil in accordance with yet another exemplary embodiment of the present invention. The method comprises the steps of providing a catalyst comprising a metal on a carbon support, a non-alumina metal oxide support, or a support comprising a combinations thereof. The treated biomass-derived pyrolysis oil is exposed to the catalyst at hydroprocessing conditions sufficient to at least partially deoxygenate the treated biomass-derived pyrolysis oil. The non-alumina metal oxide support is selected from the group consisting of a titanium oxide support, a silicon oxide support, a zirconia oxide support, and a niobium oxide support.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] The present invention will hereinafter be described in conjunction with the following drawing figures, wherein like numerals denote like elements, and wherein:

[0010] FIG. 1 is a flow diagram of a method for deoxygenating treated biomass-derived pyrolysis oils, according to exemplary embodiments of the present invention;

[0011] FIG. 2 is a schematic diagram of the method of FIG. 1, according to exemplary embodiments of the present invention;

[0012] FIG. 3 is a phase diagram for pure ethanol;

[0013] FIG. 4 is a table of exemplary metals of exemplary deoxygenation catalysts having a neutral catalyst support; and

[0014] FIG. 5 is a table of exemplary neutral catalyst supports for the metals of FIG. 4.

DETAILED DESCRIPTION

[0015] The following detailed description of the invention is merely exemplary in nature and is not intended to limit the invention or the application and uses of the invention. Furthermore, there is no intention to be bound by any theory presented in the preceding background of the invention or the following detailed description of the invention.

[0016] Various exemplary embodiments of the present invention are directed to methods for deoxygenating biomass-derived pyrolysis oils by exposing treated biomass-derived pyrolysis oil to a catalyst having a neutral catalyst support, as hereinafter described. The treated biomass-derived pyrolysis oil is introduced into a hydroprocessing reactor in the presence of the catalyst under hydroprocessing

conditions to produce low oxygen biomass-derived pyrolysis oil. Solids formation that typically occurs during deoxygenation or other hydroprocessing is decreased resulting in less plugging of the catalyst bed, increased hydroprocessing run times, and improved processability of the biomass-derived pyrolysis oil. It should be appreciated that while the deoxygenated oil produced according to exemplary embodiments of the present invention is generally described herein as a “low oxygen biomass-derived pyrolysis oil”, this term generally includes any oil produced having a lower oxygen concentration than conventional biomass-derived pyrolysis oil. The term “low oxygen biomass-derived pyrolysis oil” includes oil having no oxygen, i.e., a biomass-derived pyrolysis oil in which all the oxygenated hydrocarbons have been converted into hydrocarbons (i.e., a “hydrocarbon product”). Preferably, the low oxygen biomass-derived pyrolysis oil comprises from about 0 to about 5 wt. % oxygen. “Hydrocarbons” as used herein are organic compounds that contain principally only hydrogen and carbon, i.e., oxygen-free. “Oxygenated hydrocarbons” as used herein are organic compounds containing hydrogen, carbon, and oxygen. As noted previously, exemplary oxygenated hydrocarbons in biomass-derived pyrolysis oil include alcohols such as phenols and cresols, carboxylic acids, aldehydes, etc.

[0017] Referring to FIG. 1, a method **10** for deoxygenating biomass-derived pyrolysis oils begins by providing treated biomass-derived pyrolysis oil (step **200**). In one preferred embodiment, “treated biomass-derived pyrolysis oil” comprises esterified biomass-derived pyrolysis oil having a solids content less than about 0.10%, preferably less than about 0.01%; a total metals content of less than about 100 ppm, preferably less than about 20 ppm; and a water content of less than about 20 weight percent (wt. %), preferably less than about 15 wt. % (hereinafter “target levels”). Esterification reduces the carboxylic total acid number (TAN) to less than about 40 mg KOH/g biomass-derived pyrolysis oil (also a “target level”) in the treated biomass-derived pyrolysis oil. In another embodiment, the treated biomass-derived pyrolysis oil has not been subjected to an esterification process but has a solids content, a total metals content, and a water content, or at least one thereof, at the target levels.

[0018] Conventional as-produced biomass-derived pyrolysis oil typically contains about 1000 to about 2000 ppm total metals, about 20-33 wt. % water with high acidity (TAN>150), and a solids content of about 0.1 wt. % to about 5 wt. %. However, it is to be appreciated that should the conventional biomass-derived pyrolysis oil already have a solids content, a total metals content, a water content, and/or a carboxylic TAN at the desired target levels, the conventional biomass-derived oil may be used as the “treated biomass-derived pyrolysis oil”. Conventional biomass-derived pyrolysis oil may also be selectively treated as hereinafter described to reduce only those levels not at the target level(s). The starting conventional biomass-derived pyrolysis oil is available from, for example, Ensyn Technologies Inc., of Ontario, Canada.

[0019] Biomass-derived pyrolysis oil is provided from a source such as a feed tank or other source operative to provide such biomass-derived pyrolysis oil. Biomass-derived pyrolysis oil may be produced, for example, from pyrolysis of biomass in a pyrolysis reactor. Virtually any form of biomass can be used for pyrolysis to produce biomass-derived pyrolysis oil. Biomass-derived pyrolysis oil may be derived from biomass material such as wood, agricultural waste, nuts and

seeds, algae, grasses, forestry residues, or the like. The biomass-derived pyrolysis oil may be obtained by different modes of pyrolysis, such as fast pyrolysis, vacuum pyrolysis, catalytic pyrolysis, and slow pyrolysis (also known as carbonization) or the like. Biomass-derived pyrolysis oil composition is somewhat dependent on feedstock and processing variables.

[0020] Referring to FIG. 2, to reduce the solids content in conventional biomass-derived pyrolysis oil to the target level, the biomass-derived pyrolysis oil **15** may be, for example, filtered in a filtration apparatus **20** to substantially remove particulate solids therefrom to form low solids biomass-derived pyrolysis oil **25**, as hereinafter defined. For example, the biomass-derived pyrolysis oil may be contacted in the filtration apparatus with one or more filters (and filter media) for a selected period of time to produce a filtrate comprised of filtered biomass-derived pyrolysis oil and a filter cake. The filters may be used sequentially for treating the same volume of oil. The biomass-derived pyrolysis oil may be filtered using one or more of vacuum, gravity, or pressure filtration. The filtrate is removed from the filter cake and the filtrate is recovered. For pressure filtration, pressurized gas such as nitrogen, air, or the like may be supplied on the input side of the filter to accelerate filtration. Pressures from about 1 atmosphere (atm) absolute pressure to about 8 atm absolute pressure may be used. The period of time required for filtration is dependent on volume and viscosity of the oil being filtered, the amount and particle size of solids to be removed, the filter media (composition and pore size), and filtration pressure and temperature. For vacuum filtration, negative pressure (i.e., a vacuum) of about 0.10 atm absolute pressure to about 0.95 atm absolute pressure may be supplied on the output side of the filter. No pressure is used for gravity filtration.

[0021] While filtration as a method to reduce solids in the biomass-derived pyrolysis oil has been described, other methods of reducing solids therefrom to the target level may be used in accordance with exemplary embodiments of the present invention to obtain “low solids biomass-derived pyrolysis oil.” For example, other filtering methods, centrifugation, etc. may be used to reduce solids in the biomass-derived pyrolysis oil. “Low solids biomass-derived pyrolysis oil” as used herein means a biomass-derived pyrolysis oil having the target solids level of less than about 0.10%, preferably less than about 0.01%, solids. Conventional biomass-derived pyrolysis oil may be a low solids biomass-derived pyrolysis oil if the solids content therein is already at the target solids level. As used herein, “low solids” includes zero solids. Solids content in biomass-derived pyrolysis oil may be measured as described in the Annex to ASTM D7544-09 “Standard Specification for Pyrolysis Liquid Biofuel”, or by other known methods.

[0022] Still referring to FIG. 2, if the low solids biomass-derived pyrolysis oil **25** has a metal content level above the target level, the low solids biomass-derived pyrolysis oil undergoes a metal reduction process, for example ion-exchange on an ion-exchange resin **30**, to reduce the total metal concentration therein to the target level. The low solids biomass-derived pyrolysis oil is contacted with the ion-exchange resin. The low solids biomass-derived pyrolysis oil that contacts the ion-exchange resin undergoes ion exchange such that metal ions are captured by the ion-exchange resin. More specifically, the ion-exchange resin contains sulfonic acid at its active sites. When the low solids biomass-derived pyrolysis oil contacts the resin, the metals preferentially migrate out

of the oil to the active sites on the ion-exchange resin. The metals in the biomass-derived pyrolysis oil are replaced by hydrogen ions.

[0023] The ion-exchange can be accomplished by either a batch method or a continuous column method. In the batch method, the ion-exchange resin and biomass-derived pyrolysis oil are contacted by mixing the resin and oil in a resin vessel, batch tank, or the like. A given weight of ion-exchange resin is added to a known volume of low solids biomass-derived pyrolysis oil, as hereinafter described. The amount of ion-exchange resin added to the fixed amount of oil is typically an excess of resin (based on theoretical resin capacity, as defined below). The optimum resin to oil ratio is determined experimentally and is impacted by temperature and exposure time. The resin/oil mixture is agitated for about 0.5 hours to about 24 hours, preferably about 0.5 to about 4 hrs (hereinafter “the exposure time”) at a temperature of about 10° C. to about 120° C., preferably from about 20° C. to about 60° C. Samples of the ion-exchanged oil may be collected and analyzed for metal content, as hereinafter described.

[0024] In the continuous column method, the ion-exchange resin and the low solids biomass-derived pyrolysis oil are contacted by passing the biomass-derived pyrolysis oil through a column (of one or more “beds”) containing the ion-exchange resin. The resin temperature may be from about 10° C. to about 120° C., preferably from about 20° C. to about 60° C. The biomass-derived pyrolysis oil is passed through the column by positive pressure flow or by gravity flow. When pressure is applied, the absolute pressure is from greater than 0 KPa to about 13790 KPa (0 to about 2000 psi), preferably from greater than 0 KPa to about 689.5 KPa (greater than 0 psi to about 100 psi), and most preferably from about 13.8 KPa to about 206.8 KPa (about 2 psi to about 30 psi). When no pressure is applied, the biomass-derived pyrolysis oil passes downward through the column and is allowed to slowly elute gravimetrically.

[0025] The low solids biomass-derived pyrolysis oil is passed over the ion-exchange resin at a Liquid Hourly Space Velocity (LHSV) of about 0.1-20 hr⁻¹, preferably about 1-10 hr⁻¹. The faster the LHSV, the less time there is for the ion-exchange. When the LHSV is reduced, the concentration of the selected metal ions in the treated oil is reduced significantly.

[0026] When metal levels in the low solids biomass-derived pyrolysis oil reach a target concentration (the “target level”), or when metal concentration is constant (as determined by repeat measurements) over an extended time period, contact between the oil and the resin may be concluded and ion-exchange is deemed “complete”. Metal concentrations in biomass-derived pyrolysis oil may be measured by Atomic Absorption Spectroscopy (AAS), Inductively-Coupled Plasma-Atomic Absorption Spectroscopy (ICP-AAS), or other known methods.

[0027] The volume capacity of the ion-exchange resin (VC_r) for both batch and continuous column methods is the volume of resin needed to completely ion-exchange a given mass of oil and is determined by the equation:

$$VC_r(\text{mL resin/kg oil}) = (\sum_i (C_i * 1000 \text{ g/kg}) / MW_i) * V_i * 1000 \text{ meq/eq} / (TC_r * D_r)$$

wherein:

C_i is the concentration of metal i in the biomass-derived pyrolysis oil in gram metal/gram oil;

MW_i is the molecular weight of metal i in g/mol;

V_i is the valency (charge) of metal i in solution;

D_r is the ion-exchange resin density in g/mL; and

TC_r is the theoretical capacity of resin r. Theoretical capacity (TC_r) is often expressed in terms of milliequivalents ions/gram resin.

[0028] The maximum volume of oil (in liters) that can be processed per unit volume of ion-exchange resin in both batch and continuous column methods is expressed as:

$$V_{oil} = V_r / (VC_r * D_{feed})$$

wherein:

V_{oil} is the volume of low solids biomass-derived pyrolysis oil in liters;

D_{feed} is the feed oil (the starting biomass-derived pyrolysis oil) density (in kilograms/liter);

V_r is the resin volume in milliliters; and

VC_r is the volume capacity of acidic ion-exchange resin to a given mass of metal-containing biomass-derived pyrolysis oil as determined above and expressed in mL resin/kg of biomass-derived pyrolysis oil. The V_{oil}/V_r processed is also known as the number of bed volumes (BV) of oil processed. For a continuous column method, the volume of ion-exchange resin is fixed and a sub-theoretical volume of oil is passed through the ion-exchange resin. Filtered biomass-derived pyrolysis oil is contacted with about 0.1 to about 10 times the volume capacity (VC_r) of the acidic ion-exchange resin, preferably about 1 to about 5 VC_r.

[0029] Resin efficiency, also referred to as ion-exchange efficiency (IX_{eff}), is defined as the fraction of metals removed from the liquid biomass-derived pyrolysis oil relative to the theoretical capacity of the resin and is determined as follows:

$$IX_{eff} = (\sum_i ((C_{if} - C_{ip}) * V_i / MW_i * 1000 * M_f)) / (TC_r * M_r)$$

where C_{if} and C_{ip} are the concentration of metal i expressed in terms of grams of metal i per gram of oil in the feed (biomass-derived pyrolysis oil) and product (low metal biomass derived pyrolysis oil), respectively, M_f is the mass of feed oil in grams, MW_i is the molecular weight of metal i in g/mol, V_i is the valency (charge) of metal i in solution, TC_r is the theoretical capacity of resin r and M_r is the mass in grams of resin r utilized. If it is assumed that a single metal ion neutralizes one resin exchange site regardless of ion charge, then the valence of the individual ions (V_i) is assigned as 1 for all metals. A higher exchange efficiency is typically desired. Theoretical resin capacity multiplied by the ion exchange efficiency provides the actual capacity, which is the amount of ion-exchange resin needed to actually deionize a given amount of biomass-derived pyrolysis oil. The lower the experimental resin capacity, i.e., the lower the concentration of acid sites (eq/L), the larger the column needs to be, i.e., the greater the resin volume needed to deionize the filtered biomass-derived pyrolysis oil.

[0030] Suitable ion-exchange resins useful in this process are strongly acidic cation-exchange resins. Preferably, the resin is used in the protonated form, i.e., all of the active groups are —SO₃H. Neutralized sulfonic acid resins, in which some or all of the protons have been exchanged by a cation such as lithium, sodium, potassium, magnesium, and calcium are also suitable. However, if resins are supplied with an alternate counterion (i.e., sodium, Na⁺), then the acid form may be generated prior to use by treatment with aqueous acid (such as hydrochloric, nitric, or sulfuric acid, etc.) This is commonly known in the art as ion-exchange resin activation. Preferably, the resin comprises sulfonated copolymers of styrene.

[0031] Preferred sulfonic acid resins are macroreticular resins. As used herein, “macroreticular resins” are made of two continuous phases—a continuous pore phase and a continuous gel polymeric phase. The continuous gel polymeric phase is structurally composed of small spherical microgel particles agglomerated together to form clusters, which, in turn, form interconnecting pores. The surface area arises from the exposed surface of the microgel clusters. Macroreticular ion exchange resins can be made with different surface areas ranging from 7 to 1500 m²/g, and average pore diameters ranging from about 5 to about 10000 nm.

[0032] Gel-type resins may also be used. As used herein, “gel-type resins” are generally translucent. There are no permanent pore structures for the gel-type resins. The pores are generally considered to be molecular-scale micropores. The pore structures are determined by the distance between the polymer chains and crosslinks which vary with the crosslink level of the polymer, the polarity of the solvent, and the operating conditions. Macroreticular resins are preferable for continuous column ion-exchange applications where resin swelling/shrinking should be minimized, while gel-type resins are preferred for batch ion-exchange applications, but either type may be used in either application. Exemplary suitable acidic ion-exchange resins include those manufactured by Dow Chemical Co., Midland, Mich. (USA) under the tradenames/trademarks DOWEX® MARATHON C, DOWEX® MONOSPHERE C-350, DOWEX® HCR—S/S, DOWEX® MARATHON MSC, DOWEX® MONOSPHERE 650C, DOWEX® HCR—W2, DOWEX® MSC-1, DOWEX® HGR NG (H), DOWEX® DR-G8, DOWEX® 88, DOWEX® MONOSPHERE 88, DOWEX® MONOSPHERE C-600 B, DOWEX® MONOSPHERE M-31, DOWEX® MONOSPHERE DR-2030, DOWEX® M-31, DOWEX® G-26 (H), DOWEX® 50W-X4, DOWEX® 50W-X8, DOWEX® 66, those manufactured by Rohm and Haas, Philadelphia, Pa. (USA) under the tradenames/trademarks Amberlyst® 131, Amberlyst® 15, Amberlyst® 16, Amberlyst® 31, Amberlyst® 33, Amberlyst® 35, Amberlyst® 36, Amberlyst® 39, Amberlyst® 40, Amberlyst® 70, Amberlite® FPC11, Amberlite® FPC22, Amberlite® FPC23, those manufactured by Brotech Corp., Bala Cynwyd, Pa. (USA) under the tradenames/trademarks Purolite® PFC150, Purolite® C145, Purolite® C150, Purolite® C160, Purolite® PFC100, Purolite® C100, and those manufactured by Thermax Limited Corp., Novi, Mich. (USA) under the tradename/trademark Monoplus™ 5100 and Tulsion® T42.

[0033] A low solids, low metal biomass-derived pyrolysis oil **35** is then removed from the used ion-exchange resin (hereinafter “spent ion-exchange resin”). In a batch ion-exchange, the low solids, low metal biomass-derived pyrolysis oil may be removed by filtration, decantation, or other known method. In continuous column ion exchange, the low solids, low metal biomass-derived pyrolysis oil is removed from the spent ion-exchange resin when the low solids, low metal biomass-derived pyrolysis oil elutes from the column gravimetrically or under positive pressure. As used herein, “low metal” biomass derived pyrolysis oil” has the target level of total metals of less than about 100 ppm, preferably less than about 20 ppm. Conventional biomass-derived pyrolysis oil may be low metal biomass-derived pyrolysis oil if the total metals content therein is already at the target total metals level. As used herein, “low metals” includes zero metals. While particular ion-exchange methods have been described,

other methods of reducing the total metal content to the target level may be used in accordance with exemplary embodiments of the present invention.

[0034] Still referring to FIG. 2, the low solids, low metal biomass-derived pyrolysis oil **35** may be subjected to an azeotropic, vacuum, gas-assisted, or atmospheric distillation process in a first fractionator **40** such as a distillation apparatus to reduce the water content therein. Azeotropic, vacuum, and gas-assisted distillation processes permit the removal of water **45** from biomass-derived pyrolysis oil without having to heat the oil to at least 100° C. (the boiling point of water at one atmosphere) to remove the water, i.e., such processes allow atmospheric distillation at lower temperatures. The use of lower temperatures to remove the water from the oil substantially prevents solidification (phase separation) of the oil that is experienced at elevated temperatures (typically about 150° C.).

[0035] Vacuum distillation is performed at lower than atmospheric pressure to lower the boiling point of the water in the biomass-derived pyrolysis oil so that water therein may be removed by heating the biomass-derived pyrolysis oil at least to the lower boiling point of water at that reduced pressure. The boiling point of water at that pressure may be determined by consulting temperature/pressure charts that are available from, for example, the National Bureau of Standards (NBS)/National Research Council (NRC). Vacuum may be applied by a vacuum pump, aspirator, or the like. In a preferred embodiment, the biomass-derived pyrolysis oil is heated to about 65° C. at a vacuum of about 0.05 to about 0.95 atm (absolute pressure) until the desired amount of water is removed to reach the target level.

[0036] Gas-assisted distillation uses a standard distillation column with an inert gas such as nitrogen, air, argon, helium, hydrogen or other gas passing into and over the low metal, water-containing biomass-derived pyrolysis oil while heating the low metal biomass-derived pyrolysis oil to a selected temperature of about 30° C. to about 90° C., preferably about 70° C. at a flow rate of about 0.1 to about 100 liters (L) gas/L oil/minute, preferably about 0.5 to about 4 L gas/L oil/min. Gas-assisted distillation functionally reduces the vapor pressure of the oil, thus resulting in more water in vapor phase so that it can be removed from the low metal biomass-derived pyrolysis oil at less than 100° C. The rate at which the water is removed is limited by the vapor pressure of water at the selected temperature, the gas flow rate, and the liquid volume to be distilled. The gas flow rate (controlled by a mass flow controller or valve) and selected temperature may be varied depending on the desired rate of water removal. The wt. % water in the starting and treated biomass-derived pyrolysis oil may be measured, for example, by the Karl Fischer Reagent Titration Method (ASTM D1364) as known to one skilled in the art. Preferably, the treated biomass-derived pyrolysis oil contains less than 20 weight percent water (the “target level”).

[0037] While particular methods for reducing the water content in biomass-derived pyrolysis oil have been described, other methods of reducing water in biomass-derived pyrolysis oil known to those skilled in the art may be used. It is also noted that while ion-exchange prior to water removal has been described, metal removal (including ion-exchange) following water removal may also be performed. As a result of fractionation, a “low solids, low metal, low water biomass-derived pyrolysis oil” **50** having the target level of water of less than about 20 weight percent (wt. %), preferably less than about 15 wt. % is produced. As noted previously, conven-

tional biomass-derived pyrolysis oil may be low water biomass-derived pyrolysis oil if the water content therein is already at the target water level. As used herein, “low water” includes zero water.

[0038] Still referring to FIG. 2, in a preferred embodiment, the low solids, low metal, low water biomass-derived pyrolysis oil is esterified. Esterification is, however, optional as noted previously. Esterification increases catalyst longevity by reacting components that are believed to participate in reactions that cause fouling of the catalyst. The low solids, low metal, low water biomass-derived pyrolysis oil is esterified in the presence of supercritical alcohol **60** to form esterified biomass-derived pyrolysis oil **70**. The low solids, low metal, low water biomass-derived pyrolysis oil **50** is diluted with the alcohol **60** to form a solution **53**. The alcohol **60** employed for esterification includes, but is not limited to aliphatic alcohols, such as methanol, ethanol, propanol, and butanol.

[0039] Diluting can be achieved by placing a predetermined volume of the treated acid-containing biomass-derived pyrolysis oil in a container, such as a tank, vessel or the like, and adding the ethanol to the container to form the solution. In an example, an amount of ethanol is added to the low solids, low metal, low water biomass-derived pyrolysis oil such that the solution **53** includes at least 15% alcohol by weight. In other embodiments, more or less alcohol is added to the solution.

[0040] The solution **53** is esterified at a temperature and a pressure that are at supercritical or just below critical limitations of the alcohol. For example, esterification can be performed at a temperature in a range from of about 180° C. to about 290° C. at a pressure of at least 4.4 MPa to about 8.00 MPa (640 psig to about 1160 psig). In other embodiments, the particular temperatures and/or pressures employed are selected based on the alcohol included in the solution **53**. In any case, the solution is esterified for a residence time in a range of about 0.5 hour to about 3 hours. In other embodiments, esterification occurs for a longer or shorter time period. Esterification preferably occurs in the absence of gas. In this regard, an inert gas, such as nitrogen, can be employed to evacuate the atmosphere in which esterification occurs, and a vacuum seal may be formed after the atmosphere is substantially completely evacuated.

[0041] The solution **53** is passed through a reactor **55** under supercritical conditions or near critical conditions of alcohol to esterify the acids in the solution **53**. As used herein, the term “supercritical conditions” is defined as a temperature and pressure above a critical point of the alcohol. The terms “just below critical” and “near critical” mean $\pm 10\%$ on temperature and pressure. FIG. 3 is a phase diagram for pure ethanol. The phase diagram includes an x-axis **302** representing temperature as measured in ° C. and a y-axis **304** representing pressure as measured in megaPascals (MPa). Line **306** includes a triple point **308** from which another line **310** extends to thereby indicate a phase change threshold between the solid, liquid, and vapor phases of ethanol. Line **306** further includes a critical point **312** at which the liquid and gaseous phase of ethanol become substantially identical. The critical point **312** for ethanol is at about 243° C. and about 6.38 MPa (925 psi). As shown in FIG. 3, points along line **306** beyond the critical point **312** correspond to supercritical conditions. Other aliphatic alcohols employed during esterification have critical points that are different from that of ethanol. For example, the critical point of methanol is at about 240° C. and about 7.95 MPa (1153 psi). The critical point of propanol is at

about 268.6° C. and about 5.16 MPa (749 psi), and the critical point of butanol is at about 289.8° C. and about 4.42 MPa (641 psi).

[0042] The reactor may be an upflow tubular reactor with or without a fixed catalyst bed. Although the preferred reactor comprises the upflow tubular reactor, downflow reactors can be employed in some embodiments. Suitable types of reactors include, but are not limited to fluidized bed systems, batch reactors, continuously stirred reactors, and the like. No matter the particular type of reactor employed, the esterification catalyst composition can be simply placed within the reactor or on the catalyst bed for reaction with the solution.

[0043] According to an embodiment, esterification is performed in the absence of an esterification catalyst composition. In accordance with another embodiment, esterification is performed in the presence of an esterification catalyst composition. As used herein, an “esterification catalyst composition” is defined as solid composition comprising at least an active phase. The esterification catalyst composition is selected to reduce the total acid number of the acid-containing biomass-derived pyrolysis oil and may be referred to herein as an “esterification catalyst.” In this regard, suitable esterification catalyst compositions comprise solid acid catalysts, solid base catalysts or catalytic metals dispersed on a solid support such as those typically employed for hydroprocessing. Exemplary solid acid esterification catalysts include, but are not limited to, molecular sieves, metal oxides, and sulfated metal oxides. Suitable molecular sieves include, but are not limited to zeolites and MCM 41. The zeolite can be selected from BEA-type zeolites, zeolite X, zeolite Y, zeolite ZSM 5, and zeolite ZSM 12. Metal oxides useful as solid acid esterification catalysts include those selected from Group IV metal oxides and Group V metal oxides. For example, Group IV metal oxides include, but are not limited to titanium oxide (TiO_2) and zirconium oxide (ZrO_2). Group V metal oxides include niobium oxide (Nb_2O_5). In other embodiments, other Group IV and V metal oxides and mixtures thereof can alternatively be employed. Sulfated metal oxides used as solid acid esterification catalysts include sulfated zirconia. The aforementioned solid acid esterification catalysts are intended for use as standalone catalysts. Hence, the solid acid esterification catalyst is not employed with a support material.

[0044] The solid base esterification catalysts include, but are not limited to basic metal oxides and alkaline-earth metal exchanged molecular sieves. Suitable basic metal oxides employed as solid base catalysts include, but are not limited to calcium oxide (CaO), magnesium oxide (MgO), and other basic metal oxides. Exemplary alkaline-earth metal exchanged molecular sieves suitable for inclusion as esterification catalyst compositions include, but are not limited to, barium exchanged molecular sieves, calcium exchanged molecular sieves, and the like. The aforementioned solid base esterification catalysts are intended for use as standalone catalysts. Hence, the solid base catalyst is not employed with a support material.

[0045] In other embodiments, the esterification catalyst composition may comprise one or more metal dispersed on a metal oxide support. The metal may be dispersed on the support as the oxide, sulfide or as the metal (zero valent state). Examples of supported catalyst compositions which may be used are those employed for hydroprocessing. For example, the catalytic metals can comprise one or more noble metals or non-noble metals. In an embodiment, the noble metal may be present in an amount from about 0.1 wt. % to about 1.5 wt. % of the catalyst composition. As used herein, wt. % means the weight of the catalytic metal (as the metal) divided by the total

weight of the catalytic composition (catalytic metal weight plus weight of the support). Suitable noble metals include, but are not limited to gold (Au), platinum (Pt), rhodium (Rh), ruthenium (Ru), palladium (Pd), and iridium (Ir).

[0046] If a non-noble metal is used, the non-noble metal can be selected from nickel (Ni), cobalt (Co), molybdenum (Mo), tungsten (W), and combinations thereof. For example, metals such as Ni/Mo, Co/Mo, Ni/Co/Mo, Ni/W, and combinations thereof, may be employed. If the catalytic metals are Ni/Mo, the metals may be present in an amount from about 0.5 wt. % to about 3.5 wt. % of nickel, and about 5 wt. % to about 20 wt. % of molybdenum. In an embodiment in which Co/Mo are the catalytic metals, the metals may be present from about 0.5 wt. % to about 3.5 wt. % of cobalt and about 5 wt. % to about 20 wt. % of molybdenum. If Ni/Co/Mo are the catalytic metals, the metals may be present from about 0.1 wt. % to about 1.5 wt. % of nickel, about 0.5 wt. % to about 3.5 wt. % of cobalt, and about 5 wt. % to about 20 wt. % of molybdenum. For the case of Ni/W, the metal concentration comprises about 0.5 wt. % to about 3.5 wt. % of nickel, and about 5 wt. % to about 20 wt. % of tungsten.

[0047] The support materials include metal oxide support materials, including, but not limited to a Group IV metal oxide, a Group V metal oxide, and a Group IIIA metal oxide. The metal oxide support material can be selected from a group consisting essentially of titanium oxide (TiO₂), zirconium oxide (ZrO₂), niobium oxide (Nb₂O₅), quartz, silicon carbide, aluminum oxide (Al₂O₃), and silicon oxide (SiO₂).

[0048] In another embodiment, the catalyst material comprises a sulfated metal oxide. For example, the sulfated metal oxide comprises sulfated zirconia. The sulfated metal oxide can support a metal, in an embodiment. In an example, the metal is a noble metal. In such case, the noble metal comprises palladium.

[0049] As a result of esterification, the acids in the biomass-derived pyrolysis oil are converted into esters to thereby yield esterified biomass-derived pyrolysis oil, i.e., a low acid biomass-derived pyrolysis oil. For example, light carboxylic acids (e.g., acids having C₁-C₄) are converted to volatile esters. As used herein, "volatile esters" have a boiling point below or equal to the normal boiling point of the ethanol. In some cases, about 80% to about 95% of the light carboxylic acids are converted, thereby reducing the TAN of the biomass-derived pyrolysis oil by about 5% by weight. Exemplary equations of the reactions that may occur within the biomass-derived pyrolysis oil are provided below.

Formic Acid+Ethanol→Water+Ethyl Formate

$$\text{HCOOH} + \text{CH}_3\text{CH}_2\text{OH} \rightarrow \text{H}_2\text{O} + \text{HCOOCH}_2\text{CH}_3$$

Acetic acid+Ethanol→Water+Ethyl Acetate

$$\text{CH}_3\text{COOH} + \text{CH}_3\text{CH}_2\text{OH} \rightarrow \text{H}_2\text{O} + \text{CH}_3\text{COOCH}_2\text{CH}_3$$

Propionic Acid+Ethanol→Water+Ethyl Propionate

$$\text{CH}_3\text{CH}_2\text{COOH} + \text{CH}_3\text{CH}_2\text{OH} \rightarrow \text{H}_2\text{O} + \text{CH}_3\text{CH}_2\text{COOCH}_2\text{CH}_3$$

Butanoic Acid+Ethanol→Water+Ethyl Butyrate

$$\text{CH}_3\text{CH}_2\text{CH}_2\text{COOH} + \text{CH}_3\text{CH}_2\text{OH} \rightarrow \text{H}_2\text{O} + \text{CH}_3\text{CH}_2\text{CH}_2\text{COOCH}_2\text{CH}_3$$

[0050] Referring again to FIG. 2, optionally, after esterification, the esterified biomass-derived pyrolysis oil **70** may undergo fractionation in a second fractionator **65** to remove

ethanol. The removed ethanol can be recycled and returned to the reactor for use as the supercritical alcohol **60** in later esterification steps. The remaining low acid biomass-derived pyrolysis oil, now comprising volatile esters forms the treated biomass-derived pyrolysis oil **90**. Fractionation can be achieved in the second fractionator **65** by providing a temperature gradient along a fractionation column, where a minimum temperature of the temperature gradient is set just above the boiling point of ethanol. A fraction of the low acid biomass-derived pyrolysis oil (e.g., the ethanol) is collected at a location along the temperature gradient, distilled and directed to a separate container. While TAN reduction using esterification with an esterification catalyst and supercritical ethanol has been described, the total acid number (inclusive of the carboxylic acid number) may be further reduced by other methods known in the art, including but not limited to other esterification methods.

[0051] While the reduction of solids, metals, and water in the biomass-derived pyrolysis oil followed by esterification is shown in FIG. 2 for illustrative purposes, it will be understood, as noted previously, that esterification is optional. It will also be understood that while the treated biomass-derived pyrolysis oil preferably comprises the esterified low solids, low metal, low water biomass-derived pyrolysis oil, "treated biomass-derived pyrolysis oil" also includes non-esterified and esterified biomass-derived pyrolysis oil that is one or more of low solids, low metal, and low water, i.e., the solids content, the metal content, and the water content may not all be at the target levels. Additionally, in some cases, conventional biomass-derived pyrolysis oil may already have a solids content, a total metals content, and a water content at the desired target levels, in which case the conventional biomass-derived pyrolysis oil may be considered the low solids, low metals, low water biomass-derived pyrolysis oil. The conventional biomass-derived pyrolysis oil may also be selectively treated to reduce only those levels not at the target level(s). It is also to be understood that while a particular sequence of steps has been described, such steps may be performed in a different sequence.

[0052] Referring again to FIGS. 1 and 2, method **10** continues with exposing the treated biomass-derived pyrolysis oil **90** to a catalyst having a neutral catalyst support in a hydroprocessing reactor **105** (step **300**). As used herein, a "neutral catalyst support" is defined as one that shows less than 15% total conversion of 1-heptene in a catalytic test reactor as follows: 0.25 g of solid support material (ground and sieved to 40/60 mesh) is loaded in a tubular reactor and heated under flowing hydrogen (1 atmosphere, upflow) to 550° C. for 60 minutes. The reactor is cooled to 425° C., hydrogen flow rate is set at 1 slm (standard liter per minute) and then 1-heptene is introduced to the catalyst bed (by injection into or saturation of the hydrogen stream) at a rate of ~0.085 g/min. Conversion of 1-heptene is defined by 100*(1-X(heptene)) where X is the mol fraction 1-heptene in the hydrocarbon product as determined by gas chromatographic analysis of the reactor effluent stream. Various options for gas chromatographic analysis as known in the art are suitable, and other analytical methods known in the art may be substituted for gas chromatographic analysis as long as a mole fraction of n-heptene in the product may be calculated.

[0053] Exemplary neutral catalyst materials comprise carbon, a non-alumina metal oxide, a theta alumina, or mixtures thereof. The non-alumina metal oxide support comprises a titanium oxide (TiO₂) support, a silicon oxide support, a

zirconia oxide (ZrO_2) support, a niobium oxide (Nb_2O_5) support, or a support comprising mixtures of the non-alumina metal oxides. The non-alumina metal oxide support may be mixed with one or more additional components to improve the physical stability and/or phase stability of the metal oxide. Components that improve physical stability include, but are not limited to, carbon, other metal oxides, and clays as known in the art. Components that improve phase stability include, but are not limited to, base metals, transition metals, non-metals, lanthanide metals, and combinations thereof “Theta alumina” as used herein refers to alumina having a crystallinity as measured by X-ray diffraction corresponding to that characterized in the Joint Committee on Powder Diffraction Standards number 23-1009.

[0054] Catalysts having a neutral catalyst support comprise a metal. The metal can be a noble metal, or a Group VIII non-noble metal and a Group VIB non-noble metal. The noble metal comprises rhodium (Rh), palladium (Pd), gold (Au), and ruthenium (Ru), or combinations thereof. The noble metal comprises about 0.1 to about 5 weight percent of the catalyst having the neutral catalyst support. The effective amount of the catalyst is expressed as a catalyst to oil ratio of about 0.1 to about 10 weight of catalyst per hourly weight feed rate of treated biomass-derived pyrolysis oil.

[0055] The Group VIII non-noble metal comprises cobalt, nickel, or both. The Group VIB non-noble metal comprises molybdenum or tungsten. The Group VIB and Group VIII non-noble metals are optionally sulfided. The molar ratio of Group VIB non-noble metals to Group VIII non-noble metals ranges from about 10:1 to about 1:10. The weight percent of nickel and cobalt comprises from about 0.1 to about 5 weight percent of the total weight of the catalyst, the cobalt calculated as an oxide and the weight percent of the molybdenum and of the tungsten in the catalyst comprises from about 5 to about 20 weight percent of the total weight of the catalyst, the molybdenum calculated as an oxide. The term “calculated as an oxide” means that the metal is calculated as a metal oxide. When metals are initially incorporated onto the neutral catalyst support, they may be present as the metal oxide, rather than in the metallic state. Therefore, as used herein, if the metal is “calculated as an oxide”, that means the catalyst has x % metal oxide. The actual amount of the metal will be somewhat lower depending on the stoichiometry of the specific oxide. The oxide is removed during deoxygenation. Exemplary metals for the catalysts are listed in the FIG. 3 table, with the corresponding neutral catalyst supports listed in FIG. 4. The weight % metals identified in the cells of the table of FIG. 3 are arranged from low to high, with the preferred wt. % shown between the low and high values.

[0056] Still referring to FIGS. 1 and 2, the treated biomass-derived pyrolysis oil is exposed to the catalyst having a neutral catalyst support under hydroprocessing conditions to produce the low oxygen biomass-derived pyrolysis oil by converting at least a portion of the oxygenated hydrocarbons in the treated biomass-derived pyrolysis oil into hydrocarbons. Such deoxygenation requires a source of hydrogen gas 110 which removes the oxygen as water 115, thereby producing low oxygen biomass-derived pyrolysis oil 120. Preferably, substantially all of the oxygenated hydrocarbons are converted into hydrocarbons.

[0057] The minimum amount of hydrogen gas needed to convert substantially all of the oxygenated hydrocarbons in the treated biomass-derived pyrolysis oil comprises 1-2 equivalents of hydrogen gas per one equivalent of non-water

oxygen. The non-water oxygen in the treated biomass-derived pyrolysis oil is derived from the functional groups of the oxygenated hydrocarbons in the treated biomass-derived pyrolysis oil. For example, one equivalent of an alcohol functional group and a ketone functional group requires 1 equivalent of hydrogen gas for deoxygenation whereas one equivalent of an ester functional group requires 2 equivalents of hydrogen gas, and 1 equivalent of a carboxylic acid functional group requires 1.5 equivalents of hydrogen gas. Therefore, for example, the more esters and carboxylic acids present in the treated biomass-derived pyrolysis oil, the more hydrogen gas is necessary for substantially complete deoxygenation into hydrocarbons. The minimum amount of hydrogen gas to substantially deoxygenate the treated biomass-derived pyrolysis oil is equal to about 1 to about 3 molar equivalents of the non-water oxygen in the treated biomass-derived pyrolysis oil. The amount of non-water oxygen=A-B wherein A is the total amount of oxygen in the treated biomass-derived pyrolysis oil as determined by combustion method, as known in the art and B is the total amount of oxygen in the water in the treated biomass-derived pyrolysis oil. To determine B, the total water content in the treated biomass-derived pyrolysis oil is first determined by the Karl Fischer Reagent Titration Method (ASTM D1364) as known to one skilled in the art. An excess of hydrogen gas may also be used. Suitable hydroprocessing conditions include a temperature of about 100° C. to about 400° C., a pressure of about 2758 kPa to about 12410 kPa (400-1800 psig), and a residence time in the hydroprocessing reactor of about 0.2 hours to about 20 hours. These hydroprocessing conditions are representative only, and may be varied as well known to one skilled in the art.

[0058] From the foregoing, it is to be appreciated that the low oxygen biomass-derived pyrolysis oil 120 produced in accordance with exemplary embodiments of the present invention has significantly less oxygen and water, making it more suitable for use and processing as a biofuel. In addition, the plugging that occurs with conventional deoxygenation is substantially prevented, providing for longer run times and improved processability of the biomass-derived pyrolysis oil.

[0059] While at least one exemplary embodiment has been presented in the foregoing detailed description of the invention, it should be appreciated that a vast number of variations exist. It should also be appreciated that the exemplary embodiment or exemplary embodiments are only examples, and are not intended to limit the scope, applicability, or configuration of the invention in any way. Rather, the foregoing detailed description will provide those skilled in the art with a convenient road map for implementing an exemplary embodiment of the invention, it being understood that various changes may be made in the function and arrangement of elements described in an exemplary embodiment without departing from the scope of the invention as set forth in the appended claims and their legal equivalents.

What is claimed is:

1. A method for deoxygenating treated biomass-derived pyrolysis oil, comprising the step of:
exposing the treated biomass-derived pyrolysis oil to a catalyst having a neutral catalyst support.
2. The method of claim 1, wherein the step of exposing comprises exposing the treated biomass-derived pyrolysis oil to a catalyst having a theta alumina support.
3. The method of claim 1, wherein the step of exposing comprises exposing the treated biomass-derived pyrolysis oil

to a catalyst having a carbon support, a non-alumina metal oxide support, or a support comprising a combination of carbon and non-alumina metal oxide.

4. The method of claim 3, wherein the step of exposing comprises exposing the treated biomass-derived pyrolysis oil to a catalyst having a non-alumina metal oxide support selected from the group consisting of a titanium oxide (TiO_2) support, a silicon oxide support, a zirconia oxide (ZrO_2) support, a niobium oxide (Nb_2O_5) support, and a support comprising mixtures of non-alumina metal oxides.

5. The method of claim 1, wherein the step of exposing comprises exposing the treated biomass-derived pyrolysis oil to a catalyst comprising a noble metal on the neutral catalyst support, the noble metal selected from the group consisting of rhodium (Rh), palladium (Pd), gold (Au), ruthenium (Ru), and combinations thereof.

6. The method of claim 1, wherein the step of exposing comprises exposing the treated biomass-derived pyrolysis oil to a catalyst comprising a Group VIII non-noble metal and a Group VIB non-noble metal on the neutral catalyst support, the Group VIII non-noble metal comprising cobalt, nickel, or both, and the Group VIB non-noble metal comprising molybdenum or tungsten, wherein the Group VIB and Group VIII non-noble metals are optionally sulfided.

7. The method of claim 6, wherein the step of exposing comprises exposing the treated biomass-derived pyrolysis oil to a catalyst comprising nickel and molybdenum on a neutral catalyst support, the nickel comprising about 0.5 to about 5 weight percent of the catalyst and the molybdenum calculated as an oxide comprising about 5 to about 20 weight percent of the catalyst.

8. The method of claim 6, wherein the step of exposing comprises exposing the treated biomass-derived pyrolysis oil to a catalyst comprising nickel and tungsten on a neutral catalyst support, the nickel comprising about 0.5 to about 5 weight percent of the catalyst and the tungsten comprising about 5 to about 20 weight percent of the catalyst.

9. The method of claim 6, wherein the step of exposing comprises exposing the treated biomass-derived pyrolysis oil to a catalyst comprising nickel, cobalt, and molybdenum or tungsten on a neutral catalyst support, the nickel comprising about 0.1 to about 5 weight percent of the catalyst, the cobalt calculated as an oxide comprising about 0.5 to about 5 weight percent of the catalyst, and the molybdenum or tungsten comprising about 5 to about 20 weight percent of the catalyst, the molybdenum calculated as an oxide.

10. The method of claim 6, wherein the step of exposing comprises exposing the treated biomass-derived pyrolysis to a catalyst comprising cobalt and molybdenum or tungsten on a neutral catalyst support, the cobalt calculated as an oxide comprising about 0.5 to about 5 weight percent of the catalyst, and the molybdenum or tungsten comprising about 5 to about 20 weight percent of the catalyst, the molybdenum calculated as an oxide.

11. A method for deoxygenating treated biomass-derived pyrolysis oil, the method comprising the steps of:

providing a catalyst comprising a metal on a carbon support, a non-alumina metal oxide support, a theta alumina support, or a combination thereof; and

introducing treated biomass-derived pyrolysis oil into a hydroprocessing reactor in the presence of the catalyst under hydroprocessing conditions to produce low oxygen biomass-derived pyrolysis oil.

12. The method of claim 11, wherein the step of providing a catalyst comprises providing a catalyst having a non-alumina metal oxide support selected from the group consisting of a titanium oxide (TiO_2) support, a silicon oxide support, a zirconia oxide (ZrO_2) support, a niobium oxide (Nb_2O_5) support, and a support comprising a mixture of non-alumina metal oxides.

13. The method of claim 11, wherein the step of providing a catalyst comprises providing a catalyst comprising a noble metal on the non-alumina metal oxide support, the theta alumina support, or on a support comprising a mixture of a non-alumina metal oxide and theta alumina, the noble metal selected from the group consisting of rhodium (Rh), palladium (Pd), gold (Au), ruthenium (Ru), and combinations thereof.

14. The method of claim 11, wherein the step of providing a catalyst comprises providing a catalyst comprising a Group VIII non-noble metal and a Group VIB non-noble metal on the non-alumina metal oxide support, the theta alumina support, or on a support comprising a mixture of a non-alumina metal oxide and theta alumina, the Group VIII non-noble metal comprising cobalt, nickel, or both, and the Group VIB non-noble metal comprising molybdenum or tungsten, wherein the Group VIB and Group VIII non-noble metals are optionally sulfided.

15. The method of claim 14, wherein the step of providing a catalyst comprises providing a catalyst comprising nickel and molybdenum on the non-alumina metal oxide support, the theta alumina support, or on a support comprising a mixture of a non-alumina metal oxide and theta alumina, the nickel comprising about 0.5 to about 5 weight percent of the catalyst and the molybdenum calculated as an oxide comprising about 5 to about 20 weight percent of the catalyst, or a catalyst comprising nickel and tungsten on the non-alumina metal oxide support, the theta alumina support, or on a support comprising a mixture of a non-alumina metal oxide and theta alumina, the nickel comprising about 0.5 to about 5 weight percent of the catalyst and the tungsten comprising about 5 to about 20 weight percent of the catalyst.

16. The method of claim 14, wherein the step of providing a catalyst comprises providing a catalyst comprising nickel, cobalt, and either molybdenum or tungsten on a non-alumina metal oxide support, a theta alumina support, or a support comprising a mixture of a non-alumina metal oxide and theta alumina, the nickel comprising about 0.1 to about 5 weight percent of the catalyst, the cobalt calculated as an oxide comprising about 0.5 to about 5 weight percent of the catalyst, and the molybdenum or tungsten comprising about 5 to about 20 weight percent of the catalyst, the molybdenum calculated as an oxide.

17. The method of claim 14, wherein the step of providing a catalyst comprises providing a catalyst comprising cobalt and either molybdenum or tungsten on a neutral catalyst support, the cobalt calculated as an oxide comprising about 0.5 to about 5 weight percent of the catalyst, and the molybdenum or tungsten comprising about 5 to about 20 weight percent of the catalyst, the molybdenum calculated as an oxide.

18. A method for deoxygenating treated biomass-derived pyrolysis oil, the method comprising the steps of:

providing a catalyst comprising a metal on a carbon support, a non-alumina metal oxide support, a theta alumina support, or a support comprising combinations thereof; and

exposing the treated biomass-derived pyrolysis oil to the catalyst at hydroprocessing conditions sufficient to at least partially deoxygenate the treated biomass-derived pyrolysis oil;

wherein the non-alumina metal oxide support is selected from the group consisting of a titanium oxide (TiO_2) support, a silicon oxide support, a zirconia oxide (ZrO_2) support, a niobium oxide (Nb_2O_5) support, or a support comprising a mixture of non-alumina metal oxides.

19. The method of claim **18**, wherein the step of providing a catalyst comprises providing a catalyst comprising a noble

metal, the noble metal selected from the group consisting of rhodium (Rh), palladium (Pd), gold (Au), ruthenium (Ru), and combinations thereof.

20. The method of claim **18**, wherein the step of providing a catalyst comprises providing a catalyst comprising a Group VIII non-noble metal and a Group VIB non-noble metal, the Group VIII non-noble metal comprising cobalt, nickel, or a combination thereof, and the Group VIB non-noble metal comprising molybdenum or tungsten, wherein the Group VIB and Group VIII non-noble metals are optionally sulfided.

* * * * *