



US 20120308415A1

(19) **United States**

(12) **Patent Application Publication**
Pinkerton

(10) **Pub. No.: US 2012/0308415 A1**

(43) **Pub. Date: Dec. 6, 2012**

(54) **GRAPHENE-DRUM PUMP AND ENGINE SYSTEMS**

Related U.S. Application Data

(75) Inventor: **Joseph F. Pinkerton**, Austin, TX (US)

(60) Provisional application No. 61/301,209, filed on Feb. 4, 2010.

(73) Assignee: **Clean Energy Labs, LLC**, Austin, TX (US)

Publication Classification

(21) Appl. No.: **13/577,422**

(51) **Int. Cl.**
F04B 43/04 (2006.01)

(22) PCT Filed: **Feb. 3, 2011**


(52) **U.S. Cl.** **417/413.1**

(86) PCT No.: **PCT/US11/23618**

(57) **ABSTRACT**

§ 371 (c)(1),
(2), (4) Date: **Aug. 6, 2012**

The present invention relates to pump systems and engine systems having graphene drums. In embodiments of the invention, the graphene drum can be utilized in the main chambers and/or valves of the pumps and engines.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

GRAPHENE-DRUM PUMP AND ENGINE SYSTEMS

CROSS-REFERENCE TO RELATED PATENT APPLICATIONS

[0001] This application claims priority to: provisional U.S. Patent Application Ser. No. 61/301,209, filed on Feb. 4, 2010, entitled “Graphene-Drum Pump and Engine Systems,” which provisional patent application is each commonly assigned to the Assignee of the present invention and is hereby incorporated herein by reference in its entirety for all purposes.

TECHNICAL FIELD

[0002] The present invention relates to pump systems and engine systems having graphene drums.

SUMMARY OF THE INVENTION

[0003] Graphene membranes (also otherwise referred to as “graphene drums”) have been manufactured using process such as disclosed in Lee et al. Science, 2008, 321, 385-388. PCT Patent Appl. No. PCT/US09/59266 (Pinkerton) (the “PCT US09/59266 Application”) described tunneling current switch assemblies having graphene drums (which graphene drums generally having a diameter between about 500 nm and about 1500 nm). As described in the PCT US09/59266 Application, which is incorporated herein by reference, the graphene drum is capable of completely sealing the chamber formed by the graphene drum (i.e., the graphene drum provides a complete seal to fluids inside and outside the chamber). A graphene membrane is atomically thin.

[0004] In embodiments of the present invention, graphene drums are employed in pump systems and engine systems, such as to replace pistons and valves in conventional pumps and engines. Advantages of utilizing graphene drums (and other electrically conductive drums that are atomically thin) in such systems include:

[0005] a. Higher power density (because graphene drum “piston/valves” can operate in the MHz range (i.e., at least about 1 MHz) instead of the approximately 100 Hz range of conventional pumps and engines).

[0006] b. Higher efficiency (because graphene can withstand high temperatures and no oil is required for graphene diaphragm motion).

[0007] c. Quiet operation (because an operating frequency in the MHz range is not perceived by humans).

[0008] d. Smaller size, as compared to conventional pumps and engines.

[0009] e. More precise fluid flow.

[0010] For instance, U.S. Pat. No. 7,008,193 (Najafi) (“the Najafi Patent”) is directed to a MEMS-fabricated microvacuum pump assembly that utilizes a diaphragm made of a metal with a polymer layer on each side that is not atomically thin. Accordingly, the pump assembly is limited to kHz operation (resulting in slow pump speed) and requires a relatively high voltage to actuate (to overcome the inertia and stiffness of a thick diaphragm). It is believed that, unlike graphene drums and other atomically thin, electrically conductive drums, the MEMS-fabricated microvacuum pump assembly of the Najafi Patent cannot maintain a high vacuum on one side. This would be disadvantageous because a vacuum enables a high electric field (and, thus, a high actuation force, between the gate and the diaphragm without arcing). The Najafi Patent also appears to be a high wear device because

the pump and valve membranes of the MEMS-fabricated microvacuum pump assembly require repeated physical contact with other parts of the pump assembly to operate properly. This is disadvantageous compared to embodiments of the present invention in that the present invention does not require the graphene drum or other atomically thin, electrically conductive drum to come in contact with other parts of the pump to work.

[0011] As used herein, a “graphene-drum pump system” is a pump system that utilizes one or more graphene drums (such as a pump system that utilizes an array of graphene drums). A “graphene-drum pump” is a pump that utilizes a graphene drum, such as a pump that utilizes the graphene drum to displace the fluid during operation of the pump. A “graphene-drum engine system” is an engine system that utilizes one or more graphene drums (such as an engine system that utilizes an array of graphene drums). A “graphene-pump engine” is an engine that utilizes a graphene drum, such as an engine that utilizes a graphene drum to displace fluid during operation of the engine.

[0012] As a graphene drum may be between about 500 nm and about 1500 nm in diameter (i.e., around one micron in diameter), millions of graphene-drum pumps could fit on one square centimeter of a graphene-drum pump system or graphene-drum engine system. In other embodiments, the graphene drum may be between about 10 μm to about 20 μm in diameter and have a maximum deflection between about 1 μm to about 3 μm (i.e., a maximum deflection that is about 10% to 15% of the diameter of the graphene drum). As used herein, “deflection” of the graphene drum is measured relative to the non-deflected graphene drum (i.e., the deflection of a non-deflected graphene drum is zero).

[0013] In some instances, it is advantageous to use two or more graphene membranes stacked on top of one another for use as a unit (such as for use as a diaphragm). Such a stack of two or more graphene membranes are referred to as a “multi graphene-membrane stack.” While each of the individual graphene membranes of a multi graphene-membrane stack is atomically thin, the multi graphene-membrane stack itself generally is not. For instance, a multi graphene-membrane stack of a dozen graphene membranes generally would have a thickness of about 4 nm.

[0014] Alternatively, other types of electrically conductive membranes (also referred to as “electrically conductive drums”) that are atomically thin may be utilized in lieu of graphene membranes in embodiments of the present invention, such as, for example, graphene oxide membranes. A stack of two or more electrically conductive membranes are referred to as a “multi electrically-conductive-membrane stack.”

[0015] Moreover, the electrically conductive membranes or the multi electrically-conductive-membrane stack may include a thin (i.e., several nanometers in thickness) protective coating to protect the electrically conductive membranes from oxidation or corrosive fluids. For instance, a protective coating of graphene oxide or tungsten can be applied to a graphene drum.

[0016] In general, in one aspect, the invention features a pump that includes a cavity having a diaphragm. The diaphragm is operable to change the volume capacity of the cavity. The pump further includes an upstream valve connected to the cavity. The upstream valve is operable to be in an open position such that fluid can flow through the upstream valve into the cavity. The upstream valve is also operable to be

in a closed position such that fluid cannot flow through the upstream valve into the cavity. The pump further includes a downstream valve connected to the cavity. The downstream valve is operable to be in an open position such that fluid can flow from the cavity through the downstream valve. The downstream valve is also operable to be in a closed position such that fluid cannot flow from the cavity through the downstream valve. At least one of the cavity, upstream valve, or downstream valve of the pump includes an electrically conductive drum. The electrically conductive drum is atomically thin.

[0017] In general, in another aspect, the invention features an engine that includes a cavity having a diaphragm. The diaphragm is operable to change the volume capacity of the cavity. The cavity is operable to receive a combustible fluid mixture that can ignite in the cavity to form a combusted fluid mixture. The engine further includes an upstream valve connected to the cavity. The upstream valve is operable to be in an open position such that the combustible fluid mixture can flow through the upstream valve into the cavity. The upstream valve is also operable to be in a closed position such that the combustible fluid mixture cannot flow through the upstream valve into the cavity. The engine further includes a downstream valve connected to the cavity. The downstream valve is operable to be in an open position such that the combusted fluid mixture can flow from the cavity through the downstream valve. The downstream valve is also operable to be in a closed position such that the combusted fluid mixture cannot flow from the cavity through the downstream valve. At least one of the cavity, upstream valve, or downstream valve in the engine includes an electrically conductive drum. The electrically conductive drum is atomically thin.

[0018] Implementations of the invention can include one or more of the following features:

[0019] The engine can further include an igniter positioned inside the cavity to ignite the combustible fluid mixture in the cavity to form the combusted fluid mixture.

[0020] The cavity can be operable to provide a pressure and a temperature inside the cavity to ignite the combustible fluid mixture in the cavity to form the combusted fluid mixture.

[0021] The electrically conductive drum can have a thickness between about 0.3 nm and about 1 nm.

[0022] The electrically conductive drum of the pump or the engine may be a graphene drum.

[0023] The electrically conductive drum can be a graphene oxide membrane.

[0024] The electrically conductive drum can have a protective coating.

[0025] At least one of the cavity, upstream valve, or downstream valve can include a multi electrically-conductive-drum stack of at least two electrically conductive drums.

[0026] The multi electrically-conductive-drum stack can have a protective coating.

[0027] The protective coating can include graphene oxide, tungsten, or a combination thereof. The protective coating can have a thickness less than about 5 nm. The protective coating can protect against oxidation, corrosive fluids, or both.

[0028] The cavity of the pump or the engine may include a first electrically conductive drum. The upstream valve of the pump or the engine may include a second electrically conductive drum. And, the downstream valve of the pump or the engine may include a third electrically conductive drum. The first electrically conductive drum, the second electrically con-

ductive drum, and the third electrically conductive drum may all be part of one continuous sheet of electrically conductive material.

[0029] The first electrically conductive drum can be a first graphene drum. The second electrically conductive drum can be a second graphene drum. The third electrically conductive drum can be a third graphene drum.

[0030] The pump or the engine may further include a metallic gate. The electrically conductive drum may be operable to be pulled toward the metallic gate due to a voltage between the electrically conductive drum and the metallic gate. The metallic gate may include tungsten.

[0031] The diaphragm of the pump or the engine may be the electrically conductive drum.

[0032] The diaphragm may be operable to move to a first position such that the cavity has a first volume capacity. The diaphragm may be operable to move to a second position such that the cavity has a second volume capacity. The first volume capacity may be larger than the second larger capacity.

[0033] The diaphragm may operable to cycle back and forth between the first position and the second position at a frequency of at least about 1 MHz.

[0034] The pump or the engine may further include a second cavity. The diaphragm may be operable to change the volume capacity of the second cavity. As the volume capacity of the cavity increases, the volume capacity of the second cavity may decrease. As the volume capacity of the cavity decreases, the volume capacity of the second cavity may increase. The pump or the engine may further include a metallic gate located within the second cavity. The electrically conductive drum may be operable to be pulled toward the metallic gate due to a voltage between the electrically conductive drum and the metallic gate.

[0035] The second cavity of the pump or the engine may be under vacuum.

[0036] The upstream valve of the pump or the engine may include the electrically conductive drum. The electrically conductive drum may be operable to cycle back and forth between the open position and the closed position at a frequency of at least about 1 MHz.

[0037] The downstream valve of the pump or the engine may include the electrically conductive e drum. The electrically conductive drum may be operable to cycle back and forth between the open position and the closed position at a frequency of at least about 1 MHz.

[0038] The electrically conductive drum of the pump or the engine may have a diameter between about 500 nm and about 1500 nm.

[0039] The electrically conductive drum may have a diameter between about 10 μm and about 20 μm . The electrically conductive drum, may have a maximum deflection between about 1 μm and about 3 μm .

[0040] In general, in another aspect, the invention features an engine that includes a first cavity having a first electrically conductive drum. The first electrically conductive drum is atomically thin and is operable to change the volume of the first cavity. The engine further includes a second cavity having a second electrically conductive drum. The second electrically conductive drum is atomically thin and is operable to change the volume of the second cavity. The engine further includes a passage that allows fluid to flow between the first cavity and the second cavity. The engine further includes a heat exchanger operable to change the temperature of the fluid. The change of temperature of the fluid is either: (a)

cooling the temperature of the fluid as it moves from the first cavity to the second cavity and heating the temperature of the fluid as it moves from the second cavity to the first cavity, or (b) heating the temperature of the fluid as it moves from the first cavity to the second cavity and cooling the temperature of the fluid as it moves from the second cavity to the first cavity. The engine further includes a metallic gate located in the first cavity. The first electrically conductive drum is operable to move away from the metallic gate to generate energy.

[0041] Implementations of the invention can include one or more of the following features:

[0042] The first electrically conductive drum may be a first graphene drum. The second electrically conductive drum may be a second graphene drum.

[0043] The first electrically conductive drum may have a diameter between about 500 nm and about 1500 nm. The second electrically conductive drum may have a diameter between about 500 nm and about 1500 nm.

[0044] The first electrically conductive drum may have a diameter between about 10 μm and about 20 μm . The second electrically conductive drum may have a diameter between about 10 μm and about 20 μm .

[0045] The first electrically conductive drum may have a maximum deflection between about 1 μm and about 3 μm . The second electrically conductive drum may have a maximum deflection between about 1 μm and about 3 μm .

[0046] The engine may further include a plurality of thermally conductive nanowires. The plurality of the thermally conductive nanowires may be operatively connected to the cool cavity. The cool cavity may be the first cavity or the second cavity. The thermally conductive nanowires may be operable to cool the cool cavity.

[0047] Implementations of the invention can include one or more of the following features:

[0048] The pump or engine of the above embodiments may further include an insulating material. The insulating material may be silicon dioxide.

[0049] In general, in another aspect, the invention features a pump system that includes an array of pumps. The pumps in that array are pumps of one or more of the above embodiments.

[0050] In general, in another aspect, the invention features an engine system that includes an array of engines. The pumps in that array are engines of one or more of the above embodiments.

[0051] In general, in another aspect, the invention features a method of operating one of the pumps of the above embodiments.

[0052] In general, in another aspect, the invention features a method of operating one of the pump systems of the above embodiments.

[0053] In general, in another aspect, the invention features a method of operating one of the engines of the above embodiments.

[0054] In general, in another aspect, the invention features a method of operating one of the engine systems of the above embodiments.

[0055] In general, in another aspect, the invention features a method that includes opening an upstream valve to allow fluid to flow through the upstream valve to a cavity. The cavity is connected to a downstream valve that is in a closed position. The method further includes closing the upstream valve. The method further includes reducing the volume capacity in the cavity. The method further includes opening the downstream

valve to allow the fluid to flow from the cavity to through the downstream valve while maintaining the upstream valve in the closed position. At least one of the cavity, upstream valve, or downstream valve includes a electrically conductive drum. The electrically conductive drum is atomically thin.

[0056] In general, in another aspect, the invention features a method that includes opening an upstream valve to allow combustible fluid mixture to flow through the upstream valve to a cavity. The cavity is connected to a downstream valve that is in a closed position. The method further includes closing the upstream valve. The method further includes reducing the volume capacity of the cavity. The method further includes igniting the combustible fluid mixture forming a combusted fluid mixture that expands the volume capacity of the cavity. The method further includes opening the downstream valve to allow the fluid to flow from the cavity to through the downstream valve while maintaining the upstream valve in the closed position. At least one of the cavity, upstream valve, or downstream valve includes a electrically conductive drum. The electrically conductive is atomically thin.

[0057] In general, in another aspect, the invention features a method that includes flowing a fluid from a first cavity to a second cavity. The first cavity has a first electrically conductive drum that moves to decrease the volume of the first cavity. The first electrically conductive drum is atomically thin. The second cavity has a second electrically conductive drum that moves to increase the volume of the second cavity. The second electrically conductive drum is atomically thin. The fluid is heated. The method further includes flowing fluid from the second cavity to the first cavity. The first electrically conductive drum moves to increase the volume of the first cavity. The second electrically conductive drum moves to decrease the volume of the second cavity. The fluid is cooled. The method further includes a voltage is applied to a metallic gate. The metallic gate is located by the first electrically conductive drum or the second electrically conductive drum. Energy is generated when that electrically conductive drum (i.e., the first electrically conductive drum or the second electrically conductive drum located by the metallic gate) moves away from the metallic gate.

[0058] Implementations of the invention can include one or more of the following features:

[0059] The electrically conductive drums can be graphene drums.

[0060] In general, in another aspect, the invention features a valve that includes a cavity. The cavity has an electrically conductive membrane and an opening for flowing fluid through the cavity. The electrically conductive membrane is atomically thin. The valve further includes a gate operable to move the electrically conductive membrane between a first position and second position due to a change in voltage applied to the gate. When the electrically conductive membrane is in the first position, the electrically conductive membrane is located away from the opening such that fluid can flow freely through the opening. When the electrically conductive membrane is in the second position, the electrically conductive membrane is located at a predetermined distance from the opening such that fluid flow through the opening is restricted.

[0061] Implementations of the invention can include one or more of the following features:

[0062] The valve can further include an electrical conductor located near the opening. When the electrically conductive membrane is located at or near the second position, the elec-

trical conductor and electrically conductive membrane are operatively connected to allow a current to flow therebetween that is indicative of the location of the electrically conductive membrane.

[0063] The valve may further include a controller operable to control the voltage applied to the gate by utilizing the current to adjust the gate voltage so that the electrically conductive membrane is located at the second position.

[0064] The current may be a tunneling current.

[0065] The valve can further include a resistor and a voltage source that are operatively connected to the electrically conductive membrane and the gate. When the electrically conductive membrane is located near the second position, a current can operatively flow through the resistor that passively lowers the voltage between the electrically conductive membrane and the gate.

[0066] The valve can further include a capacitor sensor. The capacitor sensor is operatively connected to the electrically conductive membrane and the gate such that it may detect a change of capacitance between the electrically conductive membrane and the gate that is indicative of the location of the electrically conductive membrane.

[0067] The valve can further include a controller operable to control the voltage applied to the gate by utilizing the capacitance to adjust the gate voltage so that the electrically conductive membrane is located at the second position.

[0068] The valve can be operable to prevent the electrically conductive member from coming in contact with the gate.

[0069] The valve can further include a non-conductive member located between the electrically conductive membrane and the gate. The non-conductive member can prevent the electrically conductive membrane from coming in contact with the gate.

[0070] The electrically conductive membrane can be located at a distance such that stiffness of the electrically conductive membrane precludes the electrically conductive membrane from deflecting to a degree in which the electrically conductive membrane comes in contact with gate.

[0071] The valve can further include a sensor and stabilizer system operable for preventing the electrically conductive membrane from coming in contact with the gate.

[0072] The electrically conductive membrane may be a graphene membrane.

[0073] The predetermined distance may be about 1 nm.

[0074] The predetermined distance may be about 0.5 nm.

[0075] The predetermined distance may be about 0.3 nm.

[0076] The predetermine distance may be small enough to prevent most molecules of the fluid from flowing through the opening and may be big enough to avoid wear of the valve.

[0077] The predetermined distance may be a range of distances from the opening. The predetermined distance may be a range of distances between about 0.3 nm and about 1 nm. The predetermined distance may be a range of distances of about $0.7 \text{ nm} \pm 50\%$.

[0078] In general, in another aspect, the invention features a method of operating one of the valves of the above embodiments.

[0079] In general, in another aspect, the invention features a pump that includes one of the valves of the above embodiments.

[0080] In general, in another aspect, the invention features a pump of one of the above pump embodiments that includes one of the valves of the above valve embodiments.

[0081] In general, in another aspect, the invention features a method of operating one of the pumps of the above embodiments.

[0082] In general, in another aspect, the invention features a device that includes a pump. The pump includes a cavity having a diaphragm. The diaphragm is operable to change the volume capacity of the cavity. The pump further includes a first valve connected to the cavity. The first valve is operable to be in an open position in which fluid can flow (a) through the first valve into the cavity and (b) from the cavity through the first valve, depending upon the pressure differential across the first valve. The first valve is further operable to be in a closed position in which fluid cannot flow (a) through the first valve into the cavity and (b) from the cavity through the first valve, regardless of the pressure differential across the first valve. The pump further includes a second valve connected to the cavity. The second valve is operable to be in an open position in which fluid can flow (a) through the second valve into the cavity and (b) from the cavity through the second valve, depending upon the pressure differential across the second valve. The second valve is further operable to be in a closed position in which fluid cannot flow (a) through the second valve into the cavity and (b) from the cavity through the second valve, regardless of the pressure differential across the second valve. At least one of the cavity, first valve, or second valve includes an electrically conductive drum. The electrically conductive drum is atomically thin.

[0083] Implementations of the invention can include one or more of the following features:

[0084] The device may be operable as a speaker. The device may be operable as a compact audio speaker.

[0085] The electrically conductive drum may be a graphene drum.

[0086] The graphene drum may be operable for producing an audio signal having a frequency in the audio frequency range. The frequency may be between about 20 Hz and about 20 kHz.

[0087] The graphene drum may be operable for producing an audio signal having a frequency in the audio frequency range by alternating the flow of air through the pump in a first direction and a second direction. The first direction of the air flow may be flowing the air through the first valve, into and through the cavity, and through the second valve. The second direction of the air flow may be flowing air through the second valve, into and through the cavity, and through the first valve. The rate of alternating the flow of air may be the frequency of the audio signal.

[0088] The device may be operable for medical applications.

[0089] The device may be operable for drug delivery.

[0090] The device may be operable as a heart pump.

[0091] The device may be operable for electronic applications.

[0092] The device may be operable as an ink pump.

[0093] The device may be operable as a fan.

[0094] The device may be operable to flow the fluid in a first direction through the first valve, into and through the cavity, and through the second valve, while the device is not operable to flow the fluid in a second direction through the second valve, into and through the cavity, and through the first valve.

[0095] In general, in another aspect, the invention features a method of operating one of the device of the above embodiments.

[0096] There has thus been outlined, rather broadly, the more important features of the invention in order that the detailed description thereof may be better understood, and in order that the present contribution to the art may be better appreciated. There are additional features of the invention that will be described hereinafter.

[0097] In this respect, before explaining at least one embodiment of the invention in detail, it is to be understood that the invention is not limited in its application to the details of construction and to the arrangements of the components set forth in the following description or illustrated in the drawings. The invention is capable of other embodiments and of being practiced and carried out in various ways. Also, it is to be understood that the phraseology and terminology employed herein are for the purpose of the description and should not be regarded as limiting.

DESCRIPTION OF DRAWINGS

[0098] FIG. 1 depicts a perspective view of the graphene-drum pump system.

[0099] FIG. 2 depicts a close-up of a graphene-drum pump (in the graphene-drum pump system of FIG. 1) in exhaust mode.

[0100] FIG. 3 depicts a close-up of a graphene-drum pump (in the graphene-drum pump system of FIG. 1) in intake mode.

[0101] FIG. 4 depicts a graphene-drum internal combustion engine in ignition mode.

[0102] FIG. 5 depicts a perspective view of a graphene-drum Stirling engine system.

[0103] FIG. 6 depicts a side view of the graphene-drum Stirling engine system of FIG. 5.

[0104] FIG. 7 depicts an alternative embodiment of a graphene-drum pump system.

[0105] FIG. 8 depicts the graphene-drum pump system of FIG. 7 with the graphene drum in a different position.

[0106] FIG. 9 depicts a further alternative embodiment of a graphene-drum pump system.

DETAILED DESCRIPTION

[0107] In an embodiment of the present invention, one or more graphene drums can be utilized in a pump system. FIG. 1 depicts a graphene-drum pump system 100 that has an array of graphene-drum pumps 101 (as illustrated there are nine graphene pumps 101 in FIG. 1). As oriented in FIG. 1, the top layer 102 is graphene. The top layer is mounted on an insulating material 103 (such as silicon dioxide).

[0108] FIG. 2 depicts a close-up of a graphene-drum pump 101 in the graphene-drum pump system 100 of FIG. 1. Graphene-drum pump 101 utilizes a graphene drum as the main diaphragm (main diaphragm graphene drum 201). The main diaphragm seals a boundary of the cavity 202 of the graphene-drum pump 101. The cavity is also bounded by insulating material 103 and a metallic gate 203 (which is a metal such as tungsten). The metallic gate 203 is operatively connected to a voltage source (not shown), such as by a metallic trace 204. The main diaphragm graphene drum 201 can be designed to operate in a manner similar to the graphene drums taught and described in the PCT US09/59266 Application.

[0109] The graphene-drum pump also includes an upstream valve 205 and a downstream valve 206. As illustrated in FIG. 2, upstream valve 205 includes another

graphene drum (the upstream valve graphene drum 207). The upstream valve 205 is connected (a) to a fluid source (not shown) by a conduit 208 and (b) to the cavity 202 by conduit 209, which conduits 208 and 209 are operable to allow fluid (such as a gas or a liquid) to flow from the fluid source through the upstream valve 205 and into the cavity 202. The upstream valve 205 also has a cavity 210 bounded (and sealed) by the upstream valve graphene drum 207, the insulating material 103, and upstream valve gate 211. The upstream valve graphene drum 207 can be designed to operate in a manner similar to the graphene drums taught and described in the PCT US09/59266 Application. For instance, the upstream valve 205 can be closed or opened by varying the voltage between upstream valve graphene drum 207 and upstream valve gate 211. When the upstream valve 205 is closed, van der Waals forces will maintain the upstream valve graphene drum 207 in the seated position, which will keep the upstream valve 205 in the closed position.

[0110] As illustrated in FIG. 2, the downstream valve 206 includes another graphene drum (the downstream valve graphene drum 212). The downstream valve 206 is connected (a) to the cavity 202 by a conduit 213 and (b) to a fluid output (not shown) by conduit 214, which conduits 213 and 214 are operable to allow fluid to flow from the cavity 202 through the downstream valve 206 and into the fluid output. The downstream valve 206 also has a cavity 215 bounded (and sealed) by the downstream valve graphene drum 212, the insulating material 103, and downstream valve gate 216. The downstream valve graphene drum 212 can be designed to operate in a manner similar to the graphene drums taught and described in the PCT US09/59266 Application. For instance, the downstream valve 206 can be closed or opened by varying the voltage between downstream valve graphene drum 212 and downstream valve gate 216. When the downstream valve 206 is closed, van der Waals forces will maintain the downstream valve graphene drum 212 in the seated position, which will keep the downstream valve 206 in the closed position. Generally, upstream valve gate 211 and downstream valve gate 216 are synchronized so that when the upstream valve 205 is opened, downstream valve is closed (and vice versa).

[0111] FIG. 2 depicts the graphene-drum pump 101 in exhaust mode. In the exhaust mode, the upstream valve 205 is closed and the downstream valve 206 is opened, while the main diaphragm graphene drum 201 is being pulled downward (such as due to a voltage between the main diaphragm graphene drum 201 and metallic gate 203). This results in the fluid (such as air) being pumped from the cavity 202 through the downstream valve 206 and into the fluid output.

[0112] FIG. 3 depicts the graphene-drum pump 101 in intake mode. In the intake mode, the upstream valve 205 is opened and the downstream valve 206 is closed, while the main diaphragm graphene drum 201 moves upward. (For instance, by reducing the voltage between the main diaphragm graphene drum 201 and metallic gate 203, the graphene drum 201 will spring upward beyond its "relaxed" position). This results in the fluid (such as air) being drawn from the fluid source through the upstream valve 205 and into the cavity 202.

[0113] To reduce or avoid wear of the upstream valve 205 that utilizes an upstream valve graphene drum 207, embodiments of the invention can include an upstream valve element 217 to sense the position between the upstream valve graphene drum 207 and bottom of cavity 210. Likewise to reduce or avoid wear of the downstream valve 206 that uti-

lizes a downstream valve graphene drum **212**, embodiments of the invention can include an downstream valve element **218** to sense the position between the downstream valve graphene drum **212** and bottom of cavity **215**. The reason for this is because of the wear that upstream valve **205** and downstream valve **206** will incur during cyclic operation, which can be on the order of 100 trillion cycles during the device lifetime. Because of such wear, upstream valve graphene drum **207** and downstream valve graphene drum **212** cannot repeatedly hit down upon the channel openings to conduit **209** and conduit **213**, respectively.

[0114] As shown in FIG. 2, upstream valve element **217** is shown in the center/bottom of cavity **210** of the upper valve **205**, and downstream valve element **218** is shown in the center/bottom of cavity **215** of downstream valve **206**. Upstream valve element **217** is used to sense the position of the upstream valve graphene drum **207** relative to the bottom of cavity **210** by using extremely sensitive tunneling currents as feedback. A separate circuit (not shown) is connected between the upstream valve element **217** and the upstream valve graphene drum **207**. Likewise downstream valve element **218** is used to sense the position of the downstream valve graphene drum **207** relative to the bottom of cavity **215** by using extremely sensitive tunneling currents as feedback. A separate circuit (not shown) is connected between the upstream valve element **218** and the upstream valve graphene drum **212**.

[0115] With respect to the upstream valve **205**, when the upstream valve graphene drum **207** is within about 1 nm of the upstream valve element **217**, a significant tunneling current will flow between the upstream valve graphene drum **205** and the upstream valve element **217**. This current can be used as feedback to control the voltage of upstream valve gate **211**. When this current is too high, the gate voltage of upstream valve gate **211** will be decreased. And, when this current is too low, the gate voltage of upstream valve gate **211** will be increased (so that the valve stays in its “closed” position, as shown in FIG. 2, until it is instructed to open). There will likely be a gap (around 0.5 nm) between the upstream valve graphene drum **207** and channel opening to conduit **209** when the upstream valve **205** is closed; this gap is so small that it prevents most fluid molecules from passing through the upstream valve **205** yet the gap is large enough to avoid wear. For instance, in an embodiment of the invention, a resistor and voltage source (not shown) can be utilized. The resistor can be placed between the upstream valve element **217** and the voltage source. When the upstream valve graphene drum **207** comes within tunneling current distance (such as around 0.3 to 1 nanometers) of upstream valve element **217**, the tunneling current will flow through upstream valve graphene drum **207**, upstream valve element **217** and the resistor. This tunneling current in combination with the resistor will lower the voltage between upstream valve element **217** and upstream valve graphene drum **207**, thus lowering the electrostatic force between upstream valve element **217** and upstream valve graphene drum **207**. If upstream valve graphene drum moves away from upstream valve graphene **217**, the tunneling current will drop and the voltage/force between upstream valve graphene drum **207** and upstream valve element **217** will increase. Thus a 0.3 to 1 nanometer gap between upstream valve graphene drum **207** and upstream valve element **217** is maintained passively

which allows the valve to close without causing mechanical wear between upstream valve graphene drum **207** and upstream valve element **217**.

[0116] With respect to downstream valve **206**, downstream valve element **218** can be utilized similarly.

[0117] In further embodiments, while not shown, standard silicon elements (such as transistors) can be integrated within or near the insulating material **103** near the respective graphene drums (main diaphragm graphene drum **201**, upstream valve graphene drum **207**, or downstream valve graphene drum **212**) to help control the respective graphene drum and gate set.

[0118] In further embodiments, in lieu of using tunneling currents as feedback, the feedback can be the change in capacitance between upstream valve graphene drum **207** and upstream valve gate **211**. For instance, a capacitance sensor can be used to detecting the change of capacitance, which would be indicative of the location of the graphene drum.

[0119] Embodiments of the graphene-drum pump system **100** shown in FIG. 1 (and graphene-drum pump **101** shown in FIGS. 2-3) as described above, can be modified to operate as a graphene-drum internal combustion engine system. In such instance, the intake fluids from the fluid source can include a combustible fluid mixture (such as fuel and oxygen from the air). Furthermore, the opening and closing of the upstream valve **205** and the downstream valve **206** are generally designed to operate independently (such that both valves can be closed at the same time).

[0120] The process by which the graphene-drum internal combustion engine system operates can be as follows.

[0121] Intake step: In the intake step, the combustible fluid mixture is placed in the combustion chamber. For example, similar to the pump intake illustrated in FIG. 3, the upstream valve **205** is opened and the downstream valve **206** is closed, while the main diaphragm graphene drum **201** moves upward (such as reducing the voltage between the main diaphragm graphene drum **201** and metallic gate **203**). This results in the combustible fluid mixture being drawn from the fluid source through the upstream valve **205** and into the cavity **202**.

[0122] Compression step: In the compression step, the upstream valve **205** is closed while maintaining the downstream valve **206** in the closed position. The main diaphragm graphene drum **201** is then pulled downward (such as due to a voltage between the main diaphragm graphene drum **201** and metallic gate **203**). This results in compression of the combustible fluid mixture in the cavity **202**.

[0123] Ignition Step: In the ignition step, the combustible fluid mixture is ignited. FIG. 4 depicts a graphene-drum internal combustion engine **400** in the ignition mode. For instance, a metallic trace or via (connected to a voltage source) can provide a high-voltage electrical spark to ignite the combustible fluid mixture in the cavity **202**. FIG. 4 depicts the ignited combustible fluid mixture **401**. This figure also depicts that upstream valve **205** and the downstream valve **206** are generally closed during the ignition step.

[0124] Instead of drawing in just air or some other fluid, the engine system would draw in an air-fuel mixture. Like conventional internal combustion engine, the graphene-drum internal combustion engine can compress the fuel-air mix until it reached ignition (or was set off by a spark between main graphene drum and gate), the hot gas would then expand during the power stroke and then, as discussed below, the exhaust pumped out. Unlike a conventional internal combustion engine, the graphene-drum internal combustion engine

can use the time-varying capacitance between the graphene drum **201** and metallic gate **203** to extract electrical power from system during power stroke. Compressing the fuel-air mixture is accomplished by applying a voltage between graphene drum **201** and metallic gate **203**. This compression voltage can also be used to seed the time-varying capacitance process needed for power extraction. The valves would work in same manner as described for pump above.

[0125] This results in expansion of the combusted fluid mixture, which can then be used to produce useful work. Such expansion generally acts to cool the combusted fluid mixture and vary the capacitance between metallic gate **203** and graphene drum **201**. This time varying capacitance can be used along with external circuitry (not shown) to convert expansion forces into electrical energy.

[0126] Exhaust Step: In the exhaust step, the cooled combusted fluid mixture is exhausted. For example, similar to the pump exhaust illustrated in FIG. 2, the upstream valve **205** is closed and the downstream valve **206** is opened, while the main diaphragm graphene drum **201** is being pulled downward (such as due to a voltage between the main diaphragm graphene drum **201** and metallic gate **203**). This results in the cooled combusted fluid mixture being pumped from the cavity **202** through the downstream valve **206** and into the fluid output. Generally, the cooled combusted fluid mixture will ultimately be exhausted to atmosphere.

[0127] In other embodiments of the present invention, the graphene-drum pump system is a graphene-drum Stirling engine system **501**, such as depicted in FIG. 5. FIG. 6 depicts a side view of the graphene-drum Stirling engine system of FIG. 5. Like a conventional Stirling engine, the graphene-drum Stirling engine would use a temperature differential (as oriented in the FIG. 5-6, top part **501** of device **500** is kept hot, and bottom part **502** of device **500** cold) to drive the “pistons.” Device **500** is sealed with a working gas (air, helium, etc.) that can move back and forth between the hot side **501** and the cool side **502**. Like the graphene-drum internal combustion engine described above, power would be extracted by seeding the gate with a voltage and then extracting power as the graphene membrane pulled away from the gate. A piezoelectric film in contact with the graphene drums might also be used to extract power from the oscillating membranes. The metal **503** in the center of device **500** is a heat exchanger that cools the working gas as it moves from hot side **501** to cool side **502** and heats the working gas as it moves from cool side **502** to hot side **501**. The hair-like structures **504** shown on the bottom of the device **500** can be carbon nanotubes or another kind of thermally conductive nanowire to help keep cool side **502** cool (conventional thermal fins might also be used). Hot side **501** might be in thermal contact with a warm microprocessor to help cool and power the processor. Sunlight could be focused on hot side **501** to generate electrical power at efficiencies that likely exceed photo voltaic cells.

[0128] The primary way to extract power from both internal combustion and Stirling graphene-drum engines is by exploiting the fact that the capacitance between the graphene drum and the gate varies with time. If a voltage is placed between the graphene drum and the gate (just before the graphene drum pulls away from the gate), a current will be generated that is proportional to this seed voltage times dC/dt (the time rate of change of graphene drum-gate capacitance). The energy output is proportional to the force to separate the graphene drum away from the gate times the distance of travel of the graphene drum. Extracting energy from time-varying

capacitors is further described in Miyazaki M., et al., “Electric-Energy Generation Using Variable-Capacitive Resonator for Power-Free LSI: Efficiency Analysis and Fundamental Experiment,” *International Symposium on Low Power Electronics and Design, Proceedings of the 2003 International Symposium on Low Power Electronics and Design*, 193-198 (2003), which is incorporated herein by reference.

[0129] In FIGS. 7-8, an alternate embodiment of the present invention is shown that locates the graphene drum **201** such that the cavity **202** (in FIG. 2) is separated into two sealed cavities. (The change of position of graphene drum **201** is shown in FIGS. 7-8). Per the orientation of FIGS. 7-8, graphene drum **201** seals an upper cavity **701** and a lower cavity **702**. As shown in FIGS. 7-8, upstream valve **205** and the downstream valve **206** are positioned to allow the pumping of fluid in and out of upper cavity **701**.

[0130] As depicted in FIGS. 7-8, lower cavity **702** is oriented between the graphene drum **201** and the gate **203**. Lower cavity **702** can be evacuated to increase the breakdown voltage between the graphene drum **201** and the gate **203**. The maximum force (and thus the maximum graphene drum displacement) between the graphene drum **201** and the gate **203** increases as the square of this voltage. Thus, the pumping speed of the device **700** will increase significantly with an increase in the maximum allowable voltage.

[0131] As noted above, upper cavity **701** can be filled with air or some other gas/fluid that is being pumped. The vacuum in the lower cavity **702** can be created prior to mounting the graphene drum **201** over the main opening and maintained with a chemical getter. Small channels (not shown) between the lower cavities **702** could be routed to an external vacuum pump to create and maintain the vacuum. A set of dedicated graphene drum pumps mounted in the plurality of graphene drum pumps could also be used to create and maintain vacuum in the lower chambers (since pumping volume is so low these dedicated graphene drum pumps could operate with air in their lower chambers).

[0132] Similar to other embodiments shown in this Application, in FIGS. 7-8, graphene drum **201** can act like a giant spring: i.e., once the gate **203** pulls graphene down (as shown in FIG. 7), when released the graphene drum **201** will spring upward (as shown in FIG. 8).

[0133] This same approach can also be used in internal combustion embodiments to increase the power density of the device.

[0134] In FIG. 9, a further alternate embodiment of the present invention is shown. In The graphene-drum pump system **900** shown in FIG. 9 can be actuated without requiring feedback as described above with respect to FIG. 2. In this embodiment, non-conductive member **904** (such as oxide) is placed between the graphene drum **201** and metallic gate **901** so that the graphene drum **201** cannot go into runaway mode and so that graphene drum **201** will not vigorously impact metallic gate **901** when seating. In embodiments of the invention, setting the graphene drum **201** (non-deflected) to metallic gate **901** distance to 20% of the diameter of the graphene drum **201** will prevent runaway (for a maximum deflection that is in the order of 10% of diameter of the graphene drum **201**) and will allow the graphene drum **201** to seat softly on a surface of the non-conductive member **904** (such as oxide) without the need for feedback.

[0135] As shown in FIG. 9, when the graphene drum **201** is an open position, fluid can flow either (a) in inlet/outlet **902**, through cavity **202**, and out outlet/inlet **903** or (b) in outlet/

inlet **903**, through cavity **202**, and out inlet/outlet **902** (due to the pressure differential between inlet/outlet **902** and outlet/inlet **903**).

[0136] As shown in FIG. **9**, the metallic gate **901** and metallic trace **905** have a non-conductive member **904** (such as oxide) between them. A voltage source **907** can be placed between the metallic gate **901** and the metallic trace **905** operatively connected to the graphene drum **201**. The non-conductive member **904** physically prevents the graphene drum **201** and the metallic gate **901** from coming in contact with one another. This would prevent potentially damaging impacts of the graphene drum **201** and metallic gate **901**.

[0137] While not illustrated, in further embodiments of the invention, the graphene-drum pump system can be designed to prevent the graphene drum and metallic gate from coming in contact. For instance, the graphene drum could be located at a distance such that its stiffness precludes the graphene drum from being deflected to the degree necessary for it to come in contact with metallic gate. In such instance, the graphene drum would still need to be located such that it can be in the open position and the closed position. Or, a second and stabilizing system can be included in the embodiment of the invention that is operable for preventing the graphene drum from coming in contact with the gate.

[0138] As noted above, embodiments of the present invention can be used as a pump to displace fluid. This includes the use of present invention in a speaker, such as a compact audio speaker. While the graphene drums in the present invention operate in the MHz range (i.e., at least about 1 MHz), the graphene drums can produce kHz audio signal by displacing air from one side and pushing it out the other (and then reversing the direction of the flow of fluid at the audio frequency). Advantages of utilizing such an approach include: (a) this will provide the ability to make very low and very high pitch sounds with the same and very compact speaker; (b) this will provide the ability to make high volume sounds with a very small/light speaker chip; and (c) this will provide a little graphene speaker that would cool itself with high velocity airflow.

[0139] Furthermore, the present invention can be utilized in other devices and systems to take advantage of the small size and precise fluid flow of the graphene-drum pump. For instance, the small size and precise fluid flow of the graphene-drum pump renders it useful in medical applications (such as drug delivery, miniature heart pumps, etc.) and consumer electronics applications (such as tiny ink pumps, silent fans etc.).

[0140] A number of embodiments of the invention have been described. Nevertheless, it will be understood that various modifications may be made without departing from the spirit and scope of the invention. Accordingly, other embodiments are within the scope of the following claims.

[0141] While embodiments of the invention have been shown and described, modifications thereof can be made by one skilled in the art without departing from the spirit and teachings of the invention. The embodiments described and the examples provided herein are exemplary only, and are not intended to be limiting. Many variations and modifications of the invention disclosed herein are possible and are within the scope of the invention. For example, graphene-drum pumps and engines can be layered or stacked (for instance, vertically) to increase output. Also, the graphene drums can be shapes other than circles such as squares or rectangles (i.e., the use of the term “drums” does not limit the shape). Accord-

ingly, other embodiments are within the scope of the following claims. The scope of protection is not limited by the description set out above, but is only limited by the claims which follow, that scope including all equivalents of the subject matter of the claims.

[0142] The disclosures of all patents, patent applications, and publications cited herein are hereby incorporated herein by reference in their entirety, to the extent that they provide exemplary, procedural, or other details supplementary to those set forth herein

1. A pump comprising:

- (i) a cavity having a diaphragm, wherein the diaphragm is operable to change the volume capacity of the cavity;
- (ii) an upstream valve connected to the cavity, wherein
 - (a) the upstream valve is operable to be in an open position, wherein fluid can flow through the upstream valve into the cavity, and
 - (b) the upstream valve is operable to be in a closed position, wherein fluid cannot flow through the upstream valve into the cavity; and
- (iii) a downstream valve connected to the cavity, wherein
 - (a) the downstream valve is operable to be in an open position, wherein fluid can flow from the cavity through the downstream valve, and
 - (b) the downstream valve is operable to be in a closed position, wherein fluid cannot flow from the cavity through the downstream valve, wherein

at least one of the cavity, upstream valve, or downstream valve comprises an electrically conductive drum, wherein the electrically conductive drum is atomically thin.

2-5. (canceled)

6. The pump of claim **1**, wherein the electrically conductive drum is a graphene drum.

7-8. (canceled)

9. The pump of claim **1**, wherein at least one of the cavity, upstream valve, or downstream valve comprises a multi electrically-conductive-drum stack of at least two electrically conductive drums.

10-13. (canceled)

14. The pump of claim **1**, wherein the cavity comprises a first electrically conductive drum, the upstream valve comprises a second electrically conductive drum, and the downstream valve comprises a third electrically conductive drum.

15. (canceled)

16. The pump of claim **14**, wherein (a) the first electrically conductive drum is a first graphene drum, (b) the second electrically conductive drum is a second graphene drum, and (c) the third electrically conductive drum is a third graphene drum.

17. The pump of claim **1** further comprising a electrically conductive gate, wherein the electrically conductive drum is operable to be pulled toward the electrically conductive gate due to a voltage between the electrically conductive drum and the electrically conductive.

18. (canceled)

19. The pump of claim **1**, wherein the diaphragm is the electrically conductive drum.

20-21. (canceled)

22. The pump of claim **19** further comprising

- (i) a second cavity, wherein
 - (a) the diaphragm is operable to change the volume capacity of the second cavity,

- (b) as the volume capacity of the cavity increases the volume capacity of the second cavity decreases, and
 - (c) as the volume capacity of the cavity decreases the volume capacity of the second cavity increases.
 - (ii) a metallic gate located within the second cavity, wherein the electrically conductive drum is operable to be pulled toward the electrically conductive gate due to a voltage between the electrically conductive drum and the electrically conductive gate.
- 23-46.** (canceled)
- 47.** A valve comprising:
- (i) a cavity having
 - (a) an electrically conductive membrane, and
 - (b) an opening for flowing fluid through the cavity;
 - (ii) a gate operable to move the electrically conductive membrane between a first position and second position due to a change in voltage applied to the gate, wherein
 - (a) when the electrically conductive membrane is in the first position, the electrically conductive membrane is located away from the opening such that fluid can flow freely through the opening, and
 - (b) when the electrically conductive membrane is in the second position, the electrically conductive membrane is located at a predetermined distance from the opening such that fluid flow through the opening is restricted.
- 48.** The valve of claim **47**, further comprising an electrical conductor located near the opening, wherein when the electrically conductive membrane is located at or near the second position, the electrical conductor and electrically conductive membrane are operatively connected to allow a current to flow therebetween that is indicative of the location of the electrically conductive membrane.
- 49.** The valve of claim **48**, further comprising a controller operable to control the voltage applied to the gate by utilizing the current to adjust the gate voltage so that the electrically conductive membrane is located at the second position.
- 50.** The valve of claim **48**, wherein the current is a tunneling current.
- 51.** The valve of claim **48** further comprising a resistor and a voltage source operatively connected to the electrically conductive membrane and the gate, wherein when the electrically conductive membrane is located near the second position, a current can operatively flow through the resistor that passively lowers the voltage between the electrically conductive membrane and the gate.
- 52.** The valve of claim **47** further comprising a capacitor sensor operatively connected to the electrically conductive membrane and the gate such that it may detect a change of capacitance between the electrically conductive membrane and the gate that is indicative of the location of the electrically conductive membrane.
- 53.** (canceled)
- 54.** The valve of claim **47**, wherein the valve is operable to prevent the electrically conductive member from coming in contact with the gate.
- 55-57.** (canceled)
- 58.** The valve of claim **47**, wherein the electrically conductive membrane is a graphene membrane.
- 59.** The valve of claim **47**, wherein the predetermined distance is about 1 nm.
- 60-69.** (canceled)

- 70.** A device that comprises a pump, wherein the pump comprises:
- (i) a cavity having a diaphragm, wherein the diaphragm is operable to change the volume capacity of the cavity;
 - (ii) a first valve connected to the cavity, wherein
 - (a) the first valve is operable to be in an open position, wherein fluid can flow (I) through the first valve into the cavity and (II) from the cavity through the first valve, depending upon the pressure differential across the first valve, and
 - (b) the first valve is operable to be in a closed position, wherein fluid cannot flow (I) through the first valve into the cavity and (II) from the cavity through the first valve, regardless of the pressure differential across the first valve; and
 - (iii) a second valve connected to the cavity, wherein
 - (a) the second valve is operable to be in an open position, wherein fluid can flow (I) through the second valve into the cavity and (II) from the cavity through the second valve, depending upon the pressure differential across the second valve, and
 - (b) the second valve is operable to be in a closed position, wherein fluid cannot flow (I) through the second valve into the cavity and (II) from the cavity through the second valve, regardless of the pressure differential across the second valve; wherein
- at least one of the cavity, first valve, or second valve comprises an electrically conductive drum, wherein the electrically conductive drum is atomically thin.
- 71.** The device of claim **70**, wherein the device is operable as a speaker.
- 72.** The device of claim **71**, wherein the device is operable as a compact audio speaker.
- 73.** The device of claim **70**, wherein the electrically conductive drum is a graphene drum.
- 74.** The device of claim **73**, wherein the graphene drum is operable for producing an audio signal having a frequency in the audio frequency range.
- 75.** (canceled)
- 76.** The device of claim **74**, wherein the graphene drum is operable for producing an audio signal having a frequency in the audio frequency range by alternating the flow of air through the pump in a first direction and a second direction, wherein
- (a) the first direction of the air flow is flowing the air through the first valve, into and through the cavity, and through the second valve,
 - (b) the second direction of the air flow is flowing air through the second valve, into and through the cavity, and through the first valve, and
 - (c) the rate of alternating the flow of air is the frequency of the audio signal.
- 77.** The device of claim **70**, wherein the device is operable for medical applications.
- 78-79.** (canceled)
- 80.** The device of claim **70**, wherein the device is operable for electronic applications.
- 81-84.** (canceled)