



US 20140163761A1

(19) **United States**(12) **Patent Application Publication**
Kuhns et al.(10) **Pub. No.: US 2014/0163761 A1**(43) **Pub. Date: Jun. 12, 2014**(54) **UTILITY MONITORING SYSTEMS AND METHODS OF USE**


(60) Provisional application No. 60/803,323, filed on May 26, 2006.

(71) Applicant: **Board of Regents of the Nevada System of Higher Education, on Behalf of the Desert Research Instit, Reno, NV (US)****Publication Classification**(51) **Int. Cl.**
H02J 4/00 (2006.01)(72) Inventors: **Hampden Kuhns, Reno, NV (US); Peter R. Edwards, Reno, NV (US); George Nikolich, Las Vegas, NV (US); Morien Roberts, Reno, NV (US)**(52) **U.S. Cl.**
CPC **H02J 4/00** (2013.01)
USPC **700/295**(73) Assignee: **Board of Regents of the Nevada System of Higher Education, on Behalf of the Desert Research Instit, Reno, NV (US)**(57) **ABSTRACT**

Various embodiments of the present disclosure provide methods, systems, and devices for monitoring one or more utilities consumed within a monitored area. At least certain disclosed methods include detecting an amount of a first utility consumed by a load associated with a device. An amount of a second utility consumed by a load associated with the device is detected. The identity of the device is determined based on the amount of the first and second utility consumed. In further disclosed methods, a utility monitoring method is disclosed that includes measuring an amount of a utility consumed by a first device at a first time and an amount of a utility consumed by a second device at a second time. The identity of the first device is determined based on the measured consumption of the first and second devices at the first and second time. In certain implementations, the electricity meter uses an effective variance analysis of the conductance waveform on an electrical circuit to identify specific appliances.

(21) Appl. No.: **14/177,039**(22) Filed: **Feb. 10, 2014****Related U.S. Application Data**

(60) Continuation of application No. 13/758,857, filed on Feb. 4, 2013, now abandoned, which is a continuation of application No. 12/982,460, filed on Dec. 30, 2010, now Pat. No. 8,396,821, which is a division of application No. 12/301,962, filed on Nov. 21, 2008, now Pat. No. 7,885,917, filed as application No. PCT/US2006/048134 on Dec. 15, 2006.






FIG. 1




FIG. 2




FIG. 3





FIG. 4

**FIG. 5**




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

UTILITY MONITORING SYSTEMS AND METHODS OF USE

CROSS REFERENCE TO RELATED APPLICATION

[0001] This application is a continuation of U.S. application Ser. No. 13/758,857, filed Feb. 4, 2013, which is a continuation of U.S. application Ser. No. 12/982,460, filed Dec. 30, 2010, which issued as U.S. Pat. No. 8,396,821, which is a divisional of U.S. patent application Ser. No. 12/301,962, filed Nov. 21, 2008, which issued as U.S. Pat. No. 7,885,917, which is the U.S. National Stage of International Application No. PCT/US2006/048134, filed Dec. 15, 2006, which was published in English under PCT Article 21(2), which in turn claims the benefit of U.S. Provisional Patent Application No. 60/803,323, filed May 26, 2006. Each of these applications is incorporated by reference herein in its entirety.

TECHNICAL FIELD

[0002] The present application relates generally to utility monitors and their methods of use. In particular examples, the present application provides a non-intrusive utility monitor which can be used to monitor a plurality of discrete loads.

BACKGROUND

[0003] In most residences and small businesses, utility consumers learn about their utility consumption through a bill delivered once per month. This system has limited ability to promote conservation since the consumer does not have feedback to associate their specific activities to a particular cost. This lack of information can result in a disconnect between the perception of utility costs and their actual costs. The lack of timely and/or specific information can also lead to inefficiencies and poor decision making by individuals. Although gasoline prices are often a top concern for consumers, the average household spends more than twice as much on utilities as on gasoline. In 2003, an average household spent \$2811 on residential utilities, fuels, and public services; while spending \$1333 on gasoline and motor oil.

[0004] Large commercial businesses commonly employ technology for energy and utility management. Typically a building engineer reviews utility consumption data to ensure utilities are consumed in a cost effective manner. This technology has not penetrated the small business and residential market due to the system and installation expense. Moreover, the data provided by typical existing systems is not presented in a way that non-technical users can understand. Existing monitoring systems also typically do not monitor multiple utilities (i.e. natural gas, electric power, and water), or correlate the use of different utilities to one another.

[0005] Many existing electricity monitoring devices attach sensors to each electrical appliance to be monitored. However, attaching sensors and transmitters to numerous appliances in the areas to be monitored can add substantial cost to the system. Such a configuration can also increase the complexity of the system and the difficulty of installing it.

[0006] Some existing systems monitor electric loads at the point of service entry into the areas to be monitored, such as an electrical meter installed by a power company. However, such systems typically only analyze overall electricity use and do not analyze use by individual circuits or appliances.

SUMMARY

[0007] The present disclosure provides apparatus, systems, and methods for monitoring one or more utilities. In a particular embodiment, the present disclosure provides a utility monitoring method that improves on the above mentioned methods that are currently employed. An amount of a first utility consumed by a load associated with a device is detected. An amount of a second utility consumed by a load associated with the same device is detected. The identity of the device is determined based on the amount of the first and second utilities consumed. In a specific example, the first utility is electricity and the second utility is gas. In another example, the first utility is electricity and the second utility is water. In a further example, the first utility is water and the second utility is gas. In particular examples, electricity use is analyzed using a non-intrusive load monitoring algorithm, such as an effective variance analysis of the conductance waveform on an electrical circuit.

[0008] According to a further disclosed utility monitoring method, an amount of a utility consumed by a first device at a first time is measured. An amount of a utility consumed by a second device at a second time is measured. The first device is identified based on the measured consumption of the first and second devices.

[0009] In various disclosed methods, the time of day of the use, the duration of use, or the separation of time between uses are used to help identify the first device. In yet further methods sequence-based heuristics are used to identify which sequence of utility consumption is more probable.

[0010] The present disclosure also provides an energy monitoring system. In a particular embodiment, the energy monitoring system includes an electricity meter and another utility meter, such as a water meter or natural gas meter; a signal processor; and a user interface device or user computer in communication with the electricity meter and the other utility meter. In certain implementations, the electricity meter includes a non-intrusive load monitor algorithm, such as an effective variance analysis of the conductance waveform on an electrical circuit. In specific examples, the electricity meter is in communication with each of a plurality of circuits. In such examples, the system need not include the water meter. Some implementations of the electricity meter include a signal processor.

[0011] In particular implementations that include an electricity meter in communication with each of a plurality of circuits, the electricity meter includes a power line modem or wireless transceiver. In further implementations, the electricity meter has multiple monitoring channels, each channel being in communication with a current transducer or voltage sensor attached to a circuit of a monitored area. In one example, each channel is in communication with a circuit at a circuit box, or fuse box, servicing a monitored area.

[0012] Certain embodiments of the present disclosure include a user interface device. The user interface device is in communication with one or more utility meters. The user interface, in some examples, processes data from the utility meters, such as with a signal processor. In certain implementations, the user interface device includes a user input device and a display. The display may be used to communicate utility consumption information to the user. The user input device may be used by the user to select utility information to view, or to control operation of the utility monitoring system.

[0013] In some embodiments of the disclosed systems, the user's computer is in communication with the utility meters.

The user computer may also be used to process data (such as with a signal processor), display information to the user, or allow the user to control the monitoring system.

[0014] In further embodiments, the user interface device serves as an interface between the utility meters and a user's computer. The user's computer may be used to display utility consumption information and other information to the user. The user's computer may also be used by the user to control the utility monitoring system. In yet further embodiments, the user's computer or remote system may communicate with the user interface using a network protocol, such as TCP/IP.

[0015] In various embodiments, the user's computer or user interface device may be in communication with a remote network, such as with or through the internet. A remote network computer may store data from the utility meters, process such data, and transmit data to the user interface device or user's computer. For example, the remote network computer may contain profiles of various utility loads for comparison against the user's monitored area, such as for load identification or benchmarking. In other embodiments, load profiles are stored on the user's computer, the user interface device, or the signal processor. The remote system may be used to transmit applicable advertisements or offers to the user, in some examples such offers originate from appliance vendors, service organizations, or home improvement companies.

[0016] Additional embodiments provide methods for identifying an electrical device based on the electrical consumption of the device. One such method includes measuring the voltage and current consumed by the appliance at a plurality of times. The conductance of the device is determined at each of the plurality of times. The device is identified based on the change in conductance over time. In some implementations, the device is identified by comparing the change in conductance over time to a reference value. In further implementations the change in conductance over time is analyzed using statistical analysis, such as subjecting the change in conductance over time to a least squares analysis, for example, an analysis of the effective variance of the conductance. In a specific example, the time over which the conductance is measured is at least about one minute. In a further example, the conductance is measured once per voltage cycle.

[0017] The disclosed methods, systems, and apparatus can allow users to receive data regarding utility consumption relatively concurrently with such use. The availability of such data can better aid users in adjusting their utility use. In a particular example, consumption data is converted to an estimate of the environmental impacts of the utility consumption, such as an estimate of greenhouse gas emissions. The present disclosure can also allow utility consumption to be more easily, conveniently, and accurately attributed to various sources of consumption. In particular methods, the present disclosure allows the thermal efficiency of a monitored area to be measured. Such measurements can be used to help guide purchasing or renovation decisions for the monitored area.

[0018] There are additional features and advantages of the subject matter described herein. They will become apparent as this specification proceeds.

[0019] In this regard, it is to be understood that this is a brief summary of varying aspects of the subject matter described herein. The various features described in this section and below for various embodiments may be used in combination or separately. Any particular embodiment need not provide all features noted above, nor solve all problems or address all issues in the prior art noted above.

BRIEF DESCRIPTION OF THE DRAWINGS

[0020] Various embodiments are shown and described in connection with the following drawings in which:

[0021] FIG. 1 is a schematic diagram of a disclosed utility monitoring system.

[0022] FIG. 2 is a schematic diagram of a particular implementation of the utility monitoring system of FIG. 1.

[0023] FIG. 3 is a schematic diagram of an implementation of the utility monitoring system of FIG. 1 capable of monitoring a plurality of individual electrical circuits.

[0024] FIG. 4 is a graph of the average conductance waveforms for four appliances.

[0025] FIG. 5 is a graph of the average conductance waveforms of an air conditioner (2100 W) and a reading lamp (18 W).

[0026] FIG. 6 is a series of graphs showing chi-square calculations of the conductance waveforms of an air conditioner versus the air conditioner plus a reading lamp, and of an air conditioner versus itself.

[0027] FIG. 7 is a graph of chi-square values versus averaging time.

[0028] FIG. 8 is a graph of simulated utility data for an electricity meter, a gas meter, and a water meter illustrating how loads can be identified based on analyzing multiple utilities.

[0029] FIG. 9 is a graph of simulated utility data from an electricity meter and a water meter illustrating how sequence heuristics can be used to identify loads.

[0030] FIG. 10 is a process diagram illustrating how data obtained from water, gas, and electricity meters may be deconvoluted to provide consumption information for specific loads.

[0031] FIG. 11 is a sample user interface screen that may be displayed on a user's computer or the user interface by the utility monitoring system of FIG. 1.

DETAILED DESCRIPTION

[0032] As used herein, the singular forms "a," "an," and "the" refer to one or more than one, unless the context clearly dictates otherwise. As used herein, the term "includes" means "comprises." Unless the context clearly indicates otherwise, the disjunctive "or" includes the conjunctive "and."

Utility Monitoring Systems

[0033] FIG. 1 illustrates, generally, a disclosed utility monitoring system 100. The utility monitoring system 100 includes a utility monitor 110 in communication with various utility meters 120, 130, 140. As used herein, "meter" refers to a device that can track consumption or use of a particular quantity. For example, an electrical meter that tracks electricity consumption can be a meter installed by a power company or another metering device, such as a supplemental electrical meter (not shown) installed in a circuit breaker panel.

[0034] The utility monitor 110 can be, or include, a multiplexer, analog to digital converter, digital signal processor, or power line interface device. In FIG. 1, the utility meters 120, 130, 140 are, respectively, a water meter, an electric meter, and a gas meter. However, the monitoring system 100 need not include all of the meters 120, 130, 140. In particular implementations, the monitoring system 100 includes additional meters, such as, for example, a heating oil meter (not shown). The monitoring system 100 can include additional

monitors or sensors, such as temperature sensors **145** or other ambient sensors (such as humidity, or pressure sensors).

[0035] The utility monitor **110** is in communication with a user interface **150**. The user interface **150** may optionally be in communication with a user computer **160**. The user interface **150** can be connected to the user computer **160** by, for example, USB, serial, parallel, SCSI, RS232, SPI, I2C, Ethernet, wireless protocol, power line communications (such as the Homeplug standard), ZigBee, or PS/2 connections. In some implementations, the user interface **150** is a stand alone component and need not be connected to the user computer **160**. In further implementations, the user interface **150**, or user computer **160**, is in communication with a remote server **170** over a network **180**, such as the internet. In some implementations, the utility monitor **110** is integrated into the user interface **150** or the user computer **160**. In yet further implementations, the utility monitor **110** is omitted and the meters **120**, **130**, **140** communicate directly with the user interface **150** or the user computer **160**. Some embodiments omit the user interface **150**. The utility monitor **110** optionally communicates with utility providers **190**.

[0036] In some configurations, the utility meters **120**, **130**, **140** are directly connected to the user interface **150**, or user computer **160**, such as through a wired connection, including standard communication protocols and adapters such as RS-232, Ethernet, serial, parallel port, SPI, SCSI, I2C, ZigBee, and USB connections. In a particular example, the utility meters **120**, **130**, **140** send signals to the user interface **150** over power lines, such as using a power line modem. In a more particular example, the components of the system **100** communicate using the Homeplug communication standard. In further implementations, the utility meters **120**, **130**, **140** generate wireless signals that are receivable by a receiver (not shown) of the user interface **150** or the user computer **160**. In some implementations, the user computer **160** accesses the user interface **150** through a web browser. For example, the user interface **150** may be assigned an internet protocol (IP) address. In particular examples, the user interface **150** communicates with the user computer **160**, remote system **170**, or network **180** using the TCP/IP protocol.

[0037] In particular embodiments, such as the system **200** illustrated in FIG. 2, the utility monitor **110** is connected to the utility meters **120**, **130**, **140** through respective adapters **182**, **184**, **186**. In particular examples, the adapters **182**, **184**, **186** are designed to facilitate installation of the monitoring system **100**.

[0038] In some aspects, the adapters **182**, **184**, **186** are designed to be installed by a consumer or other end user. In other aspects, one or more of the adapters **182**, **184**, **186** are designed to be installed by a professional, such as an electrician or plumber. The adapters (or sensors) **182**, **184**, **186** may be powered by the local electrical supply (not shown), or may have a portable power supply (not shown), such as a battery. In particular examples, the portable power supply includes a solar cell, which may be used to power the adapter **182**, **184**, **186** or charge its batteries. Suitable adapters **182**, **184**, **186** are the Meter Interface Units (MIUs) available from Archnet of ShenZhen, China. In some implementations, the electrical adapter **184** or electricity meter **130** includes an in line shunt resistor, a current transducer, or a Hall Effect sensor. Suitable Hall Effect sensors are available from GMW Associates of San Carlos, Calif., such as the Sentron CSA-1V.

[0039] In particular implementations, the adapters **182**, **184**, **186**, such as the adapter **182** for the water meter **120**,

include a photo sensor, such as an infrared or optical sensor, that detects rotation of a dial mechanism. In one example, the sensor detects reflection of light off of the dial mechanism.

[0040] A light source, such as an optical or infrared LED, is included, in certain embodiments, to generate a signal to be measured. An integrated light emitting diode and photodiode is available from Honeywell (PN# HOA1180). A marker, such as a piece of more highly light absorbing or reflecting material, may be placed on the dial in order to help track rotation of the dial.

[0041] In further examples, a separate meter, such as a flow meter, is installed in the gas line or water line. A separate meter may also be included on the electrical line, such as a voltage or current meter. In particular implementations, the electrical adapter **184** is installed between an electrical socket and an existing electrical meter, such as an electrical meter installed by a power company. Suitable socket adapters **184** are available from RIOTronics, Inc. of Englewood, Colo. In some implementations, the adapters **182**, **184**, **186** read signals, such as wireless signals, generated by an existing meter, such as a meter installed by a utility company.

[0042] In some implementations, the electrical adapter **184**, or multiple electrical adapters **184**, is connected to one or more individual circuits entering a measurement site. Each circuit may have a separate adapter **184**, such as an electric metering device, or multiple circuits may be individually monitored by a single electrical adapter **184**. In particular examples, the electrical adapter **184** includes a current transducer (not shown) attached to the wires corresponding to each breaker switch in a circuit box. A multi-channel analog to digital voltage sensor (not shown) may be in communication with the current transducer to simultaneously monitor multiple circuits.

[0043] The user interface **150** collects data from utility monitor **110**. In some implementations, the user interface **150** contains a processor and software or firmware for processing the collected data. The data or processed data can be transferred from the user interface **150** to the user computer **160**. In particular examples, the user interface **150** includes a display and user input device. The user can, in some examples, be presented with information or control the system **100** using the user interface device **150**. In some implementations, the user interface is a device running the PALM operating system (available from Palm, Inc., of Sunnyvale, Calif.), Embedded Linux (available from uClinux at www.uclinux.org) or the Windows Mobile (Pocket PC) operating system (available from Microsoft, Inc., of Redmond, Wash.).

[0044] In embodiments where the user interface **150** transfers collected data to the user computer **160**, or the utility meters **120**, **130**, **140** are directly connected to the user computer **160**, suitable data processing software is installed on the user computer **160**. In yet further implementations, the user interface **150**, or user computer **160**, is in communication with the remote server **170**. The remote server **170** processes the collected data and displays summary information, reports, or other information to a user on the user interface **150** or user computer **160**.

[0045] The consumption of a utility by a load, such as the use of an appliance, is associated with the consumption of one or more utilities, such as one or more of water, electricity, gas, propane, coal, hydrogen, and heating oil consumption. In embodiments where electricity adapters **184**, such as current transducers, are mounted on individual breaker switches, the overall system **200** has additional information to associate

with an electrical load. Data from one or more meters **120**, **130**, **140**, adapters **182**, **184**, **186**, or ambient sensors **145** may be used to identify a particular utility load.

[0046] FIG. 3 illustrates another architecture for a utility monitoring system **300**. The monitoring system **300** includes an electricity meter adapter **310** installed at each circuit **318** in a circuit breaker panel **314**. In particular implementations, each adapter **310** monitors multiple individual circuits **318**. The monitoring system **300** also includes a gas meter **320**. The gas meter **320** may be implemented as described in conjunction with systems **100** or **200**. In further embodiments, the gas meter **320** is omitted or additional meters, such as water or heating oil meters, are included in the system **300**.

[0047] The gas meter **320** and electricity adapters **310** are in communication with a controller **330**. The controller **330** includes a multiplexer **332**, an analog to digital converter and digital signal processor **334**, and a power line interface device **336**, such as a power line modem. The controller **330** is in communication with a power line network interface device **340** which, in turn, is in communication with a user computer **350**. Powerline network integrated circuits are available from Intellon (PN#INT5200) of Ocala, Fla.

[0048] In particular examples, the controller **330** is a Blackfin Digital Signal Processor (DSP), available from Analog Devices, Inc., of Norwood, Mass. This particular DSP has built in network connectivity and an SPI interface (serial peripheral interface). In particular implementations, this controller **330** is programmed using DSP++ (Analog Devices, Inc.) or LabView (available from National Instruments, Inc., of Austin, Tex.). The analog to digital converter **334** may be a 16-bit converter connected via the SPI. The multiplexer **332** may, in particular examples, acquire data from up to 32 channels.

Load Identification

[0049] Various types of information contained in the collected data can be used to identify a particular load. For example measurements can be made of: the time the consumption began; the duration of the consumption; the rate of consumption; the total amount of utility consumed during a particular period; the maximum or peak use; the shape and magnitude of the electrical power waveform (such as the 60 Hz waveform); and any changes in the rate of consumption. These measurements can be compared to a library of standard values for different types of loads. The measurements can also be compared to a library of appliances previously observed on the utility signal. As an example of how consumption can be used to identify a load, a toilet flush can be distinguished from a shower based on the duration of the consumption, the total amount of water consumed, and the water flow rate.

[0050] Time of day information can sometimes assist in identifying a load. For example water usage in the middle of the night is more likely to be due to a toilet flush than a shower. Repetitive periodic water usage throughout the day might be due to a sprinkler system whereas repetitive periodic water usage thought the day and night might be due to an ice maker. Even if the consumption patterns are not sufficient to completely identify the loads, they can still be used to help select the most likely candidates. The user can assist the appliance

identification program by linking an unidentified appliance to the name of an appliance that is known have been in operation.

[0051] When the data is electrical data, additional information may be measured and used to identify a load. For example, the shape and size of the 60 Hz conductance waveform (defined as the current divided by the voltage) may be used to help identify the load. Typical resistive appliances, such as incandescent lights and clothes irons, draw current that is in phase with the AC voltage. Appliances with a reactive and resistive load (such as a DC transformer for a stereo amplifier and a motor on a clothes washer) draw current that is out of phase with the voltage. Yet other appliances, such as computers, have switching power supplies that consume power for brief intervals during a voltage cycle. Analysis of the amplitude and temporal variation of the current and power waveforms can help identify specific loads connected to a circuit. The circuit can be characterized by its voltage and current measured at a particular sampling rate, such as 3840 Hz to provide 64 samples per voltage cycle.

[0052] For some loads, the current or voltage may be very stable. For example, certain light bulbs are either on or off. Other loads may operate at discrete values, such as a ceiling fan with 3 speeds. Further types of loads will have a range of settings, such as a power drill having variable speed control. Finally, other loads (such as a refrigerator, TV, or computer) may have more complex combinations of conductance over time.

[0053] Signal processing techniques can be used to disaggregate a bulk signal, such as the total household electrical or water use data, into its component loads based on the unique properties of each load. A library of properties of common loads can be maintained and accessed by the user interface **150**, user computer **160**, or remote system **170**. For example, the library can include properties of appliances from model years that are most likely to be used in the monitored environment.

[0054] When located on the user interface **150** or user computer **160**, this library can be updated periodically, such as through the internet **180** by the remote server **170**. Other programming of the user interface **150**, or software running on the user computer **160**, can also be updated via the internet, such as with improved algorithms, heuristics, and the like. In certain implementations, training or other user provided data is used to update a library that can be shared with other users. With a broad set of load profiles, the systems **100**, **200**, **300** will be able to, in particular examples, automatically identify the loads consuming at least about 90% of the utilities in the monitored area.

[0055] In some aspects, the systems **100**, **200**, **300** use a processing algorithm that employs statistical analysis, such as a least squares fit, to identify individual loads. In a specific example, an effective variance analysis is performed on changes in conductance. Conductance is a useful parameter to characterize the power consumption behavior of an appliance since it is: (1) voltage independent (i.e. an appliance's conductance changes minimally with normal fluctuations in voltage delivered to the circuit) and (2) is additive for the calculation of power (i.e. the conductance on a circuit is the sum of the conductances of all appliances).

[0056] In some examples, the voltage and current waveform is sampled at a sufficient rate such that many data points are collected for each voltage period. When the AC voltage V passes from negative to positive, current I and voltage V data

points are each inserted into the first columns of a two dimensional array. The number of rows in the array is defined by the number of samples taken during a voltage cycle. When the AC voltage V passes from negative to positive again, the current and voltage data are inserted into the next columns of the arrays and so forth. With this data, instantaneous values of the Power P ($I \cdot V$) measured in Watts and Conductance G (I/V) measured in Siemens can be calculated. In particular examples, the average and standard deviation of the rows of the conductance array is calculated on a one second basis.

[0057] The current and voltage waveforms are measured as:

$$I = I_1, I_2, \dots, I_n$$

$$V = V_1, V_2, \dots, V_n$$

[0058] Where n is the number of samples measured during each voltage cycle. Similarly, the conductance of each sample is also calculated:

$$G = \frac{I_1}{V_1}, \frac{I_2}{V_2}, \dots, \frac{I_n}{V_n}$$

[0059] The average and standard deviation of each element of I , V , and G is calculated for each non-transient (non-event) period by averaging over all voltage cycle waveforms over a period for example 1 second. To minimize memory needs for the system, the point-by-point calculations are used to calculate the mean and standard deviations. This is accomplished by tracking the number of measurements, the sum of the sample measurements, and the sum of squares of the sample measurements. The mean is calculated by the equation:

$$\mu_m = \frac{x_m + \sum_{j=1}^{m-1} x_j}{m}$$

[0060] The standard deviation is subsequently calculated using the following equation:

$$\sigma_m = \sqrt{\frac{x_m^2 + \sum_{j=1}^{m-1} x_j^2}{m} - \mu_m^2}$$

[0061] In this case, the variable x is the waveform of conductance over the j^{th} voltage cycle. An example of conductance waveforms for four appliances is shown in FIG. 4. In this example, the data were collected with a 13-bit digital to analog converter with an electrical current sensitivity of 16 mA per bit. The Figure shows substantial variation of the conductance waveforms for the different appliances.

[0062] The states of appliances on a particular circuit are identified by applying an effective variance calculation using all combinations of appliance waveforms known to exist on that particular circuit.

[0063] The effective variance method seeks to find the minimum of the following equation:

$$\chi^2 = \sum_{i=1}^n \frac{\left(G_i - \sum_{k=1}^p a_{i,k} S_k \right)^2}{\sigma_{G_i}^2 + \sum_{k=1}^p \sigma_{a_{i,k}}^2 S_k^2}$$

[0064] Where χ^2 is the cost function to minimize, i is the element within a voltage cycle period, n is the number of elements within one period, k is a particular appliances out of a total of p known appliances within the appliance library, $a_{i,k}$ is the i^{th} element of the conductance array of appliance k , S_k is the binary state of appliance k (1=on, 0=off), and σ is the standard deviation of the i^{th} element of either G or a .

[0065] A transition event is defined to begin when the running χ^2 (comparing the interval from one period to the same sized interval in the next period) exceeds a certain threshold, indicating a change in the operational state of one or more appliances connected to the circuit. The transition event is defined to end when the running χ^2 falls below a predetermined threshold. Typical applications use an interval of 1 second for the running χ^2 calculation. All combinations of S_k are tested to find the minimum χ^2 . If the minimum χ^2 is above a certain threshold, a new device is added to the appliance library.

[0066] For a total of p appliances, there are 2^p different combinations of S . Since devices are generally turned on one at a time, S usually changes only one element at a time and the search for the optimal S can begin with p different combinations of S thereby reducing the number of calculations needed to find S . When looking at power increases, the number of combinations to be analyzed can be further reduced by omitting devices that are already on as possible candidates. Similarly, when looking at power reductions, devices that were not previously on can be omitted in determining possible candidates. In these situations, the number of combinations is less than p .

[0067] For appliances that are continuously variable (i.e. a light with a dimmer), the different states will initially be identified as different appliances. As the user trains the appliance identification algorithm, the algorithm will identify the appliance based on the interpolation of already measured appliance states.

[0068] The disaggregation algorithm is configured, in some embodiments, to identify small loads that are turned on while a much larger load is active. Failure to achieve this separation can cause the load identification techniques to inaccurately group various appliances and produce erroneous results. The following example demonstrates the ability of the effective variance technique to determine the operational state of an 18 W reading lamp while a 2100 W air conditioner is turned on.

[0069] A comparison of the conductance profiles are shown in FIG. 5. The error bars in the chart indicate that the variability of the conductance samples of the combination of both reading lamp plus air conditioner spans the conductance samples of the air conditioner alone.

[0070] A stochastic analysis was performed by simulating waveforms assuming each i^{th} measurement of conductance is normally distributed about its mean. A random number generator was used to add error to each average value to simulate the variation of repeated measurements. The uncertainty of

the average sample value (i.e. the standard error) decreases as the number of samples increases and is defined as the standard deviation divided by the square root of the number of samples. Based on this relationship, the average conductance waveforms for a variety of averaging periods ranging from 0.0167 seconds (one voltage cycle) up to 30 seconds were simulated.

[0071] The χ^2 was calculated for each sample point in the waveforms by comparing one simulation of the air conditioner conductance (i.e. the test set) with another simulation of the air conditioner conductance (“case one”). The standard deviations of each conductance measurement were used in calculating the χ^2 . This calculation was repeated for the conductance waveform of the test set comparing it with the conductance of the air conditioner plus the reading lamp (“case two”).

[0072] The top panel of FIG. 6 shows the χ^2 values calculated for only one voltage cycle. It can be seen that these are indistinguishable, indicating that when averaging for one voltage period (0.0167 seconds), the operational state of the lamp can not be determined when the air conditioner is on. As averaging periods increase the average χ^2 times the number of waveforms sampled increases for case two, whereas the values for case one remain constant.

[0073] FIG. 7 shows a comparison of the average χ^2 values times the number of voltage cycles for a range of averaging periods. The load identification algorithm selects the combination of appliances with the lowest chi-square. This example shows that the operational state of the lamp can be determined while the air conditioning is on after approximately 1 second. This is a substantial improvement in appliance selectivity over existing methods that use only real and reactive power (and occasionally odd number harmonic components) to infer the operational state of appliances. Accordingly, the averaging period can be chosen to provide a desired level of load resolution.

[0074] The disclosed methods can also yield other useful information for power quality assurance such as THD (total harmonic distortion Eq. 4) and PF (power factor Eq. 5) which are useful for electric utilities and more informed users:

$$THD(\%) = 100 * \frac{I_{n=1}}{\sum_{n=2}^{\infty} I_n} \% \quad \text{Eq. 4}$$

$$PF = \frac{\sum_{n=1}^{\infty} V_n * I_n * \cos(\varphi_n - \phi_n)}{\sum_{n=1}^{\infty} V_n * I_n} \quad \text{Eq. 5}$$

where n is the index of the fundamental frequency of the current I and voltage V. The term $(\phi - \varphi)$ is the difference in phase angles between the current and voltage.

[0075] The THD and PF are typically monitored by electric utilities, and large power consumers often face penalties for violating established standards. The disclosed systems can be used to monitor these quantities and determine which loads have a detrimental effect on the power quality. Examples of data processing techniques that can be used or modified for use in electrical load analysis in the disclosed systems and methods are disclosed in Hart, “Nonintrusive Appliance Load Monitoring,” *Proceedings of the IEEE* 80(12), 1870-1891 (December 1992), and U.S. Pat. No. 5,717,325, each of which

is expressly incorporated by reference herein in its entirety (in the case of any inconsistency with the present disclosure, the present disclosure shall control).

[0076] In particular embodiments, the disaggregation algorithm uses time sequence heuristics based on likely or historical load use. Appliances are often used in a particular order. For example, a user’s morning routine may be to take a shower, blow dry their hair, start a coffee maker, and make toast. In one aspect, the time a particular load consumes a utility can be used to help identify the load. For example, the aforementioned activities may typically occur in the morning. Accordingly, when discriminating between two possible loads to assign to a particular source of consumption, the time the load was activated may indicate assigning one load over another. Similarly, a particular sequence of loads may be indicated as more probable than another sequence. For example, “shower”-“hair dryer”-“coffee maker” may be indicated as more likely than “washing machine”-“hair dryer”-“coffee maker”. Both time-based and sequence-based heuristics may be weighted such that heuristics that are more probably true are weighted more heavily than heuristics that are less probable.

[0077] In further embodiments, the disaggregation algorithm uses a combination of data from two or more utilities to identify a load. For example, certain appliances, such as a dishwasher, use multiple utilities. Appliances that use a combination of utilities can thus be distinguished from appliances that use fewer utilities. Analyzing data from multiple utilities can also be used to identify loads, even when the load only consumes one utility.

[0078] For example, FIG. 8 presents simulated utility data simultaneously obtained from a gas meter, an electric meter, and a water meter. During the observed time, the user flushed a toilet, ran a washing machine, and took a bath or a shower. In addition, the user’s furnace was activated.

[0079] Looking at the water trace, area 406 represents the toilet flushing. Areas 416, 418, 420 represent wash and multiple rinse cycles of the washing machine. Area 426 represents the user’s bath or shower. The toilet flush 406 can be distinguished from the shower 426 and washing machine cycles 416, 418, 420 based on the duration of the utility use and the pattern of use. For example, the washing machine pattern 416, 418, 420 may be a standard water use pattern for the particular washing machine model owned by the user. The toilet flush 406 may be identified because it uses a fixed amount of water per flush.

[0080] Areas 430, 432, 434 of the electricity trace represent wash and rinse motor cycles of the washing machine. Again, the areas 430, 432, 434 may be characteristic of the particular washing machine used. The identification of areas 416, 418, 420 and 430, 432, 434 as being due to the washing machine is further confirmed by the relation of water use to electricity use. The washing machine would be expected to use both electricity and water. Furthermore, the water and electricity use show a clear pattern of the washing machine filling with water, followed by activation of the washing machine motor.

[0081] The electricity trace also shows a longer, less intense period of electricity use at area 440. The area 440 may correspond to lighting used during the user’s shower.

[0082] The gas trace shows heater use at areas 450, 452. Areas 450, 452 can be assigned to the heater based on the duration and magnitude of the heater use, as heating likely uses a consistent gas draw rate. Furthermore, areas 450, 452 do not correspond to any electricity or water consumption,

further confirming that the gas use is due to a heater. Gas use area **460** is assigned to a gas hot water heater. This assignment can be based on the degree and duration of gas use, as well as the correlation with hot water use during the user's shower, as confirmed by the electricity use area **440** and the water use area **426**.

[0083] FIG. 9 presents electricity and water traces for simulated utility use. The water trace contains an area **510** associated with a morning shower. An area **520** represents a sink running and an area **530** represents activation of an automatic sprinkler system. The electricity trace exhibits an area **540** associated with the use of a hairdryer and an area **550** representing activation of a toaster.

[0084] The identification of the utility loads can be made based on the time of day of the consumption, the correlation of different utility consumption, and sequence heuristics. For example, the relatively long, steady water consumption of area **510** is closely followed in time by the short, high electricity consumption area **540**. The combination of these two events, as well as the time of day, helps confirm the assignment of these areas to a shower and hair dryer.

[0085] Similarly, without any other information, the area **550** might be difficult to assign to a toaster versus a number of other small wattage appliances. However, the time of day, occurrence after the shower **510**, and before the running of the sink at area **520**, helps establish area **550** as being due to a toaster as part of the user's morning routine. If the time of day indicated that the sun was up, this would indicate that area **550** was unlikely to be a lighting device. In case of conflict, such as the time of day indicating that it was dark outside, the multiple data streams can be compared and the most probable load chosen based on the heuristics most likely to produce the correct result. In case of error, the user can correct the system and help train the system to be more accurate in future predictions. The results can be presented with a particular confidence level to give the user an idea of the likely accuracy of the data.

[0086] For example, in certain implementations, a user can program the user interface **150**, such as by adding or editing library entries or by training the user interface **150** with user input. For example, the systems **100**, **200**, **300** can include a handheld unit, such as a PALM based or Window Mobiles based computer. As an example, during a training session, the handheld unit displays a list of devices within the monitored area and the user indicates if the devices are on or off. In further embodiments, the handheld unit may specifically direct a user to turn a load on or off. With sufficient training, the systems **100**, **200**, **300** can identify when most of the major devices are on and how much of a particular utility each device is consuming. The user can then associate particular loads, behaviors, settings, and activities with specific costs.

[0087] FIG. 10 presents a dataflow diagram of a process **600** of using the disclosed utility monitoring systems, such as the monitoring systems **100**, **200**, **300**. Gas use is measured at a plurality of times at steps **608**, **610**, **612**. Electricity use is measured at a plurality of times at steps **618**, **620**, **622**. Water use is measured at a plurality of times at steps **628**, **630**, **632**. Of course, the gas, electricity, and water use may be continuously monitored, with times **608**, **610**, **612**, **618**, **620**, **622**, **628**, **630**, **632** representing particular data points.

[0088] The acquired data is transmitted to, and stored in, a storage device in process **640**. The storage device may be, for example, the user interface device **150**, the user computer **160**, or the remote server **170**. The data is then processed,

sequentially or in parallel, using various data analysis or disaggregation processes. For example, the rate of utility use, total amount of utility consumed, time of consumption, duration of consumption, and degree of consumption (such as the highest amount of the utility drawn) are analyzed in process **644**. Process **648** analyzes the data using sequence based heuristics, as previously described. Process **652** analyzes the data using correlation based heuristics, as previously described. For example, process **652** may correlate water use to electricity or gas use. Process **656** may apply phase lag heuristics or analysis to the data. The above-described effective variance analysis of the conductance may be applied in process **658**. The processes **644**, **648**, **652**, **656**, **658** may be applied multiple times, such as in an iterative process, in order to disaggregate the acquired data into utility use information for discrete loads in a monitored area.

[0089] A process **660** receives the results of the processes **644**, **648**, **652**, **656**, **658**. In particular implementations, the process **660** applies further heuristics, or hierarchical rules regarding the processes **644**, **648**, **652**, **656**, **658** to select the most likely sources of utility use giving rise to the observed data. In further implementations, the process **660** consults a database **664** of utility loads in order to help identify discrete loads. The process **660** may send data back to one or more of the processes **644**, **648**, **652**, **656**, **658** for additional analysis.

[0090] Once the observed data has been disaggregated into utility consumption from discrete loads, the information may be presented to a user at process **670**. For example, the information may be presented on the user interface **150** or user computer **160**.

Methods of Using Utility Monitoring Systems

[0091] When the disclosed systems include water monitoring, the systems can be used to detect water leaks. For example, the system can be used to locate a leaky faucet, toilet, or sprinkler. In particular implementations, water consumption exceeding a certain duration, or exceeding a certain duration and particular rate, may indicate a leak or similar problem. In some implementations, the system provides a notification to the user, such as an alert when the user accesses the system, an email, page, or telephone call. In further implementations, the system may shut off the water, such as to prevent damage to the monitored area, or may automatically call a service provider. Similar measures may be implemented with other utilities, such as gas or electricity.

[0092] The system can also be in communication with, or otherwise monitored by, a utility company. In such implementations, the system can be used to enforce restrictions, such as watering restrictions. The system can prevent unauthorized use, or restrictions can be enforced, such as by issuing a fine, after data is reviewed by the utility. Similar measures can be implemented for gas or other utilities.

[0093] In certain aspects of the present disclosure, it is undesirable, unnecessary, or overly complicated to identify numerous individual small loads. Accordingly, loads can be grouped into a particular category. For example, rather than measuring the electricity use of multiple incandescent or fluorescent light bulbs, data can be collected or calculated for all such similar loads. Abnormally low or high sub-loads can generate a flag or alarm to indicate to the user that there may be an issue with a particular load category.

[0094] The user computer **160** receives data from the user interface **150** and can present a user with various reports. Such reports may be presented on the user interface **150**, in

particular examples. Such reports may include, for example, utility consumption summaries for a load, load category, or group of loads, such as a circuit. The consumption summary may be for a particular time period, such as a day, week, month, year, or period of years. Consumption over various periods of time can be used to track increased utility consumption over a time period. In further implementations, the user reports are provided to the user computer **160** over the network **180**, such as from the remote server **170**. In some configurations, the user interface device **150** provides the reports to the user, and may be in communication with the network **180** or remote server **170**.

[0095] Consumption for a particular load can be compared, or benchmarked, against standard values. For example, a particular appliance may be associated with a standard data pattern. Comparison of the measured data with the standard data may be used to indicate the condition of the user's appliance, such as whether the appliance needs maintenance or should be replaced. The comparison may be used to help identify the type of maintenance or repair needed. For example, increased fan effort over time may indicate a clogged air filter in a furnace or air conditioning unit.

[0096] In further aspects, the user's consumption data is compared to similar users, such as users in the same zipcode, who have similar loads, or who have similar monitored areas. Such a comparison may allow a user to determine if they are consuming more utilities, or producing more pollution, than other similarly situated users. Such data can enable changes in user behavior, such as consuming less utilities or installing more efficient loads.

[0097] FIG. 11 illustrates an embodiment of a user interface screen **700** that can be displayed on the user interface device **150** or user computer **160**. The screen **700** presents the total cost of consumed utilities **710** and the abatement cost **720** associated with pollution caused by the utility consumption **710** and estimated green house gas emissions **725**. A picture **730** of the monitored area is presented and the consumed utilities **710** are broken down by type, such as lighting **740**, appliances **742**, and gas **744**. The user can get more information on each of these utility subcomponents, such as a detailed report for each associated load, by activating an appropriate link **750**.

[0098] The screen **700** also presents climate control information **760**, including heating costs **762**, cooling costs **764**, the temperature **766** outside the monitored area, and the temperature **768** within the monitored area. The screen **700** also rates the efficiency of the climate control system, such as using a star rating system **770**. A user may choose to see more detailed information regarding each climate control component by selecting an appropriate link **772**.

[0099] In another aspect, the data from the system may be used to benchmark the efficiency of the heating, ventilation, air conditioning, and insulation of a building, collectively referred to as the "thermal efficiency." When configured to measure electric power and natural gas (or heating oil) consumption, the device can attribute specific costs to the HVAC system. Users can benchmark their building's thermal efficiency by calculating a U factor based on the following equations:

$$U_{Heating} = \frac{\text{Heating Energy} + \text{Ventilation Energy}}{\text{Building Area} \cdot (\text{Inside Temperature} - \text{Outside Temperature})}$$

-continued

$$U_{Cooling} = \frac{\text{Cooling Energy} + \text{Ventilation Energy}}{\text{Building Area} \cdot (\text{Outside Temperature} - \text{Inside Temperature})}$$

This feature is useful for comparing the efficiencies of different buildings and deciding how to invest in HVAC and/or insulation upgrades. Such information can affect building purchasing decisions.

[0100] In a further aspect, the consumption for a particular load can be used to help the user determine whether the user should purchase a new appliance. For example, based on use history, as well as projections based on such historical consumption, the projected cost of a new appliance can be calculated and compared to the projected cost of continuing to use the existing appliance. If a significant amount of utility consumption can be avoided, the user may decide to purchase a newer or more efficient appliance. In particular examples, the systems **100**, **200**, **300** are used to determine whether, for example, a gas or electric appliance, such as a water heater, oven, range, clothes drying, or furnace, will be more cost effective.

[0101] The systems **100**, **200**, **300** may also be used to help a user to decide whether to take steps to make the monitored area more energy efficient. In particular examples, the systems **100**, **200**, **300** can estimate the energy savings that may be achieved through various measures, such as the installation of insulation, installation of energy efficient windows, or repair of leaky air ducts.

[0102] The disclosed systems, particularly those linked to a remote server **170**, may be used to present the user with offers from merchants or service technicians. For example, a company may advertise a new, more efficient refrigerator to a user through the system. In particular examples, the user's data is shared with such merchants and technicians so that the advertisements or solicitations are tailored to the user. For example, a user whose data indicates an appliance is in need of repair may receive advertisements from a service technician in the user's area. In particular aspects, the user may choose to subscribe to a service plan and a service technician may automatically be dispatched when the system indicates a load is in need of repair. In particular examples, a user can choose whether to receive such solicitation, or whether to share their data.

[0103] In certain aspects, the systems **100**, **200**, **300** are used to control or set load use based on the user's cost preferences. For example, the system **100** can provide a thermostat setting that will yield a particular monthly energy cost. The user may also be presented with a range of temperature options and their associated costs. The user may manually set or program the thermostat. In further examples, the systems **100**, **200**, **300** are in communication with the thermostat and automatically control the thermostat in accordance with a user's energy or cost preferences.

[0104] In some implementations, the thermostat is capable of variably heating or cooling different sub-areas of a monitored site, such as different rooms in a house or hotel. In one example, a user can manually set different heating or cooling programs for the sub-areas. In another example, the systems **100**, **200**, **300** automatically adjust utility use based on programmed conditions. For example, an absence of utility consumption in a particular room may indicate that it is unoccupied. Accordingly, the systems **100**, **200**, **300** may adjust the heating or cooling to that room to use less energy. If utility

consumption subsequently indicates the room is occupied, the systems **100, 200, 300** appropriately adjust the heating or cooling to the room.

[0105] The systems **100, 200, 300**, in further embodiments, function as a security system. Unexpected patterns of utility consumption can indicate energy siphoning or unauthorized access from or to the monitored area. For example, a user can indicate that he or she is going on vacation so that the system **100, 200, 300** expects minimal energy consumption. In some examples, energy consumption above the minimal level triggers an alarm or notifies law enforcement authorities, or a security company.

[0106] In certain aspects, the present disclosure is used to schedule utility use based on variable rates. For example, a utility may be priced lower at off-peak hours. A user may program the system to activate or change utility consumption based on such rate data. In a particular implementation, the system automatically switches utility consumption, when possible or according to a program, such as a user defined program, to off-peak times.

[0107] Some embodiments of the present disclosure allow a user to monitor, and attempt to mitigate, their utility consumption and its associated environmental consequences. For example, the system may display both the actual utility cost of the user's behavior and the predicted environmental cost of their behavior. For example, the user may be presented with the monetary cost required to abate the environmental damage associated with their utility consumption. Even if the user is not concerned by the cost of their utility consumption, they may wish to mitigate environmental damage. The system may present the user with options to both reduce their utility consumption and ways to reduce the environmental consequences of their actions. In certain situations, a user may wish to pay more for some utilities in order to reduce the environmental consequences of their actions.

[0108] Although the present disclosure generally describes apparatus, systems, and methods for monitoring utility consumption, the present disclosure may also be applied to utility generation. For example, a monitored area may receive supplemental electrical power from solar cells. The systems **100, 200, 300** are, in certain implementations, configured to regulate power drawn from the supplemental source and the main source, such as drawing power from the main source to make up for any shortfall in the amount generated by the supplemental source. In further implementations, the systems **100, 200, 300** measure an amount of power generated by the supplemental source and transferred to a main power grid, as a user may receive payment for such generated power.

[0109] The systems and methods of the present disclosure can provide a number of advantages. One such advantage is that utility consumption information can be immediately provided to a user. Such a configuration can be advantageous compared to other systems which periodically upload data to a remote data collection site for processing. In particular embodiments, presently disclosed systems continuously provide data to a user interface, allowing the user to immediately view current utility consumption data. Because aspects of the present disclosure allow a user to track utility consumption associated with particular loads, such as appliances, the user can make informed decisions about their utility consumption.

[0110] It is to be understood that the above discussion provides a detailed description of various embodiments. The above descriptions will enable those skilled in the art to make many departures from the particular examples described

above to provide apparatuses constructed in accordance with the present disclosure. The embodiments are illustrative, and not intended to limit the scope of the present disclosure. The scope of the present disclosure is rather to be determined by the scope of the claims as issued and equivalents thereto.

We claim:

1. A utility monitoring method comprising:
 - acquiring electricity consumption data from a plurality of circuits;
 - transmitting the electricity consumption data to a user device;
 - applying disaggregation algorithms to the electricity consumption data to identify individual sources of electricity consumption in the electricity consumption data;
 - accessing a local appliance load library;
 - identifying one or more appliances associated with the identified individual sources of electricity consumption based on the application of the disaggregation algorithms and the accessing of the local appliance load library; and
 - displaying electricity consumption data for each of the identified appliances on a display screen in communication with the user device.
2. The utility monitoring method of claim 1, wherein the local appliance load library is maintained at the user device.
3. The utility monitoring method of claim 1, wherein the local appliance load library is maintained at a remote server.
4. The utility monitoring method of claim 1, further comprising:
 - transmitting local appliance data obtained in connection with the identification of the one or more appliances across a computer network to a remote server; and
 - updating a remote appliance load library maintained at the remote server based on the transmitted local appliance data.
5. The utility monitoring method of claim 2, further comprising:
 - accessing a remote appliance load library maintained at a remote server across a computer network and updating the local appliance library maintained at the user device with information contained in the remote appliance load library.
6. The utility monitoring method of claim 3, wherein the remote appliance load library maintained at the remote server is updated based on local consumption data transmitted to the remote server by a plurality of user devices.
7. The utility monitoring method of claim 1, wherein the identification of the one or more appliances associated with the identified individual sources of electricity consumption further comprises performing a training session by receiving user input regarding an operational state of the identified appliances.
8. The utility monitoring method of claim 7, further comprising:
 - transmitting data from the training session across a computer network to a remote server; and
 - updating a remote appliance load library maintained at the remote server based on the transmitted training session data.
9. The utility monitoring method of claim 1, wherein the acquiring and transmitting of the electricity consumption data from the plurality of circuits comprises providing one or more electricity meters in communication with each of the plurality of circuits and transmitting the electricity consumption data

to the user device via one or more power line modems or wireless transceivers associated with the electricity meters.

10. The utility monitoring method of claim **9**, wherein at the one or more electricity meters comprise multiple monitoring channels with each channel being in communication with a current sensor and voltage sensor attached to a circuit of a monitored area.

11. A utility monitoring method comprising:

acquiring electricity consumption data from a plurality of electricity monitors in communication with a plurality of electrical sources in a monitored area;

transmitting the electricity consumption data to a server;

applying disaggregation algorithms to the electricity consumption data to identify individual sources of electricity consumption in the monitored area; and

training the server to recognize the identified individual sources of electricity consumption by receiving user input through a network connected interface regarding an operational state of the identified appliances.

12. The method of claim **11**, wherein the server is remote.

13. The method of claim **11**, wherein the server is local.

14. The utility monitoring method of claim **11**, further comprising displaying electricity consumption data for each of the identified appliances on a display screen of the network connected interface.

15. The utility monitoring method of claim **11**, further comprising:

transmitting local appliance data obtained in connection with the act of training across a computer network to a remote server; and

updating a remote appliance load library maintained at the remote server based on the transmitted local appliance data.

16. The utility monitoring method of claim **13**, wherein the act of identifying one or more appliances comprises accessing a local appliance load library maintained at the server.

17. The utility monitoring method of claim **16**, further comprising accessing a remote appliance load library maintained at a remote server across a computer network and updating the local appliance library with information contained in the remote appliance load library.

18. The utility monitoring method of claim **17**, wherein the remote appliance load library maintained at the remote server is updated based on local appliance data transmitted to the remote server by a plurality of local servers.

* * * * *