



US 20160216045A1

(19) **United States**

(12) **Patent Application Publication**
Chan

(10) **Pub. No.: US 2016/0216045 A1**

(43) **Pub. Date: Jul. 28, 2016**

(54) **FLUID HEAT EXCHANGER AND ENERGY RECYCLING DEVICE**

Publication Classification

(71) Applicant: **HONG KONG MODERN TECHNOLOGY LIMITED**, Hong Kong (CN)

(51) **Int. Cl.**
F28D 21/00 (2006.01)
F28F 13/12 (2006.01)
F28D 7/10 (2006.01)

(72) Inventor: **Sai-Fai Chan**, Kowloon (HK)

(52) **U.S. Cl.**
CPC *F28D 21/0012* (2013.01); *F28D 7/106* (2013.01); *F28F 13/12* (2013.01); *E03C 2001/005* (2013.01)

(73) Assignee: **Hong Kong Modern Technology Limited**, Kowloon (HK)

(21) Appl. No.: **15/024,906**

(57) **ABSTRACT**

(22) PCT Filed: **Sep. 30, 2014**


A heat exchanger (1), an energy recycling system, a fluid distribution manifold and a baffle. The heat exchanger comprising: a first fluid tube (25) through which a first fluid of a first temperature flows; a second fluid tubes (26) through which a second fluid of a second temperature flows; a baffle (22) located in at least one of said tubes for moderating flow of at least one fluid passing therethrough; wherein the heat exchanger (1) is configured for communicating thermal energy between the first fluid and the second fluid.

(86) PCT No.: **PCT/CN2014/088013**

§ 371 (c)(1),
(2) Date: **Mar. 25, 2016**

(30) **Foreign Application Priority Data**

Sep. 30, 2013 (HK) 13111142.9






FIG. 1

FIG. 1A




FIG. 2




FIG. 2A




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13

FIG. 14

FIG. 15




FIG. 16

FIG. 17

FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24

FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 43A




FIG. 44




FIG. 45




FIG. 45A




FIG. 46




FIG. 47




FIG. 48




FIG. 49




FIG. 50




FIG. 51




FIG. 52




FIG. 53




FIG. 54




FIG. 55




FIG. 56







FIG. 57






FIG. 61




FIG. 62




FIG. 63




FIG. 64




FIG. 65




FIG. 66




FIG. 67




FIG. 68




FIG. 69




FIG. 70





FIG. 71




FIG. 72




FIG. 73




FIG. 74




FIG. 75




FIG. 76




FIG. 77




FIG. 78

FLUID HEAT EXCHANGER AND ENERGY RECYCLING DEVICE

FIELD OF INVENTION

[0001] The present invention relates to heat exchanging technology. In particular, the present invention relates to a heat exchanger, an energy recycling system, a fluid distribution manifold and a baffle.

BACKGROUND OF THE INVENTION

[0002] In everyday life, people may use different washing facilities for cleaning and washing. These facilities include, for example, bathroom showers, sinks, washing tanks and the like. However, if the washing facilities use hot water as a washing medium, such wastewater discharged by the facilities still contains a huge amount of heat, thereby resulting in a waste of energy.

[0003] All along, people have tried various methods to recover and utilize the energy lost in vain. For example, U.S. Pat. No. 4,619,311 discloses an “equal volume, contra flow heat exchanger”, which provides a heat exchanger and an energy recovery device for improving heat energy recovery from hot wastewater. As shown in FIGS. 1 and 1A, a heat exchanger 430 includes an inner wastewater pipe 410 made of copper or aluminum with smooth inner walls and an outer pipe 412, the heat exchanger 430 is installed vertically, and the inner wastewater pipe 410 is connected to a drain pipe 429 of a bathtub or sink 460 or the like, so that hot wastewater 432 passes through the inner wastewater pipe 410 from the top down and drains into sewers, cold feed water 426 enters the heat exchanger 430 from a water inlet 417 through a cold water pipe 416 and flows out from a water outlet 419 as preheated water, and the preheated water flows into a water heater 420 through a pipeline 418 to be further heated for application or storage. As shown in FIG. 1A, the cold feed water 426 passes between the inner wastewater pipe 410 and the outer pipe 412 from the bottom up and forms a “cold water jacket” surrounding the inner wastewater pipe 410, and the cold feed water exchanges heat with hot wastewater reversely flowing in the inner wastewater pipe 410. As the inner diameter of the inner wastewater pipe 410 is greater than that of the drain pipe 429, the hot wastewater will not fill the cavity of the whole inner wastewater pipe 410 when passing through the inner wastewater pipe 410, which can be attached to the inner wall of the inner wastewater pipe 410 to form a thin film of the hot wastewater 432 to flow downwards spirally. The preheated water flowing out from the water outlet 419 may simultaneously flow into a mixing valve 434 through a pipeline 427, is mixed into tepid water with hot water from the water heater 420 through a pipeline 444, and flows out from a sprinkler 346 or a water tap 452 for use.

[0004] Although the heat exchanger and the energy recovery device have a simple structure and can reduce the amount of hot water use and heating energy consumption, the problem of low heat recovery efficiency still exists. As the “cold water jacket” 426 exchanges heat with the hot wastewater through a pipe wall of the inner wastewater pipe 410, due to resistance of the pipe wall, most of the cold water may quickly pass through a central portion between the inner wastewater pipe 410 and the outer pipe 412 at a higher speed without being fully heated, and with a laminar flow phenomenon of water flow, the cold water quickly passed through is not fully

mixed with preheated water that has been heated adjacent to the pipe wall of the inner wastewater pipe 410, which causes low recovery efficiency.

[0005] The U.S. Pat. No. 4,619,311 is incorporated into the present invention by reference.

OBJECT OF THE INVENTION

[0006] Accordingly, it is an object of the present invention to overcome or at least partially alleviate at least some of the deficiencies associated with the prior art.

SUMMARY OF THE INVENTION

[0007] Broadly speaking, the present invention has described a fluid heat exchanger and an energy recovery device with high energy recovery efficiency, are simple to install, convenient to use and easy to clean.

[0008] According to a first broad form of the present invention, there is provided a heat exchanger comprising a first fluid tube through which a first fluid of a first temperature flows, a second fluid tube through which a second fluid of a second temperature flows, a baffle located in at least one of said tubes for moderating flow of at least one fluid passing therethrough, wherein the heat exchanger is configured for communicating thermal energy between the first fluid and the second fluid.

[0009] Preferably, the baffle may be configured to exchange thermal energy between the first and second fluid.

[0010] Advantageously, the first tube and second tube may be configured for exchange of thermal energy between the first and second fluid.

[0011] Preferably, the heat exchanger may further comprises a passage between the first fluid tube and the second fluid tube, the passage for receiving fluid leaking from the first fluid tube or the second fluid tube.

[0012] Advantageously, the baffle may be configured for moderating the flow of fluid through at least one of the fluid tubes, according to any one or more of the following configurations: at least one elongate member extending in a direction of radially or along at least one of the fluid tubes; at least one protrusion extending radially from a wall of at least one of the fluid tubes, wherein the protrusion is integrally formed or detachably mounted on the wall; at least one protrusion extending in a direction of along a wall of at least one of the fluid tubes, the protrusion being integrally formed or detachably mounted on the wall; at least one spiral guiding structure extending along at least one of the fluid tubes; and at least one sleeve extending along at least one of the tubes.

[0013] Preferably, the baffle may comprises at least one elongate member extending in a spiral arrangement, wherein the at least one elongate member extends in the direction of around or about at least one of the fluid tubes, or along the direction of the longitudinal axis of at least one of the fluid tubes.

[0014] Preferably, the baffle may comprises at least one elongate member, formed in one or more spiral elements which extend around the inner circumference of the fluid tubes or along the longitudinal axis of the fluid tubes for moderating the flow of fluid through at least one of the fluid tubes, and wherein the at least one elongate member extends in the direction of around or about at least one of the fluid tubes, or extends along the direction of the longitudinal axis of at least one of the fluid tubes.

[0015] Preferably, the at least one elongate member may extend about a core in an interengaged spiral arrangement, in a longitudinal direction along at least one of the fluid tubes.

[0016] Preferably, the baffle may comprises at least one elongate member extending in a direction of around or about at least one of the fluid tubes, or along the direction of the longitudinal axis of at least one of the fluid tubes, and said at least one elongate member includes annular or spiral protrusions thereon.

[0017] Preferably, the baffle may includes at least one protrusion extending radially from a wall of at least one of the fluid tubes and wherein the at least one protrusion extends in a annular or spiral arrangement.

[0018] Preferably, the protrusions may extend in an annular or spiral arrangement along, about or within either or both of the fluid tubes.

[0019] Preferably, the protrusions may extend in a spiral arrangement include a plurality of spaces therebetween, the spaces being substantially aligned to create a turbulent flow with the spiral flow.

[0020] Advantageously, the heat exchanger may further comprises a plurality of elongate members having circumferential helical grooves formed therein, and both the elongate members and the grooves extend in a direction of along at least one of the fluid tubes.

[0021] Preferably, the baffle may includes at least one spiral guiding structure extending along at least one of the fluid tubes, the spiral guiding structure formed by a plurality of members together define a spiral flow path.

[0022] Preferably, the spiral guiding structure may include a plurality of elements formed therein substantially aligned to create a turbulent flow with the spiral flow path.

[0023] Preferably, the baffle may includes a sleeve which extends along at least one of the fluid tubes.

[0024] Preferably, the sleeve may extend along, about or within either or both of the fluid tubes and includes a plurality of holes therein.

[0025] Preferably, the sleeve may extend in interengaged spiral arrangements with a plurality of elongate members.

[0026] Preferably, the baffle may include at least a first and a further layer of elongate members, each of the layers comprising a plurality of elongate members each extending in a common direction, the common direction of the elongate members of the first layer being different from the common direction of the elongate members of the further layer **20**. A heat exchanger according to claim **19**, wherein the elongate members of the first layer are configured so as to be in thermal communication with the wall of at least one of the fluid tubes.

[0027] Advantageously, the baffle may include a sleeve, extending along at least one of the fluid tubes and located between the first layer and the further layer.

[0028] Advantageously, the sleeve may include a plurality of holes therein.

[0029] Advantageously, at least one fluid tube may include a plurality of elongate members wrapped about a common longitudinal axis and along the at least one fluid tube, wherein the fluid tube has generally elliptical cross sectional profile formed by compression of a fluid tube having a generally circular cross sectional profile.

[0030] Advantageously, the baffle may include at least one disc disposed within at least one of the tubes and wherein the disc includes protrusions thereon which define a plurality of flow paths.

[0031] Advantageously, at least one of the fluid tubes of the heat exchanger may be configured for receiving a cleaning tube through an opening formed therein, the cleaning tube directing a fluid stream for displacing deposits formed within the heat exchanger.

[0032] Advantageously, a fluid distribution manifold may have at least one protrusion which is located proximate the inlet of at least one fluid tube of a corresponding heat exchanger, wherein the fluid distribution manifold further includes a vent therein.

[0033] Advantageously, the manifold may distribute fluid into fluid tubes of the heat exchanger via at least one or more passageways defined by the protrusion and manifold, wherein the vent is in communication with at least one of the protrusions.

[0034] Optionally, the air flow to the fluid may be spaced tube apart from the fluid flow by the vent.

[0035] Optionally, the protrusions of the manifold may be spaced apart from the inlet of at least one or more of the fluid tubes so as to direct the flow of air and fluid into the fluid tubes.

[0036] Optionally, the protrusions of the manifold may contact at least a portion of the inlet of at least one or more of the fluid tubes.

[0037] According to a second broad form of the present invention, there is provided an energy recycling system including a heat exchanger and a fluid distribution manifold.

[0038] Preferably, the baffle may be according to any baffle in the embodiment of the heat exchanger above.

[0039] According to a third broad form of the present invention, there is provided a kit for a heat exchanger including a first fluid tube through which a first fluid of a first temperature flows, a second fluid tube through which a second fluid of a second temperature flows, and a baffle for moderating the flow of fluid through at least one of the fluid tubes according to any embodiment of the heat exchanger above.

[0040] According to a fourth broad form of the present invention, there is provided a kit for a heat exchanger according to any embodiment above, and further including a cleaning tube according to any embodiment above, and/or a fluid distribution manifold according to any embodiment above.

[0041] In a further aspect of an embodiment of the present invention, there may be provided a kit for a heat exchanger including a first fluid tube through which a first fluid of a first temperature flows, a second fluid tube through which a second fluid of a second temperature flows, and a baffle for providing resistance to the flow of fluid through at least one of the fluid tubes according to the above.

[0042] In a further embodiment of the present invention there is provided a fluid heat exchanger, including: a first fluid collector having an opening, a cavity and a plurality of first fluid outlets, where the opening covers all the first fluid outlets, for introducing a first fluid into the cavity, and then exporting the first fluid out of the first fluid outlets in parallel; a housing having a second fluid inlet, a second fluid outlet and a second fluid cavity between the second fluid inlet and the second fluid outlet; and a plurality of metal pipes each placed in the second fluid cavity, and forming a plurality of first fluid channels through the second fluid cavity and the housing for the first fluid to pass through in parallel, the first fluid channels separately communicate with the first fluid outlets of the first fluid collector to receive the first fluid exported from the first fluid outlets, where the second fluid inlet is used for

introducing a second fluid with a temperature different from that of the first fluid, which flows through the second fluid cavity, and exchanges heat with the first fluid passing through in parallel within the first fluid channels by means of the plurality of metal pipes to change the temperature of the second fluid and then exported from the second fluid outlet.

[0043] In a further embodiment of the present invention there is provided an energy recovery device, which includes the heat exchanger described above and an external means for changing the temperature of the second fluid discharged from the second fluid outlet to an appropriate temperature of use and making the second fluid serve as the first fluid entered the opening of the first fluid collector of the heat exchanger after use.

[0044] The heat exchanger, the energy recovery device and the energy recovery system according to the present invention can efficiently recover energy in fluids, are simple to install, convenient to use and easy to clean, which are suitable for use in showers or sinks or other facilities.

[0045] According to an illustrative embodiment of the present disclosure, a thermal conductive baffle disposed in a fluid channel, wherein the fluid channel is an annular channel formed by internal and external tubular surfaces mutually nested, at least one part of the two tubular surfaces is formed by metal, the baffle clings to the two tubular surfaces and maintains good thermal contact with the metal part of the tubular surfaces, fluids passing through the annular channel exchange heat with substances outside the annular channel by means of the baffle and the metal part of the tubular surfaces, the baffle is formed by one or more metal strips having protruding solid structures, and the centerline of the metal strip is configured to surround the internal tubular surface.

[0046] Optionally, a plurality of annular projections is spaced apart along a length direction of a surface of the metal strip.

[0047] Optionally, the metal strip is spiral spring-like.

[0048] Optionally, a spiral center of the spiral spring-like metal strip has another metal strip.

[0049] Optionally, the metal strip is formed by intertwining of a plurality of metal wires.

[0050] Optionally, the metal strip is a spiral strip having a non-circular cross-section.

[0051] Optionally, the centerline of the metal strip is parallel to the centerline of the internal tubular surface.

[0052] Optionally, the centerline of the metal strip spirally extends around the centerline of the internal tubular surface.

[0053] Optionally, the centerline of the metal strip vertically surrounds the centerline of the internal tubular surface.

[0054] According to another illustrative embodiment of the present disclosure, a baffle having a thermal conductive baffle disposed in a fluid channel, wherein the fluid channel is an annular channel formed by internal and external tubular surfaces mutually nested, at least one part of the two tubular surfaces is formed by metal, the baffle clings to the two tubular surfaces and maintains good thermal contact with the metal part of the tubular surfaces, fluids passing through the annular channel exchange heat with substances outside the annular channel by means of the baffle and the metal part of the tubular surfaces, the baffle comprises a barrel structure made of metal sheets and having a plurality of spiral pits on a surface, and the pits form, in the annular channel, a plurality of spiral channels surrounding the internal tubular surface to allow the fluids to pass in parallel.

[0055] Optionally, the spiral channels leave a straight-through channel therebetween to allow part of the fluids to directly pass through adjacent spiral channels, to increase turbulence effects.

[0056] According to another illustrative embodiment of the present disclosure, a baffle having a thermal conductive baffle disposed in a fluid channel, wherein the fluid channel is an annular channel formed by internal and external tubular surfaces mutually nested, at least one part of the two tubular surfaces is formed by metal, the baffle clings to the two tubular surfaces and maintains good thermal contact with the metal part of the tubular surfaces, fluids passing through the annular channel exchange heat with substances outside the annular channel by means of the baffle and the metal part of the tubular surfaces, and the baffle comprises two layers of metal wires surrounding the internal tubular surface, wherein each layer of metal wires comprises a plurality of metal wire sections with gaps therebetween and arranged in parallel, and at least part of the wire sections in the two layers of metal wires are not parallel to each other.

[0057] According to another illustrative embodiment of the present disclosure, a baffle having a thermal conductive baffle disposed in a fluid channel, wherein the fluid channel is an annular channel formed by internal and external tubular surfaces mutually nested, at least one part of the two tubular surfaces is formed by metal, the baffle clings to the two tubular surfaces and maintains good thermal contact with the metal part of the tubular surfaces, fluids passing through the annular channel exchange heat with substances outside the annular channel by means of the baffle and the metal part of the tubular surfaces, the baffle is formed by a plurality of sheet-like objects superposed in the fluid channel with gaps, the plurality of sheet-like objects each has an opening that allows the fluids to pass, at least one part of the sheet-like objects are spoilers, whose opening is configured such that the fluids passing through the fluid channel need to circuitously pass between the spoilers, and at least one part of the sheet-like object is made of metal and thermally contacts the metal part of the tubular surfaces.

[0058] Optionally, openings of any two closest spoilers do not overlap each other in a main surface direction and are separately adjacent to the internal and external tubular surfaces forming the annular channel.

[0059] According to another illustrative embodiment of the present disclosure, a baffle having a thermal conductive baffle disposed in a fluid channel, wherein the fluid channel is an annular channel formed by internal and external tubular surfaces mutually nested, at least one part of the two tubular surfaces is formed by metal, the baffle clings to the two tubular surfaces and maintains good thermal contact with the metal part of the tubular surfaces, fluids passing through the annular channel exchange heat with substances outside the annular channel by means of the baffle and the metal part of the tubular surfaces, the baffle has a barrel structure made of metal to partition the annular channel into internal and external annular channels mutually nested, and solid baffle structures are formed in the two annular channels separately, and separately thermally contact the barrel structure and the metal part of the two tubular surfaces.

[0060] Optionally, the solid baffle structures form, in the annular channels, a plurality of spiral channels that allows the fluids to pass in parallel.

[0061] Optionally, a straight-through channel is disposed between the spiral channels to allow part of the fluids to pass

through adjacent spiral channels by means of the straight-through channel, to increase turbulence effects.

[0062] Optionally, the barrel structure is porous.

[0063] Optionally, the internal and external annular channels have the baffle according to the present invention.

[0064] According to another illustrative embodiment of the present disclosure, a baffle having a thermal conductive baffle disposed in a fluid channel, wherein the fluid channel is formed between two parallel sheet-like objects and a plurality of metal pipes passing through the two sheet-like objects, the two sheet-like objects tightly nest the plurality of metal pipes, the baffle comprises a plurality of first metal wires parallel to each other and a plurality of second metal wires parallel to each other, which are superposed not in parallel to each other to form a metal net, the metal net has a plurality of through holes corresponding to the plurality of metal pipes so as to tightly nest and thermally contact the plurality of metal pipes, and fluids passing through the fluid channel pass through gaps between the two layers of metal wires and the plurality of metal pipes in disorder and exchange heat with substances in the plurality of metal pipes by means of the net-like baffle and the plurality of metal pipes.

[0065] According to another illustrative embodiment of the present disclosure, a baffle having a thermal conductive baffle disposed in a fluid channel, wherein the fluid channel is formed jointly by an inner wall of a pipeline and outer walls of a plurality of metal pipes disposed in the pipeline and parallel to the centerline of the pipeline, the baffle is formed by parallel superposition of a plurality of sheet-like objects whose surface is provided with a plurality of grooves, the sheet-like objects have a plurality of through holes corresponding to the plurality of metal pipes so as to tightly nest the plurality of metal pipes, grooves on surfaces of two adjacent sheet-like objects are not parallel to each other, the plurality of sheet-like objects each has an opening that allows fluids to pass, at least one part of the sheet-like objects are spoilers, configured such that openings of any two closest spoilers do not overlap each other in a main surface direction, so that the fluids passing through the fluid channel need to circuitously pass between the spoilers, at least one part of the sheet-like objects is made of metal and thermally contacts the plurality of metal pipes, and the fluids pass between the grooves in disorder when passing through the fluid channel, and exchange heat with substances in the metal pipes by means of the metallic sheet-like object and the plurality of metal pipes in thermal contact therewith.

[0066] According to another illustrative embodiment of the present disclosure, a baffle having a thermal conductive baffle disposed in a fluid channel, wherein the fluid channel is formed jointly by an inner wall of a pipeline and outer walls of a plurality of metal pipes disposed in the pipeline and parallel to the centerline of the pipeline, the baffle is formed by superposition of a plurality of net-like spoilers, each of the net-like spoilers comprises a plurality of first metal wires parallel to each other and a plurality of second metal wires parallel to each other, the first metal wires and the second metal wires are not in parallel to each other and the first metal wires are superposed on the second metal wires, and each of the net-like spoilers has a plurality of through holes corresponding to the metal pipes so as to nest and thermally contact the metal pipes, and fluids pass between the first and second metal wires in turbulence, and exchange heat with substances in the metal pipes by means of the baffle and the metal pipes.

[0067] Optionally, the net-like spoilers are constructed to form rings having substantially the same width with the through holes as centers, the rings are connected with each other, and except the part of rings, other parts of the net-like spoilers form gaps.

[0068] Optionally, the net-like spoilers are constructed to form rings having substantially the same width with the through holes as centers, the rings are connected with each other, and except the part of rings, the first metal wires and the second metal wires in other parts of the net-like spoilers are flattened to close meshes therebetween.

[0069] According to another illustrative embodiment of the present disclosure, a thermal conductive baffle disposed in a fluid channel, wherein the fluid channel has two parallel surfaces, at least one part of the two parallel surfaces is made of metal, the baffle is formed by at least two layers of non-parallel metal wires, which separately form two parallel surfaces of the fluid channel through contact and thermally contact the metal part, and fluids passing through the fluid channel pass between the metal wires, and exchange heat with substances outside the channel through the metal wires and the metal part forming the channel.

[0070] Optionally, each layer of metal wires comprises a plurality of metal wire sections parallel to each other.

[0071] Optionally, part of metal wire sections of at least two layers of metal wires of the multiple layers of metal wires are formed by the same metal wire and are connected through at least one bend.

[0072] Optionally, the baffle is formed through the following process: a. disposing one or more spiral spring-like metal wires in a circular metal pipe with gaps; and b. flattening the circular metal pipe to form two parallel surfaces, and making the two parallel surfaces press against the plurality of metal wires.

[0073] Optionally, the baffle comprises four layers of metal wires.

[0074] Optionally, the baffle is formed through the following process: a. curling a metal net formed by two layers of non-parallel metal wires into a cylindrical shape to be placed in a circular metal pipe; and b. flattening the circular metal pipe to form two parallel surfaces, and making the two parallel surfaces press against the layers of metal wires forming the net-like cylinder.

[0075] According to another illustrative embodiment of the present disclosure, a fluid heat exchanger, comprising: a metal pipe, in which a first fluid channel that allows a first fluid to pass is formed; and a second fluid channel surrounding the metal pipe, wherein a metal protruding spiral baffle structure in good thermal contact with the metal pipe is formed on an inner wall of the metal pipe; in use, the metal pipe is basically arranged vertically, and the first fluid passing therein does not fill a cavity of the metal pipe, is attached to the inner wall of the metal pipe, is spirally downward along the baffle structure, and exchanges heat with a second fluid passing from the bottom up in the second fluid channel through the metal pipe and the protruding metal spiral structure.

[0076] Optionally, the spiral baffle structure has a plurality of open ends.

[0077] Optionally, open ends of the spiral baffle structure are covered or form a slope to reduce accumulation of fouling at the open ends.

[0078] Optionally, the second fluid channel is an annular channel jointly formed by an inner wall of a second fluid pipeline and an outer wall of a metal pipe disposed in the second fluid pipeline.

[0079] Optionally, the annular channel has a metal baffle thermally contacting the metal pipe, and a second fluid passing through the annular channel exchanges heat with the first fluid passing through the metal pipe through the baffle and the metal pipe in thermal contact therewith.

[0080] Optionally, the annular channel has the baffle according to the present invention.

[0081] Optionally, the second fluid channel is formed by one or more flat metal pipes having two parallel surfaces, the flat metal pipe spirally and tightly nests the metal pipe, and one of the parallel surfaces clings to an outer wall of the metal pipe.

[0082] Optionally, the flat metal pipe has the baffle according to the present invention.

[0083] According to another illustrative embodiment of the present disclosure, a fluid heat exchanger, comprising: a first fluid collector having an opening, a cavity and a plurality of first fluid outlets, wherein the opening covers all the first fluid outlets, and a first fluid is collected and introduced to the cavity, and then is exported out of the first fluid outlets in parallel; a housing having a second fluid inlet, a second fluid outlet and a second fluid cavity between the second fluid inlet and the second fluid outlet; and a plurality of metal pipes each placed in the second fluid cavity, and forming a plurality of first fluid channels passing through the second fluid cavity and the housing to allow the first fluid to pass in parallel, the first fluid channels separately communicating with the first fluid outlets of the first fluid collector to receive the first fluid exported from the first fluid outlets, wherein the second fluid cavity has a metal baffle thermally contacting the plurality of metal pipes; and the second fluid inlet is used for introducing a second fluid whose temperature is different from that of the first fluid, which passes through the second fluid cavity, and exchanges heat with the first fluid passing in parallel in the first fluid channels by means of the plurality of metal pipes and the metal baffle, so that the temperature of the second fluid is changed and then the second fluid is exported from the second fluid outlet.

[0084] Optionally, the opening of the first fluid collector is used for introducing the first fluid into the cavity of the first fluid collector.

[0085] Optionally, the metal pipes are formed by mutual nesting of internal and external metal pipes, the internal and external metal pipes maintain good thermal contact therebetween and are provided with a micro-channel that allows the first or second fluid to pass when the internal or external metal pipe breaks.

[0086] Optionally, the micro-channel is communicated to the outlet above the plurality of metal pipes.

[0087] Optionally, the flow divider comprises a plurality of baffles for evenly introducing the first fluid into the plurality of first fluid channels.

[0088] Optionally, the flow divider is detachably installed to the opening of the first fluid collector.

[0089] Optionally, the first fluid is a liquid, the baffles are disposed adjacent to the first fluid outlet and are provided with through holes, and each through hole communicates with an air vent disposed in a higher position.

[0090] Optionally, the through hole is communicated to the air vent through a vent pipe and the collector is further provided with a filtration device which has a through hole nested to the vent pipe.

[0091] Optionally, the baffles are spiral members disposed in the first fluid channel, which facilitate the first fluid to spirally pass in the first fluid channel.

[0092] Optionally, the baffles are detachable.

[0093] Optionally, inner walls of the metal pipes are provided with spiral protruding metal baffle structures in thermal contact with the metal pipes.

[0094] Optionally, upstream open ends of the spiral baffle structure are covered or form a slope to reduce accumulation of fouling at the open ends.

[0095] Optionally, a plurality of second fluid annular channels separately surrounding each metal pipe to allow the second fluid to pass in parallel is formed in the second fluid cavity and the second fluid channel has the metal baffle according to the present invention, which thermally contacts the metal pipes.

[0096] Optionally, the second fluid cavity has a baffle formed by parallel superposition of a plurality of sheet-like objects with gaps, each of the sheet-like objects has a plurality of through holes corresponding to the metal pipes so as to nest the metal pipes, at least one part of the sheet-like objects is made of metal and thermally contacts the metal pipes, at least one part of the sheet-like objects are spoilers, on which an opening that allows the second fluid to pass is formed, and openings of any two closest spoilers do not overlap each other in a main surface direction of the spoilers, to facilitate the second fluid to circuitously pass between the spoilers in the second fluid cavity, and to exchange heat with the first fluid in the metal pipes by means of the baffle and the metal pipes.

[0097] Optionally, the sheet-like objects have the baffle according to the present invention therebetween, which thermally contacts the plurality of metal pipes.

[0098] Optionally, the second fluid cavity has the baffle according to the present invention.

[0099] Optionally, the first fluid is a liquid, and centerlines of the plurality of metal pipes are basically arranged horizontally.

[0100] Optionally, a section of an inner wall of the metal pipes is flat and has a major axis and a minor axis, and the major axis is basically arranged horizontally.

[0101] Optionally, the inner wall of the metal pipes has two parallel surfaces and the two parallel surfaces have the baffle according to the present invention therebetween.

[0102] Optionally, a vertical height of the inner wall of the metal pipes is not more than 6.5 mm.

[0103] According to another illustrative embodiment of the present disclosure, an energy recovery device, comprising: the heat exchanger according to the present invention; and an external temperature-varying apparatus, wherein the second fluid after heat exchange in the heat exchanger is introduced into the external temperature-varying apparatus, the temperature of the second fluid is changed to a suitable operating temperature, and the second fluid, after use, serves as the first fluid introduced into the heat exchanger.

[0104] Optionally, the external temperature-varying apparatus comprises a heater or a cooler.

[0105] Optionally, the external temperature-varying apparatus comprises a fluid mixer mixing the second fluid after heat exchange with an external preheated or precooled third fluid to change the temperature.

[0106] Optionally, the first fluid is wastewater, and the second fluid is clean water.

[0107] Optionally, the heat exchanger is installed to the bottom of a bathtub or a sink of a washing facility or a base of a shower, or is integrally formed with the base of the shower or the sink, to receive hot wastewater generated in shower or washing.

[0108] Optionally, a drain hole of the bathtub, the sink of the washing facility, or the shower covers all first fluid outlets in a horizontal direction.

BRIEF DESCRIPTION OF THE DRAWINGS

[0109] The basic structure of the present invention is illustrated below with reference to the accompanying drawings, where:

[0110] FIG. 1 is a schematic structural view of an equal volume, contraflow heat exchanger and an energy recovery device in the prior art;

[0111] FIG. 1A is a sectional view along Line 1A-1A in FIG. 1, illustrating a cross-sectional structure of the heat exchanger in the prior art;

[0112] FIG. 2 is an exploded perspective view of a first embodiment of a fluid heat exchanger according to the present invention, illustrating a schematic structural view of a first embodiment of a baffle according to the present invention;

[0113] FIG. 2A is a schematic view showing that a protruding spiral structure in a wastewater channel covered by a ring according to a first embodiment of the present invention;

[0114] FIG. 3 is a sectional perspective view of the main body of the fluid heat exchanger shown in FIG. 2;

[0115] FIG. 4 is a sectional perspective view of an assembling state of the fluid heat exchanger shown in FIG. 2;

[0116] FIG. 5 is a schematic view of a metal strip in the first embodiment of the baffle according to the present invention;

[0117] FIG. 6 is a perspective view of a second embodiment of the baffle according to the present invention;

[0118] FIGS. 7-9 are schematic views of a third embodiment of the baffle according to the present invention;

[0119] FIG. 10 is a perspective view of a fourth embodiment of the baffle according to the present invention;

[0120] FIG. 11 is a schematic view of a spiral spring-like metal strip in the fourth embodiment of the baffle according to the present invention;

[0121] FIG. 12 is a perspective view of a fifth embodiment of the baffle according to the present invention;

[0122] FIG. 13 is a perspective view of a sixth embodiment of the baffle according to the present invention;

[0123] FIG. 14 is a schematic view of spiral spring-like metal strips in the sixth embodiment of the baffle according to the present invention;

[0124] FIG. 15 is a perspective view of a seventh embodiment of the baffle according to the present invention;

[0125] FIG. 16 is a schematic view of metal strips of metal wires in the seventh embodiment of the baffle according to the present invention;

[0126] FIG. 17 is a perspective view of an eighth embodiment of the baffle according to the present invention;

[0127] FIG. 18 is a schematic view of a metal spiral strip in the eighth embodiment of the baffle according to the present invention;

[0128] FIG. 19 is a perspective view of a ninth embodiment of the baffle according to the present invention;

[0129] FIG. 20 is an exploded perspective view of the ninth embodiment of the baffle according to the present invention;

[0130] FIG. 21 is a perspective view showing that the baffle shown in FIG. 19 is installed in the heat exchanger;

[0131] FIG. 22 is a perspective view of a tenth embodiment of the baffle according to the present invention;

[0132] FIG. 23 is a perspective view showing that the baffle shown in FIG. 22 is installed in the heat exchanger;

[0133] FIGS. 24-25 are schematic views of an eleventh embodiment of the baffle according to the present invention;

[0134] FIG. 26 is a schematic view of a twelfth embodiment of the baffle according to the present invention;

[0135] FIG. 27 is a perspective view of a metal strip for manufacturing the baffle shown in FIG. 26;

[0136] FIG. 28 is a perspective view showing that the baffle shown in FIG. 26 is installed in the heat exchanger;

[0137] FIG. 29 is a schematic view of a thirteenth embodiment of the baffle according to the present invention;

[0138] FIGS. 30 and 31 illustrate spoilers of the baffle shown in FIG. 29;

[0139] FIG. 32 illustrates a heat transfer sheet of the baffle shown in FIG. 29;

[0140] FIG. 33 is a schematic view of a fourteenth embodiment of the baffle according to the present invention;

[0141] FIG. 34 is a schematic view of a heat conducting cylinder used in the baffle shown in FIG. 33;

[0142] FIG. 35 is a perspective view showing the baffle shown in FIG. 33 installed in the heat exchanger;

[0143] FIG. 36 is a schematic view of a second embodiment of the heat exchanger according to the present invention;

[0144] FIG. 37 is a schematic view of a fifteenth embodiment of the baffle according to the present invention;

[0145] FIG. 38 is a schematic view of a sixteenth embodiment of the baffle according to the present invention;

[0146] FIG. 39 is a schematic view of a seventeenth embodiment of the baffle according to the present invention;

[0147] FIG. 40 is a schematic view of a circular fluid pipeline internally provided with a plurality of parallel spiral metal wires clinging thereto which forms the baffle of FIG. 37 or 38 after flattening;

[0148] FIG. 41 is a perspective view of a third embodiment of the heat exchanger according to the present invention;

[0149] FIG. 42 is an exploded perspective view of the heat exchanger shown in FIG. 41;

[0150] FIGS. 43 and 43A is a perspective view of a flow divider used in the heat exchanger shown in FIG. 41;

[0151] FIG. 44 is a schematic view of a filtration device in the heat exchanger shown in FIG. 41;

[0152] FIGS. 45 and 45A is a sectional perspective view of the heat exchanger shown in FIG. 41;

[0153] FIG. 46 is a sectional perspective view of the main body of the heat exchanger shown in FIG. 41;

[0154] FIG. 47 is an exploded perspective view of a nested structure of a heat exchange pipe;

[0155] FIG. 48 is a sectional perspective view of a heat exchanger identical to that of FIG. 45, illustrating an operation of removing fouling of the heat exchange pipe;

[0156] FIG. 49 is a perspective view of a baffle forming the second embodiment of the flow divider according to the present invention;

[0157] FIG. 50 is a perspective view showing the baffle shown in FIG. 49 installed in the heat exchanger;

[0158] FIG. 51 is a perspective view of a situation where the main body of the heat exchanger shown in FIG. 42 is disposed with an annular channel;

[0159] FIG. 52 is a sectional perspective view of an eighteenth embodiment of the baffle according to the present invention;

[0160] FIGS. 53-54 are perspective views of a spoiler in the eighteenth embodiment of the baffle according to the present invention;

[0161] FIG. 55 is a perspective view of a heat transfer sheet in the eighteenth embodiment of the present invention;

[0162] FIG. 56 is a sectional perspective view of a nineteenth embodiment of the baffle according to the present invention;

[0163] FIG. 57 is a perspective view of a spoiler in the nineteenth embodiment of the baffle according to the present invention;

[0164] FIG. 58 is a sectional perspective view of a twentieth embodiment of the baffle according to the present invention;

[0165] FIGS. 59-60 are perspective views of a spoiler in the twentieth embodiment of the baffle according to the present invention;

[0166] FIG. 61 is a perspective view of a heat transfer sheet in the twentieth embodiment of the baffle according to the present invention;

[0167] FIG. 62 is a sectional perspective view of a twenty-first embodiment of the baffle according to the present invention;

[0168] FIG. 63 is an exploded perspective view of the twenty-first embodiment of the baffle according to the present invention;

[0169] FIG. 64 is a sectional perspective view of a twenty-second embodiment of the baffle according to the present invention;

[0170] FIG. 65 is a perspective view of a spoiler in the twenty-second embodiment of the baffle according to the present invention;

[0171] FIG. 66 is an exploded perspective view of the twenty-second embodiment of the baffle according to the present invention;

[0172] FIG. 67 is a sectional perspective view of a twenty-third embodiment of the baffle according to the present invention;

[0173] FIG. 68 is a perspective view of a spoiler in the twenty-third embodiment of the present invention;

[0174] FIG. 69 is an exploded perspective view of a fourth embodiment of the heat exchanger according to the present invention and a bathroom drain device;

[0175] FIG. 70 is a perspective view of an assembling state of the heat exchanger and the bathroom drain device shown in FIG. 69;

[0176] FIG. 71 is an exploded perspective view of the heat exchanger shown in FIG. 69;

[0177] FIG. 72 is a sectional perspective view of an assembling state of the heat exchanger shown in FIG. 69;

[0178] FIG. 73 is an exploded perspective view of the heat exchange pipe shown in FIG. 69;

[0179] FIG. 74 is a perspective view of a nested state of the heat exchange pipe shown in FIG. 73;

[0180] FIG. 75 is a schematic view of a fifth embodiment of the heat exchanger according to the present invention being placed on the bathroom floor;

[0181] FIG. 76 is an exploded perspective view of the heat exchanger and a water collector shown in FIG. 75;

[0182] FIG. 77 is an exploded perspective view of the heat exchanger shown in FIG. 75; and

[0183] FIG. 78 is a schematic view of an internal baffle structure of a heat exchange pipe in the heat exchanger shown in FIG. 75.

DETAILED DESCRIPTION

[0184] The present invention relates to a thermal conductive baffle, a fluid heat exchanger and an energy recovery device. Embodiments in which the thermal conductive baffle, the fluid heat exchanger and the energy recovery device of the present invention are combined with a bathroom shower and a sink of a washing facility are described below only by way of examples with reference to the accompanying drawings. It should be understood that the present invention is not limited thereto.

[0185] FIGS. 2, 2A, 3 and 4 illustrate a structure of a first embodiment of a fluid heat exchanger according to the present invention. The heat exchanger 1 includes a heat exchanger main body 11 and a baffle 31. The heat exchanger main body 11 includes a housing 13 and a metal pipe 15. The housing 13 has a cold water (second fluid) inlet 17, a tepid water (preheated second fluid) outlet 18 and a cold water (second fluid) conduit 19 between the cold water inlet 17 and the tepid water outlet 18. The metal pipe 15 is vertically disposed in the cold water conduit 19 and passes through the housing 13, and a hot wastewater (first fluid) channel 21 for hot wastewater (first fluid) to pass through is formed in the metal pipe 15. A protruding baffle structure 22 is disposed on an inner wall of the metal pipe 15. The baffle structure 22 is formed by one or more solid metal spiral structures extending along a length direction of the metal pipe 15, and maintains good thermal contact with the inner wall of the metal pipe 15. The baffle structure 22 can be assembled into the metal pipe 15 in the following manner:

[0186] a. spiraling and coiling one or more solid metal wires on a straight bar with gaps, to such that overall outer diameter thereof less than the inner diameter of the metal pipe 15;

[0187] b. placing the straight bar and the metal wires together in a suitable position within the metal pipe 15;

[0188] c. loosening the metal wires, such that the metal wires naturally rebound to press against the inner wall of the metal pipe 15; and

[0189] d. removing the straight bar.

[0190] A cold water (second fluid) annular channel 23 (FIG. 3) surrounding an outer wall of the metal pipe 15 is formed between the metal pipe 15 and the cold water conduit 19. In the following description about various embodiments of the present invention, the first fluid is hot wastewater and the second fluid is cold water as an example for illustration, but the present invention is not limited thereto.

[0191] During the operation of the heat exchanger 1, the cold water inlet 17 is directly or indirectly connected to a cold water source (not shown) of a building, the tepid water outlet 18 is connected to a bathroom heater (not shown) or a mixing valve (not shown), and the hot wastewater channel 21 is communicated to a drain pipe (not shown) of a shower device or the like to receive hot wastewater generated during shower. The inner diameter of the hot wastewater channel 21 is designed such that hot wastewater generated generally by shower is not sufficient to fill its cavity. The hot wastewater attaches to an inner wall of the hot wastewater channel 21 to slowly flow downwards. The baffle structure 22 slows down

the speed at which the hot wastewater flows downwards, and facilitates the spiral motion of the hot wastewater in the metal pipe 15 to delay the time period of its stay in the hot wastewater channel 21. In the meantime, heat exchange surfaces of the hot wastewater is also significantly increased. These all effectively enhance heat exchange efficiency of the heat exchanger. To further enhance the efficiency of heat conduction between the baffle structure 22 and the metal pipe 15 and prevent the baffle structure 22 from shifting, a layer of solder may be pre-coated on surfaces of the metal wires. After the metal wires are placed in the metal pipe 15, relevant parts may be placed in a high-temperature furnace for heating, so that the solder melts to braze the baffle structure onto the inner wall of the metal pipe 15. Certainly, the baffle structure is optional, which may be omitted in the following drawings and description of embodiments.

[0192] To reduce that fouling (such as hair) accumulated on one or more open ends of the top (upstream) of the protruding spiral structure 22 affecting the drainage effect, the open ends may form a slope 10 (FIG. 2) that facilitates the fouling to slide or may be covered by another ring 29 as illustrated in FIG. 2a.

[0193] Meanwhile, the cold water is introduced from the cold water inlet 17 to flow through the cold water annular channel 23 from the bottom up, and exchanges heat with hot wastewater flowing through the hot wastewater channel 21 by means of the metal pipe 15, so that the temperature of the cold water is changed and the cold water becomes preheated water, and then exported from the tepid water outlet 18 and provided to the bathroom heater or the mixing valve (not shown) for use.

[0194] As shown in FIGS. 2-4, the metal pipe 15 is formed by mutual nesting of two metal pipes, i.e., an external metal pipe 25 and an internal metal pipe 26, and the external metal pipe 25 and the internal metal pipe 26 maintain good thermal contact therebetween, and leave a micro-channel 27 that can allow the wastewater or cold water to pass through. The micro-channel 27 is formed between the external metal pipe 25 and the internal metal pipe 26 by having small concave-convex structures on a surface of the internal metal pipe 26 through knurling or the like. Under normal conditions, no cold water or wastewater seeps leak out from the micro-channel 27 between the external metal pipe 25 and the internal metal pipe 26. However, when one of the external metal pipe 25 or the internal metal pipe 26 is damaged to cause seepage of cold water or hot wastewater, the cold water or hot wastewater may flow out of the heat exchanger 1 through the micro-channel 27 and alert the user. Certainly, the nested structure is optional, and for the sake of simplicity, in the following drawings and description, the metal pipe 15 may be illustrated and described in the form of a single piece.

[0195] The heat exchanger 1 in the first embodiment of the fluid heat exchanger according to the present invention further includes a baffle 31, to further improve the heat exchange efficiency. As shown in FIG. 4, the baffle 31 surrounding the metal pipe 15 is disposed in the cold water annular channel 23 formed by tubes, i.e., the metal pipe 15 and the cold water conduit 19. The baffle 31 is made of metal, which tightly presses against on the inner wall of the cold water conduit 19 and maintains good thermal contact with the outer wall of the metal pipe 15. A manner in which the baffle 31 is installed may include welding, or after the baffle 31 is placed, the inner diameter of the metal pipe 15 is slightly expanded so that the

outer wall of the metal pipe 15, the baffle 31 and the inner wall of the cold water conduit 19 pressed together.

[0196] FIGS. 2, 3 and 4 illustrate a structure of a first embodiment of a thermal conductive baffle according to the present invention. The baffle 31 includes a plurality of solid metal strips 33 (see FIG. 5). A plurality of solid annular projections 34 is spaced apart along a length direction of the metal strips 33. The plurality of solid metal strips 33 is adjacently configured around the outer wall of the metal pipe 15 with their centerlines parallel to the centerline of the metal pipe 15. The cold water is blocked by the plurality of metal strips 33 when passing through the cold water annular channel 23, and the cold water passes through between the outer wall of the metal pipe 15, the metal strips 33, the annular projections 34 and the inner wall of the cold water conduit 19 in turbulence, and exchanges heat with the hot wastewater flowing through the hot wastewater channel 21 by means of heat conduction of the baffle 31 and the metal pipe 15. The thermal conductive baffle 31 significantly increases the heat exchange surface with the cold water, and can constantly change the flow direction of the cold water to generate a turbulence effect, thereby improving the heat exchange efficiency. The cold water conduit 19 may also be made of metal, so that the inner wall of the cold water conduit 19 also becomes the heat exchange surface with the cold water.

[0197] FIG. 6 illustrates a structure of a second embodiment of a thermal conductive baffle according to the present invention. The baffle 41 is made of one or more solid metal strips 33 as shown in FIG. 5. The metal strips 33 spirally extend with their centerlines around the outer wall of the metal pipe 15. The function and the effect of the baffle 41 are substantially the same as those of the baffle 31, which are not repeated herein.

[0198] FIGS. 7-9 illustrate a structure of a third embodiment of a thermal conductive baffle according to the present invention. The baffle 41' includes a plurality of solid metal strips 36 made of metal. A plurality of solid annular projections 37 are spaced apart from each other along a length direction of the metal strips 36. Each of the metal strips 36 surrounds the metal pipe with its centerline perpendicular to the centerline of the metal pipe 15, and the annular projections 37 of adjacent metal strips 36 are staggered. The function and the effect of the baffle 41' are substantially the same as those of the baffle 31, which are not repeated herein.

[0199] To facilitate assembly of the plurality of metal strips 36, planes 38 back to each other may be formed on the solid annular projections 37, and then the metal strips 36 are fixed to a metal sheet 39 by means of the planes 38. Afterwards, the metal sheet 39 is bent into a cylindrical shape (FIG. 9) to be nested onto the metal pipe 15, and another plane 38 of the annular projections 37 is pressed against the metal pipe 15. In this way, a contact area of the baffle 41' and the metal pipe 15 is increased, and the thermal conductive function is enhanced.

[0200] FIGS. 10-11 illustrate a structure of a fourth embodiment of a thermal conductive baffle according to the present invention. The baffle 51 includes a plurality of spiral spring-like metal strips 53 (see FIG. 11) made of solid metal wires. The metal strips 53 are adjacently configured around the outer wall of the metal pipe 15 with their centerlines parallel to the centerline of the metal pipe 15. The function and the effect of the baffle 51 are substantially the same as those of the baffle 31, which are not repeated herein.

[0201] FIG. 12 illustrates a structure of a fifth embodiment of a thermal conductive baffle according to the present inven-

tion. The baffle **61** is formed by one or more metal strips **53** as shown in FIG. **11**. The metal strips **53** spirally extend with their centerlines around the outer wall of the metal pipe **15**. The function and the effect of the baffle **61** are substantially the same as those of the baffle **31**, which are not repeated herein.

[0202] Similarly, the metal strips **53** shown in FIG. **12** may also surround the metal pipe with their centerlines perpendicular to the centerline of the outer wall of the metal pipe **15**, so as to construct a baffle (not shown) similar to the baffle shown in FIG. **7**.

[0203] FIGS. **13-14** illustrate a structure of a sixth embodiment of the baffle having a thermal conductive baffle according to the present invention. The baffle **71** includes a plurality of metal strip **75**, each comprises a first spiral spring-like metal element **73** (see FIG. **14**) and a second metal strips **74** extending along the center of the spiral element **73** to increase the heat exchange surface. The second metal strips **74** shown in FIG. **14** are straight bars, but they may be various kinds of metal strips described previously or below. The metal strips **75** are adjacently configured around the outer wall of the metal pipe **15** with their centerlines parallel to the centerline of the metal pipe **15**. The function and the effect of the baffle **71** are substantially the same as those of the baffle **31**, which are not repeated herein.

[0204] Similarly, one or more metal strips **75** shown in FIG. **14** may spirally extend with their centerlines around the outer wall of the metal pipe **15**, or the plurality of metal strips surrounds the metal pipe with their centerlines perpendicular to the centerline of the metal pipe **15**, so as to construct a baffle (not shown) similar to the baffle shown in FIGS. **6** and **7**.

[0205] FIGS. **15-16** illustrate a structure of a seventh embodiment of a thermal conductive baffle according to the present invention. The baffle **81** includes a plurality of metal strips **83** (see FIG. **16**), and each of the metal strips **83** is made by intertwining of two solid metal wires **84** and **85**, on whose surface there is a spiral concave structure. The metal strips **83** are adjacently configured around the outer wall of the metal pipe **15** with their centerlines parallel to the centerline of metal pipe **15**. The metal strips may also be formed by intertwining of a plurality of metal wires. The function and the effect of the baffle **81** are substantially the same as those of the baffle **31**, which are not repeated herein.

[0206] Similarly, one or more metal strips **83** shown in FIG. **16** can spirally extend with their centerlines around the outer wall of the metal pipe **15**, or the plurality of metal strips **83** surrounds the outer wall of the metal pipe with their centerlines perpendicular to the centerline of the metal pipe **15**, so as to construct a baffle (not shown) similar to the baffle shown in FIGS. **6** and **7**.

[0207] FIGS. **17-18** illustrate a structure of an eighth embodiment of a thermal conductive baffle according to the present invention. The baffle **91** includes a plurality of metal spiral strips **93** having rectangular or non-circular cross-sections, on whose surfaces there are spiral concave structures **95** (see FIG. **18**). The metal spiral strips **93** are adjacently configured around the outer wall of the metal pipe **15** with their centerlines parallel to the centerline of the metal pipe **15**. The function and the effect of the baffle **91** are substantially the same as those of the baffle **31**, which are not repeated herein.

[0208] Similarly, one or more metal spiral strips **93** shown in FIG. **18** can spirally extend with their centerlines around the outer wall of the metal pipe **15**, or the plurality of metal strips **93** surrounds the outer wall of the metal pipe with their

centerlines perpendicular to the centerline of the metal pipe **15**, so as to construct a baffle (not shown) similar to the baffle shown in FIGS. **6** and **7**.

[0209] FIGS. **19-20** illustrate a structure of a ninth embodiment of the baffle having a thermal conductive baffle according to the present invention. The baffle **101** has a barrel structure made by stamping of metal, and is formed by two semi-barrel structures **102** and **103**, on whose surfaces there are a plurality of spiral pits **104** and **105** to form a plurality of spiral channels that allows the cold water to flow through in parallel, and a plurality of straight-through through holes **106** and **107** is further provided between the spiral pits **104** and **105** to allow part of the cold water to directly pass through adjacent spiral channels with a non-circuitous straight-through path to generate turbulence effects. FIG. **21** illustrates a state in which the baffle **101** is installed in the heat exchanger main body **11**. The cold water exchanges heat with the hot wastewater flowing through the hot wastewater channel **21** by means of heat conduction of the baffle **101** and the metal pipe **15** when flowing through the plurality of spiral channels in parallel.

[0210] FIG. **22** illustrates a structure of a tenth embodiment of the thermal conductive baffle according to the present invention. The baffle **111** includes two layers of helically configured un-parallel (preferably with reverse helical direction) solid metal wires **112** and **113** overlapping each other that surround the metal pipe **15**. Each layer of metal wires **112** and **113** includes a plurality of metal wires sections spaced apart and parallel to each other where the metal wires **112** in the inner layer presses against and thermally contacts the outer wall of metal pipe **15** along the majority of their length, while the metal wires **113** in the outer layers butts against the inner wall of the cold water conduit **19**. The cold water passing through the annular channel **23**, flows through gaps **114** (see FIG. **23**) between the two layers of wires **112** and **113** and exchanges heat with hot wastewater in the wastewater channel **21**. The baffle **111** significantly increases the heat exchange surface of cold water and constantly changes the flow direction; these are helpful to improve the heat exchange efficiency of the heat exchanger.

[0211] The baffle **111** with thermal conductive function as illustrated in FIG. **22** may be fabricated by method as illustrated in FIG. **22 A**:

[0212] 1. A plurality of metal wires **112A**, **112B**, **112C** and **112D** are spirally arranged about mandrel **114** with gaps and in parallel, to form an inner metal wire layer **112**;

[0213] 2. Upon spirally arranged about mandrel **114** for a certain of length, the plurality of metal wire **112A**, **112B**, **112C** and **112D** are further spirally arranged about mandrel **114** in counterclockwise direction with gaps and in parallel, to form an outer metal wire layer **113**;

[0214] 3. Prior to relieving or cutting the plurality of metal wires **112A**, **112B**, **112C** and **112D**, the two metal wire layers are welded in suitable position with suitable means (such as spot welding) to form a rigid metal tubular mesh;

[0215] 4. The metal wires are removed from mandrel **114** and then cutting into suitable length to form the baffle as illustrated in FIG. **22**.

[0216] In the aforementioned example, mandrel **114** may also be replaced by metal tube **15** and directly weld the plurality of metal wires **112A**, **112B**, **112C** and **112D** thereon.

[0217] By using the method as above, baffle with more than two metal wire layers may be fabricated to increase heat exchange surface and enhance turbulence effect. FIGS. **24-25**

illustrate a structure of an eleventh embodiment of the thermal conductive baffle according to the present invention. Structure of baffle **121** is basically same as baffle **111** (FIG. **22**) except that it is formed by curling a metal mesh **121'** as shown in FIG. **25**. The metal mesh **121'** includes two layers of metal wires. Each layer includes a plurality of solid straight metal wires **122'** and **123'** parallel to each other and spaced apart. The two layers are superposed and welded with the wires unparallel to form the mesh **121'**. The function and effect of the baffle **121** are substantially the same as those of baffle **111**, which are not repeated herein.

[0218] FIG. **26** illustrates a structure of a twelfth embodiment of a thermal conductive baffle according to the present invention, FIG. **27** illustrates a shape of the metal strips **132** for manufacturing the baffle **131**, and FIG. **28** illustrates a state in which the baffle **131** is installed in the heat exchanger main body **11**. The baffle **131** has a barrel structure made by cutting of metal strip **132** after curling. Multiple pairs of mutually aligned solid spoilers **134** and **135** functioning to baffle flow are convexly formed on internal and external surfaces of cylindrical walls **133** respectively, and the spoilers **134** and **135** maintain good thermal contact with the outer wall of the metal pipe **15** and press against the inner wall of the conduit **19**. The cylindrical walls **133** and the spoilers **134** and **135** respectively form two groups of internal and external spiral channels **136** and **137** in the cold water annular channel **23**. The cold water passes through the two groups of internal and external spiral channels **136** and **137** in parallel. Due to heat conduction of the mutually aligned solid spoilers **134** and **135** of the baffle **131** as well as the cylindrical walls **133** and the metal pipe **15**, the heat exchange surface with the cold water is significantly increased, thereby improving the heat exchange efficiency. The spoilers **134** and **135** are further respectively provided with a plurality of substantially aligned notches **138** and **139**, to allow part of the cold water to directly pass through two adjacent spiral channels **136** and **137** with a non-circuitous straight-through path, thereby generating turbulence effects.

[0219] FIG. **29** to FIG. **32** illustrate a structure of a thirteenth embodiment of a thermal conductive baffle according to the present invention. The baffle **55** is horizontally superposed in the annular channel **23** (FIG. **29**) through sheet-like objects as shown in FIG. **30** to FIG. **32** with gaps, and the sheet-like objects **56**, **57** and **58** (FIGS. **30-32**) all have central through holes (**561**, **581** and **571**) for tightly nesting the metal pipe **15** and openings that allow the fluids to pass, where the opening **562** of the sheet-like object **56** (FIG. **30**) is formed in adjacent to the central through hole **561**, the opening **574** of the sheet-like object **57** (FIG. **31**) is formed by a gap between a periphery **572** thereof and the inner wall of the cold water conduit **19**, and the sheet-like object **58** (FIG. **32**) has two openings, including an opening **582** formed adjacent to the central through hole **581** and an opening **584** formed by a gap between a periphery **583** thereof and the inner wall of the cold water conduit **19**. The sheet-like objects **56**, **57** and **58** are at least partially made of metal (in the above example, the sheet-like objects **56**, **57** and **58** are all made of metal) and thermally contact the outer wall of the metal pipe **15**. The sheet-like objects **56** and **57** are spoilers, and any two closest spoiler **56** and **57** when placed in the annular channel **23** (FIG. **29**), whose openings do not overlap each other in a main surface direction, so that the cold water passing through the annular channel **23** needs to circuitously flow between the baffle spoiler **56** and **57** alternately from inside to outside and then

from outside to inside so as to alternately pass through the openings **562** and **574** to form turbulence effects, and increase the rate of heat exchange.

[0220] To further increase heat transfer effects, one or more metal heat transfer sheets **58** may be added between the spoiler **56** and **57**. When the cold water passing through the annular channel **23** passes through any two closest spoiler **56** and **57**, the cold water passes in parallel through two main surfaces of the heat transfer sheets **58**, and exchanges heat with the hot wastewater passing through the metal pipe **15** by means of the heat transfer sheets **58** and the metal pipe **15**. The metal sheet-like object **56**, **57** or **58** significantly increases the heat exchange surface of the cold water; the spoiler **56** and **57** constantly change the flow direction of the cold water to generate turbulence effects; these are all helpful to improve the heat exchange efficiency of the heat exchanger **11**.

[0221] FIGS. **33-35** illustrate a structure of a fourteenth embodiment of a thermal conductive baffle according to the present invention. The baffle **141** is similar to the baffle **111** in the tenth embodiment, and includes two layers of un-parallel solid metal wires **142** and **143** overlapping each other to surround the metal pipe **15**. The difference merely lies in that a heat conducting cylinder **144** is disposed between the two layers of metal wires **142** and **143** of the baffle **141**. A plurality of through holes **146** is formed on cylinder walls **145** of the heat conducting cylinder **144**. FIG. **35** illustrates a state in which the baffle **141** is installed in the heat exchanger main body **11**. The heat conducting cylinder **144** partitions the cold water annular channel **23** into internal and external annular channels, the solid metal wires **142/143** thereby forming two groups of cold water spiral channels. Part of the cold water spirally passes through the two groups of cold water spiral channels, and part of the cold water passes through the through holes **146** on the heat conducting cylinder **144** between the metal wires, to generate turbulence effects. The baffle **141** significantly increases the heat exchange surface of the cold water, thereby enhancing the heat exchange efficiency of the heat exchanger. In this embodiment, the metal wires **142** and **143** respectively constitute internal and external baffles, and the internal and external baffles may be any one or a combination of any two of the baffles in the first to thirteenth embodiments. Due to the thermal conduction of the heat conducting cylinder **144**, the internal and external baffles and the metal pipe **15**, the heat exchange surface with the cold water is significantly increased, thereby enhancing the heat exchange efficiency.

[0222] In the foregoing embodiments, pipe **15** and the thermal conductive baffles are made of metal, preferably they should be made of good thermal conductors such as copper or aluminium or its alloy to enhance heat exchange. Optionally, cold water conduit **19** can also be made of metal so that its internal wall becomes a heat exchange surface to enhance heat exchange.

[0223] In the foregoing embodiments, the thermal conductive baffles are placed in an annular channel formed by 2 tubes (metal pipe **15** & cold water conduit **19**) which includes at least one metal wall (metal pipe **14**) and is in thermal contact with at least one metal wall (metal pipe **15**) that form the annular channel. Fluid (cold water) exchange heat with hot wastewater (second fluid) outside the annular channel. But optionally, other substance, such as electric heating wires, can be placed outside the annular channel, for example, inside metal pipe **15** or outside cold water conduit **19**, so that the heat exchanger can serve as a fluid heater. If an electric heating

wire is placed outside the cold water conduit, the metal pipe **15** may be replaced by a solid member.

[0224] FIG. **36** illustrates a second embodiment of the heat exchanger according to the present invention. The heat exchanger **32** includes a metal pipe **15** and a metal cold water conduit **42** spirally surrounding the metal pipe **15**, which tightly nests and thermally contacts the metal pipe **15**. A section of the cold water conduit **42** is flat, and a section on an outer wall thereof has at least one straight side and clings to an outer wall of the metal pipe **15** so as to increase a contact surface with the metal pipe **15**.

[0225] In use of the heat exchanger **32**, an inlet **43** (cold water inlet) of the cold water conduit **42** located in the bottom is directly or indirectly connected to a cold water source (not shown) of the building; an outlet **44** (tepid water outlet) on the top thereof is connected to a bathroom heater (not shown) or a bathroom mixing valve (not shown). Like the heat exchanger **11** in the first embodiment, the hot wastewater channel **21** of the heat exchanger **32** is communicated to a drain pipe (not shown) of a shower device or the like to receive hot wastewater generated during shower. The hot wastewater passes through the metal pipe **15** in a manner identical to that in the first embodiment, which is not repeated herein.

[0226] In the meantime, the cold water is introduced from the cold water inlet **43** to flow through the spiral conduit **42** from the bottom up, and exchanges heat with hot wastewater flowing through the hot wastewater channel **21** by means of the metal pipe **15**, so that the temperature of the cold water is changed and the cold water becomes preheated water, and then is exported from the tepid water outlet **44** and provided to the bathroom heater or mixing valve (not shown) for use.

[0227] To increase the heat exchange efficiency, the spiral protruding structure in the first embodiment (FIG. **2**) can optionally be added to the wastewater channel **21**, the function of which is not repeated herein; meanwhile, a thermal conductive baffle as shown in FIG. **37**, **38** or **39** may also be added to the cold water conduit **42**.

[0228] As shown in FIG. **37**, the baffle **35** is placed in a metal fluid conduit **42'**, a fluid channel **45** formed on an inner wall of the fluid conduit **42'** has two parallel surfaces **47** and **48**. The baffle is formed by upper and lower layers of metal wires **49** and **52**, each layer of metal wires is formed by a plurality of metal wire sections parallel to each other and arranged with gaps, and each layer of metal wires (thermally) contacts the two parallel surfaces **47** and **48** respectively. Part of wire sections in the two layers of metal wires are formed by the same metal wire and are connected through bends **54** and **59**. Fluids passing through the fluid channel **45** pass between the two layers of metal wires **49** and **52** and between various sections of parallel metal wires in turbulence, and exchange heat with substances outside the channel **45** (for example, the hot waste water in the metal pipe **15**) by means of the two layers of metal wires **49** and **52** and walls of metal channels in thermal contact therewith.

[0229] One or more metal fluid conduit **42'** having the baffle **35** as shown in FIG. **37** may tightly be wound to the outer wall of the metal pipe **15** to form the heat exchanger **32** (FIG. **38**). The baffle **35** in the fluid channel **45** significantly increases the heat exchange surface of the cold water, and constantly changes the flow direction of the cold water, to effectively improve heat exchange effects.

[0230] The fluid channel having the heat conducting baffle **35** may be manufactured in the following manner:

[0231] a. coiling one or more metal wires on a straight bar with gaps, such that an overall outer diameter thereof slightly less than the inner diameter of a circular metal pipe;

[0232] b. placing the straight bar and the metal wires together in a suitable position in the metal pipe;

[0233] c. loosening the metal wires, such that the metal wires are naturally rebound to press against the inner wall of the metal pipe;

[0234] d. removing the straight bar, to form a circular fluid conduit having a plurality of parallel spiral metal wires clinging thereto as shown in FIG. **40**; and

[0235] e. flattening the circular metal pipe to form the fluid pipeline of the baffle having a thermal conductive baffle as shown in FIG. **37** or **38**.

[0236] The difference between FIG. **37** and FIG. **38** lies in that: for the baffle **35** shown in FIG. **37**, the upper and lower layers of metal wires thereof are tightly pressed together, so that heat can be rapidly transferred from one parallel surface to the other parallel surface through thermal conduction between the two layers of metal wires; and for the baffle **35'** (in the sixteenth embodiment) shown in FIG. **38**, the upper and lower layers of metal wires thereof leave a gap therebetween, to allow more fluids to pass through and result in smaller pressure loss, and technicians can choose to use the baffle according to situations.

[0237] FIG. **39** illustrates a seventeenth embodiment of the baffle according to the present invention. The baffle **62** is disposed in a metal fluid channel **45**, and the fluid channel **45** has two parallel surfaces **47** and **48**. The baffle is formed by superposition of four layers of metal wires **63**, **64**, **65** and **66** which are pressed together to provide thermal contact therebetween, each layer of metal wires has a plurality of metal wire sections parallel to each other and having gaps, and metal wire sections in two adjacent layers of metal wires are not parallel to each other. The metal wire **63** in the top layer (thermally) contacts the upper parallel surface **48** of the fluid channel **45**; the metal wire **66** in the bottom layer (thermally) contacts the lower parallel surface **47** of the fluid channel **45**, and part of sections of the metal wires **63** and **66** in the top layer and the bottom layer are formed by the same metal wire, and are connected through bends **67** and **67'**. Part of sections of two layers of metal wires **64** and **65** in the middle are formed by the same metal wire and are connected through bends **68** and **68'**. The fluids passing through the fluid channel **45** pass through the four layers of metal wires and the parallel metal wire sections in turbulence, and exchange heat with substances outside the channel (for example, the hot waste water in the metal pipe **15**) by means of the metal wires and metal walls of fluid channels in thermal contact therewith.

[0238] One or more metal fluid channels **42'** having the baffle **62** as shown in FIG. **39** may tightly be wound to the metal pipe **15** to form the heat exchanger **32** (FIG. **36**). The baffle **62** significantly increases the heat exchange surface of the cold water, and constantly changes the flow direction of the cold water, which are helpful to improve heat exchange effects.

[0239] The fluid channel having the baffle **62** may be manufactured in the following manner:

[0240] a. placing the net-like metal cylinder shown in FIG. **22** or **24** into a metal circular pipe whose inner diameter is slightly greater than that of the net-like cylinder; and

[0241] b. flattening the metal circular pipe and the net-like cylinder together such that the circular pipe form two parallel surfaces and tightly press the (four layers of) metal wires.

[0242] FIG. 41 illustrates a third embodiment of the heat exchanger according to the present invention. The heat exchanger 160 is installed below a sink 162 and a tabletop 163. As shown in FIG. 42, the heat exchanger 160 includes a wastewater collector 165, a main body 167 and a wastewater connector 169. The wastewater collector 165 has an opening 172, a cavity 173 and a plurality of wastewater outlets 174. The opening 172 is located above the plurality of wastewater outlets 174, and covers all the wastewater outlets 174 in a horizontal direction. The main body 167 includes a housing 177 and a plurality of heat exchange pipes 179. The wastewater connector 169 has a plurality of wastewater receiving holes 182 and wastewater discharge ports 183. The opening 172 of the wastewater collector 165 communicates with a drain hole 161 of the sink 162, to receive hot wastewater generated during washing. The drain hole 161 covers all the wastewater outlets 174 in a horizontal direction. The hot wastewater flows into the cavity 173 through the opening 172 of the wastewater collector and then flows out of the cavity 173 in parallel from the plurality of wastewater outlets 174. The plurality of wastewater outlets 174 separately communicates with the plurality of heat exchange pipes 179, such that the hot wastewater pass through hot wastewater channels 185 in parallel. The hot wastewater, enters the wastewater connector 169 from the plurality of wastewater receiving holes 182 after passing through the main body 167, and is then discharged from the wastewater discharge ports 183 to a drain pipeline (not shown) outside the building.

[0243] To ensure the wastewater flow out from the plurality of wastewater outlets 174 evenly and avoid that the wastewater only rapidly flows out from one or two wastewater outlets to affect the heat exchange efficiency, a flow divider 181 (see FIG. 43) may detachably be disposed in the cavity 173. The flow divider 181 includes a chassis 1811, a riser 1812 extending upwards from the chassis 1811 and an upper cover 1813 covering an upper end of the riser 1812. The chassis 1811 is provided with a plurality of baffles 1814 corresponding to the wastewater outlets 174. The baffles 1814 are adjacent to or placed in inlet ends of the wastewater outlets 174 respectively, so that the wastewater is blocked by the baffles 1814 to pass through gaps 180 (see FIG. 45) between the baffles 1814 and the wastewater outlets 174 with relatively even flow in entering the wastewater channels 185. The quantity of wastewater flow is insufficient to fill the whole wastewater channels 185, and thus the wastewater is attached to inner walls of the wastewater channels 185 and flows downwards around a central air column of the wastewater channels 185.

[0244] The baffles 1814 have through holes 1815, which communicate with the riser 1812. An air vent 1817 is formed on the upper end of the riser 1812. The wastewater, when passing through the baffles 1814, forms low pressure in the vicinity of the through holes 1815, to suck air into the wastewater channels 185 from the air vent 1817, so that the air can still enter the wastewater channels 185 when the wastewater floods the wastewater outlets 174 to maintain the state of having the central air column.

[0245] Alternatively, as shown in FIG. 43A, Baffles 1814 of the flow divider 181 may include gaps 1818. When inserted in the wastewater outlet 174 (FIG. 45A) the Baffles 1814 contacts the waste water outlet 174 and the gap 1818 form passageway 182 for wastewater to evenly flow through.

[0246] The downward flowing wastewater, exchanges heat with cold water flowing reversely outside the heat exchange pipes through the heat exchange pipes 179.

[0247] To reduce the fouling accumulated and clogged in the wastewater channels 185, a strainer 64 as shown in FIG. 44 may be disposed in the cavity 173 of the wastewater collector 165 for separating hair and other garbage. The strainer 64 has a through hole 641 located in the center to allow the riser 1812 to pass through and small holes 642 located in the periphery to allow the wastewater to pass through. The strainer 64 and the flow divider 181 are detachably installed in the cavity 173 of the wastewater collector 165 such that a user may remove the strainer 64 and the flow divider 181 at the opening 172 for cleaning.

[0248] As shown in FIG. 45, a protruding baffle structure 186 can be formed on the inner walls of the wastewater channels 185 to improve the heat exchange efficiency, where the function, effect, and assembly method are substantially the same as those of the baffle structure 22 shown in FIG. 3, and thus are not repeated herein. Similarly, the baffle structure is optional, and such baffle structure may be omitted in the following drawings and description for the sake of simplicity.

[0249] FIG. 46 illustrates an internal structure of the heat exchanger 160. The housing 177 has a cold water inlet 192 and a tepid water outlet 193. The plurality of heat exchange pipes 179 communicates with the plurality of wastewater outlets 174 and the plurality of wastewater receiving holes 182 respectively, such that the hot wastewater pass through from the hot wastewater channels 185 in parallel. The hot wastewater enters the wastewater connector 169 after passing through the main body 167. During operation, the cold water inlet 192 is directly or indirectly connected to a cold water source (not shown) of the building, and the tepid water outlet 193 is connected to a heater (not shown) outside the sink 162 or mixing valve (not shown). Hot wastewater generated during washing flows downwards in parallel in the plurality of hot wastewater channels 185. Meanwhile, the cold water is introduced into a cavity 194 of the housing 177 from the cold water inlet 192 and flows through outer walls of the plurality of heat exchange pipes 179 from the bottom up, and is then exported from the tepid water outlet 193. In the meantime, the cold water exchanges heat with the hot wastewater flowing through the hot wastewater channels 185 of the heat exchange pipes 179, and is heated up as preheated water to reduce energy consumption.

[0250] As shown in FIG. 47, the heat exchange pipes 179 are formed by mutual nesting of two metal pipes, i.e., an external metal pipe 195 and an internal metal pipe 196, the external metal pipe 195 and the internal metal pipe 196 maintain good thermal contact therebetween, and leave a micro-channel 197 for the wastewater or cold water to pass through. The micro-channel 197 is formed between the external metal pipe 195 and the internal metal pipe 196 by having small concave-convex structures on a surface of the internal metal pipe 196 through knurling or the like. Under normal conditions, no cold water or wastewater seeps out of the micro-channel 197 between the external metal pipe 195 and the internal metal pipe 196. However, when one of the external metal pipe 195 and the internal metal pipe 196 is damaged to cause seepage of cold water or hot wastewater, the cold water or hot wastewater may flow out of the heat exchanger main body 167 through the micro-channel 197, for example, flowing out of a gap 198 between the main body 167 and the wastewater collector 165 or a gap 199 (FIG. 45) between the

main body 167 and the wastewater connector 169, to send an alarm. Certainly, the nested structure is optional, and the metal pipe 179 may be illustrated and described in the form of a single piece in the following drawings and description for the sake of simplicity.

[0251] After operating for a period of time, it is inevitable that fouling is accumulated on the inner walls of the wastewater channels 185 and the baffle structure 186, which affects efficiency of heat recovery. As the opening 172 and the drain hole 161 are located above the plurality of wastewater outlets 174 and cover all the wastewater outlets 174 in a horizontal direction, as shown in FIG. 48, the user can wash away the fouling only by using a straight pipe 202 to insert one end thereof into the wastewater channels 185 through the wastewater outlets 174 of the wastewater collector 165, and connecting pressurized water from the other end of the straight pipe 202 (for example, the other end is directly communicated to the cold water source of the building).

[0252] FIG. 49 illustrates a structure of baffles in a second embodiment of the flow divider according to the present invention. FIG. 50 illustrates a state in which the baffles are installed in each heat exchange pipe separately. Baffles 211 include strips 214 of which surfaces forming a spiral diversion structure 213, and leave gaps 215 (see FIG. 50) between the baffles and the heat exchange pipes 179. When hot wastewater flows through the hot wastewater channels 185, part of the hot wastewater vertically passes through the gaps 215, and the other part blocked by the spiral diversion structure 213 spirally passes through the hot wastewater channels 185, and the two water flows interfere with each other such that the hot wastewater is fully mixed and effectively exchange heat with cold water flowing reversely outside the heat exchange pipes 179.

[0253] A filtration device (not shown) can be disposed in the cavity 173 of the wastewater collector 165 to reduce clogging. After operating for a period of time, it is inevitable that fouling is accumulated on the inner walls of the wastewater channels 185, and thus affecting water drainage and heat recovery efficiency. The user only needs to remove the filtration device and the baffles 211 from the opening 172 of the wastewater collector 165 for cleaning.

[0254] As shown in FIG. 51, to further improve the heat exchange efficiency of the fluid heat exchanger 160 according to the present invention, a flow diverter 250 with a plurality of through holes 252 is disposed in the cavity 194 of the housing 177, and a plurality of annular channels each surrounding each of the heat exchange pipes 179 is formed in the cavity 194 of the housing 177. Various thermal conductive baffle as stated above can be configured in the annular channels.

[0255] FIG. 52 illustrates an eighteenth embodiment of a thermal conductive baffle according to the present invention. The baffle 221 is formed by a plurality of sheet-like objects 222, 223 and 226 (FIGS. 53, 54 and 55) disposed up and down with gaps. The sheet-like objects 222 and 223 are spoilers, which are alternately disposed horizontally in the cavity 194.

[0256] The spoiler 222 (FIG. 53) is disc-like, and has a plurality of through holes 2221 corresponding to the heat exchange pipes 179 for nesting the heat exchange pipes 179 and forms a central opening 2222 for cold water to flow through, wherein edge 2223 clings to an inner wall of the cavity 194. The spoiler 223 (FIG. 54) is also disc-like, and also has a plurality of through holes 2231 corresponding to the heat exchange pipes 179 for nesting the heat exchange pipes 179, and an edge 2232 and the inner wall of the cavity

194 leave a gap therebetween to form an opening 224 on the periphery for the cold water to pass through. A gap 225 is formed between any two closest spoilers 222 and 223, and the openings 2222 and 224 do not overlap each other in the main surface direction of the spoilers 222 or 223. After entering the cavity 194 through the cold water inlet 192, the cold water is blocked by the spoiler 222 to enter the gap 225 between the baffle plates/sheets 222 and 223 from the opening 2222, and then the cold water flows from the center to the periphery, and flows upwards through the spoiler 223 and the opening 224. The cold water is once again blocked by the spoiler 222 in the upper layer to flow from the periphery to the center, and flows upwards through the opening 2222 of spoiler 222. The process is repeated until the cold water flows out from the tepid water outlet 193. In the meantime, the cold water circuitously flows through the plurality of heat exchange pipes 179 and exchanges heat with the hot wastewater flowing reversely therein, and the spoilers 222 and 223 constantly change the flow direction of the cold water, to generate turbulence effects, which are helpful to improve the heat exchange efficiency. To further improve the efficiency, one or more heat transfer sheets 226 as shown in FIG. 55 can optionally be added between the spoilers 222 and 223. The heat transfer sheets 226 are made of metal and are disc-like, which have a plurality of through holes 2261 corresponding to the heat exchange pipes 179 for nesting and thermally contacting the heat exchange pipes 179 and form a central opening 2262 for cold water to pass through, and an edge 2263 and the inner wall of the cavity 194 leave a gap therebetween to form an opening 227 at the periphery for cold water to pass through. When passing through the gap 225 between any two closest spoilers 222 and 223, the cold water flows through two main surfaces of the heat transfer sheets 226 in parallel, and exchanges heat with hot wastewater in the pipes by means of the heat transfer sheets 226 and the plurality of heat exchange pipes 179 in good thermal contact therewith. The heat transfer sheets 226 significantly increase the heat exchange surface of the cold water, thereby improving the efficiency of the heat exchanger 165. To further increase the heat exchange surface of the cold water, the spoilers 222 and 223 can also optionally be made of metal and thermally contact the plurality of metal pipes 179.

[0257] FIGS. 56-57 illustrate a structure of a nineteenth embodiment of a thermal conductive baffle according to the present invention. The baffle 231 is similar to the baffle 221 in the eighteenth embodiment, and their difference merely lies in that a net-like flow restrictor 232 is disposed between two adjacent parallel sheet-like objects 222, 223 or 226 of the baffle 231, where the net-like flow restrictor 232 is also disc-like and is made by blanking a metal mesh as shown in FIG. 25. The net-like flow restrictor 232 has a plurality of through holes 2323 corresponding to the heat exchange pipes 179 for nesting and thermally contacting the heat exchange pipes 179. The manner in which the cold water passes through the baffle 231 is substantially the same as that in which the cold water passes through the baffle 221, but if the cold water encounters the net-like flow restrictor 232 when passing through a fluid channel formed by two adjacent parallel sheet-like objects 222, 223 or 226 and the plurality of heat exchange pipes 179, the cold water may flow through gaps between the metal wires 2321 and 2322. Thus, the heat exchange surface of the cold water can be increased and further generate turbulence effects, which are helpful to improve the heat exchange efficiency.

[0258] FIGS. 58-61 illustrate a structure of a twentieth embodiment of a thermal conductive baffle according to the present invention. The baffle 241 is similar to the baffle 221 in the fifteenth embodiment, and their difference merely lies in that a plurality of parallel grooves 2423, 2432 and 2443 are disposed on upper and lower surfaces of sheet-like objects 242, 243 and 244 of the baffle 241 respectively. Similarly, the spoiler 242 includes a plurality of through holes 2421 corresponding to the heat exchange pipes 179 for nesting and thermally contacting the heat exchange pipes 179 and a central opening 2422; the spoiler 243 also has a plurality of through holes 2431 corresponding to the heat exchange pipes 179 for nesting the heat exchange pipes 179; the heat transfer sheet 224 includes a plurality of through holes 2441 corresponding to the heat exchange pipes 179 for nesting and thermally contacting the heat exchange pipes 179 and also a central opening 2442. The groove 2243 of the heat transfer sheet 224 increases the heat exchange surface of the cold water, and the grooves of the baffle sheet like objects 242, 243 and 244 constantly change the flow direction of the cold water, to further generate turbulence effects, which are helpful to improve the heat exchange efficiency. To further increase the heat exchange efficiency, the spoliars 242 and 243 can optionally be made of metal and thermally contact the plurality of heat exchange pipes 179.

[0259] FIGS. 62-63 illustrate a structure of a twenty-first embodiment of a thermal conductive baffle according to the present invention. The baffle 251 is formed by superposition of a plurality of net-like flow restrictor 232. The specific structure of the net-like flow restrictor 232 has been described previously, which is not repeated herein.

[0260] FIGS. 64-66 illustrate a structure of a twenty-second embodiment of the thermal conductive baffle according to the present invention. The baffle 261 is formed by superposition of a plurality of net-like flow restrictor 262. The net-like flow restrictor 262 is made by blanking a metal mesh as shown in FIG. 25. The net-like flow restrictor 262 have a plurality of through holes 2623 corresponding to the heat exchange pipes 179 for nesting and thermally contacting the heat exchange pipes 179. The net-like flow restrictor 262 are constructed to form rings having substantially the same width with the through holes 2623 as centers, and further form a central hole 2624 in the center of the net-like flow restrictor 262. Correspondingly, shapes coupled to the rings are formed on the inner wall 264 of the cavity 194, such that the baffle 261 clings to the inner wall of the cavity when being assembled into the cavity 194. In addition, a center rod 263 can be inserted into the central hole 2624 of the baffle 261 to prevent the cold water from flowing through the central hole. Distances between portion of the baffle 261 for the cold water to flow through and the heat exchange pipe are substantially uniform, thus avoid the situation where heat exchange of the cold water in different portion of the baffle 261 is non-uniform.

[0261] FIGS. 67-68 illustrate a structure of a twenty-third embodiment of the baffle having a thermal conductive baffle according to the present invention. The baffle 271 is formed by superposition of a plurality of net-like spoliars 272, where the structure of the net-like spoliars 272 is basically similar to that of the net-like spoliars 232 in the seventeenth embodiment, and their difference merely lies in that, in the net-like spoliars 272, metal wires in other peripheral parts 2721 and a central part 2723 are flattened except the rings having substantially the same width center to the through holes 2722 to

close meshes and prevent the cold water from flowing there through. Therefore, distances between parts of the baffle 271 for the cold water to flow through and the heat exchange pipe are substantially uniform, and thus avoid the situation where heat exchange of the cold water in different parts of the baffle 271 is non-uniform.

[0262] FIGS. 69-71 illustrate a fourth embodiment of the heat exchanger according to the present invention. The heat exchanger 280 is detachably disposed in a drain hole 295 of a bathroom floor drain device 283. The heat exchanger 280 has a wastewater collector opening 291, a wastewater collector cavity 292 and a plurality of wastewater collector outlets 293. Hot wastewater generated after shower enters the wastewater collector opening 291 and flows into the wastewater collector cavity 292 from the drain hole 295, then passes through the heat exchanger 280 in parallel in a plurality of wastewater channels 298 formed in a plurality of heat exchange pipes 296, and is further discharged to a drain pipe (not shown) of the building through a drain port 299 of the drain device 283.

[0263] FIGS. 70-72 illustrate an assembly structure of the heat exchanger 280. The heat exchanger 280 includes a main body 301 and a leakproof shell 302. As shown in FIG. 72, cold water is introduced from a cold water inlet 303, passes through a cavity 304, and then is exported from a tepid water outlet 305. In the meantime, the cold water exchanges heat with hot wastewater passing through the wastewater channels 298 through the plurality of heat exchange pipes 296. Any one of the foregoing thermal conductive baffle can be disposed in the cavity 304 to increase the heat exchange efficiency.

[0264] As shown in FIGS. 73 and 74, the heat exchange pipes 296 are formed by mutual nesting of two metal pipes, i.e., an internal metal pipe 306 and an external metal pipe 307, where a bottom outer wall of the internal metal pipe 306 is in a sealed connection with the leakproof shell 302, and the bottom of an outer wall of the external metal pipe 307 is in a sealed connection with a bottom shell 308 of the main body 301. When there is leakage from the external metal pipe 307, the cold water may flow into a cavity formed between an outer wall of the main body 301 and an inner wall of the leak proof shell 302 through a micro-channel 309 formed between the internal metal pipe 306 and the external metal pipe 307, and then flows out from a leakage alarm hole 310 located above the heat exchange pipes 296 and in adjacent to a wastewater opening 301. The user can notice the leakage in the bathroom and thus notify technicians for repair or replacement.

[0265] FIGS. 75-76 illustrate a fifth embodiment of the heat exchanger according to the present invention. The heat exchanger 380 is installed to the bottom of a water catch 370, and the water catch 370 has a platform 371, a periphery 372 and a water catch outlet 375. The water catch 370 is disposed on a shower room floor 378. During operation, a person taking a shower stands on the platform 371, and hot wastewater generated during shower is collected by the platform 371 and the periphery 372, and flows out from the water catch outlet 375.

[0266] FIG. 77 illustrates a structure of the heat exchanger 380, including a wastewater collector 381 and a heat exchanger main body 386. The wastewater collector 381 has an opening 382, a cavity 383 and a plurality of wastewater outlets 384, where the opening 382 is located above the plurality of wastewater outlets 384, and covers all the wastewater outlets 384 in a horizontal direction; the main body 386 includes a housing 387 and a plurality of metal pipes 391, where the housing 387 has a cold water (second fluid) inlet

395, a tepid water (preheated second fluid) outlet **396** and a cold water conduit **390** between the cold water inlet **395** and the tepid water outlet **396**; the plurality of metal pipes **391** are disposed in the cold water conduit **390** of which the plurality of metal pipes **391** passes through the housing **387** and forms, in the cold water conduit **390**, a plurality of wastewater (first fluid) channels **392** for the hot wastewater to pass through in parallel. The plurality of wastewater channels **392** communicates with the plurality of wastewater outlets **384** of the wastewater collector **381** respectively. Wastewater, after flowing out from the water collector catch **375**, enters the cavity **383** through the opening **382** of the wastewater collector **381**, then passes through the plurality of wastewater channels **392** in parallel, and finally flows from a gap **376** (FIG. 75) to a bathroom drain port **377** in the bottom of the water catch **370**.

[0267] In use of the heat exchanger **380**, the cold water inlet **395** is directly or indirectly connected to a cold water source (not shown) of the building, and the tepid water outlet **396** is connected to a bathroom heater (not shown) or a mixing valve (not shown).

[0268] In the meantime, the cold water is introduced from the cold water inlet **395** to flow through a cold water channel **400** from right to left, and exchanges heat with hot wastewater flowing through the hot wastewater channels **392** by means of the metal pipes **391**, such that the temperature of the cold water is changed and the cold water becomes preheated water, and then is exported from the tepid water outlet **396** and provided to the bathroom heater or the mixing valve (not shown) for use.

[0269] As shown in FIG. 77, waste water channels **392** is flat, and has a major axis and a minor axis, where its centerlines are basically arranged horizontally, and the major axis is also arranged horizontally. The vertical height (minor axis) is designed so that wastewater flowing therein is in contact with both its upper and lower surfaces. In one example, when a vertical height (minor axis) of the wastewater channel **392** is less than 6.5 mm, even if the wastewater is flowing at an extremely low flow rate or even is almost stationary, due to resistance of the pipe wall and surface tension of the water, the wastewater passing through may still simultaneously contact two surfaces on the top and in the bottom of the waste water channel **392**. This ensures that the hot wastewater still has a sufficient heat exchange surface even if at a low flow rate.

[0270] Optionally, the metal pipes **391** as shown in FIG. 77 may be formed by mutual nesting of an internal metal pipe and an external metal pipe as illustrated in the third embodiment (FIG. 48). The internal and external metal pipes maintain good thermal contact therebetween, and leave a micro-channel for the cold water to pass through. Under normal conditions, no cold water flows through the micro-channel **394**; however, when the external metal pipe is damaged, the cold water may enter the leak proof shell **398** through the micro-channel **394**, and flow out from an alarm hole **401** (FIG. 77), located above the metal pipes **391**, of the water catch **370** through a connecting pipe **399** (FIG. 76) to alert the user.

[0271] After operating for a period of time, it is inevitable that fouling is accumulated on the inner walls of the wastewater channels **392**, which affects efficiency of heat recovery. As the opening **382** of the collector covers all the wastewater outlets **384** in a horizontal direction, the user can wash away the fouling by removing a baffle plate **502** and insert straight pipe **202** connecting pressurized water (For example, the

other end is directly communicated to the cold water feed of the shower) as shown in the third embodiment (FIG. 9) into the wastewater outlets **384**.

[0272] As shown in FIG. 78, a protruding baffle structure **402** may be formed on the inner walls of the wastewater channels **392** to improve the heat exchange efficiency, whereas the function and manufacturing method are substantially the same as those of the baffle structure shown in FIG. 38, and hence are not repeated herein.

[0273] To further improve the efficiency of the heat exchanger **386**, various described a thermal conductive baffle can be added to the cold water cavity **400**, which is not repeated herein.

[0274] An energy recovery device of the present invention including various heat exchangers stated above is described below.

[0275] The energy recovery device further includes an external temperature-varying apparatus (not shown), where cold clean water (second fluid) after heat exchanged in the heat exchanger is introduced into the external temperature-varying apparatus, such that the temperature of the second fluid is changed to a suitable operating temperature, and the second fluid, after use, serves as hot wastewater (first fluid) introduced into the heat exchanger.

[0276] The external temperature-varying apparatus includes a heater or a cooler (not shown). The external temperature-varying apparatus includes a fluid mixer for mixing the cold water (second fluid) after heat exchanged with an external preheated or pre-cooled third fluid to change the temperature.

[0277] The heat exchanger can be installed to the bottom of a bathtub or a sink of a washing facility or a base of a shower, or is integrally formed with the base of the shower or the sink, to receive hot wastewater generated in shower or washing.

1-34. (canceled)

35. A heat exchanger comprising:

- a first fluid tube through which a first fluid of a first temperature flows;
- a baffle located in the first fluid tube for moderating flow of the first fluid passing therethrough;
- wherein the heat exchanger is configured for communicating thermal energy between the first fluid and an environment external of the first fluid tube having a different temperature to the first fluid.

36. A heat exchanger according to claim 35, wherein the baffle is configured to include at least one formation selected from a group comprising

- at least one elongate member extending in a direction of radially to or along said at least one first fluid tube;
- at least one protrusion extending radially from a wall of said at least one first fluid tube, wherein the protrusion is integrally formed or detachably mounted thereon;
- at least one protrusion extending in a direction of along a wall of said at least one first fluid tube, the protrusion being integrally formed or detachably mounted thereon;
- at least one spiral guiding structure extending along said at least one first fluid tube; and
- at least one sleeve extending along said at least one first fluid tube.

37. A heat exchanger according to claim 35, wherein the baffle comprises at least one elongate member extending around or about said at least one first fluid tube or along the

direction of the longitudinal axis of said at least one first fluid tube, and said elongate member(s) is selected from the group of configurations comprising:

- an at least one elongate member including annular or spiral protrusions thereon;
- an at least one elongate member arranged in one or more spiral elements which extend around the inner circumference of said at least one first fluid tube or along the longitudinal axis of said at least one first fluid tube;
- at least one elongate member arranged in one or more spiral elements which extend around the inner circumference of said at least one first fluid tube or along the longitudinal axis of said at least one first fluid tube, and extends about a core in an interengaged spiral arrangement, in a longitudinal direction along said at least one first fluid tube;
- at least one elongate member extending in a spiral arrangement;
- at least one elongate member including circumferential helical grooves formed therein, and both the elongate member and the grooves extending in a direction of along said at least one first fluid tube;
- at least one elongate member wrapping about the longitudinal axis and along said at least one first fluid tube, wherein the first fluid tube has generally elliptical cross profile formed by compression of a fluid tube having a generally circular cross section profile; and
- at least one elongate member forming two layers in said at least one first fluid tube, wherein each of the layers comprising a plurality of elongate members each extending in a common direction, the common direction of the elongate members of the two layers are different from each other, at least one end of the elongate member is covered or forms a slope to reduce accumulation of fouling thereon.

38. A heat exchanger according to claim **37**, wherein the baffle further includes at least one sleeve extending along said at least one first fluid tube.

39. A heat exchanger according to claim **35**, wherein the baffle includes at least one disc disposed within said at least one first fluid tube, the disc including protrusions thereon to define a plurality of flow paths.

40. A heat exchanger according to claim **37**, wherein the baffle includes at least one disc disposed within said at least one first fluid tube, the disc including protrusions thereon to define a plurality of flow paths.

41. A heat exchanger according to claim **35**, wherein at least one inlet of one of the fluid tube of the heat exchanger is configured for receiving a cleaning tube through an opening formed therein, the cleaning tube directing a fluid stream for displacing deposits formed within the heat exchanger.

42. A heat exchanger according to claim **35**, further comprising:

- at least one second fluid tube through which a second fluid of a second temperature flows and including a baffle therein for moderating flow of the second fluid passing therethrough;

wherein the heat exchanger is configured for communicating thermal energy between the first fluid and environment external thereof.

43. A heat exchanger according to claim **42**, wherein the baffle is configured to include at least one formation selected from a group comprising:

- at least one elongate member extending in a direction of radially or at least along at least one of the fluid tubes;
- at least one protrusion extending radially from a wall of at least one fluid tubes, wherein the protrusion is integrally formed or detachably mounted thereon;
- at least one protrusion extending in a direction of along a wall of at least one of the fluid tubes, the protrusion being integrally formed or detachably mounted thereon;
- at least one spiral guiding structure extending along at least one of the fluid; and
- at least one sleeve extending along at least one of the fluid tubes.

44. A heat exchanger according to claim **42**, wherein the at least one baffle comprises at least one elongate member extending around or about the axis of at least one of the fluid tubes or along the direction of the axis of the fluid tubes, and said elongate member(s) is selected from a group comprising:

- at least one elongate member including annular or spiral protrusions thereon;
- at least one elongate member formed in one or more spiral elements extending around the inner circumference of at least one of the fluid tubes or along the longitudinal axis of at least one of the fluid tubes;
- at least one elongate member formed in one or more spiral elements extending around the inner circumference of at least one of the fluid tubes or along the longitudinal axis of at least one of the fluid tubes, and extending about a core in an interengaged spiral arrangement, in a longitudinal direction along at least one of the fluid tubes;
- at least one elongate member extending in a spiral arrangement;
- at least one elongate member having circumferential helical grooves formed therein, and both the elongate member and the grooves extending in a direction of along at least one of the fluid tubes;
- at least one elongate member wrapped about the longitudinal axis and along at least one of the fluid tubes, wherein the first fluid tube has generally elliptical cross profile formed by compression of a fluid tube having a generally circular cross section profile; and
- at least one elongate member forming two layers in at least one of the fluid tubes, wherein each of the layers comprising a plurality of elongate members each extending in a common direction, the common direction of the elongate members of the two layers are different from each other, at least one end of the elongate member is covered or form a slope to reduce accumulation of fouling thereon.

45. A heat exchanger according to claim **44**, wherein the baffle further includes at least one sleeve extending along at least one of the fluid tubes.

46. A heat exchanger according to claim **42**, wherein at least one baffle includes at least one disc disposed within one of the said fluid tube, the disc including protrusions thereon to define a plurality of flow paths.

47. A heat exchanger according to claim **42**, wherein at least one inlet of one of the fluid tube of the heat exchanger is configured for receiving a cleaning tube through an opening formed therein, the cleaning tube directing a stream of fluid for displacing deposits formed within the heat exchanger.

48. A heat exchanger according to claim **47**, further comprising a fluid collector, wherein the fluid collector includes an opening for collecting fluid, and at least one inlet of one of

the first and/or second fluid tubes is configured for receiving the cleaning tube through the opening of the fluid collector.

49. A heat exchanger according to claim **35**, wherein the baffle includes at least one protrusion extending radially from a wall of at least one of the fluid tubes in an annular or spiral arrangement,

wherein the protrusions extend in an annular or spiral arrangement along, about or within at least one of the fluid tubes; and

wherein the protrusions extending in a spiral arrangement to include a plurality of spaces therebetween, the spaces being substantially aligned to create a turbulent flow with the spiral flow.

50. The heat exchanger according to claim **35** further comprising a liquid distribution manifold having at least one protrusion which is located proximate the inlet of said first fluid tube,

wherein the liquid distribution manifold includes a vent in communication with said at least one of the protrusions for communicating a gas flow spaced apart from the liquid flow by the vent, and

wherein the manifold distributes liquid into the first fluid tube via at least one or more passageways defined therein.

51. The heat exchanger according to claim **41** further comprising a liquid distribution manifold having at least one protrusion which is located proximate the inlet of said first fluid tube,

wherein the liquid distribution manifold includes a vent in communication with said at least one of the protrusions for communicating a gas flow spaced apart from the liquid flow by the vent, and

wherein the manifold distributes liquid into the first fluid tube via at least one or more passageways defined therein.

* * * * *