



(19) **United States**

(12) **Patent Application Publication**  
**Mindell et al.**

(10) **Pub. No.: US 2016/0363659 A1**

(43) **Pub. Date: Dec. 15, 2016**

(54) **HIGH-PRECISION TIME OF FLIGHT MEASUREMENT SYSTEMS**

(71) Applicant: **HUMATICS CORPORATION**,  
Cambridge, MA (US)

(72) Inventors: **David A. Mindell**, Cambridge, MA (US); **Gregory L. Charvat**, Guilford, CT (US); **Gary A. Cohen**, Boston, MA (US); **Dana R. Yoerger**, Woods Hole, MA (US)

(21) Appl. No.: **15/181,930**

(22) Filed: **Jun. 14, 2016**

**Related U.S. Application Data**

(63) Continuation of application No. 62/175,819, filed on Jun. 15, 2015.

(60) Provisional application No. 62/198,633, filed on Jul. 29, 2015, provisional application No. 62/243,264, filed on Oct. 19, 2015, provisional application No. 62/253,983, filed on Nov. 11, 2015, provisional application No. 62/268,727, filed on Dec. 17, 2015, provisional application No. 62/268,734, filed on Dec. 17, 2015, provisional application No. 62/268,736, filed on Dec. 17, 2015, provisional application No. 62/268,741, filed on Dec. 17, 2015, provisional ap-

plication No. 62/268,745, filed on Dec. 17, 2015, provisional application No. 62/271,136, filed on Dec. 22, 2015, provisional application No. 62/275,400, filed on Jan. 6, 2016, provisional application No. 62/306,469, filed on Mar. 10, 2016, provisional application No. 62/306,478, filed on Mar. 10, 2016, provisional application No. 62/306,483, filed on Mar. 10, 2016.


**Publication Classification**

(51) **Int. Cl.**  
**G01S 13/34** (2006.01)  
**G01S 7/35** (2006.01)  
(52) **U.S. Cl.**  
CPC ..... **G01S 13/34** (2013.01); **G01S 7/352** (2013.01); **G01S 2007/358** (2013.01); **G01S 2007/356** (2013.01)

(57) **ABSTRACT**

A system and method is disclosed for measuring time of flight to an object. A transmitter transmits an electromagnetic signal and provides a reference signal corresponding to the electromagnetic signal. A receiver receives the electromagnetic signal and provides a response signal corresponding to the received electromagnetic signal. A detection circuit is configured to determine a time of flight between the transmitter and the receiver based upon the reference signal and the response signal.

**TIME OF FLIGHT**






FIG. 1

FMCW

200




FIG. 2

MODULATION RANGING




FIG. 3

800




FIG. 4

FHSS FMCW

400





FIG. 5



500

FIG. 6





FIG. 7





700

FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15






FIG. 16





FIG. 17



## HIGH-PRECISION TIME OF FLIGHT MEASUREMENT SYSTEMS

### CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of co-pending U.S. provisional application Ser. No. 62/175,819 filed Jun. 15, 2015; 62/198,633 filed Jul. 29, 2015; 62/243,264 filed Oct. 19, 2015; 62/253,983 filed Nov. 11, 2015; 62/268,727, 62/268,734, 62/268,736, 62/268,741, and 62/268,745, each filed Dec. 17, 2015; 62/271,136 filed Dec. 22, 2015; 62/275,400 filed Jan. 6, 2016; and 62/306,469, 62/306,478, and 62/306,483, each filed Mar. 10, 2016, each of which is herein incorporated by reference in its entirety for all purposes.

### BACKGROUND

[0002] 1. Field of the Disclosure

[0003] The present disclosure generally relates to distance measurements, and more particularly to measuring distances using electromagnetic signals.

[0004] 2. Discussion of Related Art

[0005] Tracking and ranging of an object typically relies on reflected signals from the object, as in radar tracking and ranging, and yields only bulk information about the relative position and movements of the object. Orientation of the object is difficult to perceive with such systems, and visual or imaging systems yield only slightly better results because they tend to be limited to two dimensional images of the object which may mislead a system or observer as to the actual orientation of the object. There exists a need for a system able to yield precise information about the range (distance) to an object, which allows precise sensing of changes, precise tracking of motion, and, when implemented to locate various parts of the object, may precisely determine orientation of the object.

### SUMMARY

[0006] Aspects and embodiments relate to measuring time of flight and, in particular, measuring time of flight by electromagnetic signals.

[0007] In one aspect, a system for measuring time of flight to an object includes at least one transmitter configured to transmit an electromagnetic signal and provide a reference signal corresponding to the electromagnetic signal, at least one receiver configured to receive the electromagnetic signal and in response provide a response signal corresponding to the received electromagnetic signal, and a detection circuit configured to determine a time of flight between the transmitter and the receiver based upon the reference signal and the response signal.

[0008] In some embodiments the detection circuit is further configured to determine a distance between the transmitter and the receiver based at least in part upon the time of flight. In some embodiments the electromagnetic signal is a frequency modulated continuous wave (FMCW) signal, a direct sequence spread spectrum signal (DSSS), a pulse compressed signal, or a frequency hopping spread spectrum (FHSS) signal. In some embodiments the detection circuit includes a mixer that receives the reference signal and the response signal, and provides a beat signal corresponding to the time of flight between the transmitter and the receiver. In some embodiments the detection circuit also includes an

analog to digital converter that receives the beat signal and provides a sampled beat signal, and includes a processor coupled to an output of the analog to digital converter that receives the sampled beat signal and performs a fast Fourier transform on the sampled beat signal.

[0009] In some embodiments the system includes a cable coupled between the detection circuit and at least one of the transmitter and the receiver, the cable configured to convey to the detection circuit at least one of the reference signal and the response signal. In some embodiments the detection circuit is configured to wirelessly receive at least one of the reference signal and the response signal.

[0010] In some embodiments the transmitter includes a pseudo noise generator.

[0011] In some embodiments the transmitter is configured to transmit and the receiver is configured to receive the electromagnetic signal having one of a command protocol and an embedded unique code in the electromagnetic signal to address and enable each receiver.

[0012] In some embodiments the receiver includes an auxiliary wireless receiver configured to receive an auxiliary wireless signal configured with a unique code to target the receiver, and the receiver is configured to power up the receiver to provide the response signal when the receiver has received the auxiliary wireless signal and not to provide the response signal when the receiver has not received the auxiliary wireless signal. In some embodiments the auxiliary wireless receiver is configured to receive the auxiliary wireless signal as a Bluetooth signal, a Zigbee signal, a Wi-Fi signal, or a cellular signal.

[0013] In some embodiments the receiver includes at least one antenna configured to receive the electromagnetic signal at a first frequency, and a multiplier coupled to the at least one antenna to receive the electromagnetic signal at the first frequency and that provides a multiplied signal having a harmonic component at a second frequency that is a harmonic multiple of the first frequency. In some embodiments the receiver includes a power source that is configured to normally bias the multiplier to a biased off state and that is configured to bias on the multiplier to an on state in response to receipt of the auxiliary wireless signal configured with the unique code to target the receiver. In some embodiments the power source is further configured to forward bias the multiplier to increase a sensitivity and range of the receiver. In some embodiments the receiver has no active components other than the multiplier, which is configured to normally be off so as to require substantially no power. In some embodiments the power source is one of a low power battery source or power is derived by one or more energy harvesting techniques. In some embodiments the antenna comprises a single antenna for both receiving the electromagnetic signal at the first frequency and transmitting the multiplied signal at the second frequency. In some embodiments the receiver includes the multiplier integrated with the antenna element.

[0014] In some embodiments the transmitter includes a plurality of receive channels configured to receive the electromagnetic signal at the second frequency in a spatially diverse array. In some embodiments the plurality of receive channels can either be multiplexed to receive the electromagnetic signal at the second frequency at different times or can be configured to operate simultaneously.

[0015] In some embodiments the transmitter is configured to provide a modulated electromagnetic signal and the

receiver is configured to receive the modulated electromagnetic signal to uniquely address the receiver.

[0016] In some embodiments the transmitter and the receiver are configured to operate simultaneously.

[0017] In some embodiments the transmitter comprises in phase and 90° out of phase (quadrature) channels with multipliers that are modulated in quadrature to send coded electromagnetic signals to a plurality of receivers simultaneously.

[0018] In some embodiments the at least one receiver includes a plurality of receivers and the at least one transmitter and the plurality of receivers are configured to time share and uniquely address each receiver of the plurality of receivers.

[0019] In some embodiments the at least one receiver includes a plurality of receivers and the at least one transmitter and the plurality of receivers are configured to dynamically assess and address the plurality of receivers that are moving faster than others more frequently.

[0020] In some embodiments the at least one receiver includes a plurality of receivers and the at least one transmitter and the plurality of receivers are configured with their own proprietary micro-location frequency allocation protocol so that the receiver and at least one transmitter can operate at unused frequency bands that exist amongst existing allocated frequency bands. In some embodiments the at least one transmitter and the plurality of receivers are configured to license-free bands. In some embodiments the at least one transmitter and the plurality of receivers are configured to communicate with existing systems at existing licensed frequencies to use existing frequency allocations in situations that warrant using existing frequency band allocations. In some embodiments the at least one transmitter and the plurality of receivers are configured to detect loading issues within any used frequency band and to allocate signals to be used based on system usage.

[0021] In some embodiments the system includes a plurality of transmitters configured to transmit a plurality of electromagnetic signals, and the detection circuit is configured to determine one or more distances between the receiver and one or more of the transmitters.

[0022] In some embodiments the detection circuit is further configured to determine a position of the receiver at least in part from one or more of the one or more distances.

[0023] In some embodiments the system includes a plurality of transmitters configured to transmit a plurality of electromagnetic signals, and the detection circuit is configured to determine one or more time differences of arrival between two or more of the plurality of electromagnetic signals. In some embodiments the detection circuit is further configured to determine a position of the receiver at least in part from one or more of the one or more time differences of arrival.

[0024] In another aspect, a method of measuring time of flight to an object includes receiving a reference signal from an interrogator, the reference signal corresponding to an electromagnetic signal transmitted by the interrogator, receiving a response signal from a transponder, the response signal provided by the transponder in response to receiving the electromagnetic signal, and the response signal corresponding to the received electromagnetic signal, and determining a time of flight of the electromagnetic signal between the interrogator and the transponder based upon the reference signal and the response signal.

[0025] In some embodiments the method includes determining the distance between the interrogator and the transponder based at least in part upon the time of flight.

[0026] In some embodiments the electromagnetic signal is a frequency modulated continuous wave (FMCW) signal, a direct sequence spread spectrum (DSSS) signal, a pulse compressed signal, or a frequency hopping spread spectrum (FHSS) signal.

[0027] In some embodiments determining the time of flight includes mixing the response signal and the reference signal to provide a beat signal corresponding to the time of flight. In some embodiments the method includes converting the beat signal into a digital form to provide a sampled beat signal and performing a fast Fourier transform on the sampled beat signal.

[0028] In some embodiments at least one of the reference signal and the response signal are received via a cable. In some embodiments at least one of the reference signal and the response signal are received wirelessly.

[0029] In some embodiments the electromagnetic signal is generated, at least in part, from a pseudo noise generator.

[0030] In some embodiments the response signal is received from the transponder only when the transponder has received an auxiliary signal, and the response signal is not received from the transponder when the transponder has not received the auxiliary signal. In some embodiments the auxiliary signal is a Bluetooth signal, a Zigbee signal, a Wi-Fi signal, a cellular signal, or a unique code.

[0031] In some embodiments the method includes receiving a plurality of response signals from the transponder, each of the plurality of response signals provided in response to receiving one of a plurality of electromagnetic signals from a plurality of interrogators, and determining one or more distances between the transponder and one or more of the plurality of interrogators. In some embodiments the method includes determining a position of the transponder at least in part from one or more of the one or more distances.

[0032] In some embodiments the method includes receiving a plurality of response signals from the transponder, each of the plurality of response signals provided in response to receiving one of a plurality of electromagnetic signals from a plurality of interrogators, and determining one or more time differences of arrival between two or more of the plurality of electromagnetic signals. In some embodiments the method includes determining a position of the transponder at least in part from one or more of the one or more time differences of arrival.

[0033] Still other aspects, embodiments, and advantages of these exemplary aspects and embodiments are discussed in detail below. Embodiments disclosed herein may be combined with other embodiments in any manner consistent with at least one of the principles disclosed herein, and references to “an embodiment,” “some embodiments,” “an alternate embodiment,” “various embodiments,” “one embodiment” or the like are not necessarily mutually exclusive and are intended to indicate that a particular feature, structure, or characteristic described may be included in at least one embodiment. The appearances of such terms herein are not necessarily all referring to the same embodiment.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0034] Various aspects of at least one embodiment are discussed below with reference to the accompanying figures, which are not intended to be drawn to scale. The figures are

included to provide illustration and a further understanding of the various aspects and embodiments, and are incorporated in and constitute a part of this specification, but are not intended as a definition of the limits of the invention. In the figures, each identical or nearly identical component that is illustrated in various figures is represented by a like numeral. For purposes of clarity, not every component may be labeled in every figure.

[0035] In the Figures:

[0036] FIG. 1 illustrates one embodiment of a system for measuring distance with precision based on a bi-static ranging system configuration for measuring a direct time-of-flight (TOF);

[0037] FIG. 2 illustrates one embodiment of a system for measuring distance with precision based on frequency modulated continuous wave (FMCW) TOF signals;

[0038] FIG. 3 illustrates one embodiment of a system for measuring distance with precision based on direct sequence spread spectrum (DSSS) TOF signals;

[0039] FIG. 4 illustrates one embodiment of a system for measuring distance with precision based on wide-band, ultra-wide-band pulsed signals, or any pulse compressed waveform;

[0040] FIG. 5 illustrates one embodiment of a system for measuring distance with precision based on DSSS or frequency hopping spread spectrum (FHSS) FMCW ranging techniques;

[0041] FIG. 6 illustrates one embodiment of a system for measuring distance with precision with TOF signals having multiple transmitters, multiple transceivers, or a hybrid combination of transmitter and transceivers;

[0042] FIG. 7 illustrates one embodiment of a system for measuring distance with precision with TOF signals having multiple receivers, multiple transponders, or a hybrid combination of receivers and transponders;

[0043] FIG. 8 illustrates one embodiment of a system for measuring distance with precision with TOF signals having multiple transmitters, multiple transceivers, or a hybrid combination of transmitter and transceivers and well as multiple receivers, multiple transponders, or a hybrid combination of receivers and transponders;

[0044] FIG. 9 illustrates one embodiment of a system for measuring location with precision with modulated TOF signals;

[0045] FIG. 10 illustrates another embodiment of a system for measuring location with precision with modulated TOF signals;

[0046] FIG. 11 illustrates a block diagram of an interrogator for linear FMCW two-way TOF ranging;

[0047] FIG. 12 illustrates another embodiment of a block diagram of an interrogator for linear FMCW two-way TOF ranging;

[0048] FIG. 13 illustrates one embodiment of a system for measuring distance with precision with TOF signals for detecting a user's body movement in cooperation with an industrial automation environment;

[0049] FIG. 14 illustrates one embodiment of a system for measuring distance with precision with TOF signals for measuring cell phone-to-cell phone or cell phone-to-object metrics;

[0050] FIG. 15 illustrates one embodiment of a system for measuring distance with precision with TOF signals for guiding an unmanned aerial vehicle for delivering a package or object;

[0051] FIG. 16 illustrates one embodiment of a system for measuring distance with precision with TOF signals for guiding an unmanned aerial vehicle with a beacon;

[0052] FIG. 17 illustrates one embodiment of a system for measuring distance with precision with TOF signals for guiding a vehicle along a roadway, with respect to other vehicles and objects and for maneuvering an intersection; and

[0053] FIG. 18 illustrates one embodiment of a system for measuring distance with precision with TOF signals for monitoring a bridge or other structure.

#### DETAILED DESCRIPTION

[0054] It is to be appreciated that embodiments of the methods and apparatuses discussed herein are not limited in application to the details of construction and the arrangement of components set forth in the following description or illustrated in the accompanying drawings. The methods and apparatuses are capable of implementation in other embodiments and of being practiced or of being carried out in various ways. Examples of specific implementations are provided herein for illustrative purposes only and are not intended to be limiting. Also, the phraseology and terminology used herein is for the purpose of description and should not be regarded as limiting. The use herein of "including," "comprising," "having," "containing," "involving," and variations thereof is meant to encompass the items listed thereafter and equivalents thereof as well as additional items. References to "or" may be construed as inclusive so that any terms described using "or" may indicate any of a single, more than one, and all of the described terms. Any references to front and back, left and right, top and bottom, upper and lower, and vertical and horizontal are intended for convenience of description, not to limit the present systems and methods or their components to any one positional or spatial orientation.

#### DEFINITIONS

[0055] A transceiver is a device comprising both a transmitter (an electronic device that, with the aid of an antenna, produces electromagnetic signals) and a receiver (an electronic device that, with the aid of an antenna, receives electromagnetic signals and converts the information carried by them to a usable form) that share common circuitry.

A transmitter-receiver is a device comprising both a transmitter and a receiver that are combined but do not share common circuitry.

A transmitter is a transmit-only device, but may refer to transmit components of a transmitter-receiver, a transceiver, or a transponder.

A receiver is a receive-only device, but may refer to receive components of a transmitter-receiver, a transceiver, or a transponder.

A transponder is a device that emits a signal in response to receiving an interrogating signal identifying the transponder and received from a transmitter.

Radar (for Radio Detection and Ranging) is an object-detection system that uses electromagnetic signals to determine the range, altitude, direction, or speed of objects. For purposes of this disclosure, "radar" refers to primary or "classical" radar, where a transmitter emits radiofrequency

signals in a predetermined direction or directions, and a receiver listens for signals, or echoes, that are reflected back from an object.

Radio frequency signal or “RF signal” refers to electromagnetic signals in the RF signal spectrum that can be CW or pulsed or any form.

Pulse Compression or pulse compressed signal refers to any coded, arbitrary, or otherwise time-varying waveform to be used for Time-of-Flight (TOF) measurements, including but not limited to FMCW, Linear FM, pulsed CW, Impulse, Barker codes, and any other coded waveform.

Wired refers to a network of transmitters, transceivers, receivers, transponders, or any combination thereof, that are connected by a physical waveguide such as a cable to a central processor.

Wireless refers to a network of transmitters, transceivers, receivers, transponders, or any combination thereof that are connected only by electromagnetic signals transmitted and received wirelessly, not by physical waveguide.

Calibrating the network refers to measuring distances between a transmitters, transceivers, receivers, transponders, or any combination thereof.

High precision ranging refers to the use electromagnetic signals to measure distances with millimeter or sub-millimeter precision.

One-way travel time or TOF refers to the time it takes an electromagnetic signal to travel from a transmitter or transceiver to a receiver or transponder.

Two-way travel time or TOF refers to the time it takes an electromagnetic signal to travel from a transmitter or transceiver to a transponder plus the time it takes for the signal, or response, to return to the transceiver or a receiver.

**[0056]** Referring to FIG. 1, aspects and embodiments of one embodiment of a system for measuring distance with precision of the present invention are based on a bi-static ranging system configuration, which measures a direct time of flight (TOF) of a transmitted signal between at least one transmitter **10** and at least one receiver **12**. This embodiment of a ranging system of the invention can be characterized as an apparatus for measuring TOF of an electromagnetic signal **14**. This embodiment of an apparatus is comprised of at least one transmitter **10**, which transmits an electromagnetic signal **14** to at least one receiver **12**, which receives the transmitted signal **14** and determines a time of flight of the received signal. A time of flight of the electromagnetic signal **14** between the transmission time of the signal **14** transmitted from the transmitter **10** to the time the signal is received by the receiver **12** is measured to determine the TOF of the signal **14** between the transmitter and the receiver. A signal processor within one of the transmitter **10** and the receiver **12** analyzes the received and sampled signal to determine the TOF. The TOF of the signal **14** is indicative of the distance between the transmitter **10** and the receiver **12**, and can be used for many purposes, some examples of which are described herein.

**[0057]** A preferred embodiment of the ranging system of the present invention is illustrated and described with reference to FIG. 2. In particular, one embodiment of a ranging system according to the present invention includes a transmitter **10** which can, for example, be mounted on an object for which a position and/or range is to be sensed. The transmitter **10** transmits a frequency modulated continuous wave (FMCW) signal **14'**. At least one receiver **12** is coupled to the transmitter **10** by a cable **16**. The cable **16** returns the

received transmitted signal received by the at least one receiver back to the transmitter **10**. In the transmitter **10**, the transmitted signal **14'** is split by a splitter **17** prior to being fed to and transmitted by an antenna **18**. A portion of the transmitted signal **14'** that has been split by the splitter **16** is fed to a first port of a mixer **20** and is used as local oscillator (LO) signal input signal for the mixer. The transmitted signal **14'** is received by an antenna **22** at the receiver **12** and is output by the at least one receiver **12** to a combiner **24**, which combines the received signals from the at least one receiver **12** and forwards the combined received signals with the cable **16** to a second port of the mixer **20**. An output signal **21** from the mixer has a beat frequency that corresponds to a time difference between the transmitted signal from the transmitter **10** to the received signal by the receiver **12**. Thus, the beat frequency of the output signal **21** of the mixer is representative of the distance between the transmitter and the receiver. The output signal **21** of the mixer **20** is supplied to an input of an Analog to Digital converter **26** to provide a sampled output signal **29**. The sampled signal **29** can be provided to a processor **28** configured to determine the beat frequency to indicate a TOF, which is indicative of the distance between the transmitter and receiver.

**[0058]** This embodiment of the ranging system is based on the transmission and reception of an FMCW transmitted signal and determining a beat frequency difference between the transmitted and received signals. The beat frequency signal is proportional to the TOF distance between the transmitter and the receiver. By way of example, the sampled signal from the A/D converter **26** is fed to the Fast Fourier Transform (FFT) device **30** to transform the sampled time signal into the frequency domain  $x(t) \Rightarrow X(k)$ . It will be understood that other transforms or algorithms may be used, such as multiple signal classifiers (MUSIC), estimation of signal parameters via rotational invariance techniques (ES-PRIT), discrete Fourier transforms (DFT), and inverse Fourier transforms (IFT), for example. From the FFT, the TOF of the signal **14'** can be determined. In particular, the data output from the A/D converter **26** is a filtered set of amplitudes, with some low frequency noise. According to aspects of this embodiment a minimum amplitude threshold for object detection to occur can be set so that detection is triggered by an amplitude above the minimum threshold. If an amplitude of the sampled signal at a given frequency does not reach the threshold, it may be ignored.

**[0059]** In the system illustrated in FIG. 2, any number of additional receivers **12** can be included in the system. The output signals from the additional receivers **12** are selected by a switch **24** and fed back to the transmitter **10** by the cable **16** to provide selected received signals at the additional receivers for additional time of flight measured signals at additional receivers **12**. In an alternate embodiment, the mixer **20** and the A/D converter **26** can be included in each receiver to output a digital signal from each receiver. In this embodiment, the digital signal can be selected and fed back to the transmitter for further processing. It is appreciated that for this embodiment, the FFT processing can be done either in each receiver or at the transmitter. The TOF measured signals resulting from the additional receivers **12** can be processed to indicate the position of the object to which the transmitter **10** is mounted with a number of degrees of freedom and with excellent resolution according to the present invention. Also as is illustrated with reference to FIG. 8, according to aspects and embodiments of this

disclosure, it is appreciated that multiple transmitters can be coupled to multiple receivers to produce a sophisticated position-detecting system.

[0060] In the ranging system of FIG. 2, at least one transmitter 10 can be mounted on an object to be tracked in distance and position. The receivers each generate a signal for determining a TOF measurement for the signal 14' transmitted by the transmitter. The receivers 12 are coupled to the processor 28 to produce data indicating the TOF from the transmitter to each of the three receivers, which can be used for precise position detection of the transmitter 10 coupled to the object. It is appreciated that various arrangements of transmitters and receivers may be used to triangulate the position of the object to which the transmitter is attached, providing information such as x, y, z position as well as translation and 3 axes of rotation of the transmitter 10.

[0061] It is appreciated that for any of the embodiments and aspects disclosed herein, there can be coordinated timing between the transmitter and receivers to achieve the precise distance measurements. It is also appreciated that the disclosed embodiments of the system are capable of measuring distance by TOF on the order of about a millimeter or sub-millimeter scale in precision, at 1 Hz or less in frequency over a total range of hundreds of meters. It is anticipated that embodiments of the system can be implemented with very low-cost components for less \$100.

#### Modulation Ranging Systems.

[0062] Referring to FIG. 3, there is illustrated another embodiment of a ranging system 300 implemented according to the present invention. It is appreciated that various form of modulation such as harmonic modulation, Doppler modulation, amplitude modulation, phase modulation, frequency modulation, signal encoding, and combinations thereof can be used to provide precision navigation and localization. One such example is illustrated in FIG. 3, which illustrates a use of pulsed direct sequence spread spectrum (DSSS) signals 32 to determine range or distance. In direct sequence spread spectrum ranging systems, code modulation of the transmitted signal 32 and demodulation of a received and re-transmitted signal 36 can be done by phase shift modulating a carrier signal. A transmitter portion of a transceiver 38 transmits via an antenna 40 a pseudo-noise code-modulated signal 32 having a frequency F1. It is to be appreciated that in a duplex ranging system, the transceiver 38 and a transponder 42 can operate simultaneously.

[0063] As shown in FIG. 3, the transponder 42 receives the transmitted signal 32 having frequency F1, which is fed to and translated by a translator 34 to a different frequency F2, which can be for example  $2 \times F1$  and is retransmitted by the transponder 42 as code-modulated signal 36 having frequency F2. A receiver subsystem of the transceiver 38, which is co-located with the transmitter portion of the transceiver 38 receives the retransmitted signal 36 and synchronizes to the return signal. In particular, by measuring the time delay between the transmitted signal 32 being transmitted and received signal 36, the system can determine the range from itself to the transponder. In this embodiment, the time delay corresponds to the two-way propagation delay of the transmitted 32 and retransmitted signals 36.

[0064] According to aspects of this embodiment, the system can include two separate PN code generators 44, 46 for the transmitter and receiver subsystems of the transceiver

38, so that the code at the receiver portion of the transceiver can be out of phase with the transmitted code or so that the codes can be different.

[0065] The transmitter portion of the transceiver 38 for measuring TOF distance of an electromagnetic signal comprises a 1st pseudo noise generator 44 for generating a first phase shift signal, a first mixer 48 which receives a carrier signal 50, which modulates the carrier signal with a first phase shift signal 52 to provide a pseudo-noise code-modulated signal 32 having a center frequency F1 that is transmitted by the transceiver 38. The transponder apparatus 42 comprises the translator 34 which receives the pseudo-noise code-modulated signal 32 having center frequency F1 and translates the pseudo-noise code-modulated signal of frequency F1 to provide a translated pseudo-noise code-modulated signal having a center frequency F2 or that provides a different coded signal centered at the center frequency F1, and that is transmitted by the transponder back to the transceiver 38. The transceiver apparatus 38 further comprises a second pseudo noise generator 46 for generating a second phase shift signal 56, and a second mixer 54 which receives the second phase shift signal 56 from the pseudo-noise generator 46, which receives the translated pseudo-noise code-modulated signal 36 at frequency F2 and modulates the pseudo-correlated code-modulated signal 36 having center frequency F2 with the second phase shift signal 56 to provide a return signal 60. The apparatus further comprises a detector 62 which detects the return signal 60, and a ranging device/counter 64 that measures the time delay between the transmitted signal 32 and the received signal 36 to determine the round trip range from the transceiver 38 to the transponder 42 and back to the transceiver 38 so as to determine the two-way propagation delay. According to aspects of some embodiments, the first PN generator 44 and the second PN generator 46 can be two separate PN code generators.

[0066] It is appreciated that the preciseness of this embodiment of the system depends on the signal-to-noise ratio (SNR) of the signal, the bandwidth, and the sampling rate of the sampled signals. It is also appreciated that this embodiment of the system can use any pulse compressed signal.

[0067] FIG. 9 illustrates another embodiment of a modulation ranging system 301. This embodiment can be used to provide a transmitted signal at frequency F1 from interrogator 380, which is received and harmonically modulated by transponder 420 to provide a harmonic return signal 360 at F2, which can be for example  $2 \times F1$ , that is transmitted by the transponder 420 back to the interrogator 380 to determine precise location of the transponder. With the harmonic ranging system, the doubling of the transmitted signal 320 by the transponder can be used to differentiate the retransmitted transponder signal from a signal reflected for example by scene clutter.

[0068] As illustrated by FIGS. 3 and 9-10 along with the discussion above, a transponder 42, 420, 421, 423 may translate a received frequency F1 to a response frequency F2 and the response frequency F2 may be harmonically related to F1. A simple harmonic transponder device capable of doing so may include a single diode used as a frequency doubler, or multiplier, coupled to one or more antennas. FIG. 9 illustrates a simple harmonic transponder 423 that includes a receive antenna RX, a multiplier 422 that can simply be a diode, an optional battery 425, and an optional auxiliary



receiver 427. FIG. 3 shows a transponder 42 having a single antenna for both receiving and transmitting signals to and from the transponder 42, while FIG. 9 shows separate antennas (labelled RX, TX) for both receiving and transmitting signals to and from the transponders 420, 423. It is appreciated that embodiments of any transponder 42, 420, 421, and 423 as disclosed herein, may have one shared antenna, may have multiple antennas such as a TX and an RX antenna, and may include different antenna arrangements.

[0069] An embodiment of transponder 42, 420, 421, 423 can include a frequency multiplying element 422, such as but not limited to a diode, integrated into an antenna structure. For example, a diode may be placed upon and coupled to a conducting structure, such as a patch antenna or microstrip antenna structure, and placed in a configuration so as to match impedance of a received and/or transmitted signal so as to be capable of exciting antenna modes at each of the receive and response frequencies.

[0070] An embodiment of a passive harmonic transponder 423 includes a low power source such as a battery 425 (for example a watch battery), which can be used to reverse bias the diode multiplier 422 to normally be off, and the low power source can be turned off to turn the harmonic transponder to an on state (a wake up state) to multiply or otherwise harmonically shift a frequency of a received signal. The low power source can be used to reverse bias the multiplier 422 to turn on and off the transponder, for example in applications like those discussed herein. According to an embodiment of the transponder, the power source 425 can also be configured to forward bias the multiplier (diode) 422 to increase the sensitivity and increase the range of the transponder to kilometer range up from for example, a 10-100 meter range. In still another embodiment, amplification (LNA, LNA2, LNA3, LNA4) either solely or in combination with forward biasing of the multiplier diode 422, may also or alternatively be used to increase sensitivity of the transponder. It is appreciated that in general, amplification may be employed with any transponder to increase the sensitivity of any of the embodiments of a transponder of any of the ranging systems as disclosed herein.

[0071] According to aspects and embodiments, the diode-based transponder 423 can be a passive transponder that is configured to use very little power and may be powered via button-type or watch battery, and/or may be powered by energy harvesting techniques. This embodiment of the transponder is configured to consume low amounts of energy with the transponder in the powered off mode most of the time, and occasionally being switched to a wake up state. It is appreciated that the reverse biasing of the diode and the switching on and off of the diode bias takes little power. This would allow passive embodiments of the transponder 423 to run off of watch batteries or other low power sources, or to even be battery-less by using power harvesting techniques, for example from the TOF electromagnetic signals, or from motion, such as a piezoelectric source, a solenoid, or an inertial generator, or from a light source, e.g., solar. With such an arrangement, the interrogator 38, 380, 381 can include an auxiliary wireless transmitter 429 and the transponder 42, 420, 421, and 423 can include an auxiliary wireless receiver 427 as discussed herein, particularly with respect to FIGS. 3, 9-10, that is used to address each transponder to tell each transponder when to wake up. The auxiliary signal transmitted by auxiliary wireless transmitter

429 and received by auxiliary wireless receiver 427 is used to address each transponder to tell each transponder when to turn on and turn off. One advantage of providing the interrogator with the auxiliary wireless transmitter 429 and each transponder with an auxiliary wireless signal receiver 427 is that it provides for the TOF signal channel to be unburdened by unwanted signal noise such as, for example, communication signals from transponders that are not being used. With that said, it is also appreciated that another embodiment of the TOF system could in fact use the TOF signal channel to send and receive radio/control messages to and from the transponders to tell transponders to turn on and off, etc.

[0072] With such an arrangement, the auxiliary wireless receiver 427 is optional.

[0073] It is appreciated that embodiments of the passive harmonic transponder 423 do not require a battery source that needs to be changed every day/few days. The passive harmonic transponder 423 can either have a long-life battery or for shorter range applications may be wirelessly powered by the main channel signal or by an auxiliary channel signal for longer range (e.g. the interrogator and transponder can operate over the 3-10 GHz range, while power harvesting can occur using either or both of the main signal range and a lower frequency range such as, for example, 900 MHz or 13 MHz. In contrast, classic harmonic radar tags simply respond as a chopper to an incoming signal, such that useful tag output power levels require very strong incoming signals such as  $>-30$  dBm at the tag from a transmitter. It is appreciated that the passive harmonic transponder 423 provides a compact, long/unlimited lifetime long-range transponder by storing energy to bias the diode, drastically increasing the diode sensitivity and range of the transponder to, for example, 1 km scales.

[0074] One aspect of the embodiment shown in FIG. 9 of a modulation ranging system, or any of the embodiments of a ranging system as disclosed herein, is that each transponder 420 can be configured with an auxiliary wireless receiver 427 to be uniquely addressable by an auxiliary wireless signal 401 from the auxiliary wireless transmitter 429, such as for example a blue tooth signal, a Wi-Fi signal, a cellular signal, a Zigbee signal and the like, which can be transmitted by the interrogator 380. Thus, the interrogator 380 can be configured with an auxiliary wireless transmitter 429 to transmit an auxiliary wireless signal 401 to identify and turn on a particular transponder 420. For example, the auxiliary wireless signal 401 could be configured to turn on each transponder based on each transponder's serial number. With this arrangement, each transponder could be uniquely addressed by an auxiliary wireless signal provided by the interrogator. Alternately, an auxiliary signal to address and enable individual or groups of transponders may be an embedded control message in the transmitted interrogation signal, which may take the form of command protocols or unique codes. In other embodiments the auxiliary signal to enable a transponder may take various other forms.

[0075] As shown in FIG. 9, a transmitter portion of an interrogator 380 transmits via an antenna 400 a signal 320 having a frequency F1. The transponder can be prompted to wake up by auxiliary wireless transmitter 429 transmitting an auxiliary wireless signal and the transponder receiving with an auxiliary wireless receiver 427 the auxiliary wireless signal 401, such that the transponder 420 receives the transmitted signal 320 having frequency F1, which is

doubled in frequency by the transponder to frequency F2 ( $=2 \times F1$ ) and is retransmitted by the transponder 420 as signal 360 having frequency F2. A receiver subsystem of the interrogator 380, which is co-located with the transmitter portion of the interrogator 380 receives the retransmitted signal 360 and synchronizes the return signal to measure the precise distance and location between the interrogator 380 and the transponder 420. In particular, by measuring the time delay between the transmitted signal 320 being transmitted and the received signal 360, the system can determine the range from the interrogator to the transponder. In this embodiment, the time delay corresponds to the two-way propagation delay of the transmitted 320 and retransmitted signals 360.

[0076] For example, the transmitter portion of the interrogator 380 for measuring precise location of a transponder 420 comprises an oscillator 382 that provides a first signal 320 having a center frequency F1 that is transmitted by the interrogator 380. The transponder apparatus 420 comprises a frequency harmonic translator 422 which receives the first signal 320 having center frequency F1 and translates the signal of frequency F1 to provide a harmonic of the signal F1 having a center frequency F2, for example  $2 \times F1$  that is transmitted by the transponder 420 back to the interrogator 380. The interrogator 380 as shown further comprises four receive channels 390, 392, 394, 396 for receiving the signal F2. Each receive channel comprises a mixer 391, 393, 395, 397 which receives the second signal 360 at frequency F2 and down converts the return signal 360. The interrogator apparatus further comprises a detector which detects the return signal, an analog-to-digital converter and a processor to determine a precise measurement of the time delay between the transmitted signal 320 and the received signal 360 to determine the round trip range from the interrogator 380 to the transponder 420 and back to the interrogator 380 so as to determine the two-way propagation delay.

[0077] According to aspects of this embodiment, the interrogator can include four separate receive channels 390, 392, 394, 396 to receive the harmonic return frequencies of the retransmitted signal 401 in a spatially diverse array for the purpose of navigation. It is appreciated that the first signal 320 having a center frequency F1 can be varied in frequency according to any of the modulation schemes that have been discussed herein, such as, for example FMCW, and that the modulation could also be any of CW pulsed, pulsed, impulse, or any other waveform. It is to be appreciated that any number of channels can be used. It is also to be appreciated that in the four receive channels of the interrogator can either be multiplexed to receive the signal 360 at different times or can be configured to operate simultaneously. It is further appreciated that, at least in part because modulation is being used, the interrogator 380 and the transponder 420 can be configured to operate simultaneously.

[0078] It is to be appreciated that according to aspects and embodiments disclosed herein, the modulator can use different forms of modulation. For example, as noted above direct sequence spread spectrum (DSSS) modulation can be used. In addition, other forms of modulation such as Doppler modulation, amplitude modulation, phase modulation, coded modulation such as CDMA, or other known forms of modulation can be used either in combination with a frequency or harmonic translation or instead of a harmonic or frequency translation. In particular, the interrogator signal

320 and the transponder signal 360 can either be at the same frequency, i.e. F1, and a modulation of the interrogator signal by the transponder 420 can be done to provide the signal 360 at the same frequency F1, or the interrogator can also frequency translate the signal 320 to provide the signal 360 at a second frequency F2, which may be at a harmonic of F1, in addition to modulate the signal F1, or the interrogator can only frequency translate the signal 320 to provide the signal 360. As noted above, any of the noted modulation techniques provide the advantage of distinguishing the transponder signal 360 from background clutter reflected signal 320. It is to be appreciated that with some forms of modulation, the transponders can be uniquely identified by the modulation, such as coded modulation, to respond to the interrogation signal so that multiple transponders 420 can be operated simultaneously. In addition, as been noted herein, by using a coded waveform, there need not be a translation of frequency of the retransmitted signal 360, which has the advantage of providing a less expensive solution since no frequency translation is necessary.

[0079] It is to be appreciated that according to aspects and embodiments of any of the ranging system as disclosed herein, multiple channels may be used by various of the interrogator and transponder devices, for example, multiple frequency channels, quadrature phase channels, or code channels may be incorporated in either or both of interrogation or response signals. In other embodiments, additional channel schemes may be used. For example, one embodiment of a transponder 42, 420, 421, 423 can have both in phase and  $90^\circ$  out of phase (quadrature) channels with two different diodes where the diodes are modulated in quadrature by reverse biasing of the diodes. With such an arrangement, the interrogator could be configured to send coded waveform signals to different transponders simultaneously. In addition, other methods as discussed herein, such as polarization diversity, time sharing, a code-multiplexed scheme where each transponder has a unique pseudo-random code to make each transponder uniquely addressable, and the like provide for allow increased numbers of transponders to be continuously monitored at full energy sensitivity.

[0080] FIG. 10 illustrates another embodiment of a modulation ranging system 310. This embodiment can be used to provide a transmitted signal at frequency F1 from interrogator 381, which is received by transponder 421 and frequency translated by transponder 421 to provide a frequency shifted return signal 361 at F2, which can be arbitrarily related in frequency to F1 of the interrogator signal (it doesn't have to be a harmonic signal), that is transmitted by the transponder 421 back to the interrogator 381 to determine precise location of the transponder 421. With this arrangement illustrated in FIG. 10, for example the signal 321 at F1 can be at the 5.8 GHz Industrial Scientific and Medical band, and the return signal 361 at F2 can be in the 24 GHz ISM band. It is to be appreciated also that with this arrangement of a modulation system, the frequency shifting of the transmitted signal 321 by the transponder 421 can be used to differentiate the retransmitted transponder signal 361 from a signal reflected for example by background clutter.

[0081] One aspect of this embodiment 310 of a modulation ranging system or any of the embodiments of a ranging system as disclosed herein is that each transponder 42, 420, 421, 423 can be configured to be uniquely addressable to wake up each transponder by receiving with an auxiliary

wireless receiver **427** an auxiliary wireless signal **401** from an auxiliary wireless transmitter **429**, such as for example a blue tooth signal, a Wi-Fi signal, a cellular signal, a Zigbee signal, and the like, which auxiliary wireless signal can be transmitted by the interrogator **381**. Thus, the interrogator **381** can be configured with an auxiliary signal transmitter **429** to transmit an auxiliary wireless signal **401** to identify and turn on a particular transponder **42**, **420**, **421**, **423**. For example, the auxiliary wireless signal could be configured to turn on each transponder based on each transponder's serial number. With this arrangement, each transponder could be uniquely addressed by an auxiliary wireless signal provided by the interrogator or another source.

**[0082]** With respect to FIG. **10**, it is appreciated that an oscillator such as OSC3 will have finite frequency error that manifests itself as finite estimated position error. One possible mitigation with a low cost TCXO (temperature controlled crystal oscillator) used for OSC3 is to have a user periodically touch their transponder to a calibration target. This calibration target is equipped with magnetic, optical, radar, or other suitable close range high precision sensors to effectively null out the position error caused by any long-term or short-term drift of the TCXO or other suitable low cost high stability oscillator. The nulling out is retained in the radar and/or transponder as a set of calibration constants that may persist for minutes, hours, or days depending on the users position accuracy needs.

**[0083]** According to aspects and embodiments the interrogator and each transponder of the system can be configured to use a single antenna (same antenna) to both transmit and receive a signal. For example, the interrogator **38**, **380**, **381** can be configured with one antenna **40**, **400**, to transmit the interrogator signal **32**, **320**, **321** and receive the response signal **36**, **360**, **361**. Similarly, the transponder can be configured with one antenna to receive the interrogator signal **32**, **320**, **321** and transmit the response signal **36**, **360**, **361**. This can be accomplished, for example, if coded waveforms are used for the signals. Alternatively, where the signals are frequency translated but are close in frequency, such as for example 4.9 GHz and 5.8 GHz, the same antenna can be used. Alternatively or in addition, it may be possible to provide the interrogator signal **32**, **320**, **321** at a first polarization, such as Left Hand Circular Polarization (LHCP), Right Hand Circular Polarization (RHCP), vertical polarization, horizontal polarization, and to provide the interrogator signal **36**, **360**, **361** at a second polarization. It is appreciated that providing the signals with different polarizations can also enable a system with the interrogator and the transponder each using a single antenna, thereby reducing costs. It is further appreciated that using circular polarization techniques mitigates the reflections from background clutter thereby reducing the effects of multi-path return signals, because when using circular polarization, the reflected signal is flipped in polarization, and so the multi-path return signals could be attenuated by using linear polarizations and/or polarization filters.

**[0084]** According to aspects and embodiments of any of the systems disclosed herein, it is further appreciated that there can be selective pinging of each transponder **42**, **420**, **421**, **423** to wake up each transponder by receiving with an auxiliary wireless receiver **427** an auxiliary wireless signal **401**, such as for example a blue tooth signal, a Wi-Fi signal, a cellular signal, a Zigbee signal and the like, which can be transmitted by the interrogator **380** to provide for scene data

compression. In particular, there can be some latency when using an auxiliary wireless signal to identify and interrogate each transponder **42**, **420**, **421**, **423**. As the number of transponders increases, this can result in slowing down of interrogation of all the transponders. However, some transponders may not need to be interrogated as often as other transponders. For example, in an environment where some transponders may be moving and others may be stationary, the stationary transponders need not be interrogated as often as the transponders that are actively moving. Still others may not be moving as fast as other transponders. Thus, by dynamically assessing and pinging more frequently the transponders that are moving or that are moving faster than other transponders, there can be a compression of the transponder signals, which can be analogized for example to MPEG4 compression where only pixels that are changing are sampled.

**[0085]** According to aspects and embodiments disclosed herein, the interrogators and transponders can be configured with their own proprietary micro-location frequency allocation protocol so that the transponders and interrogators can operate at unused frequency bands that exist amongst existing allocated frequency bands. In addition, the interrogators and transponders can be configured so as to inform users of legacy systems at other frequencies for situational awareness, e.g. to use existing frequency allocations in situations that warrant using existing frequency band allocations. Some advantages of these aspects and embodiments are that it enables a control for all modes of travel (foot, car, aerial, boat, etc.) over existing wired and wireless backhaul networks, with the interrogators and the transponders inter-operating with existing smart vehicle and smart phone technologies such as Dedicated Short Range Communications (DSRC) and Bluetooth Low Energy (BLE) radio.

**[0086]** In particular, aspects and embodiments are directed to high power interrogators in license-free bands e.g. 5.8 GHz under U-NII and frequency sharing schemes via dynamic frequency selection and intra-pulse sharing wherein the system detects other loading issues such as system timing and load factor, and the system allocates pulses in between shared system usage. One example of such an arrangement is dynamic intra pulse spectrum notching on the fly. Another aspect of embodiments disclosed herein is dynamic allocation of response frequencies by a lower power transponder at license-free frequency bands (lower power enables wider selection of transponder response frequencies).

**[0087]** Another aspect of embodiments of interrogators and transponders disclosed herein is an area that has been configured with a plurality of interrogators (a localization enabled area) can have each of the transponders enabled with BLE signal emitting beacons (no connection needed), as has been noted herein. With this arrangement, when a user having a transponder, such as a wearable transponder, enters into the localization area, the transponder "wakes up" to listen for the BLE interrogation signal and replies as needed. It is also appreciated that the transponder can be configured to request an update on what's going on, either over the BLE channel or another frequency channel, such as a dynamically allocated channel.

**[0088]** Some examples of applications where this system arrangement can be used are for example as a human or robot walks, drives, or pilots a vehicle or unmanned vehicle through any of for example a dense urban area, a wooded

area, or a deep valley area where direct line of sight is problematic and multipath reflections cause GNSS navigation solutions to be highly inaccurate or fail to converge altogether. The human or robot or vehicle or unmanned vehicle can be equipped with such configured with transponders and interrogators can be configured to update the transponders with their current state vector as well as broadcast awareness of their state vector over preselected or dynamically selected frequency using wireless protocols, Bluetooth Low Energy, DSRC, and other appropriate mechanisms for legal traceability (accident insurance claims, legal compliance).

[0089] One implementation can be for example with UDP multicasting, wherein the transponders are configured to communicate all known state vectors of target transponders with UDP multicast signals. The UDP multicast encrypted signals can be also be configured to be cybersecurity protected against spoofing, denial of service and the like. One practical realization of the network infrastructure may include: Amazon AWS IoT service, 512 byte packet increments, TCP Port 443, MQTT protocol, designed to be tolerant of intermittent links, late to arrive units, and brokers and logs data for traceability, and machine learning.

#### Wide-Band or Ultra-Wide-Band Ranging Systems.

[0090] FIG. 4 illustrates an embodiment of a wide-band or ultra-wide-band impulse ranging system 800. The system includes an impulse radio transmitter 900. The transmitter 900 comprises a time base 904 that generates a periodic timing signal 908. The time base 904 comprises a voltage controlled oscillator, or the like, which is typically locked to a crystal reference, having a high timing accuracy. The periodic timing signal 908 is supplied to a code source 912 and a code time modulator 916.

[0091] The code source 912 comprises a storage device such as a random access memory (RAM), read only memory (ROM), or the like, for storing codes and outputting the codes as code signal 920. For example, orthogonal PN codes are stored in the code source 912. The code source 912 monitors the periodic timing signal 908 to permit the code signal to be synchronized to the code time modulator 916. The code time modulator 916 uses the code signal 920 to modulate the periodic timing signal 908 for channelization and smoothing of the final emitted signal. The output of the code time modulator 916 is a coded timing signal 924.

[0092] The coded timing signal 924 is provided to an output stage 928 that uses the coded timing signal as a trigger to generate electromagnetic pulses. The electromagnetic pulses are sent to a transmit antenna 932 via a transmission line 936. The electromagnetic pulses are converted into propagating electromagnetic waves 940 by the transmit antenna 932. The electromagnetic waves propagate to an impulse radio receiver through a propagation medium, such as air.

[0093] FIG. 4 further illustrates an impulse radio receiver 1000. The impulse radio receiver 1000 comprises a receive antenna 1004 for receiving a propagating electromagnetic wave 940 and converting it to an electrical received signal 1008. The received signal is provided to a correlator 1016 via a transmission line coupled to the receive antenna 1004.

[0094] The receiver 1000 comprises a decode source 1020 and an adjustable time base 1024. The decode source 1020 generates a decode signal 1028 corresponding to the code used by the associated transmitter 900 that transmitted the

signal 940. The adjustable time base 1024 generates a periodic timing signal 1032 that comprises a train of template signal pulses having waveforms substantially equivalent to each pulse of the received signal 1008.

[0095] The decode signal 1028 and the periodic timing signal 1032 are received by the decode timing modulator 1036. The decode timing modulator 1036 uses the decode signal 1028 to position in time the periodic timing signal 1032 to generate a decode control signal 1040. The decode control signal 1040 is thus matched in time to the known code of the transmitter 900 so that the received signal 1008 can be detected in the correlator 1016.

[0096] An output 1044 of the correlator 1016 results from the multiplication of the input pulse 1008 and the signal 1040 and integration of the resulting signal. This is the correlation process. The signal 1044 is filtered by a low pass filter 1048 and a signal 1052 is generated at the output of the low pass filter 1048. The signal 1052 is used to control the adjustable time base 1024 to lock onto the received signal. The signal 1052 corresponds to the average value of the correlator output, and is the lock loop error signal that is used to control the adjustable time base 1024 to maintain a stable lock on the signal. If the received pulse train is slightly early, the output of the low pass filter 1048 will be slightly high and generate a time base correction to shift the adjustable time base slightly earlier to match the incoming pulse train. In this way, the receiver is held in stable relationship with the incoming pulse train.

[0097] It is appreciated that this embodiment of the system can use any pulse compressed signal. It is also appreciated that the transmitter 900 and the receiver 1000 can be incorporated into a single transceiver device. First and second transceiver devices according to this embodiment can be used to determine the distance  $d$  to and the position of an object. Further reference to functionalities of both a transmitter and a receiver are disclosed in U.S. Pat. No. 6,297,773 System and Method for Position Determination by Impulse Radio, which is herein incorporated by reference.

#### Linear FM and FHSS FMCW Ranging Systems.

[0098] Referring to FIG. 5, there is illustrated another embodiment of a ranging system 400 implemented according to the present invention that can use either linear FMCW ranging or frequency hopping spread spectrum (FHSS) FMCW ranging signals and techniques.

[0099] According to one embodiment implementing linear FMCW ranging, a transmitted signal 74 is swept through a linear range of frequencies and transmitted as transmitted signal 74. For one way linear TOF FMCW ranging, at a separate receiver 80, a linear decoding of the received signal 74 and a split version of the linear swept transmitted signal are mixed together at a mixer 82 to provide a coherent received signal corresponding to the TOF of the transmitted signal. Because this is done at a separate receiver 80, it yields a one-way TOF ranging.

[0100] FIG. 11 illustrates a block diagram of an embodiment of an interrogator for linear FMCW two-way TOF ranging. In the Embodiment of FIG. 11, an interrogator transmits via antenna 1 (ANT1) a linear FM modulated chirp signal 74 (or FMCW) towards a transponder (not illustrated) as shown for example in FIG. 5. The transponder can for example frequency shift the linear FM modulated chirp signal 74 and re-transmit a frequency shifted signal 75 at

different frequency as discussed herein for aspects of various embodiments of a transponder. For example, as discussed herein, a transponder tag is tracked by receiving, amplifying, then frequency mixing the linear FM modulated interrogation signal and re-transmitting it out at a different frequency. This allows the tag to be easily discernable from clutter, or in other words, so it can be detected among other radar reflecting surfaces. The frequency offset return signal **75** and any scattered return signal **74** are collected by receiver antenna 2 (ANT2), antenna 3 (ANT3) and antenna 4 (ANT4), amplified by a low noise amplifier LNA1 and an Amplifier AMP1, and multiplied by the original chirp signal supplied via the circulator CIRC2 in the mixer MXR1. In the illustrated embodiment the antennas are multiplexed by a single-pole multi-throw switch SW1. The product is amplified via a video amplifier fed out to a digitizer where ranging information can be computed. It is appreciated that although linear FM is discussed in this example any arbitrary waveform can be used including but not limited to impulse, barker codes, or any pulse or phase coded waveforms of any kind. The interrogator and the transponder can work with any arbitrary waveforms including but not limited to linear FM (or FMCW), impulse, pulsed CW, barker codes, or any other modulation techniques that fits within the bandwidth of its signal chain.

**[0101]** FIG. 12 illustrates another embodiment of a block diagram of an interrogator for linear FMCW two-way TOF ranging. This embodiment differs from the embodiment of FIG. 11, primarily in that the interrogator has three transmit antennas to allow for three dimensional ranging of the interrogator and four receive channels for receiving the re-transmitted signal. This embodiment was prototyped and tested. The transmitted signal was transmitted with a Linear FM modulation, 10 mS chirp over a 4 GHz bandwidth from 8.5 GHz to 12.5 GHz. The transmitted output power was +14 dBm. With this arrangement, precision localization was measured and achieved to an accuracy of 27  $\mu$ m in Channel 0, 45  $\mu$ m in Channel 1, 32  $\mu$ m in Channel 2 and 59  $\mu$ m in Channel 3.

**[0102]** With FHSS FMCW ranging, the transmitted signal is not linearly swept through a linear range of frequencies as is done with linear FMCW ranging, instead the transmitted signal is frequency modulated with a series of individual frequencies that are varied and transmitted sequentially in some pseudo-random order according to a specific PN code. It might also exclude particular frequency bands, for example, for purposes of regulatory compliance. For FHSS FMCW ranging at a separate receiver **80** for one way TOF ranging, a decoding of the received signal **74** and a split version of the individual frequencies that are varied and transmitted sequentially according to a specific PN code are mixed together at a mixer **82** to provide a coherent received signal corresponding to the TOF of the transmitted signal. For FHSS FMCW, this is done at a separate receiver **80** for one-way TOF ranging.

**[0103]** More specifically, this embodiment of an apparatus **400** for measuring TOF distance via a linear FHSS FMCW electromagnetic signal comprises a transmitter **70** comprising a local oscillator **72** for generating a signal **74** and a linear ramp generator **76** coupled to the local oscillator that sweeps the local oscillator signal to provide a linear modulated transmitted signal **74** for linear modulation. According to the FHSS FMCW embodiment, instead of a linear ramp generator, the signal provided to modulate the local oscil-

lator signal is broken up into discrete frequency signals **78** that modulate the local oscillator signal to provide a series of individual frequencies according to a specific PN code for modulating the local oscillator signal. The modulated transmitted signal **74** modulated with the series of individual frequencies are transmitted sequentially in some pseudo-random order, according to a specific PN code, as the transmitted signal. For one-way TOF measurements, a split off version of the transmitted signal is also fed via a cable **88** to a receiver **80**. The receiver **80** receives the transmitted signal at an antenna **90** and forwards the received signal to a first port **91** of the mixer. The mixer also receives the signal on cable **88** at a second port **92** and mixes the signal with the received signal **74**, to provide at an output **94** of the mixer a signal corresponding to the time of flight distance between the transmitter **70** and the receiver **80** of the transmitted signal **74** that is either linear modulated (for linear FMCW) or modulated with the PN codes of individual frequencies (for FHSS FMCW). The apparatus further comprises an analog to digital converter **84** coupled to an output **94** of the mixer **82** that receives that signal output from the mixer and provides a sampled output signal **85**. The sampled output signal **85** is fed to a processor **86** that performs a FFT on the sampled signal. According to aspects of this embodiment, the ranging apparatus further comprises a frequency generator configured to provide signals at a plurality of discrete frequencies and processor to provide a randomized sequence of the individual frequency signals.

**[0104]** It is appreciated that this embodiment of the system can use any pulse compressed signal.

**[0105]** It is desirable to make the interrogators and the transponders as have been discussed herein as small as possible and as cheap as possible, so that the interrogators and transponders can be used anywhere and for anything. This it is desirable to implement as much of the interrogator structure and functionality and as much of the transponder structure and functionality as can be done on a chip. It is appreciated that one of the most inexpensive forms of manufacturing electronic devices is as a CMOS implementation. Accordingly, aspects and embodiments of the interrogators and transponders as described herein are to be implemented as CMOS.

#### Multiple Transmitter and/or Transceivers

**[0106]** Referring to FIG. 6, it is to be appreciated that various embodiments of a ranging system **500** according to the invention can comprise multiple transmitters **96**, multiple transceivers **98**, or a combination of both transmitter and transceivers that transmit a transmitted signal **106** that can be any of the signals according to any of the embodiments described herein. Such embodiments include at least one receiver **102** that either receives the transmitted signal **106** from each transmitter and/or at least one transponder **104** that receives the transmitted signal and re-transmits a signal **108** that is a re-transmitted version of the transmitted signal **106** back to a plurality of transceivers **98**, according to any of ranging signals and systems described herein.

**[0107]** One example of a system according to this embodiment includes one transceiver **98** (interrogator) that transmits a first interrogation signal **106** to at least one transponder **104**, which transponder can be attached to an object being tracked. The at least one transponder retransmits a second re-transmitted signal **108** that is received by, for example second, third, and fourth transceivers **98** to determine a position and a range of the transponder and the object

being tracked. For example two transceivers can be grouped in pairs to do hyperbolic positioning and three transceivers can be grouped to do triangulation position to the transponder/object. It is appreciated that any of the transceivers **98** can be varied to be the interrogator that sends the first transmit interrogation signal to the transponder **104** and that any of the transceivers **98** can be varied to receive the re-transmitted signal from the responder. It is appreciated that where ranging to the transponder is being determined at the transceivers, the range and position determination is a time of flight measurement between the signals transmitted by the transponder **104** and received by at least two of the transceivers **98**.

[0108] Another example of a system according to this embodiment includes at least one transponder **104**, which can be attached to an object being tracked. The at least one transponder **104** receives a signal **106** that is transmitted by any of at least first, second, third, and fourth transceivers **98** (interrogators). The signal can be coded to ping at least one of the transponders. It is appreciated that more than one transponder **104** can be provided. It is appreciated that each transponder can be coded to respond to a different ping of the transmitted signal **106**. It is appreciated that multiple transponders can be coded to respond to a same ping of the transmitted signal **106**. Thus, it is appreciated that one transponder or any of a plurality of transponders or a plurality of the transponders can be pinged by the signal **106** transmitted by at least one of the transceivers **98**. It is appreciated that multiple transceivers can be configured to send a signal **106** having a same code/ping. It is also appreciated that each transceiver can be configured to send a transmitted signal having a different code/ping. It is further appreciated that pairs or more of transceivers can be configured to send a signal having the same code/ping. It is also appreciated that pairs or more of the transponders can be configured to respond to a signal having the same code/ping. It is appreciated that where the range to the transponder is being determined at the transponder (the device being tracked), the range determination is a time difference of arrival measurement between the signal transmitted by at least two of the transceivers **98**. For example, where the transponder is pinged by two of the transceivers **98** a hyperbolic positioning of the transponder (object) can be determined. Where the transponder is pinged by three of the transceivers **98**, triangulation positioning of the transponder (object) can be determined.

[0109] Alternatively, instead of coding each signal with a ping, it is appreciated that according to some embodiments a precise time delay can be introduced between signals transmitted by the transmitters and/or transceivers. Alternatively, a precise time delay can be introduced between signals re-transmitted by the at least one transponder in response to receipt of the transmitted signal. With this arrangement pairs of transceivers can be used to accomplish 3D or hyperbolic positioning or at least three transceivers can be used to perform triangular positioning according to any of the signals described herein.

[0110] Another example of a system according to this embodiment includes one transmitter **96** that is a reference transmitter that provides a waveform by which the receivers **102** and/or transponders **104** correlate against to measure a delta in time of the time difference of arrival (TDOA) signal

relative to the reference transmitter **96**. It is also appreciated that this embodiment of the system can use any pulse compressed signal.

#### Multiple Receivers and/or Transponders

[0111] Various embodiments of a system according to the invention can comprise at least one transmitter **96** or transceiver **98** that transmits a transmitted **106** signal and a plurality of receivers **102** or transponders **104** that receive the transmitted signal from each transmitter or transceiver, according to any of ranging systems and signals described herein. Such embodiments include at least one transmitter **96** or transceiver **98** that transmits the transmitted signal **106** and a plurality of receivers **102** or transponders **104** that either receive the transmitted signal **106** or receive and re-transmit a signal **108** that is a re-transmitted version of the transmitted signal **106** back to the at least one transceivers **98**, according to any of ranging signals and systems described herein.

[0112] It is appreciated that according to aspects of this embodiment a transmitter **96** can be attached to an object being tracked and can transmit a first signal **106** to a plurality of receivers **102** to perform time of flight positioning and ranging from the transmitter to the receiver. For example, where two receivers receive the transmitted signal, hyperbolic positioning of the transmitter/object can be achieved. Alternatively or in addition, where at least three receivers receive the transmitted signal **106**, triangulation positioning to the transmitter **96** and object can be achieved.

[0113] According to aspects of another embodiment, at least one transceiver **98** can be attached to an object being tracked and can transmit a first signal **106** to a plurality of transponders **104** to perform positioning and ranging from the transmitter to the receiver. For example, where two transponders receive and re-transmit the transmitted signal **106**, hyperbolic positioning of the transmitter/object can be achieved. Alternatively or in addition, where at least three transponders **104** receive and re-transmit the transmitted signal **106**, triangulation positioning to the transceiver **98** and object can be achieved.

[0114] It is appreciated that any of the transponders can be varied to respond to the interrogator **98** that sends the first transmit interrogation signal to the transponder **104**. It is appreciated that the at least one transponder **104** receives a signal **106** that is transmitted by the transceivers **98** (interrogators). The signal can be coded to ping at least one of the transponders. It is appreciated that each transponder can be coded to respond to a different ping of the transmitted signal **106**. It is appreciated that multiple transponders can be coded to respond to a same ping of the transmitted signal **106**. It is appreciated that one transponder or any of a plurality of transponders or a plurality of the transponders can be pinged by the signal **106** transmitted by at least one transceivers **98**. It is also appreciated that pairs or more of the transponders can be configured to respond to a signal having the same code/ping.

[0115] Alternatively, instead of coding each signal with a ping, it is appreciated that according to some embodiments a precise time delay can be introduced between signals re-transmitted by the transponders **104** in response to receipt of the transmitted signal. With this arrangement pairs of transponders can be used to accomplish hyperbolic positioning of the at least one transceiver or at least three transponders can be used to perform triangular positioning according

to any of the signals described herein. It is also appreciated that this embodiment of the system can use any pulse compressed signal.

#### Hybrid Ranging Systems

**[0116]** Referring to FIG. 8, various embodiments of a system according to the invention can comprise a plurality of transmitters that transmit a transmitted signal and a plurality of receivers that receive a transmitted signal according to any of the signals and systems disclosed herein.

**[0117]** Various embodiments of a system according to the invention can comprise a plurality of transceivers **98** that transmit a transmitted signal and a plurality of transponders **104** that receive the transmitted signal **106** and re-transmit the transmitted signal **108**, according to any of ranging signals and ranging systems described herein. It is further appreciated that the plurality of the transmitters **96** or transceiver **98** can be coupled together either by a cable or a plurality of cables e.g. to create a wired mesh of transmitters or transceivers, or coupled together wirelessly to create a wireless mesh of transmitters or transceivers. It is also appreciated that the plurality of the receivers **102** or transponders **104** can be coupled together either by a cable or a plurality of cables e.g. to create a wired mesh of receivers or transponders, or coupled together wirelessly to create a wireless mesh of receivers or transponders. Still further it is appreciated that the system can comprise a mixture of plurality of transmitters and transceivers and/or a mixture of a plurality of receivers or transponders. It is appreciated that the mixture of the plurality of transmitters and transceivers and/or the mixture of a plurality of receivers or transponders can be coupled together either by one or more cables or wirelessly or a combination of one or more cables and wirelessly. Such embodiments can be configured to determine range and positioning to at least one object according to any of the signals and systems that have been described herein.

**[0118]** In order to facilitate communication between the various and disparately located component parts of any of the herein disclosed systems, a network topology or network infrastructure can be utilized. Typically the network topology and/or network infrastructure can include any viable communication and/or broadcast technology, for example, wired and/or wireless modalities and/or technologies can be utilized to effectuate the subject application. Moreover, the network topology and/or network infrastructure can include utilization of Personal Area Networks (PANs), Local Area Networks (LANs), Campus Area Networks (CANs), Metropolitan Area Networks (MANs), extranets, intranets, the Internet, Wide Area Networks (WANs)—both centralized and/or distributed—and/or any combination, permutation, and/or aggregation thereof.

**[0119]** According to the disclosure above regarding any of the TOF ranging systems disclosed, it will be apparent that a TOF ranging system may be comprised of devices, any of which may transmit, receive, respond, or process signals associated with any of the foregoing TOF ranging systems. In aspects and embodiments, any transceiver, interrogator, transponder, or receiver may determine TOF information in one or more of the manners discussed above in accordance with any of the TOF ranging systems disclosed. Any transmitter, transceiver, interrogator, or transponder may be the source of a signal necessary for determining the TOF

information in one or more of the manners discussed above in accordance with any of the TOF ranging systems disclosed.

**[0120]** It is appreciated that in embodiments, the exact position of signal generating and signal processing components may not be significant, but the position of an antenna is germane to precise ranging, namely the position and the location from which an electromagnetic signal is transmitted or received. Accordingly, the TOF ranging systems locations disclosed herein are typically configured to determine by the TOF ranging to antenna positions and locations. For example, the exemplary embodiments discussed above with respect to FIG. 2 and FIGS. 9 to 12 have multi-antenna components, and it is also appreciated that any of the embodiments of interrogators and transponders as disclosed in FIGS. 1-12 can have multiple antennas. In such example embodiments, and others like them, various components may be shared among more than one antenna and TOF ranging can be done to the multiple antenna components. For example, a single oscillator, modulator, combiner, correlator, amplifier, digitizer, or other component may provide functionality to more than one antenna. In such cases, each of the multiple antennas may be considered an individual TOF transmitter, receiver, interrogator, or transponder, to the extent that associated location information may be determined for such antenna.

**[0121]** In aspects and embodiments, multiple antennas may be provided in a single device to take advantage of spatial diversity. For example, an object with any of the TOF ranging components embedded may have multiple antennas to ensure that at least one antenna may be unobstructed at any given time, for example as the orientation of the object changes. In one embodiment, a wristband may have multiple antennas spaced at intervals around a circumference to ensure that one antenna may always receive without being obstructed by a wearer's wrist.

**[0122]** In aspects and embodiments, signal or other processing, such as calculations, for example, to determine distances based on TOF information, and positions of TOF devices, may be performed on a TOF device or may be performed at other suitable locations or by other suitable devices, such as, but not limited to, a central processing unit or a remote or networked computing device.

**[0123]** It should be noted without limitation or loss of generality that while persistence devices (e.g., memory, storage media, and the like) are not depicted, typical examples of these devices include computer readable media including, but not limited to, an ASIC (application specific integrated circuit), CD (compact disc), DVD (digital video disk), read only memory (ROM), random access memory (RAM), programmable ROM (PROM), floppy disk, hard disk, EEPROM (electrically erasable programmable read only memory), memory stick, and the like.

#### Example Applications of Various Embodiments of TOF Ranging Systems

##### Human-Machine Interaction

**[0124]** Referring to FIG. 13, In accordance with various aspects and/or embodiments of the subject disclosure, there is illustrated an example of a system **700** and method for detecting a user's body movement in cooperation with an industrial automation environment. The system and method includes employing plurality of TOF transmitters **96** or

transceivers **98** (depicted by an antenna) as has been described herein that transmit and/or receive a signal **110** that detects movement of a transponder **114** mounted to a body part of a user positioned proximate to industrial machinery **112**, hereinafter referred to as TOF sensors, according to any of the embodiments systems and with any of the signals that have been disclosed herein, for detecting movement of a body part of the user, ascertaining whether or not the movement of the body part conforms to a recognized movement of the body part, interpreting the recognized movement of the body part as a performable action, and actuating industrial machinery to perform a performable action based on and cooperation with the recognized movement of the body part.

**[0125]** The system includes a plurality of TOF transmitters **96** or transceivers **98** (depicted by an antenna) as has been described herein that transmit and/or transmit and receive a signal **110** for measuring movement of a transponder **114** mounted to a body part of a user positioned proximate to industrial machinery **112**, such as a robotic arm, and proximate to the TOF sensors **96/98**. The system further includes at least one transponder **118** mounted to the industrial machinery **112**, such as a robotic arm, and proximate to the TOF sensors **96/98**. According to aspects of this embodiment, a controller can be configured to receive measurements of movement of the receivers or transponders **114, 118** as measured by the transmitters or transceivers **96/98**, to determine any or all of whether or not the movement of the body part conforms with a recognized movement of the body part, to determine a precise position and location of the receivers or transponders **114, 118**, to predict movement of the human limb, and to control the robotic arm **112** to perform an action based at least in part on instructions received from the industrial controller and a position of the receivers or transponders **114, 118**, to control the robotic arm to perform an action based at least in part on instructions received from the industrial controller and a position of the receivers or transponders **114, 118** so that the human and the robotic arm can work in cooperation and without any risk or danger of harm to the human. The system can also be configured to have a transmitter or transceiver on the robotic arm and a transponder or transceiver on the arm of a human so as to have direct time of flight ranging between them robotic arm and the human arm or limb.

**[0126]** In accordance with yet further aspects or embodiments, the system includes time of flight transmitters and/or transceivers and time of flight receivers or transponders (time of flight sensors) in any of the combinations and using any of the signals disclosed herein for constantly monitoring the movement performed by the user, for detecting an appropriate movement performed by the user, for demarcating a safety zone around the industrial equipment for appropriate movement performed by the user and for cooperating with the industrial equipment, and for controlling and actuating the industrial equipment to stay clear of the safety zone and/or to cooperate with and interact with movement of the user.

**[0127]** According to aspects of one embodiment, the time of flight sensors as have been disclosed herein can be used in industrial automation environments of large scale or where, due to distance and/or overwhelming ambient noise, voice commands are futile, it is not uncommon for body movements (e.g., hand gestures, arm motion, or the like) to be employed to direct persons in control of industrial

equipment to perform tasks, such as directing a fork lift operator to load a pallet of goods onto a storage shelf, or to inform an overhead gantry operator to raise or lower, move to the right or left, backward or forward, an oversized or heavy component portion (e.g., wing spar or engine) for attachment to the fuselage of an aircraft. These human hand, arm, body gestures, and/or finger gesticulations can have universal meaning to human observers, and/or if they are not immediately understood, they typically are sufficiently intuitive that they can easily be learned without a great investment in training, and moreover they can be repeated, by most, with a great deal of uniformity and/or precision. In the same manner that a human observer can understand consistently repeatable body motion or movement to convey secondary meaning, a system **710** can also utilize human body movement, body gestures, and/or finger gesticulations to have conveyed meaningful information in the form of commands, and can therefore perform subsequent actions based at least in part on the interpreted body movement and the underlying command.

**[0128]** In accordance with one embodiment, TOF sensors can monitor or detect motion associated with the torso of the user located proximate the TOF sensor. In accordance with another embodiment, TOF sensors can detect or monitor motion associated with the hands and/or arms of the user situated within the TOF sensors line of sight. In accordance with another embodiment, TOF sensors can detect or monitor movement associated with the hand and/or digits (e.g., fingers) of the user positioned proximate to automatic machinery.

**[0129]** It is understood that TOF sensors in conjunction or cooperation with other components (e.g., a controller and a logic component) can perceive motion of an object in at least three-dimensions. In accordance with embodiments, TOF sensor can perceive lateral body movement (e.g., movement in the x-y plane) taking place within its line of sight, and also discern body movement in the z-axis as well.

**[0130]** Additionally it is appreciated, in cooperation with further components such as controller and/or associated logic component, TOF sensor as disclosed herein can gauge the velocity with which a body movement, gesticulation, or gesture is performed. For example, where the user is configured with one or more TOF sensors is moving their hands with vigor or velocity, the time of flight sensors in conjunction with a controller and/or logic component, can comprehend the velocity and/or vigor with which the user is moving their hands to connote urgency or aggressiveness. Accordingly, in one embodiment, TOF sensors can perceive the vigor and/or velocity of the body movement. For instance, in an industrial automated environment, where a forklift operator is receiving directions from a colleague, the colleague can have initially commenced his/her directions by gently waving his/her arm back and forth (indicating to the operator of the forklift that he/she is clear to move the forklift in reverse). The colleague on perceiving that the forklift operator is reversing too rapidly and/or that there is a possibility of a collision with on-coming traffic can either start waving his/her arm back and forth with great velocity (e.g., informing the forklift operator to hurry up) or hold up their arm with great emphasis (e.g., informing the forklift operator to come to an abrupt halt) in order to avoid the impending collision. According to aspects of embodiments of this disclosure, the systems disclosed herein can be used to interpret such hand commands and transmit instructions for



example to a fork lift operator, where the fork lift operator may not be able to see or hear instructions from the human providing the instructions.

[0131] It is appreciated also that according to aspects of such embodiment, the TOF sensors in conjunction with a controller and/or logic component, can detect the sluggishness or cautiousness with which the user configured with time of flight sensors is moving their hands. Such time-of-flight measurements of sluggishness, cautiousness, or lack of emphasis can be interpreted by the controller and/or logic component to convey uncertainty, warning, or caution, and once again can providing instructions to instructions for previously perceived body movements or future body movements. Thus, continuing with the foregoing forklift operator example, the colleague can, after having waved his/her arm back and forth with great velocity, vigor, and/or emphasis can now commence moving his/her arm in a much more languid or tentative manner, indicating to the forklift operator that caution should be used to reverse the forklift.

[0132] It is appreciated without limitation or loss of generality that TOF sensors, controller (and associated logic component), and industrial machinery **112** can be located in disparate ends of an automated industrial environment. For instance, in accordance with an embodiment, TOF sensors and industrial machinery **112** can be situated in close proximity to one another, while controller and associated logic component can be located in an environmentally controlled (e.g., air-conditioned, dust free, etc.) environment. In accordance with a further embodiment, time of flight sensors, a controller and logic components can be located in an environmentally controlled safe environment (e.g., a safety control room) while industrial machinery can be positioned in a environmentally hazardous environment.

[0133] In order to facilitate communication between the various and disparately located component parts of system **710**, a network topology or network infrastructure will usually be utilized. Typically the network topology and/or network infrastructure can include any viable communication and/or broadcast technology, for example, wired and/or wireless modalities and/or technologies can be utilized to effectuate the subject application. Moreover, the network topology and/or network infrastructure can include utilization of Personal Area Networks (PANs), Local Area Networks (LANs), Campus Area Networks (CANs), Metropolitan Area Networks (MANs), extranets, intranets, the Internet, Wide Area Networks (WANs)—both centralized and/or distributed—and/or any combination, permutation, and/or aggregation thereof.

[0134] It can be appreciated from the foregoing, the sequences and/or series of body/movements, signals, gestures, or gesticulations utilized by the subject application can be limitless, and as such a complex command structure or set of commands can be developed for use with industrial machinery **112**. Moreover, one need only contemplate established human sign language (e.g. American Sign Language) to realize that a great deal of complex information can be conveyed merely through use of sign language. Accordingly, as will have been observed in connection with the foregoing, in particular contexts, certain gestures, movements, motions, etc. in a sequence or set of commands can act as modifiers to previous or prospective gestures, movements, motions, gesticulations, etc.

[0135] According to aspects of certain embodiments, a controller and/or logic component can further be configured

to distinguish valid body movement (or patterns of body movement) intended to convey meaning from invalid body movement (or patterns of body movement) not intended to communicate information, parse and/or interpret recognized and/or valid body movement (or patterns of body movement), and translate recognized and/or valid body movement (or patterns of body movement) into a command or sequence of commands or instructions necessary to actuate or effectuate industrial machinery to perform tasks. For example, to aid a controller and/or associated logic component in differentiating valid body movement from invalid or unrecognized body movement, a controller and/or logic component can consult a persisted library or dictionary of pre-established or recognized body movements (e.g., individual hand gestures, finger movement sequences, etc.) in order to ascertain or correlate the body movement supplied by, and received from, TOF sensors with recognized body movement, and thereafter to utilize the recognized body movement to interpret whether or not the recognized body movement is capable of one or more performable action in cooperation with industrial machinery **112**.

[0136] It should be noted without limitation or loss of generality that the library or dictionary of pre-established or recognized body movements as well as translations or correlations of recognized body movement to commands or sequences of command can be persisted to memory or storage media. Thus, while the persistence devices (e.g., memory, storage media, and the like) are not depicted, typical examples of these devices include computer readable media including, but not limited to, an ASIC (application specific integrated circuit), CD (compact disc), DVD (digital video disk), read only memory (ROM), random access memory (RAM), programmable ROM (PROM), floppy disk, hard disk, EEPROM (electrically erasable programmable read only memory), memory stick, and the like.

[0137] In connection with the aforementioned library or dictionary of established or recognized body movements, it should be appreciated that the established or recognized body movements are generally correlative to sets of industrial automation commands universally comprehended or understood by diverse and/or disparate industrial automation equipment in the industrial automation environment. The sets of commands therefore are typically unique to industrial automation environments and generally can include body movement to command correlations for commands to stop, start, slow down, speed up, etc. Additionally, the correlation of body movements to industrial automation commands can include utilization of established sign language (e.g., American Sign Language) wherein sign language gestures or finger movements can be employed to input alphanumeric symbols. Thus, in accordance with an aspect, letters (or characters) and/or numerals can be input by way of time of flight sensors to correlate to applicable industrial automation commands.

Cell Phone-to-Cell Phone and/or Object Ranging

[0138] Referring to FIG. **14**, In accordance with various aspects and/or embodiments of the subject disclosure, there is illustrated an example of a system **720** and method for detecting a user's body movement and for ranging to another user, for example holding a mobile device, or to an object. This embodiment of a system and method includes employing any of a TOF transmitter **96** or transceiver **98** (depicted as part of a mobile device) in a mobile device **120** as has been described herein that transmits a signal **126** to a

receiver in a second mobile device **122** and/or receives a re-transmitted signal **126** from a transponder in the second mobile device **122**. Mobile device **122** may also transmit a signal **128** to a receiver in another object **124** and/or receive a re-transmitted signal **128** from a transponder in the object **124**.

[0139] According to this embodiment, a user can waive his mobile device **120** containing a time of flight transmitter **96** or transceiver **98** along a line **132** to create a plurality of positions of the mobile device **120**, thus in effect creating a plurality of transmitters or transceivers at various positions. According to this embodiment, the plurality of transmitters or transceivers created by waving the mobile device **120** along line **132** forms a set of pseudo-array elements providing multiple TOF ranging measurements at the various positions along line **132**. The relationship between the various positions may be determined by the mobile device **120** by, e.g., accelerometer data, GPS data, or a pre-established movement sequence, for example. By analyzing the TOF ranging measurements from the various positions to another transponder, e.g., in object **124** or second mobile device **122**, the mobile device **120** can determine by, e.g., triangulation, the position of the object **124** or the second mobile device **122** relative to mobile device **120**. Further, having determined a relative position of an object **124**, second mobile device **122**, or other devices, mobile device **120** can use knowledge of their relative locations for future determinations of its own location; such would be a synthetic baseline of reference positions, e.g., the relative locations of the object **124**, second mobile device **122**, and other devices determined during a pseudo-array measurement of TOF ranges.

[0140] Also according to this embodiment, a mobile device **120** may be outfitted with a GPS receiver and an inertial sensor, such as a micro electromechanical system (MEMS) sensor, e.g., an accelerometer, and may use position information from these other sources in combination with the pseudo-array TOF rangefinding information to precisely locate the object **124** or second mobile device **122** in latitude, longitude, and elevation, or relative to some other coordinate system. A further advantage for some applications of this embodiment includes the mobile device **120** providing a higher rate or frequency of position fixes by combining TOF-based location determinations at intervals with accelerometer-based increments between the TOF-based location determinations. This approach could be used to increase the rate of position fixes by a multiplying factor without increasing power requirements or transmit intervals of the TOF transmitters or transceivers. For example, positioning intervals could be increased by a factor of ten or more with this approach. Alternately, the TOF transmit intervals could be reduced (to save power) while maintaining a certain rate of position determinations.

[0141] According to this embodiment, the plurality of transmitters or transceivers created by waving the mobile device **120** along line **132** can send a signal **126** to a receiver in a second mobile device **122** and/or receives a re-transmitted signal **126** from a transponder in the second mobile device to perform precise ranging between first mobile device **120** and the second mobile device. According to aspects of this embodiment, an object **124** can be provide with a receiver that receives a transmitted signal **128** from the mobile device **120** and/or a transponder that receives and transmits a re-transmitted signal **128** from the transponder

back to the first mobile device and/or to a receiver and/or a transponder in the second mobile device **122**. According to this embodiment, the plurality of transmitters or transceivers created by moving the mobile device **120** along the line **132** can send a signal **126** to object to perform precise ranging between first mobile device **120** and the object and/or to the second mobile device. It is appreciated that according to aspects of this embodiment is that the object can be any object and the purpose of ranging to the object can be for many purposes, some of which are discussed herein in relation to other embodiments disclosed herein. Thus the system according to this embodiment includes a plurality of TOF transmitters **96** or transceivers **98** disposed in a mobile device **120** as has been described herein that transmit and/or receive a signal that detects a distance and/or a position between the mobile device **120** and an object **124**, such as for example another mobile device **122**.

#### UAV Package Delivery

[0142] Reference is now made to FIG. **15** in accordance with various aspects and/or embodiments of the subject disclosure, there is illustrated an example of a system **730** and method for guiding an unmanned aerial vehicle (“UAV”) configured to autonomously deliver or to pick up items of inventory to and from various delivery locations. As discussed in further detail below, in some implementations, the UAV may receive delivery parameters (e.g., item information, source location information, and/or delivery location information), autonomously or semi-autonomously retrieve the item(s) from a source location (e.g., a materials handling facility or a third party seller), compute a route from the source location to a delivery location, and aurally transport the retrieved item(s) to the delivery location.

[0143] This embodiment of a system and method includes employing a plurality of TOF transmitters **96** or transceivers **98** as has been described herein that transmit a signal **130** to a receiver **102** and/or receives a re-transmitted signal **130** from a transponder **104**. It is appreciated that the transmitters **96** can be located on fixed structures such as the tops of buildings, etc. and that receiver **102** or transponders **104** (depicted as antennas on the UAV) can be located on the UAV. Alternatively, transceivers **98** can be located on a UAV (depicted as antennas on the UAV) and transponders **104** can be located for example on top of building or any other structure. A UAV can be configured to fly, for example, above the rooftops of city buildings on the way to pick up a package **136** at a landing site **140** and/or deliver the package to a “landing site” **142**, such as for example on the roof of a distant building. The UAV can be configured to receive GPS navigation signals **144** from a satellite **146** orbiting the earth above the city. The UAV can also be configured to receive navigation signals **130** from antennae located on the rooftops of the buildings so as to navigate the UAV in addition to the GPS signals or as a replacement for receiving any GPS signals. In particular, the signals from the many rooftop antennae **96** and/or **104** create an invisible “highway in the sky” path that the UAV’s follow when moving above the city and between buildings. An analogy would be, for example, in the U.S., commercial and civilian aircraft navigate using GPS, plus a backup system of VHF Omni-directional Range (VOR) distributed across the landscape. If/when GPS fails, aircraft can “follow” the flight paths established by these beacons. Package delivery UAVs, similarly could use GPS signals to navigate and an addi-

tional navigation system, similar to VOR beacons to navigate UAVs to package pickup and/or delivery sites. Such high-precision TOF transmitters **96** or transponders **104** can be placed on building rooftops, other parts of a building, or elsewhere to create safe pathways for UAVs to follow.

**[0144]** According to aspects of this embodiment and referring to FIG. **16**, the UAV can make a stop along the way to the delivery address **142** to pick up a package. It can be navigated by GPS signals **144** and/or time of flight signals **130**. In addition, in order for the UAV to be able to precisely pick up the package **136** for delivery, the package itself may have a beacon **138** that can for example be a transponder **104** that responds to and re-transmits signal **130** so as to precisely navigate the UAV to pick up the package **136**.

**[0145]** It is appreciated according to aspects of this disclosure that the package delivery UAVs presently have limited battery life and it's possible that these drones will need to make stops along their delivery routes to exchange batteries or recharge their batteries. In addition, it is anticipated that UAVs flying in, e.g., urban areas, may need to make emergency landings in safe "ditch" zones, where the drone can be serviced and/or retrieved. Thus according to aspects and embodiments, it is envisioned that transmitter **96** or transceiver **98** or transponders **104** can also be placed on/at select UAV recharge/gas/service stations for guiding UAV's, where UAV's can land to any of swap out batteries, recharge its battery, "ditch" in the event of system failure, etc. After any of these, the UAV will continue on its way to the package pickup **140** or package delivery site **142**, where it can pickup and/or drop off of the package **136**.

**[0146]** Thus, according to embodiments of this, an UAV is configured to autonomously deliver items of inventory to various delivery locations. According to embodiments of this disclosure, an UAV may receive delivery parameters (e.g., item information, source location information, and/or delivery location information), autonomously or semi-autonomously retrieve the item(s) from a source location (e.g., a materials handling facility or a third party seller), compute a route from the source location to a delivery location, and aerially transport the retrieved item(s) to the delivery location. According to some implementations, the UAV will communicate with other UAVs in the area to obtain information. This information may be stored in a central location and/or dynamically shared between nearby UAVs, materials handling facilities, relay locations, a UAV management system and/or secure delivery locations. For example, other UAVs may provide information regarding weather (e.g., wind, snow, and rain), landing conditions, traffic, etc. The UAV may utilize this information to plan the route from the source location to the delivery location and/or to modify the actual navigation of the route. In addition, in some implementations, the UAV may consider other environmental factors while navigating a route.

**[0147]** According to some implementation, when the UAV reaches the delivery location, it will identify an area at the delivery location where it can safely approach the ground, or another surface, and leave the inventory item, thereby completing the delivery. This may be done through assistance of the time of flight beacons, and/or with the aid of the beacon **138** on the ground that helps to navigate the UAV to a location to either pickup or drop off a package. In other implementations, if the UAV has previously landed at the delivery location, it may use stored information about the delivery location (e.g., safe landing area, geographic coor-

dinates of the landing area) to navigate the landing at the delivery location. Upon completion of the delivery, the UAV may return to a materials handling facility or another location to receive different inventory, recharge, etc.

**[0148]** As used herein, a materials handling facility may include, but is not limited to, warehouses, distribution centers, cross-docking facilities, order fulfillment facilities, packaging facilities, shipping facilities, rental facilities, libraries, retail stores, wholesale stores, museums, or other facilities or combinations of facilities for performing one or more functions of materials (inventory) handling. A delivery location, as used herein, refers to any location at which one or more inventory items may be delivered. For example, the delivery location may be a person's residence, a place of business, a location within a materials handling facility (e.g., packing station, inventory storage), any location where a user or inventory is located, etc. Inventory or items may be any physical goods that can be transported using a UAV. A service location as used herein may include, but is not limited to, a delivery location, a materials handling facility, a cellular tower, a rooftop of a building, a secure delivery location, or any other location where a UAV can any of land, charge, retrieve inventory, replace batteries, and/or receive service.

#### Autonomous or Semi-Autonomous Vehicle Navigation

**[0149]** Reference is now made to FIG. **17** in accordance with various aspects and/or embodiments of the subject disclosure, there is illustrated an example of a system **740** and method for guiding a vehicle either autonomously or semi-autonomously to various locations. As discussed in further detail below, in some implementations, the vehicle may receive destination parameters (e.g., location information), autonomously or semi-autonomously compute a route from the current destination to another destination, and autonomously or semi-autonomously be navigated to such location.

**[0150]** This embodiment of a system and method includes employing a plurality of TOF transmitters **96** or transceivers **98** as has been described herein that transmit a signal **130** to a receiver **102** and/or receives a re-transmitted signal **130** from a transponder **104**. It is appreciated that the transmitters **96** can be located on fixed structures such as the tops of buildings, etc and that receiver **102** or transponders **104** (depicted as antennas on the UAV) can be located on the vehicles **146**, **148**. Alternatively, transceivers **98** can be located on a vehicle (depicted as antennas on vehicles) and transponders **104** can be located for example on top of building or any other structure such a traffic light or post. A vehicle can be configured to move along roadways, to navigate intersections, etc. It is appreciate that such a TOF system can be part of an overall navigation and collision avoidance guidance system. For example, the vehicle can also be configured to receive GPS navigation signals from a satellite orbiting the earth. The vehicles can also be configured with additional transceivers to communicate between the vehicles to for example avoid collisions. It is also appreciated that the vehicles can be outfitted with other existing collision avoidance systems such as radar, optical, and the like, as are known to those of skill in the art. Thus, according to aspects of this embodiment, vehicles **146**, **148** can also be configured to receive navigation signals **150** from antennae located on the rooftops of the buildings, traffic lights, light posts, and the like so as to navigate the

vehicle, to update the navigation sensors, to calibrate or reset the navigation sensors, which navigation signals can be used in addition to the GPS signals or as a replacement for receiving any GPS signals. In particular, the signals from the many rooftop antennae **96** and/or **104** create signals that the vehicles can range to follow when moving along roadways, encountering intersections, and the like. Such high-precision TOF transmitters **96** or transponders **104** can be placed on building rooftops to create safe pathways for vehicles to use to navigate autonomously or semi-autonomously.

#### Bridge Inspection

**[0151]** Reference is now made to FIG. **18** in accordance with various aspects and/or embodiments of the subject disclosure, there is illustrated an example of a time of flight signaling system **750** and method for monitoring a bridge for example for performing in situ monitoring of real time load dynamics of a bridge structure to quantify acceptable structural integrity characteristics which may be compared over time with actual bridge loads to determine structural degradation and thereby alert repair. Another aspect of this disclosure is to provide a bridge monitoring system capable of providing non-contact measurement of structural loading of a bridge. Another aspect of this disclosure is to provide a bridge monitoring system capable of monitoring structural members of a bridge to create velocity and displacement time signals of the bridge's vibratory response to quiescent conditions, which sensed velocity time data can for example be converted to the frequency domain data to provide a "signature" waveform for the bridge indicative of acceptable structural integrity characteristics of the bridge. Another aspect of this disclosure is to provide a bridge monitoring system capable including a site installed time of flight signal based motion monitoring system for obtaining velocity time signal data of an onsite bridge structure and for reporting the sensed data to a remote central analysis center which is responsive to sensed time of flight signal data from a plurality of site installed time of flight sensors, thereby creating a centralized time history for bridges. Thus, aspects of the disclosure provide a comprehensive bridge management system using time of flight signals to obtain data on the condition of a bridge, such as to monitor the impacts and repercussions of bridge deterioration or failure to be dealt with in the most efficient, safe and cost effective manner.

**[0152]** This embodiment of a system and method includes employing a plurality of TOF transmitters **96** or transceivers **98** as has been described herein that transmit a signal **130** to a receiver **102** and/or receives a re-transmitted signal **130** from a transponder **104**. It is appreciated that the transmitters **96** or transceivers **98** can be located on fixed structures such as tripods **150** on land, the stanchion of a bridge, or any other fixed location of structure, and that a receiver **102** or transponders **104** (depicted as antennas on the bridge) can be located at a plurality of locations on a bridge. Alternatively, transmitter **96** or transceivers **98** can be located on a bridge (depicted as antennas on vehicles) and receivers **102** or transponders **104** can be located at any fixed location such as a tripod on land, the top of building, etc. A vehicle can be configured to move along roadways, to navigate intersections, etc. It is appreciated that such a TOF system can be part used as part of an overall bridge inspection system. Thus, according to aspects of this embodiment, the various embodiments of the time of flight systems disclosed herein can be used to monitor a bridge for example for performing

in situ monitoring of real time load dynamics of a bridge structure to quantify acceptable structural integrity characteristics which may be compared over time with actual bridge loads to determine structural degradation and thereby alert repair.

#### Other Examples

**[0153]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used to accomplish precise distance measurements.

**[0154]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used to accomplish multiple distance measurements for multilateration.

**[0155]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used to accomplish highly precise absolute TOF measurements.

**[0156]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used to accomplish precision localization of a plurality of transceivers.

**[0157]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used to accomplish ranging with a hyperbolic time difference of arrival methodology.

**[0158]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can use any pulse compressed signal.

**[0159]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, each transponder can be configured to detect a signal of a unique code and respond only to that unique code.

**[0160]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, a plurality of transmitters or transceivers can be networked together and configured to transmit at regular, precisely timed intervals, and a plurality of transponders can be configured to receive the transmissions and localize themselves via a hyperbolic time difference of arrival methodology.

**[0161]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, at least one transceiver is carried on a vehicle.

**[0162]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, at least one transceiver is carried on an unmanned aerial vehicle.

**[0163]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, at least one transceiver may be fixed to a person or animal, or to clothing, or embedded in clothing, a watch, or wristband, or embedded in a cellular or smart phone or other personal electronic device, or a case for a cellular or smart phone or other personal electronic device.

**[0164]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, transceivers can discover each other and make an alert regarding the presence of other transceivers. Such discovery and/or alerts may be triggered by responses to interrogation signals or may be triggered by enabling transceivers via an auxiliary wireless signal as discussed. For example, vehicles could broadcast a BLE signal that activates any TOF transceiver in its path and thereby discover humans, animals, vehicles, or other objects in its path. Similarly, a human, animal, or vehicle in the path may be alerted to the approaching vehicle. In another

scenario, people with transceivers on their person may be alerted to other people's presence, e.g., when joining a group or entering a room or otherwise coming in to proximity. In such a scenario, distance and location information may be provided to one or more of the people.

**[0165]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, a plurality of transponders are carried on an unmanned vehicle and are configured to make up a wireless network for ranging to the at least one transceiver.

**[0166]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can comprise a wireless network of wireless transponders in fixed locations, and wherein the element to be tracked includes at least one transceiver that pings the wireless transponders with coded pulses so that the transponders only respond and reply with precisely coded pulses. According to aspects of this embodiment, the system can use any pulse compressed signal. According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system further comprises a wireless network of wireless transponders in fixed locations that interrogate and reply to each other for purposes of measuring a baseline between the wireless transponders for calibrating the network.

**[0167]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, an object to be tracked includes at least one transceiver that is configured to transmit the first signal to interrogate one of a plurality of transponders in the network, and wherein the at least one transponder is configured to respond to the first signal and to transmit a signal to interrogate one or more other transponders in the network, and wherein the one or more other transponders emit a second signal that is received by the original interrogator-transceiver for purposes of calibration.

**[0168]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, an object being tracked can comprise multiple transceivers wired together to form an object network, each transceiver being capable of interrogating and receiving from a network of transponders for purposes of making multiple measurements from the vehicle measuring orientation such as pitch and roll of the vehicle.

**[0169]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system further comprises a wireless network of wireless transceivers in fixed locations that transmit and reply to each other for purposes of measuring a baseline between the wireless transceivers for calibrating the network.

**[0170]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system comprises at least one transponder that is programmed to send a burst of data and its timing transmission and including data for purposes of revealing any of temperature, battery life, other sensor data, and other characteristics of the transponder.

**[0171]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can include wireless transponders configured to send ranging signals between each of the transponders for measuring distances between transponders.

**[0172]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can include multiple unmanned vehicles that can be tracked by the system, each unmanned vehicle having a transceiver or

transponder configured for sending and receiving signals to range to each other so that the multiple unmanned vehicles move precisely with respect to each other, and each unmanned vehicle further comprises a transmitter and/or receiver for transmitting and/or receiving signals for purposes of capturing data with each unmanned vehicle. According to aspects of this embodiment, the multiple unmanned vehicles are configured to hold position with respect to each other or fly precision control lines so as to make up an array of sensors, and the transmitters and/or receivers are configured to transmit and/or receive signals for mapping a surface or for other data collection. According to aspects of this embodiment, the multiple unmanned vehicles can be configured to hold position with respect to each other so as to fly in an orbit around an object to be imaged, and wherein the transmitters and/or receivers can be configured to transmit and/or receive signals for imaging the object.

**[0173]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can include multiple unmanned vehicles that are being tracked by the system, each unmanned vehicle having a transceiver or transponder configured for sending and receiving signals to range to each other so that the multiple unmanned vehicles move precisely with respect to each other, and each unmanned vehicle further comprises a transmitter and/or receiver for transmitting and/or receiving signals so that the multiple unmanned vehicles self-position for purposes of creating a precision navigation network in an unprepared environment. According to aspects and embodiments of this embodiment, a first unmanned vehicle can be configured to fly to a fixed location, and another unmanned vehicle includes can be configured with an inertial or acceleration sensor so that it navigates itself by ranging to the fixed location of the first unmanned vehicle by creating a synthetic baseline, by integrating an accelerometer signal and ranging over time in order to localize itself relative to a fixed point.

**[0174]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can include a plurality of transponders or transceivers that are configured to be placed at various points on a human body and are configured to measure precise ranges between each other, the system can be further configured to collect and record such measurements in a central processor for purposes of identifying any of motion patterns for exercise, physical therapy, locomotion aberrations, and progression of disease-related movement defects or tremors.

#### Example Purposes

**[0175]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used for measuring precise travel times between two points so as to measure changes in propagation characteristics of the medium.

**[0176]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used as a synthetic aperture for providing position information of any measured quantity in a two or three dimensional space. For example, light intensity in a room may be measured at various positions, for instance by moving around a light sensor equipped with a TOF ranging device, and the system may record the light intensity at the precise TOF locations to enable a two or three dimensional model or image to be re-created. The light intensity information

could include multiple channels, such as for red, green, and blue color information. Any measurable quantity of interest may be 2-D or 3-D mapped. Other measured quantities might include sound intensity levels, such as in a performance hall, industrial environment, or within or around a piece of machinery; temperature, such as at various positions within a room, in a home, office, or inside a refrigerator, radiation levels, such as inside a reactor room or control room, outside a shipping container being inspected, or in and around an area of interest (on the ground or in the airways above) such as a disaster area or a military complex.

**[0177]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can include a plurality of unmanned vehicles that include a laser scanner or other type of sensor, the sensor or the plurality of laser scanners configured to collectively create a physical map of a local area. According to aspects of this embodiment, the unmanned vehicles can comprise a thermal or chemical sensor, the thermal or chemical sensor configured to collectively create a thermal or chemical map of a local area. According to aspects of this embodiment, the sensors or the plurality of laser scanners can be configured to collectively map the heights of crops, and provide day-to-day comparisons to measure crop growth rates. According to aspects of this embodiment, the unmanned vehicles can be configured to fly with respect to each other to make up a measurement array for purposes of mapping and detecting buried objects such as land mines, electromagnetic fields, chemical concentrations/plumes, or the settling of structures.

**[0178]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used for earthquake and volcano lava dome monitoring and to provide an early warning system.

**[0179]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used as guide localization technology, for example where a museum could be configured with a plurality of TOF transmitters or transceivers/interrogators to locate various transponders implemented in a device such as, for example, a cell phone. The Museums could be outfitted with beacons that tell you which exhibits are near and guide you to the various exhibits. A visitor to the museum could, for example, download an app for the museum on their smart phone, and the system could serve as the measurement source and overall guide to the visitor. The system could also be configured to push information about the exhibit to be shown on the user's phone.

**[0180]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used to navigate an unmanned vehicle so that an operator can remain in safe, well-defined areas and/or within a line-of-site to unmanned vehicle. According to aspects of this embodiment, the system can be used for creating forward supply depots, moving materials and supplies to troop areas.

**[0181]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can include at least one transceiver carried on an unmanned aerial vehicle for guiding the unmanned vehicle, the unmanned vehicle further comprising GPS receivers to receive GPS signals to navigate the unmanned vehicles, the at least one transceiver configured to navigate the unmanned vehicle for package delivery in addition to or in cooperation

with the GPS receivers, the at least one transceiver configured to transmit and/or receive signals from time of flight transmitters or transponders placed on land structures to create a navigation network of beacons for guiding the unmanned vehicle. According to aspects of this embodiment, the system can be used for comprise gas/service stations configured to navigate unmanned vehicles for landing and so that the unmanned can be services, for example to swap out batteries, recharge batters, or land for repairs in the event of failure. According to aspects of this embodiment, a package for pickup and/or delivery is configured with a TOF beacon for guiding the unmanned vehicle to pickup and/or deliver the package.

**[0182]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can include at least one transceiver carried on an unmanned aerial vehicle for guiding the unmanned vehicle and a transceiver/transponder configured to transmit and receive signals with the transceiver on the unmanned vehicle so as to keep a camera disposed on the unmanned vehicle in a fixed position with respect to transceiver/transponder, the transceiver/transponder configured to worn by or attached to any of an object, person, animal, living being for taking videos and/or pictures of the person, animal, living being. According to aspects of this embodiment, the transceiver/transponder can be attached to a cameraman and the camera is configured to take pictures of news events. According to aspects of this embodiment, the transceiver/transponder can be attached to a paramedic and the unmanned vehicle is configured for delivering supplies and/or equipment including a portable defibrillator, or medications or supplies to the paramedic at the site of the patient. According to aspects of this embodiment, the transceiver/transponder can be placed on wild animals such as endangered African elephants so that the unmanned vehicle follows and monitors the wild animals. According to aspects of this embodiment, the transceiver/transponder can be placed on the roof of a police car during a traffic stop so that the unmanned vehicle is tethered to the police car, and wherein the tether of the unmanned vehicle is configured to play out so that the drone gains altitude as police officer walks further from squad car. According to aspects of this embodiment, the transceiver/transponder can be provided to family members or caregivers of people suffering from communicable disease is rural area so that the unmanned vehicles delivers supplies/medication to home-confined patients and their caregivers, avoiding land-based transport of supplies and potential disease exposure to healthcare workers.

**[0183]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used for tracking a person's hands and a robotic arm for purposes of human-robot collaboration, training or other performance monitoring.

**[0184]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used for measuring physiological parameters, such as heart and respiration rates, for example.

**[0185]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used for precisely locating medical or surgical instruments inside the body.

**[0186]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used for deploying an airbag.

**[0187]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used for measuring collision detection between helmets and for triggering airbag deployment or (or other technology) other collision protection systems.

**[0188]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used for monitoring the motion of body parts in relation to one another for health and fitness purposes.

**[0189]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used for measuring kinesthetic feedback for robotic-assisted mechanical exoskeleton arms and legs.

**[0190]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used for measuring changes in gait, tremors, restless leg motion, early warning for Parkinson's or other motion degradation diseases.

**[0191]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used for monitoring a building for purpose of any of inspection, quality control, and health monitoring.

**[0192]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can include a plurality of transponders placed in fixed points around a building/structure, and the system can be configured to measure shifting/settling of the structure. According to aspects of this embodiment, the plurality of transponders is placed in fixed points on a fence enabling an unmanned vehicle to fly around the perimeter for fence inspections.

**[0193]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be configured for verification of construction specifications.

**[0194]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used for precisely tracking human limbs and robotic arms to enable robots to avoid collisions and better collaborate with human co-workers. According to aspects of this embodiment, the system can be configured to enable mobile robots to become position-aware of human collaborators with transponders for safety. According to aspects and embodiments of this embodiment, the system can be configured for tracking an end effector on a robot arm.

**[0195]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be configured for tracking hands of human pilots in a cockpit for training and monitoring.

**[0196]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be configured for tracking an end effector on a robot arm.

**[0197]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used for configured for precision ranging between two phones for purposes of coordinating activities.

**[0198]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be configured for precision ranging between a phone and an object such as a parked car.

**[0199]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be configured measuring precise locomotion of people at sporting, convention and other events.

**[0200]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can

include at least one transmitter configured as a transceiver placed at an intersection, e.g., on a traffic light, and a transponder placed in or on an automobile for purposes of vehicle navigation and/or collision avoidance, so that when an automobile approaches an intersection, a precision range to the traffic light transponder is obtained for purposes of calibrating and resetting automobile navigation solution to a high level of precision.

**[0201]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used for configured as a part of a vehicle-to-vehicle communications system, where each vehicle interrogates its surroundings and receives replies from nearby comparably equipped vehicles providing precision ranging and other data.

**[0202]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can include a network of transceivers distributed in a garage or parking facility to enable an automobile with autonomous control system to approach and align/park precisely.

**[0203]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be configured for measurement of travel time between two points for purposes of measuring changes in radio-propagation for monitoring changes in the medium between the points.

**[0204]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can include two or more transponders housed on two or more orbiting vehicles for purposes of approaching, docking, and refueling, at least one of the orbiting vehicles.

**[0205]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can include two or more UAVs configured for precision movement with respect to each other and for using precision radar as a penetrating signal for circling and measuring a weather event such as a tornado, a hurricane, etc.

**[0206]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can include two or more UAVs are configured for precision movement with respect to each other and for transmitting and receiving a body penetrating signal for human body tomography based on measurements of the body penetrating signal propagation.

**[0207]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can include two or more transceivers configured for movement on a circular track and for taking multiple measurements while spinning around for purposes of measuring characteristics of an object at the center of the circular track.

**[0208]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can include multiple transponders placed on a human body in the presence of a network of transceivers and the individual points on the body can be tracked during motion for the purpose of capturing motion for film creation.

**[0209]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, a transmitter or receiver can be placed in any of a ball, a pucks, etc. for purposes of any of goal detection, monitoring a position of a ball, training, camera following, and other analytics.

**[0210]** According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used to provide a wireless tether between a rider of a

surfboard and an UAV housing a camera for the purpose of following a surfer on the surf board and taking a video of the surfer with the camera.

[0211] According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used to provide a wireless tether between a rider of a bicycle and an UAV housing a camera for the purpose of following a rider on a bicycle and taking a video of the rider with the camera.

[0212] According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used to provide a wireless tether between a skier or snowboarder and an UAV housing a camera for the purpose of following the skier or snowboarder and taking a video of the skier or snowboarder with the camera.

[0213] According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used to create an invisible fence for pets and for monitoring of pets.

[0214] According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used for tracking a hand, a toy bat, a toy gun within a room environment for purposes of coordinating with a motion sensing gaming device.

[0215] According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used for guiding of an aerial vehicle for refueling of airplanes.

[0216] According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used for refueling of a UAV.

[0217] According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can include a UAV having a video camera that follows a suspect who has been “shot” with a non-lethal goop/net containing a transponder for tracking and apprehending.

[0218] According to aspects and embodiments of any of the TOF ranging systems disclosed herein, the system can be used for collecting data on the motion of objects in space and stored for analytics.

[0219] Having described above several aspects of at least one embodiment, it is to be appreciated various alterations, modifications, and improvements will readily occur to those skilled in the art. Such alterations, modifications, and improvements are intended to be part of this disclosure and are intended to be within the scope of the invention. Accordingly, the foregoing description and drawings are by way of example only, and the scope of the invention should be determined from proper construction of the appended claims, and their equivalents.

What is claimed is:

1. A system for measuring time of flight to an object, comprising:

at least one transmitter configured to transmit an electromagnetic signal and provide a reference signal corresponding to the electromagnetic signal;

at least one receiver configured to receive the electromagnetic signal and in response provide a response signal corresponding to the received electromagnetic signal; and

a detection circuit configured to determine a time of flight between the transmitter and the receiver based upon the reference signal and the response signal.

2. The system of claim 1 wherein the detection circuit is further configured to determine a distance between the transmitter and the receiver based at least in part upon the time of flight.

3. The system of claim 1 wherein the electromagnetic signal is one of a frequency modulated continuous wave (FMCW) signal, a direct sequence spread spectrum signal (DSSS), a pulse compressed signal, and a frequency hopping spread spectrum (FHSS) signal.

4. The system of claim 1 wherein the detection circuit includes a mixer that receives the reference signal and the response signal, and provides a beat signal corresponding to the time of flight between the transmitter and the receiver.

5. The system of claim 4 wherein the detection circuit further comprises:

an analog to digital converter that receives the beat signal and provides a sampled beat signal; and

a processor coupled to an output of the analog to digital converter that receives the sampled beat signal and performs a fast Fourier transform on the sampled beat signal.

6. The system of claim 1 further comprising a cable coupled between the detection circuit and at least one of the transmitter and the receiver, the cable configured to convey to the detection circuit at least one of the reference signal and the response signal.

7. The system of claim 1 wherein the detection circuit is configured to wirelessly receive at least one of the reference signal and the response signal.

8. The system of claim 1 wherein the transmitter includes a pseudo noise generator.

9. The system of claim 1 wherein the transmitter is configured to transmit and the receiver is configured to receive the electromagnetic signal having one of a command protocol and an embedded unique code in the electromagnetic signal to address and enable each receiver.

10. The system of claim 1 wherein the receiver further comprises an auxiliary wireless receiver configured to receive an auxiliary wireless signal configured with a unique code to target the receiver, and wherein the receiver is further configured to power up the receiver to provide the response signal when the receiver has received the auxiliary wireless signal and not to provide the response signal when the receiver has not received the auxiliary wireless signal.

11. The system of claim 10, wherein the auxiliary wireless receiver is configured to receive the auxiliary wireless signal that is any of a Bluetooth signal, a Zigbee signal, a Wi-Fi signal, and a cellular signal.

12. The system of claim 10, wherein the receiver further comprises:

at least one antenna configured to receive the electromagnetic signal at a first frequency; and

a multiplier coupled to the at least one antenna to receive the electromagnetic signal at the first frequency and that provides a multiplied signal having a harmonic component at a second frequency that is a harmonic multiple of the first frequency.

13. The system of claim 12, wherein the receiver further comprises a power source that is configured to normally bias the multiplier to a biased off state and that is configured to bias on the multiplier to an on state in response to receipt of the auxiliary wireless signal configured with the unique code to target the receiver.



**14.** The system of claim **13**, wherein the power source is further configured to forward bias the multiplier to increase a sensitivity and range of the receiver.

**15.** The system of claim **13**, wherein the receiver has no active components other than the multiplier, which is configured to normally be off so as to require substantially no power.

**16.** The system of claim **15**, wherein the power source is one of a low power battery source or power is derived by one or more energy harvesting techniques.

**17.** The system of claim **15**, wherein the at least one antenna comprises a single antenna for both receiving the electromagnetic signal at the first frequency and transmitting the multiplied signal at the second frequency.

**18.** The system of claim **12**, wherein the receiver further comprises the multiplier integrated with the at least one antenna element.

**19.** The system of claim **12**, wherein the transmitter further comprises a plurality of receive channels configured to receive the electromagnetic signal at the second frequency in a spatially diverse array.

**20.** The system of claim **19**, wherein the plurality of receive channels can either be multiplexed to receive the electromagnetic signal at the second frequency at different times or can be configured to operate simultaneously.

**21.** The system of claim **12**, wherein the transmitter is configured to provide a modulated electromagnetic signal and the receiver is configured to receive the modulated electromagnetic signal to uniquely address the receiver.

**22.** The system of claim **12**, wherein the transmitter and the receiver are configured to operate simultaneously.

**23.** The system of claim **1**, wherein the transmitter comprises in phase and 90° out of phase (quadrature) channels with multipliers that are modulated in quadrature to send coded electromagnetic signals to a plurality of receivers simultaneously.

**24.** The system of claim **1**, wherein the at least one receiver includes a plurality of receivers and the at least one transmitter and the plurality of receivers are configured to time share and uniquely address each receiver of the plurality of receivers.

**25.** The system of claim **1**, wherein the at least one receiver includes a plurality of receivers and the at least one transmitter and the plurality of receivers are configured to dynamically assess and address the plurality of receivers that are moving faster than others more frequently.

**26.** The system of claim **1**, wherein the at least one receiver includes a plurality of receivers and the at least one transmitter and the plurality of receivers are configured with their own proprietary micro-location frequency allocation protocol so that the receiver and at least one transmitter can operate at unused frequency bands that exist amongst existing allocated frequency bands.

**27.** The system of claim **26**, wherein the at least one transmitter and the plurality of receivers are configured to license-free bands.

**28.** The system of claim **27**, wherein the at least one transmitter and the plurality of receivers are configured to communicate with existing systems at existing licensed frequencies to use existing frequency allocations in situations that warrant using existing frequency band allocations.

**29.** The system of claim **27**, wherein the at least one transmitter and the plurality of receivers are configured to

detect loading issues within any used frequency band and to allocate signals to be used based on system usage.

**30.** The system of claim **1**, further comprising a plurality of transmitters configured to transmit a plurality of electromagnetic signals, the detection circuit configured to determine one or more distances between the receiver and one or more of the transmitters.

**31.** The system of claim **12**, wherein the detection circuit is further configured to determine a position of the receiver at least in part from one or more of the one or more distances.

**32.** The system of claim **1**, further comprising a plurality of transmitters configured to transmit a plurality of electromagnetic signals, the detection circuit configured to determine one or more time differences of arrival between two or more of the plurality of electromagnetic signals.

**33.** The system of claim **32**, wherein the detection circuit is further configured to determine a position of the receiver at least in part from one or more of the one or more time differences of arrival.

**34.** A method of measuring time of flight to an object, comprising:

receiving a reference signal from an interrogator, the reference signal corresponding to an electromagnetic signal transmitted by the interrogator;

receiving a response signal from a transponder, the response signal provided by the transponder in response to receiving the electromagnetic signal, and the response signal corresponding to the received electromagnetic signal; and

determine a time of flight of the electromagnetic signal between the interrogator and the transponder based upon the reference signal and the response signal.

**35.** The method of claim **34**, further comprising determining the distance between the interrogator and the transponder based at least in part upon the time of flight.

**36.** The method of claim **34**, wherein the electromagnetic signal is one of a frequency modulated continuous wave (FMCW) signal, a direct sequence spread spectrum (DSSS) signal, a pulse compressed signal, and a frequency hopping spread spectrum (FHSS) signal.

**37.** The method of claim **34**, wherein determining the time of flight includes mixing the response signal and the reference signal to provide a beat signal corresponding to the time of flight.

**38.** The method of claim **37**, further comprising:

converting the beat signal into a digital form to provide a sampled beat signal; and

performing a fast Fourier transform on the sampled beat signal.

**39.** The method of claim **34**, wherein at least one of the reference signal and the response signal are received via a cable.

**40.** The method of claim **34**, wherein at least one of the reference signal and the response signal are received wirelessly.

**41.** The method of claim **34**, wherein the electromagnetic signal is generated, at least in part, from a pseudo noise generator.

**42.** The method of claim **34**, wherein the response signal is received from the transponder only when the transponder has received an auxiliary signal, and the response signal is not received from the transponder when the transponder has not received the auxiliary signal.

**43.** The method of claim **42**, wherein the auxiliary signal is one of a Bluetooth signal, a Zigbee signal, a Wi-Fi signal, a cellular signal, and a unique code.

**44.** The method of claim **34**, further comprising:  
receiving a plurality of response signals from the transponder, each of the plurality of response signals provided in response to receiving one of a plurality of electromagnetic signals from a plurality of interrogators; and

determining one or more distances between the transponder and one or more of the plurality of interrogators.

**45.** The method of claim **44**, further comprising determining a position of the transponder at least in part from one or more of the one or more distances.

**46.** The method of claim **34**, further comprising:  
receiving a plurality of response signals from the transponder, each of the plurality of response signals provided in response to receiving one of a plurality of electromagnetic signals from a plurality of interrogators; and

determining one or more time differences of arrival between two or more of the plurality of electromagnetic signals.

**47.** The method of claim **46**, further comprising determining a position of the transponder at least in part from one or more of the one or more time differences of arrival.

\* \* \* \* \*