




US 20220031343A1


(19) **United States**(12) **Patent Application Publication**  
**Friedman et al.**(10) **Pub. No.: US 2022/0031343 A1**(43) **Pub. Date: Feb. 3, 2022**(54) **RADIAL EXPANSION CONTROL  
MECHANISMS FOR INTRALUMINAL  
DEVICE**(71) Applicant: **RAPID MEDICAL LTD., YOKNEAM  
(IL)**(72) Inventors: **Aharon Friedman**, Haifa (IL); **Matan  
Gedulter**, Givat Ela (IL); **Moshe  
Miller**, Jerusalem (IL)(73) Assignee: **RAPID MEDICAL LTD., YOKNEAM  
(IL)**(21) Appl. No.: **17/451,116**(22) Filed: **Oct. 15, 2021****Related U.S. Application Data**(63) Continuation of application No. 16/265,891, filed on  
Feb. 1, 2019, now Pat. No. 11,179,171, which is a  
continuation-in-part of application No. PCT/IB2017/  
001773, filed on Dec. 18, 2017.(60) Provisional application No. 62/435,796, filed on Dec.  
18, 2016.**Publication Classification**(51) **Int. Cl.****A61B 17/221** (2006.01)**A61F 2/01** (2006.01)(52) **U.S. Cl.**CPC .. **A61B 17/221** (2013.01); **A61B 2017/22034**  
(2013.01); **A61F 2/01** (2013.01)

(57)


**ABSTRACT**

An intraluminal device and a method of removing a clot from a body lumen with an intraluminal device may be provided. The intraluminal device may include a hollow elongated shaft and a radially-expandable mesh segment situated distal to the elongated shaft. The elongated shaft may be secured relative to a first portion of the mesh segment. The intraluminal device may additionally include a core wire affixed to a second portion of the mesh segment and extending through the elongated shaft. The elongated shaft may be configured to radially expand the mesh segment by axially moving the first portion of the mesh segment relative to the second portion of the mesh segment. In addition, the core wire may be configured to radially expand the mesh segment by axially moving the second portion of the mesh segment relative to the first portion of the mesh segment.





**FIG. 1**



**FIG. 2**






FIG. 3




FIG. 4







FIG. 5



**FIG. 8**






FIG. 9B

FIG. 9A




FIG. 10B






FIG. 10A



**FIG. 11**



**FIG. 12**






FIG. 13







FIG. 14

















# OF WIRES	JUNCTION IN STANDARD BRAIDING	NO SLIPPAGE JUNCTION IN DEVICE	JUNCTION IMAGE	DEVICE IMAGE
8		 2 WIRES 2 WIRES 2 WIRES 2 WIRES		
10		 2 WIRES 3 WIRES 3 WIRES 2 WIRES		
12		 2 WIRES 2 WIRES 2 WIRES 2 WIRES 2 WIRES 2 WIRES		

FIG. 19A




FIG. 19B









FIG. 19C




**FIG. 21A**

**FIG. 21B**







**FIG. 22A**




**FIG. 22B**



**FIG. 22C**




**FIG. 23A**




**FIG. 23B**







**FIG. 24**




**FIG. 25**




**FIG. 26A**



**FIG. 26B**




**FIG. 27**




**FIG. 28**







**FIG. 29A**




**FIG. 29B**




**FIG. 29C**  
*Prior Art*




**FIG. 29D**



**FIG. 30A**




**FIG. 30B**




**FIG. 30C**







**FIG. 31A**




**FIG. 31B**




**FIG. 31C**



**FIG. 32A**




**FIG. 32B**




**FIG. 32C**







**FIG. 33A**




**FIG. 33B**




**FIG. 33C**



**FIG. 34A**








**FIG. 34B**



**FIG. 34C**












FIG. 36D




FIG. 36F




FIG. 36C







FIG. 36E



**FIG. 37A**





**FIG. 37B**



**FIG. 37C**










FIG. 39A




FIG. 39B

# **RADIAL EXPANSION CONTROL MECHANISMS FOR INTRALUMINAL DEVICE**

## **CROSS-REFERENCE TO RELATED APPLICATIONS**

**[0001]** This application is a Continuation-In-Part of International Application No. PCT/IB2017/001773, filed Dec. 18, 2017, which claims the benefit of priority from U.S. Provisional Application No. 62/435,796, filed Dec. 18, 2016, both of which are herein incorporated by reference in their entireties.

## **TECHNICAL FIELD**

**[0002]** This disclosure relates to intravascular and/or intraluminal medical devices that are configured to retrieve an obstruction from human blood vessels. Obstructions to be retrieved can include clots and clot material.

## **SUMMARY**

**[0003]** Embodiments of the present disclosure may include an intraluminal device including a hollow elongated shaft extending between a distal end thereof and a proximal end thereof. The intraluminal device may additionally include a first mesh segment situated distal to the elongated shaft. The first mesh segment may be configured to transition between a radially-contracted state and a radially-expanded state. In the radially-contracted state, a distal end of the first mesh segment may be spaced a first distance from a proximal end of the first mesh segment. In the radially-expanded state, the distal end of the first mesh segment may be spaced a second distance from the proximal end of the first mesh segment. The first distance may be greater than the second distance. The intraluminal device may additionally include a core wire affixed to at least a portion of the first mesh segment. The core wire may be configured for axial movement. The axial movement of the core wire may control movement of the first mesh segment between the radially-contracted state and the radially-expanded state by adjusting a distance between the proximal and distal ends of the first mesh segment. The intraluminal device may additionally include a first mesh expansion limiter situated at least partially within the first mesh segment. The first mesh expansion limiter may be configured to hold the proximal and distal ends of the first mesh segment apart by a minimum distance equal to the second distance.

**[0004]** The core wire may be affixed to the distal end of the first mesh segment. The proximal end of the first mesh segment may be secured to the distal end of the elongated shaft. The first mesh segment may include a plurality of wires woven to form the first mesh segment. The first mesh segment may be configured to capture a blood clot. The first mesh segment may be configured to be retained within a delivery catheter when the first mesh segment is in the radially-contracted state. The first mesh segment may be configured to assume a first diameter when the first mesh segment is in the radially-contracted state. The first mesh segment may also be configured to assume a second diameter when the first mesh segment is in the radially-expanded state. The second diameter may be larger than the first diameter. The first mesh expansion limiter may be configured to prevent radial expansion of the first mesh segment beyond the second diameter. The first mesh expansion

limiter may include a cylindrical shaft having an axial length approximately equal to the second distance. The first mesh expansion limiter may include an elastic coil configured to have a minimum axial length approximately equal to the second distance. The elastic coil may be configured to stretch from an axial length equal to the second distance to an axial length equal to the first distance. The elastic coil of the first mesh expansion limiter may be contained within the first mesh segment and may be configured to abut the proximal and distal ends of the first mesh segment. The elastic coil of the first mesh expansion limiter may be biased to hold the proximal and distal ends of the first mesh segment apart by at least the first distance. The intraluminal device may additionally include a second mesh segment arranged between the first mesh segment and the distal end of the elongated shaft. The second mesh segment may be configured to transition between a radially-contracted state and a radially-expanded state. In the radially-contracted state, a distal end of the second mesh segment may be spaced a third distance from a proximal end of the second mesh segment. In the radially-expanded state, the distal end of the second mesh segment may be spaced a fourth distance from the proximal end of the second mesh segment. The third distance may be greater than the fourth distance. The axial movement of the core wire may control movement of the second mesh segment between the radially-contracted state and the radially-expanded state by adjusting a distance between the proximal and distal ends of the second mesh segment. The intraluminal device may additionally include a second mesh expansion limiter situated at least partially within the second mesh segment. The second mesh expansion limiter may be configured to hold the proximal and distal ends of the second mesh segment apart by a minimum distance equal to the fourth distance. The second mesh expansion limiter may include a cylindrical shaft having an axial length approximately equal to the fourth distance. The second mesh expansion limiter may include an elastic coil configured to have a minimum axial length approximately equal to the fourth distance and configured to extend from the fourth distance to the third distance. The elastic coil of the second mesh expansion limiter may be contained within the second mesh segment and may be configured to abut the proximal and distal ends of the second mesh segment. The elastic coil of the second mesh expansion limiter may be biased to hold the proximal and distal ends of the second mesh segment apart by at least the third distance. The first mesh segment may be configured for radial expansion independent of radial expansion of the second mesh segment. The core wire may be devoid of connections to the second mesh segment.

**[0005]** Alternative embodiments of the present disclosure may include a method of removing occlusive material from a body lumen. The method may include positioning a first mesh segment of an intraluminal device downstream of the occlusive material in the body lumen. The first mesh segment may be arranged in a first radially-contracted state in which a distal end of the first mesh segment may be spaced a first distance from a proximal end of the first mesh segment. The method may additionally include arranging the first mesh segment in a first radially-expanded state in which the distal end of the first mesh segment may be spaced a second distance from the proximal end of the first mesh segment. The first distance may be greater than the second distance. A first mesh expansion limiter situated at least



partially within the first mesh segment may prevent a distance between the proximal and distal ends of the first mesh segment from decreasing below the second distance. The method may additionally include moving the radially-expanded first mesh segment into engagement with the occlusive material. The method may additionally include removing the occlusive material by moving the radially-expanded first mesh segment in an upstream direction.

**[0006]** The intraluminal device may include a hollow elongated shaft having a distal end and a proximal end. The first mesh segment may be situated distally of the elongated shaft. The intraluminal device may additionally include a core wire affixed to at least a portion of the first mesh segment. Axial movement of the core wire may control movement of the first mesh segment between the first radially-contracted state and the first radially-expanded state by adjusting a distance between the proximal and distal ends of the first mesh segment. The core wire may be affixed to the distal end of the first mesh segment and the proximal end of the first mesh segment may be secured to the distal end of the elongated shaft. The first mesh expansion limiter may prevent radial expansion of the first mesh segment beyond a predetermined diameter while the first mesh segment is arranged in the first radially-expanded state. The first mesh expansion limiter may include a cylindrical shaft having an axial length approximately equal to the second distance. The first mesh expansion limiter may include an elastic coil. The elastic coil may have a first axial length approximately equal to the first distance during positioning of the first mesh segment downstream of the occlusive material and a second axial length approximately equal to the second distance while the first mesh segment is arranged in the first radially-expanded state. The elastic coil of the first mesh expansion limiter may be contained within the first mesh segment and may abut the proximal and distal ends of the first mesh segment during positioning of the first mesh segment downstream of the occlusive material. The method may additionally include positioning a second mesh segment of the intraluminal device in the body lumen while the second mesh segment is arranged in a second radially-contracted state in which a distal end of the second mesh segment may be spaced a third distance from a proximal end of the second mesh segment. The method may additionally include arranging the second mesh segment in a second radially-expanded state in which the distal end of the second mesh segment may be spaced a fourth distance from the proximal end of the second mesh segment. The third distance may be greater than the fourth distance. A second mesh expansion limiter situated at least partially within the second mesh segment may prevent a distance between the proximal and distal ends of the second mesh segment from decreasing below the fourth distance. The second mesh segment may be arranged in the second radially-expanded state prior to the first mesh segment being arranged in the first radially-expanded state. The second mesh segment may be arranged in the second radially-expanded state after the first mesh segment is arranged in the first radially-expanded state. The second mesh expansion limiter may prevent radial expansion of the second mesh segment beyond a predetermined diameter while the second mesh segment is arranged in the second radially-expanded state. The second mesh expansion limiter may include a cylindrical shaft having an axial length approximately equal to the fourth distance. The second mesh expansion limiter may include an elastic coil. The elastic

coil may have a first axial length approximately equal to the third distance during positioning of the second mesh segment in the body lumen and a second axial length approximately equal to the fourth distance while the second mesh segment is arranged in the second radially-expanded state. The elastic coil of the second mesh expansion limiter may be contained within the second mesh segment and may abut the proximal and distal ends of the second mesh segment during positioning of the second mesh segment in the body lumen.

**[0007]** Further alternative embodiments of the present disclosure may include an intraluminal device having a hollow elongated shaft that may include a distal end and a proximal end. The intraluminal device may additionally include a first radially-expandable mesh segment situated distal to the elongated shaft. The elongated shaft may be secured relative to a first portion of the first mesh segment. The intraluminal device may additionally include a core wire affixed to a second portion of the first mesh segment and extending through the elongated shaft. The elongated shaft may be configured to radially expand the first mesh segment by axially moving the first portion of the first mesh segment relative to the second portion of the first mesh segment. The core wire may be configured to radially expand the first mesh segment by axially moving the second portion of the first mesh segment relative to the first portion of the first mesh segment.

**[0008]** The first portion of the first mesh segment may include a proximal end of the first mesh segment. The second portion of the first mesh segment may include a distal end of the first mesh segment. The axial movement of the first portion of the first mesh segment may be in a distal axial direction relative to the second portion of the first mesh segment. The axial movement of the second portion of the first mesh segment may be in a proximal axial direction relative to the first portion of the first mesh segment. The elongated shaft and core wire may be configured to simultaneously radially expand the first mesh segment. The elongated shaft and core wire may be configured to effect equidistant axial movement of the first portion of the first mesh segment and the second portion of the first mesh segment, respectively. The intraluminal device may additionally include a handle situated proximal to the elongated shaft. The elongated shaft and the core wire may be configured for axial movement relative to the handle. The handle may include a first handle segment secured relative to the core wire and a second handle segment secured relative to the elongated shaft. The first handle segment and second handle segment may be configured for equidistant movement in opposite axial directions. The handle may be configured to be secured relative to a delivery catheter such that the elongated shaft and the core wire may be configured for axial movement relative to the delivery catheter. The handle may additionally include a locking shaft extending from the distal end of the handle over at least a portion of the elongated shaft. The locking shaft of the handle may be configured to be secured to at least a portion of the delivery catheter. The first mesh segment may include a plurality of wires woven to form the first mesh segment. The first mesh segment may be configured to capture a blood clot. The intraluminal device may additionally include a second radially-expandable mesh segment situated between the first mesh segment and the elongated shaft. The elongated shaft may be affixed to a proximal end of the second mesh segment and may be configured to radially expand the first



mesh segment and the second mesh segment by axially moving the proximal end of the second mesh segment. The core wire may be configured to radially expand the first mesh segment and the second mesh segment by axially moving a distal end of the first mesh segment. The second mesh segment may include a plurality of wires woven to form the second mesh segment. The second mesh segment may be configured to capture a blood clot.

**[0009]** A still further embodiment of the present disclosure may include a method of removing a clot from a body lumen. The method may include positioning a radially-expandable mesh segment of an intraluminal device downstream of the clot in the body lumen while the mesh segment is in a radially-contracted state. The mesh segment may include a proximal end and a distal end. The method may additionally include radially-expanding the mesh segment by moving the proximal end of the mesh segment a first distance in a first direction and by moving the distal end of the mesh segment a second distance in a second direction. The first distance may be equal to the second distance. The first direction may be opposite the second direction. The method may additionally include moving the radially-expanded mesh segment into engagement with the clot. The method may additionally include removing the clot by moving the radially-expanded mesh segment in an upstream direction.

**[0010]** The proximal and distal ends of the mesh segment may move simultaneously during radial expansion of the mesh segment. The first direction may be a distal direction and the second direction may be a proximal direction. The intraluminal device may include a hollow elongated shaft situated proximal to the mesh segment. The elongated shaft may be secured relative to the proximal end of the mesh segment. The intraluminal device may additionally include a core wire affixed to the distal end of the mesh segment. The intraluminal device may additionally include a handle situated proximal to the elongated shaft. The elongated shaft and the core wire may move axially relative to the handle during radial expansion of the mesh segment. The elongated shaft and the core wire may move simultaneously to radially expand the mesh segment. Radially-expanding the mesh segment may include axially moving the proximal end of the mesh segment relative to the distal end of the mesh segment with the elongated shaft and axially moving the distal end of the mesh segment relative to the proximal end of the mesh segment with the core wire. The handle may include a first handle segment secured relative to the core wire and a second handle segment secured relative to the elongated shaft. The first handle segment and second handle segment may move the same distance in opposite axial directions during radial expansion of the mesh segment.

#### BRIEF DESCRIPTION OF THE DRAWINGS

**[0011]** The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate disclosed embodiments and, together with the description, serve to explain the disclosed embodiments.

**[0012]** FIG. 1 is an illustration of a first exemplary intraluminal device, consistent with at least one of the disclosed embodiments;

**[0013]** FIG. 2 is an illustration of a second exemplary intraluminal device, in accordance with at least one of the disclosed embodiments;

**[0014]** FIG. 3 is an illustration of a third exemplary intraluminal device, in accordance with at least one of the disclosed embodiments;

**[0015]** FIG. 4 is an illustration of a fourth exemplary intraluminal device, in accordance with at least one of the disclosed embodiments;

**[0016]** FIG. 5 is an illustration of a fifth exemplary intraluminal device, in accordance with at least one of the disclosed embodiments;

**[0017]** FIG. 6 is an illustration of a sixth exemplary intraluminal device, in accordance with at least one of the disclosed embodiments;

**[0018]** FIG. 7 is an illustration of a seventh exemplary intraluminal device, in accordance with at least one of the disclosed embodiments;

**[0019]** FIG. 8 is an illustration of exemplary cable interweaving, such as is disclosed in connection with FIG. 7;

**[0020]** FIG. 9A is an illustration of another exemplary intraluminal device, in accordance with at least one of the disclosed embodiments;

**[0021]** FIG. 9B is an enlarged view of a portion of the exemplary intraluminal device shown in FIG. 9A;

**[0022]** FIG. 10A is an illustration of another exemplary intraluminal device, in accordance with at least one of the disclosed embodiments;

**[0023]** FIG. 10B is a cross-sectional view of a portion of the exemplary intraluminal device shown in FIG. 10A;

**[0024]** FIG. 11 is an illustration of a braid structure of an exemplary intraluminal device;

**[0025]** FIG. 12 is an illustration of a braid structure of an exemplary intraluminal device, in accordance with at least one of the disclosed embodiments;

**[0026]** FIG. 13 is a cross section view of an exemplary braided structure without twists, and an associated loaded beam diagram;

**[0027]** FIG. 14 is a cross section view of an exemplary braided structure with twists, and an associated loaded beam diagram;

**[0028]** FIG. 15 is an illustration of an exemplary intraluminal device, consistent with at least one of the disclosed embodiments;

**[0029]** FIG. 16 is an enlarged view of a portion of the exemplary intraluminal device shown in FIG. 15;

**[0030]** FIG. 17 is an enlarged view of a portion of the exemplary intraluminal device shown in FIG. 15 in an expanded position;

**[0031]** FIG. 18 is an illustration of exemplary intraluminal device in an expanded position, in accordance with at least one of the disclosed embodiments;

**[0032]** FIGS. 19A-19C illustrate a number of braiding structures consistent with at least some of the disclosed embodiments;

**[0033]** FIG. 20 is an illustration of another exemplary intraluminal device, in accordance with at least one of the disclosed embodiments;

**[0034]** FIG. 21A is an illustration of another exemplary intraluminal device, in accordance with at least one of the disclosed embodiments;

**[0035]** FIG. 21B is an illustration of the exemplary intraluminal device shown in FIG. 21A in an expanded position;

**[0036]** FIG. 22A is an illustration of another exemplary intraluminal device in a first exemplary position, in accordance with at least one of the disclosed embodiments;



[0037] FIG. 22B is an illustration of the exemplary intraluminal device shown in FIG. 22A in a second exemplary position;

[0038] FIG. 22C is an illustration of the exemplary intraluminal device shown in FIG. 22A in a third exemplary position;

[0039] FIG. 23A is an illustration of another exemplary intraluminal device, in accordance with at least one of the disclosed embodiments;

[0040] FIG. 23B is an illustration of the exemplary intraluminal device shown in FIG. 23A in an expanded position;

[0041] FIG. 24 is an illustration of another exemplary intraluminal device, in accordance with at least one of the disclosed embodiments;

[0042] FIG. 25 is an illustration of another exemplary intraluminal device, in accordance with at least one of the disclosed embodiments;

[0043] FIG. 26A is an illustration of another exemplary intraluminal device, in accordance with at least one of the disclosed embodiments;

[0044] FIG. 26B is an illustration of the exemplary intraluminal device shown in FIG. 26A in an expanded position;

[0045] FIG. 27 is an illustration of another exemplary intraluminal device, in accordance with at least one of the disclosed embodiments;

[0046] FIG. 28 is an illustration of another exemplary intraluminal device, in accordance with at least one of the disclosed embodiments;

[0047] FIGS. 29A and 29B illustrate another exemplary intraluminal device, in accordance with at least one of the disclosed embodiments;

[0048] FIG. 29C is an illustration of a prior art intraluminal device expanded within a body lumen;

[0049] FIG. 29D is an illustration of the exemplary intraluminal device shown in FIGS. 29A and 29B expanded within a body lumen;

[0050] FIGS. 30A and 30B illustrate another exemplary intraluminal device, in accordance with at least one of the disclosed embodiments;

[0051] FIG. 30C is an illustration of the exemplary intraluminal device shown in FIGS. 30A and 30B expanded within a body lumen;

[0052] FIGS. 31A-31C illustrate another exemplary intraluminal device, in accordance with at least one of the disclosed embodiments;

[0053] FIGS. 32A-32C illustrate another exemplary intraluminal device, in accordance with at least one of the disclosed embodiments;

[0054] FIGS. 33A-33C illustrate another exemplary intraluminal device, in accordance with at least one of the disclosed embodiments;

[0055] FIGS. 34A-34C illustrate another exemplary intraluminal device, in accordance with at least one of the disclosed embodiments;

[0056] FIGS. 35A-35C illustrate a method of removing occlusive material from a body lumen with an exemplary intraluminal device, in accordance with at least one of the disclosed embodiments;

[0057] FIGS. 36A and 36B illustrate another exemplary intraluminal device, in accordance with at least one of the disclosed embodiments;

[0058] FIGS. 36C and 36D illustrate enlarged views of an expandable mesh segment of the exemplary intraluminal device shown in FIGS. 36A and 36B;

[0059] FIGS. 36E and 36F illustrate radial-expansion of the mesh segment shown in FIGS. 36C and 36D within a body lumen;

[0060] FIGS. 37A-37C illustrate a handle of an exemplary intraluminal device, in accordance with at least one of the disclosed embodiments;

[0061] FIGS. 38A and 38B illustrate another exemplary intraluminal device, in accordance with at least one of the disclosed embodiments; and

[0062] FIGS. 39A and 39B illustrate an exemplary intraluminal device delivered through an exemplary catheter, in accordance with at least one of the disclosed embodiments.

[0063] Annotations appearing in the figures are exemplary only, and are not restrictive of the invention as claimed.

#### DETAILED DESCRIPTION

[0064] Reference will now be made in detail to the present embodiments (exemplary embodiments) of the disclosure, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts.

[0065] FIG. 1 illustrates an exemplary intraluminal device 1000 including five alternating wire zones 1001, 1002, 1003, 1004, and 1005. Zones 1001, 1003 and 1005 include groups of woven wires 1010 and may provide structural support for zones 1002 and 1004. Additionally, since the openings between wires 1010 of zone 1 and 5 may be much smaller they also may provide a distal and proximal filter. (An example of variable sized openings is illustrated in FIGS. 10A-B, discussed below.) As a result, clot particles that might appear during the retrieval may be captured at these zones, for example. As further shown in FIG. 1, zones 1002 and 1004 may be constructed of looped wires 1020 to allow a large clot capturing area. And also shown in FIG. 1, zones 1001, 1003, and 1005 may be constructed by woven wires 1010. The number of zones illustrated are exemplary. More or less zones may be provided.

[0066] FIG. 2 illustrates an intraluminal device 2000 in a more open position than illustrated in FIG. 1, highlighting the clot entry cells 2020 that may be made from the looped wires 1020. As further shown in FIG. 2, zones 1002 and 1004 may be constructed of looped wires 1020 to allow a large clot capturing area.

[0067] FIG. 3 illustrates yet another exemplary intraluminal device 3000. In this example, as shown in FIG. 3, the device 3000 may be configured so as to include only two different zones. Zone 3001 may be constructed from a group of woven wires 3010, such as for example, densely braided, which provides structural support for the device 3000. In addition, zone 3001 may also serve as a distal filter that prevents emboli from the distal vasculature. As also shown in FIG. 3, zone 3002 may be constructed from wires which are looped which are longitudinally located and provide the clot entry zone 3020. Additionally, zone 3001 may, for example, give structural support and may also serve as a distal filter. As further shown in FIG. 3, zone 3002 may be the clot entering zone.

[0068] FIG. 4 illustrates yet another exemplary intraluminal device 4000 with four regions. In the first region 4001, the wires may be twisted or coiled to form a shaft 4015. In the second region 4002, the wires may be woven to form a scaffold 4017 that supports the opening of the third region 4003. In the third region 4003, the wires may be woven set



in looped pairs to form a clot capture structure **4020**. For example, the wires of the third region **4003** may be loosely looped or loosely coupled. Further, the fourth region **4004** may be woven to form a distal filter **4030** that captures distal emboli or clot particles. The fourth region **4004** may also serve as a scaffold for the third region **4003**.

[0069] FIG. 5 illustrates yet another exemplary intraluminal device **5000**. For example, as shown in FIG. 5, the clot opening region **5001** may be woven from three wires that are looped together. Further, the number of wires that are looped together may be greater than two.

[0070] FIG. 6 illustrates yet another exemplary intraluminal device **6000**. For example, as shown in FIG. 6, the clot opening region **6001** may be woven from three wires that are loosely looped together. Further, the number of wires that are looped together may be greater than two.

[0071] FIG. 7 illustrates yet another exemplary intraluminal device **7000**. For example, as shown in FIG. 7, the device **7000** may include six cables **7025**, in which each cable **7025** may include paired wires. This may create a strong but flexible crossing. And this may further allow, for example, the device **7000** to achieve a flexible structure with a high radial force.

[0072] FIG. 8 illustrates an example of cable interweaving **8000**, as discussed above. Each cable **7025**, for example, may be made from a looped pair of wires **8027** that are woven with a pair of wires **8027** from a crossing cable. As a result, for example, a semi-flexible and strong crossing point may be achieved.

[0073] FIGS. 9A-9B illustrate yet another exemplary intraluminal device. As shown in FIG. 9A, the cables, for example, may be made from three wires that are unwound and then woven together with the wires from the crossing cable. FIG. 9B also illustrates the cable crossing point **9006** where the cables (which includes wires **9024** and **9025**) are unwound and woven back together. As discussed below in connection with FIGS. 12 and 19, the braiding structure of FIG. 9A may include a 12-wire braiding structure with a twist before and after each junction frame.

[0074] As discussed above in connection with FIG. 1, FIG. 10A illustrates device **10000** with variable-sized openings. Region **10001** includes groups of woven wires **10010** adjacent to intermediate location **10002**, and may provide structural support for intermediate location **10002**. Specifically, the groupings of woven wires **10010** in region **10001** can provide the support to hold open the first interstices **10028**. The first interstices **10028** are larger than the second interstices **10018**, where the second interstices are present in region **10001**. The cross section illustrated in FIG. 10B depicts how the cables **10025** are circumferentially displaced in the intermediate location **10002**. Cables **10025** are generally circumferentially displaced about a central region. Moreover, first interstices **10028** may provide relatively large openings for clot entry in the intermediate location **10002**.

[0075] In accordance with embodiments consistent with the present disclosure, the exemplary intraluminal device may include, for example, two braiding mechanisms, configurations, or structures which may help increase the performance of the device relative to a device incorporating standard braiding structures.

[0076] For example, as shown in FIG. 12, in accordance with at least some embodiments of an intraluminal device consistent with the present disclosure, the braiding structure

**12000** may include a twist of wires before and after each junction frame **12050**. Braiding structure **12000** includes three strands of two-wire pairs (two wires **12015** and **12025**) braided with three strands of two-wire pairs (two wires **12030** and **12040**). FIG. 12 depicts a total of nine (9) junction frames. The junction position within the mesh structure may help prevent slipping of wires across the twist which may otherwise work to become homogeneously separated on a circumference of a mesh structure of an intraluminal device. While a braid structure **11000**, as shown in FIG. 11, may enable slippage (illustrated by arrows **11005**) until the wire **11040** (for example) reaches a parallel wire **11030**, the twists as shown in braiding structure **12000** shown in FIG. 12, may operate to help prohibit substantial slippage across the twist and enable a solid structure when the intraluminal device is expanded.

[0077] In accordance with at least some embodiments of an intraluminal device consistent with the present disclosure, and as illustrated in FIGS. 13 and 14, a braiding structure which includes a twist structure may add strength to a mesh structure by operating as a restraint system grasping the wire and dividing an external force applied on the mesh onto additional elements. FIG. 13 depicts cross section **11010** of braiding structure **11000** of FIG. 11 and FIG. 14 depicts cross section **12010** of braiding structure **12000** of FIG. 12. The dotted lines in cross section **12010** of FIG. 14 illustrate a twist in wires **12015** and **12025**, and also illustrate a twist in wires **12030** and **12040**. The force distribution mechanism in the braiding structures is similar, for example, to force distribution of a loaded beam with varying numbers of supports. This is also illustrated in FIGS. 13 and 14 with the loaded beam diagram **13000** (associated with braided structure **11000**) and loaded beam diagram **14000** (associated with braided structure **12000**). As illustrated in FIGS. 13 and 14, a loaded beam **13020** with three supports **14010**, for example, will react to and distribute the force more effectively than a loaded beam **13020** with two supports **13010**, as there is a smaller distance between three supports **14010**.

[0078] In accordance with at least some embodiments consistent with the present disclosure, the exemplary intraluminal device may be delivered through a microcatheter with an internal diameter of between 0.013 inches and 0.027 inches. In some embodiments, the microcatheter may have an internal diameter of 0.017 inches. As a result, the exemplary intraluminal device may have a low profile (in a retracted or compressed state) that is less than that of the internal diameter of a microcatheter. In accordance with at least some embodiments of an intraluminal device consistent with the present disclosure, the device may have the five following parts, for example:

- [0079] a) a control handle;
- [0080] b) a stiff proximal shaft (for example, a stainless steel hypotube);
- [0081] c) a flexible shaft (made from a cable of wires, for example);
- [0082] d) an expandable mesh which is made from the same wires of the cable; and
- [0083] e) a corewire/control wire which may be connected to the distal tip of the mesh and runs through the shafts to the handle.

[0084] For example, as illustrated in the 8-wire row in FIG. 19A, an intraluminal device may include a flexible shaft with eight (8) wires (each wire having a diameter of 70



μm) and a mesh including eight (8) wires (each wire having a diameter of 70 μm). The eight wires, for example, may be formed, for example, by creating four strands of wires braided together, with each strand including two (2) wires each. As shown in FIG. 19A, and discussed above, the braiding structure of the intraluminal device may include a twist of wires before and after each junction frame to help prevent slippage. A detailed view of cable interweaving **8000** (discussed in connection with FIG. 8) is also shown in FIG. 19A. Cable interweaving **8000** illustrates a junction in the braiding structure of the intraluminal device in detail. The wires may, for example, be made from Nitinol. FIG. 19A also depicts a braiding structure of the intraluminal device without a twist before and after a junction frame.

[0085] In another exemplary embodiment, as illustrated in the 12-wire row in FIG. 19A, the intraluminal device may include a flexible shaft with twelve (12) wires and a mesh including twelve (12) wires. FIG. 19C depicts a detailed view of the 12-wire row in FIG. 19A. The twelve (12) wires may be formed, for example, by creating six strands of wires braided together: with three strands including two (2) wires each; while the other three strands may include two (2) wires each. As shown in FIG. 19C, and as discussed above (such as in connection with FIG. 8, which shows cable interweaving **8000**, and FIG. 12, which shows braiding structure **12000**), the braiding structure **12000** for this embodiment may include a twist of wires before and after each junction frame to help prevent slippage. FIG. 19C also depicts braiding structure **11000** without a twist before and after a junction frame. An exemplary intraluminal device with twelve (12) wires includes device **9000** of FIG. 9A.

[0086] In accordance with another embodiment consistent with the present disclosure, as illustrated in the 10-wire row in FIG. 19, the flexible shaft of the exemplary intraluminal device may include a flexible shaft with ten (10) wires and a mesh including ten (10) wires. FIG. 19B depicts a detailed view of the 10-wire row in FIG. 19A. The ten (10) wires may be formed, for example, by creating four strands of wires braided together: with two strands including three (3) wires each; while the other two strands may include two (2) wires each. Exemplary braiding structures with ten (10) wires are illustrated in FIG. 19B. The braiding structure **19500** may include a twist of wires before and after each junction frame. Braiding structure **19500** includes two-wire strand (wires **12015** and **12025**) and three-wire strand (wires **12015**, **12025**, and **19025**) braided with two-wire strand (wires **12030** and **12040**) and three-wire strand (**12030**, **12040**, and **19040**). Slippage arrows **19505** are also shown. A braiding structure **19400** without a twist is also illustrated. Braiding structure **19400** includes two-wire strand (wires **11015** and **11025**) and three-wire strand (wires **11015**, **11025**, and **19015**) braided with two-wire strand (wires **11030** and **11040**) and three-wire strand (**11030**, **11040**, and **19030**). Slippage arrows **19005** are also shown. In each strand of wires, the wires may, for example, be intertwined to create a stable strand. The wires may, for example, be made from Nitinol, and this configuration may be achieved, for example, by cutting two wires at a transition between a cable and mesh (although this may involve another manufacturing step). As shown in FIG. 15, which represents a general view of an exemplary intraluminal device **15000** in accordance with the present disclosure, the strands may cross each other to create large openings (cells). In the intersections, for example, the strands may be intertwined with one another to

create a loosely coupled junction. Before and after the junction, for example, the wires of the strands may be intertwined.

[0087] As shown in FIG. 16, a strand of two wires (i.e., wires **16020**) may cross a strand of three wires (i.e., wires **16010**). The intertwined wires before and after the junction and the intertwining of the wires inside the junction may create a loosely coupled but stable junction and cross-section, which helps prevent slippage and create large cells, ultimately helping to resist collapse of the device when expanded with high radial force within a tube. And, as shown in FIGS. 17-18 (where FIG. 17 is a detail of region **16015** of FIG. 16 in an expanded configuration, and FIG. 18 is a detail of FIG. 15 in an expanded configuration), when the mesh is expanded, the junction structure keeps the wires together even when the mesh is expanded. As a result, the mesh size remains the same.

[0088] FIGS. 19A-C illustrate 8-, 10-, and 12-wire junctions and configurations. In addition, as discussed above, devices **15000** and **18000**, and the detailed views of FIGS. 16 and 17 may use the 12-wire junctions of FIGS. 19A and 19C. Of course, these are only examples, and the wire junctions and configurations with more or less wires may be used, and that regardless of the number of wires, differing braiding arrangements may be employed.

[0089] As shown in FIG. 20, in accordance with at least some alternative embodiments of an intraluminal device **20000** in accordance with the present disclosure, the device **20000** may have the five following parts, for example:

- [0090] a) a control handle **20100**;
- [0091] b) a stiff proximal shaft **20200**, such as a stainless steel hypotube;
- [0092] c) a flexible shaft **20300** (made from a cable of wires, for example);
- [0093] d) clot engaging component **20400**, such as an clot engaging expandable mesh and/or an clot anchor platform which is made from the same wires of the cable of flexible shaft **20300**; and
- [0094] e) a corewire or control wire (not shown in FIG. 20) which may be connected to the distal tip of the mesh of clot engaging component **20400** and which runs through the shafts **20200**, **20300** to the handle **20100**.

[0095] As shown in FIGS. 21A-B and 22A-C, in accordance with at least some embodiments of an intraluminal device **20000** in accordance with the present disclosure, the clot engaging component **20400** of intraluminal device **20000** may include a clot anchoring segment **21600** distal to a clot engaging mesh **21400**, configured to engage hard clots **21800**. The clot anchoring segment **21600** may be manually adjustable and/or self-expandable. In some embodiments, clot anchoring segment **21600** may be heat-treated such that it is configured to expand radially outward when released from catheter **21700**. According to various embodiments in which clot anchoring segment **21600** is manually adjustable, its expansion may be controlled, at least in part, by a control wire. In some embodiments, the distal end of a control wire **21550** may be connected to a portion of clot anchoring segment **21600**, such as the distal portion thereof. In some embodiments, proximal clot engaging mesh **21400** and clot anchoring segment **21600** may be a unitary structure or may be connected together, such that a force (e.g., a pulling force) exerted upon clot anchoring segment **21600** by the control wire **21550** may transfer to clot engaging mesh **21400**,



causing simultaneous adjustment of clot anchoring segment **21600** and proximal clot engaging mesh **21400**. According to various embodiments in which clot anchoring segment **21600** is self-expanding, a control wire **21500** may be connected to a portion of proximal clot engaging mesh **21400**, such as the distal end thereof.

[0096] In accordance with alternative embodiments, the intraluminal device may have two or more control wires which run through the shafts **20200**, **20300** and which may be connected to a handle **20100**. A first control wire **21500** may be connected to proximal clot engaging mesh **21400**, such as the distal end thereof, and may be actuated to control expansion of proximal clot engaging mesh **21400**. A second control wire **21550** may be connected to a portion of clot anchoring segment **21600**, such as a distal end thereof, and may be actuated to control expansion of clot anchoring segment **21600**.

[0097] In accordance with at least some embodiments of the present disclosure, the outer diameter of proximal clot engaging mesh **21400** may be equal to or larger than the outer diameter of clot anchoring segment **21600** when they are in their respective retracted states. For example, FIG. **22A** illustrates an embodiment in which proximal clot engaging mesh **21400** and clot anchoring segment **21600** are both retracted. Additionally or alternatively, the outer diameter of proximal clot engaging mesh **21400** may be equal to or larger than the outer diameter of clot anchoring segment **21600** when they are in their respective fully-expanded states. For example, FIG. **22C** illustrates an embodiment in which proximal clot engaging mesh **21400** and clot anchoring segment **21600** are both fully expanded. As explained above, proximal clot engaging mesh **21400** may be configured for expansion independent of clot anchoring segment **21600**, and vice versa. For example, FIG. **22B** illustrates an embodiment in which proximal clot engaging mesh **21400** is expanded while clot anchoring segment **21600** remains retracted. Proximal clot engaging mesh **21400** may include at least one pore **21405** which is larger than other openings in the intraluminal device, including pores of clot anchoring segment **21600**. The at least one pore **21405** may form a clot capturing area, allowing capture of clots within proximal clot engaging mesh **21400**. In various embodiments, proximal clot engaging mesh **21400** may be configured for at least partial penetration of a clot and for expansion within the clot, either via a self-expansion mechanism or by actuation of at least one control cable. Proximal clot engaging mesh **21400** may exert an outward radial force upon the clot, achieving fracture and/or capture of the clot.

[0098] According to various embodiments, the distal end of intraluminal device **20000** may be configured to penetrate a clot. As illustrated in FIGS. **21A-B**, proximal clot engaging mesh **21400** and clot anchoring segment **21600** may be pushed through clot **21800** until clot anchoring segment **21600** passes through the distal end of clot **21800** and is positioned within the portion of the vessel distal to the clot **21800**. Proximal clot engaging mesh **21400** and clot anchoring segment **21600** may be configured to achieve small respective outer diameters when in their retracted states, such that they may penetrate and pass through clot **21800**, such as by manipulation of handle **20100**. Proximal clot engaging mesh **21400** may be expanded to capture the clot **21800**. However, according to embodiments in which clot **21800** is too rigid for expansion of proximal clot engaging mesh **21400**, clot anchoring segment **21600** may be

expanded since it is positioned distal to the clot. According to some embodiments, the outer diameter of expanded clot anchoring segment **21600** may be smaller than the inner diameter of the blood vessel, such that clot anchoring segment **21600** does not contact the vessel wall. Alternatively, clot anchoring segment **21600** may be configured to expand until it contacts and conforms to the shape of the vessel wall. Expansion of clot anchoring segment **21600** may form a platform which may trap clot **21800** and prevent it from traveling distal to clot anchoring segment **21600**. Once the intraluminal device **20000** is pulled proximally, clot anchoring segment **21600** may engage the clot **21800** and push it upstream. Any adhesion between the clot **21800** and the vessel may be overcome by the resultant shear forces. In some embodiments, partial expansion of proximal clot engaging mesh **21400** within clot **21800** may at least partially secure clot **21800** to proximal clot engaging mesh **21400**. Once the clot is pushed proximally by clot anchoring segment **21600** and disengages from the vessel wall, the clot **21800** may be retrieved into the guiding catheter **21700**. In some embodiments, at least one of proximal clot engaging mesh **21400** and clot anchoring segment **21600** may remain expanded until the clot **21800** is captured within catheter **21700**.

[0099] As depicted in FIGS. **23A-B**, **24**, and **25**, in accordance with at least some alternative embodiments of an intraluminal device **20000** in accordance with the present disclosure, the intraluminal device **20000** may include at least one clot anchoring segment and an expandable clot engaging mesh segment **23400** at the distal end thereof. The embodiment depicted in FIGS. **23A-B**, **24**, and **25** include three clot anchoring segments **23600**, **23602**, **23604**. However, intraluminal device **20000** may include one, two, three, four, five, or more anchoring segments according to various embodiments. Clot engaging mesh segment **23400** may be manually expandable, such as by actuation of control wire **23550**, and/or self-expanding, according to mechanisms discussed above, and may be configured to engage hard clots. According to some embodiments, clot anchoring segments **23600-23604** may be expanded by a single control wire **23500** that is connected to the most distal end of these segments, such as the distal-most segment **23604**. Alternatively, each clot anchoring segment **23600**, **23602**, **23604** may be controlled by a respective control wire, which may be connected to the distal end of its respective clot anchoring segment. The respective outer diameters of clot anchoring segments **23600-23604** may be substantially equal in when the retracted state. When in the retracted state, the outer diameter of clot engaging mesh segment **23400** may be equal to or larger than the outer diameter of at least one of clot anchoring segments **23600-23604** when in the retracted state.

[0100] As illustrated in FIG. **23B**, the clot anchoring segments **23600-23604** may be expanded with high radial forces, each forming a platform configured to substantially prevent passage of clots thereby. According to some embodiments, the outer diameters of expanded clot anchoring segments **23600-23604** may be substantially equal and smaller than the inner diameter of the blood vessel, such that the clot anchoring segments **23600-23604** do not contact the vessel wall. According to alternative embodiments, clot anchoring segments **23600-23604** may be configured to expand until each contacts and conforms to the shape of the vessel wall. In still further embodiments, clot anchoring



segments **23600-23604** may be configured for varying outer diameters when fully expanded. In some embodiments, proximal-most segment **23600** may have the largest expanded outer diameter and distal-most segment **23604** may have the smallest expanded outer diameter. In other embodiments, proximal-most segment **23600** may have the smallest expanded outer diameter and distal-most segment **23604** may have the largest expanded outer diameter. In still further embodiments, one or two of segments **23600-23604** may have expanded outer diameters which do not contact the vessel wall, while the remaining segments are configured to expand until they contact and conform with the vessel wall. Clot engaging mesh segment **23400** may be configured to have an outer expanded diameter which is equal to or larger than the expanded outer diameters of clot anchoring segments **23600-23604**. Clot engaging mesh segment **23400** may be configured to self-expand independently of clot anchoring segments **23600-23604**. For example, FIG. **24** illustrates an embodiment in which clot anchoring segments **23600-23604** are retracted and clot engaging mesh segment **23400** is expanded. While FIG. **25** illustrates an embodiment in which clot anchoring segments **23600-23604** and clot engaging mesh segment **23400** are all expanded.

[0101] When expanded, clot anchoring segments **23600-23604** may each form a platform with a larger outer diameter than that of any adjoining section between clot anchoring segments. For example, the transition between clot anchoring segment and adjoining section may be steep so as to form a shelf or seat capable of seating against a portion of a clot. The clot may be trapped between adjacent platforms, and then pushed (or pulled) as the device is retrieved proximally. As shown in FIGS. **23A-B**, the clot engaging mesh segment **23400** (which can function as a distal self-expanding filter) may be configured to catch any detached clot fragments to secure a clean pass.

[0102] According to some embodiments, the intraluminal device may be delivered into a blood vessel, in proximity to a blood clot. Clot anchoring segments **23600-23604** and clot engaging mesh segment **23400** may be in their retracted states during delivery. The intraluminal device may be positioned such that clot engaging mesh segment **23400** is positioned distal to the clot location, with the clot positioned distal to at least one of clot anchoring segments **23600-23604**. In some embodiments, the clot may be positioned proximal to proximal-most clot anchoring segment **23600**. Additionally or alternatively, the clot may be positioned between two consecutive clot anchoring segments. Clot engaging mesh segment **23400** may self-expand or be expanded manually to catch any clot fragments distal to the clot anchoring segments. Before, during, or after expansion of clot engaging mesh segment **23400**, the clot anchoring segments **23600-23604** may be expanded, either simultaneously or individually. In some embodiments, distal clot anchoring segment **23604** may be expanded first and proximal clot anchoring segment **23600** may be expanded last. Alternatively, in some embodiments, proximal clot anchoring segment **23600** may be expanded first and distal clot anchoring segment **23604** may be expanded last. Expansion of the clot anchoring segments **23600-23604** may form platforms which may trap the clot. The intraluminal device may be pulled proximally, causing the clot anchoring segments to push the clot proximally and into guiding catheter **21700**. In some embodiments, at least one of clot anchoring

segments **23600-23604** and clot engaging mesh segment **23400** may remain expanded until the clot is captured and removed from the vessel.

[0103] As depicted in FIGS. **26A-B**, in accordance with another embodiment, the intraluminal device **20000** may include a long clot engaging segment **26400**. The long clot engaging segment **26400** may include several sequential adjustable clot engaging mesh segments **26402** and **26404** to allow improved clot engagement where the clot has mixed hard and soft areas. In some embodiments, long clot engaging segment **26400** may include two, three, four five, or more adjustable clot engaging mesh segments. The clot engaging mesh segments **26402**, **26404** can vary in radial force, wire arrangement, diameter, pore size, sparse and design. As a result, the clot engaging mesh segments **26402**, **26404** may assume different sizes and/or shapes when expanded and may be configured to exert varying radial outward forces when expanded. The variation in force may be due, at least in part, to the wire arrangement (such as the braiding pattern), the pore size, and the segment length. In one embodiment, a first one of the clot engaging mesh segments **26402**, **26404** may be expanded within a clot location. In the event that the segment exerts insufficient force to engage the clot, the first segment may be retracted, the device repositioned, and a second, more rigid clot engaging mesh segment may be expanded to penetrate and capture the clot. In another embodiment, when a first clot engaging mesh segment exerts insufficient outward force to expand and engage a clot, at least one other clot engaging mesh segment may be expanded to engage the clot in a softer area.

[0104] As also illustrated in FIGS. **26A-B**, in accordance with at least some embodiments of an intraluminal device **20000** in accordance with the present disclosure, at least one distal adjustable clot anchor **26600** may be arranged at the distal end of the intraluminal device. Clot anchor **26600** may be configured to expand with high radial force, forming a platform at the distal end of the device. For example, clot anchor **26600** may be configured to expand until it contacts and conforms with the vessel wall. Once the intraluminal device is pulled proximally, the expanded clot anchor **26600** may engage the clot and push it proximally, in case that the clot engaging mesh segments **26402**, **26404** did not capture the clot or a portion thereof. In some embodiments, at least one of clot engaging mesh segments **26402**, **26404** and adjustable clot anchor **26600** may remain expanded until the clot is captured and removed from the vessel. Furthermore, a control wire **26550** may be attached to the distal-most anchoring segment **26600**, and/or one or more control wires (such as control wire **26500**) may be attached to the distal portion of one or more clot engaging mesh segments **26402** and **26404**. Such control wires may be actuated to expand and retract their respective segment(s) as discussed throughout.

[0105] As depicted in FIGS. **27-28**, in accordance with another embodiment, the intraluminal device **20000** may include several adjustable clot anchoring segments **27600-27608**, each of which may be configured to change its respective configuration to consequent platforms when expanded, to allow clot entrapment between the platforms. The intraluminal device may include two, three, four, five, six, seven, eight, nine, ten, or more clot anchoring segments. The clot anchoring segments **27600-27608** may vary in radial force, wire arrangement, diameter, pore size, sparse



and design, for example. In some embodiments, each clot anchoring segment **27600-27608** may include a respective control wire, such that the segments may be individually expanded. In other embodiments, a single or multiple control wires may be attached to the distal-most clot anchoring segment and may be actuated to simultaneously expand all clot anchoring segments **27600-27608**. In one embodiment, a first one of the clot anchoring segments **27600-27608** may be expanded distal to a clot location, so as to capture the clot. In the event that the clot anchoring segment does not capture the clot or at least a fragment thereof, a second clot anchoring segment may be expanded, for example distal to the first clot anchoring segment, to capture the remaining fragments of the clot. In some embodiments, the second clot anchoring segment may have a larger expanded outer diameter than the first clot anchoring segment and/or exert greater outward force than the first clot anchoring segment when expanded. For example, the second clot anchoring segment may be configured to expand until it contacts and conforms to the shape of the vessel wall. Advantageously, this may permit any clot fragments not captured by the first clot anchoring segment to be captured by the second clot anchoring segment. According to other embodiments, two or more of clot anchoring segments **27600-27608** may be expanded simultaneously, thus capturing the clot and any fragments thereof. Once the device is pulled proximally, the platforms formed by clot anchoring segments **27600-27608** may engage the clot and any fragments thereof and push it proximally. The platforms may also act as a filter, catching detached clot fragments. In some embodiments, at least one of clot anchoring segments **27600-27608** may remain expanded until the clot is captured and removed from the vessel.

[0106] FIGS. 29A and 29B illustrate an exemplary intraluminal device **29000**. Intraluminal device **29000** may include a control handle **29100**, a proximal shaft portion **29200** extending from the distal end of the control handle **29100**, and a distal shaft portion **29300** extending from, or otherwise connected to, the distal end of proximal shaft portion **29200**. Proximal shaft portion **29200** and distal shaft portion **29300** may form a hollow, elongated shaft of intraluminal device **29000** extending along a longitudinal axis A of the intraluminal device. In some embodiments, proximal shaft portion **29200** may include a rigid hypotube (e.g., a stainless steel hypotube). Additionally, or alternatively, distal shaft portion **29300** may be configured to be more flexible than proximal shaft portion **29200**. For example, in some embodiments, distal shaft portion **29300** may include a cable constructed of a plurality of flexible wires, which may extend into expandable mesh segment **29400** (which is described below). Optionally, a flexible atraumatic tip **29005** may be secured to the distal end of the intraluminal device **29000**.

[0107] Intraluminal device **29200** may include an expandable mesh segment **29400** connected to, or otherwise situated distal to, the distal end of distal shaft portion **29300**. Mesh segment **29400** may be formed by a plurality of wires that are woven or coiled to form the first mesh segment. In some embodiments, expandable mesh segment **29400** may include one or more of the exemplary wire arrangements (i.e., wire braiding patterns) discussed above. For example, at least a portion of mesh segment **29400** may be woven to form an exemplary clot capture section that is configured to capture and remove occlusive material (e.g., blood clots) from body lumens. Additionally, or alternatively, at least a

portion of mesh segment **29400** may be woven to form an exemplary clot anchoring segment configured to form a platform that may trap an occlusion and, when pulled proximally, may engage the occlusion and push it upstream. Additionally, or alternatively, at least a portion of mesh segment **29400** may be woven to form a structure configured to assist in an aneurism coiling procedure and/or for treating vasospasm.

[0108] Mesh segment **29400** may be configured for radial expansion and contraction between a radially-contracted state (e.g., the state illustrated in FIG. 29A) and a radially-expanded state (e.g., the state illustrated in FIG. 29B). When the mesh segment **29400** is in the radially-contracted state, the distal end **29420** of the mesh segment may be spaced a first distance **29401a** from the proximal end **29410** of the mesh segment. In some embodiments, mesh segment **29400** may have a first distance **29401a** of between approximately 20.0 mm and approximately 100.0 mm. In some embodiments, the outer diameter of the mesh segment **29400** may be small when the mesh segment **29400** is in the radially-contracted state so that the mesh segment **29400** may be retained within a delivery device (e.g., delivery catheter **21700**). For example, mesh segment **29400** may have an outer diameter of between approximately 0.5 mm and approximately 2.0 mm when the mesh segment **29400** is in the radially-contracted state. When the mesh segment **29400** is in the radially-expanded state, the outer diameter of the mesh segment **29400** may be larger than when the mesh segment **29400** is in the radially-contracted state. For example, mesh segment **29400** may be configured to radially expand until the mesh contacts the inner surface of a body lumen **29820** (e.g., a blood vessel). When the mesh segment **29400** is in the radially-expanded state, the distal end **29420** of the mesh segment may be spaced a second distance **29401b** from the proximal end **29410** of the mesh segment; the second distance **29401b** may be smaller than the first distance **29401a**.

[0109] Exemplary intraluminal device **29000** may also include a core wire **29500**, which may be connected to a portion of the expandable mesh segment **29400** and may extend through the distal shaft portion **29300** and proximal shaft portion **29200** to the control handle **29100**. In some embodiments, core wire **29500** may be secured to the distal end **29420** of the expandable mesh segment **29400**; additionally, or alternatively, core wire **29500** may be secured to a different portion of the expandable mesh segment **29400**. Core wire **29500** may be secured to a wire actuator **29112** in the control handle **29100**, which may be configured to effect axial movement of the core wire **29500** relative to the distal shaft portion **29300** and proximal shaft portion **29200**. Wire actuator **29112** may include any appropriate mechanism for actuating axial movement of core wire **29500**, examples of which include, but are not limited to, a rotatable knob, a wheel, a button, a slider, a lever, a joystick, a touchpad, and combinations thereof. Due to the connection between the core wire **29500** and mesh segment **29400**, axial movement of the core wire **29500** (e.g., due to actuation of wire actuator **29112**) may control movement of the mesh segment **29400** between the radially-contracted state and the radially-expanded state of the mesh segment by adjusting the distance between the proximal end **29410** and distal end **29420** of the mesh segment **29400**. For example, in embodiments in which core wire **29500** is connected to the distal end **29420** of the mesh segment, proximal movement of core wire



**29500** (represented by arrow **29500a**) may pull the distal end **29420** of the mesh segment towards the proximal end **29410** of the mesh segment, causing the mesh segment **29400** to radially expand.

[0110] FIG. 29C illustrates a problem experienced by prior art mesh segments (represented as mesh segment **29400p**) when the mesh segments are expanded within a hollow body lumen **29820** or within a hollow device (e.g., catheter **21700**) due to actuation of a core wire **29500p**. As illustrated in FIG. 29C, when the outer diameter of the mesh segment **29400p** contacts the body lumen **29820**, further actuation of the core wire **29500** causes a fold-back of the distal end of the mesh segment **29400p** in which the distal end **29420p** of the mesh segment is pulled proximally while the mesh outer edges **29440p** are held in place due to their contact with body lumen **29820**. Existing intraluminal meshes do not include any mechanism to prevent this folding-back effect. As a result, the fold-back can cause irreversible damage to the mesh segment **29400p**, to the point that the intraluminal device **29000p** may no longer be functional. In addition, fold-back of the mesh segment reduces the magnitude of the radial force exerted by the mesh segment on the body lumen and often limits, or even completely eliminates, the user's ability to control expansion and contraction of the mesh segment.

[0111] To prevent fold-back of the mesh segment **29400**, exemplary intraluminal device **29000** may include at least one expansion limiter **29900** situated partially or entirely within the mesh segment **29400**. The expansion limiter **29900** may include at least one lumen therethrough and may be contained within the mesh segment **29400**, with the core wire **29500** passing through the expansion limiter **29900**. The expansion limiter **29900** may be configured to hold the proximal end **29410** and distal end **29420** of the mesh segment apart by a minimum predetermined distance, such that radial expansion of the mesh segment **29400** beyond a predetermined diameter may be prevented. In some embodiments, the expansion limiter **29900** may be configured to hold the proximal end **29410** and distal end **29420** of the mesh segment apart by at least the second distance **29401b**, such that the expansion limiter **29900** may, at least in part, limit the maximum outer diameter of the mesh segment **29400** in the radially-expanded state. As illustrated in FIG. 29D, the expansion limiter **29900** may prevent fold-back of the mesh segment **29400** because once the proximal end **29410** and distal end **29420** of the mesh segment reach the minimum predetermined distance (e.g., second distance **29401b**), further proximal advancement of the distal end **29420** due to actuation of the core wire **29500** is prevented by the expansion limiter **29900**.

[0112] In some embodiments, the expansion limiter **29900** may be devoid of permanent connection to other elements of the intraluminal device **29000**; instead, it may be held in place due to its placement within the expandable mesh segment **29400**. In alternative embodiments, expansion limiter **29900** may be connected to one or more portions of the mesh segment **29400**, such as the proximal end **29410** and/or the distal end **29420**. Additionally, or alternatively, expansion limiter **29900** may be secured to the distal end of distal shaft portion **29300**. The expansion limiter **29900** may be constructed of an alloy or metal (e.g., nickel-titanium alloy), stainless steel, a polymer, and/or another suitable material.

In some embodiments, the expansion limiter **29900** may have an outer diameter of between approximately 0.12 mm and approximately 0.25 mm.

[0113] In some embodiments, the expansion limiter **29900** may include a hollow, cylindrical tube constructed of a material such as stainless steel or nickel-titanium alloy. The hollow tube may be laser-cut, so as to allow the expansion limiter **29900** to be sufficiently pliable to bend through tortuous anatomy during delivery of the intraluminal device **29000** to a treatment site within the body. In some embodiments, the hollow tube of the expansion limiter **29900** may have an axial length of between approximately 5.0 mm and 20.0 mm. Accordingly, mesh segment **29400** may have a second distance **29401b** of between approximately 5.0 mm and 20.0 mm, in some embodiments. In some embodiments, the hollow tube of the expansion limiter **29900** may contact both the proximal end **29410** and distal end **29420** of the mesh segment when the mesh segment is expanded (e.g., as depicted in FIGS. 29B and 29C), thus preventing further expansion of the mesh segment **29400**. However, the hollow tube of the expansion limiter **29900** may not be in contact with one or both of the proximal end **29410** and distal end **29420** of the mesh segment when the mesh segment is radially-contracted (e.g., as depicted in FIG. 29A) due to the increased axial distance between the proximal end **29410** and distal end **29420** of the mesh segment.

[0114] FIGS. 30A and 30B illustrate an exemplary intraluminal device **30000** that may be similarly configured as intraluminal device **29000**, apart from including an alternative expansion limiter **30900** situated partially or entirely within the expandable mesh segment **30400**. Expansion limiter **30900** may include an elastic, helical coil configured to axially stretch and contract between a free length (i.e., the axial length of the coil when no axial forces are exerted upon the coil) and a solid length of the coil i.e., the minimum axial length of the coil, beyond which the coil cannot be shortened). In some embodiments, the solid length of the helical coil of expansion limiter **30900** may be substantially equal to the second distance **30401b**, such that the helical coil of expansion limiter **30900** may hold the proximal end **30410** and distal end **30420** of the mesh segment apart by at least the second distance **30401b**. For example, the helical coil of expansion limiter **30900** may have a solid length of between approximately 5.0 mm and 20.0 mm. As illustrated in FIG. 30C, this configuration of the helical coil of expansion limiter **30900** may prevent fold-back during expansion of the mesh segment **30400** within a body lumen **29820** by holding the proximal and distal ends of the mesh segment **30400** apart by at least the second distance **30401b**. In some embodiments, the expansion limiter **30900**, including the helical coil, may have an outer diameter of between approximately 0.12 mm and approximately 0.25 mm.

[0115] In some embodiments, the helical coil of expansion limiter **30900** may have a free length that is longer than the second distance **30401b** and shorter than the first distance **30401a**. In such embodiments, the helical coil may not contact the proximal end **30410** and distal end **30420** of the mesh segment when the mesh segment **30900** is in the radially-contracted state. In some alternative embodiments, the helical coil of expansion limiter **30900** may have a free length that is longer than both the second distance **30401b** and the first distance **30401a**. In such embodiments, the helical coil may be in contact with the proximal end **30410** and distal end **30420** of the mesh segment, and may be at



least partially compressed, at all degrees of expansion of the mesh segment **30900**. Accordingly, the helical coil may be biased to hold the proximal end **30410** and distal end **30420** of the mesh segment apart by at least the first distance **30401a**. In further alternative embodiments, the helical coil of expansion limiter **30900** may have a free length that is equal to the first distance **30401a**. In such embodiments, the helical coil may be in a non-compressed state when the mesh segment **30900** is in the radially-contracted state and may also contact the proximal end **30410** and distal end **30420** of the mesh segment when the mesh segment **30900** is in the radially-contracted state.

[0116] FIGS. 31A-C illustrate another exemplary intraluminal device **31000** having multiple radially-expandable mesh segments, each of which may be configured to expand from a radially-contracted state thereof to a radially-expanded state thereof. Although the example illustrated in FIGS. 31A-C includes two mesh segments **31400** and **31402**, those of ordinary skill will understand that intraluminal device **31000** may include one mesh segment, two mesh segments, three mesh segments, four mesh segments, five mesh segments, or any other suitable number of mesh segments. The mesh segments **31400** and **31402** may extend between a mesh segment proximal end **31410** and a mesh segment distal end **31420** and may be separated by a transition zone **31430**, which may be configured for minimal or no radial expansion. Core wire **29500** may extend through both mesh segments **31400** and **31402** and may be secured to a portion of the distal mesh segment **31400** (e.g., to mesh segment distal end **31420**). Axial movement of core wire **29500** (e.g., under control of wire actuator **29112**) may control expansion and contraction of both mesh segments **31400** and **31402** between their respective radially-contracted and radially-expanded states.

[0117] Mesh segments **31400** and **31402** may be configured for radial expansion and contraction between a radially-contracted state (FIG. 31A illustrates an example in which both meshes **31400** and **31402** are in a radially-contracted state) and a radially-expanded state (FIG. 31C illustrates an example in which both meshes **31400** and **31402** are in a radially-expanded state). When the distal mesh segment **31400** is in the radially-contracted state, the mesh segment distal end **31420** may be spaced a first distance **31401a** from the transition zone **31430**. Similarly, when the proximal mesh segment **31402** is in the radially-contracted state, the transition zone **31430** may be spaced a third distance **31401c** from the mesh segment proximal end **31410**. When the distal mesh segment **31400** transitions from the radially-contracted state to the radially-expanded state (e.g., due to axial movement of core wire **29500**), the mesh segment distal end **31420** may be drawn proximally until it is spaced a second distance **31401b** from the transition zone **31430**, causing expansion of the distal mesh segment **31400**. A distal expansion limiter **31900a** may prevent further expansion of the distal mesh segment beyond the diameter corresponding to second distance **31401b**. Similarly, when the proximal mesh segment **31402** transitions from the radially-contracted state to the radially-expanded state (e.g., due to axial movement of core wire **29500**), the transition zone **31430** may be drawn proximally until it is spaced a fourth distance **31401d** from the mesh segment proximal end **31410**, causing expansion of the proximal mesh segment **31402**. A proximal expansion limiter **31900b** may prevent further expansion of the proximal mesh segment beyond the diam-

eter corresponding to fourth distance **31401d**. The first distance **31401a** may be larger than the second distance **31401b**, and the third distance **31401c** may be larger than the fourth distance **31401d**.

[0118] In some embodiments, mesh segments **31400** and **31402** may each include an expansion limiter **31900a** and **31900b**, respectively. Expansion limiters **31900a** and **31900b** may be configured as a hollow, cylindrical tube, as an elastic, helical coil, or may have any other suitable configuration. In the example depicted in FIGS. 31A-31C, expansion limiters **31900a** and **31900b** are configured as cylindrical tubes through which core wire **29500** may extend.

[0119] As illustrated in FIGS. 31A-C, mesh segments **31400** and **31402** may be expanded sequentially when a proximal force is applied by core wire **29500**, with the distal-most mesh segment **31400** expanding first and the proximal-most mesh segment **31402** expanding last. In some embodiments, core wire **29500** may pull mesh segment distal end **31420** proximally towards transition zone **31430**. As illustrated in FIG. 31B, this may cause radial expansion of distal mesh segment **31400**, while proximal mesh segment **31402** may remain radially-contracted. This may occur because the proximal force exerted by the core wire **29500** is applied to the distal end of the distal mesh segment **31400**, and minimal or no force is transmitted to proximal mesh segment **31402**. Once the distal mesh segment **31400** is fully radially-expanded (i.e., once distal mesh segment **31400** has an axial length equal to second length **31410b** and expansion limiter **31900a** prevents further expansion of the distal mesh segment), the proximally-applied force from the core wire **29500** is then transferred to transition zone **31430** via the expansion limiter **31900a**. The applied force then pulls transition zone **31430** proximally towards the mesh segment proximal end **31410**, causing radial expansion of the proximal mesh segment **31402**. This expansion may occur until the proximal mesh segment **31402** is fully radially-expanded (i.e., when proximal mesh segment **31402** has an axial length equal to fourth length **31410d** and expansion limiter **31900b** prevents further expansion of the proximal mesh segment). At this point, exemplary intraluminal device **31000** may be configured in the state illustrated in FIG. 31C; any additional proximally-directed force may be prevented from causing further expansion (and thus fold-back) of the mesh segments **31400** and **31402**, since the expansion limiters **31900a** and **31900b** may hold mesh segments **31400** and **31402** at second distance **31401b** and fourth distance **31401d**, respectively. Advantageously, this sequential expansion mechanism may provide greater control over the expansion of the mesh segments **31400**, **31402** because the specific order of mesh expansion is known. In addition, incorporation of the expansion limiters **31900a** and **31900b** may prevent fold-back of all mesh segments, including the distal-most mesh segment **31400**.

[0120] FIGS. 32A-C illustrate another exemplary intraluminal device **32000** having multiple radially-expandable mesh segments **31400**, **31402** containing expansion limiters **32900a** and **32900b**, respectively. Expansion limiters **32900a** and **32900b** may each include an elastic, helical coil configured to axially stretch and contract between a free length and a solid length, as described above. Expansion limiters **32900a** and **32900b** may be configured to cause sequential expansion of mesh segments **31400** and **31402**. FIG. 32A illustrates a state in which both mesh segments



**31400** and **31402** are in a radially-contracted state. As shown in FIG. 32B, proximal movement of core wire **29500** exerts a radially-expanding force upon distal mesh segment **31400**, while proximal mesh segment **31402** may remain radially-contracted. Upon full expansion of the distal mesh segment **31400**, proximally-applied force may then be applied to transition zone **31430** via expansion limiter **32900a**, causing radial expansion of proximal mesh segment **31402**. Upon full expansion of the proximal mesh segment **31402**, as illustrated in FIG. 32C, expansion limiters **32900a** and **32900b** may be configured to prevent further expansion, and thus fold-back, of mesh segments **31400** and **31402**.

[0121] FIGS. 33A-C illustrate another exemplary intraluminal device **33000** having multiple radially-expandable mesh segments **31400**, **31402** containing expansion limiters **32900a** and **32900b**, respectively. In the example of FIGS. 33A-C, the expansion limiters **32900a** and **32900b** may have different configurations. For example, one or more expansion limiters may be configured as a cylindrical tube, while one or more expansion limiters may be configured as a helical coil. Additionally, or alternatively, one or more expansion limiters may have some other suitable configuration.

[0122] FIGS. 34A-C illustrate another exemplary intraluminal device **34000** having multiple radially-expandable mesh segments **34400**, **34402** and a single expansion limiter **34900** configured to limit expansion of both mesh segments. In some embodiments, expansion limiter **34900** may be secured to the interior surface of transition zone **34430** by solder, welding, adhesive, one or more mechanical fasteners, or other suitable means. Although expansion limiter **34900** is configured as a cylindrical tube in the example of FIGS. 34A-C, expansion limiter **34900** may alternatively be configured as a helical coil or may have any other suitable configuration. Core wire **29500** may extend through both mesh segments **34400** and **34402** and through expansion limiter **34900**, and may be secured to a portion of the distal mesh segment **31400** (e.g., to mesh segment distal end **31420**).

[0123] Axial movement of core wire **29500** (e.g., under control of wire actuator **29112**) may control expansion and contraction of both mesh segments **34400** and **34402** between their respective radially-contracted and radially-expanded states. As illustrated in FIGS. 34A-C, mesh segments **34400** and **34402** may be expanded sequentially in at least some embodiments, with the distal-most mesh segment **34400** expanding first and the proximal-most mesh segment **34402** expanding last. In some embodiments, core wire **29500** may pull mesh segment distal end **34420** proximally towards transition zone **34430**, causing radial expansion of distal mesh segment **31400** while proximal mesh segment **31402** remains radially contracted. Distal mesh segment **31400** may be fully radially-expanded when the distal end of the distal mesh segment contacts the expansion limiter **34430**; this configuration is illustrated in FIG. 34B. At this point, additional proximally-directed force from the core wire **29500** is transmitted to transition zone **34430** via its attachment to expansion limiter **34900**. The applied force may pull transition zone **34430** proximally towards the mesh segment proximal end **34410**, causing radial expansion of the proximal mesh segment **34402** until the expansion limiter **34430** is pulled into contact with the proximal end of the proximal mesh segment **34402**. At this point, exemplary intraluminal device **34000** may be configured in the state

illustrated in FIG. 34C; any additional proximally-directed force may be prevented from causing further expansion (and thus fold-back) of the mesh segments **34400** and **34402** due to the engagement of the expansion limiter **34900** with the proximal end **34420** and distal end **34410** of the mesh segments. Advantageously, utilizing a single expansion limiter **34900** to control multiple mesh segments may reduce the number of components within intraluminal device **34000** and may require fewer assembly steps.

[0124] FIGS. 35A-C illustrate a method of removing occlusive material **35800** from a body lumen **35820** with an exemplary intraluminal device **35000**. In FIG. 35A, the intraluminal device **35000** may be delivered into the lumen **35820** via a delivery catheter **35700**. Intraluminal device **35000** may include at least one expandable mesh segment at the distal end of shaft portion **35300**. Although the example depicted in FIGS. 35A-C depicts an intraluminal device **35000** with two expandable mesh segments **35400** and **35402**, any suitable number of mesh segments may be utilized with intraluminal device **35000**, such as one mesh segment, two mesh segments, three mesh segments, four mesh segments, or some other number of mesh segments. Mesh segments **35400** and **35402** may include expansion limiters **35900a** and **35900b**, respectively. Although the example depicted in FIGS. 35A-C depicts expansion limiters **35900a** and **35900b** configured as helical coils, any suitable configuration of expansion limiters may be utilized with intraluminal device **35000**, such as a cylindrical shaft.

[0125] In FIG. 35A, intraluminal device **35000** may be delivered to an upstream side of occlusive material **35800**, with mesh segments **35400** and **35402** in their respective radially-contracted states. As shown in FIG. 35B, at least one of the mesh segments **35400** and **35402** may be delivered downstream of occlusive material **35800**. In some embodiments, the occlusive material **35800** may be positioned proximal to proximal-most mesh segment (i.e., proximal mesh segment **35402**). Additionally, or alternatively, the occlusive material **35800** may be positioned between two consecutive mesh segments. Core wire **35500** may then be pulled proximally (i.e., to the right in FIG. 35B), causing radial expansion of distal mesh segment **35400**, while proximal mesh segment **35402** may remain radially-contracted. Radial expansion of distal mesh segment **35400** may continue until further expansion is prevented by expansion limiter **35900a**. As illustrated in FIG. 35C, additional actuation of core wire **35500** may cause radial expansion of proximal mesh segment **35402** until further expansion is prevented by expansion limiter **35900b**. After both mesh segments **35400** and **35402** are fully radially-expanded, further radial expansion of the mesh segments may be prevented by expansion limiters **35900a** and **35900b**.

[0126] Once the mesh segments **35400** and **35402** are fully expanded, as depicted in FIG. 35C, the mesh segments may form a filter configured to trap portions of the occlusive material **35800**. The intraluminal device **35000** may be pulled proximally until at least the proximal-most mesh segment (i.e., proximal mesh segment **35402**) comes in contact with the occlusive material **35800**. Continued proximal movement of intraluminal device **35000** causes the mesh segments **35400** and **35402** to push the occlusive material **35800** proximally and into catheter **35700**. In some embodiments, at least one of the mesh segments **35400** and



**35402** may remain radially-expanded until the occlusive material **35800** is captured and removed from the body lumen **35820**.

[0127] FIGS. 36A and 36B illustrate an exemplary intraluminal device **36000**. Intraluminal device **36000** may include a control handle **36100**, a proximal shaft portion **36200** extending from the distal end of the control handle **36100**, and a distal shaft portion **36300** extending from, or otherwise connected to, the distal end of proximal shaft portion **36200**. Proximal shaft portion **36200** and distal shaft portion **36300** may form a hollow, elongated shaft **36350** of intraluminal device **36000** extending along a longitudinal axis A of the intraluminal device. A flexible, atraumatic tip **36005** may optionally be secured to the distal end of the intraluminal device **36000**. Intraluminal device **36200** may include an expandable mesh segment **36400** connected to, or otherwise secured relative to, the distal end of the elongated shaft **36350**. Mesh segment **36400** may be configured for radial expansion and contraction between a radially-contracted state (e.g., the state illustrated in FIGS. 36A and 36C) and a radially-expanded state (e.g., the state illustrated in FIGS. 36B and 36D). Intraluminal device **36000** may also include a core wire **36500**, which may be connected to a portion of the expandable mesh segment **36400** (e.g., the distal end of mesh segment **36400**) and may extend through the elongated shaft **36350** to the control handle **36100**. Core wire **36500** may be secured to a wire actuator **36112** in the control handle **36100**, which may be configured to effect axial movement of the core wire **36500** to control expansion and contraction of the mesh segment **36400**.

[0128] In some embodiments, elongated shaft **36350** and core wire **36500** may be secured to different portions of expandable mesh segment **36400**. In some embodiments, elongated shaft **36350** may be secured to the proximal end **36410** of the mesh segment, and core wire **36500** may be secured to the distal end **36420** of the mesh segment. In addition, elongated shaft **36350** and core wire **36500** may both be configured for axial movement relative to control handle **36100** (via a mechanism detailed below). Accordingly, elongated shaft **36350** and core wire **36500** may both be configured to radially expand and contract the mesh segment **36400**. For example, elongated shaft **36350** may be configured to expand the mesh segment **36400** by pushing the proximal end **36410** of the mesh segment distally, towards distal end **36420**. Core wire **36500** may be configured to expand the mesh segment **36400** by pulling the distal end **36420** of the mesh segment proximally, towards proximal end **36410**. Elongated shaft **36350** and core wire **36500** may also be configured to contract the mesh segment **36400** by the opposite movements.

[0129] In some embodiments, elongated shaft **36350** and core wire **36500** may be configured to drive expansion of mesh segment **36400** simultaneously, from both the proximal end **36410** of the mesh segment and the distal end **36420** of the mesh segment. For example, FIGS. 36C and 36D show enlarged views of the contracted and expanded mesh segment **36400**, respectively. During transition from the radially-contracted state shown in FIG. 36C to the radially-expanded state shown in FIG. 36D, core wire **36500** may pull distal end **36420** in a proximal direction at the same time that elongated shaft **36350** pushes proximal end **36410** in a distal direction. In some embodiments, the proximal end **36410** and distal end **36420** of the mesh segment **36400** may be configured to move the same axial distance during radial

expansion of the mesh segment. For example, in FIG. 36C, **36410c** and **36420c** represent an axial length between the midpoint of the mesh segment **36400** and the distal end **36410** and proximal end **36420** of the mesh segment, respectively, when the mesh segment is in the radially-contracted state. Similarly, in FIG. 36D, **36410e** and **36420e** represent an axial length between the midpoint of the mesh segment **36400** and the distal end **36410** and proximal end **36420** of the mesh segment, respectively, when the mesh segment is in the radially-expanded state. The proximal end **36410** and distal end **36420** may be moved the same axial distance by the elongated shaft **36300** and core wire **36500**, respectively, during expansion and contraction of the mesh segment **36400**. As a result, the difference between distances **36410c** and **36410e** may be equal to the difference between distances **36420c** and **36420e**. As a result, the midpoint of the mesh segment **36400** may remain stationary during expansion and contraction, leading to improved anchoring and easier monitoring of the mesh location.

[0130] Advantageously, expanding the mesh segment **36400** from both ends may allow more uniform expansion of the mesh segment, especially in environments in which a portion of the mesh segment **36400** encounters resistance (such as from a clot or small vessel). For example, FIGS. 36E and 36F illustrate radial-expansion of the mesh segment **36400** within a body lumen **36820** having occlusive material **36800**. Because mesh segment **36400** is expanded from both the distal end **36420** and proximal end **36410**, it may engage the occlusive material **36800** from both the distal and proximal directions. For example, if the occlusive material **36800** creates resistance against the axial movement of the core wire **36500**, thus limiting the ability of the core wire **36500** to radially expand the mesh segment **36400**, the elongated shaft **36300** may complete radial expansion of the mesh segment **36400** and ensure that the occlusive material **36800** is fully engaged by the mesh segment (leading to better penetration of the occlusive material **36800**). As a result, the mesh segment **36400** may contact a larger surface area of the body lumen **36820** and provide more uniform and larger magnitude force application to the body lumen **36820**.

[0131] FIGS. 37A-C illustrate an exemplary control handle **37100** of an intraluminal device. Control handle **37100** may be configured to affect simultaneous axial movement of the elongated shaft and the core wire to expand the mesh segment (not pictured in FIGS. 37A-C). Control handle **37100** may include a first handle segment **37110** that is secured relative to the core wire **37500**. In some embodiments, core wire **37500** may extend into the control handle **37100** and may be secured to the first handle segment **37110** by solder, welding, adhesive, one or more mechanical fasteners, or other suitable means. Accordingly, axial movement of the first handle segment **37110** may cause corresponding axial movement of the core wire **37500**. The first handle segment **37110** may additionally be operably connected to wire actuator **37112**, which may include any appropriate mechanism for actuating axial movement of core wire **37500**, examples of which include, but are not limited to, a rotatable knob, a wheel, a button, a slider, a lever, a joystick, a touchpad, and combinations thereof. In some embodiments, wire actuator **37112** may affect axial movement of the first handle segment **37110**, which may cause corresponding axial movement of the core wire **37500**.



[0132] Control handle **37100** may additionally include a second handle segment **37120** that is secured relative to the proximal shaft segment **37200**, and thus, to the entire elongated shaft of the intraluminal device. In some embodiments, proximal shaft segment **37200** may extend into the control handle **37100** and may be secured to the second handle segment **37120** by solder, welding, adhesive, one or more mechanical fasteners, or other suitable means. For example, in FIG. 37B, site **37205** may be a location of connection between the second handle segment **37120** and the proximal shaft segment **37200**. As a result, axial movement of the second handle segment **37120** may cause corresponding axial movement of the proximal shaft segment **37200** and elongated shaft.

[0133] FIG. 37C illustrates a bottom plan view of the control handle **37100**. As shown in FIG. 37C, the first handle segment **37110** may include a first toothed rack **37114** and the second handle segment **37120** may include a second toothed rack **37124**. Both racks may engage a rotating gear **37130**, which may be configured to synchronize opposite axial movement of the handle segments **37110**, **37120**. In some embodiments, when the first handle segment **37110** moves in a first axial direction (e.g., in a distal direction) due to actuation of the wire actuator **37112**, first toothed rack **37114** may rotate gear **37130**, which may in turn drive axial movement of the second toothed rack **37124**, and thus the entire second handle segment **37120**, in a second axial direction that is opposite to the first axial direction (e.g., in a proximal direction). As a result, actuation of the wire actuator **37112** may cause opposite axial movements of the core wire **37500** and the elongated shaft, thus controlling radial expansion and contraction of the expandable mesh segment.

[0134] In some embodiments, the first handle segment **37110** and second handle segment **37120** may be configured to have a 1:1 movement ratio, such that the segments move the same axial distance in opposite directions. In some alternative embodiments, the first handle segment **37110** and second handle segment **37120** may be configured to have a different movement ratio, such as a 2:1 movement ratio, a 1:2 movement ratio, or any other suitable movement ratio. As a result, axial movement of one handle segment may correspond to an axial movement by the other handle segment that is a fraction of the distance. The movement ratio may be controlled by suitable mechanism, such as by incorporating an additional rotating gear into control handle **37100**, such that racks **37114** and **37124** are configured to have a different movement ratio.

[0135] In alternative embodiments, other structures may be utilized in place of the elongated shaft and/or the core wire. Other structures may include, for example, any composition of tubes, cable, coils, or other suitable elements.

[0136] FIGS. 38A and 38B illustrate an exemplary intraluminal device **38000** having multiple mesh segments **38400** and **38402**. Although the example illustrated in FIGS. 38A and 38B includes two mesh segments **38400** and **38402**, those of ordinary skill will understand that intraluminal device **38000** may include one mesh segment, two mesh segments, three mesh segments, four mesh segments, five mesh segments, or any other suitable number of mesh segments. Intraluminal device **38000** may be configured to actuate synchronized axial movement of the shaft segments **38200**, **38300** and of core wire **38500**, as discussed above. For example, core wire **38500** may be configured to move

mesh segment distal end **38420** in a first axial direction, and the elongated shaft may be configured to move mesh segment proximal end **38410** in a second, opposite axial direction. As a result, the core wire and elongated shaft may drive the radial expansion and contraction of all mesh segments **3840**, **38402** simultaneously.

[0137] FIGS. 39A and 39B illustrate an exemplary intraluminal device **39000** delivered through a catheter **39700**. In some embodiments, the distal end of intraluminal device **39000** may be passed through a first opening **39702** of the catheter and advanced distally to a treatment site within the body. The distal end of the intraluminal device **39000** may emerge from the distal end of the catheter **39700**, such that the expandable mesh portion **39400** may engage with the anatomy at the treatment site and may be configured for radial-expansion without being constrained by the catheter **39700**. The control handle **39100** of the intraluminal device may include a handle-shaft **39150**, which may extend distally from the handle over at least a portion of the elongated shaft (including at least a portion of the proximal shaft segment, which is not depicted in FIGS. 39A and 39B). Handle-shaft **39150** may be secured against movement relative to the control handle **39100**. Once the intraluminal device **39000** advanced through the catheter **39700**, the catheter opening **39702** may be removably locked to the handle-shaft **39150**, thus securing the catheter **39700** and control handle **39100** together. Once locked to the catheter **39700**, the wire actuator **39112** in the control handle **39100** may be actuated to control the synchronized axial movements of the core wire **39500** and the elongated shaft to expand and contract the mesh segment **39400**. Advantageously, this locking configuration may improve the maneuverability of the intraluminal device **39000** while the distal end thereof is positioned within the body, and may make it easier for the user to control expansion of the mesh segment **39400**.

[0138] Moreover, while illustrative embodiments have been described herein, the scope includes any and all embodiments having equivalent elements, modifications, omissions, combinations (e.g., of aspects across various embodiments), adaptations or alterations based on the present disclosure. The elements in the claims are to be interpreted broadly based on the language employed in the claims and not limited to examples described in the present specification or during the prosecution of the application, which examples are to be construed as non-exclusive. Further, the steps of the disclosed methods can be modified in any manner, including by reordering steps or inserting or deleting steps. It is intended, therefore, that the specification and examples be considered as example only, with a true scope and spirit being indicated by the following claims and their full scope of equivalents.

What is claimed is:

1. An intraluminal device, comprising:
  - a hollow elongated shaft having a distal end and a proximal end;
  - a first radially-expandable mesh segment situated distal to the elongated shaft, wherein the elongated shaft is secured relative to a first portion of the first mesh segment; and
  - a core wire affixed to a second portion of the first mesh segment and extending through the elongated shaft, wherein the elongated shaft is configured to radially expand the first mesh segment by axially moving the



first portion of the first mesh segment relative to the second portion of the first mesh segment, and wherein the core wire is configured to radially expand the first mesh segment by axially moving the second portion of the first mesh segment relative to the first portion of the first mesh segment.

2. The intraluminal device of claim 1, wherein the first portion of the first mesh segment includes a proximal end of the first mesh segment; and wherein the second portion of the first mesh segment includes a distal end of the first mesh segment.

3. The intraluminal device of claim 1, wherein the axial movement of the first portion of the first mesh segment is in a distal axial direction relative to the second portion of the first mesh segment.

4. The intraluminal device of claim 1, wherein the axial movement of the second portion of the first mesh segment is in a proximal axial direction relative to the first portion of the first mesh segment.

5. The intraluminal device of claim 1, wherein the elongated shaft and core wire are configured to simultaneously radially expand the first mesh segment.

6. The intraluminal device of claim 1, wherein the elongated shaft and core wire are configured to effect equidistant axial movement of the first portion of the first mesh segment and the second portion of the first mesh segment, respectively.

7. The intraluminal device of claim 1, further comprising: a handle situated proximal to the elongated shaft, wherein the elongated shaft and the core wire are configured for axial movement relative to the handle.

8. The intraluminal device of claim 7, wherein the handle comprises:

a first handle segment secured relative to the core wire; and

a second handle segment secured relative to the elongated shaft,

wherein the first handle segment and second handle segment are configured for equidistant movement in opposite axial directions.

9. The intraluminal device of claim 7, wherein the handle is configured to be secured relative to a delivery catheter such that the elongated shaft and the core wire are configured for axial movement relative to the delivery catheter.

10. The intraluminal device of claim 9, wherein the handle comprises:

a locking shaft extending from the distal end of the handle over at least a portion of the elongated shaft, wherein the locking shaft of the handle is configured to be secured to at least a portion of the delivery catheter.

11. The intraluminal device of claim 1, wherein the first mesh segment comprises:

a plurality of wires woven to form the first mesh segment, wherein the first mesh segment is configured to capture a blood clot.

12. The intraluminal device of claim 1, further comprising:

a second radially-expandable mesh segment situated between the first mesh segment and the elongated shaft, wherein the elongated shaft is affixed to a proximal end of the second mesh segment and is configured to radially expand the first mesh segment and the second mesh segment by axially moving the proximal end of the second mesh segment, and

wherein the core wire is configured to radially expand the first mesh segment and the second mesh segment by axially moving a distal end of the first mesh segment.

13. The intraluminal device of claim 12, wherein the second mesh segment comprises:

a plurality of wires woven to form the second mesh segment, wherein the second mesh segment is configured to capture a blood clot.

14. A method of removing a clot from a body lumen, the method comprising:

positioning a radially-expandable mesh segment of an intraluminal device downstream of the clot in the body lumen while the mesh segment is in a radially-contracted state, the mesh segment having a proximal end and a distal end;

radially-expanding the mesh segment by moving the proximal end of the mesh segment a first distance in a first direction and by moving the distal end of the mesh segment a second distance in a second direction, wherein the first distance is equal to the second distance and wherein the first direction is opposite the second direction;

moving the radially-expanded mesh segment into engagement with the clot; and

removing the clot by moving the radially-expanded mesh segment in an upstream direction.

15. The method of claim 14, wherein the proximal and distal ends of the mesh segment move simultaneously during radial expansion of the mesh segment.

16. The method of claim 14, wherein the first direction is a distal direction and the second direction is a proximal direction.

17. The method of claim 14, wherein the intraluminal device further comprises:

a hollow elongated shaft situated proximal to the mesh segment, wherein the elongated shaft is secured relative to the proximal end of the mesh segment;

a core wire affixed to the distal end of the mesh segment; and

a handle situated proximal to the elongated shaft, wherein the elongated shaft and the core wire move axially relative to the handle during radial expansion of the mesh segment.

18. The method of claim 14, wherein the elongated shaft and the core wire move simultaneously to radially expand the mesh segment.

19. The method of claim 14, wherein radially-expanding the mesh segment comprises:

axially moving the proximal end of the mesh segment relative to the distal end of the mesh segment with the elongated shaft; and

axially moving the distal end of the mesh segment relative to the proximal end of the mesh segment with the core wire.

20. The method of claim 14, wherein the handle comprises:

a first handle segment secured relative to the core wire; and

a second handle segment secured relative to the elongated shaft,

wherein the first handle segment and second handle segment move the same distance in opposite axial directions during radial expansion of the mesh segment.

\* \* \* \* \*