

US 20220341516A1

(19) **United States**(12) **Patent Application Publication**
Dhagat et al.(10) **Pub. No.: US 2022/0341516 A1**(43) **Pub. Date: Oct. 27, 2022**(54) **SWAGED PIPE FITTING SYSTEMS AND METHODS**(71) Applicant: **TRINITY BAY EQUIPMENT HOLDINGS, LLC**, Houston, TX (US)(72) Inventors: **Alok Dhagat**, Katy, TX (US); **Matthew Allen Hegler**, Kingwood, TX (US); **Mark Douglas Kalman**, Luthersville, GA (US); **Richard Charles Lawrence**, Mont Belvieu, TX (US); **Mikel Lee Lewis**, Baytown, TX (US); **Nader Matari**, Houston, TX (US)(21) Appl. No.: **17/857,911**(22) Filed: **Jul. 16, 2022****Related U.S. Application Data**

(63) Continuation of application No. 16/953,595, filed on Nov. 20, 2020, now Pat. No. 11,378,207.


(60) Provisional application No. 62/939,375, filed on Nov. 22, 2019.

Publication Classification(51) **Int. Cl.****F16L 13/14** (2006.01)**F16L 33/01** (2006.01)(52) **U.S. Cl.**CPC **F16L 13/142** (2013.01); **F16L 33/01** (2013.01); **F16L 11/081** (2013.01)

(57)

ABSTRACT

Techniques for implementing and/or installing a system including pipe segment tubing and a swaged pipe fitting secured to the pipe segment tubing. The pipe segment tubing includes a carcass layer, an internal pressure sheath layer disposed around the carcass layer, a reinforcement layer disposed around the internal pressure sheath layer, and an outer sheath layer disposed around the reinforcement layer. The swaged pipe fitting includes a fitting body that defines a bore, an internal pressure sheath seal that seals the internal pressure sheath layer of the pipe segment tubing within the swaged pipe fitting, and a fitting jacket secured to the fitting body, in which the fitting jacket is conformally deformed around the pipe segment tubing to anchor the reinforcement layer of the pipe segment tubing in the swaged pipe fitting.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 19
(Continued)

SWAGED PIPE FITTING SYSTEMS AND METHODS

CROSS-REFERENCE

[0001] The present disclosure claims priority to and benefit of U.S. Provisional Patent Application No. 62/939,375, entitled “SWAGED END FITTINGS FOR FLEXIBLE PIPE AND METHODS OF INSTALLING SAME” and filed Nov. 22, 2019 and U.S. Non-provisional patent application Ser. No. 16/953,595 entitled “SWAGED PIPE FITTING SYSTEMS AND METHODS” filed Nov. 20, 2020, which is incorporated herein by reference in its entirety for all purposes.

BACKGROUND

[0002] Flexible pipe can be utilized to transport production fluids, such as oil and/or gas and/or water, from one location to another. Flexible pipe is generally formed as an assembly of a portion of flexible pipe body and one or more end fittings. The end fittings may be used to connect segments of flexible pipe together or to connect them to terminal equipment, such as sub-sea structures or floating facilities. End fittings are important components for terminating and anchoring the pipe layers, sealing and venting gas in these environments.

[0003] Existing end fittings have certain deficiencies and disadvantages. For example, current end fittings used with offshore flexible pipe as described in API RP 17B (“17B Recommended Practice for Unbonded Flexible Pipe”) with carcass are costly and have a long installation time. Improvements in this field of technology are therefore desired.

SUMMARY

[0004] This summary is provided to introduce a selection of concepts that are further described below in the detailed description. This summary is not intended to identify key or essential features of the claimed subject matter, nor is it intended to be used as an aid in limiting the scope of the claimed subject matter.

[0005] In one embodiment, a system including pipe segment tubing and a swaged pipe fitting secured to the pipe segment tubing. The pipe segment tubing includes a carcass layer, an internal pressure sheath layer disposed around the carcass layer, a reinforcement layer disposed around the internal pressure sheath layer, and an outer sheath layer disposed around the reinforcement layer. The swaged pipe fitting includes a fitting body that defines a bore, an internal pressure sheath seal that seals the internal pressure sheath layer of the pipe segment tubing within the swaged pipe fitting, and a fitting jacket secured to the fitting body, in which the fitting jacket is conformally deformed around the pipe segment tubing to anchor the reinforcement layer of the pipe segment tubing in the swaged pipe fitting.

[0006] In another embodiment, a method of installing a swaged pipe fitting on a pipe segment includes disposing a fitting jacket of the swaged pipe fitting circumferentially around tubing of the pipe segment, in which the fitting jacket is secured to a fitting body of the swaged pipe fitting that defines a body bore, disposing a support cylinder directly adjacent to a carcass layer of the pipe segment, in which the carcass layer of the pipe segment comprises an interlocked metal layer, and conformally deforming the fitting jacket of

the swaged pipe fitting around the tubing of the pipe segment to secure the swaged pipe fitting to the pipe segment and to seal tubing of the pipe segment within the swaged pipe fitting.

[0007] In another embodiment, a swaged pipe fitting includes a fitting body that defines a body bore, a fitting connector secured to the fitting body to enable the swaged pipe fitting to be connected to another pipeline component, a face seal compressed between the fitting body and the fitting connector, an internal pressure sheath seal compressed against an internal pressure sheath layer of a pipe segment to seal the internal pressure sheath layer within the swaged pipe fitting, a carcass isolating ring that electrically isolates a carcass layer of the pipe segment in the swaged pipe fitting, and a fitting jacket secured to the fitting body, in which the fitting jacket is conformally deformed around an outer sheath layer of the pipe segment to secure the swaged pipe fitting to the pipe segment and to seal the outer sheath layer of the pipe segment within the swaged pipe fitting.

BRIEF DESCRIPTION OF DRAWINGS

[0008] FIG. 1 is a block diagram of an example of a pipeline system including pipe segments and pipe fittings, in accordance with an embodiment of the present disclosure.

[0009] FIG. 2 is a side view of an example of a pipe segment of FIG. 1 that includes a pipe bore defined by its tubing as well as fluid conduits within an annulus of its tubing, in accordance with an embodiment of the present disclosure.

[0010] FIG. 3 is an example of a portion of the pipe segment of FIG. 2 with one or more reinforcement layers which may also define one or more helically shaped fluid conduits within the annulus of its tubing, in accordance with an embodiment of the present disclosure.

[0011] FIG. 4 is an axial cross-section profile of an example of a pipe segment that includes a carcass layer, in accordance with an embodiment of the present disclosure.

[0012] FIG. 5 is an axial cross-section profile of a portion of a pipeline system that includes an example of a swaged pipe fitting and a pipe segment, in accordance with an embodiment of the present disclosure.

[0013] FIG. 6 is an axial cross-section profile of a swage machine and a portion of a swaged pipe fitting, in accordance with an embodiment of the present disclosure.

[0014] FIG. 7 is a perspective view of a grab sleeve that may be included in a swaged pipe fitting, in accordance with an embodiment of the present disclosure.

[0015] FIG. 8 is an axial cross-section profile of a portion of a pipeline system that includes another example of a swaged pipe fitting and a pipe segment, in accordance with an embodiment of the present disclosure.

[0016] FIG. 9 is an axial cross-section profile of a portion of a pipeline system that includes a further example of a swaged pipe fitting and a pipe segment, in accordance with an embodiment of the present disclosure.

[0017] FIG. 10 is an axial cross-section profile of a portion of a pipeline system that includes another example of a swaged pipe fitting and a pipe segment, in accordance with an embodiment of the present disclosure.

[0018] FIG. 11 is an axial cross-section profile of a portion of a pipeline system that includes a further example of a swaged pipe fitting and a pipe segment, in accordance with an embodiment of the present disclosure.

[0019] FIG. 12 is an axial cross-section profile of a portion of a pipeline system that includes another example of a swaged pipe fitting and a pipe segment, in accordance with an embodiment of the present disclosure.

[0020] FIG. 13 is an axial cross-section profile of a portion of a pipeline system that includes a further example of a swaged pipe fitting and a pipe segment, in accordance with an embodiment of the present disclosure.

[0021] FIG. 14 is an axial cross-section profile of a portion of a pipeline system that includes another example of a swaged pipe fitting and a pipe segment, in accordance with an embodiment of the present disclosure.

[0022] FIG. 15 is an axial cross-section profile of a portion of a pipeline system that includes a further example of a swaged pipe fitting and a pipe segment, in accordance with an embodiment of the present disclosure.

[0023] FIG. 16 is an axial cross-section profile of a portion of a pipeline system that includes another example of a swaged pipe fitting and a pipe segment, in accordance with an embodiment of the present disclosure.

[0024] FIG. 17 is a perspective view of an example of a support cylinder tool that may be used to support a pipe segment during swaging, in accordance with an embodiment of the present disclosure.

[0025] FIG. 18 is an axial cross-section profile of the support cylinder tool of FIG. 17 disposed within a pipe segment, in accordance with an embodiment of the present disclosure.

[0026] FIG. 19 is a flow diagram of an example of a process for deploying a swaged pipe fitting at a pipe segment, in accordance with an embodiment of the present disclosure.

DETAILED DESCRIPTION

[0027] One or more specific embodiments of the present disclosure will be described below with reference to the figures. As used herein, the term “coupled” or “coupled to” may indicate establishing either a direct or indirect connection and, thus, is not limited to either unless expressly referenced as such. The term “set” may refer to one or more items. Wherever possible, like or identical reference numerals are used in the figures to identify common or the same features. The figures are not necessarily to scale. Certain features and/or certain views of the figures may be shown exaggerated in scale for purposes of clarification. Additionally, all depicted examples are intended to be illustrative and not limiting.

[0028] The present disclosure generally relates to pipeline systems that may be implemented and/or operated to transport (e.g., convey) fluid, such as liquid and/or gas, from a fluid source to a fluid destination. Generally, a pipeline system may include pipe fittings, such as a midline pipe fitting and/or a pipe end fitting, and one or more pipe segments. More specifically, a pipe segment may generally be secured and sealed in one or more pipe fittings to facilitate fluidly coupling the pipe segment to another pipeline component, such as another pipe segment, another pipe fitting, a fluid source, and/or a fluid destination.

[0029] An example of a pipeline system 10 is shown in FIG. 1. A pipeline system 10 may generally, be coupled between a fluid source 12 and a fluid destination 14. For example, in some instances, the fluid source 12 may be a production well and the fluid destination 14 may be a fluid storage tank. In other instances, the fluid source 12 may be

a first (e.g., lease facility) storage tank and the fluid destination 14 may be a second (e.g., refinery) storage tank.

[0030] In any case, the pipeline system 10 may generally convey fluid, such as gas and/or liquid, from the fluid source 12 to the fluid destination 14. The pipeline system 10 may be used in many applications, including without limitation, both onshore and offshore oil and gas applications. For example, the pipeline system 10 may be used to transport hydrocarbon, aqueous fluid, and/or another suitable fluid, such as crude oil, petroleum, natural gas, produced water, fresh water, fracturing fluid, flowback fluid, carbon dioxide, or any combination thereof.

[0031] To convey fluid from the fluid source 12 to the fluid destination 14, a pipeline system 10 may include one or more pipe fittings 18 and one or more pipe segments 20. For example, the depicted pipeline system 10 includes a first pipe segment 20A, a second pipe segment 20B, and an Nth pipe segment 20N. Additionally, the depicted pipeline system 10 includes a first pipe (e.g., end) fitting 18A, which couples the fluid source 12 to the first pipe segment 20A, a second pipe (e.g., midline) fitting 18B, which couples the first pipe segment 20A to the second pipe segment 20B, and an Nth pipe (e.g., end) fitting 18N, which couples the Nth pipe segment 20N to the fluid destination 14.

[0032] In other embodiments, a pipeline system 10 may include fewer than three (e.g., two or one) pipe segments 20 or more than three (e.g., four, five, or more) pipe segments 20. Additionally or alternatively, in other embodiments, a pipeline system 10 may include fewer than four (e.g., three or two) pipe fittings 18 or more than four (e.g., five, six, or more) pipe fittings 18.

[0033] In any case, a pipe segment 20 generally includes tubing that may be used to convey (e.g., transfer and/or transport) water, gas, oil, and/or any other suitable type of fluid. The tubing of a pipe segment 20 may be made of any suitable type of material, such as plastic, metal, and/or a composite (e.g., fiber-reinforced composite) material. In fact, as will be described in more detail below, in some embodiments, the tubing of a pipe segment 20 may have multiple different tubing layers. For example, the tubing of a pipe segment 20 may include a first high-density polyethylene (e.g., fluid containment) layer, one or more reinforcement (e.g., steel strip) layers external to the first high-density polyethylene layer, and a second high-density polyethylene (e.g., external corrosion protection) layer external to the one or more reinforcement layers.

[0034] Additionally, as in the depicted example, one or more (e.g., second and/or Nth) pipe segments 20 in a pipeline system 10 may be curved (e.g., large deflection). To facilitate producing a curve in a pipe segment 20, in some embodiments, the pipe segment 20 may be flexible, for example, such that the pipe segment 20 is spoolable on a reel and/or in a coil (e.g., during transport and/or before deployment of the pipe segment 20). In other words, in some embodiments, one or more pipe segments 20 in the pipeline system 10 may be a flexible pipe, such as a bonded flexible pipe, an unbonded flexible pipe, a flexible composite pipe (FCP), a thermoplastic composite pipe (TCP), or a reinforced thermoplastic pipe (RTP). Generally, as described in API RP 17B, a flexible pipe combines low bending stiffness with high axial tensile stiffness, which is achieved by a multi-layer construction. The two basic components are helical reinforcement layers and polymer sealing layers, which allow a much smaller radius of curvature than for a

steel pipe with the same pressure capacity. In general, an unbonded flexible has a lower bending stiffness than bonded flexible pipe due to the tubing layers not being bonded to one another. Bending stiffness may also be reduced in both bonded and unbonded flexible pipe when they have annular gaps between adjacent reinforcement strips in the reinforcement layers. In fact, at least in some instances, increasing flexibility (e.g. reducing bending stiffness) of a pipe segment **20** may facilitate improving deployment efficiency of a pipeline system **10**, for example, by having long coiled or reeled pipe segments transported to installation locations, thereby substantially reducing the number of pipe fittings relative to rigid pipe installations.

[0035] In some embodiments, the annular gaps between reinforcement strips are devoid of solid material. In fact, in some embodiments, the free space in the tubing annulus of a pipe segment **20** may span the length of the pipe segment **20** and, thus, define one or more fluid conduits in the annulus of the tubing, which are separate from the pipe bore. In other words, in such embodiments, a pipe segment **20** may enable fluid flow via its pipe bore, fluid flow via a fluid conduit defined within its tubing annulus, or both.

[0036] To help illustrate, an example of a pipe segment **20**, which includes tubing **22** with annular gaps (e.g., fluid conduits and/or free space) **24** defined in its annulus **25**, is shown in FIG. 2. As depicted, the pipe segment tubing **22** includes multiple tubing layers including an internal pressure sheath (e.g., inner barrier) layer **26** and an outer sheath (e.g., outer barrier) layer **28**. In some embodiments, the internal pressure sheath layer **26** and/or the outer sheath layer **28** of the pipe segment tubing **22** may be made from composite material and/or plastic, such as high-density polyethylene (HDPE), raised temperature polyethylene (PE-RT), cross-linked polyethylene (XLPE), polyamide 11 (PA-11), polyamide 12 (PA-12), polyvinylidene difluoride (PVDF), or any combination thereof. Although a number of particular layers are depicted, it should be understood that the techniques described in the present disclosure may be broadly applicable to composite pipe body structures including two or more layers, for example, as distinguished from a rubber or plastic single-layer hose subject to vulcanization.

[0037] In any case, as depicted, an inner surface **30** of the internal pressure sheath layer **26** defines (e.g., encloses) a pipe bore **32** through which fluid can flow, for example, to facilitate transporting fluid from a fluid source **12** to a fluid destination **14**. In some embodiments, the internal pressure sheath layer **26** of a pipe segment **20** may be the innermost layer of the pipe segment **20**. However, as will be described in more detail below, in other embodiments, a carcass layer may be disposed under the internal pressure sheath layer **26** and, thus, the carcass layer may be the innermost layer of the pipe segment.

[0038] Additionally, in some embodiments, the outer sheath layer **28** of a pipe segment **20** may be the outermost layer of the pipe segment **20**. In particular, as described in API RP 17B, the outer sheath layer **28** may protect the pipe segment **20** against penetration of seawater and other external environmental conditions, corrosion, abrasion, and/or mechanical damage. In any case, in some embodiments, the outer sheath layer **28** of a pipe segment **20** may include a number of sublayers.

[0039] Furthermore, as depicted, the tubing annulus **25** of the pipe segment **20** is between its internal pressure sheath layer **26** and its outer sheath layer **28**. As will be described

in more detail below, the tubing annulus **25** of a pipe segment **20** may include one or more intermediate layers. Additionally, as depicted, annular gaps **24** running along the length of the pipe segment **20** are defined in the tubing annulus **25**.

[0040] However, in other embodiments, a pipe segment **20** may include fewer than two (e.g., one) or more than two (e.g., three, four, or more) annular gaps **24** defined in its tubing annulus **25**. Additionally, in other embodiments, an annular gap **24** defined in the tubing annulus **25** of a pipe segment **20** may run non-parallel to the pipe bore **32** of the pipe segment **20**, for example, such that the annular gap **24** is skewed relative to the longitudinal axis of the pipe bore **32**.

[0041] To help illustrate, an example of a portion **36** of a pipe segment **20**, which includes an internal pressure sheath layer **26** and an intermediate layer—namely a reinforcement (e.g., tensile and/or armor) layer **34**—included in the annulus **25** of its pipe segment tubing **22**, is shown in FIG. 3. However, it should be appreciated that, in other embodiments, the intermediate layers of pipe segment tubing **22** may include one or more tape layers, one or more insulation layers one or more intermediate sheath layers, one or more anti-wear layers, or any combination thereof.

[0042] As depicted, the reinforcement layer **34** includes a reinforcement strip **40**. To improve tensile strength and/or hoop strength of pipe segment tubing **22**, in some embodiments, a reinforcement strip **40** in the pipe segment tubing **22** may be made at least in part using solid material that has a higher tensile strength and/or a higher linear modulus of elasticity than solid material that is used to make the internal pressure sheath layer **26** and/or the outer sheath layer **28** of the pipe segment tubing **22**. For example, the internal pressure sheath layer **26** may be made using plastic, such as high-density polyethylene (HDPE), while the reinforcement strip **40** may be made using metal, such as carbon steel, stainless steel, duplex stainless steel, super duplex stainless steel, or any combination thereof. In other words, at least in some such embodiments, a reinforcement strip **40** of the pipe segment tubing **22** may be made from electrically conductive material, which, at least in some instances, may enable communication of electrical (e.g., control and/or sensor) signals via the reinforcement strip **40**. However, in other embodiments, one or more reinforcement strips **40** of pipe segment tubing **22** may be made at least in part using a composite material.

[0043] Additionally, the reinforcement strip **40** is helically disposed (e.g., wound and/or wrapped) on the internal pressure sheath layer **26** such that gaps (e.g., openings) are left between adjacent windings to define an annular gap (e.g., fluid conduit) **24**. In other words, in some embodiments, the reinforcement layer **34** may be made at least in part by winding the reinforcement strip **40** around the internal pressure sheath layer **26** at a non-zero lay angle (e.g., fifty-two degrees) relative to the longitudinal axis of the pipe bore **32**. In any case, as depicted, the resulting annular gap **24** runs helically along the pipe segment **20**, for example, such that the annular gap **24** is skewed fifty-two degrees relative to the longitudinal axis of the pipe bore **32**.

[0044] Nevertheless, in some embodiments, one or more other intermediate layers, such as an anti-wear layer, may be included in the annulus **25** of pipe segment tubing **22**. In other words, in such embodiments, a reinforcement strip **40** of the reinforcement layer **34** may be disposed on another

intermediate layer, for example, instead of directly on the internal pressure sheath layer 26 of the pipe segment tubing 22. Moreover, in other embodiments, a reinforcement layer 34 of pipe segment tubing 22 may include multiple reinforcement strips 40.

[0045] In any case, in some embodiments, an outer sheath layer 28 may be disposed directly over the depicted reinforcement layer 34 and, thus, cover the depicted annular gap 24. However, in other embodiments, the tubing annulus 25 of pipe segment tubing 22 may include multiple (e.g., two, three, four, or more) reinforcement layers 34. In other words, in such embodiments, one or more other reinforcement layers 34 may be disposed over the depicted reinforcement layer 34. In fact, in some such embodiments, the reinforcement strips 40 in the one or more other reinforcement layers 34 may also each be helically disposed such that there are annular gaps (e.g., fluid conduits and/or free space) 24 between adjacent windings.

[0046] For example, a first other reinforcement strip 40 of a first other reinforcement layer 34 may be helically disposed on the depicted reinforcement strip 40 using the same non-zero lay angle as the depicted reinforcement strip 40 to cover (e.g., enclose) the depicted annular gap 24 and to define another annular gap 24 in the first other reinforcement layer 34. Additionally, a second other reinforcement strip 40 of a second other reinforcement layer 34 may be helically disposed on the first other reinforcement strip 40 using another non-zero lay angle, which may be at or near the inverse of the non-zero lay angle of the depicted reinforcement strip 40, to define another annular gap 24 in the second other reinforcement layer 34. Furthermore, a third other reinforcement strip 40 of a third other reinforcement layer 34 may be helically disposed on the second other reinforcement strip 40 using the same non-zero lay angle as the second other reinforcement strip 40 to cover the other annular gap 24 in the second other reinforcement layer 34 and to define another annular gap 24 in the third other reinforcement layer 34. In some embodiments, an outer sheath layer 28 may be disposed over the third other reinforcement layer 34 and, thus, cover (e.g., enclose) the other annular gap 24 in the third other reinforcement layer 34.

[0047] In any case, in some instances, a pipe segment 20 may be deployed in an elevated pressure environment, for example, underwater in a subsea application. To improve the collapse and/or crush resistance of its tubing 22, a carcass layer may be disposed within (e.g., under) the internal pressure sheath layer 26 of the pipe segment 20. In other words, in such instances, the internal pressure sheath layer 26 may be disposed around (e.g., over) the carcass layer and, thus, the carcass layer may be the innermost layer of the pipe segment tubing 22.

[0048] To help illustrate, an example of pipe segment tubing 22 that includes a carcass layer 37 is shown in FIG. 4. To improve collapse and/or crush resistance, in some embodiments, the carcass layer 37 may be made from metal, such as carbon steel, stainless steel, duplex stainless steel, super duplex stainless steel, or any combination thereof. Additionally, as depicted, the carcass layer 37 is an interlocked layer in the pipe segment tubing 22.

[0049] In addition to the carcass layer 37, as depicted, the pipe segment tubing 22 includes an internal pressure sheath layer 26 and an outer sheath layer 28. Furthermore, as depicted, the pipe segment tubing 22 includes intermediate

layers 38 disposed between the internal pressure sheath layer 26 and the outer sheath layer 28 and, thus, in the annulus 25 of the pipe segment tubing 22. As depicted, the intermediate layers 38 include at least a reinforcement layer 34 with one or more reinforcement strips 40 that define one or more annular gaps (e.g., fluid conduits and/or free space) 24 in the tubing annulus 25.

[0050] In some embodiments, the intermediate layers 38 of pipe segment tubing 22 may include one or more tape layers, one or more intermediate sheath layers, one or more anti-wear layers, one or more insulation layers, or any combination thereof. Additionally, as described above, in some embodiments, pipe segment tubing 22 may include multiple reinforcement layers 34, which each include one or more reinforcement strips 40. In any case, in a pipeline system 10, the tubing 22 of a pipe segment 20 may be secured and sealed in a pipe fitting 18.

[0051] To help illustrate, a portion 42A of a pipeline system 10, which includes an example of a pipe fitting 18—namely a swaged pipe fitting 44A—and pipe segment tubing 22A, is shown in FIG. 5. As in the depicted example, a swaged pipe fitting 44 may include a fitting body 48, which defines a body (e.g., fitting) bore, a fitting connector (e.g., flange or weldneck) 46, and a fitting jacket 50. The fitting connector 46 may be secured to the fitting body 48 to enable the swaged pipe fitting 44 to be connected to another pipeline component, such as a fluid source 12, a fluid destination 14, or another pipe fitting 18.

[0052] Additionally, to facilitate securing a swaged pipe fitting 44 to pipe segment tubing 22, a fitting jacket 50 of the swaged pipe fitting 44 may be secured (e.g., welded) to its fitting body 48. To facilitate securing the swaged pipe fitting 44A to the pipe segment tubing 22A, the fitting jacket 50A of the swaged pipe fitting 44A may be compressed radially inward such that an inner surface 52 of the fitting jacket 50A engages (e.g., grips) an outer surface 54 of the pipe segment tubing 22A, for example, via a swage machine secured to the swaged pipe fitting 44A. In other words, the fitting jacket 50A is shown in its swaged state in FIG. 5. Before being swaged, a fitting jacket 50 may be in an unswaged state in which its inner surface diameter is larger than the outer surface diameter of corresponding pipe segment tubing 22, thereby enabling the pipe segment tubing 22 to be inserted under (e.g., within) the fitting jacket 50.

[0053] To help further illustrate, an example of a swage machine 56 and a portion 58B of a swaged pipe fitting 44 are shown in FIG. 6. As depicted, open space 60 is present between the inner surface 52 of the fitting jacket 50B and the outer surface 54 of the pipe segment tubing 22B, thereby enabling the pipe segment tubing 22B to be inserted (e.g., disposed) under (e.g., within) the fitting jacket 50B. In other words, the fitting jacket 50B is shown in its unswaged state in FIG. 6.

[0054] To transition a fitting jacket 50 from its unswaged state to its swaged state, a swage machine 56 may include a grab plate 62 and a die plate 64. The grab plate 62 may include a grab attachment 66 with an L-shaped axial cross-section profile, which may interlock with an end of the fitting body 48 of a swaged pipe fitting 44. In other words, the grab plate 62 of a swage machine 56 may generally facilitate securing the swage machine 56 to a swaged pipe fitting 44.

[0055] Additionally, as depicted, the die plate 64 of a swage machine 56 may have a set of die segments 68 loaded

therein. In particular, the set of die segments **68** may be loaded into the die plate **64** such that the set of die segments **68** open toward the grab plate **62** of the swage machine **56**. When compressed against a fitting jacket **50** of a swaged pipe fitting **44** in an axial direction **70** toward the grab plate **62**, the die segments **68** may compress the fitting jacket **50** inward in a radial direction **72** around the circumference, for example, such that the inner surface **52** of the fitting jacket **50** engages the outer surface **54** of pipe segment tubing **22** disposed thereunder.

[0056] To facilitate preserving the pipe bore **32** defined by pipe segment tubing **22** during a swaging operation, as in the depicted example, in some embodiments, a swaged pipe fitting **44** may include a support cylinder **74**, which is disposed directly adjacent to an innermost (e.g., carcass) layer of the pipe segment tubing **22**. In the depicted example, the support cylinder **74B** of the swaged pipe fitting **44** is disposed under (e.g., within) the carcass layer **37** of the pipe segment tubing **22B**. To facilitate supporting pipe segment tubing **22** during a swaging operation, the support cylinder **74** of a swaged pipe fitting **44** may extend beyond both ends of a corresponding fitting jacket **50**. Additionally, due to a fitting jacket **50** being swaged, one or more intermediate (e.g., reinforcement) layers **38** of pipe segment tubing **22** may be compressed between the fitting jacket **50** and the support cylinder **74** of a swaged pipe fitting **44**, thereby anchoring the one or more intermediate layers **38** in the swaged pipe fitting **44**. Furthermore, due to swaging, the fitting jacket **50** of a swaged pipe fitting **44** may engage the outer sheath layer **28** of a pipe segment **20** and, thus, block the ingress of external environmental fluids, such as seawater into the tubing annulus **25** of the pipe segment **20**, thereby sealing the outer sheath layer **28** of the pipe segment **20**.

[0057] Moreover, as will be described in more detail below, in some embodiments, the support cylinder **74** of a swaged pipe fitting **44** may include threading on its outer surface. In particular, in such embodiments, the threading on the outer surface of the support cylinder **74** may threadingly interlock with the inner surface of the carcass layer **37** of a corresponding pipe segment **20**. Thus, in such embodiments, the support cylinder **74** may anchor the carcass layer **37** in the swaged pipe fitting **44**. However, in other embodiments, the support cylinder **74** of a swaged pipe fitting **44** may not include threading, for example, instead having a smooth, knurled, serrated or other outer surface condition.

[0058] In any case, as will be described in more detail below, in other embodiments, the support cylinder **74** of a swaged pipe fitting **44** may be integrated with its fitting connector **46** or its fitting body **48**, for example, instead of being a separate component. Alternatively, as will be described in more detail below, in other embodiments, a swaged pipe fitting **44** may not include a support cylinder **74**, for example, when a support cylinder tool is used instead.

[0059] To compress a set of die segments **68** against a fitting jacket **50** in an axial direction **70**, as depicted, a swage machine **56** may include one or more swaging actuators **76**. In the depicted example, the swage machine **56** includes a first swaging actuator **76A** and an Nth swaging actuator **76N**. In some embodiments, one or more swaging actuators **76** in a swage machine **56** may be a fluid actuator, such as a hydraulic actuator or a pneumatic actuator. Each swaging actuator **76** of the swage machine **56** includes an actuator

cylinder **78** and an actuator piston **80**, which selectively extends out from the actuator cylinder **78** based at least in part on the supply of fluid (e.g., liquid and/or gas) to the actuator cylinder **78** and/or selectively retracts into the actuator cylinder **78** based at least in part on the extraction of fluid from the actuator cylinder **78**.

[0060] In the depicted example, the actuator cylinder **78** of each swaging actuator **76** is secured to the die plate **64** of the swage machine **56**. Additionally, in the depicted example, the actuator piston **80** of each swaging actuator **76** extends through the die plate **64** and is secured to the grab plate **62** of the swage machine **56**. As such, to perform a swaging operation, one or more swaging actuators **76** in the swage machine **56** may be operated to pull the grab plate **62** toward the die plate **64** via one or more reverse (e.g., retracting) strokes such that the fitting jacket **50B** moves through the set of die segments **68** loaded in the die plate **64**. In this manner, a swage machine **56** may be operated to transition a fitting jacket **50** of a swaged pipe fitting **44** from its unswaged state to its swaged state and, thus, securing the swaged pipe fitting **44** to pipe segment tubing **22** inserted under the fitting jacket **50**.

[0061] However, it should be noted that the techniques described in the present disclosure are not limited to a specific configuration of a swage machine **56**. For example, in other embodiments, a swage machine **56** may include fewer than two (e.g., one) swaging actuators **76** or more than two (e.g., three, four, or more) swaging actuators **76**. Additionally, in other embodiments, a swage machine **56** may be operated to push its die plate **64** toward its grab plate **62** via one or more forward (e.g., extending) strokes such that a corresponding fitting jacket **50** moves through the set of die segments **68** loaded in the die plate **64**. Furthermore, in other embodiments, a swaged pipe fitting **44** may be swaged as a whole. Moreover, to improve securement strength, in some embodiments, a swaged pipe fitting **44** may include a grab sleeve, which may be disposed between the internal pressure sheath layer **26** and an intermediate layer **38** of pipe segment tubing **22** before a fitting jacket **50** of the swaged pipe fitting **44** is swaged around the pipe segment tubing **22**.

[0062] To help illustrate, an example of a grab sleeve **82**, which may be included in a swaged pipe fitting **44**, is shown in FIG. 7. As mentioned above, a grab sleeve **82** may be disposed between the internal pressure sheath layer **26** and an intermediate (e.g., reinforcement) layer **38** of pipe segment tubing **22**. In some embodiments, the grab sleeve **82** may be made from material that is more rigid than material used to make the internal pressure sheath layer **26** of the pipe segment tubing **22**. For example the grab sleeve **82** may be made from metal, such as carbon steel, stainless steel, duplex stainless steel, super duplex stainless steel, or any combination thereof.

[0063] Additionally, as depicted, the grab sleeve **82** includes a slit **84** along its longitudinal axis. Thus, during swaging, the grab sleeve **82** may contract radially inward and engage the internal pressure sheath layer **26** of pipe segment tubing **22**. Due to the resulting increased thickness, the grab sleeve **82** may facilitate anchoring an intermediate layer **38** (e.g., reinforcement layer **34**) of the pipe segment tubing **22** between the grab sleeve **82** and a fitting jacket **50** of a corresponding swaged pipe fitting **44**.

[0064] To facilitate contraction around the internal pressure sheath layer **26** of pipe segment tubing **22**, in some embodiments, a grab sleeve **82** may include a crumple zone

86. The crumple zone **86** may include multiple openings **88** formed through the grab sleeve **82**. To facilitate insertion between the internal pressure sheath layer **26** and an intermediate layer **38** of pipe segment tubing **22**, in some embodiments, a grab sleeve **82** may include a first tapered end **90A** and a second tapered end **90B**.

[0065] However, in other embodiments, a grab sleeve **82** may not include a tapered end **90** or include a single tapered end **90**. Additionally, in other embodiments, a grab sleeve **82** may not include a dedicated crumple zone **86**. Alternatively, in other embodiments, a swaged pipe fitting **44** may not include a grab sleeve **82**.

[0066] In any case, returning to the swaged pipe fitting **44A** of FIG. **5**, after the support cylinder **74A** is inserted and the fitting jacket **50A** is swaged, the fitting connector **46A** may be secured to the fitting body **48A**. As in the depicted example, in some embodiments, the fitting connector **46** of a swaged pipe fitting **44** may be secured to a corresponding fitting body **48** via one or more threaded fasteners **92**, such as a bolt or a screw.

[0067] However, in other embodiments, the fitting connector **46** of a swaged pipe fitting **44** may be secured to a corresponding fitting body **48** via fewer than two (e.g., one) threaded fasteners **92** or more than two (e.g., three, four, or more) threaded fasteners **92**. Alternatively, in other embodiments, the fitting connector **46** of a swaged pipe fitting **44** may be secured to a corresponding fitting body **48** via hot tooling, such as welding or brazing.

[0068] In any case, to facilitate sealing pipe segment tubing **22** therein, a swaged pipe fitting **44** may include fitting seals. The fitting seals of a swaged pipe fitting **44** may include one or more face seals **94**, which may be compressed between components of the swaged pipe fitting **44**. For example, a face seal **94A** of the swaged pipe fitting **44A** may be compressed between its fitting connector **46A** and its fitting body **48A**.

[0069] In addition to a face seal **94**, in some embodiments, the fitting seals of a swaged pipe fitting **44** may include one or more internal pressure sheath seals **95**, which may be compressed against the internal pressure sheath layer **26** of a pipe segment **20**, thereby sealing the internal pressure sheath layer **26** and, thus, block fluid flow between the pipe bore **32** and the tubing annulus **25** of the pipe segment **20**. For example, an internal pressure sheath seal **95A** of the swaged pipe fitting **44A** may be compressed against the internal pressure sheath layer **26** of the pipe segment tubing **22A** due to compression between the fitting body **48A** and the fitting connector **46A** of the swaged pipe fitting **44A**. To enable an internal pressure sheath seal **95** to be compressed against an outer surface **97** of the internal pressure sheath layer **26** of pipe segment tubing **22**, as in the depicted example, the outer sheath layer **28** and each intermediate layer **38** of the pipe segment tubing **22** may be cut back relative to the internal pressure sheath layer **26**, for example, while the internal pressure sheath layer **26** is cut back relative to the carcass layer **37** of the pipe segment tubing **22**.

[0070] Furthermore, in some embodiments, one or more fitting seals in a swaged pipe fitting **44** may be made from metal. For example, a fitting seal in the swaged pipe fitting **44** may be made from carbon steel, stainless steel, duplex stainless steel, super duplex stainless steel, or any combination thereof. However, in other embodiments, one or more fitting seals in a swaged pipe fitting **44** may be made from a non-metallic material. For example, in such embodiments,

a fitting seal in the swaged pipe fitting **44** may be made from a polymer, rubber, and/or plastic.

[0071] In any case, as described above, one or more intermediate layers **38** in a pipe segment **20** may define one or more annular gaps (e.g., fluid conduits and/or free space) **24** in its tubing annulus **25**. To facilitate venting the annulus **25** of pipe segment tubing **22**, as in the depicted example, in some embodiments, a swaged pipe fitting **44** may include one or more vent valves **96**. As in the depicted example, a vent valve **96** of a swaged pipe fitting **44** may be fluidly connected to the annulus **25** of pipe segment tubing **22** via a fluid path **98** formed through the fitting body **48** of the swaged pipe fitting **44**.

[0072] However, in other embodiments, a swaged pipe fitting **44** may not include a vent valve **96** or include more than one (e.g., two, three, or more) vent valve **96**. In other words, it should be appreciated that the various examples described in the present disclosure may or may not include a vent valve **96**. Additionally, as will be described in more detail below, in other embodiments, an internal pressure sheath seal **95** of a swaged pipe fitting **44** may have a different geometry, such as a J-shaped axial cross-section profile, and/or disposed under a fitting jacket **50** of the swaged pipe fitting **44**. Furthermore, in other embodiments, a swaged pipe fitting **44** may include a carcass ring—namely a carcass isolating ring, which electrically isolates the carcass layer **37** of pipe segment tubing **22**, or a carcass anchoring ring, which anchors the carcass layer **37** in the swaged pipe fitting **44**.

[0073] To help illustrate, a portion **42C** of a pipeline system **10**, which includes another example of a swaged pipe fitting **44C** and pipe segment tubing **22C**, is shown in FIG. **8**. Similar to FIG. **5**, as depicted, the swaged pipe fitting **44C** of FIG. **8** generally includes a fitting body **48C**, a fitting connector **46C**, a fitting jacket **50C**, which is shown in its swaged state, a support cylinder **74C**, and fitting seals—namely a face seal **94C** and an internal pressure sheath seal **95C**.

[0074] However, as depicted in FIG. **8**, the swaged pipe fitting **44C** includes a carcass anchoring ring **100C**, which is secured to the outer surface **101** of the carcass layer **37** of the pipe segment tubing **22C**. In some embodiments, the carcass anchoring ring **100** of a swaged pipe fitting **44** may be threaded and/or welded onto an outer surface of a corresponding carcass layer **37**, which is an interlocked metal layer. Thus, to anchor the carcass layer **37** in some embodiments, the carcass anchoring ring **100** may be made from metal, such as carbon steel, stainless steel, duplex stainless steel, super duplex stainless steel, or any combination thereof. Additionally, to enable a carcass anchoring ring **100** to be secured to the outer surface **101** of the carcass layer **37** of pipe segment tubing **22**, as in the depicted example, the internal pressure sheath layer **26** of the pipe segment tubing **22** may be cut back relative to the carcass layer **37**.

[0075] As depicted in FIG. **8**, the fitting connector **46C** of the swaged pipe fitting **44C** accommodates the carcass anchoring ring **100C**. Thus, the carcass anchoring ring **100C** may be secured to the carcass layer **37** of the pipe segment tubing **22C** before the fitting connector **46C** is secured to the fitting body **48C**. After the fitting connector **46C** is secured to the fitting body **48C**, the carcass anchoring ring **100C**, which is secured to the carcass layer **37** of the pipe segment tubing **22C**, may be trapped between the fitting connector **46C** and the internal pressure sheath layer **26** of the pipe

segment tubing 22C. Since the carcass layer 37 is anchored by the carcass anchoring ring 100C, in some embodiments, the support cylinder 74C may have a smooth, knurled, or serrated outer surface, for example, instead of threading. In any case, in this manner, a swaged pipe fitting 44 may separately anchor the carcass layer 37 of corresponding pipe segment tubing 22 in the swaged pipe fitting 44.

[0076] Nevertheless, in some embodiments, the swaged pipe fitting 44C may include one or more vent valves 96 and corresponding fluid paths 98 formed in its fitting body 48C. Additionally, in other embodiments, the swaged pipe fitting 44C may not include a support cylinder 74C, for example, when a support cylinder tool is used instead. Furthermore, in other embodiments, a swaged pipe fitting 44 may include a seal flange, which is secured between its fitting connector 46 and its fitting body 48, for example, to improve sealing integrity of the swaged pipe fitting 44. Moreover, in such embodiments, the swaged pipe fitting 44 may trap its carcass anchoring ring 100 between its fitting connector 46 and its seal flange, for example, to improve anchoring strength.

[0077] To help illustrate, a portion 42D of a pipeline system 10, which includes a further example of a swaged pipe fitting 44D and pipe segment tubing 22D, is shown in FIG. 9. Similar to FIG. 8, as depicted, the swaged pipe fitting 44D of FIG. 9 generally includes a fitting body 48D, a fitting connector 46D, a fitting jacket 50D, which is shown in its swaged state, a support cylinder 74D, an carcass anchoring ring 100D, and fitting seals—namely face seals 94D and an internal pressure sheath seal 95D.

[0078] However, as depicted in FIG. 9, the swaged pipe fitting 44D includes a seal flange 102, which is secured between its fitting connector 46D and its fitting body 48D, for example, via one or more threaded fasteners 92, such as a bolt or a screw. As in the depicted example, the seal flange 102 of a swaged pipe fitting 44 may be secured to a corresponding fitting body 48D such that a face seal 94 is compressed therebetween and secured to a corresponding fitting connector 46 such that another face seal 94 is compressed therebetween. Additionally, as in the depicted example, the seal flange 102 of a swaged pipe fitting 44 may be secured to a corresponding fitting body 48 such that an internal pressure sheath seal 95 is compressed against the internal pressure sheath layer 26 of pipe segment tubing 22.

[0079] Nevertheless, similar to FIG. 8, as depicted in FIG. 9, the fitting connector 46D accommodates the carcass anchoring ring 100D. However, as depicted in FIG. 9, after the fitting connector 46D is secured to the seal flange 102, the carcass anchoring ring 100D is trapped between the fitting connector 46D and the seal flange 102, for example, instead of between the fitting connector 46D and the internal pressure sheath layer 26 of the pipe segment tubing 22D. Since the seal flange 102 is generally made from material, such as metal, that is more rigid than the internal pressure sheath layer 26 of pipe segment tubing 22, at least in some instances, implementing and/or deploying a swaged pipe fitting 44 in this manner may improve the strength with which the carcass layer 37 of the pipe segment tubing 22 is anchored in the swaged pipe fitting 44. Additionally, since the carcass layer 37 is anchored by the carcass anchoring ring 100D, in some embodiments, the support cylinder 74D may have a smooth, knurled or serrated outer surface, for example, instead of threading.

[0080] In any case, in some embodiments, the swaged pipe fitting 44D may include one or more vent valves 96 and

corresponding fluid paths 98 formed in its fitting body 48D. Additionally, in other embodiments, the swaged pipe fitting 44D may not include a support cylinder 74C, for example, when a support cylinder tool is used instead. Furthermore, in other embodiments, the seal flange 102 may be secured to the fitting body 48D via a first one or more threaded fasteners 92 while the fitting connector 46D is secured to the seal flange 102 via a second one or more threaded fasteners 92. Moreover, in other embodiments, the carcass anchoring ring 100 of a swaged pipe fitting 44 may be disposed under a fitting jacket 50 of the swaged pipe fitting 44. Additionally, as mentioned above, in other embodiments, an internal pressure sheath seal 95 of a swaged pipe fitting 44 may have a different geometry, such as a J-shaped axial cross-section profile.

[0081] To help illustrate, a portion 42E of a pipeline system 10, which includes another example of a swaged pipe fitting 44E and pipe segment tubing 22E, is shown in FIG. 10. Similar to FIG. 8, as depicted, the swaged pipe fitting 44E of FIG. 10 generally includes a fitting body 48E, a fitting connector 46E, a fitting jacket 50E, which is shown in its unswaged state, a support cylinder 74E, a carcass anchoring ring 100E, and fitting seals—namely a face seal 94E and an internal pressure sheath seal 95E.

[0082] However, as depicted in FIG. 10, the carcass anchoring ring 100E of the swaged pipe fitting 44E is disposed under its fitting jacket 50E. Nevertheless, as depicted, the carcass anchoring ring 100E is secured to the outer surface 101 of the carcass layer 37 of the pipe segment tubing 22E. For example, the carcass anchoring ring 100E may be secured to the carcass layer 37 of the pipe segment tubing 22 at least in part by welding and/or threading the carcass anchoring ring 100E to the outer surface 101 of the carcass layer 37.

[0083] Moreover, as depicted in FIG. 10, the internal pressure sheath seal 95E of the swaged pipe fitting 44E is disposed under the fitting jacket 50E and has a J-shaped axial cross-section profile, for example, instead of a wedge-shaped axial cross-section profile. In other words, as depicted, the internal pressure sheath seal 95E includes a hook portion 104 and a leg portion 106. The hook portion 104 of the internal pressure sheath seal 95E matingly interlocks with a retainer lip 108 on the carcass anchoring ring 100E to secure the internal pressure sheath seal 95E to the carcass anchoring ring 100E.

[0084] Additionally, as depicted, the leg portion 106 of the internal pressure sheath seal 95E slants against the pipe segment tubing 22E. To enable an internal pressure sheath seal 95 to slant against pipe segment tubing 22, as in the depicted example, the outer sheath layer 28 of the pipe segment tubing 22 may be cut back relative to each intermediate layer 38 of the pipe segment tubing 22 while each intermediate layer 38 may be cut back relative to the internal pressure sheath layer 26 of the pipe segment tubing 22. Since disposed under the fitting jacket 50E, when the fitting jacket 50E is swaged, the internal pressure sheath seal 95E may be compressed radially inward against the internal pressure sheath layer 26 of the pipe segment tubing 22E, thereby sealing the internal pressure sheath layer 26.

[0085] In other embodiments, the swaged pipe fitting 44E may include one or more vent valves 96 and corresponding fluid paths 98 formed in its fitting body 48E. Additionally, in other embodiments, the swaged pipe fitting 44E may not include a support cylinder 74C, for example, when a support

cylinder tool is used instead. Furthermore, in other embodiments, the fitting body 48 of a swaged pipe fitting 44 may be integrated with a corresponding fitting connector 46, such as a flange. Furthermore, in other embodiments, an internal pressure sheath seal 95 of a swaged pipe fitting 44 may have a different geometry, such as a U-shaped axial cross-section profile, and/or be compressed between the fitting body 48 and the support cylinder 74 of the swaged pipe fitting 44.

[0086] To help illustrate, a portion 42F of a pipeline system 10, which includes a further example of a swaged pipe fitting 44F and pipe segment tubing 22F, is shown in FIG. 11. Similar to FIG. 5, as depicted, the swaged pipe fitting 44F of FIG. 11 generally includes a fitting body 48F, a fitting connector 46F, a fitting jacket 50F, which is shown in its swaged state, a support cylinder 74F, and fitting seals—namely face seals 94F and an internal pressure sheath seal 95F.

[0087] However, as depicted in FIG. 11, the internal pressure sheath seal 95F of the swaged pipe fitting 44F has a U-shaped axial cross-section profile, for example, instead of a wedge-shaped axial cross-section profile or a J-shaped axial cross-section profile. Additionally, as depicted, the support cylinder 74F of the swaged pipe fitting 44F includes a flange 110, which extends radially outward, for example, instead of into the fitting connector 46F. As depicted, the internal pressure sheath seal 95F is compressed against the internal pressure sheath layer 26 of the pipe segment tubing 22F due to compression between the flange 110 of the support cylinder 74D and the fitting body 48F of the swaged pipe fitting 44F, for example, instead of due to compression directly between the fitting body 48F and the fitting connector 46F of the swaged pipe fitting 44F.

[0088] Additionally, as in the depicted example, to anchor the carcass layer 37 of pipe segment tubing 22 in a swaged pipe fitting 44, in some embodiments, a support cylinder 74 of the swaged pipe fitting 44 may include threading 111 that extends outwardly along its outer surface 113. As in the depicted example, the threading 111 on the support cylinder 74 may threadingly engage an inner surface 115 of the carcass layer 37 of pipe segment tubing 22, thereby securing the support cylinder 74 to the carcass layer 37. In other words, in such embodiments, the support cylinder 74 may be disposed under the carcass layer 37 of the pipe segment tubing 22 at least in part by rotating the support cylinder 74 relative to the carcass layer 37. In fact, due to the threading engagement, internal pressure sheath seal 95F may be activated at least in part by securing the support cylinder 74F to the carcass layer 37 of the pipe segment tubing 22F.

[0089] However, in other embodiments, the support cylinder 74F of the swaged pipe fitting 44F may have a smooth, serrated or knurled outer surface. Thus, in such embodiments, the internal pressure sheath seal 95F may be activated at least in part by securing the fitting connector 46F to the fitting body 48F, for example, due to the flange 110 of the support cylinder 74F being disposed therebetween.

[0090] In any case, as in the depicted example, to improve securement strength, in some embodiments, a swaged pipe fitting 44 may include teeth (e.g., serrations) 109 that extend radially inward from the inner surface 52 of its fitting jacket 50. Additionally, as in the depicted example, in addition to a face seal 94 compressed between its fitting connector 46 and its fitting body 48, in some embodiments, a swaged pipe fitting 44 may include another face seal 94 disposed between the fitting body 48 and a fitting jacket 50.

[0091] In other embodiments, the swaged pipe fitting 44F may include one or more vent valves 96 and corresponding fluid paths 98 formed in its fitting body 48E. Additionally, in other embodiments, the internal pressure sheath seal 95F may have a wedge-shaped axial cross-section profile, for example, instead of a U-shaped axial cross-section profile. Furthermore, in other embodiments, the support cylinder 74 of a swaged pipe fitting 44 may be integrated with the fitting connector 46 of the swaged pipe fitting 44.

[0092] To help illustrate, a portion 42G of a pipeline system 10, which includes another example of a swaged pipe fitting 44G and pipe segment tubing 22G, is shown in FIG. 12. Similar to FIG. 5, as depicted, the swaged pipe fitting 44G of FIG. 12 generally includes a fitting body 48G, a fitting connector 46G, a fitting jacket 50G, which is shown in its swaged state, and fitting seals—namely a face seal 94G and an internal pressure sheath seal 95G.

[0093] However, as depicted in FIG. 12, a support cylinder feature 74G of the swaged pipe fitting 44G is integrated with its fitting connector 46G. In other words, to support pipe segment tubing 22 during swaging, in such embodiments, the fitting connector 46 of a swaged pipe fitting 44 may be inserted into the pipe segment tubing 22 before a fitting jacket 50 of the swaged pipe fitting 44 is swaged (e.g., conformally deformed) around the pipe segment tubing 22. Nevertheless, in some such embodiments, the fitting connector 46 may be secured to the fitting body 48 of the swaged pipe fitting 44 after the fitting jacket 50 is swaged around the pipe segment tubing 22.

[0094] In other embodiments, the swaged pipe fitting 44G may include one or more vent valves 96 and corresponding fluid paths 98 formed in its fitting body 48G. Additionally, in other embodiments, the support cylinder 74 of a swaged pipe fitting 44 may be integrated with the fitting body 48 of the swaged pipe fitting 44.

[0095] To help illustrate, a portion 42H of a pipeline system 10, which includes a further example of a swaged pipe fitting 44H and pipe segment tubing 22H, is shown in FIG. 13. Similar to FIG. 5, as depicted, the swaged pipe fitting 44H of FIG. 13 generally includes a fitting body 48H, a fitting connector 46H, a fitting jacket 50H, which is shown in its swaged state, and fitting seals—namely a face seal 94H and an internal pressure sheath seal 95H.

[0096] However, as depicted in FIG. 13, a support cylinder feature 74H of the swaged pipe fitting 44H is integrated with the fitting body 48H. In other words, to support pipe segment tubing 22 during swaging, in such embodiments, the fitting body 48 of a swaged pipe fitting 44 may be inserted into the pipe segment tubing 22 before a fitting jacket 50 of the swaged pipe fitting 44 is swaged (e.g., conformally deformed) around the pipe segment tubing 22. Additionally, as depicted, the support cylinder feature 74H includes a carcass support section 112H, which supports the carcass layer 37 of the pipe segment tubing 22H, and an internal pressure sheath support section 114H, which supports the internal pressure sheath layer 26 of the pipe segment tubing 22H. To enable the internal pressure sheath support section 114 of a swaged pipe fitting 44 to support the internal pressure sheath layer 26 of pipe segment tubing 22, as in the depicted example, the carcass layer 37 of the pipe segment tubing 22 may be cut back relative to the internal pressure sheath layer 26.

[0097] In fact, since internal pressure sheath support section 114H is disposed directly under the internal pressure

sheath layer 26, swaging the fitting jacket 50H around the pipe segment tubing 22H may compress the internal pressure sheath layer 26 against the internal pressure sheath support section 114H, thereby sealing the internal pressure sheath layer 26. To improve sealing integrity, in some embodiments, the swaged pipe fitting 44H may nevertheless include a discrete internal pressure sheath seal 95H, which may be compressed between the internal pressure sheath support section 114H and the internal pressure sheath layer 26. In some such embodiments, the discrete internal pressure sheath seal 95H may be an O-ring seal or a belt (e.g., flat) seal. However, in other embodiments, the discrete internal pressure sheath seal 95H may be obviated by the seal provided between the internal pressure sheath support section 114H and the internal pressure sheath layer 26 and, thus, not be included in the swaged pipe fitting 44H.

[0098] To anchor the carcass layer 37 in the swaged pipe fitting 44H, in some embodiments, the carcass support section 112H may include threading on its outer surface, for example, which threadingly engages an inner surface 115 of the carcass layer 37 of the pipe segment tubing 22H. Additionally, to anchor the pipe segment tubing 22H in the swaged pipe fitting 44H, in some embodiments, the internal pressure sheath support section 114H may include teeth on its inner surface, for example, which engages the inner surface 30 of the internal pressure sheath layer 26. However, in other embodiments, the carcass support section 112H may have a smooth outer surface, the internal pressure sheath support section 114H may have a smooth outer surface, or both.

[0099] In any case, in other embodiments, the swaged pipe fitting 44H may include one or more vent valves 96 and corresponding fluid paths 98 formed in its fitting body 48H. Additionally, to account for thickness difference, in some embodiments, the fitting jacket 50H may have a stepped geometry such that the portion of the fitting jacket 50H that overlaps with the carcass support section 112H may be thinner while the portion of the fitting jacket 50H that overlaps with the internal pressure sheath support section 114H may be thicker. Furthermore, in other embodiments, the fitting body 48 of a swaged pipe fitting 44 may be integrated with a corresponding fitting connector 46, such as a weldneck. Alternatively, in other embodiments, a swaged pipe fitting 44 may not include a fitting connector 46. Moreover, in other embodiments, the internal pressure sheath support section 114 and the carcass support section 112 of a swaged pipe fitting 44 may be separate components.

[0100] To help illustrate, a portion 42I of a pipeline system 10, which includes another example of a swaged pipe fitting 44I and pipe segment tubing 22I, is shown in FIG. 14. Similar to FIG. 13, as depicted, the swaged pipe fitting 44I of FIG. 14 generally includes a fitting body 48I, a fitting connector 46I, a fitting jacket 50I, which is shown in its swaged state, and fitting seals—namely a face seal 94I and an internal pressure sheath seal 95I.

[0101] However, as depicted in FIG. 14, the carcass support section 112I of the support cylinder feature 74I is implemented using a separate carcass support cylinder 116, for example, instead of being integrated with the internal pressure sheath support section 114I and the fitting body 48I of the swaged pipe fitting 44I. In other words, to support pipe segment tubing 22 during swaging, in such embodiments, the carcass support cylinder 116 of the swaged pipe fitting 44 may be inserted into the pipe segment tubing 22

followed by the fitting body 48 of the swaged pipe fitting 44 before a fitting jacket 50 of the swaged pipe fitting 44 is swaged (e.g., conformally deformed) around the pipe segment tubing 22. Nevertheless, similar to FIG. 13, to enable the internal pressure sheath support section 114I of the swaged pipe fitting 44I to support the internal pressure sheath layer 26 of the pipe segment tubing 22E, as depicted in FIG. 14, the carcass layer 37 of the pipe segment tubing 22E is cut back relative to the internal pressure sheath layer 26.

[0102] To improve sealing integrity, in some embodiments, the swaged pipe fitting 44I may nevertheless include a discrete internal pressure sheath seal 95I, which may be compressed between the internal pressure sheath support section 114I and the internal pressure sheath layer 26. In some such embodiments, the discrete internal pressure sheath seal 95I may be an O-ring seal or a belt (e.g., flat) seal. However, in other embodiments, the discrete internal pressure sheath seal 95I may be obviated by the seal provided between the internal pressure sheath support section 114I and the internal pressure sheath layer 26 and, thus, not be included in the swaged pipe fitting 44I.

[0103] In any case, to anchor the carcass layer 37 in the swaged pipe fitting 44I, in some embodiments, the carcass support cylinder 116 may include threading on its outer surface, for example, which threadingly engages an inner surface 115 of the carcass layer 37 of the pipe segment tubing 22I. Additionally, to anchoring the pipe segment tubing 22I in the swaged pipe fitting 44I, in some embodiments, the internal pressure sheath support section 114I may include teeth on its inner surface, for example, which engages the inner surface 30 of the internal pressure sheath layer 26. However, in other embodiments, the carcass support section 112I may have a smooth outer surface, the internal pressure sheath support section 114I may have a smooth outer surface, or both.

[0104] Additionally, in other embodiments, the swaged pipe fitting 44I may include one or more vent valves 96 and corresponding fluid paths 98 formed in its fitting body 48I. Furthermore, to account for thickness difference, in some embodiments, the fitting jacket 50I may have a stepped geometry such that the portion of the fitting jacket 50I that overlaps with the carcass support section 112I may be thinner while the portion of the fitting jacket 50I that overlaps with the internal pressure sheath support section 114I is thicker. Moreover, although support cylinders 74 disposed under the carcass layer 37 of pipe segment tubing 22 are described above, in other embodiments, a swaged pipe fitting 44 may include a support cylinder 74, which is disposed around (e.g., over) the carcass layer 37 of pipe segment tubing 22.

[0105] To help illustrate, a portion 42J of a pipeline system 10, which includes a further example of a swaged pipe fitting 44J and pipe segment tubing 22J, is shown in FIG. 15. Similar to FIG. 5, as depicted, the swaged pipe fitting 44J of FIG. 15 generally includes a fitting body 48J, a fitting connector 46J, a fitting jacket 50J, which is shown in its swaged state, a support cylinder 74J, and face seals 94J.

[0106] However, as depicted in FIG. 15, the support cylinder 74J of the swaged pipe fitting 44J is disposed around (e.g., over) the carcass layer 37 of the pipe segment tubing 22J, for example, instead of under the carcass layer 37. In other words, the support cylinder 74J may be inserted (e.g., disposed) between the carcass layer 37 and the internal

pressure sheath layer 26 of the pipe segment tubing 22J. To facilitate insertion, as in the depicted example, in some embodiments, the support cylinder 74 of a swaged pipe fitting 44 may include a tapered end 118.

[0107] Additionally, as depicted, inserting the support cylinder 74J under the internal pressure sheath layer 26 of the pipe segment tubing 22J may produce a flared section 119 in the internal pressure sheath layer 26 and a flared section 120 in each intermediate layer 38 of the pipe segment tubing 22J. As depicted, a flared section 121 in the outer sheath layer 28 of the pipe segment tubing 22J also overlaps with the support cylinder 74J. In some embodiments, the flared section 121 in the outer sheath layer 28 may also be produced by insertion of the support cylinder 74J under the internal pressure sheath layer 26.

[0108] However, in other embodiments, the flared section 121 in the outer sheath layer 28 of the pipe segment tubing 22J may be produced using a separate installation sleeve. In such embodiment, before the support cylinder 74J is inserted, the installation sleeve may be inserted (e.g., disposed) between the outer sheath layer 28 and an intermediate layer 38 of the pipe segment tubing 22J to produce the flared section 121 in the outer sheath layer 28. The flared section 121 of the outer sheath layer 28 may then be cut off from a remaining portion of the outer sheath layer 28 and the installation sleeve may be removed to enable the internal pressure sheath layer 26 and each intermediate layer 38 of the pipe segment tubing 22J to expand radially outward to produce flared sections therein when the support cylinder 74J is inserted under the internal pressure sheath layer 26. Before the fitting jacket 50J is disposed around the pipe segment tubing 22J, in such embodiments, the flared section 121 of the outer sheath layer 28 may be reattached (e.g., poly welded) to the remaining portion of the outer sheath layer 28. In fact, to improve fitting integrity, as in the depicted example, the fitting jacket 50 of a swaged pipe fitting 44 may be implemented to extend beyond a flared section 121 in the outer sheath layer 28 of corresponding pipe segment tubing 22 and, thus, beyond the location the flared section 121 of the outer sheath layer 28 is reattached to the remaining portion of the outer sheath layer 28. However, in other embodiments, the fitting jacket 50J may not extend beyond the flared section 121 in the outer sheath layer 28.

[0109] However, in other embodiments, the swaged pipe fitting 44J may include one or more vent valves 96 and corresponding fluid paths 98 formed in its fitting body 48J. Additionally, in other embodiments, the swaged pipe fitting 44J may anchor the carcass layer 37 of pipe segment tubing 22 therein via a carcass ring 100 similar to FIG. 8 or FIG. 9. Furthermore, as mentioned above, in other embodiments, a swaged pipe fitting 44 may not include a support cylinder 74.

[0110] To help illustrate, a portion 42K of a pipeline system 10, which includes another example of a swaged pipe fitting 44K and pipe segment tubing 22K, is shown in FIG. 16. Similar to FIG. 5, as depicted in FIG. 16, the swaged pipe fitting 44K generally includes a fitting body 48K, a fitting connector 46K, a fitting jacket 50K, which is shown in its swaged state, a vent valve 96, and fitting seals—namely a face seal 94K and an internal pressure sheath seal 95K.

[0111] However, as depicted in FIG. 16, the swaged pipe fitting 44K does not include a permanent support cylinder 74. Instead, in such embodiments, a support cylinder tool

may be used to support pipe segment tubing 22 during swaging. In such embodiments, the support cylinder tool may be inserted into the pipe segment tubing 22 while in a contracted state and, subsequently, transitioned to an expanded state such that an outer surface of the support cylinder tool expands (e.g., is compressed) against and, thus, directly abuts an inner surface of the pipe segment tubing 22. After swaging, the support cylinder tool may then be transitioned from its expanded state back to its contracted state and withdrawn from within the pipe segment tubing 22. In other words, in such embodiments, the support cylinder tool may act as a temporary support cylinder 74. For example, in some such embodiments, the support cylinder tool used with a swaged pipe fitting 44 may be an inflatable packer. However, in other such embodiments, the support cylinder tool used with a swaged pipe fitting 44 may be a special-purpose tool.

[0112] To help illustrate, an example of a special-purpose support cylinder tool 122 is shown in FIG. 17. As depicted, the support cylinder tool 122 generally includes a threaded shaft 124, multiple support cylinder sections 126 disposed circumferentially around the threaded shaft 124, metallic elastic bands 128 disposed circumferentially around the support cylinder sections 126, an outer stationary nut 130 disposed around the threaded shaft 124, and an activation nut 132 disposed around the threaded shaft 124. Although partially obfuscated from view, the support cylinder tool 122 includes an activation collar 134, which is disposed between the support cylinder sections 126 and the activation nut 132, as well as a stationary collar, which is disposed between the outer stationary nut 130 and the support cylinder sections 126.

[0113] To more clearly illustrate, an example of a support cylinder tool 122 disposed within pipe segment tubing 22L is shown in FIG. 18. As depicted, open space 136 is present between an inner surface 138 of the pipe segment tubing 22L and an outer surface 140 of the support cylinder sections 126 of the support cylinder tool 122. In other words, in FIG. 18, the support cylinder tool 122 is shown in a contracted state, which enables the support cylinder tool 122 to be relatively freely inserted into and/or withdrawn from the pipe segment tubing 22L.

[0114] To facilitate transitioning a support cylinder tool 122 between its contracted state and its expanded state and, thus, controlling its activation state, as depicted, the activation collar 134 of the support cylinder tool 122 has a wedge-shaped axial cross-section profile and, thus, a conical outer surface 142 while the stationary collar 144 also has a wedge-shaped axial cross-section profile and, thus, a conical outer surface 146. Additionally, as depicted, a first end 148 of the support cylinder sections 126 has a conical inner surface (e.g., female taper) 150, which can slide along the conical outer surface (e.g., male taper) 146 of the stationary collar 144, while the conical outer surface (e.g., male taper) 142 of the activation collar 134 can slide along a conical inner surface (e.g., female taper) 152 at a second (e.g., opposite) end 154 of the support cylinder sections 126. Furthermore, as depicted, the stationary collar 144 is trapped between and, thus, held in place on the threaded shaft 124 of the support cylinder tool 122 via an outer stationary nut 130 and an inner stationary nut 156.

[0115] Thus, to transition the support cylinder tool 122 from its contacted state toward its expanded state, the activation nut 132 may be rotated on the threaded shaft 124

to push more of the activation collar 134 under the support cylinder sections 126, thereby pushing the support cylinder sections 126 radially outward. To support the pipe segment tubing 22L during swaging, the activation collar 134 may continue to be pushed under the support cylinder sections 126 until the outer surface 140 of the support cylinder sections 126 expands against the inner surface 138 of the pipe segment tubing 22L. On the other hand, to transition the support cylinder tool 122 from its expanded state toward its contracted state, the activation nut 132 may be rotated on the threaded shaft in an opposite direction to enable the pipe segment tubing 22L to push more of the activation collar 134 out from under the support cylinder sections 126 while contracting radially inward against the support cylinder sections 126.

[0116] In other embodiments, a support cylinder tool 122 used with a swaged pipe fitting 44 may include fewer than two (e.g., one) or more than two (e.g., three, four, or more) metallic elastic bands 128 disposed around its support cylinder sections 126. Furthermore, in other embodiments, a support cylinder tool 122 used with a swaged pipe fitting 44 may include fewer than three (e.g., two) support cylinder sections 126 or more than three (e.g., four, five, or more) support cylinder sections 126. In any case, in this manner, a support cylinder tool 122 may be implemented and/or operated to support pipe segment tubing 22 during a swaging operation used to secure a swaged pipe fitting 44 to the pipe segment tubing 22.

[0117] Returning to the swaged pipe fitting 44K of FIG. 16, similar to FIG. 5, after the fitting jacket 50K is swaged around the pipe segment tubing 22K, the fitting connector 46K may be secured to the fitting body 48K, for example, after a support cylinder tool 122 is removed from within the pipe segment tubing 22K. As in the depicted example, in some embodiments, a swaged pipe fitting 44 may include a carcass isolating ring 100, which electrically isolates the carcass layer 37 of corresponding pipe segment tubing 22 from the remainder of the swaged pipe fitting 44. To facilitate electrically isolating the carcass layer 37, the carcass isolating ring 100K of the swaged pipe fitting 44K may be made from an electrical insulative material, such as a polymer and/or plastic.

[0118] Furthermore, as in the depicted example, in some embodiments, a swaged pipe fitting 44 may include a spacer ring 182. As depicted in the depicted example, the spacer ring 182 may directly abut the internal pressure sheath layer 26 of pipe segment tubing 22 and, thus, supports the internal pressure sheath layer 26, for example, to reduce the likelihood of a blow through in the internal pressure sheath layer 26 occurring within the swaged pipe fitting 44. In other words, the spacer ring 182 may bridge the structural support provided to the internal pressure sheath layer 26 by the one or more intermediate (e.g., reinforcement) layers 38 of the pipe segment tubing 22 and the structural support provided by the fitting body 48 of the swaged pipe fitting 44.

[0119] Additionally, as in the depicted example, the spacer ring 182 in a swaged pipe fitting 44 may directly abut an intermediate (e.g., reinforcement) layer 38 in the annulus 25 of pipe segment tubing 22, for example, to enable the swaged pipe fitting 44 to provide electrical continuity and, thus, cathodic protection to the intermediate layer 38. To provide electrical continuity, the spacer ring 182 may be made from the same type of metal as the intermediate layer 38 of the pipe segment tubing 22K. For example, the spacer

ring 182 and the intermediate layer 38 may both be made of carbon steel while the fitting body 48K is made of stainless steel. Moreover, to facilitate providing cathodic protection in a swaged pipe fitting 44, as in the depicted example, an electrical terminal 184 may be connected to the spacer ring 182 of the swaged pipe fitting 44 through its fitting body 48, for example, to enable an anode to be electrically connected to the intermediate layer 38 of corresponding pipe segment tubing 22.

[0120] In fact, as in the depicted example, to facilitate improving electrical connection with and/or structural support of corresponding pipe segment tubing 22, in some embodiments, the spacer ring 182 of a swaged pipe fitting 44 may include an extension 186, which is disposed under the intermediate layer 38. In other words, as in the depicted example, the extension 186 on the spacer ring 182 may be inserted (e.g., disposed) between the intermediate layer 38 and the internal pressure sheath layer 26 of the pipe segment tubing 22. Furthermore, as in the depicted example, to enable the annulus 25 of pipe segment tubing 22 to be vented, in some embodiments, a fluid path 188 may be formed through the spacer ring 182 of a swaged pipe fitting 44 such that the fluid path 188 can be fluidly connected to another fluid path 98 that is formed in the fitting body 48 of the swaged pipe fitting 44 and fluidly connected to a vent valve 96.

[0121] However, in other embodiments, the swaged pipe fitting 44K may not include a vent valve 96 or include more than one (e.g., two, three, or more) vent valves 96. Additionally, in other embodiments, the swaged pipe fitting 44K may not include a spacer ring 182 or an electrical terminal 184. Alternatively, in other embodiments, the spacer ring 182 of the swaged pipe fitting 44K may not include an extension 186. Furthermore, in other embodiments, the swaged pipe fitting 44K may not include a carcass isolating ring 100K. In any case, in this manner, a swaged pipe fitting 44 may be implemented and/or deployed (e.g., installed) at pipe segment tubing 22.

[0122] To help further illustrate, an example of a process 190 for installing a swaged pipe fitting 44 at a pipe segment 20 is described in FIG. 19. Generally, the process 190 includes cutting back a tubing layer of a pipe segment (process block 192), disposing a support cylinder directly adjacent to an innermost layer of the pipe segment (process block 194), and disposing a fitting jacket circumferentially around an outer sheath layer of the pipe segment (process block 196). Additionally, the process 190 generally includes conformally deforming the fitting jacket around the pipe segment (process block 198) and securing a fitting connector to a fitting body that is secured to the fitting jacket (process block 202).

[0123] In other embodiments, a process 190 for installing a swaged pipe fitting 44 at a pipe segment 20 may include one or more additional blocks and/or omit one or more of the depicted blocks. For example, some embodiments of the process 190 may include reattaching a cut back portion of an outer sheath layer of the pipe segment to a remaining portion of the outer sheath layer (process block 204) while other embodiments of the process 190 do not. As another example, some embodiments of the process 190 may include disposing a grab sleeve between an internal pressure sheath layer and an intermediate layer of the pipe segment (process block 206) while other embodiments of the process 190 do not. As a further example, some embodiments of the process 190

may include disposing a spacer ring directly adjacent to the intermediate layer of the pipe segment (process block 208) while other embodiments of the process do not.

[0124] As another example, some embodiments of the process 190 may include disposing an internal pressure sheath seal around the internal pressure sheath layer of the pipe segment (process block 209) while other embodiments of the process 190 do not. As a further example, some embodiments of the process 190 may include securing a seal flange to the fitting body (process block 210) while other embodiments of the process 190 do not. As another example, some embodiments of the process 190 may include securing a carcass ring to a carcass layer of the pipe segment (process block 212) while other embodiments of the process 190 do not. As a further example, some embodiments of the process 190 may include removing a support cylinder tool from the pipe segment (process block 214) while other embodiments of the process 190 do not. Moreover, in other embodiments, one or more of the depicted blocks may be performed in a different order, for example, such that the fitting jacket is disposed around the outer sheath layer of the pipe segment before the support cylinder is disposed directly adjacent to the innermost layer of the pipe segment.

[0125] In any case, as described above, one or more tubing layers of a pipe segment 20 at which a swaged pipe fitting 44 is to be deployed may be cut back. As such, deploying a swaged pipe fitting 44 at a pipe segment 20 may generally include cutting back one or more tubing layers of the pipe segment 20 (process block 192). As described with regard to FIGS. 5 and 8-12, in some embodiments, the outer sheath layer 28 and each intermediate layer 38 of the pipe segment 20 may be cut back relative to the internal pressure sheath layer 26 of the pipe segment 20, for example, to enable an internal pressure sheath seal 95 of the swaged pipe fitting 44 to be compressed against the outer surface 97 of the internal pressure sheath layer 26 (process block 216).

[0126] Additionally, as described above, in some embodiments, a swaged pipe fitting 44 may include a carcass ring 100, which is secured to the carcass layer 37 of a pipe segment 20 to anchor the carcass layer 37 in the swaged pipe fitting 44. In particular, as described above with regard to FIGS. 8-10, the carcass ring 100 may be secured (e.g., welded and/or threaded) to the outer surface 101 of the carcass layer 37. As described above, to enable the carcass ring 100 to be secured to the outer surface 101 of the carcass layer 37, in such embodiments, the internal pressure sheath layer 26 of the pipe segment 20 may be cut back relative to the carcass layer 37 (process block 218).

[0127] Furthermore, as described with regard to FIGS. 10 and 15, in some embodiments, the outer sheath layer 28 of the pipe segment 20 may be cut back relative to an intermediate layer 38 of the pipe segment 20 (process block 220). In particular, as described with regard to FIG. 10, in some such embodiments, the outer sheath layer 28 may be cut back relative to the intermediate layer 38 to enable the leg portion 106 of an internal pressure sheath seal 95, which has a J-shaped axial cross-section profile, to slant against the tubing 22 of the pipe segment 20. Alternatively, as described with regard to FIG. 15, in some such embodiments, the cutoff portion of the outer sheath layer 28 may be a flared section 121, for example, which may be produced by inserting a temporary installation sleeve under the outer sheath layer 28. Moreover, as described with regard to FIGS. 13 and 14, in some embodiments, the carcass layer 37 of the

pipe segment 20 may be cut back relative to the internal pressure sheath layer 26 of the pipe segment 20, for example, to enable an internal pressure sheath seal 95 of a swaged pipe fitting 44 to be compressed against the inner surface 30 of the internal pressure sheath layer 26 and/or the swaged pipe fitting 44 to support the internal pressure sheath layer 26 during a swaging operation (process block 222).

[0128] In any case, as described above, to support tubing 22 of a pipe segment 20 while a swaged pipe fitting 44 is being swaged thereto, a support cylinder 74 may be disposed directly adjacent to the innermost (e.g., carcass or internal pressure sheath) layer of the pipe segment 20. As such, deploying a swaged pipe fitting 44 at a pipe segment 20 may generally include disposing a support cylinder 74 directly adjacent to (e.g., under or over) the innermost layer of the pipe segment 20 (process block 194). As described above, in some embodiments, the support cylinder 74 may be a component (e.g., feature) of the swaged pipe fitting 44.

[0129] More specifically, as described above with regard to FIGS. 5 and 8-14, the support cylinder 74 of a swaged pipe fitting 44 may be disposed under (e.g., within) the carcass layer 37 of a corresponding pipe segment 20 (process block 224). As described with regard to FIG. 12, in some such embodiments, a support cylinder feature of a swaged pipe fitting 44 may be integrated with its fitting connector 46 and, thus, disposing the support cylinder 74 under the carcass layer 37 may include inserting the fitting connector 46 under the carcass layer 37 of the pipe segment 20. Alternatively, as described above with regard to FIGS. 13 and 14, a support cylinder feature of a swaged pipe fitting 44 may be integrated with its fitting body 48 and, thus, disposing the support cylinder 74 under the carcass layer 37 may include inserting the fitting body 48 under the carcass layer 37 of the pipe segment 20.

[0130] However, as described above with regard to FIG. 15, the support cylinder 74 of a swaged pipe fitting 44 may be inserted between the carcass layer 37 and the internal pressure sheath layer 26 of a corresponding pipe segment 20 (process block 226). In other words, in such embodiments, the support cylinder 74 of the swaged pipe fitting 44 may be disposed under (e.g., within) the internal pressure sheath layer 26 and each intermediate layer 38 of the pipe segment 20 to produce a flared section 119 along the internal pressure sheath layer 26 and flared sections 120 along each intermediate layer 38. In such embodiments, the cut back portion (e.g., flared section 121) of the outer sheath layer 28 may then be reattached (e.g., poly welded) back to the remaining portion of the outer sheath layer 28 to cover the flared section 120 in each intermediate layer 38 and the flared section 119 in the internal pressure sheath layer 26 (process block 204).

[0131] However, as described above, in other embodiments, a swaged pipe fitting 44 may not include a support cylinder 74. Instead, in such embodiments, a support cylinder tool 122 may be used to temporarily support the tubing 22 of a pipe segment 20 while the swaged pipe fitting 44 is being swaged thereto. In particular, the support cylinder tool 122 may be inserted into the pipe bore 32 of the pipe segment 20 while in its contracted state and, subsequently, transitioned from its contracted state to its expanded state such that the outer surface 140 of its support cylinder sections 126 of the support cylinder tool 122 expands against the inner surface of an innermost layer of the pipe segment 20 (process block 228). For example, the support

cylinder tool 122 may be operated to transition from its contracted state to its expanded state at least in part by rotating an activation nut 132 to push more of a corresponding activation collar 134 under the support cylinder sections 126 of the support cylinder tool 122.

[0132] To facilitate securing a swaged pipe fitting 44 to a pipe segment 20, a fitting jacket 50 of the swaged pipe fitting 44 may be disposed circumferentially around the outer sheath layer 28 of the pipe segment 20 (process block 196). As described above, a fitting jacket 50 of a swaged pipe fitting 44 may be secured (e.g., welded) to the fitting body 48 of the swaged pipe fitting 44. As such, disposing the fitting jacket 50 of a swaged pipe fitting 44 circumferentially around the outer sheath layer 28 of a pipe segment 20 may include disposing the fitting body 48 of the swaged pipe fitting 44 adjacent to the pipe segment 20 (process block 236).

[0133] However, in some embodiments, the fitting body 48 of a swaged pipe fitting 44 may be made from a different type of metal as compared to an intermediate layer 38 of a corresponding pipe segment 20. For example, the fitting body 48 may be made of stainless steel while solid material in the intermediate layer 38 is made of carbon steel. To facilitate providing electrical continuity (e.g., to provide cathodic protection) to the intermediate layer 38, in some such embodiments, a swaged pipe fitting 44 may include a spacer ring 182, which is made from the same type of metal as the intermediate layer 38 of the pipe segment 20 and can be disposed directly adjacent to the intermediate layer 38 of the pipe segment 20. Thus, in such embodiments, deploying the swaged pipe fitting 44 at a pipe segment 20 may include disposing a spacer ring 182 directly adjacent to an intermediate layer 38 of the pipe segment 20, for example, at least in part by inserting an extension 186 on the spacer ring 182 under the intermediate layer 38 (process block 208). To bridge the gap between structural support provided to the internal pressure sheath layer 26 of the pipe segment 20 by the fitting body 48 of the swaged pipe fitting 44 and the structural support provided by one or more reinforcement layers 34 of the pipe segment 20, the spacer ring 182 may be disposed directly adjacent to the internal pressure sheath layer 26, for example, at least in part by inserting an extension 186 on the spacer ring 182 between the internal pressure sheath layer 26 and the one or more reinforcement layers 34 (process block 208).

[0134] The fitting jacket 50 of the swaged pipe fitting 44 may then be conformally deformed (e.g., swaged) around the tubing 22 of the pipe segment 20 such that the inner surface 52 of the fitting jacket 50 engages the outer surface 54 of the pipe segment tubing 22 and, thus, facilitates securing the swaged pipe fitting 44 to the pipe segment 20 as well as sealing the pipe segment tubing 22 within the swaged pipe fitting 44 (process block 198). In some embodiments, a fitting jacket 50 of a swaged pipe fitting 44 may be swaged using a swage machine 56. As described above, a swage machine 56 may generally include a grab plate 62, which may facilitate securing the swage machine 56 to the fitting body 48 of a swaged pipe fitting 44, for example, via a grab attachment 66 that has an L-shaped axial cross-section profile. Furthermore, as described above, a swage machine 56 may generally include a die plate 64, which may enable a set of die segments 68 to be loaded in the swage machine 56 such that the set of die segments 68 compress a fitting jacket 50 of a swaged pipe fitting 44 inwardly in a

radial direction 72 when moved over the fitting jacket 50 in an axial direction 70. Thus, in such embodiments, conformally deforming the fitting jacket 50 of a swaged pipe fitting 44 around a pipe segment 20 may include securing a grab plate 62 of a swage machine 56 to the fitting body 48 of the swaged pipe fitting 44 (process block 238) and moving a die plate 64 of the swage machine 56 over the fitting jacket 50 (process block 240).

[0135] To improve securement (e.g., anchoring) of an intermediate layer 38 of a pipe segment 20 therein, as described above, in some embodiments, a swaged pipe fitting 44 may include a grab sleeve 82, which may be disposed between the internal pressure sheath layer 26 and the intermediate layer 38 of the pipe segment 20. In such embodiments, deploying the swaged pipe fitting 44 at a pipe segment 20 may include disposing a grab sleeve 82 between the internal pressure sheath layer 26 and an intermediate layer 38 of the pipe segment 20 before a fitting jacket 50 of the swaged pipe fitting 44 is disposed around the outer sheath layer 28 of the pipe segment 20 (process block 206). The grab sleeve 82 may include a slit 84 that enables the grab sleeve 82 to grab onto the internal pressure sheath layer 26 when the fitting jacket 50 is swaged such that the intermediate layer 38 of the pipe segment 20 is compressed between the grab sleeve 82 and the fitting jacket 50 and, thus, anchored in the swaged pipe fitting 44. Additionally or alternatively, swaging a fitting jacket 50 of a swaged pipe fitting 44 may compress one or more intermediate (e.g., reinforcement) layers 38 of a corresponding pipe segment 20 between the fitting jacket 50 and a support cylinder 74 of the swaged pipe fitting 44, thereby anchoring the one or more intermediate layers 38 in the swaged pipe fitting 44.

[0136] In any case, as described above, in some embodiments, a support cylinder tool 122 may be temporarily used to support the tubing 22 of a pipe segment 20 during a swaging operation. Thus, in such embodiments, after conformally deforming the fitting jacket 50 of the swaged pipe fitting 44, the support cylinder tool 122 may be removed from within the pipe segment 20 (process block 214). As described above, in such embodiments, the support cylinder tool 122 may be operated to transition from its expanded state to its contracted state and withdrawn from within the pipe segment 20 while in its contracted state (process block 250). The support cylinder tool 122 may be operated to transition from its expanded state to its contracted state at least in part by rotating an activation nut 132 to enable the pipe segment 20 to push more of a corresponding activation collar 134 out from under the support cylinder sections 126 while contracting radially inward against the support cylinder sections 126.

[0137] Furthermore, as described, in some embodiments, an internal pressure sheath seal 95 of a swaged pipe fitting 44 may be disposed under a fitting jacket 50 of the swaged pipe fitting 44. In such embodiments, the internal pressure sheath seal 95 may have a J-shaped axial cross-section profile that includes a hook portion 104, which interlocks with a carcass ring 100 of the swaged pipe fitting 44, and a leg portion 106, which may slant against the tubing 22 of a pipe segment 20. Thus, when the fitting jacket 50 is conformally deformed around the pipe segment tubing 22, in such embodiments, the internal pressure sheath seal 95 may be compressed against the pipe segment tubing 22, thereby activating the internal pressure sheath seal 95 (process block 242).

[0138] However, as described above, in other embodiments, an internal pressure sheath seal 95 of a swaged pipe fitting 44 may be compressed against the fitting body 48 of the swaged pipe fitting 44. Thus, in such embodiments, installing the swaged pipe fitting 44 to a pipe segment 20 may include disposing an internal pressure sheath seal 95 around the internal pressure sheath layer 26 of the pipe segment 20 after (e.g., behind) the fitting body 48 of the swaged pipe fitting 44 (process block 209). In some such embodiments, the internal pressure sheath seal 95 may be compressed between the fitting body 48 and a seal flange 102 of the swaged pipe fitting 44.

[0139] In other words, in such embodiments, installing the swaged pipe fitting 44 to a pipe segment 20 may include securing a seal flange 102 to the fitting body 48 of the swaged pipe fitting 44 (process block 210), for example, such that a corresponding internal pressure sheath seal 95 is compressed against the internal pressure sheath layer 26 of the pipe segment 20 due to compression between the fitting body 48 and the seal flange 102 and, thus, activated (process block 244). In some such embodiments, a seal flange 102 may be secured to a corresponding fitting body 48 via one or more threaded fasteners 92, such as a bolt or a screw. However, in other embodiments, a seal flange 102 may be secured to a corresponding fitting body 48 via hot tooling, such as welding and/or brazing.

[0140] In any case, as described above, the fitting connector 46 of the swaged pipe fitting 44 may then be secured to its fitting body 48 (process block 202). In some embodiments, the fitting connector 46 may be secured to a seal flange 102 of the swaged pipe fitting 44, which is secured to the fitting body 48. More specifically, in some such embodiments, a fitting connector 46 may be secured to a corresponding seal flange 102 and a corresponding fitting body 48 via one or more threaded fasteners 92, such as a bolt or a screw. However, in other embodiments, a fitting connector 46 may be secured to a corresponding seal flange 102 via hot tooling, such as welding and/or brazing.

[0141] In other embodiments, the fitting connector 46 of a swaged pipe fitting 44 may be secured directly to a corresponding fitting body 48, for example, via one or more threaded fasteners 92, such as a bolt or a screw, and/or hot tooling, such as welding and/or brazing. In fact, in some such embodiments, an internal pressure sheath seal 95 of a swaged pipe fitting 44 may be compressed between its fitting body 48 and its fitting connector 46. Accordingly, in such embodiments, securing the fitting connector 46 to the fitting body 48 may compress the internal pressure sheath seal 95 therebetween such that the internal pressure sheath seal 95 is compressed against the internal pressure sheath layer 26 of a pipe segment 20 and, thus, activated (process block 246).

[0142] To facilitate anchoring the carcass layer 37 of a pipe segment 20 therein, in some embodiments, a swaged pipe fitting 44 may include a carcass anchoring ring 100, which may be secured to the carcass layer 37, and the fitting connector 46 of the swaged pipe fitting 44 may accommodate the carcass ring 100. In such embodiments, installing the swaged pipe fitting 44 to a pipe segment 20 may include securing a carcass ring 100 to the carcass layer 37 of the pipe segment 20, for example, at least in part by welding and/or threading the carcass ring 100 onto the outer surface 101 of the carcass layer 37 (process block 212). Additionally, in such embodiments, securing the fitting connector 46 to the

fitting body 48 may include disposing the fitting connector 46 over a carcass ring 100, which is secured to the carcass layer 37 of a pipe segment 20, for example, such that the carcass ring 100 is trapped between the fitting connector 46 and the internal pressure sheath layer 26 of the pipe segment 20 or between the fitting connector 46 and a seal flange 102 of the swaged pipe fitting 44 (process block 248). In this manner, the present disclosure provides techniques for implementing and/or deploying a swaged pipe fitting.

[0143] While the present disclosure has been described with respect to a limited number of embodiments, those skilled in the art, having benefit of this disclosure, will appreciate that other embodiments may be devised which do not depart from the scope of the disclosure as described herein. Accordingly, the scope of the disclosure should be limited only by the attached claims.

1.-20. (canceled)

21. A pipeline system comprising:

a pipe segment, wherein tubing of the pipe segment comprises:

- an internal pressure sheath layer that defines a pipe bore;
- an intermediate layer formed around the internal pressure sheath layer; and
- an outer sheath layer formed around the intermediate layer; and

a swaged pipe fitting configured to be secured to the pipe segment, wherein the swaged pipe fitting comprises:

- a fitting body configured to be disposed circumferentially around the internal pressure sheath layer of the pipe segment;
- a fitting jacket secured to the fitting body, wherein the fitting jacket is configured to be conformally deformed around the tubing of the pipe segment such that the fitting jacket directly and circumferentially engages the outer sheath layer of the pipe segment;
- a support cylinder configured to be axially inserted into the pipe bore of the pipe segment under the internal pressure sheath layer to facilitate supporting the tubing of the pipe segment while the fitting jacket is being conformally deformed therearound; and
- an internal pressure sheath seal configured to be radially compressed against the internal pressure sheath layer of the pipe segment.

22. The pipeline system of claim 21, wherein:

- the pipe segment comprises a carcass layer formed under the internal pressure sheath layer; and
- the swaged pipe fitting comprises a carcass isolating ring configured to facilitate electrically isolating the carcass layer of the pipe segment from a remainder of the swaged pipe fitting.

23. The pipeline system of claim 21, wherein the swaged pipe fitting comprises:

- a fitting connector configured to be secured to the fitting body to enable the swaged pipe fitting to be connected to another pipeline component; and
- a face seal configured to be compressed between the fitting body and the fitting connector.

24. The pipeline system of claim 23, wherein the internal pressure sheath seal of the swaged pipe fitting is configured to be radially compressed against the internal pressure sheath layer of the pipe segment due to being axially compressed between the fitting connector and the fitting body.

- 25.** The pipeline system of claim **24**, wherein:
the intermediate layer of the pipe segment defines a fluid conduit within a tubing annulus of the pipe segment;
and
the swaged pipe fitting comprises:
a fluid path defined in the fitting body such that the fluid path is configured to be fluidly connected to the fluid conduit in the tubing annulus of the pipe segment;
and
a vent valve fluidly configured to be fluidly connected to the fluid path defined in the fitting body.
- 26.** A system comprising a swaged pipe fitting configured to be secured to a pipe segment, wherein the swaged pipe fitting comprises:
a fitting body configured to be disposed circumferentially around a carcass layer of the pipe segment and an internal pressure sheath layer of the pipe segment that is formed around the carcass layer to define a pipe bore;
an internal pressure sheath seal configured to be compressed against the internal pressure sheath layer of the pipe segment to facilitate sealing the internal pressure sheath layer within the swaged pipe fitting;
a carcass isolating ring configured to facilitate electrically isolating the carcass layer of the pipe segment in the swaged pipe fitting; and
a fitting jacket secured to the fitting body, wherein the fitting jacket is configured to be conformally deformed directly and circumferentially against an outer sheath layer of the pipe segment to facilitate securing a reinforcement layer of the pipe segment that is formed between the internal pressure sheath layer and the outer sheath layer of the pipe segment within the swage pipe fitting and sealing the outer sheath layer of the pipe segment within the swaged pipe fitting.
- 27.** The system of claim **26**, wherein the swaged pipe fitting comprises:
a fitting connector configured to be secured to the fitting body to enable the swaged pipe fitting to be connected to another pipeline component, wherein the internal pressure sheath seal is configured to be radially compressed against the internal pressure sheath layer of the pipe segment due to being axially compressed between the fitting connector and the fitting body; and
a face seal configured to be compressed between the fitting body and the fitting connector.
- 28.** The system of claim **26**, wherein the swaged pipe fitting comprises:
a fluid path defined in the fitting body such that the fluid path is configured to be fluidly connected to a fluid conduit defined by the reinforcement layer in a tubing annulus of the pipe segment; and
a vent valve fluidly configured to be fluidly connected to the fluid path defined in the fitting body.
- 29.** The system of claim **26**, wherein the swaged pipe fitting comprises a support cylinder configured to be axially inserted into the pipe bore of the pipe segment under the internal pressure sheath layer to facilitate supporting tubing of the pipe segment at least while the fitting jacket is being conformally deformed therearound.
- 30.** The system of claim **26**, comprising a support cylinder tool configured to be:
axially inserted into the pipe bore of the pipe segment while in a contracted state;

- transitioned from the contracted state to an expanded state such that the support cylinder tool is radially expanded against tubing of the pipe segment to facilitate supporting the tubing of the pipe segment while the fitting jacket is being conformally deformed therearound;
transitioned from the expanded state back to the contracted state such that the support cylinder tool radially contracts to facilitate disengaging the support cylinder tool from the tubing of the pipe segment; and
withdrawn from the pipe bore of the pipe segment while in the contracted state.
- 31.** The system of claim **30**, wherein the support cylinder tool comprises:
a threaded shaft;
a stationary collar disposed around the threaded shaft, wherein the stationary collar comprises a first conical outer surface;
an outer stationary nut and an inner stationary nut disposed around the threaded shaft on either side of the stationary collar to hold the stationary collar in place on the threaded shaft;
a plurality of support cylinder sections secured around the threaded shaft, wherein the plurality of support cylinder sections comprises a first conical inner surface configured to slide along the first conical outer surface of the stationary collar and a second conical inner surface;
an activation collar disposed around the threaded shaft, wherein the activation collar comprises a second conical outer surface configured to slide along the second conical inner surface of the plurality of support cylinder sections; and
an activation nut secured around the threaded shaft.
- 32.** The system of claim **30**, wherein the swaged pipe fitting does not include a permanent cylinder disposed within the pipe bore of the pipe segment.
- 33.** A system comprising a swaged pipe fitting configured to be secured to a pipe segment, wherein the swaged pipe fitting comprises:
a fitting body configured to be disposed circumferentially around a carcass layer of the pipe segment and an internal pressure sheath layer of the pipe segment that is formed around the carcass layer to define a pipe bore;
a fitting connector configured to be secured to the fitting body to enable the swaged pipe fitting to be connected to another pipeline component;
a face seal configured to be compressed between the fitting body and the fitting connector;
an internal pressure sheath seal configured to be compressed against the internal pressure sheath layer of the pipe segment to facilitate sealing the internal pressure sheath layer within the swaged pipe fitting; and
a fitting jacket secured to the fitting body, wherein the fitting jacket is configured to be conformally deformed directly and circumferentially against an outer sheath layer of the pipe segment to facilitate securing a reinforcement layer of the pipe segment that is formed between the internal pressure sheath layer and the outer sheath layer of the pipe segment within the swage pipe fitting and sealing the outer sheath layer of the pipe segment within the swaged pipe fitting.
- 34.** The system of claim **33**, wherein the swaged pipe fitting comprises a carcass isolating ring configured to facilitate electrically isolating the carcass layer of the pipe segment in the swaged pipe fitting

35. The system of claim **33**, wherein the swaged pipe fitting comprise:

- a fluid path defined in the fitting body such that the fluid path is configured to be fluidly connected to a fluid conduit defined by the reinforcement layer in a tubing annulus of the pipe segment; and
- a vent valve configured to be fluidly connected to the fluid path defined in the fitting body.

36. The system of claim **33**, wherein the internal pressure sheath seal of the swaged pipe fitting is configured to be radially compressed against the internal pressure sheath layer of the pipe segment due to being axially compressed between fitting connector and the fitting body.

37. The system of claim **33**, wherein the swaged pipe fitting comprises a support cylinder configured to be axially inserted into the pipe bore of the pipe segment under the internal pressure sheath layer to facilitate supporting tubing of the pipe segment at least while the fitting jacket is being conformally deformed therearound.

38. The system of claim **33**, comprising a support cylinder tool configured to be:

- axially inserted into the pipe bore of the pipe segment while in a contracted state;
- transitioned from the contracted state to an expanded state such that the support cylinder tool is radially expanded against tubing of the pipe segment to facilitate supporting the tubing of the pipe segment while the fitting jacket is being conformally deformed therearound;
- transitioned from the expanded state back to the contracted state such that the support cylinder tool radially

contracts to facilitate disengaging the support cylinder tool from the tubing of the pipe segment; and
withdrawn from the pipe bore of the pipe segment while in the contracted state.

39. The system of claim **38**, wherein the support cylinder tool comprises:

- a threaded shaft;
- a stationary collar disposed around the threaded shaft, wherein the stationary collar comprises a first conical outer surface;
- an outer stationary nut and an inner stationary nut disposed around the threaded shaft on either side of the stationary collar to hold the stationary collar in place on the threaded shaft;
- a plurality of support cylinder sections secured around the threaded shaft, wherein the plurality of support cylinder sections comprises a first conical inner surface configured to slide along the first conical outer surface of the stationary collar and a second conical inner surface;
- an activation collar disposed around the threaded shaft, wherein the activation collar comprises a second conical outer surface configured to slide along the second conical inner surface of the plurality of support cylinder sections; and
- an activation nut secured around the threaded shaft.

40. The system of claim **33**, wherein the swaged pipe fitting does not include a permanent cylinder disposed within the pipe bore of the pipe segment.

* * * * *