



US 20230055514A1

(19) **United States**

(12) **Patent Application Publication**
Narayanan et al.

(10) **Pub. No.: US 2023/0055514 A1**

(43) **Pub. Date: Feb. 23, 2023**

(54) **WIRELESS POWERING AND CONTROL OF CONVEYORS ON SHUTTLES**

Publication Classification

(71) Applicant: **Amazon Technologies, Inc.**, Seattle, WA (US)

(51) **Int. Cl.**
B60L 9/00 (2006.01)
H02J 50/10 (2006.01)

(72) Inventors: **Vivek S. Narayanan**, Franklin, TN (US); **Ganesh Krishnamoorthy**, Seattle, WA (US); **Michael Alan Bray**, Elkhorn, NE (US); **Rajeev Dwivedi**, Sammamish, WA (US); **Mohit Malik**, Seattle, WA (US); **Shahid Azad**, Seattle, WA (US)

(52) **U.S. Cl.**
CPC **B60L 9/00** (2013.01); **H02J 50/10** (2016.02); **B65G 1/00** (2013.01)


(73) Assignee: **Amazon Technologies, Inc.**, Seattle, WA (US)

(57) **ABSTRACT**

(21) Appl. No.: **17/404,362**

Systems and methods are disclosed for wireless powering and control of conveyors on shuttles. An example system may include a track, and a shuttle configured to move along the track, the shuttle having a conveyor, and a first induction coil. The system may include a second induction coil disposed at a first location along the track, where the second induction coil is configured to interact with the first induction coil to power the conveyor. The shuttle may not have an onboard power source coupled to the conveyor.

(22) Filed: **Aug. 17, 2021**







FIG. 1






FIG. 3A




FIG. 3B




FIG. 4




FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 7




FIG. 8

WIRELESS POWERING AND CONTROL OF CONVEYORS ON SHUTTLES

BACKGROUND

[0001] As users increasingly make online purchases, fulfillment of such purchases and other orders may become increasingly complicated. For example, a fulfillment center may have output of upwards of one million packages per day. With such demands, efficiency of logistics related to processing orders and packages may be important. For example, use of equipment to move or otherwise handle objects may improve efficiency. However, such equipment may create chokepoints or cause bottlenecks in fulfillment center operations. Accordingly, improvements in various operations and components of order fulfillment, such as improvements to picking technology, sorting technology, transport technology, packing technology, and so forth may be desired, such that manual efforts can be redirected to different tasks.

BRIEF DESCRIPTION OF THE DRAWINGS

[0002] FIG. 1 is a hybrid schematic illustration of an example use case for wireless powering and control of conveyors on shuttles in accordance with one or more embodiments of the disclosure.

[0003] FIG. 2 is a schematic illustration of an example use case and facility layout for wireless powering and control of conveyors on shuttles in accordance with one or more embodiments of the disclosure.

[0004] FIGS. 3A-3B are schematic illustrations of a perspective view of a shuttle rail system and a perspective view of a shuttle matrix in accordance with one or more embodiments of the disclosure.

[0005] FIG. 4 is a schematic illustration of various views of portions of a shuttle rail system and wireless powering and control of a conveyor on a shuttle in accordance with one or more example embodiments of the disclosure.

[0006] FIGS. 5A-5B are schematic illustrations of a shuttle system in various views in accordance with one or more embodiments of the disclosure.

[0007] FIGS. 6A-6B are schematic illustrations of a shuttle having a conveyor configured for wireless powering and control in accordance with one or more embodiments of the disclosure.

[0008] FIG. 7 is a schematic illustration of a transceiver and example power and data flow in accordance with one or more embodiments of the disclosure.

[0009] FIG. 8 schematically illustrates an example architecture of a computer system associated with a shuttle system in accordance with one or more embodiments of the disclosure.

[0010] The detailed description is set forth with reference to the accompanying drawings. The drawings are provided for purposes of illustration only and merely depict example embodiments of the disclosure. The drawings are provided to facilitate understanding of the disclosure and shall not be deemed to limit the breadth, scope, or applicability of the disclosure. The use of the same reference numerals indicates similar, but not necessarily the same or identical components. Different reference numerals may be used to identify similar components. Various embodiments may utilize elements or components other than those illustrated in the drawings, and some elements and/or components may not be

present in various embodiments. The use of singular terminology to describe a component or element may, depending on the context, encompass a plural number of such components or elements and vice versa.

DETAILED DESCRIPTION

Overview

[0011] Fulfillment centers may be used to fulfill online purchases and other orders. For example, fulfillment centers may include product inventory that may be pulled when an order for a particular product or multiple products is placed. In some instances, the product(s) may be packed and shipped from the fulfillment center. However, the process of obtaining the product(s), packing the product(s), and shipping the product(s) may be complicated due to the amount of inventory, the number of orders to process, the size of the fulfillment center, and/or other factors. In addition, a portion of the fulfillment center designated for packing or shipping may be different than the portion of the fulfillment center designated for holding product inventory. As a result, transportation of products in an order may be time consuming.

[0012] Moving items or objects through a fulfillment center may require handling of the item itself. For example, picking the item from inventory, placing the item into a container, removing the item from a container, and so forth may all be examples of actions for which an item may need to be handled. In addition, different items may have different types of packaging. For example, some items may come in boxes, some items may come in loose bags, some items may come shrink wrapped, some items may not have any packaging, and so forth. Humans may be able to manually handle individual items with ease. However, robotic handling of individual items may require various levels of dexterity. Moreover, fulfillment centers may include lengthy conveyors that may be used to transport objects, such as packages, products, items, or other objects, as well as containers that may be at least partially full of objects. Transport of containers or items (e.g., individual items or multiple items, etc.) may involve the use of container shuttles that move on one or more rails to transport a container from one location to another. For example, a container of items may be loaded onto a shuttle, and the shuttle may transport the container from an inventory field to a sortation system or other location. Shuttles may be used to transport containers and/or one or more items from a first location to a second location.

[0013] In a typical warehouse environment, such as that illustrated in FIG. 1, items may be transported through various means such as conveyors, belts, shuttles, etc. as they undergo different operations like picking, sorting, storing, shipping/dispatch, and so forth. In some of these cases, containers may be used to transport items, either individually or in groups, from one location to another. For instance, transporting items from a pick station to a sort station may involve the item(s) being picked into a container, such as a tote, which may then be transported via a shuttle.

[0014] Container shuttles, which may carry containers, individual items or multiple items without containers, and the like, may be in continuous operation and may move at relatively high speeds, such as speeds of three meters per second or more. As a result, additional weight carried by the shuttle may negatively impact performance. In some instances, shuttles may carry onboard power sources, such as capacitors or batteries, to power various shuttle compo-

nents, such as a conveyor on the shuttle. Such power sources may be additional weight that not only impacts shuttle performance, but reduces shuttle longevity and may also negatively impact handling and movement of the shuttle. In some instances, shuttles may use contact-based external power sources that rely on contact between mechanical components, such as electrical pins and the like, to power onboard components. However, such components also present drawbacks, such as deterioration of mechanical components over time, frequent maintenance requirements, and so forth.

[0015] To solve such issues, embodiments of the disclosure include systems and methods for wireless powering and control of conveyors and other onboard components on shuttles. Some embodiments may eliminate the need for onboard power sources, thereby reducing overall shuttle weight and resulting in improved longevity and performance. Some embodiments further remove the need for mechanical contact to provide power to shuttle components. Embodiments may use inductive powering to not only power onboard shuttle components, but also to send and/or receive data, such as command data instructing the shuttle to initiate the conveyor in a certain direction. Such data may be used to facilitate unloading of containers or items to a particular side of the shuttle, as well as to provide shuttle status updates and the like. Some embodiments may use inductive powering to provide power to a transceiver or a receiver onboard the shuttle, as well as to the conveyor of the shuttle. For example, the shuttle may include an onboard antenna and a power and communication management module that is powered externally via inductive powering. Various delivery points along a track may include one or more antennae and transceivers that can communicate with the shuttle at the different delivery points. Shuttles may be precisely propelled and moved using linear synchronous motors, which may allow for rough alignment with induction coils disposed along the track(s) along which the shuttle runs. At a delivery point, the transmitter and receiver antennas may overlap to power the receiver antenna of the shuttle via inductive coupling. The communication across the two modules can be used to update the shuttle status, to control the direction of conveyor spin or movement, and so forth. As a result, throughput of fulfillment centers may be improved, and/or logistics of fulfillment center operations may be less complicated.

[0016] Referring to FIG. 1, an example use case **100** for wireless powering and control of conveyors on shuttles is depicted in accordance with one or more embodiments of the disclosure. Although discussed in the context of online orders, other embodiments may be directed to any suitable use case where containers or items are transported, such as instances where objects are picked from inventory, placed into containers, containers are transported, and so forth.

[0017] In FIG. 1, a fulfillment center may be a traditional fulfillment center and may include an inventory field **110**, a routing sorter **160**, one or more item sorting machines **170**, and one or more packing stations **180**. The inventory field **110** may include a storage platform, or a portion of the fulfillment center at which products picked from product inventory are placed. Robots may be used to pick products from inventory and to deliver to the robotic storage platform in some instances, while in other instances, manual labor or a combination thereof may be used to pick products. The picking process at the robotic storage platform may include

locating a product in an order, obtaining the product, and sending the product to a robotic storage platform, such as via a conveyor belt. In the illustrated embodiment, products at the robotic storage platform may be placed in a container, such as a tote.

[0018] The inventory field **110** may include multiple items that are in inventory. The items may be used to fulfill orders. The inventory field **110** may be a robotic field in some instances. One or more picking stations **130** may be positioned along a perimeter **120** of the inventory field **110**. The picking stations **130** may be manually operated or may include robotic components, or a combination thereof. In some instances, picking of items from the inventory field **110** may be completed by robots that include automated robotic arms, where the items are delivered to the picking stations **130** after being retrieved from the inventory field **110**. Any number of picking stations **130** may be included, and the picking stations **130** may be located in a different position than that illustrated in FIG. 1.

[0019] In a traditional fulfillment center, such as that illustrated in FIG. 1, one or more conveyors **150** may be disposed about the inventory field **110**. For example, conveyors **150** may be disposed along the perimeter **120** of the inventory field **110**. The conveyors **150** may run adjacent to the picking stations **130** in some embodiments. Any suitable conveyor configuration may be used. In the illustrated example, the conveyors **150** may include belts or rollers that run alongside the picking stations **130** and include one or more paths to one or more routing sorters.

[0020] The conveyors **150** may be used to transport one or more containers, such as totes **140**. For example, as totes **140** move along the conveyors **150**, items may be moved from the picking stations **130** into respective totes **140**. The totes **140** may be associated with particular item sorting machines, and may be moved using the conveyors **150** to a routing sorter **160**. In contrast, embodiments of the disclosure may not include some or all of the conveyors **150**, and instead may include rails that may be used to guide shuttles from one location to another. The rails may be used with systems that allow for wireless powering and control of conveyors on shuttles as described herein.

[0021] The routing sorter **160** may be configured to route, divert, or otherwise guide certain totes to an item sorting machine. The routing sorter **160** may include any combination of ramps, slides, rollers, arms, guides, and/or other components to route totes to a particular item sorting machine. At the routing sorter **160**, totes including products that have been picked may be routed to the appropriate or designated item sorting machine. For example, the routing sorter **160** may determine an identifier associated with the tote, and may determine an item sorting machine associated with the tote using the identifier. The routing sorter **160** may route or direct the tote to the appropriate item sorting machine.

[0022] A number of item sorting machines **170** may be coupled to the routing sorter **160**. For example, a first item sorting machine **172**, a second item sorting machine **174**, a third item sorting machine **176**, and so forth may be coupled to the routing sorter **160**. The routing sorter **160** may optionally guide totes to the item sorting machines to which they are assigned. For example, a first tote **162** may include item **1**, item **16**, and item **23**, and may be assigned to the first item sorting machine **172**. The routing sorter **160** may therefore route the first tote **162** to the first item sorting

machine **172** for sortation of the respective items. A second tote **164** may include item **1656**, and may be assigned to the second item sorting machine **174**. The routing sorter **160** may therefore route the second tote **164** to the second item sorting machine **174** for sortation of the item. A third tote **166** may include item **989**, item **145**, and item **34**, and may be assigned to the third item sorting machine **176**. The routing sorter **160** may therefore route the third tote **166** to the third item sorting machine **176** for sortation of the respective items.

[0023] Some or all of the item sorting machines may be associated with one or more packing stations **180** that may be used to pack items into a shipment when a multi-item order is complete. For example, the first item sorting machine **172** may be coupled to a first packing station **182**, the second item sorting machine **174** may be coupled to a second packing station **184**, the third item sorting machine **176** may be coupled to a third packing station **186**, and so forth. The item sorting machines may be configured to receive items from totes that have one or more, or multiple, items. The number of totes and/or the number of items associated with respective item sorting machines may be balanced, and multiple totes may be routed to the first item sorting machine **172** and the second item sorting machine **174** at the same time.

[0024] At any of the stages of the example fulfillment process of FIG. **1** where handling of containers is used, shuttle powering systems as described herein may be used for wireless powering and control of conveyors on shuttles.

[0025] Embodiments of the disclosure include systems and methods for wireless powering and control of conveyors on shuttles. Certain embodiments may improve processing speed and/or throughput of fulfillment centers. Certain embodiments may improve performance of mechanical equipment for sortation and/or consolidation of items. Certain embodiments eliminate the need for onboard power sources to power conveyors and/or other components of a shuttle, thereby reducing the weight of the shuttle and improving shuttle dynamics and reducing propulsion power requirements. Frequent charging and discharging of the power source can be eliminated, and due to contactless and/or wireless charging, actual mechanical contact for powering is avoided. While described in the context of online orders, aspects of this disclosure are more broadly applicable to other forms of object handling.

[0026] Example embodiments of the disclosure provide a number of technical features or technical effects. For example, in accordance with example embodiments of the disclosure, certain embodiments of the disclosure may improve processing speed, throughput, and/or efficiency of fulfillment centers. The above examples of technical features and/or technical effects of example embodiments of the disclosure are merely illustrative and not exhaustive.

[0027] One or more illustrative embodiments of the disclosure have been described above. The above-described embodiments are merely illustrative of the scope of this disclosure and are not intended to be limiting in any way. Accordingly, variations, modifications, and equivalents of the embodiments disclosed herein are also within the scope of this disclosure. The above-described embodiments and additional and/or alternative embodiments of the disclosure will be described in detail hereinafter through reference to the accompanying drawings.

Illustrative Embodiments and Use Cases

[0028] FIG. **2** is a schematic illustration of an example use case **200** and facility layout for wireless powering and control of conveyors on shuttles in accordance with one or more embodiments of the disclosure. Other embodiments may include additional or fewer components. The illustration of FIG. **2** may not be to scale, and may not be illustrated to scale with respect to other figures.

[0029] In FIG. **2**, a fulfillment center may include an inventory field **210**, at which products or other items may be stored in inventory. As the items are ordered in online orders, the products may be picked from the inventory field **210** and routed for downstream processing in the fulfillment center. The items may be picked manually, using vehicles, or a combination thereof.

[0030] The picked products may be placed into one or more containers and the containers may be transported using one or more shuttles, such as one or more shuttles on rails **220**. In some embodiments, items may be transported by the shuttles without using containers. The shuttles on rails **220** may include container shuttles that are configured to transport items and/or containers from one location to another via rails. The rails may include switching rail components that allow for the shuttles to move from one set of rails to another. The shuttles on rails **220** may transport containers from the inventory field **210** to one or more downstream processes, such as a sortation system **230**, or a packing system **240**. For example, the sortation system **230** may be a system at which items picked from the inventory field **210** may be re-sorted into respective totes or other containers for particular orders. For example, items for different orders may be placed into containers that are transported by the shuttles on rails **220** from the inventory field **210**. The containers may be sent to the sortation system **230** for sorting into particular orders. The packing system **240** may be a station at which one or more items associated with an order may be packed into a box or other container for shipment. A shipping label may be applied and the package may be dispatched to a loading dock or elsewhere for shipment. Other destinations or downstream processes in addition to, or instead of, the sortation systems and packing systems may be used.

[0031] A rail system **260** is depicted in schematic view in FIG. **2**. In other embodiments, the rail system may be a matrix-based rail system that includes more than one level, such as that illustrated in FIG. **3B**. The rail system **260** is an example of a network of rails that may be used by shuttles to transport containers from one location to another. The network of rails may include locations at which a shuttle can be directed to a straight path or to a loop, turn, oval, circle, and/or other geometries that involve a change in direction of a shuttle on the rails. Such changes in direction may be implemented using switching rail components. Conveyors and other components onboard the shuttles can be powered using the wireless powering and control systems described herein. The rail system **260** may include rails that link various systems, such as sortation systems, to each other and/or to other systems, such as container handling systems, manual induction systems **290**, and so forth. For example, the rail system **290** may link a first sortation system **270** to a second sortation system **272**, as well as to a first container handling system **280**, a second container handling system **282**, a third container handling system **284**, and so forth. The

rail system **260** may be used to connect any of the systems to each other and/or other systems.

[0032] Shuttles may move along the rails of the rail system **260**. The shuttles may include linear drive motors or other drive components. Some drive components may provide a drive force via electromagnetism. As a result, one or more electromagnets may be disposed along the network of rails. Shuttles may optionally include a conveyor belt that may have a first set of one or more raised flaps and a second set of one or more raised flaps. The first set of raised flaps may form a first barrier along a first open-ended side of the shuttle, and the second set of raised flaps may form a second barrier along a second open-ended side of the shuttle to prevent items rolling off of the conveyor belt. The shuttles may include an onboard drive motor configured to move the conveyor belt in a forward direction and/or a reverse direction. The onboard motor may be powered via induction coils, as described herein. The shuttles may include a magnet disposed on a lower surface of the shuttle. The magnet may be used to propel and/or secure the shuttle. For example, the magnet may prevent the shuttle from moving while the vehicle is in motion and the linear drive motor is engaged.

[0033] FIGS. 3A-3B are schematic illustrations of a perspective view of a shuttle rail system and a perspective view of a shuttle matrix in accordance with one or more embodiments of the disclosure. Other embodiments may include additional or fewer components. The illustration of FIGS. 3A-3B are not to scale, and may not be illustrated to scale with respect to other figures. The system illustrated in FIGS. 3A-3B may be used with the systems described herein for wireless powering and control of conveyors on shuttles discussed with respect to FIGS. 1-2.

[0034] In FIG. 3A, the shuttle rail system **300** may be configured to provide continuous rail for switching the direction of a shuttle **350** in an electromagnetically propelled shuttle-on-rail arrangement. Shuttle-on-rail arrangements may be used in many systems, such as sortation systems, pick systems, delivery systems, etc. The shuttle rail system **300** may include rail switch mechanisms to allow the rail to be directed to alternate path. Shuttle-rail arrangements that are based on electromagnetic propulsion, such as linear drive motors, may have sets of electromagnets arranged along the direction of the rails. Shuttles may also have a magnet, such as a permanent magnet, coupled to a lower side of the shuttle. The electromagnet and the permanent magnet may have to be separated by a very narrow gap for optimal performance. Such factors may make removal of the shuttle **350** from the shuttle rail system **300** difficult, due to potential unintended interaction between the magnets. Embodiments of the disclosure include systems that power conveyors and other components of shuttles at various fixed locations along the shuttle rail system **300**.

[0035] The shuttle **350** may be wirelessly powered via inductive coupling using induction coils disposed along the shuttle rail system **300**, which may also be located at a curved section of rail. For example, the shuttle rail system **300** may include a first branched path **310**, where if shuttles were moving along the shuttle rail system **300** in a clockwise direction, the shuttle could move in either a straight direction along the oval path of the shuttle rail system **300**, or may make a left-handed curve onto a separate path of the shuttle rail system **300**. Similarly, a second branched path **320** may allow for merging of shuttles that took a left curve at the first branched path **310** to merge back onto the oval path of the

shuttle rail system **300**. Any number of curved path and straight path intersections may be included in the shuttle rail system **300**. For example, the shuttle rail system **300** may include a third branched path **330** and a fourth branched path **340**. At any of the branched paths, the shuttle may be removed using the shuttle disengagement mechanisms described herein.

[0036] In an alternate embodiment, a shuttle rail system **360** may include one or more levels, such as the multi-level matrix system depicted in FIG. 3B. In such embodiments, individual levels may include tracks along which shuttles may move, and induction coils may be disposed along the tracks to power the conveyor and/or communication hardware onboard the shuttle(s). In some instances, rail systems may include combinations of the flat rail system of FIG. 3A and the matrix-based rail system of FIG. 3B.

[0037] FIG. 4 is a schematic illustration of various views of portions of a shuttle rail system and wireless powering and control of a conveyor on a shuttle in accordance with one or more example embodiments of the disclosure. Other embodiments may include additional or fewer components. The illustration of FIG. 4 is not to scale, and may not be illustrated to scale with respect to other figures. The system illustrated in FIG. 4 may include the same shuttle and shuttle rail system discussed with respect to FIGS. 1-3B.

[0038] FIG. 4 depicts a portion of the shuttle rail system **400** in a top schematic view. The shuttle rail system **400** may include one or more sets of rails that form a track **410** on which shuttles **420** may ride. The track **410** may guide shuttles **420** to various locations. Each track **410** may include two rails, so as to support two sides of a shuttle **420** on the rails. The shuttle rail system **400** may include a number of supports disposed between the two rails of a track **410**. A number of electromagnets **470** may optionally be disposed along the rails at various intervals. The electromagnets **470** may be configured to propel shuttles along the respective sets of rails.

[0039] A perspective view **440** in FIG. 4 depicts the shuttle **420** engaged with the shuttle rail system **400**. The shuttle **420** may include wheels **450** that engage the track **410**. Some embodiments may include four wheels **450**, while other embodiments may include different numbers of wheels. Any suitable number and size of wheels may be used to engage with the track **410**.

[0040] The shuttle **420** may include a permanent magnet **460** disposed underneath the shuttle **420**. The permanent magnet **460** may interact with the electromagnets **470** to electromagnetically propel the shuttle **420**. The electromagnets **470** and permanent magnet **460** may together form a linear synchronous motor in some embodiments.

[0041] Although the shuttle **420** is depicted as traveling in a sideways configuration with respect to the shuttle rail system **400** (e.g., a payload on the shuttle **420** may be moving sideways with respect to the shuttle rail system **400**, etc.), in other embodiments, the shuttle **420** may be oriented differently.

[0042] The shuttle rail system **400** may therefore include the track **410** having a central axis. The track **410** may include a first rail segment on a first side of the central axis and a second rail segment on a second side of the central axis. The shuttle rail system **400** may include the set of electromagnets **470** disposed along the central axis of the track. The shuttle rail system **400** may be used with the shuttles **420**, where the shuttles **420** are configured to

transport individual items or containers from a first location to a second location using the track **410**. The shuttle may include a first pair of wheels **450** disposed at a front end of the shuttle **420**, and a second pair of wheels **450** disposed at a rear end of the shuttle **420**. In some embodiments, the shuttle **420** may include a conveyor assembly having a central axis that is transverse to the central axis of the track, such as in the embodiment depicted in FIG. 4. The shuttle **420** may include the permanent magnet **460** coupled to a lower surface of the shuttle **420**. The permanent magnet **460** may be configured to engage with the set of electromagnets **470** to propel the shuttle **420**. The shuttle **420** may not include an onboard power source coupled to the conveyor assembly.

[0043] FIGS. 5A-5B are schematic illustrations of a system **500** in various views in accordance with one or more embodiments of the disclosure. Other embodiments may include additional or fewer components. The illustration of FIGS. 5A-5B are not to scale, and may not be illustrated to scale with respect to other figures. The system illustrated in FIGS. 5A-5B may be the same system discussed with respect to FIGS. 1-4.

[0044] In FIG. 5A, a portion of the system **500** is depicted in perspective view. The portion of the system **500** is depicted in a top view **580** and a bottom view **590** in FIG. 5B. The system **500** may include a track **510** and one or more shuttles **530**. The shuttles **530** may be configured to move along the track **510** and may be propelled via one or more electromagnets **570**. The shuttle **530** may include a permanent magnet coupled to a lower surface of the shuttle **530**, and the electromagnets **570** disposed along the track **510** may interact with the permanent magnet to propel the shuttle **530** along the track **510**. The shuttle **530** may stop at various points along the track **510** to deliver containers or items to delivery locations **520**. Container slots and/or container matrices (not shown) may be disposed along one or both sides of the track **510**. The system **500** may be configured to wirelessly power and control a conveyor of the shuttle **530**. The system **500** may further be configured to power one or more radios and/or transceivers coupled to the shuttle **530**.

[0045] For example, the shuttle **530** may be configured to transport items from a pickup location to a delivery location using the track **510**. The shuttle **530** may include a conveyor, a first induction coil disposed on a lower surface, and a first transceiver, which may be a data receiver module, configured to receive command data. The conveyor may be configured to move bidirectionally in some embodiments, and unidirectional in other embodiments. The shuttle **530** may not include an onboard power source that is coupled to the conveyor. As a result, the conveyor may be inoperable without external power.

[0046] To power the conveyor of the shuttle **530**, and in some instances to power the first transceiver, the system **500** may include a number of induction coils disposed along the track **510**. For example, the system **500** may include a second induction coil **540** disposed at a first location along the track **510**, a third induction coil **550** disposed at a second location along the track **510**, a fourth induction coil **560** disposed at a third location along the track **510**, a fifth induction coil **570** disposed at a fourth location along the track **510**, and so forth. Any number of induction coils may be disposed along the track **510**.

[0047] The induction coils may be disposed at various delivery locations **520** along the track **510**, such that power is available to power the conveyor of the shuttle **530** at any location at which the shuttle **530** may have to deliver an item or container.

[0048] The induction coils disposed along the track **510** may interact with the first induction coil on the shuttle **530**, so as to induce or impart an electrical current at the first induction coil, which may then be used to power the conveyor of the shuttle **530**, as well as the first transceiver in instances where the shuttle **530** does not include an onboard power source coupled to the transceiver. The induction coils disposed along the track **510** interact with the first induction coil by imparting an electric current to the first induction coil when the first induction coil is within a distance of the induction coil on the track **510**. Precise positioning may not be required due to the contactless and wireless nature of the inductive coupling between the induction coils.

[0049] In some embodiments, the system **500** may include a number of data transmitter modules or transceivers disposed along the track **510**, such as adjacent to the respective induction coils **540**, **550**, **560**, **570**. The transceivers disposed along the track **510** may be used to communicate with the first data transceiver on the shuttle **530**. Data communicated may include command data related to operation of the conveyor of the shuttle, such as which direction to actuate the conveyor, how long to actuate the conveyor for (e.g., a length of time the conveyor is to be activated, etc.), a stop position for the shuttle relative to the track, and/or other operational data. In some embodiments, the data may include shuttle status update data, such as whether the container or item on the shuttle has been delivered, and so forth. The data may be communicated via the inductive coupling using the induction coil on the track **510** and the induction coil on the shuttle **530**. In some embodiments, data transfer may be one-way from the transceiver on the track to the first transceiver on the shuttle **530** (in which case the onboard module on the shuttle may be a receiver instead of a transceiver), whereas in other embodiments, data transfer may be two-way and the first transceiver on the shuttle **530** may be configured to send data, such as shuttle status updates, to the transceiver on the track.

[0050] Because the shuttle **530** may not include an onboard power source for the conveyor, the conveyor may not be operable unless the shuttle **530** is positioned adjacent to one of the induction coils disposed along the track. For example, the conveyor may therefore be inoperable along the track between the first location of the first induction coil **540** and the second location of the second induction coil **550** due to a lack of power. Similarly, the first transceiver or the data receiver module of the shuttle may be inoperable along the track between the first location and the second location due to a lack of power.

[0051] Moreover, because the transceivers may be coupled to the induction coils along the track, advance instruction of conveyor operation, such as which way to move the conveyor, may not be needed. The shuttle may therefore be operable with reduced weight and no onboard power source for the conveyor. In some embodiments, the shuttle may also not include an onboard power source for the first transceiver, which may also be powered using the wireless powering system inductive coupling used to power the conveyor.

[0052] FIGS. 6A-6B are schematic illustration of a system 600 with a shuttle 620 having a conveyor 630 configured for wireless powering and control in accordance with one or more embodiments of the disclosure. Other embodiments may include additional or fewer components. The illustration of FIGS. 6A-6B are not to scale, and may not be illustrated to scale with respect to other figures. The system illustrated in FIGS. 6A-6B may be the same system discussed with respect to FIGS. 1-5B.

[0053] In FIG. 6A, the shuttle 620 is depicted coupled to a track 610 of the system 600. The shuttle 620 may include the conveyor 630, which may move in one or both directions. The shuttle 620 is depicted adjacent to an induction coil 640 disposed along the track 610. The shuttle 620 may include an induction coil disposed on a lower surface that may interact with the induction coil 640 on the track 610. When the induction coil of the shuttle 620 is positioned approximately over the induction coil 640, the induction coils may be inductively coupled and energy transfer may occur. Power from the inductive coupling may be used to power various components of the shuttle 620, such as the conveyor 630, one or more radios or transceivers onboard the shuttle 620, and/or other components. In some embodiments, data may be transferred via the inductive coupling. For example, command data related to operation of the conveyor may be sent via the induction coil 640 from a transceiver coupled to the induction coil 640.

[0054] As depicted in side cross-sectional view in FIG. 6A, the shuttle 620 may include a first transceiver 660 coupled to a first induction coil 650. When the first induction coil 650 is near (e.g., within several inches, etc.) the induction coil 640, the induction coils may be coupled and energy transfer may occur. The induction coil 640 may be coupled to a second transceiver 670. The second transceiver 670 may be disposed below an upper surface of the track 610, whereas the induction coil 640 may be slightly elevated with respect to the upper surface of the track 610.

[0055] To power the conveyor 630 of the shuttle 620, and in some instances to power the first transceiver 660, the system 600 may guide the shuttle 620 to the induction coil 640. The induction coil 640 may provide power to power the conveyor 630. For example, the induction coil 640 may interact with the first induction coil 660 on the shuttle 620, so as to induce or impart an electrical current at the first induction coil, which may then be used to power the conveyor 630, as well as the first transceiver 660 in instances where the shuttle 620 does not include an onboard power source coupled to the transceiver. Precise positioning may not be required due to the contactless and wireless nature of the inductive coupling between the induction coils.

[0056] In some embodiments, the system 600 may include a number of data transmitter modules or transceivers disposed along the track 610. The transceivers disposed along the track 610 may be used to communicate with the first data transceiver 660 on the shuttle 620. Data communicated may include command data related to operation of the conveyor of the shuttle, such as which direction to actuate the conveyor, how long to actuate the conveyor for (e.g., a length of time the conveyor is to be activated, etc.), a stop position for the shuttle relative to the track, and/or other operational data. The stop position may include information related to an optimal location or range of locations for the shuttle to stop, such that energy transfer occurs via the respective induction coils. In some embodiments, the data may include shuttle

status update data, such as whether the container or item on the shuttle has been delivered, and so forth. The data may be communicated via the inductive coupling using the induction coil 640 on the track 610 and the first induction coil 660 on the shuttle 620. In some embodiments, data transfer may be one-way from the transceiver on the track to the first induction coil 660 on the shuttle 620 (in which case the onboard module on the shuttle may be a receiver instead of a transceiver), whereas in other embodiments, data transfer may be two-way and the first induction coil 660 on the shuttle 620 may be configured to send data, such as shuttle status updates, to the transceiver on the track. In other embodiments, other forms of wireless communication, such as WiFi, NFC, ZigBee, Bluetooth, and the like may be used for data transfer instead of transmitting data via the induction coils.

[0057] Because the shuttle 620 may not include an onboard power source for the conveyor 630, the conveyor 630 may not be operable unless the shuttle 620 is positioned adjacent to one of the induction coils disposed along the track. Moreover, because the transceivers may be coupled to the induction coils along the track, advance instruction of conveyor operation, such as which way to move the conveyor, may not be needed. The shuttle may therefore be operable with reduced weight and no onboard power source for the conveyor. In some embodiments, the shuttle may also not include an onboard power source for the first transceiver, which may also be powered using the wireless powering system inductive coupling used to power the conveyor.

[0058] In FIG. 6B, an alternate embodiment where the shuttle 620 does not include an onboard data receiver, or the onboard data receiver is not used to receive conveyor actuation direction information. Instead of wirelessly receiving conveyor actuation direction information, different locations along the track may be associated with different spin or actuation directions of the conveyor 630 of the shuttle 620. For example, a first mechanical switch 690 or other component may be disposed along the track 610, and may engage with a corresponding contact or other component of the shuttle 620. The shuttle 620 may have contacts on both sides of the shuttle 620. Depending on which contact on the different sides of the shuttle 620 is actuated, the shuttle 620 may cause the conveyor 630 to spin different directions. For instance, in the example of FIG. 6B, the first mechanical switch 690 may cause the conveyor 630 to move in a counter-clockwise direction, whereas a second mechanical switch 692 may cause the conveyor 630 to move in a clockwise direction. In such embodiments, wireless communication for conveyor actuation direction information may not be needed.

[0059] FIG. 7 is a schematic illustration of a transceiver module 700 and example power and data flow 730 in accordance with one or more embodiments of the disclosure. Other embodiments may include additional or fewer components. The illustration of FIG. 7 is not to scale, and may not be illustrated to scale with respect to other figures. The transceiver module illustrated in FIG. 7 may be used with the shuttles and/or rails discussed with respect to FIGS. 1-6.

[0060] In some embodiments, the transceiver module 700 may be used to facilitate data communication between a shuttle 750 and a transceiver on a track 740. In some embodiments, the transceiver module 700 may be included both onboard the shuttle 750 and coupled to the track 740. The transceiver module 700 may include one or more inputs,

such as a first input **710** and a second input **720**. The transceiver module **700** may communicate with other transceiver modules **700** via wireless and/or contactless inductive coupling **760**. In other embodiments, a transmitter module may be used on the track **740**, and a receiver module may be used on the shuttle **750**.

[0061] In some embodiments, shuttle operation may be controlled by a remote server or remote computer system, but conveyor operation may be communicated to the shuttle using the transceiver module **700**. For example, a remote computer system may be configured to direct a shuttle from a pickup location to a delivery location, where the delivery location is aligned with a first induction coil **742** disposed along the track **740**. One or more electromagnets **744** may also be disposed along the track **740**.

[0062] Similarly, the shuttle **750** may include a second induction coil **752** that interacts with the first induction coil **742** disposed along the track **740** to generate an electric current. The electric current may be used to power a conveyor **756** of the shuttle, and optionally to power a transceiver of the shuttle **750**. The second induction coil **752** may also interact with the first induction coil **742** disposed along the track **740** to receive data that is sent to the transceiver **700** of the shuttle **750**. The data may be used to control operation of the conveyor **756** via an onboard controller **754** in communication with the transceiver **700** of the shuttle **750**. In other embodiments, the transceiver **700** of the shuttle **750** may be configured to transmit a shuttle status indicator to the remote computer system via the transceiver **700** disposed along the track **740**.

[0063] One or more operations of the methods, process flows, or use cases of FIGS. **1-7** may have been described above as being performed by a user device, or more specifically, by one or more program module(s), applications, or the like executing on a device. It should be appreciated, however, that any of the operations of the methods, process flows, or use cases of FIGS. **1-7** may be performed, at least in part, in a distributed manner by one or more other devices, or more specifically, by one or more program module(s), applications, or the like executing on such devices. In addition, it should be appreciated that processing performed in response to the execution of computer-executable instructions provided as part of an application, program module, or the like may be interchangeably described herein as being performed by the application or the program module itself or by a device on which the application, program module, or the like is executing. While the operations of the methods, process flows, or use cases of FIGS. **1-7** may be described in the context of the illustrative devices, it should be appreciated that such operations may be implemented in connection with numerous other device configurations.

[0064] The operations described and depicted in the illustrative methods, process flows, and use cases of FIGS. **1-7** may be carried out or performed in any suitable order, such as the depicted orders, as desired in various example embodiments of the disclosure. Additionally, in certain example embodiments, at least a portion of the operations may be carried out in parallel. Furthermore, in certain example embodiments, less, more, or different operations than those depicted in FIGS. **1-7** may be performed.

[0065] Although specific embodiments of the disclosure have been described, one of ordinary skill in the art will recognize that numerous other modifications and alternative embodiments are within the scope of the disclosure. For

example, any of the functionality and/or processing capabilities described with respect to a particular device or component may be performed by any other device or component. Further, while various illustrative implementations and architectures have been described in accordance with embodiments of the disclosure, one of ordinary skill in the art will appreciate that numerous other modifications to the illustrative implementations and architectures described herein are also within the scope of this disclosure.

[0066] Certain aspects of the disclosure are described above with reference to block and flow diagrams of systems, methods, apparatuses, and/or computer program products according to example embodiments. It will be understood that one or more blocks of the block diagrams and flow diagrams, and combinations of blocks in the block diagrams and the flow diagrams, respectively, may be implemented by the execution of computer-executable program instructions. Likewise, some blocks of the block diagrams and flow diagrams may not necessarily need to be performed in the order presented, or may not necessarily need to be performed at all, according to some embodiments. Further, additional components and/or operations beyond those depicted in blocks of the block and/or flow diagrams may be present in certain embodiments.

[0067] Accordingly, blocks of the block diagrams and flow diagrams support combinations of means for performing the specified functions, combinations of elements or steps for performing the specified functions, and program instruction means for performing the specified functions. It will also be understood that each block of the block diagrams and flow diagrams, and combinations of blocks in the block diagrams and flow diagrams, may be implemented by special-purpose, hardware-based computer systems that perform the specified functions, elements or steps, or combinations of special-purpose hardware and computer instructions.

Illustrative Computer Architecture

[0068] FIG. **8** is a schematic block diagram of one or more illustrative computer system(s) **800** associated with a shuttle rail system in accordance with one or more example embodiments of the disclosure. The computer system(s) **800** may include any suitable computing device including, but not limited to, a server system, a voice interaction device, a mobile device such as a smartphone, a tablet, an e-reader, a wearable device, or the like; a desktop computer; a laptop computer; a content streaming device; or the like. The computer system(s) **800** may correspond to an illustrative device configuration for the controller(s) or computer system(s) of FIGS. **1-7**. For example, the computer system(s) **800** may be a controller and may control one or more aspects of the conveyors on shuttles described in FIGS. **1-7** and/or may be configured to direct movement of shuttles along tracks to certain delivery locations.

[0069] The computer system(s) **800** may be configured to communicate with one or more servers, user devices, or the like. The computer system(s) **800** may be configured to control shuttle movement, conveyor movement, rail switches, identify shuttles, direct shuttles, move shuttles, and so forth.

[0070] The computer system(s) **800** may be configured to communicate via one or more networks. Such network(s) may include, but are not limited to, any one or more different types of communications networks such as, for example,

cable networks, public networks (e.g., the Internet), private networks (e.g., frame-relay networks), wireless networks, cellular networks, telephone networks (e.g., a public switched telephone network), or any other suitable private or public packet-switched or circuit-switched networks. Further, such network(s) may have any suitable communication range associated therewith and may include, for example, global networks (e.g., the Internet), metropolitan area networks (MANs), wide area networks (WANs), local area networks (LANs), or personal area networks (PANs). In addition, such network(s) may include communication links and associated networking devices (e.g., link-layer switches, routers, etc.) for transmitting network traffic over any suitable type of medium including, but not limited to, coaxial cable, twisted-pair wire (e.g., twisted-pair copper wire), optical fiber, a hybrid fiber-coaxial (HFC) medium, a microwave medium, a radio frequency communication medium, a satellite communication medium, or any combination thereof.

[0071] In an illustrative configuration, the computer system(s) **800** may include one or more processors (processor(s)) **802**, one or more memory devices **804** (also referred to herein as memory **804**), one or more input/output (I/O) interface(s) **806**, one or more network interface(s) **808**, one or more sensor(s) or sensor interface(s) **810**, one or more transceiver(s) **812**, one or more optional display(s) **814**, one or more optional microphone(s) **816**, and data storage **820**. The computer system(s) **800** may further include one or more bus(es) **818** that functionally couple various components of the computer system(s) **800**. The computer system(s) **800** may further include one or more antenna(s) **830** that may include, without limitation, a cellular antenna for transmitting or receiving signals to/from a cellular network infrastructure, an antenna for transmitting or receiving Wi-Fi signals to/from an access point (AP), a Global Navigation Satellite System (GNSS) antenna for receiving GNSS signals from a GNSS satellite, a Bluetooth antenna for transmitting or receiving Bluetooth signals, a Near Field Communication (NFC) antenna for transmitting or receiving NFC signals, and so forth. These various components will be described in more detail hereinafter.

[0072] The bus(es) **818** may include at least one of a system bus, a memory bus, an address bus, or a message bus, and may permit the exchange of information (e.g., data (including computer-executable code), signaling, etc.) between various components of the computer system(s) **800**. The bus(es) **818** may include, without limitation, a memory bus or a memory controller, a peripheral bus, an accelerated graphics port, and so forth. The bus(es) **818** may be associated with any suitable bus architecture including, without limitation, an Industry Standard Architecture (ISA), a Micro Channel Architecture (MCA), an Enhanced ISA (EISA), a Video Electronics Standards Association (VESA) architecture, an Accelerated Graphics Port (AGP) architecture, a Peripheral Component Interconnect (PCI) architecture, a PCI-Express architecture, a Personal Computer Memory Card International Association (PCMCIA) architecture, a Universal Serial Bus (USB) architecture, and so forth.

[0073] The memory **804** of the computer system(s) **800** may include volatile memory (memory that maintains its state when supplied with power) such as random access memory (RAM) and/or non-volatile memory (memory that maintains its state even when not supplied with power) such as read-only memory (ROM), flash memory, ferroelectric

RAM (FRAM), and so forth. Persistent data storage, as that term is used herein, may include non-volatile memory. In certain example embodiments, volatile memory may enable faster read/write access than non-volatile memory. However, in certain other example embodiments, certain types of non-volatile memory (e.g., FRAM) may enable faster read/write access than certain types of volatile memory.

[0074] In various implementations, the memory **804** may include multiple different types of memory such as various types of static random access memory (SRAM), various types of dynamic random access memory (DRAM), various types of unalterable ROM, and/or writeable variants of ROM such as electrically erasable programmable read-only memory (EEPROM), flash memory, and so forth. The memory **804** may include main memory as well as various forms of cache memory such as instruction cache(s), data cache(s), translation lookaside buffer(s) (TLBs), and so forth. Further, cache memory such as a data cache may be a multi-level cache organized as a hierarchy of one or more cache levels (L1, L2, etc.).

[0075] The data storage **820** may include removable storage and/or non-removable storage including, but not limited to, magnetic storage, optical disk storage, and/or tape storage. The data storage **820** may provide non-volatile storage of computer-executable instructions and other data. The memory **804** and the data storage **820**, removable and/or non-removable, are examples of computer-readable storage media (CRSM) as that term is used herein.

[0076] The data storage **820** may store computer-executable code, instructions, or the like that may be loadable into the memory **804** and executable by the processor(s) **802** to cause the processor(s) **802** to perform or initiate various operations. The data storage **820** may additionally store data that may be copied to the memory **804** for use by the processor(s) **802** during the execution of the computer-executable instructions. Moreover, output data generated as a result of execution of the computer-executable instructions by the processor(s) **802** may be stored initially in the memory **804**, and may ultimately be copied to the data storage **820** for non-volatile storage.

[0077] More specifically, the data storage **820** may store one or more operating systems (O/S) **822**; one or more database management systems (DBMS) **824**; and one or more program module(s), applications, engines, computer-executable code, scripts, or the like. Some or all of these module(s) may be sub-module(s). Any of the components depicted as being stored in the data storage **820** may include any combination of software, firmware, and/or hardware. The software and/or firmware may include computer-executable code, instructions, or the like that may be loaded into the memory **804** for execution by one or more of the processor(s) **802**. Any of the components depicted as being stored in the data storage **820** may support functionality described in reference to corresponding components named earlier in this disclosure.

[0078] The data storage **820** may further store various types of data utilized by the components of the computer system(s) **800**. Any data stored in the data storage **820** may be loaded into the memory **804** for use by the processor(s) **802** in executing computer-executable code. In addition, any data depicted as being stored in the data storage **820** may potentially be stored in one or more datastore(s) and may be accessed via the DBMS **824** and loaded in the memory **804** for use by the processor(s) **802** in executing computer-

executable code. The datastore(s) may include, but are not limited to, databases (e.g., relational, object-oriented, etc.), file systems, flat files, distributed datastores in which data is stored on more than one node of a computer network, peer-to-peer network datastores, or the like.

[0079] The processor(s) **802** may be configured to access the memory **804** and execute the computer-executable instructions loaded therein. For example, the processor(s) **802** may be configured to execute the computer-executable instructions of the various program module(s), applications, engines, or the like of the computer system(s) **800** to cause or facilitate various operations to be performed in accordance with one or more embodiments of the disclosure. The processor(s) **802** may include any suitable processing unit capable of accepting data as input, processing the input data in accordance with stored computer-executable instructions, and generating output data. The processor(s) **802** may include any type of suitable processing unit including, but not limited to, a central processing unit, a microprocessor, a Reduced Instruction Set Computer (RISC) microprocessor, a Complex Instruction Set Computer (CISC) microprocessor, a microcontroller, an Application Specific Integrated Circuit (ASIC), a Field-Programmable Gate Array (FPGA), a System-on-a-Chip (SoC), a digital signal processor (DSP), and so forth. Further, the processor(s) **802** may have any suitable microarchitecture design that includes any number of constituent components such as, for example, registers, multiplexers, arithmetic logic units, cache controllers for controlling read/write operations to cache memory, branch predictors, or the like. The microarchitecture design of the processor(s) **802** may be capable of supporting any of a variety of instruction sets.

[0080] Referring now to other illustrative components depicted as being stored in the data storage **820**, the O/S **822** may be loaded from the data storage **820** into the memory **804** and may provide an interface between other application software executing on the computer system(s) **800** and the hardware resources of the computer system(s) **800**. More specifically, the O/S **822** may include a set of computer-executable instructions for managing the hardware resources of the computer system(s) **800** and for providing common services to other application programs (e.g., managing memory allocation among various application programs). In certain example embodiments, the O/S **822** may control execution of the other program module(s). The O/S **822** may include any operating system now known or which may be developed in the future including, but not limited to, any server operating system, any mainframe operating system, or any other proprietary or non-proprietary operating system.

[0081] The DBMS **824** may be loaded into the memory **804** and may support functionality for accessing, retrieving, storing, and/or manipulating data stored in the memory **804** and/or data stored in the data storage **820**. The DBMS **824** may use any of a variety of database models (e.g., relational model, object model, etc.) and may support any of a variety of query languages. The DBMS **824** may access data represented in one or more data schemas and stored in any suitable data repository including, but not limited to, databases (e.g., relational, object-oriented, etc.), file systems, flat files, distributed datastores in which data is stored on more than one node of a computer network, peer-to-peer network datastores, or the like. In those example embodiments in which the computer system(s) **800** is a mobile device, the

DBMS **824** may be any suitable lightweight DBMS optimized for performance on a mobile device.

[0082] Referring now to other illustrative components of the computer system(s) **800**, the input/output (I/O) interface(s) **806** may facilitate the receipt of input information by the computer system(s) **800** from one or more I/O devices as well as the output of information from the computer system(s) **800** to the one or more I/O devices. The I/O devices may include any of a variety of components such as a display or display screen having a touch surface or touchscreen; an audio output device for producing sound, such as a speaker; an audio capture device, such as a microphone; an image and/or video capture device, such as a camera; a haptic unit; and so forth. Any of these components may be integrated into the computer system(s) **800** or may be separate. The I/O devices may further include, for example, any number of peripheral devices such as data storage devices, printing devices, and so forth.

[0083] The I/O interface(s) **806** may also include an interface for an external peripheral device connection such as universal serial bus (USB), FireWire, Thunderbolt, Ethernet port or other connection protocol that may connect to one or more networks. The I/O interface(s) **806** may also include a connection to one or more of the antenna(s) **830** to connect to one or more networks via a wireless local area network (WLAN) (such as Wi-Fi) radio, Bluetooth, ZigBee, and/or a wireless network radio, such as a radio capable of communication with a wireless communication network such as a Long Term Evolution (LTE) network, WiMAX network, 3G network, a ZigBee network, etc.

[0084] The computer system(s) **800** may further include one or more network interface(s) **808** via which the computer system(s) **800** may communicate with any of a variety of other systems, platforms, networks, devices, and so forth. The network interface(s) **808** may enable communication, for example, with one or more wireless routers, one or more host servers, one or more web servers, and the like via one or more networks.

[0085] The antenna(s) **830** may include any suitable type of antenna depending, for example, on the communications protocols used to transmit or receive signals via the antenna(s) **830**. Non-limiting examples of suitable antenna(s) may include directional antenna(s), non-directional antenna(s), dipole antenna(s), folded dipole antenna(s), patch antenna(s), multiple-input multiple-output (MIMO) antenna(s), or the like. The antenna(s) **830** may be communicatively coupled to one or more transceivers **812** or radio components to which or from which signals may be transmitted or received.

[0086] As previously described, the antenna(s) **830** may include a cellular antenna configured to transmit or receive signals in accordance with established standards and protocols, such as Global System for Mobile Communications (GSM), 3G standards (e.g., Universal Mobile Telecommunications System (UMTS), Wideband Code Division Multiple Access (W-CDMA), CDMA2000, etc.), 4G standards (e.g., Long-Term Evolution (LTE), WiMax, etc.), direct satellite communications, or the like.

[0087] The antenna(s) **830** may additionally, or alternatively, include a Wi-Fi antenna configured to transmit or receive signals in accordance with established standards and protocols, such as the IEEE 802.11 family of standards, including via 2.4 GHz channels (e.g., 802.11b, 802.11g, 802.11n), 5 GHz channels (e.g., 802.11n, 802.11ac), or 60

GHz channels (e.g., 802.11ad). In alternative example embodiments, the antenna(s) **830** may be configured to transmit or receive radio frequency signals within any suitable frequency range forming part of the unlicensed portion of the radio spectrum.

[0088] The antenna(s) **830** may additionally, or alternatively, include a GNSS antenna configured to receive GNSS signals from three or more GNSS satellites carrying time-position information to triangulate a position therefrom. Such a GNSS antenna may be configured to receive GNSS signals from any current or planned GNSS such as, for example, the Global Positioning System (GPS), the GLO-NASS System, the Compass Navigation System, the Galileo System, or the Indian Regional Navigational System.

[0089] The transceiver(s) **812** may include any suitable radio component(s) for—in cooperation with the antenna(s) **830**—transmitting or receiving radio frequency (RF) signals in the bandwidth and/or channels corresponding to the communications protocols utilized by the computer system(s) **800** to communicate with other devices. The transceiver(s) **812** may include hardware, software, and/or firmware for modulating, transmitting, or receiving—potentially in cooperation with any of antenna(s) **830**—communications signals according to any of the communications protocols discussed above including, but not limited to, one or more Wi-Fi and/or Wi-Fi direct protocols, as standardized by the IEEE 802.11 standards, one or more non-Wi-Fi protocols, or one or more cellular communications protocols or standards. The transceiver(s) **812** may further include hardware, firmware, or software for receiving GNSS signals. The transceiver(s) **812** may include any known receiver and baseband suitable for communicating via the communications protocols utilized by the computer system(s) **800**. The transceiver(s) **812** may further include a low noise amplifier (LNA), additional signal amplifiers, an analog-to-digital (A/D) converter, one or more buffers, a digital baseband, or the like.

[0090] The sensor(s)/sensor interface(s) **810** may include or may be capable of interfacing with any suitable type of sensing device such as, for example, inertial sensors, force sensors, thermal sensors, photocells, and so forth. Example types of inertial sensors may include accelerometers (e.g., MEMS-based accelerometers), gyroscopes, and so forth.

[0091] The optional display(s) **814** may be configured to output light and/or render content. The optional speaker(s)/microphone(s) **816** may be any device configured to receive analog sound input or voice data.

[0092] It should be appreciated that the program module(s), applications, computer-executable instructions, code, or the like depicted in FIG. **8** as being stored in the data storage **820** are merely illustrative and not exhaustive and that processing described as being supported by any particular module may alternatively be distributed across multiple module(s) or performed by a different module. In addition, various program module(s), script(s), plug-in(s), Application Programming Interface(s) (API(s)), or any other suitable computer-executable code hosted locally on the computer system(s) **800**, and/or hosted on other computing device(s) accessible via one or more networks, may be provided to support functionality provided by the program module(s), applications, or computer-executable code depicted in FIG. **8** and/or additional or alternate functionality. Further, functionality may be modularized differently such that processing described as being supported collectively by the collection of program module(s) depicted in

FIG. **8** may be performed by a fewer or greater number of module(s), or functionality described as being supported by any particular module may be supported, at least in part, by another module. In addition, program module(s) that support the functionality described herein may form part of one or more applications executable across any number of systems or devices in accordance with any suitable computing model such as, for example, a client-server model, a peer-to-peer model, and so forth. In addition, any of the functionality described as being supported by any of the program module(s) depicted in FIG. **8** may be implemented, at least partially, in hardware and/or firmware across any number of devices.

[0093] It should further be appreciated that the computer system(s) **800** may include alternate and/or additional hardware, software, or firmware components beyond those described or depicted without departing from the scope of the disclosure. More particularly, it should be appreciated that software, firmware, or hardware components depicted as forming part of the computer system(s) **800** are merely illustrative and that some components may not be present or additional components may be provided in various embodiments. While various illustrative program module(s) have been depicted and described as software module(s) stored in the data storage **820**, it should be appreciated that functionality described as being supported by the program module(s) may be enabled by any combination of hardware, software, and/or firmware. It should further be appreciated that each of the above-mentioned module(s) may, in various embodiments, represent a logical partitioning of supported functionality. This logical partitioning is depicted for ease of explanation of the functionality and may not be representative of the structure of software, hardware, and/or firmware for implementing the functionality. Accordingly, it should be appreciated that functionality described as being provided by a particular module may, in various embodiments, be provided at least in part by one or more other module(s). Further, one or more depicted module(s) may not be present in certain embodiments, while in other embodiments, additional module(s) not depicted may be present and may support at least a portion of the described functionality and/or additional functionality. Moreover, while certain module(s) may be depicted and described as sub-module(s) of another module, in certain embodiments, such module(s) may be provided as independent module(s) or as sub-module(s) of other module(s).

[0094] Program module(s), applications, or the like disclosed herein may include one or more software components including, for example, software objects, methods, data structures, or the like. Each such software component may include computer-executable instructions that, responsive to execution, cause at least a portion of the functionality described herein (e.g., one or more operations of the illustrative methods described herein) to be performed.

[0095] A software component may be coded in any of a variety of programming languages. An illustrative programming language may be a lower-level programming language such as an assembly language associated with a particular hardware architecture and/or operating system platform. A software component comprising assembly language instructions may require conversion into executable machine code by an assembler prior to execution by the hardware architecture and/or platform.

[0096] Another example programming language may be a higher-level programming language that may be portable

across multiple architectures. A software component comprising higher-level programming language instructions may require conversion to an intermediate representation by an interpreter or a compiler prior to execution.

[0097] Other examples of programming languages include, but are not limited to, a macro language, a shell or command language, a job control language, a script language, a database query or search language, or a report writing language. In one or more example embodiments, a software component comprising instructions in one of the foregoing examples of programming languages may be executed directly by an operating system or other software component without having to be first transformed into another form.

[0098] A software component may be stored as a file or other data storage construct. Software components of a similar type or functionally related may be stored together such as, for example, in a particular directory, folder, or library. Software components may be static (e.g., pre-established or fixed) or dynamic (e.g., created or modified at the time of execution).

[0099] Software components may invoke or be invoked by other software components through any of a wide variety of mechanisms. Invoked or invoking software components may comprise other custom-developed application software, operating system functionality (e.g., device drivers, data storage (e.g., file management) routines, other common routines and services, etc.), or third-party software components (e.g., middleware, encryption, or other security software, database management software, file transfer or other network communication software, mathematical or statistical software, image processing software, and format translation software).

[0100] Software components associated with a particular solution or system may reside and be executed on a single platform or may be distributed across multiple platforms. The multiple platforms may be associated with more than one hardware vendor, underlying chip technology, or operating system. Furthermore, software components associated with a particular solution or system may be initially written in one or more programming languages, but may invoke software components written in another programming language.

[0101] Computer-executable program instructions may be loaded onto a special-purpose computer or other particular machine, a processor, or other programmable data processing apparatus to produce a particular machine, such that execution of the instructions on the computer, processor, or other programmable data processing apparatus causes one or more functions or operations specified in the flow diagrams to be performed. These computer program instructions may also be stored in a computer-readable storage medium (CRSM) that upon execution may direct a computer or other programmable data processing apparatus to function in a particular manner, such that the instructions stored in the computer-readable storage medium produce an article of manufacture including instruction means that implement one or more functions or operations specified in the flow diagrams. The computer program instructions may also be loaded onto a computer or other programmable data processing apparatus to cause a series of operational elements or steps to be performed on the computer or other programmable apparatus to produce a computer-implemented process.

[0102] Additional types of CRSM that may be present in any of the devices described herein may include, but are not limited to, programmable random access memory (PRAM), SRAM, DRAM, RAM, ROM, electrically erasable programmable read-only memory (EEPROM), flash memory or other memory technology, compact disc read-only memory (CD-ROM), digital versatile disc (DVD) or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the information and which can be accessed. Combinations of any of the above are also included within the scope of CRSM. Alternatively, computer-readable communication media (CRCM) may include computer-readable instructions, program module(s), or other data transmitted within a data signal, such as a carrier wave, or other transmission. However, as used herein, CRSM does not include CRCM.

[0103] Although embodiments have been described in language specific to structural features and/or methodological acts, it is to be understood that the disclosure is not necessarily limited to the specific features or acts described. Rather, the specific features and acts are disclosed as illustrative forms of implementing the embodiments. Conditional language, such as, among others, “can,” “could,” “might,” or “may,” unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments could include, while other embodiments do not include, certain features, elements, and/or steps. Thus, such conditional language is not generally intended to imply that features, elements, and/or steps are in any way required for one or more embodiments or that one or more embodiments necessarily include logic for deciding, with or without user input or prompting, whether these features, elements, and/or steps are included or are to be performed in any particular embodiment.

1. A system comprising:

- a set of rails that form a track;
- a shuttle configured to transport individual items from a pickup location to a delivery location using the set of rails, the shuttle comprising:
 - a bidirectional conveyor;
 - a first induction coil; and
 - a data receiver module configured to receive command data indicative of a direction to actuate the conveyor;
- a second induction coil disposed at a first location along the track, wherein the second induction coil is configured to interact with the first induction coil to power the conveyor and the data receiver module;
- a first data transmitter module disposed along the track adjacent to the second induction coil, the first data transmitter module configured to transmit the command data;
- a third induction coil disposed at a second location along the track, wherein the third induction coil is configured to interact with the first induction coil to power the conveyor and the data receiver module; and
- a second data transmitter module disposed along the track adjacent to the third induction coil, the second data transmitter module configured to transmit the command data;

wherein the shuttle does not comprise an onboard power source coupled to the conveyor, and wherein the con-

veyor is inoperable along the track between the first location and the second location due to a lack of power.

2. The system of claim 1, wherein the command data is transmitted via the second induction coil or the third induction coil.

3. The system of claim 1, wherein the second induction coil interacts with the first induction coil by imparting an electric current to the first induction coil when the first induction coil is within a distance of the second induction coil.

4. The system of claim 1, wherein the shuttle further comprises a permanent magnet coupled to a lower surface of the shuttle, and wherein the system further comprises:

a set of electromagnets disposed along the set of rails;
wherein the permanent magnet is configured to engage with the set of electromagnets to propel the shuttle.

5. A system configured to transport items, the system comprising:

a track;
a first data transmitter module disposed along the track, the first data transmitter module configured to transmit command data;
a shuttle configured to move along the track, the shuttle comprising:
a conveyor;
a data receiver module to receive the command data; and
a first induction coil; and

a second induction coil disposed at a first location along the track, wherein the second induction coil is configured to interact with the first induction coil to power the conveyor;

wherein the shuttle does not comprise an onboard power source coupled to the conveyor, and wherein the conveyor is inoperable along the track between the first location and a second location due to a lack of power.

6. The system of claim 5, wherein the shuttle is configured to receive command data representing one or more of: a direction the conveyor is to be actuated, a length of time the conveyor is to be actuated, or a stop position for the shuttle relative to the track.

7. The system of claim 5, wherein the conveyor is configured to move bidirectionally.

8. (canceled)

9. The system of claim 5, wherein the command data is transmitted via the second induction coil.

10. The system of claim 5, further comprising:

a third induction coil disposed at the second location along the track, wherein the third induction coil is configured to interact with the first induction coil to power the conveyor and the data receiver module; and
a second data transmitter module disposed along the track, the second data transmitter module configured to transmit the command data.

11. The system of claim 5, wherein the data receiver module is inoperable along the track between the first location and the second location due to a lack of power.

12. The system of claim 11, wherein the shuttle is configured to transport items from a pickup location to a delivery location using the track, the system further comprising:

a remote computer system configured to direct the shuttle from the pickup location to the delivery location, wherein the delivery location is aligned with the second induction coil.

13. The system of claim 12, wherein the data receiver module and the first data transmitter module are transceivers; and

wherein the data receiver module or the first data transmitter module are further configured to transmit a shuttle status indicator to the remote computer system.

14. The system of claim 5, wherein the shuttle further comprises a permanent magnet coupled to a lower surface of the shuttle, and wherein the system further comprises:

a set of electromagnets disposed along the track;
wherein the permanent magnet is configured to engage with the set of electromagnets to propel the shuttle.

15. The system of claim 5, wherein the second induction coil interacts with the first induction coil by imparting an electric current to the first induction coil when the first induction coil is within a distance of the second induction coil.

16. An item delivery system comprising:

a track;
a first data transmitter module disposed along the track, the first data transmitter module configured to transmit command data;
a shuttle configured to move along the track, the shuttle comprising:
a conveyor;
a data receiver module to receive the command data; and
a first induction coil;
a second induction coil disposed at a first location along the track, wherein the second induction coil is configured to interact with the first induction coil to power the conveyor; and
a third induction coil disposed at a second location along the track, wherein the third induction coil is configured to interact with the first induction coil to power the conveyor;

wherein the conveyor is inoperable along the track between the first location and the second location due to a lack of power.

17. The item delivery system of claim 16, further comprising:

a second data transmitter module disposed along the track, the second data transmitter module configured to transmit the command data.

18. The item delivery system of claim 16, wherein the command data is transmitted via the second induction coil.

19. The item delivery system of claim 16, wherein the shuttle is configured to transport items from a pickup location to a delivery location using the track, the item delivery system further comprising:

a remote computer system configured to direct the shuttle from the pickup location to the delivery location, wherein the delivery location is aligned with the second induction coil.

20. The item delivery system of claim 16, wherein the shuttle further comprises a permanent magnet coupled to a lower surface of the shuttle, and wherein the system further comprises:

a set of electromagnets disposed along the track;
wherein the permanent magnet is configured to engage
with the set of electromagnets to propel the shuttle.

* * * * *