




US 20230128630A1

(19) **United States**(12) **Patent Application Publication**
Teeneti et al.(10) **Pub. No.: US 2023/0128630 A1**(43) **Pub. Date: Apr. 27, 2023**(54) **UNFOLDER-BASED SINGLE-STAGE AC-AC
CONVERSION SYSTEM***H02M 1/42* (2006.01)*H02M 7/5395* (2006.01)(71) Applicants: **Chakridhar Reddy Teeneti**, North
Logan, UT (US); **Regan A. Zane**, Hyde
Park, UT (US); **Hongjie Wang**, North
Logan, UT (US); **Dorai Babu
Yelaverthi**, Raleigh, NC (US)(52) **U.S. Cl.**CPC *H02M 5/2932* (2021.05); *H02M 5/225*
(2013.01); *H02M 1/4216* (2013.01); *H02M*
7/5395 (2013.01); *H02M 1/007* (2021.05)(72) Inventors: **Chakridhar Reddy Teeneti**, North
Logan, UT (US); **Regan A. Zane**, Hyde
Park, UT (US); **Hongjie Wang**, North
Logan, UT (US); **Dorai Babu
Yelaverthi**, Raleigh, NC (US)(73) Assignee: **Utah State University**, Logan, UT
(US)(21) Appl. No.: **17/499,735**(22) Filed: **Oct. 12, 2021****Publication Classification**(51) **Int. Cl.***H02M 5/293* (2006.01)*H02M 5/22* (2006.01)(57) **ABSTRACT**

An power converter includes an unfolder connected to a three-phase source and has an output connection with a positive terminal, a negative terminal and a neutral terminal. The unfolder creates two unipolar piece-wise sinusoidal DC voltage waveforms offset by a half of a period. A three-input converter connected to the unfolder produces a quasi-sinusoidal output voltage across output terminals. Switches of the converter selectively connect the positive, negative and neutral inputs across the output terminals. A PWM controller controls a first duty ratio and a second duty ratio for the converter based on a phase angle of the source and a modulation index generated from an error signal related to a control variable. The duty ratios are time varying with a fundamental frequency of the source. The modulation index relates to output voltage of the converter, peak voltage or current of the source and/or peak current at the output terminals.






FIG. 1





FIG. 2






FIG. 4




FIG. 5




FIG. 6






FIG. 7




Plot of phase voltage (v_{an}), and balanced 3-phase line currents (i_a , i_b and i_c)

FIG. 8




Plot of voltages and currents of the grid (v_{an} , i_a) and the resonant tank (v_{xy} , I_{Pri}), demonstrating the PFC action and tank voltage/current control

FIG. 9



Plot of soft DC-link voltages (v_{po} , v_{on}) and currents (i_p , i_n)

FIG. 10



Plot of 5-level tank voltage (v_{xy}) at unequal d_p and d_n values

FIG. 11


Plot of 3-level tank voltage (v_{xy}) at equal d_{pu} and d_{on}

FIG. 12




FIG. 13

UNFOLDER-BASED SINGLE-STAGE AC-AC CONVERSION SYSTEM

GOVERNMENT LICENSE RIGHTS

[0001] This invention was made with government support under contract #DE-EE0008803 awarded by the Department of Energy. The government has certain rights in the invention.

FIELD

[0002] This invention relates to switching converters and more particularly relates to an unfold-based single-stage AC to AC converter.

BACKGROUND

[0003] With the ongoing electrification of heavy-duty vehicles, there is a need for high-power charging systems. Wireless Power Transfer (“WPT”) offers a convenient and safe way of charging electric vehicles by eliminating the use of high-voltage and high-current connectors. Conventional WPT converters use a two-stage approach consisting of an input Power Factor Correction (“PFC”) stage with a stiff DC-link output followed by an inverter stage to drive a resonant tank. The stiff DC-link & couples the two power stages and offers easier and faster control. However, the limitations of this method include the need for bulky electrolytic DC-link capacitors and hard switching operation of the PFC stage. To overcome these limitations, single-stage AC-AC converters have been increasingly explored for conductive charging and WPT applications. Unlike in a two-stage converter, a single converter carries out both the PEC and the inverter action in a single-stage system. However, most existing single-stage systems have serious drawbacks. In addition, other applications that drive a resonant circuit also typically include a two-stage approach and also include the same problems as WPT applications. For example, the two-stage approach is also often used for conductive charge applications with a tightly coupled transformer and other applications like power supplies for welding.

SUMMARY

[0004] A power converter for an unfold-based single AC to AC converter includes an unfold with an input connection that has three input terminals that connect to a three-phase alternating current (“AC”) power source and that has an output connection with a positive terminal, a negative terminal and a neutral terminal. The unfold unfolds bipolar AC voltages into two unipolar piece-wise sinusoidal direct current (“DC”) voltage waveforms offset from each other by a half of a period. The power converter includes a three-input converter that produces a quasi-sinusoidal output voltage across output terminals at an output frequency. The three-input converter has a positive input connection connected to the positive terminal, a negative input connection connected to the negative terminal and a neutral input connection connected to the neutral terminal. The three-input converter includes switches that selectively connect the positive, negative and neutral input connections across the output terminals. The power converter includes a pulse-width modulation controller configured to control a first duty ratio d_{po} and a second duty ratio d_{on} for the three-input converter as a function of a phase angle of a phase of the

three-phase AC power source and a modulation index generated from an error signal related to a control variable compared to a reference. The first duty ratio d_{po} and the second duty ratio d_{on} are time varying at a rate related to a fundamental frequency of the three-phase AC power source, and the modulation index relates to output voltage of the three-input converter, a peak voltage of the three-phase AC power source, a peak current of the three-phase AC power source and/or a peak current of output current at the output terminals.

[0005] A system for an unfold-based single AC to AC converter includes an unfold with an input connection that has three input terminals that connect to a three-phase AC power source and that has an output connection with a positive terminal, a negative terminal and a neutral terminal. The unfold unfolds bipolar AC voltages into two unipolar piece-wise sinusoidal DC voltage waveforms offset from each other by a half of a period. The system includes a three-input converter that produces a quasi-sinusoidal output voltage across output terminals at an output frequency. The three-input converter includes a positive input connection connected to the positive terminal, a negative input connection connected to the negative terminal and a neutral input connection connected to the neutral terminal. The three-input converter includes switches that selectively connect the positive, negative and neutral input connections across the output terminals. The system includes a wireless power transfer (“WPT”) primary pad coupled to output terminals of the three-input converter, a WPT secondary pad electromagnetically coupled to the WPT primary pad over a gap, and a rectifier section coupled to an output of the WPT secondary pad. The rectifier section has an output. The system includes a pulse-width modulation controller configured to control a first duty ratio d_{po} and a second duty ratio d_{on} for the three-input converter as a function of a phase angle of a phase of the three-phase AC power source and a modulation index generated from an error signal related to a converter output variable compared to a reference. The converter output variable is from the output of the rectifier section. The first duty ratio d_{po} and the second duty ratio d_{on} are time varying at a rate related to a fundamental frequency of the three-phase AC power source, and the modulation index relates to output voltage of the three-input converter, a peak voltage of the three-phase AC power source, a peak current of the three-phase AC power source and/or a peak current of output current at the output terminals.

[0006] A method for operation of an unfold-based single AC to AC converter includes receiving input power at three input terminals of an unfold. The three input terminals receive the power from a three-phase AC power source and, the unfold includes an output connection with a positive terminal, a negative terminal and a neutral terminal. The unfold unfolds bipolar AC voltages into two unipolar piece-wise sinusoidal DC voltage waveforms offset from each other by a half of a period. The method includes receiving output power from the unfold at a three-input converter that produces a quasi-sinusoidal output voltage across output terminals at an output frequency. The three-input converter receives the output power at a positive input connection connected to the positive terminal, a negative input connection connected to the negative terminal and a neutral input connection connected to the neutral terminal. The three-input converter includes switches that selectively connect the positive, negative and neutral input connections

across the output terminals. The method includes controlling, with a pulse-width modulation controller, a first duty ratio d_{po} and a second duty ratio d_{on} for the three-input converter as a function of a phase angle of a phase of the three-phase AC power source and a modulation index generated from an error signal related to a control variable compared to a reference. The first duty ratio d_{po} and the second duty ratio d_{on} are time varying at a rate related to a fundamental frequency of the three-phase AC power source, and the modulation index relates to output voltage of the three-input converter, a peak voltage of the three-phase AC power source, a peak current of the three-phase AC power source and/or a peak current of output current at the output terminals.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] In order that the advantages of the invention will be readily understood, a more particular description of the invention briefly described above will be rendered by reference to specific embodiments that are illustrated in the appended drawings. Understanding that these drawings depict only typical embodiments of the invention and are not therefore to be considered to be limiting of its scope, the invention will be described and explained with additional specificity and detail through the use of the accompanying drawings, in which:

[0008] FIG. 1 is a schematic block diagram illustrating one embodiment of an unfold-based single-stage AC to AC converter;

[0009] FIG. 2 is a schematic block diagram illustrating one embodiment of an unfold-based single-stage AC to AC converter implemented in a wireless power transfer system;

[0010] FIG. 3 is a schematic block diagram illustrating one embodiment of an unfold along with a switching sequence and ideal waveforms of a three-phase unfold operating at unity power factor;

[0011] FIG. 4 is a modulation scheme of a three-input converter for a first duty ratio d_{po} greater than a second duty ratio d_{on} and for the first duty ratio d_{po} less than the second duty ratio d_{on} ;

[0012] FIG. 5 are waveforms of the first duty ratio d_{po} and the second duty ratio d_{on} for different modulation indexes M ;

[0013] FIG. 6 is a waveform diagram of a simulation result for a step load change from 50 kW to 100 kW;

[0014] FIG. 7 is a waveform diagram of simulation results of a three-input converter at 100 kW;

[0015] FIG. 8 is a plot of experimental results of phase voltage (v), and balanced three-phase line currents (i_a , i_b and i_c) at 1 kW output power where the power factor is 0.99 and the total harmonic distortion is 1.4%;

[0016] FIG. 9 is a plot of experimental results of voltages and currents at the input of the unfold (v_{an} , i_a) and at the output of the three-phase converter (v_{xy} , I_{xy}) demonstrating power factor correction and output voltage and current control;

[0017] FIG. 10 is a plot of experimental results of soft DC-link voltages (v_{po} , V_{on}) and currents (i_p , i_n);

[0018] FIG. 11 is a plot of experimental results of a five-level output voltage of the three-input converter (v_{xy}) at unequal first duty ratio d_{po} and d_{on} values;

[0019] FIG. 12 is a plot of experimental results of a five-level output voltage of the three-input converter (v_{xy}) at equal first duty ratio d_{po} and d_{on} values; and

[0020] FIG. 13 is a schematic flowchart diagram illustrating one embodiment of a method for using an unfold-based single-stage AC to AC converter.

DETAILED DESCRIPTION

[0021] Reference throughout this specification to “one embodiment,” “an embodiment,” or similar language means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment. Thus, appearances of the phrases “in one embodiment,” “in an embodiment,” and similar language throughout this specification may, but do not necessarily, all refer to the same embodiment, but mean “one or more but not all embodiments” unless expressly specified otherwise. The terms “including,” “comprising,” “having,” and variations thereof mean “including but not limited to” unless expressly specified otherwise. An enumerated listing of items does not imply that any or all of the items are mutually exclusive and/or mutually inclusive, unless expressly specified otherwise. The terms “a,” “an,” and “the” also refer to “one or more” unless expressly specified otherwise.

[0022] Furthermore, the described features, advantages, and characteristics of the embodiments may be combined in any suitable manner. One skilled in the relevant art will recognize that the embodiments may be practiced without one or more of the specific features or advantages of a particular embodiment. In other instances, additional features and advantages may be recognized in certain embodiments that may not be present in all embodiments.

[0023] These features and advantages of the embodiments will become more fully apparent from the following description and appended claims, or may be learned by the practice of embodiments as set forth hereinafter. As will be appreciated by one skilled in the art, aspects of the present invention may be embodied as a system, method, and/or computer program product. Accordingly, aspects of the present invention may take the form of an entirely hardware embodiment, an entirely software embodiment (including firmware, resident software, micro-code, etc.) or an embodiment combining software and hardware aspects that may all generally be referred to herein as a “circuit,” “module,” or “system.” Furthermore, aspects of the present invention may take the form of a computer program product embodied in one or more computer readable medium(s) having program code embodied thereon.

[0024] Many of the functional units described in this specification have been labeled as modules, in order to more particularly emphasize their implementation independence. For example, a module may be implemented as a hardware circuit comprising custom very large scale integrated (“VLSI”) circuits or gate arrays, off-the-shelf semiconductor devices such as logic chips, transistors, or other discrete components. A module may also be implemented in programmable hardware devices such as a field programmable gate array (“FPGA”), programmable array logic, programmable logic devices or the like.

[0025] Modules may also be implemented in software for execution by various types of processors and/or controllers. As used herein, execution of program code by a processor also refers to execution by a controller. An identified module of program code may, for instance, comprise one or more physical or logical blocks of computer instructions which may, for instance, be organized as an object, procedure, or function. Nevertheless, the executables of an identified

module need not be physically located together, but may comprise disparate instructions stored in different locations which, when joined logically together, comprise the module and achieve the stated purpose for the module.

[0026] Indeed, a module of program code may be a single instruction, or many instructions, and may even be distributed over several different code segments, among different programs, and across several memory devices. Similarly, operational data may be identified and illustrated herein within modules, and may be embodied in any suitable form and organized within any suitable type of data structure. The operational data may be collected as a single data set, or may be distributed over different locations including over different storage devices, and may exist, at least partially, merely as electronic signals on a system or network. Where a module or portions of a module are implemented in software, the program code may be stored and/or propagated on in one or more computer readable medium(s).

[0027] The computer program product may include a computer readable storage medium (or media) having computer readable program instructions thereon for causing a processor/controller to carry out aspects of the present invention.

[0028] The computer readable storage medium is a tangible device that can retain and store instructions for use by an instruction execution device. The computer readable storage medium may be, for example, but is not limited to, an electronic storage device, a magnetic storage device, an optical storage device, an electromagnetic storage device, a semiconductor storage device, or any suitable combination of the foregoing. A non-exhaustive list of more specific examples of the computer readable storage medium includes the following: a portable computer diskette, a hard disk, a random access memory (“RAM”), a read-only memory (“ROM”), an erasable programmable read-only memory (“EPROM” or Flash memory), a static random access memory (“SRAM”), a portable compact disc read-only memory (“CD-ROM”), a digital versatile disk (“DVD”), a memory stick, a floppy disk, a mechanically encoded device such as punch-cards or raised structures in a groove having instructions recorded thereon, and any suitable combination of the foregoing. A computer readable storage medium, as used herein, is not to be construed as being transitory signals per se, such as radio waves or other freely propagating electromagnetic waves, electromagnetic waves propagating through a waveguide or other transmission media (e.g., light pulses passing through a fiber-optic cable), or electrical signals transmitted through a wire.

[0029] The computer readable program code may execute entirely on a user’s computing device/controller, partly on the user’s computing device/controller, as a stand-alone software package, or partly on the user’s computing device/controller and partly on a remote computer. In some embodiments, electronic circuitry including, for example, programmable logic circuitry, field-programmable gate arrays (“FPGA”), or programmable logic arrays (“PLA”) may execute the computer readable program instructions by utilizing state information of the computer readable program instructions to personalize the electronic circuitry, in order to perform aspects of the present invention.

[0030] As used herein, a list with a conjunction of “and/or” includes any single item in the list or a combination of items in the list. For example, a list of A, B and/or C includes only A, only B, only C, a combination of A and B, a

combination of B and C, a combination of A and C or a combination of A, B and C. As used herein, a list using the terminology “one or more of” includes any single item in the list or a combination of items in the list. For example, one or more of A, B and C includes only A, only B, only C, a combination of A and B, a combination of B and C, a combination of A and C or a combination of A, B and C. As used herein, a list using the terminology “one of” includes one and only one of any single item in the list. For example, “one of A, B and C” includes only A, only B or only C and excludes combinations of A, B and C.

[0031] An power converter for an unfold-based single AC to AC converter includes an unfold with an input connection that has three input terminals that connect to a three-phase alternating current (“AC”) power source and that has an output connection with a positive terminal, a negative terminal and a neutral terminal. The unfold unfolds bipolar AC voltages into two unipolar piece-wise sinusoidal direct current (“DC”) voltage waveforms offset from each other by a half of a period. The power converter includes a three-input converter that produces a quasi-sinusoidal output voltage across output terminals at an output frequency. The three-input converter has a positive input connection connected to the positive terminal, a negative input connection connected to the negative terminal and a neutral input connection connected to the neutral terminal. The three-input converter includes switches that selectively connect the positive, negative and neutral input connections across the output terminals. The power converter includes a pulse-width modulation controller configured to control a first duty ratio d_{po} and a second duty ratio d_{on} for the three-input converter as a function of a phase angle of a phase of the three-phase AC power source and a modulation index generated from an error signal related to a control variable compared to a reference. The first duty ratio d_{po} and the second duty ratio d are time varying at a rate related to a fundamental frequency of the three-phase AC power source, and the modulation index relates to output voltage of the three-input converter, a peak voltage of the three-phase AC power source, a peak current of the three-phase AC power source and/or a peak current of output current at the output terminals.

[0032] In some embodiments, a modulation scheme for switches of the three-input converter depends on the first duty ratio d_{po} and the second duty ratio d . In other embodiments, the modulation scheme includes a first modulation scheme when d_{po} is greater than d and a second modulation scheme when d is greater than d_{po} . In other embodiments, the modulation scheme includes switching of the switches of the three-input converter to produce a positive output voltage at the output terminals during a first half of a switching period of the three-input converter and to produce a negative output voltage at the output terminals during a second half of a switching period of the three-input converter.

[0033] In some embodiments, equations defining the first duty ratio d_{po} and the second duty ratio d_{on} include first sector equations for a first sector and second sector equations for a second sector. The first sector is when voltage from the positive terminal to the neutral terminal v_{po} is decreasing and voltage from the neutral terminal to the negative terminal v_{on} is increasing and the second sector is when v_{po} is increasing and v_{on} is decreasing. In other embodiments, first and second sector equations for the first duty ratio d_{po} and the second duty ratio d_{on} are defined as:

$$\begin{aligned}
 d_{po} &= \frac{2}{\pi} \sin^{-1}(M \cos \theta_{grid}) \text{ for the first sector;} \\
 d_{po} &= \frac{2}{\pi} \sin^{-1}\left(M \cos\left(\theta_{grid} - \frac{\pi}{6}\right)\right) \text{ for the second sector;} \\
 d_{on} &= \frac{2}{\pi} \sin^{-1}(M \sin(\theta_{grid})) \text{ for the first sector; and} \\
 d_{on} &= \frac{2}{\pi} \sin^{-1}\left(M \sin\left(\theta_{grid} - \frac{\pi}{6}\right)\right) \text{ for the second sector,}
 \end{aligned}$$

where θ_{grid} is the phase angle of the phase of the three-phase AC power source, and M is the modulation index.

[0034] In some embodiments, the modulation index M is:

$$M = \frac{V_{xy1(rms)}}{V_{xy1(rms)max}} = \frac{V_{xy1(rms)}\pi}{\sqrt{6} V_m} = \frac{I_m\pi}{2I_{Lsm}\cos(\psi)}$$

where:

[0035] $V_{xy1(rms)}$ is a root-mean-square (“rms”) of the fundamental component of the output voltage of the three-input converter;

[0036] $V_{xy1(rms)max}$ is a maximum rms voltage of the three-input converter;

[0037] V_m is the peak voltage of the three-phase AC power source;

[0038] I_{Lsm} is the peak current of the three-phase AC power source;

[0039] I_{Lsm} is the peak current of output current at the output terminals; and

[0040] Ψ is the phase angle between the fundamental components of v_{xy} and i_{xy} .

In other embodiments, the pulse-width modulation controller controls switching of the three-input converter to maintain unity power factor at the input to the unfolded. In other embodiments, a switching frequency of the three-input converter is at least two orders of magnitude higher than a fundamental frequency of the three-phase AC power source.

[0041] In some embodiments, d_{po} and d_{on} are centered at a phase angle of 90 degrees of a switching period of the three-input converter for a positive output voltage at the output terminals and are centered at a phase angle of 270 degrees of the switching period of the three-input converter for a negative output voltage at the output terminals. In other embodiments, the output terminals of the three-input converter are connected to a resonant section which connects to a rectification section and an output of the rectification section is a DC voltage and the control variable is for controlling the output of the rectification section. In other embodiments, the resonant section includes a transmission pad separated from a receiver pad on a mobile device, where the transmission pad transfers power over a gap to the receiver pad as part of a wireless power transmission system, the resonant section includes a transformer and the power converter is a DC power supply, and the resonant section includes output terminals and the power converter is an inverter.

[0042] A system for an unfolded-based single AC to AC converter includes an unfolded with an input connection that has three input terminals that connect to a three-phase AC power source and that has an output connection with a positive terminal, a negative terminal and a neutral terminal. The unfolded unfolds bipolar AC voltages into two unipolar

piece-wise sinusoidal DC voltage waveforms offset from each other by a half of a period. The system includes a three-input converter that produces a quasi-sinusoidal output voltage across output terminals at an output frequency. The three-input converter includes a positive input connection connected to the positive terminal, a negative input connection connected to the negative terminal and a neutral input connection connected to the neutral terminal. The three-input converter includes switches that selectively connect the positive, negative and neutral input connections across the output terminals. The system includes a wireless power transfer (“WPT”) primary pad coupled to output terminals of the three-input converter, a WPT secondary pad electromagnetically coupled to the WPT primary pad over a gap, and a rectifier section coupled to an output of the WPT secondary pad. The rectifier section has an output. The system includes a pulse-width modulation controller configured to control a first duty ratio d_{po} and a second duty ratio d_{on} for the three-input converter as a function of a phase angle of a phase of the three-phase AC power source and a modulation index generated from an error signal related to a converter output variable compared to a reference. The converter output variable is from the output of the rectifier section. The first duty ratio d_{po} and the second duty ratio d_{on} are time varying at a rate related to a fundamental frequency of the three-phase AC power source, and the modulation index relates to output voltage of the three-input converter, a peak voltage of the three-phase AC power source, a peak current of the three-phase AC power source and/or a peak current of output current at the output terminals.

[0043] In some embodiments, a modulation scheme for switches of the three-input converter depends on the first duty ratio d_{po} and the second duty ratio d_{on} . The modulation scheme includes a first modulation scheme when d_{po} is greater than d and a second modulation scheme when d_{on} is greater than d_{po} , and the modulation scheme includes switching of the switches of the three-input converter to produce a positive output voltage at the output terminals during a first half of a switching period of the three-input converter and to produce a negative output voltage at the output terminals during a second half of a switching period of the three-input converter. In other embodiments, the output variable is one of output power, output voltage and output current of the rectification section.

[0044] In other embodiments, equations defining the first duty ratio d_{po} and the second duty ratio d include first sector equations for a first sector and second sector equations for a second sector. The first sector is when voltage from the positive terminal to the neutral terminal v_{po} is decreasing and voltage from the neutral terminal to the negative terminal v_{on} is increasing and the second sector is when v_{po} is increasing and v_{on} is decreasing. In other embodiments, first and second sector equations for the first duty ratio d_{po} and the second duty ratio d_{on} are defined as:

$$\begin{aligned}
 d_{po} &= \frac{2}{\pi} \sin^{-1}(M \cos \theta_{grid}) \text{ for the first sector;} \\
 d_{po} &= \frac{2}{\pi} \sin^{-1}\left(M \cos\left(\theta_{grid} - \frac{\pi}{6}\right)\right) \text{ for the second sector;} \\
 d_{on} &= \frac{2}{\pi} \sin^{-1}(M \sin(\theta_{grid})) \text{ for the first sector; and}
 \end{aligned}$$

-continued

$$d_{on} = \frac{2}{\pi} \sin^{-1} \left(M \sin \left(\theta_{grid} - \frac{\pi}{6} \right) \right) \text{ for the second sector,}$$

where θ_{grid} is the phase angle of the phase of the three-phase AC power source, and M is the modulation index, and the modulation index M is:

$$M = \frac{V_{xy1(rms)}}{V_{xy1(rms)max}} = \frac{V_{xy1(rms)\pi}}{\sqrt{6} V_m} = \frac{I_m \pi}{2 I_{Lsm} \cos(\psi)}$$

[0045] where:

[0046] $V_{xy1(rms)}$ is a root-mean-square (“rms”) voltage and is the output voltage of the three-input converter,

[0047] $V_{xy1(rms)max}$ is a maximum rms voltage of the three-input converter,

[0048] V_m is the peak voltage of the three-phase AC power source,

[0049] I_m is the peak current of the three-phase AC power source,

[0050] I_{Lsm} is the peak current of output current at the output terminals,

[0051] Ψ is the phase angle between the fundamental components of v_{xy} and i_{xy} .

[0052] A method for operation of an unfold-based single AC to AC converter includes receiving input power at three input terminals of an unfold. The three input terminals receive the power from a three-phase AC power source and, the unfold includes an output connection with a positive terminal, a negative terminal and a neutral terminal. The unfold unfolds bipolar AC voltages into two unipolar piece-wise sinusoidal DC voltage waveforms offset from each other by a half of a period. The method includes receiving output power from the unfold at a three-input converter that produces a quasi-sinusoidal output voltage across output terminals at an output frequency. The three-input converter receives the output power at a positive input connection connected to the positive terminal, a negative input connection connected to the negative terminal and a neutral input connection connected to the neutral terminal. The three-input converter includes switches that selectively connect the positive, negative and neutral input connections across the output terminals. The method includes controlling, with a pulse-width modulation controller, a first duty ratio d_{po} and a second duty ratio d_{on} for the three-input converter as a function of a phase angle of a phase of the three-phase AC power source and a modulation index generated from an error signal related to a control variable compared to a reference. The first duty ratio d_{po} and the second duty ratio d_{on} are time varying at a rate related to a fundamental frequency of the three-phase AC power source, and the modulation index relates to output voltage of the three-input converter, a peak voltage of the three-phase AC power source, a peak current of the three-phase AC power source and/or a peak current of output current at the output terminals.

[0053] In some embodiments, the method includes modulating switches of the three-input converter according to a modulation scheme that depends on the first duty ratio d_{po} and the second duty ratio d_{on} , and the method selects a first part of the modulation scheme when d_{po} is greater than d_{on} and a second part of the modulation scheme when d_{on} is

greater than d_{po} , and the modulation scheme includes switching of the switches of the three-input converter to produce a positive output voltage at the output terminals during a first half of a switching period of the three-input converter and to produce a negative output voltage at the output terminals during a second half of a switching period of the three-input converter. In other embodiments, equations defining the first duty ratio d_{po} and the second duty ratio d_{on} include first sector equations for a first sector and second sector equations for a second sector. The first sector is when voltage from the positive terminal to the neutral terminal v_{po} is decreasing and voltage from the neutral terminal to the negative terminal v_{on} is increasing and the second sector is when v_{po} is increasing and v_{on} is decreasing.

I. Operation of the Proposed Ac-Ac Converter

[0054] FIG. 1 is a schematic block diagram illustrating one embodiment of an unfold-based single-stage AC to AC converter 100. The converter 100 includes an unfold 102 and a three-input converter 104 with output terminals x and y with an output voltage v_{xy} . The converter 100 is fed from a three-phase AC power source 106 (or three-phase source 106 for simplicity). The unfold 102 is controlled by a phase lock loop (“PLL”) 108 connected to the three-phase source 106 where the PLL 108 is connected to a switching sequence generator 110 that controls the switches Qa1, Qb1, Qc1, Qa2, Qb2, Qc2, Qa3, Qb3, Qc3 of the unfold 102. The switching sequence of the unfold 102 is described in more detail with respect to FIG. 3. The three-input converter 104 is controlled by a pulse-width modulation (“PWM”) controller 112. The PWM controller 112 includes a duty cycle calculator 114 that has an input of a phase angle (θ_{grid}) of the three-phase source 106 from the PLL 108 and a modulation index M. The modulation index M is generated from an error signal from a control variable compared with a reference and multiplied by a control loop compensation, such as proportional-integral compensation (as depicted in FIG. 1). The control loop compensation may be a proportional-integral (“PI”) compensation, proportional compensation, a proportional-integral-derivative (“PID”) compensation, or other suitable compensation. The PWM controller 112 is described in more detail below.

[0055] The unfold 102 has an input that connects to the three-phase source 106 and has an output connection with a positive terminal p, a negative terminal n and a neutral terminal o. The unfold 102 unfolds bipolar AC voltages into two unipolar piece-wise sinusoidal DC voltage waveforms offset from each other by a half of a period. The unipolar piece-wise sinusoidal DC voltage waveforms are described with regard to FIG. 3.

[0056] The three-input converter 104 produces a quasi-sinusoidal output voltage v_{xy} across output terminals x and y at an output frequency. Typically the output frequency of the three-input converter 104 is much higher than the fundamental frequency of the three-phase source 106, which is typically 60 hertz (“Hz”) or 50 Hz. In some embodiments, the output frequency of the three-input converter 104 is two orders of magnitude greater than fundamental frequency of the three-phase source 106. In some instances, the output frequency of the three-input converter 104 is two orders of magnitude greater than fundamental frequency of the three-phase source 106 of about 10 kilo hertz (“kHz”) to 300 kHz. In some embodiments, a switching frequency of the switches of the three-input converter 104 is about 85 kHz

and produces a quasi AC waveform related to the switching frequency. The three-input converter **104** includes a positive input connection connected to the positive terminal p, a negative input connection connected to the negative terminal n and a neutral input connection connected to the neutral terminal o. The three-input converter **104** includes switches that selectively connect the positive, negative and neutral input connections across the output terminals x and y.

[0057] In some embodiments, the control variable is the output voltage v_o of the three-input converter **104**. In other embodiments, the output of the three-input converter **104** feeds a filter that reduces harmonics of the three-input converter **104** and the control variable is an output of the filter. In other embodiments, the three-input converter **104** feeds a resonant section, which is connected to a rectification section that feeds a DC load and the control variable is the output voltage of the rectification section. In some embodiments, the converter **100** of FIG. 1 is part of a converter in a WPT system, such as the WPT system **200** of FIG. 2.

[0058] The PWM controller **112** is configured to control a first duty ratio d_{po} and a second duty ratio d_{on} for the three-input converter **104** as a function of the phase angle θ_{grid} of a phase (e.g. phase “a”) of the three-phase source **106** and the modulation index M generated from an error signal related to a control variable compared to a reference. The first duty ratio d_{po} and the second duty ratio d_{on} are time varying at a rate related to a fundamental frequency of the three-phase source **106** and, in various embodiments, the modulation index M relates to the output voltage v_o of the three-input converter **104**, a peak voltage V_m of the three-phase source **106**, a peak current I_m of the three-phase source **106** and/or a peak current $I_{m_{xy}}$ of output current at the output terminals x, y.

[0059] FIG. 2 is a schematic block diagram illustrating one embodiment of an unfolded-based single-stage AC to AC converter **200** implemented in a wireless power transfer (“WPT”) system **200**. The circuit diagram of FIG. 2 is a single-stage AC-AC resonant topology with a three-phase unfolded **102** and a three-input, T-type converter **104** (which may be referred to herein as a three-input converter **104** or a T-type converter **104**). FIG. 3 is a schematic block diagram **300** illustrating one embodiment of an unfolded **102** along with a switching sequence and ideal waveforms of a three-phase unfolded **102** operating at unity power factor. The three-input converter **104** is connected to a resonant circuit **202**, which connects to a rectification section **204** connected to a battery. For wireless power transfer, the resonant circuit **202** includes a primary pad, represented by a primary inductor L_{pri} separated from a secondary pad, represented by a secondary inductor L_{pri} where the primary pad and secondary pad are separated by a gap. The primary pad and the secondary pad are coupled with a mutual inductance M_{PS} . For example, the primary pad may be ground mounted and the secondary pad, rectification section **204** and battery may be on an electric vehicle that is positioned with the secondary pad over the primary pad for charging the battery.

[0060] In the WPT system **200** of FIG. 2, the control variable for the PWM controller **112** is power P_{bat} transferred to the battery, which is calculated from a battery current I_{bat} multiplied by battery voltage V_{bat} . The power to the battery is compared with a power reference P_{ref} . In some embodiments, the power reference P_{ref} is based on a state-of-charge of the battery and is generated by a battery charging controller on the vehicle and is transferred along

with the power to the battery P_{bat} through a wireless communication link. While a WPT system **200** is depicted in FIG. 2, the converter **100** may be used for various other applications to provide or sink power.

[0061] The unfolded **102** is depicted with switches Qa1, Qb1, Qc1, Qa2, Qb2, Qc2, Qa3, Qb3, Qc3 for bi-directional power transfer. In some embodiments, switches Qa1, Qb1, Qc1, Qa2, Qb2, and Qc2 may be replaced by diodes Da1, Db1, Dc1, Da2, Db2, and Dc2, as depicted in the bottom unfolded **302** of FIG. 3 for unidirectional power transfer. In other embodiments, the unfolded **102** with switches may also be used for unidirectional power transfer.

[0062] The unfolded **102** of the power converter **100** and WPT system **200** of FIGS. 1 and 2 are depicted in FIG. 3 and the incoming AC phases can be connected to positive, negative, or midpoint of a soft DC-link using the switching sequence shown in FIG. 3. The soft DC-link is depicted in FIGS. 1 and 2 at the output of the unfolded **102** at terminals p, n and o. The three input phases each at a time of a maximum and minimum instantaneous voltage are connected to the positive p and negative n points of the soft DC-link respectively and the remaining phase is connected to the midpoint o. This switching sequence results in the time-varying soft DC-link voltages v_{po} and v_{on} , which are the respectively the voltages across the p and o terminals of the DC-link and the o and n terminals of the DC-link of the three-input converter **104**. For example, in the first switching period (marked with a “1”) in switching diagram of FIG. 3, from time 0 to $\pi/3$ switch Qc1 connects phase c of the three-phase source **106** to terminal p, switch Qb2 connects phase b to terminal n and switch Qa3 connects phase a to terminal o. This switching combination then connects the voltage across phases c and a (v_{ca}) across terminals p and o so $v_{ca}=v_{po}$ and connects the voltage across phases a and b (v_{ab}) across terminals o and n so $v_{ab}=v_{on}$, as can be seen in the voltage waveform at the top right side of FIG. 3.

[0063] In the waveforms on the right side of FIG. 3, v_{ab} is a voltage across input terminals a and b of the unfolded **102**, v_{bc} is a voltage across the input terminals b and c of the unfolded **102**, and v_{ca} is a voltage across the input terminals c and a of the unfolded **102**. Voltages V_m and $-V_m$ are respectively a maximum and a minimum instantaneous voltage of each input phase from the three-phase source **106**. Note that v_{po} and v_{on} are unipolar piece-wise sinusoidal DC voltage waveforms offset from each other by a half of a period. The frequency of the unipolar piece-wise sinusoidal DC voltage waveforms is three times the fundamental frequency of the three-phase source **106**. The unipolar piece-wise sinusoidal DC voltage waveforms includes a DC component that is about half of the maximum instantaneous voltage V_m .

[0064] The middle waveform on the right side of FIG. 3 depicts phase currents, current to terminal p i_p and current to terminal n i_n . The bottom waveform of the three waveforms at the right side of FIG. 3 shows power waveforms generated by the voltage and current waveforms at the output terminals p, n, and o of the unfolded **102**. Power P_1 is $v_{po} * i_p$ and power P_2 is $v_{on} * i_n$. Note that the output power P_{as} of the unfolded **102** is constant.

[0065] Switches Qa3, Qb3 and Qc3 are two complementary insulated metal-oxide semiconductor field-effect transistor (“MOSFETs”) switches in series to prevent current in either direction through a body diode the switches Qa3, Qb3 and Qc3 when turned off. In other embodiments, other types

of semiconductor switches are used, such as gate bipolar transistors (“IGBTs”) switches may be used. In other embodiments, a switch pair may be replaced by a single switch where a body diode is not included with the switch. The capacitors across terminals p and o C_p and across terminals o and n C_n may be film-type capacitors, which are smaller and more reliable than the electrolytic capacitors of multi-stage AC-AC inverters and other topologies, which is beneficial.

[0066] The three-input converter **104**, which is a T-type topology, converts the soft DC-link voltages v_{po} and v_{on} into a high-frequency 5-level voltage. Although, the powers **P1** ($v_{po} \cdot i_p$) and **P2** ($v_{on} \cdot i_n$) across the soft DC-link are time-varying between 0 and P_{ac} as shown in FIG. 3, the output power of the T-type converter **104** is constant over a switching cycle. This AC-AC topology of the converter **100** provides a buck-type power factor correction (“PFC”) action and regulates the fundamental component of the output voltage v_{xy} , which is the input voltage to the resonant tank of the WPT system **200** of FIG. 2, over the entire grid cycle. The soft switching of the unfolded **102** switches at a unity power factor and results in negligible switching losses. The T-type converter **104** performs both power factor correction and output current control, thus affecting the overall system operation. Hence, it is referred to as a single-stage power conversion system.

II. Modulation Strategy and Control Scheme

[0067] The three-phase unfolded **102** is switched at twice the line frequency of the three-phase source **106** with the sequence presented in FIG. 3. The T-type converter **104** switches at the operating frequency of the WPT system **200**. A modulation scheme and switching sequence for the T-type converter **104** is shown in FIG. 4, where a first duty ratio d_{po} and a second duty ratio d_{on} are the duty ratios corresponding to the soft DC-link voltages v_{po} and v_{on} , respectively. The modulation scheme for switches of the three-input converter **104** depends on the first duty ratio d_{po} and the second duty ratio d_{on} . The modulation scheme includes a first modulation scheme when d_{po} is greater than d_{on} and a second modulation scheme when d_{on} is greater than d_{po} . The left waveform is the first modulation scheme for $d_{po} > d_{on}$ and the right waveform is the second modulation scheme for $d_{po} < d_{on}$.

[0068] The modulation scheme includes switching of the switches (e.g. S_{x1} , S_{y1} , S_{x2} , S_{y2} , S_{x3}^+ , S_{x3}^- , S_{y3}^+ , S_{y3}^-) of the three-input converter **104** to produce a positive output voltage at the output terminals v_o during a first half of a

switching period of the three-input converter **104** and to produce a negative output voltage v_{xy} at the output terminals during a second half of a switching period of the three-input converter **104**. The notation for each of the waveforms includes a main switch and a complimentary switch. For example, when S_{x1} is high, S_{x3}^+ is low, when S_{x2} is high, S_{x3}^- is low, when S_{y1} is high, S_{y3}^+ is low, and when S_{y2} is high, S_{y3}^- is low, and vice-versa.

[0069] The voltage pulses corresponding to v_{po} and v_{on} are center-aligned in the depicted embodiments such that d_{po} and d_{on} are centered at a phase angle of 90 degrees of a switching period of the three-input converter **104** for a positive output voltage v_{xy} at the output terminals and are centered at a phase angle of 270 degrees of the switching period of the three-input converter **104** for a negative output voltage v_{xy} at the output terminals. In other embodiments, the modulation scheme includes voltage pulses that are not center aligned. The duty ratios d_{po} and d_{on} of the 3-input, T-type converter **104** are modulated to achieve the PFC action and output voltage (v_{xy}) regulation. Voltages v_{po} and v_{on} vary at three times the line frequency. This causes d_{po} and d_{on} to vary at three times the line frequency as well, which is a rate much slower than the switching frequency of the three-input converter **104**. At some points, d_{po} is equal to d_{on} , which results in a three-level output voltage v_{xy} at the output terminals of the three-input converter **104**. Therefore, the mathematical analysis is done for two periods—which include Sector-I ($v_{po} > v_{on}$) and Sector-II ($v_{po} < v_{on}$), as shown in FIG. 3. The first sector is when v_{po} is decreasing and v_{on} is increasing and the second sector is when v_{po} is increasing and v_{on} is decreasing. The fundamental components of the primary voltage (v_{xy1}) and the primary current (i_{xy1}) are given by:

$$v_{xy1} = \frac{4}{\pi} \left[v_{po} \sin\left(\frac{\pi d_{po}}{2}\right) + v_{on} \sin\left(\frac{\pi d_{on}}{2}\right) \right] \sin(\omega_s t), \quad (1)$$

$$i_{xy1} = I_{Lsm} \sin(\omega_s t - \Psi), \quad (2)$$

where ω_s is the angular switching frequency, I_{Lsm} is the amplitude of the fundamental component of primary current, and Ψ is the phase angle of fundamental current of i_{xy1} with respect to the fundamental voltage of v_{xy1} . The expressions for d_{po} and d_{on} are derived by equating the values of i_{dc}^p and i_{dc}^n averaged over one switching cycle to the instantaneous values of i_p and i_n respectively as presented in Table I.

TABLE 1

Calculation of d_{po} and d_{on} for sectors I and II		
Parameter	Sector-I ($0 < \theta_{grid} < \frac{\pi}{3}$)	Sector-II ($\frac{\pi}{3} < \theta_{grid} < \frac{2\pi}{3}$)
v_{po}	$V_m \sin\left(\theta_{grid} + \frac{2\pi}{3}\right)$	$V_m \sin\left(\theta_{grid} - \frac{\pi}{3}\right)$
v_{on}	$V_m \sin(\theta_{grid})$	$V_m \sin\left(\theta_{grid} + \frac{\pi}{3}\right)$
$\langle i_{dc}^p \rangle > T_s = i_p$	$\frac{2I_{Lsm} \cos \psi}{\pi} \sin\left(\frac{\pi d_{po}}{2}\right) = I_m \cos(\theta_{grid})$	$\frac{2I_{Lsm} \cos \psi}{\pi} \sin\left(\frac{\pi d_{po}}{2}\right) = I_m \sin\left(\theta_{grid} - \frac{\pi}{6}\right)$

TABLE 1-continued

Calculation of d_{po} and d_{on} for sectors I and II		
Parameter	Sector-I ($0 < \theta_{grid} < \frac{\pi}{3}$)	Sector-II ($\frac{\pi}{3} < \theta_{grid} < \frac{2\pi}{3}$)
$\langle i_{dc}^n \rangle T_s = i_n$	$\frac{2I_{Lsm}\cos\psi}{\pi}\sin\left(\frac{\pi d_{on}}{2}\right) = I_m\sin\left(\theta_{grid} + \frac{\pi}{6}\right)$	$\frac{2I_{Lsm}\cos\psi}{\pi}\sin\left(\frac{\pi d_{on}}{2}\right) = I_m\sin\left(\theta_{grid} + \frac{\pi}{6}\right)$
d_{po}	$\frac{2}{\pi}\sin^{-1}(M\cos(\theta_{grid}))$	$\frac{2}{\pi}\sin^{-1}(M\sin(\theta_{grid} - \frac{\pi}{6}))$
d_{on}	$\frac{2}{\pi}\sin^{-1}(M\sin(\theta_{grid} + \frac{\pi}{6}))$	$\frac{2}{\pi}\sin^{-1}(M\sin(\theta_{grid} + \frac{\pi}{6}))$

[0070] M is the modulation index given by

$$M = \frac{V_{xy1(rms)}}{V_{xy1(rms)max}} = \frac{V_{xy1(rms)}}{\sqrt{6}V_m} = \frac{I_m^\pi}{2I_{Lsm}\cos(\psi)}. \quad (3)$$

The duty ratios depend on the modulation index (M) and the grid phase angle (θ_{grid}). A plot of d_{po} and d_{on} for various modulation indexes is given in FIG. 5. The leading edges of the five-level v_{xy} voltage waveform, as shown in FIG. 4, are hard-switched for a certain portion of the grid cycle.

[0071] A region of converter soft switching is dependent on the phase angle Ψ of the primary current (I_{Pri}) and the modulation index (M). The higher the M, the higher is the soft-switching region of the three-input converter 104 over the grid cycle. Detuning the resonant tank to be inductive helps in achieving soft switching over the majority portion of the grid cycle when operated at M closer to one. At lower M, the leading edges of the output voltage v are hard switched, similar to a phase-shift controlled inverter in a two-stage converter. Soft switching enables higher overall system efficiency compared to a two-stage conversion, which has losses in both the PFC stage and the inverter stage.

[0072] From equation (1), it can be seen that the voltage v_{xy1} depends on both d_{po} and d_{on} . However, d_{po} and d_{on} are decoupled through M. This presents an easier control of power without sensing the DC-link currents i_p and i_n . The control loop shown in FIG. 2 has a proportional-integral (“PI”) compensator that processes the error in the battery power and generates the modulation index (M). In other embodiments, other compensators are used. M and the grid phase angle (θ_{grid}) are used to calculate d_{po} and d_{on} and generate the PWM signals for the three-input converter 104. The proposed method does not require DC-link current sensing. If the phase-locked loop PLL 108 is implemented by sensing the grid voltages instead of the unfold phase voltages, grid currents will lag the voltages by a small angle due to the voltage drop across the grid filter inductor L_g . To eliminate the impact of the power conversion stage non-idealities on the input power factor, a feedback method with an inner DC current regulation loop along with the decoupling terms may be used.

III. Simulation Results

[0073] The WPT circuit in FIG. 2 is simulated in Piecewise Linear Electrical Circuit Simulation (“PLECS”®) with the parameters listed in Table II. The simulation results

presented in FIG. 6 demonstrate unity-power-factor operation of the system. The simulation results for a step-change in battery power from 50 kW to 100 kW at $t=0.02$ seconds are presented in FIG. 6. The system settles within 1 milliseconds (“ms”) as seen from the plot of the modulation index. Distortions in the DC-link currents i_p and i_n at the sector transitions can be seen from FIG. 6. This effect is seen in all unfold-based topologies. The distortions are due to the ripple in the soft DC-link voltages v_{po} and v_{on} , which results in undesired conduction of body diodes of the switches of the unfold 102 of the commuting phase during the sector transition. The distortion in the grid currents at the sector transitions corresponds to the under-damped ringing of the grid inductance with the DC-link capacitance. The waveforms corresponding to the WPT system 200 are shown in FIG. 7 and include waveforms of the three-input converter 104 and rectification section 204.

TABLE II

Simulation parameters of the converter 100 of FIG. 2	
Parameter	Value
Nominal input voltage	480 V (1-1), 60 Hz AC 3- Φ
Maximum Output power	100 kW
Switching frequency (f_s)	85 kHz
Primary inductance (L_{Pri})	27.92 μ H
Secondary inductance (L_{Sec})	27.92 μ H
Mutual inductance (M_{PS})	6.62 μ H
Coupling coefficient (k)	0.237
Nominal battery voltage	800 V
Capacitances C_p and C_n	30 μ F
Grid filter inductance (L_g)	5 μ H
Filter capacitance (C_f)	150 μ F

IV. Experimental Results

[0074] A 1 kW scaled-down prototype of the AC-AC power converter 100 was developed in a laboratory to validate the proposed topology and the modulation strategy. The WPT system 200 in FIG. 2 was implemented in hardware without the secondary coil, rectification stage and the battery as the focus was to demonstrate the PFC action and voltage control of the front-end converter (e.g. 100). To emulate the battery load, a resistor equals to the reflected resistance of the WPT system 200 was connected in series with the primary coil L_{Pri} . The series resistance-inductance-capacitance (“RLC”) load (R , C_{p1} , L_{Pri} in Table III) was tuned to 20 degrees lagging power factor to aid soft switching. A Pacific Power 390-ASX power supply was used to

emulate the three-phase source **106**. The unfolded **102** and the three-input converter **104** were implemented using Cree SiC devices C3M0120100J (1000 V/22 A/120 mΩ). For unidirectional power transfer, the unfolded switches Q_{a1} , Q_{a2} , Q_{b1} , Q_{b2} , Q_{c1} , and Q_{c2} can be realized using power diodes. The mid-point switches Q_{a3} , Q_{b3} , and Q_{c3} can be realized by inexpensive IGBTs due to the low frequency switching of the unfolded stage. The parameters of the hardware setup are given in Table III.

[0075] The modulation strategy was implemented in a Texas Instruments® F28379D microcontroller using feed-forward control. During the transition instant between Sector-I ($d_{po} < d_{on}$) and Sector-II ($d_{po} > d_{on}$), extra care was taken in the software to avoid momentary shoot-through of the top and bottom devices in the three-input converter **104**. The selected solution was to force the PWM controller **112** into the starting state of the new sector, when the sector change is detected. The compare register values of the new sector are then loaded into enhanced PWM (“EPWM”) registers. Calculation of the d_{po} and d_{on} functions was computationally intensive due to the arcsin function, which required 18.5 microseconds (“μs”) of processing time. The control algorithm was implemented at a rate of 17 kHz, which is five times slower than the switching frequency of 85 kHz.

TABLE III

Parameters of the hardware setup	
Parameter	Value
Input voltage	128 V (1-1), 60 Hz AC 3-ph
Output power	1 kW
Switching frequency (f_s)	85 kHz
Primary inductance (L_{pri})	89.92 μH
Primary capacitance (C_{p1})	48.86 μF
Reflected resistance (R)	17.1 Ω
Capacitances C_p and C_n	1.5 μF
Grid filter inductance (L_g)	30 μH
Modulation index (M)	1

[0076] The three-phase ac line currents of the inverter at 1 kW output power are shown in FIG. 8. An efficiency of 95% from the grid to the resistive load was achieved at this operating point. An input power factor of 0.99 and a grid current total harmonic distortion (“THD”) of 1.4% was measured using a Yokogawa WT1806E power analyzer. The PFC action as well as the tank voltage v_{pn} and current control are illustrated in FIG. 9. The 360 Hz envelope of the tank voltage (v_{pn}) is also shown in FIG. 9. The 180 Hz soft DC link voltages v_{po} , v_{on} and currents i_p , i_n are illustrated in FIG. 10. The soft DC-link currents i_p , i_n have high ripple due to the lower value of DC-link capacitances C_p , C_n used in the hardware.

[0077] The 5-level waveform of the tank voltage under unequal d_{po} and d_{on} values is given in FIG. 11. When d_{po} and d_{on} are equal, the tank voltage has a 3-level waveform as shown in FIG. 12. As seen in FIG. 11 and FIG. 12, the leading edges are hard-switched at very low currents and the trailing edges are completely soft switched. At higher modulation indexes, the proposed topology depicted in FIGS. 1 and 2 can achieve soft switching over a major portion of the grid cycle. Hence, the proposed topology can achieve a higher efficiency compared to a conventional two-stage system or a matrix converter based system. Furthermore, the

proposed topology requires a very small grid filter due to the low voltage ripple on the grid filter inductor and hence more compact components.

[0078] Single-stage AC-AC converters have the potential to improve the efficiency and power density of the WPT systems. A control scheme for an AC-AC conversion system utilizing a three-phase unfolded **102** and three-input converter **104** is described herein. The mathematical analysis of the proposed modulation scheme and the simulation results for a 100 kW WPT system demonstrating the efficacy of the proposed control scheme is presented herein. Hardware results of a 1 kW scaled-down hardware prototype demonstrate the effectiveness of the proposed topology. The hardware system achieved a power factor of 0.99 with a grid current THD well under 2%. The proposed topology offers a clear advantage over the two-stage system and matrix converter in terms of grid current quality, filtering requirement, and system efficiency.

[0079] FIG. 13 is a schematic flowchart diagram illustrating one embodiment of a method **1300** for using an unfolded-based single-stage AC to AC converter. The method **1300** begins and receives **1302** input power at three input terminals of an unfolded **102**. The three input terminals receive **1302** the power from a three-phase AC power source **106** and the unfolded **102** includes an output connection with a positive terminal p, a negative terminal n and a neutral terminal o. The unfolded **103** unfolds bipolar AC voltages into two unipolar piece-wise sinusoidal DC voltage waveforms offset from each other by a half of a period. The method **1300** receives **1304** output power from the unfolded **102** at a three-input converter **104** that produces a quasi-sinusoidal output voltage across output terminals at an output frequency. The three-input converter **104** receives the output power at a positive input connection connected to the positive terminal p, a negative input connection connected to the negative terminal n and a neutral input connection connected to the neutral terminal o. The three-input converter **104** includes switches that selectively connect the positive, negative and neutral input connections across the output terminals.

[0080] The method **1300** controls **1306**, with a pulse-width modulation controller **112**, a first duty ratio d_{po} and a second duty ratio d_{on} for the three-input converter **104** as a function of a phase angle θ_{grid} of a phase of the three-phase AC power source **106** and a modulation index M generated from an error signal related to a control variable compared to a reference. The method **1300**, in some embodiments, modulates **1308**, using the PWM controller **112**, switches of the three-input converter **104** according to a modulation scheme that depends on the first duty ratio d_{po} and the second duty ratio d_{on} , and the method **1300** selects **1310** a first part of the modulation scheme when d_{po} is greater than d_{on} and a second part of the modulation scheme when d_{on} is greater than d_{po} , and the method **1300** ends. The modulation scheme includes switching of the switches of the three-input converter **104** to produce a positive output voltage at the output terminals during a first half of a switching period of the three-input converter **104** and to produce a negative output voltage at the output terminals during a second half of a switching period of the three-input converter **104**. In various embodiments, the method **1300** is implemented with the power converter **100** of FIG. 1 or 2.

[0081] Embodiments may be practiced in other specific forms. The described embodiments are to be considered in

all respects only as illustrative and not restrictive. The scope of the invention is, therefore, indicated by the appended claims rather than by the foregoing description. All changes which come within the meaning and range of equivalency of the claims are to be embraced within their scope.

What is claimed is:

1. A power converter comprising:

an unfolder comprising an input connection comprising three input terminals that connect to a three-phase alternating current (“AC”) power source and comprising an output connection with a positive terminal, a negative terminal and a neutral terminal, wherein the unfolder unfolds bipolar AC voltages into two unipolar piece-wise sinusoidal direct current (“DC”) voltage waveforms offset from each other by a half of a period;

a three-input converter that produces a quasi-sinusoidal output voltage across output terminals at an output frequency, the three-input converter comprising a positive input connection connected to the positive terminal, a negative input connection connected to the negative terminal and a neutral input connection connected to the neutral terminal, wherein the three-input converter comprises switches that selectively connect the positive, negative and neutral input connections across the output terminals; and

a pulse-width modulation controller configured to control a first duty ratio d_{po} and a second duty ratio d_{on} for the three-input converter as a function of a phase angle of a phase of the three-phase AC power source and a modulation index generated from an error signal related to a control variable compared to a reference,

wherein the first duty ratio d_{po} and the second duty ratio d_{on} are time varying at a rate related to a fundamental frequency of the three-phase AC power source, and

wherein the modulation index relates to output voltage of the three-input converter, a peak voltage of the three-phase AC power source, a peak current of the three-phase AC power source and/or a peak current of output current at the output terminals.

2. The power converter of claim **1**, wherein a modulation scheme for switches of the three-input converter depends on the first duty ratio d_{po} and the second duty ratio d_{on} .

3. The power converter of claim **2**, wherein the modulation scheme comprises a first modulation scheme when d_{po} is greater than d_{on} and a second modulation scheme when d_{on} is greater than d_{po} .

4. The power converter of claim **2**, wherein the modulation scheme comprises switching of the switches of the three-input converter to produce a positive output voltage at the output terminals during a first half of a switching period of the three-input converter and to produce a negative output voltage at the output terminals during a second half of a switching period of the three-input converter.

5. The power converter of claim **1**, wherein equations defining the first duty ratio d_{po} and the second duty ratio d_{on} comprise first sector equations for a first sector and second sector equations for a second sector, wherein the first sector is when voltage from the positive terminal to the neutral terminal v_{po} is decreasing and voltage from the neutral terminal to the negative terminal v_{on} is increasing and the second sector is when v_{po} is increasing and v_{on} is decreasing.

6. The power converter of claim **5**, wherein first and second sector equations for the first duty ratio d_{po} and the second duty ratio d_{on} are defined as:

$$d_{po} = \frac{2}{\pi} \sin^{-1}(M \cos \theta_{grid}) \text{ for the first sector;}$$

$$d_{po} = \frac{2}{\pi} \sin^{-1}\left(M \cos\left(\theta_{grid} - \frac{\pi}{6}\right)\right) \text{ for the second sector;}$$

$$d_{on} = \frac{2}{\pi} \sin^{-1}(M \sin(\theta_{grid})) \text{ for the first sector; and}$$

$$d_{on} = \frac{2}{\pi} \sin^{-1}\left(M \sin\left(\theta_{grid} - \frac{\pi}{6}\right)\right) \text{ for the second sector,}$$

wherein:

θ_{grid} is the phase angle of the phase of the three-phase AC power source, and

M is the modulation index.

7. The power converter of claim **1**, wherein the modulation index M is:

$$M = \frac{V_{xy1(rms)}}{V_{xy1(rms)max}} = \frac{V_{xy1(rms)}\pi}{\sqrt{6} V_m} = \frac{I_m\pi}{2I_{Lsm}\cos(\psi)}$$

wherein:

$V_{xy1(rms)}$ is a root-mean-square (“rms”) voltage and is the output voltage of the three-input converter;

$V_{xy1(rms)max}$ is a maximum rms voltage of the three-input converter;

V_m is the peak voltage of the three-phase AC power source;

I_m is the peak current of the three-phase AC power source;

I_{Lsm} is the peak current of output current at the output terminals; and

Ψ is the phase angle between the fundamental components of v_{xy} and i_{xy} .

8. The power converter of claim **1**, wherein the pulse-width modulation controller controls switching of the three-input converter to maintain unity power factor at the input to the unfolder.

9. The power converter of claim **1**, wherein a switching frequency of the three-input converter is at least two orders of magnitude higher than a fundamental frequency of the three-phase AC power source.

10. The power converter of claim **1**, wherein d_{po} and d_{on} are centered at a phase angle of 90 degrees of a switching period of the three-input converter for a positive output voltage at the output terminals and are centered at a phase angle of 270 degrees of the switching period of the three-input converter for a negative output voltage at the output terminals.

11. The power converter of claim **1**, wherein the output terminals of the three-input converter are connected to a resonant section, which connects to a rectification section and an output of the rectification section is a DC voltage and the control variable is for controlling the output of the rectification section.

12. The power converter of claim **11**, wherein one of:
the resonant section comprises a transmission pad separated from a receiver pad on a mobile device, wherein the transmission pad transfers power over a gap to the receiver pad as part of a wireless power transmission system;

the resonant section comprises a transformer and the power converter is a DC power supply; and

the resonant section comprises output terminals and the power converter is an inverter.

13. A system comprising:

an unfolder comprising an input connection comprising three input terminals that connect to a three-phase alternating current (“AC”) power source and comprising an output connection with a positive terminal, a negative terminal and a neutral terminal, wherein the unfolder unfolds bipolar AC voltages into two unipolar piece-wise sinusoidal direct current (“DC”) voltage waveforms offset from each other by a half of a period;

a three-input converter that produces a quasi-sinusoidal output voltage across output terminals at an output frequency, the three-input converter comprising a positive input connection connected to the positive terminal, a negative input connection connected to the negative terminal and a neutral input connection connected to the neutral terminal, wherein the three-input converter comprises switches that selectively connect the positive, negative and neutral input connections across the output terminals;

a wireless power transfer (“WPT”) primary pad coupled to output terminals of the three-input converter;

a WPT secondary pad electromagnetically coupled to the WPT primary pad over a gap;

a rectifier section coupled to an output of the WPT secondary pad, the rectifier section comprising an output; and

a pulse-width modulation controller configured to control a first duty ratio d_{po} and a second duty ratio d_{on} for the three-input converter as a function of a phase angle of a phase of the three-phase AC power source and a modulation index generated from an error signal related to a converter output variable compared to a reference, the converter output variable from the output of the rectifier section,

wherein the first duty ratio d_{po} and the second duty ratio d_{on} are time varying at a rate related to a fundamental frequency of the three-phase AC power source, and

wherein the modulation index relates to output voltage of the three-input converter, a peak voltage of the three-phase AC power source, a peak current of the three-phase AC power source and/or a peak current of output current at the output terminals.

14. The system of claim **13**, wherein a modulation scheme for switches of the three-input converter depends on the first duty ratio d_{po} and the second duty ratio d_{on} , the modulation scheme comprises a first modulation scheme when d_{po} is greater than d_{on} and a second modulation scheme when d_{on} is greater than d_{po} , and the modulation scheme comprises switching of the switches of the three-input converter to produce a positive output voltage at the output terminals during a first half of a switching period of the three-input converter and to produce a negative output voltage at the output terminals during a second half of a switching

15. The system of claim **13**, wherein equations defining the first duty ratio d_{po} and the second duty ratio d_{on} comprise first sector equations for a first sector and second sector equations for a second sector, wherein the first sector is when voltage from the positive terminal to the neutral terminal v_{po} is decreasing and voltage from the neutral terminal to the negative terminal v_{on} is increasing and the second sector is when v_{po} is increasing and v_{on} is decreasing.

16. The system of claim **15**, wherein first and second sector equations for the first duty ratio d_{po} and the second duty ratio d_{on} are defined as:

$$\begin{aligned} d_{po} &= \frac{2}{\pi} \sin^{-1}(M \cos \theta_{grid}) \text{ for the first sector;} \\ d_{po} &= \frac{2}{\pi} \sin^{-1}\left(M \cos\left(\theta_{grid} - \frac{\pi}{6}\right)\right) \text{ for the second sector;} \\ d_{on} &= \frac{2}{\pi} \sin^{-1}(M \sin(\theta_{grid})) \text{ for the first sector; and} \\ d_{on} &= \frac{2}{\pi} \sin^{-1}\left(M \sin\left(\theta_{grid} - \frac{\pi}{6}\right)\right) \text{ for the second sector,} \end{aligned}$$

wherein:

θ_{grid} is the phase angle of the phase of the three-phase AC power source, and

M is the modulation index, and

wherein the modulation index M is:

$$M = \frac{V_{xy1(rms)}}{V_{xy1(rms)max}} = \frac{V_{xy1(rms)}\pi}{\sqrt{6} V_m} = \frac{I_m\pi}{2I_{Lsm}\cos(\psi)}$$

wherein:

$V_{xy1(rms)}$ is a root-mean-square (“rms”) voltage and is the output voltage of the three-input converter;

$V_{xy1(rms)max}$ is a maximum rms voltage of the three-input converter;

V_m is the peak voltage of the three-phase AC power source;

I_m is the peak current of the three-phase AC power source;

I_{Lsm} is the peak current of output current at the output terminals; and

Ψ is the phase angle between the fundamental components of v_{xy} and i_{xy} .

17. The system of claim **13**, wherein the output variable comprises one of output power, output voltage and output current of the rectification section.

18. A method comprising:

receiving input power at three input terminals of an unfolder, the three input terminals receive the power from a three-phase alternating current (“AC”) power source and, the unfolder comprises an output connection with a positive terminal, a negative terminal and a neutral terminal, wherein the unfolder unfolds bipolar AC voltages into two unipolar piece-wise sinusoidal direct current (“DC”) voltage waveforms offset from each other by a half of a period;

receiving output power from the unfolder at a three-input converter that produces a quasi-sinusoidal output voltage across output terminals at an output frequency, the three-input converter receives the output power at a positive input connection connected to the positive terminal, a negative input connection connected to the negative terminal and a neutral input connection connected to the neutral terminal, wherein the three-input converter comprises switches that selectively connect the positive, negative and neutral input connections across the output terminals; and

controlling, with a pulse-width modulation controller, a first duty ratio d_{po} and a second duty ratio d_{on} for the

three-input converter as a function of a phase angle of a phase of the three-phase AC power source and a modulation index generated from an error signal related to a control variable compared to a reference,

wherein the first duty ratio d_{po} and the second duty ratio d_{on} are time varying at a rate related to a fundamental frequency of the three-phase AC power source, and

wherein the modulation index relates to output voltage of the three-input converter, a peak voltage of the three-phase AC power source, a peak current of the three-phase AC power source and/or a peak current of output current at the output terminals.

19. The method of claim **18**, further comprising modulating switches of the three-input converter according to a modulation scheme that depends on the first duty ratio d_{po} and the second duty ratio d_{on} , wherein the method selects a first part of the modulation scheme when d_{po} is greater than

d_{on} and a second part of the modulation scheme when d_{on} is greater than d_{po} , and wherein the modulation scheme comprises switching of the switches of the three-input converter to produce a positive output voltage at the output terminals during a first half of a switching period of the three-input converter and to produce a negative output voltage at the output terminals during a second half of a switching period of the three-input converter.

20. The method of claim **18**, wherein equations defining the first duty ratio d_{po} and the second duty ratio d_{on} comprise first sector equations for a first sector and second sector equations for a second sector, wherein the first sector is when voltage from the positive terminal to the neutral terminal v_{po} is decreasing and voltage from the neutral terminal to the negative terminal v_{on} is increasing and the second sector is when v_{po} is increasing and v_{on} is decreasing.

* * * * *