



US 20230128722A1

(19) **United States**

(12) **Patent Application Publication**
Pamula et al.

(10) **Pub. No.: US 2023/0128722 A1**

(43) **Pub. Date: Apr. 27, 2023**

(54) **BEAD INCUBATION AND WASHING ON A DROPLET ACTUATOR**

tion No. 12/615,609, filed on Nov. 10, 2009, now Pat. No. 8,313,895,

(Continued)

(71) Applicant: **Advanced Liquid Logic, Inc.**, San Diego, CA (US)

Publication Classification

(72) Inventors: **Vamsee K. Pamula**, Cary, NC (US);
Michael G. Pollack, Durham, NC (US);
Ramakrishna Sista, Cary, NC (US);
Arjun Sudarsan, Carlsbad, CA (US)

(51) **Int. Cl.**
G01N 33/543 (2006.01)
B01L 3/00 (2006.01)
B03C 1/02 (2006.01)
B03C 1/28 (2006.01)
B03C 1/30 (2006.01)
B03C 5/00 (2006.01)
C12N 15/10 (2006.01)
G01N 33/561 (2006.01)
B01F 31/65 (2006.01)
B01F 33/302 (2006.01)
B01F 33/3031 (2006.01)

(21) Appl. No.: **18/063,874**

(22) Filed: **Dec. 9, 2022**

Related U.S. Application Data


(60) Continuation of application No. 16/811,789, filed on Mar. 6, 2020, now Pat. No. 11,525,827, which is a continuation of application No. 16/132,175, filed on Sep. 14, 2018, now Pat. No. 10,585,090, which is a division of application No. 15/210,634, filed on Jul. 14, 2016, now Pat. No. 10,078,078, which is a continuation of application No. 14/731,740, filed on Jun. 5, 2015, now Pat. No. 9,395,361, which is a continuation of application No. 14/466,193, filed on Aug. 22, 2014, now Pat. No. 9,081,007, which is a continuation of application No. 14/081,376, filed on Nov. 15, 2013, now Pat. No. 8,846,410, which is a division of application No. 13/081,927, filed on Apr. 7, 2011, now Pat. No. 8,637,324, which is a continuation-in-part of application No. 11/639,531, filed on Dec. 15, 2006, now Pat. No. 8,613,889, said application No. 14/466,193 is a continuation-in-part of application No. 11/639,736, filed on Dec. 15, 2006, now Pat. No. 7,439,014, said application No. 14/466,193 is a continuation-in-part of application No. 12/113,385, filed on May 1, 2008, now Pat. No. 8,541,176, which is a division of application No. 11/639,736, filed on Dec. 15, 2006, now Pat. No. 7,439,014, said application No. 14/466,193 is a continuation-in-part of applica-

(52) **U.S. Cl.**
CPC .. **G01N 33/54333** (2013.01); **B01L 3/502715** (2013.01); **B01L 3/502761** (2013.01); **B01L 3/502784** (2013.01); **B01L 3/502792** (2013.01); **B03C 1/02** (2013.01); **B03C 1/288** (2013.01); **B03C 1/30** (2013.01); **B03C 5/005** (2013.01); **C12N 15/1013** (2013.01); **G01N 33/561** (2013.01); **B01F 31/65** (2022.01); **B01F 33/3021** (2022.01); **B01F 33/3031** (2022.01); **Y10T 436/25625** (2015.01); **B01L 7/52** (2013.01)

(57)

ABSTRACT

Methods are provided for separating magnetically responsive beads from a droplet in a droplet actuator. Droplet operations electrodes and a magnet are arranged in a droplet actuator to manipulate a bead-containing droplet and position it relative to a magnetic field region that attracts the magnetically responsive beads. The droplet operations electrodes are operated to control the droplet shape and transport it away from the magnetic field region to form a concentration of beads in the droplet. The continued transport of the droplet away from the magnetic field causes the concentration of beads to break away from the droplet to yield a small, concentrated bead-containing droplet immobilized by the magnet.













Related U.S. Application Data


which is a continuation of application No. 12/113,385, filed on May 1, 2008, now Pat. No. 8,541,176, which is a division of application No. 11/639,736, filed on Dec. 15, 2006, now Pat. No. 7,439,014, said application No. 14/466,193 is a continuation-in-part of application No. 12/615,666, filed on Nov. 10, 2009, now Pat. No. 8,951,721, which is a continuation of application No. 12/113,385, filed on May 1, 2008, now Pat. No. 8,541,176, which is a division of application No. 11/639,736, filed on Dec. 15, 2006, now Pat. No. 7,439,014, said application No. 13/081,927 is a continuation of application No. PCT/US2009/059868, filed on Oct. 7, 2009.

- (60) Provisional application No. 60/745,058, filed on Apr. 18, 2006, provisional application No. 60/745,039, filed on Apr. 18, 2006, provisional application No. 60/745,043, filed on Apr. 18, 2006, provisional application No. 60/745,059, filed on Apr. 18, 2006, provisional application No. 60/745,914, filed on Apr.

28, 2006, provisional application No. 60/745,950, filed on Apr. 28, 2006, provisional application No. 60/746,797, filed on May 9, 2006, provisional application No. 60/746,801, filed on May 9, 2006, provisional application No. 60/806,412, filed on Jun. 30, 2006, provisional application No. 60/807,104, filed on Jul. 12, 2006, provisional application No. 60/745,058, filed on Apr. 18, 2006, provisional application No. 60/745,039, filed on Apr. 18, 2006, provisional application No. 60/745,043, filed on Apr. 18, 2006, provisional application No. 60/745,059, filed on Apr. 18, 2006, provisional application No. 60/745,914, filed on Apr. 28, 2006, provisional application No. 60/745,950, filed on Apr. 28, 2006, provisional application No. 60/746,797, filed on May 9, 2006, provisional application No. 60/746,801, filed on May 9, 2006, provisional application No. 60/806,412, filed on Jun. 30, 2006, provisional application No. 60/807,104, filed on Jul. 12, 2006, provisional application No. 61/103,302, filed on Oct. 7, 2008, provisional application No. 61/122,791, filed on Dec. 16, 2008.







400 ↗









Figure 4



600 ↘





Figure 6






Figure 8A




Figure 8B















Figure 9









1400 →




Figure 14

1500




Figure 15




Figure 16A




Figure 16B




Figure 17




Figure 18

BEAD INCUBATION AND WASHING ON A DROPLET ACTUATOR

1 RELATED APPLICATIONS

[0001] This application is a continuation of and incorporates by reference U.S. patent application Ser. No. 16/811,789, entitled “Bead Incubation and Washing on a Droplet Actuator” filed Mar. 6, 2020, which is a continuation of and incorporates by reference U.S. patent application Ser. No. 16/132,175 (now U.S. Pat. No. 10,585,090 issued Mar. 10, 2020), entitled “Bead Incubation and Washing on a Droplet Actuator” filed Sep. 14, 2018, which is a divisional of and incorporates by reference U.S. patent application Ser. No. 15/210,634 (now U.S. Pat. No. 10,078,078 issued Sep. 18, 2018), entitled “Bead Incubation and Washing on a Droplet Actuator” filed Jul. 14, 2016, which is a continuation of and incorporates by reference U.S. patent application Ser. No. 14/731,740 (now U.S. Pat. No. 9,395,361 issued Jul. 19, 2016), entitled “Bead Incubation and Washing on a Droplet Actuator” filed on Jun. 5, 2015, which is a continuation of and incorporates by reference U.S. patent application Ser. No. 14/466,193 (now U.S. Pat. No. 9,081,007 issued Jul. 14, 2015), entitled “Bead Incubation and Washing on a Droplet Actuator” filed on Aug. 22, 2014, which is a continuation of and incorporates by reference U.S. patent application Ser. No. 14/081,376 (now U.S. Pat. No. 8,846,410 issued Sep. 30, 2014), entitled “Bead Incubation and Washing on a Droplet Actuator” filed on Nov. 15, 2013, which is a divisional of and incorporates by reference U.S. patent application Ser. No. 13/081,927 (now U.S. Pat. No. 8,637,324 issued Jan. 28, 2014), entitled “Bead Incubation and Washing on a Droplet Actuator” filed on Apr. 7, 2011, which is a continuation-in-part of U.S. patent application Ser. No. 11/639,531 (now U.S. Pat. No. 8,613,889 issued Dec. 24, 2013), entitled “Droplet-based washing” filed on Dec. 15, 2006. U.S. patent application Ser. No. 14/466,193 (now U.S. Pat. No. 9,081,007 issued Jul. 14, 2015), is a continuation-in-part of U.S. patent application Ser. No.: 11/639,736 (now U.S. Pat. No. 7,439,014 issued Oct. 21, 2008), entitled “Droplet-Based Surface Modification and Washing” filed on Dec. 15, 2006; Ser. No. 12/113,385 (now U.S. Pat. No. 8,541,176 issued Sep. 24, 2013), entitled “Droplet-Based Surface Modification and Washing” filed on May 1, 2008, the application of which is a divisional of and incorporates by reference U.S. patent application Ser. No. 11/639,736 (now U.S. Pat. No. 7,439,014 issued Oct. 21, 2008); Ser. No. 12/615,609 (now U.S. Pat. No. 8,313,895 issued Nov. 20, 2012), entitled “Droplet-Based Surface Modification and Washing” filed on Oct. 10, 2009, the application of which is a continuation of and incorporates by reference U.S. patent application Ser. No. 12/113,385 (now U.S. Pat. No. 8,541,176 issued Sep. 24, 2013), which is a divisional of U.S. patent application Ser. No. 11/639,736 (now U.S. Pat. No. 7,439,014 issued Oct. 21, 2008); and Ser. No. 12/615,666, entitled “Droplet-Based Surface Modification and Washing” filed on Nov. 10, 2009, the application of which is a continuation of and incorporates by reference U.S. patent application Ser. No. 12/113,385 (now U.S. Pat. No. 8,541,176 issued Sep. 24, 2013), which is a divisional of U.S. patent application Ser. No. 11/639,736 (now U.S. Pat. No. 7,439,014 issued Oct. 21, 2008). U.S. patent application Ser. No.: 11/639,531 (now U.S. Pat. No. 8,613,889 issued Dec. 24, 2013) and Ser. No. 11/639,736 (now U.S. Pat. No. 7,439,014 issued Oct. 21, 2008) claim priority to and

incorporate by reference related provisional U.S. Provisional Patent Application Nos.: 60/745,058, entitled “Filler Fluids for Droplet-Based Microfluidics” filed on Apr. 18, 2006; 60/745,039, entitled “Apparatus and Methods for Droplet-Based Blood Chemistry,” filed on Apr. 18, 2006; 60/745,043, entitled “Apparatus and Methods for Droplet-Based PCR,” filed on Apr. 18, 2006; 60/745,059, entitled “Apparatus and Methods for Droplet-Based Immunoassay,” filed on Apr. 18, 2006; 60/745,914, entitled “Apparatus and Method for Manipulating Droplets with a Predetermined Number of Cells” filed on Apr. 28, 2006; 60/745,950, entitled “Apparatus and Methods of Sample Preparation for a Droplet Microactuator,” filed on Apr. 28, 2006; 60/746,797 entitled “Portable Analyzer Using Droplet Based Microfluidics,” filed on May 9, 2006; 60/746,801, entitled “Apparatus and Methods for Droplet-Based Immuno-PCR,” filed on May 9, 2006; 60/806,412, entitled “Systems and Methods for Droplet Microactuator Operations,” filed on Jun. 30, 2006; and 60/807,104, entitled “Method and Apparatus for Droplet Based Nucleic Acid Amplification,” filed on Jul. 12, 2006.

[0002] Additionally, U.S. patent application Ser. No. 13/081,927 (now U.S. Pat. No. 8,637,324 issued Jan. 28, 2014), is a continuation of, claims priority to, and incorporates by reference International Patent Application Ser. No. PCT/US2009/059868, entitled “Bead Incubation And Washing On A Droplet Actuator” International filing date of Oct. 7, 2009, the application of which claims priority to U.S. Provisional Patent Application Nos.: 61/103,302, filed on Oct. 7, 2008, entitled “Bead Incubation and Washing on a Droplet Actuator” and 61/122,791, filed on Dec. 16, 2008, entitled “Bead Incubation and Washing on a Droplet Actuator,” the entire disclosures of which are incorporated herein by reference.

[0003] Each of the patents and patent applications provided herein is incorporated by reference in its entirety.

2 GRANT INFORMATION

[0004] This invention was made with government support under AI066590, HG003706, and CA114993 awarded by the National Institutes of Health. The United States Government has certain rights in the invention.

3 FIELD OF THE INVENTION

[0005] The present invention provides methods and apparatuses for incubating and washing magnetically responsive beads on a droplet actuator. More specifically the present invention provides methods for incubating magnetically responsive beads that are labeled with primary antibody, a sample (i.e., analyte), and secondary reporter antibodies on a magnet, on and off a magnet, and completely off a magnet. The invention also provides methods for washing magnetically responsive beads using shape-assisted merging of droplets. The invention also provides methods for shape-mediated splitting, transporting, and dispensing of a sample droplet that contains magnetically responsive beads. The methods of the invention provide for rapid time to result and optimum detection of an analyte in an immunoassay.

4 BACKGROUND OF THE INVENTION

[0006] Droplet actuators are used to conduct a wide variety of droplet operations. A droplet actuator typically includes two substrates separated by a gap. The substrates

include electrodes for conducting droplet operations. The gap between the substrates is typically filled with a filler fluid that is immiscible with the fluid that is to be subjected to droplet operations. Droplet operations are controlled by electrodes associated with one or both of the substrates. Droplet actuators are used in a variety of applications, including molecular diagnostic assays, such as immunoassays where time to result is directly affected by the protocols used for each step of the assay. The most time consuming steps in an immunoassay are incubation and washing. "Time to result" is directly affected by the protocols used for incubation, the duration of time for incubating the antibodies and the antigens, and the duration of time for incubating the substrate with sandwich beads, all of which may depend on the mixing efficiency within the droplets and the reaction and binding kinetics. The amount of washing required to obtain the required sensitivity may also influence the total time to result for immunoassays. There is a need for efficient incubation and washing protocols for immunoassays on a droplet actuator that provide for rapid time to result and optimum detection of an analyte.

5 BRIEF DESCRIPTION OF THE INVENTION

[0007] The present invention is directed to bead incubation and washing on a droplet actuator. The methods described herein may include providing a droplet including one or more magnetically responsive beads. The methods may include exposing the magnetically responsive beads in the droplet to a first region of a magnetic field capable of substantially attracting magnetically responsive beads in the droplet. The methods may include separating the droplet from the first region of the magnetic field, the magnetically responsive beads remaining in the magnetic field. The magnetically responsive beads may be separated from the droplet while exposing the magnetically responsive beads in the droplet to a first region of a magnetic field and/or while the droplet is being separated from the first region of the magnetic field. Exposing the magnetically responsive beads in the droplet to a first region of a magnetic field may include transporting the droplet into the first region of the magnetic field and/or transporting the first region of the magnetic field into proximity with the magnetically responsive beads. Separating the droplet from the first region of the magnetic field may include transporting the droplet away from the first region of the magnetic field and/or moving the first region of the magnetic field away from the droplet.

[0008] In one embodiment, a method of incubating droplets having magnetically responsive beads is provided and comprises providing a droplet actuator comprising droplet operations electrodes arranged for conducting droplet operations on a droplet operations surface and a magnet positioned relative to the droplet operations surface such that a droplet controlled by one or more of the droplet operations electrodes may be positioned within or away from a first region of the magnet's magnetic field capable of substantially attracting magnetically responsive beads in the droplet. The method also comprises positioning a droplet having magnetically responsive beads therein at a location on the droplet operations surface within the first region of the magnetic field to form a concentration of beads in the droplet; transporting the droplet through activation of selected droplet operations electrodes away from the first region of the magnetic field, thereby resuspending the magnetically responsive beads in the droplet; operating the

droplet operations electrodes to cause the droplet to split into two droplets, thereby redistributing the magnetically responsive beads; and operating the droplet operations electrodes to merge the two droplets into a single droplet.

[0009] In another embodiment, a method of incubating droplets having magnetically responsive beads therein is provided and comprises providing a droplet actuator comprising droplet operations electrodes arranged for conducting droplet operations on a droplet operations surface and a magnet positioned relative to the droplet operations surface such that a droplet controlled by one or more of the droplet operations electrodes may be positioned within or away from a first region of the magnet's magnetic field capable of substantially attracting magnetically responsive beads in the droplet. The method also comprises positioning a droplet having magnetically responsive beads therein at a location within the first region of the magnetic field of the magnet to form a concentration of beads in the droplet; transporting the droplet through activation of selected droplet operations electrodes away from the first region of the magnetic field of the magnet to resuspend the magnetically responsive beads in the droplet; operating the droplet operations electrodes to cause the droplet to elongate and then split into two droplets at a location away from the magnet; and operating the droplet operations electrodes to merge the two droplets into a single droplet at a location away from the magnet, whereby the transporting, splitting, and merging comprise an incubation cycle.

[0010] In yet another embodiment, a method of incubating droplets having magnetically responsive beads therein is provided and comprises providing a droplet actuator comprising droplet operations electrodes arranged for conducting droplet operations on a droplet operations surface and a magnet positioned relative to the droplet operations surface such that a droplet controlled by one or more of the droplet operations electrodes may be positioned within or away from a first region of the magnet's magnetic field capable of substantially attracting magnetically responsive beads in the droplet. The method further comprises positioning a droplet having magnetically responsive beads therein on a droplet operations electrode, the droplet having a footprint approximately two times the area of a single droplet operations electrode; transporting the droplet through activation of selected droplet operations electrodes in one direction in a manner elongating the droplet; and operating the droplet operations electrodes in a manner to cause the droplet to be transported in an opposite direction to cause mixing and incubation within the droplet.

[0011] In a further embodiment, a method of washing magnetically responsive beads for separating and removing unbound material is provided and comprises providing a droplet actuator comprising droplet operations electrodes arranged for conducting droplet operations on a droplet operations surface and a magnet positioned relative to the droplet operations surface such that a droplet controlled by one or more of the droplet operations electrodes may be positioned within or away from a first region of the magnet's magnetic field capable of substantially attracting magnetically responsive beads in the droplet. The method further comprises positioning a droplet having magnetically responsive beads therein to have a first region of the droplet within the first region of the magnetic field to form a concentration of beads; at another end of the magnetic field, positioning a wash buffer droplet such that a first region of the wash buffer

droplet is within the first region of the magnetic field; operating the droplet operations electrodes to merge the droplet and the wash droplet to cause redistribution of beads; operating the droplet operation electrodes to cause the merged droplet to partially move away from the magnet, and to cause beads in the droplet to concentrate in the merged droplet; and operating the droplet operations electrodes to split the merged droplet to form a supernatant droplet containing unbound reagents.

[0012] In a still further embodiment, a method of resuspending magnetically responsive beads between wash cycles is provided and comprises providing a droplet actuator comprising droplet operations electrodes arranged for conducting droplet operations on a droplet operations surface and a magnet positioned relative to the droplet operations surface such that a droplet controlled by one or more of the droplet operations electrodes may be positioned within or away from a first region of the magnet's magnetic field capable of substantially attracting magnetically responsive beads in the droplet. The method further comprises positioning a droplet having magnetically responsive beads therein at a location partially overlapping the first region of the magnetic field; transporting the droplet through activation of selected droplet operations electrodes away from the first region of the magnetic field; operating the droplet operations electrodes to cause the droplet to move towards the first region of the magnetic field; and repeating the transporting and operating steps to cause sufficient resuspension of beads such that unbound material may be effectively removed in subsequent wash cycles.

[0013] In another embodiment, a droplet actuator device having a structure for conducting a bead washing protocol is provided and comprises an array of droplet operations electrodes configured to provide a plurality of individual wash lanes, and a single waste lane intersecting each one of the plurality of wash lanes; and waste wells associated at the end of each one of the plurality of wash lanes, and at the end of the single waste lane.

[0014] In yet another embodiment, a method of separating magnetically responsive beads from a droplet is provided and comprises providing a droplet actuator comprising droplet operations electrodes arranged for conducting droplet operations on a droplet operations surface and a magnet positioned relative to the droplet operations surface such that a droplet controlled by one or more of the droplet operations electrodes may be positioned within or away from a first region of the magnet's magnetic field capable of substantially attracting magnetically responsive beads in the droplet. The method further comprises positioning a droplet having magnetically responsive beads therein within the first region of the magnetic field of the magnet to cause the magnetically responsive beads to be attracted to the magnet, and activating the droplet operations surface to cause the droplet to be circular in shape; operating the droplet operations surface to cause the droplet to move away from the first region of the magnetic field to form a concentration of magnetically responsive beads in the droplet, and the droplet operations surface being operated to cause the droplet to be transported away from the magnet one droplet operations electrode at a time, to cause the geometry of the droplet to be distorted; and continuing to transport the droplet away from the magnet to cause the concentration of magnetically responsive beads to break away from the droplet to result in

a relatively small and highly concentrated magnetically responsive bead droplet left behind and held immobilized by the magnet.

[0015] In a further embodiment, a method of transporting magnetically responsive beads within droplets is provided and comprises providing a droplet actuator comprising droplet operations electrodes arranged for conducting droplet operations on a droplet operations surface and a magnet positioned relative to the droplet operations surface such that a droplet controlled by one or more of the droplet operations electrodes may be positioned within or away from a first region of the magnet's magnetic field capable of substantially attracting magnetically responsive beads in the droplet. The method further comprises positioning a droplet having magnetically responsive beads located therein at a location wherein the droplet partially overlaps the magnet; operating the droplet operations electrodes to subject an edge of the droplet nearest the magnet to both a magnetic force from the first region of the magnetic field and an electrowetting force from the droplet operations electrodes, and to subject an edge of the droplet furthest from the magnet only to an electrowetting force, to cause the droplet to be transported away from the magnet while retaining the magnetically responsive beads within the droplet; and continuing to transport the droplet away from the magnet to cause the magnetically responsive beads to be redistributed within the droplet.

[0016] In a still further embodiment, a method of separating beads from a droplet onto a magnet is provided and comprises providing a droplet actuator comprising droplet operations electrodes arranged for conducting droplet operations on a droplet operations surface and a magnet positioned relative to the droplet operations surface such that a droplet controlled by one or more of the droplet operations electrodes may be positioned within or away from a first region of the magnet's magnetic field capable of substantially attracting magnetically responsive beads in the droplet. The method further comprises positioning a droplet having magnetically responsive beads therein within the first region of the magnetic field of the magnet to cause the beads to be attracted to the magnet, and activating the droplet operations surface in a manner to cause the droplet to take an elongate shape; operating the droplet operations surface to activate one electrode at a time, to cause the droplet to move away from the magnet, and thereby cause the geometry of the droplet to be distorted; and continuing to operate the droplet operations surface to transport the droplet further away from the magnet and inactivating an electrode intermediate to the droplet to cause the droplet to split into a supernatant droplet and a smaller droplet that has the magnetically responsive beads therein.

[0017] In another embodiment, a droplet actuator structure for extracting DNA from a sample is provided and comprises at least six on-actuator reservoirs interconnected for storing and dispensing different reagents onto the droplet actuator; and the reservoirs interconnected through paths of droplet operations electrodes, including at least two paths having magnets associated therewith, and a bead collection reservoir connected to the six on-actuator reservoirs through the droplet operations electrodes paths.

[0018] In yet another embodiment, a method of extracting DNA from whole blood is provided and comprises using a droplet actuator comprising at least six on-actuator reservoirs interconnected for storing and dispensing different

reagents onto the droplet actuator; and the reservoirs interconnected through paths of droplet operations electrodes, including at least two paths having magnets associated therewith, and a bead collection reservoir connected to the six on-actuator reservoirs through the droplet operations electrodes paths. The method further comprises dispensing a droplet of magnetically responsive beads suspended in a lysis buffer from a first of the six on-actuator reservoirs, and transporting the droplet through the droplet operations electrodes to a specific location having one of the magnets associated with the location, to hold the magnetically responsive beads within the droplet thereon; dispensing droplets of whole blood from a second reservoir and lysis buffer from a third reservoir into a fourth mixing reservoir to be mixed therein to form a cell lysate; dispensing droplets of the cell lysate across the magnetically responsive beads in succession and removing supernatant from the droplets while holding the magnetically responsive beads; dispensing wash droplets from at least a fifth reservoir to wash the magnetically responsive beads to remove cell debris; and eluting and collecting DNA captured on the magnetically responsive beads at the bead collection reservoir.

[0019] In a further embodiment, a method of detecting a component in a sample is provided and comprises providing a droplet actuator comprising droplet operations electrodes arranged for conducting droplet operations on a droplet operations surface; a magnet positioned related to the droplet operations surface such that a droplet controlled by one of more droplet operations electrodes may be positioned within or away from a first region of the magnet's magnetic field capable of substantially attracting magnetically responsive beads in the droplet; and a wash reservoir at one end of the arrangement of droplet operations electrodes. The method further comprises positioning a droplet having magnetically responsive beads located therein, the magnetically responsive beads being coated with an antibody having an affinity for a specific target antigen, away from the magnet; operating the droplet operations surface in a manner to repeatedly transport the droplet back and forth, away from the magnet, in a manner to provide sufficient resuspension and mixing of the magnetically responsive beads for antibody and antigen binding; operating the droplet operations surface in a manner to transport the droplet to a location within the first region of the magnetic field, and splitting off a supernatant droplet from the droplet by selectively operating the droplet operations surface, and retaining the magnetically responsive beads at the magnet; operating the droplet operations electrodes to transport a reagent droplet to the droplet operations electrode in the first region of the magnetic field to merge the reagent droplet with the droplet containing the magnetically responsive beads, and transporting the merged droplet back and forth, at a location away from the magnet, to cause incubation; and transporting the merged droplet through operation of the droplet operations electrodes to the droplet operations electrode at the magnet and splitting off a supernatant droplet through operation of the droplet operations electrodes.

6 DEFINITIONS

[0020] As used herein, the following terms have the meanings indicated.

[0021] “Activate” with reference to one or more electrodes means effecting a change in the electrical state of the one or more electrodes which results in a droplet operation.

[0022] “Bead,” with respect to beads on a droplet actuator, means any bead or particle that is capable of interacting with a droplet on or in proximity with a droplet actuator. Beads may be any of a wide variety of shapes, such as spherical, generally spherical, egg shaped, disc shaped, cubical and other three dimensional shapes. The bead may, for example, be capable of being transported in a droplet on a droplet actuator or otherwise configured with respect to a droplet actuator in a manner which permits a droplet on the droplet actuator to be brought into contact with the bead, on the droplet actuator and/or off the droplet actuator.

[0023] Beads may be manufactured using a wide variety of materials, including for example, resins, and polymers. The beads may be any suitable size, including for example, microbeads, microparticles, nanobeads and nanoparticles. In some cases, beads are magnetically responsive; in other cases beads are not significantly magnetically responsive. For magnetically responsive beads, the magnetically responsive material may constitute substantially all of a bead or one component only of a bead. The remainder of the bead may include, among other things, polymeric material, coatings, and moieties which permit attachment of an assay reagent. Examples of suitable magnetically responsive beads are described in U.S. Patent Publication No. 2005-0260686, entitled, “Multiplex flow assays preferably with magnetic particles as solid phase,” published on Nov. 24, 2005, the entire disclosure of which is incorporated herein by reference for its teaching concerning magnetically responsive materials and beads. The fluids may include one or more magnetically responsive and/or non-magnetically responsive beads. Examples of droplet actuator techniques for immobilizing magnetically responsive beads and/or non-magnetically responsive beads and/or conducting droplet operations protocols using beads are described in U.S. patent application Ser. No. 11/639,566, entitled “Droplet-Based Particle Sorting,” filed on Dec. 15, 2006; U.S. Patent Application No. 61/039,183, entitled “Multiplexing Bead Detection in a Single Droplet,” filed on Mar. 25, 2008; U.S. Patent Application No. 61/047,789, entitled “Droplet Actuator Devices and Droplet Operations Using Beads,” filed on Apr. 25, 2008; U.S. Patent Application No. 61/086,183, entitled “Droplet Actuator Devices and Methods for Manipulating Beads,” filed on Aug. 5, 2008; International Patent Application No. PCT/US2008/053545, entitled “Droplet Actuator Devices and Methods Employing Magnetic Beads,” filed on Feb. 11, 2008; International Patent Application No. PCT/US2008/058018, entitled “Bead-based Multiplexed Analytical Methods and Instrumentation,” filed on Mar. 24, 2008; International Patent Application No. PCT/US2008/058047, “Bead Sorting on a Droplet Actuator,” filed on Mar. 23, 2008; and International Patent Application No. PCT/US2006/047486, entitled “Droplet-based Biochemistry,” filed on Dec. 11, 2006; the entire disclosures of which are incorporated herein by reference.

[0024] “Droplet” means a volume of liquid on a droplet actuator that is at least partially bounded by filler fluid. For example, a droplet may be completely surrounded by filler fluid or may be bounded by filler fluid and one or more surfaces of the droplet actuator. Droplets may, for example, be aqueous or non-aqueous or may be mixtures or emulsions including aqueous and non-aqueous components. Droplets may take a wide variety of shapes; nonlimiting examples include generally disc shaped, slug shaped, truncated sphere, ellipsoid, spherical, partially compressed sphere, hemi-

spherical, ovoid, cylindrical, and various shapes formed during droplet operations, such as merging or splitting or formed as a result of contact of such shapes with one or more surfaces of a droplet actuator.

[0025] “Droplet Actuator” means a device for manipulating droplets. For examples of droplets, see U.S. Pat. No. 6,911,132, entitled “Apparatus for Manipulating Droplets by Electrowetting-Based Techniques,” issued on Jun. 28, 2005 to Pamula et al.; U.S. patent application Ser. No. 11/343,284, entitled “Apparatuses and Methods for Manipulating Droplets on a Printed Circuit Board,” filed on Jan. 30, 2006; U.S. Pat. No. 6,773,566, entitled “Electrostatic Actuators for Microfluidics and Methods for Using Same,” issued on Aug. 10, 2004 and U.S. Pat. No. 6,565,727, entitled “Actuators for Microfluidics Without Moving Parts,” issued on Jan. 24, 2000, both to Shenderov et al.; Pollack et al., International Patent Application No. PCT/US2006/047486, entitled “Droplet-Based Biochemistry,” filed on Dec. 11, 2006, the disclosures of which are incorporated herein by reference. Methods of the invention may be executed using droplet actuator systems, e.g., as described in International Patent Application No. PCT/US2007/009379, entitled “Droplet manipulation systems,” filed on May 9, 2007. In various embodiments, the manipulation of droplets by a droplet actuator may be electrode mediated, e.g., electrowetting mediated or dielectrophoresis mediated.

[0026] “Droplet operation” means any manipulation of a droplet on a droplet actuator. A droplet operation may, for example, include: loading a droplet into the droplet actuator; dispensing one or more droplets from a source droplet; splitting, separating or dividing a droplet into two or more droplets; transporting a droplet from one location to another in any direction; merging or combining two or more droplets into a single droplet; diluting a droplet; mixing a droplet; agitating a droplet; deforming a droplet; retaining a droplet in position; incubating a droplet; heating a droplet; vaporizing a droplet; condensing a droplet from a vapor; cooling a droplet; disposing of a droplet; transporting a droplet out of a droplet actuator; other droplet operations described herein; and/or any combination of the foregoing. The terms “merge,” “merging,” “combine,” “combining” and the like are used to describe the creation of one droplet from two or more droplets. It should be understood that when such a term is used in reference to two or more droplets, any combination of droplet operations sufficient to result in the combination of the two or more droplets into one droplet may be used. For example, “merging droplet A with droplet B,” can be achieved by transporting droplet A into contact with a stationary droplet B, transporting droplet B into contact with a stationary droplet A, or transporting droplets A and B into contact with each other. The terms “splitting,” “separating” and “dividing” are not intended to imply any particular outcome with respect to size of the resulting droplets (i.e., the size of the resulting droplets can be the same or different) or number of resulting droplets (the number of resulting droplets may be 2, 3, 4, 5 or more). The term “mixing” refers to droplet operations which result in more homogenous distribution of one or more components within a droplet. Examples of “loading” droplet operations include microdialysis loading, pressure assisted loading, robotic loading, passive loading, and pipette loading. In various embodiments, the droplet operations may be electrode mediated, e.g., electrowetting mediated or dielectrophoresis mediated.

[0027] “Filler fluid” means a fluid associated with a droplet operations substrate of a droplet actuator, which fluid is sufficiently immiscible with a droplet phase to render the droplet phase subject to electrode-mediated droplet operations. The filler fluid may, for example, be a low-viscosity oil, such as silicone oil. Other examples of filler fluids are provided in International Patent Application No. PCT/US2006/047486, entitled, “Droplet-Based Biochemistry,” filed on Dec. 11, 2006; and in International Patent Application No. PCT/US2008/072604, entitled “Use of additives for enhancing droplet actuation,” filed on Aug. 8, 2008.

[0028] “Immobilize” with respect to magnetically responsive beads, means that the beads are substantially restrained in position in a droplet or in filler fluid on a droplet actuator. For example, in one embodiment, immobilized beads are sufficiently restrained in position to permit execution of a splitting operation on a droplet, yielding one droplet with substantially all of the beads and one droplet substantially lacking in the beads.

[0029] “Magnetically responsive” means responsive to a magnetic field. “Magnetically responsive beads” include or are composed of magnetically responsive materials. Examples of magnetically responsive materials include paramagnetic materials, ferromagnetic materials, ferrimagnetic materials, and metamagnetic materials. Examples of suitable paramagnetic materials include iron, nickel, and cobalt, as well as metal oxides, such as Fe_3O_4 , $\text{BaFe}_{12}\text{O}_{19}$, CoO , NiO , Mn_2O_3 , Cr_2O_3 , and CoMnP .

[0030] “Washing” with respect to washing a magnetically responsive bead means reducing the amount and/or concentration of one or more substances in contact with the magnetically responsive bead or exposed to the magnetically responsive bead from a droplet in contact with the magnetically responsive bead. The reduction in the amount and/or concentration of the substance may be partial, substantially complete, or even complete. The substance may be any of a wide variety of substances; examples include target substances for further analysis, and unwanted substances, such as components of a sample, contaminants, and/or excess reagent. In some embodiments, a washing operation begins with a starting droplet in contact with a magnetically responsive bead, where the droplet includes an initial amount and initial concentration of a substance. The washing operation may proceed using a variety of droplet operations. The washing operation may yield a droplet including the magnetically responsive bead, where the droplet has a total amount and/or concentration of the substance which is less than the initial amount and/or concentration of the substance. Other embodiments are described elsewhere herein, and still others will be immediately apparent in view of the present disclosure.

[0031] The terms “top” and “bottom” are used throughout the description with reference to the top and bottom substrates of the droplet actuator for convenience only, since the droplet actuator is functional regardless of its position in space.

[0032] “Transporting into the magnetic field of a magnet,” “transporting towards a magnet,” and the like, as used herein to refer to droplets and/or magnetically responsive beads within droplets, is intended to refer to transporting into a region of a magnetic field capable of substantially attracting magnetically responsive beads in the droplet. Similarly, “transporting away from a magnet or magnetic field,” “transporting out of the magnetic field of a magnet,” and the like,

as used herein to refer to droplets and/or magnetically responsive beads within droplets, is intended to refer to transporting away from a region of a magnetic field capable of substantially attracting magnetically responsive beads in the droplet, whether or not the droplet or magnetically responsive beads is completely removed from the magnetic field. It will be appreciated that in any of such cases described herein, the droplet may be transported towards or away from the desired region of the magnetic field, and/or the desired region of the magnetic field may be moved towards or away from the droplet. Reference to an electrode, a droplet, or magnetically responsive beads being “within” or “in” a magnetic field, or the like, is intended to describe a situation in which the electrode is situated in a manner which permits the electrode to transport a droplet into and/or away from a desired region of a magnetic field, or the droplet or magnetically responsive beads is/are situated in a desired region of the magnetic field, in each case where the magnetic field in the desired region is capable of substantially attracting any magnetically responsive beads in the droplet. Similarly, reference to an electrode, a droplet, or magnetically responsive beads being “outside of” or “away from” a magnetic field, and the like, is intended to describe a situation in which the electrode is situated in a manner which permits the electrode to transport a droplet away from a certain region of a magnetic field, or the droplet or magnetically responsive beads is/are situated away from a certain region of the magnetic field, in each case where the magnetic field in such region is capable of substantially attracting any magnetically responsive beads in the droplet.

[0033] When a liquid in any form (e.g., a droplet or a continuous body, whether moving or stationary) is described as being “on”, “at”, or “over” an electrode, array, matrix or surface, such liquid could be either in direct contact with the electrode/array/matrix/surface, or could be in contact with one or more layers or films that are interposed between the liquid and the electrode/array/matrix/surface.

[0034] When a droplet is described as being “on” or “loaded on” a droplet actuator, it should be understood that the droplet is arranged on the droplet actuator in a manner which facilitates using the droplet actuator to conduct one or more droplet operations on the droplet, the droplet is arranged on the droplet actuator in a manner which facilitates sensing of a property of or a signal from the droplet, and/or the droplet has been subjected to a droplet operation on the droplet actuator.

7 BRIEF DESCRIPTION OF THE DRAWINGS

[0035] FIGS. 1A, 1B, 1C, 1D, and 1E illustrate top views of an example of a region of a droplet actuator and show a process of incubating beads on a magnet;

[0036] FIGS. 2A, 2B, 2C, 2D, and 2E illustrate top views of an example of a region of a droplet actuator of FIGS. 1A through 1E and show a process of incubating droplets that include magnetically responsive beads on and off a magnet;

[0037] FIGS. 3A, 3B, 3C, 3D, and 3E illustrate top views of an example of a region of a droplet actuator and show a process of incubating droplets that include magnetically responsive beads completely off a magnet;

[0038] FIG. 4 shows a plot of a comparison of incubation time between on-magnet and off-magnet incubation protocols of FIG. 1 and FIG. 2, respectively, on immunoassay performance measured in chemiluminescence;

[0039] FIGS. 5A, 5B, 5C, 5D, and 5E show a top view of a region of a droplet actuator and a process of washing magnetically responsive beads using shape-assisted merging of droplets;

[0040] FIG. 6 shows a plot of a comparison of washing protocols between slug shaped and circular shaped wash droplets on immunoassay performance measured in chemiluminescence;

[0041] FIGS. 7A, 7B, 7C, and 7D illustrate top views of an example of a region of a droplet actuator of FIGS. 5A through 5E and show a process of resuspending magnetically responsive beads between wash cycles;

[0042] FIGS. 8A and 8B show plots of a comparison of washing protocols of FIG. 5 without resuspension cycles and with resuspension cycles, respectively;

[0043] FIG. 9 illustrates a top view of a region of a droplet actuator 900 that includes multiple waste wells;

[0044] FIGS. 10A, 10B, and 10C show a top view of a region of a droplet actuator and a process of separating beads from a sample droplet;

[0045] FIGS. 11A, 11B, and 11C show a top view of a region of a droplet actuator of FIGS. 10A through 10C and a process of transporting beads within a droplet;

[0046] FIGS. 12A, 12B, and 12C show a top view of a region of a droplet actuator of FIGS. 10A through 10C and another process of separating beads from a sample droplet onto a magnet;

[0047] FIGS. 13A and 13B show a comparison of bench top and droplet actuator immunoassay reagent ratios and a plot of reagent concentration versus signal strength, respectively, that provide for optimum droplet based immunoassay performance;

[0048] FIG. 14 shows a plot of the kinetics of a reaction between a chemiluminescent substrate and ALP reporter on magnetically responsive beads for Troponin I (TnI);

[0049] FIG. 15 is a top view of a droplet actuator that may be used for extracting DNA from a whole blood sample;

[0050] FIGS. 16A and 16B illustrate top views of an example of a portion of a droplet actuator and show a process of cytokine detection on a droplet actuator;

[0051] FIG. 17 shows a plot of two 5-point standard curves for cytokine IL-6; and

[0052] FIG. 18 shows a plot of two 6-point standard curves for cytokine TNF- α .

8 DETAILED DESCRIPTION OF THE INVENTION

[0053] The present invention provides methods and apparatuses for incubating and washing magnetically responsive beads on a droplet actuator. More specifically the present invention provides methods for incubating magnetically responsive beads that are labeled with primary antibody, a sample (i.e., analyte), and secondary reporter antibodies on a magnet, on and off a magnet, and completely off a magnet. The invention also provides methods for washing magnetically responsive beads using shape-assisted merging of droplets. The invention also provides methods for shape-mediated splitting, transporting, and dispensing of a sample droplet that contains magnetically responsive beads. The methods of the invention provide for rapid time to result and optimum detection of an analyte in an immunoassay.

[0054] In an alternative embodiment of the invention, a droplet actuator may be used to extract human genomic DNA from a sample.

8.1 Incubation Protocols

[0055] Incubation protocols on a droplet actuator are generally comprised of transporting a droplet (e.g., a droplet that includes an antigen, primary capture antibodies conjugated to magnetically responsive beads, and secondary reporter antibodies) along a path of electrodes by use of splitting and merging operations that are inserted between transport cycles. Transporting, splitting, and merging the droplet ensures that the beads are well distributed (i.e., mixed) within the droplet. An incubation cycle (e.g., transport, split, and merge) may be repeated two or more times. The high mixing efficiency provided by a series of incubation cycles provides for sufficient antigen-antibody binding.

[0056] Magnetically responsive beads have a tendency to settle and form aggregates due to gravity and/or continued exposure to strong magnetic forces. These aggregates reduce the available surface area for binding and slow down reaction kinetics and, consequently, the time to result and sensitivity of the assay. Moreover, interstices in magnetically responsive bead aggregates can hold unbound species that leads to ineffective washing. This may result in less sensitive assays and inaccuracies between assays due to differing amounts of unbound species held in the interstices. Therefore, it is useful to keep the beads dispersed or resuspended during incubation and in the steps immediately following separation for further processing of the droplets away from the magnets. Resuspension of magnetically responsive beads within droplets, akin to rigorous vortexing of bench scale systems, may be achieved by moving the bead droplet back and forth and exploiting the inherent circulatory flow patterns that are developed during droplet transport.

[0057] FIGS. 1A, 1B, 1C, 1D, and 1E illustrate top views of an example of a region of a droplet actuator **100** and show a process of incubating droplets that include magnetically responsive beads on a magnet. The method of the invention of FIGS. 1A through 1E is an example of an incubation method wherein a droplet is transported into the magnetic field of a magnet and a series of split and merge droplet operations are performed to resuspend the beads within the droplet. Because of the magnet field, resuspension of the beads is primarily in the X-Y direction.

[0058] Droplet actuator **100** may include a path or array of droplet operations electrodes **110** (e.g., electrowetting electrodes). A magnet **114** is arranged in close proximity to droplet operations electrodes **110**. In particular, magnet **114** is arranged such that certain droplet operations electrodes **100** (e.g., 3 droplet operations electrodes **110M**) are within the magnetic field of magnet **114**. Magnet **114** may, for example, be a permanent magnet or an electromagnet. Droplet actuator **100** may contain a droplet **118** that may be transported along droplet operations electrodes **110** via electrowetting and upon which droplet operations may be performed. Droplet **118** may, for example, be a 3× droplet, meaning that its footprint is approximately 3 times the area of one droplet operations electrode **110**. Droplet **118** may, for example, include 1 part magnetically responsive beads and 2 parts sample. Droplet **118** may, for example, be a sample droplet that includes an analyte (e.g., an antigen) to be evaluated.

[0059] Droplet **118** may include one or more beads **122**, which may be magnetically responsive beads. Beads **122** may have an affinity for certain target substances, such as, for example, a certain type of cell, protein, nucleic acid

and/or antigen. In one example, beads **122** are coated with a primary antibody with affinity for a specific target antigen.

[0060] FIG. 1A shows a first step in a process of incubating droplets that includes magnetically responsive beads on a magnet. In this step, droplet **118** that has beads **122** therein is positioned adjacent to and overlapping droplet operations electrodes **110M**, which is within the magnetic field of magnet **114**. Because beads **122** are magnetically responsive, a concentration of beads is formed at the side of droplet **118** that is closest to magnet **114**.

[0061] FIG. 1B shows another step in the process of incubating droplets that include magnetically responsive beads on a magnet. In this step, droplet **118** is transported via electrowetting to adjacent electrodes **110M** and takes on a slug-shaped geometry. Typically, two droplet operations electrodes **110** may be used to transport a 3× droplet **118**. Because beads **122** are magnetically responsive, a concentration of beads **122** is formed at the bottom of droplet **118** (e.g., on the surface of droplet actuator **100**) and at the center of magnet **114**. Elongation of droplet **118** to a slug geometry provides for sufficient flow of fluid within droplet **118** to resuspend beads **122** in droplet **118**.

[0062] FIG. 1C shows yet another step in the process of incubating droplets that include magnetically responsive beads on a magnet. In this step, droplet **118** is split near the central region of magnet **114** using droplet operations to form, for example, two sample droplets. Splitting of droplet **118** provides for redistribution of beads **122** within the sample droplets.

[0063] FIG. 1D shows yet another step in the process of incubating droplets that include magnetically responsive beads on a magnet. In this step, split droplet **118** is merged on magnet **114** using droplet operations to form a single droplet **118**. The transporting, splitting, and merging operations of FIGS. 1B, 1C, and 1D comprise an incubation cycle. Several incubation cycles may be performed to provide for resuspension and redistribution (i.e., mixing) of beads **122** in droplet **118**.

[0064] FIG. 1E shows yet another step in the process of incubating droplets that include magnetically responsive beads on a magnet. In this step, magnet **114**, which is, for example, an electromagnet, is not activated. Therefore, no magnetic field is generated by magnet **114** and beads **122** of droplet **118** have no attraction to magnet **114**. Droplet **118** is transported via electrowetting to adjacent electrodes **110**. Beads **122** are resuspended in droplet **118**.

[0065] FIGS. 2A, 2B, 2C, 2D, and 2E illustrate top views of an example of a region of a droplet actuator **100** of FIGS. 1A through 1E and show a process of incubating, on and off a magnet, droplets that include magnetically responsive beads. The method of the invention of FIGS. 2A through 2E is an example of an incubation method wherein a droplet is transported near the magnetic field of a magnet and then away from the magnet to perform a series of split and merge droplet operations that are used to resuspend the beads within the droplet. Because the split and merge operations are performed away from the magnet, resuspension of the beads is in the lateral X-Y, and vertical Z directions.

[0066] The steps shown in FIGS. 2A, 2B, 2C, 2D, and 2E are substantially the same as those that are described in FIGS. 1A, 1B, 1C, 1D, and 1E except that, instead of incubating droplet **118** on droplet operations electrodes

110M, droplet incubation is performed adjacent to magnet **114** and away from magnet **114** on droplet operations electrodes **110**.

[0067] FIG. 2A shows a first step in a process of incubating droplets that include magnetically responsive beads on and off a magnet. In this step, droplet **118** that has beads **122** therein is positioned adjacent to droplet operations electrodes **110M**, which is within the magnetic field of magnet **114**. Because beads **122** are magnetically responsive, a concentration of beads is formed at the side of droplet **118** that is closest to magnet **114**.

[0068] FIG. 2B shows another step in a process of incubating, on and off a magnet, droplets that include magnetically responsive beads. In this step, droplet **118** is transported via electrowetting away from the magnetic field of magnet **114**. Beads **122** are sufficiently resuspended in droplet **118**.

[0069] FIG. 2C, 2D, and 2E show the process steps of droplet elongation (i.e., formation of slug-shaped geometry), droplet splitting and droplet merging, respectively, that are used to provide for sufficient flow of fluid within droplet **118** to resuspend and redistribute beads **122** in droplet **118**. Because the split and merge operations are performed away from the magnet, resuspension of the beads is in the X, Y, and Z directions.

[0070] FIGS. 3A, 3B, 3C, 3D, and 3E illustrate top views of an example of a region of a droplet actuator **300** and show a process of incubating droplets that include magnetically responsive beads substantially out of the magnetic field of a magnet. The method of the invention of FIGS. 3A through 3E is an example of an incubation method wherein a series of droplet transport operations are used to resuspend the beads within the droplet. Because the droplet operations are performed a sufficient distance away from a magnet, resuspension of the beads is in the lateral X-Y, and vertical Z directions.

[0071] Droplet actuator **300** is substantially the same as droplet actuator **100** of FIGS. 1A through 1E except that it is configured to support droplet operations on a 2× droplet. In this embodiment, droplet **118** is a 2× droplet, meaning that its footprint is approximately 2 times the area of one droplet operations electrode. Droplet **118** may, for example, include 1 part magnetically responsive beads and 1 part sample. Alternatively, droplet **118** may include 1 part sample plus magnetically responsive beads and 1 part secondary reporter antibody.

[0072] FIGS. 3A through 3E show the process steps of transporting droplet **118** along a linear path of droplet operation electrodes **110** to provide mixing of magnetically responsive beads **122**. The use of a 2× droplet provides several advantages over the use of a 3× droplet in a droplet actuator-based immunoassay. For example, mixing a 2× droplet using two droplet operations electrodes is more efficient than mixing a 3× droplet using two droplet operations electrodes. The concentration of magnetically responsive beads is also higher in a 2× droplet than a 3× droplet. A higher concentration of magnetically responsive beads provides for increased binding rate. Because the incubation cycle of a 2× droplet is substantially out of the magnetic field of magnet **114**, the binding efficiency is also increased. In addition, transport of a 3× droplet in proximity to a magnetic field via electrowetting using 2 droplet operation electrodes may result in the formation of a tail in which magnetically

responsive beads may aggregate. The formation of bead aggregates may result in reduced binding efficiency.

[0073] FIG. 4 shows a plot **400** of a comparison of incubation time between on-magnet and off-magnet incubation protocols on immunoassay performance measured in chemiluminescence. Data was generated using the incubation protocols of FIG. 1 (on-magnet) and FIG. 2 (off-magnet). Immunoassays were performed on a 300 nanoliter (nL) droplet that contained capture antibody magnetically responsive beads, alkaline phosphatase (ALP)-labeled reporter antibodies and 5 ng/mL Troponin I (TnI). Four immunoassays were performed on the magnet with incubation times of 72 seconds (sec), 198 sec, 450 sec, and 630 sec. Four more immunoassays were performed off the magnet with incubation times of 90 sec, 180 sec, 252 sec, and 324 sec. Droplet operations were the same for each incubation protocol.

[0074] As shown in FIG. 4, when incubation was performed on the magnet, the time to reach saturation was almost doubled the time to reach saturation when compared to incubation performed off the magnet. The difference in time to reach saturation between the two protocols may occur because in the presence of a magnet, the magnetically responsive beads are attracted to the surface of the droplet actuator and the recirculation patterns produce within a droplet would resuspend the magnetically responsive beads only in the lateral plane (X-Y) direction. When incubation is performed off the magnet and a sufficient distance away from the magnet (e.g., more than 2 droplet operations electrodes), resuspension of the magnetically responsive beads is in both the lateral plane (X-Y direction) and vertical plane (Z direction). Resuspension of the beads in the X, Y, and Z directions provides more surface area for binding reactions and increased rate of reaction.

[0075] In another embodiment, an incubation protocol may include merging of a circular bead droplet on a magnet with two circular sample droplets. Mixing in the merged droplet is provided by moving the merged droplet back and forth on droplet operations electrodes while the magnetically responsive beads are immobilized on the magnet.

[0076] In yet another embodiment, an incubation protocol may include merging of a circular bead droplet on a magnet with a 4×, 5× elongated (slug-shaped) sample droplet. Mixing in the merged slug-shaped droplet is provided by moving the merged droplet back and forth on droplet operations electrodes while the magnetically responsive beads are immobilized on the magnet.

8.2 Washing Protocols

[0077] Washing of magnetically responsive beads, where unbound molecules are separated and removed, is one of the most critical steps in implementing an immunoassay in a digital microfluidic system. In some embodiments, washing is performed using a merge-and-split protocol, which is repeated until the unbound material is sufficiently depleted from the supernatant to permit accurate and precise detection.

[0078] FIGS. 5A, 5B, 5C, 5D, and 5E show a top view of a region of a droplet actuator **500** and a process of washing magnetically responsive beads using shape-assisted merging of droplets. The method of the invention of FIGS. 5A through 5E is an example of a wash method wherein a wash buffer droplet and a magnetically responsive bead droplet are elongated in a slug-shaped geometry and series of merge

and split operations are used to remove unbound material from a bead droplet. The merge and split operations provide for substantially complete fluid replacement of unbound supernatant with wash buffer in the absence of mixing.

[0079] Droplet actuator **500** may include a path or array of droplet operations electrodes **510** (e.g., electrowetting electrodes). A magnet **512** is arranged in close proximity to droplet operations electrodes **510**. In particular, magnet **512** is arranged such that certain droplet operations electrodes **510** (e.g., **3** droplet operations electrodes **510M**) are within the magnetic field of magnet **512**. Magnet **512** may, for example, be a permanent magnet or an electromagnet. Droplet actuator **500** may contain a wash buffer droplet **516** and a bead droplet **514** that may be transported along droplet operations electrodes **510** via electrowetting and upon which droplet operations may be performed. Bead droplet **514** may, for example, include a quantity of magnetically responsive beads **518** that includes bound antigen and reporter antibody (i.e., antigen-antibody-reporter complex), and unbound material such as excess unbound reporter antibody.

[0080] Bead droplet **514** and wash buffer droplet **516** may, for example, be $2\times$ droplets, meaning that their footprint is approximately 2 times the area of one droplet operations electrode **510**. Bead droplet **514** and wash buffer droplet **516** may be configured as slug-shaped droplets (i.e., elongated droplets) by performing droplet operations on the $2\times$ droplets using two active droplet operations electrodes **510**. Because the excess droplet volume is now spread over a second active droplet operations electrode **510**, the droplets are elongated and conform to the shape of two electrodes.

[0081] FIG. 5A shows a first step in a process of washing beads using shape-assisted merging of droplets. In this step, bead droplet **514** that has beads **518** therein is positioned such that one region of droplet **514** is on a droplet operations electrodes **510M** which is within the magnetic field of magnet **512** and a second region of droplet **514** is on an adjacent droplet operations electrode **510**. Because beads **518** are magnetically responsive, a concentration of beads is formed at the side of bead droplet **514** that is closest to magnet **512**. At the opposite end of magnet **512**, wash buffer droplet **516** is similarly positioned such that one region of wash buffer droplet **516** is on a droplet operations electrodes **510M** which is within the magnetic field of magnet **512** and a second region of droplet **516** is on an adjacent droplet operations electrode **510**. The timing of the sequence of droplet operations for merging bead droplet **514** and wash buffer **516** is such that bead droplet **514** is elongated to a slug-shaped geometry just as wash buffer droplet is positioned via electrowetting for merging with bead droplet **514**.

[0082] FIGS. 5B shows another step in a process of washing beads using shape-assisted merging of droplets. In this step, bead droplet **514** and washed droplet **516** are merged. Merging of bead droplet **514** and wash droplet **516** provides for redistribution of beads **518**.

[0083] FIGS. 5C and 5D show another step in a process of washing beads using shape-assisted merging of droplets. In this step, a slug of fluid **520** is extended away from magnet **512** by activating the contiguous droplet operations electrodes **510** and inactivating the intermediate droplet operations electrodes **510** outside the magnetic field of magnet **512**. Fluid **520** includes wash buffer from wash buffer droplet **516** and unbound reagents from bead droplet **514**. As fluid **520** is extended, beads **518** remain concentrated on magnet **512**.

[0084] FIG. 5E shows yet another step in a process of washing beads using shape-assisted merging of droplets. In this step, a fluid **520** is split using droplet operations to form supernatant droplet **522**. Supernatant droplet **522** includes unbound reagents such as unbound reporter antibody from bead droplet **514**. Supernatant droplet **522** is typically discarded in a waste well (not shown). FIGS. 5A through 5E show the set of droplet operations that comprise a wash cycle. Several wash cycles may be performed to provide for sufficient removal of unbound material.

[0085] In an alternative embodiment, a washing protocol may use a wash droplet and a bead droplet that are circular in shape. A circular shape of a droplet may, for example, be obtained by performing droplet operations on a $2\times$ wash droplet and a $2\times$ bead droplet using only one droplet operations electrode each. Because a $2\times$ droplet (i.e., footprint is approximately 2 times the area of one droplet operations electrode) is much larger than a single droplet operations electrode, the droplet takes a more rounded shape.

[0086] FIG. 6 shows a plot **600** of a comparison of washing protocols between slug shaped and circular shaped wash droplets on immunoassay performance measured in chemiluminescence. In both protocols, incubation was performed using the off-magnet incubation protocol of FIG. 2 for 3 minutes. Each wash cycle takes about 10 seconds in a slug-based protocol of FIG. 5 and about 14 seconds in a circular droplet protocol.

[0087] As shown is FIG. 6, a washing protocol performed using slugs of fluid (or elongated droplets as shown in FIG. 5), wherein a $2\times$ wash buffer droplet and a $2\times$ bead droplet were operated using two electrodes, a sufficient wash level was achieved using fewer wash cycles when compared to washing using circular shaped droplets. In a slug-based washing protocol, mixing was minimized and the bulk of the unbound material from the supernatant was replaced with fresh wash buffer at each cycle. In a circular-droplet based protocol, mixing was ensured by operating the $2\times$ droplets using only one electrode each. Also, the dispersion of magnetically responsive beads in the lateral plane (X-Y direction) was higher in the slug-based protocol when a fresh wash buffer droplet was merged with a bead droplet. Greater dispersion of magnetically responsive beads in the merged droplet enables any unbound antibody trapped in the interstices to diffuse into the supernatant and be washed away in subsequent washes. In this example, sufficient wash levels were achieved in about 10 wash cycles using a slug-based washing protocol compared to >18 wash cycles in a circular droplet based wash protocol.

[0088] The washing behavior has two distinct regimes, one regime where washing may be very pronounced and the second where the washing may be subtle. In the slug based washing case, the washing is pronounced with each wash cycle up to about 9 cycles and after that the effect of washing is almost negligible. In the circular droplet protocol, the washing effect is pronounced until about the 15th wash; although the wash efficiency is less than that observed for the slug-based protocol. Washing is only marginally effective for the circular droplet protocol between about the 15th and 18th washes with only a slight reduction in signal with each cycle. This could happen because all the free unbound material may be washed away in the first few cycles and after that washing only removes the unbound material trapped between the beads.

[0089] FIGS. 7A, 7B, 7C, and 7D illustrate top views of an example of a region of a droplet actuator **500** of FIGS. 5A through 5E and show a process of resuspending magnetically responsive beads between wash cycles. The method of the invention of FIGS. 7A through 7D is an example of a sequence in a wash method that uses a series of droplet resuspension cycles to resuspend the magnetically responsive beads between wash cycles such as a wash cycle shown in FIG. 5. The resuspension cycles provide sufficient resuspension of the beads such that unbound material from the interstices of bead aggregates may be effectively removed.

[0090] FIG. 7A shows the first step in a process of resuspending magnetically responsive beads between wash cycles. In this step, bead droplet **514** that includes magnetically responsive beads **518** is transported via electrowetting away from magnet **512** in the direction of arrow A.

[0091] FIGS. 7B, 7C, and 7D show the process steps of transporting bead droplet **514** along a path of droplet operation electrodes **510** in the direction of arrow A. Three transport operations are shown in FIGS. 7B, 7C, and 7D, but any number of transport operations may be used to comprise a resuspension cycle. Transporting of bead droplet **514** provides for sufficient resuspension of beads **518** such that unbound material from the interstices of bead aggregates may be effectively removed in subsequent wash cycles.

[0092] A complete wash protocol may include a series of wash cycles, such as the slug based wash cycles of FIG. 5, interspersed with a one or more resuspension cycles of FIG. 7. Depending on the sensitivity of the assay required and the time to result requirement, any number of wash cycles may be interspersed with any number of resuspension cycles. For example, a complete wash protocol sequence may include, for example, four wash cycles, four resuspension cycles, and four wash cycles. A complete wash protocol sequence ends at a wash cycle.

[0093] FIGS. 8A and 8B show plots of a comparison of washing protocols of FIG. 5 without resuspension cycles and with resuspension cycles, respectively. As shown in FIG. 8A, a washing protocol in the absence of one or more resuspension cycles provides an initial drop in signal after a number of wash cycles (A). As the number of wash cycles increase (B), there is a further reduction in signal that may be due to loss of unbound material from the interstices of bead aggregates.

[0094] As shown in FIG. 8B, a washing protocol that includes one or more resuspension cycles provides more efficient removal of unbound material to a near zero level using fewer numbers of wash cycles (A).

[0095] FIG. 9 illustrates a top view of a region of a droplet actuator **900** that includes multiple waste wells. In this embodiment, multiple waste wells are provided to improve the efficiency (e.g., time to result) of a bead washing protocol such as a bead washing protocol shown in FIG. 5.

[0096] As illustrated, droplet actuator **900** includes an array of droplet operations electrodes **910** (e.g., electrowetting electrodes) configured to provide wash lanes **912a**, **912b**, **912c**, and **912d**, and a single waste lane **916**. Wash lanes **912a**, **912b**, **912c**, and **912d** may include magnets **914a**, **914b**, **914c**, and **914d**, respectively, and waste wells **920a**, **920b**, **920c**, and **920d**, respectively. Waste lane **916** may include a waste well **918**.

[0097] In operation, droplet actuator **900** may be used to conduct a bead washing protocol on four different samples in wash lanes **912a** through **912d**. In a bead washing

protocol, the supernatant droplet(s) that contain unbound material, such as unbound antigen and secondary reporter antibody, is typically discarded in a waste well. In one example, a bead washing protocol may use a single waste well **918**. In this example, a single waste lane **916** that includes waste well **918** may be used to transport supernatant (i.e., waste) droplets from wash lanes **912a** through **912d**.

[0098] In this example, supernatant (i.e., waste) droplets from wash lanes **912a** through **912d** may be transported via electrowetting in the direction of Arrow A to wash lane **916**. Individual supernatant droplets may then be transported in waste lane **916** in the direction of Arrow B to waste well **918**. Because waste lane **916** is common to wash lanes **912a** through **912d**, supernatant droplets must be transported serially (i.e., one after another).

[0099] In an alternative example, individual waste wells **920a** through **920d** may be provided for each wash lane **912a** through **912d**, respectively. In this example, supernatant droplets may be transported simultaneously in the direction of arrow C to individual waste wells **920a** through **920d**. Multiple, individual waste wells provide for increased efficiency (e.g., time to result) in a washing protocol. Multiple waste wells also provide for a reduction in the number of droplet operations electrodes **910** that are required to shuttle a supernatant droplet to a waste well. A reduction in the number of operations electrodes **910** that may be used to transport a supernatant droplet also provides for a reduction in the potential for cross-contamination of subsequent droplets used in a protocol.

8.3 Bead-Mediated Droplet Splitting

[0100] FIGS. 10A, 10B, and 10C show a top view of a region of a droplet actuator **1000** and a process of separating beads from a sample droplet. The method of the invention of FIGS. 10A through 10C is an example of a method wherein magnetically responsive beads are split from a circular shaped droplet.

[0101] Droplet actuator **1000** may include a path or array of droplet operations electrodes **1010** (e.g., electrowetting electrodes). A magnet **1014** is arranged in close proximity to droplet operations electrodes **1010**. In particular, magnet **1014** is arranged such that certain droplet operations electrodes **1010** (e.g., 3 droplet operations electrodes **1010M**) are within the magnetic field of magnet **1014**. Magnet **1014** may, for example, be a permanent magnet or an electromagnet.

[0102] Droplet actuator **1000** may contain a droplet **1016** that may be transported along droplet operations electrodes **1010** via electrowetting and upon which droplet operations may be performed. Droplet **1016** may include a quantity of beads **1020**, which may be magnetically responsive beads. An example of a process of separating beads from a circular droplet may include, but is not limited to, the following steps.

[0103] FIG. 10A shows a first step in a process of separating beads from a circular droplet. In this step, droplet **1016** that has beads **1020** therein is positioned at a droplet operations electrode **1010M**, which is within the magnetic field of magnet **1014**. Because beads **1020** are magnetically responsive, beads **1020** are attracted to magnet **1014**. Because a single droplet operations electrode **1010M** is active, droplet **1016** is circular in shape.

[0104] FIG. 10B shows another step in a process of separating beads from a circular droplet. In this step, droplet 1016 is transported via electrowetting away from droplet operations electrode 1010M and to the adjacent droplet operations electrode 1010. As droplet 1016 moves away from droplet operations electrode 1010M, a concentration of beads 1020 is formed at the side of droplet 1016 that is closest to magnet 1014. Because droplet 1016 is transported away from magnet 1014 one droplet operations electrode 1010 at a time, the geometry of droplet 1016 may be distorted (e.g., formation of a neck) by the concentration of beads 1020 as droplet 1016 pulls away from magnet 1020.

[0105] FIG. 10C shows yet another step in the process of separating beads from a circular droplet. In this step, droplet 1016 is transported via electrowetting further away from droplet operations electrode 1010M and to a droplet operations electrode 1010 that is yet further away. In doing so, the concentration of beads 1020 breaks away (snaps off) from droplet 1016. This occurs because one side (e.g., the side nearest magnet 1014) of droplet 1016 is subjected to a magnetic force and the opposite side (e.g., the side farthest from magnet 1014) is subjected to electrowetting force. When beads 1020 snap off of droplet 1016, a relatively small and highly concentrated bead droplet 1022 is left behind at droplet operations electrode 1010M and held immobilized by magnet 1014.

[0106] A similar result can be achieved using a barrier that permits a bead-containing droplet to be transported while restraining transport of the beads with the main body of the droplet.

[0107] FIGS. 11A, 11B, and 11C show a top view of a region of a droplet actuator 1000 of FIGS. 10A through 10C and a process of transporting beads within a droplet. The method of the invention of FIGS. 11A through 11C is an example of a method wherein magnetically responsive beads are transported within an elongated droplet away from a magnetic force.

[0108] The steps shown in FIGS. 11A, 11B, and 11C are substantially the same as those that are described in FIGS. 10A, 10B, and 10C except that, instead of processing a 1× droplet via electrowetting using one active electrode at a time, droplet 1016 is a slug-shaped 3× droplet that is processed using three active electrodes for each droplet operation.

[0109] FIGS. 11A, 11B, and 11C show the process steps of transporting beads 1020 within an elongated droplet 1016 away from magnet 1014. In this example, one side (e.g., the side nearest magnet 1014) of droplet 1016 is subjected to both a magnetic force and electrowetting force and the opposite side (e.g., the side farthest from magnet 1014) is subjected to electrowetting force. Because electrowetting force occurs on both sides of droplet 1016, all of the fluid within the droplet is electrowetted and beads 1020 are retained within droplet 1016 during droplet transport away from magnet 1014.

[0110] FIGS. 12A, 12B, and 12C show a top view of a region of a droplet actuator 1000 and a process of separating beads from a sample droplet onto a magnet. The method of the invention of FIGS. 12A through 12C is an example of a method wherein magnetically responsive beads are split from an elongated droplet (e.g., 3× droplet) onto a magnet. In one example, the method of the invention of FIGS. 12A through 12C may be used to dispense magnetically responsive beads onto a magnet.

[0111] The steps shown in FIGS. 12A, 12B, and 12C are substantially the same as those that are described in FIGS. 10A, 10B, and 10C except that, beads 1020 are split from an elongated 3× droplet 1016. An example of a process of dispensing beads from an elongated droplet may include, but is not limited to, the following steps.

[0112] FIG. 12A shows a first step in a process of dispensing beads from an elongated droplet. In this step, droplet 1016 that has beads 1020 therein is positioned at a droplet operations electrode 1010M, which is within the magnetic field of magnet 1014. Because beads 1020 are magnetically responsive, beads 1020 are attracted to magnet 1014. Because three droplet operations electrodes 1010 are active, droplet 1016 is elongated in shape.

[0113] FIG. 12B shows another step in a process of dispensing beads from an elongated droplet. In this step, droplet 1016 is transported away from magnet 1014 via electrowetting using one active droplet operations electrode 1010 at a time. As droplet 1016 moves away from droplet operations electrode 1010M, a concentration of beads 1020 is formed at the side of droplet 1016 that is closest to magnet 1014. Because droplet 1016 is transported away from magnet 1014 one droplet operations electrode 1010 at a time, the geometry of droplet 1016 may be distorted.

[0114] FIG. 12C shows yet another step in process of dispensing beads from an elongated droplet. In this step, droplet 1016 is transported via electrowetting further away from droplet operations electrode 1010M and to a droplet operations electrode 1010 that is yet further away. Once the sample droplet overlaps the droplet operation electrode 1010 on which droplet 1022 is to be formed, the intermediate electrode 1010 is deactivated. In doing so, droplet 1016 is split into a supernatant droplet 1022 and a smaller droplet 1016 that has beads 1020 therein.

8.4 Component Ratios

[0115] FIGS. 13A and 13B show a comparison of bench top and droplet actuator immunoassay reagent ratios and a plot of reagent concentration versus signal strength, respectively, that provide for optimum droplet based immunoassay performance.

[0116] As shown in FIG. 13A, the ratio of three components of an immunoassay, beads (i.e., capture antibody conjugated to beads), sample (e.g., serum, plasma), and secondary antibody (II° Ab) are provided. For a bench top immunoassay, a typical ratio is 1 part beads (60 μ L): 1/2 part sample (30 μ L): 1 part II° Ab (60 μ L). A reagent ratio for a droplet actuator based immunoassay is typically 1/2 bead droplet (150 nL): 1 sample droplet (300 nL): 2 II° Ab droplets (600 nL). The use of fewer beads (i.e., 1/2 bead droplet or 1/2 concentration of beads) in a droplet actuator immunoassay provides for increased efficiency of bead washing and a sufficient reduction in non-specific binding of non-target analytes to the capture beads. In addition, the concentration of secondary antibody is the same in both bench top and droplet actuator immunoassays, but the volume of secondary antibody solution is double in the droplet actuator assay.

[0117] FIG. 13B shows the improvement in detection signal that is provided by the use of 2 droplets of secondary antibody and 2 droplets of detection substrate in a droplet actuator immunoassay.

8.5 Incubation of Magnetically Responsive Beads with Chemiluminescent Substrate

[0118] Another parameter which may influence the time to result in an immunoassay is the generation of a signal during the incubation of a chemiluminescent substrate with the washed magnetically responsive beads that contain the antigen-antibody complex.

[0119] FIG. 14 shows a plot 1400 of the kinetics of a reaction between a chemiluminescent substrate and the ALP on magnetically responsive beads for Troponin I (TnI). Immunoassays were performed on TnI (100 ng/mL) using an on-magnet incubation protocol and a circular shaped droplet washing protocol. As shown in FIG. 14, about 90% of the end point signal was obtained in about 120 to about 130 seconds. For a lower concentration of the analyte, maximum signal was achieved in about <120 seconds. Based on this data, for the type of substrate used, 2 minutes may be selected as an optimum incubation time to generate maximum signal for the chemiluminescence reaction. However, if the chemiluminescence reaction is observed to behave as a flash signal instead of a glow reaction, the 2 minute incubation may be reduced to about a few seconds.

8.6 Rapid Immunoassays

[0120] Using optimized protocols for incubation and washing, a full immunoassay was performed on TnI (5 ng/mL). Magnetically responsive beads were incubated with capture antibody, analyte and secondary antibody labeled with ALP reporter using an off-magnet incubation protocol as shown in FIG. 3. Subsequently, ten slugbased washes were performed to remove the unbound material from the supernatant (wash time approximately 2 minutes). The droplet with washed magnetically responsive beads with the antigen-antibody complex was mixed with one droplet of a chemiluminescent substrate and incubated for 2 minutes. The end point chemiluminescence was detected using a photon counter. In this example, the total time to result was approximately 10 minutes per immunoassay.

8.7 Protocol for Droplet Actuator Extraction of Human Genomic DNA

[0121] FIG. 15 is a top view of a droplet actuator 1500 that may be used for extracting DNA from a whole blood sample. The droplet actuator 1500 includes six on-actuator reservoirs, each with a capacity of 2 μ L, which may be used for storing and dispensing different reagents. A typical protocol for DNA extraction on a droplet actuator may include the following steps.

[0122] In a first step, a droplet of magnetically responsive beads, such as paramagnetic Dynabeads® DNA Direct Universal from Dynal Biotech (1.05 μ m diameter), suspended in a lysis buffer are dispensed from an on-chip reservoir and transported via electrowetting to a specific location on the chip. The beads, which are magnetically responsive, are held by a permanent magnet placed underneath the chip.

[0123] In another step, droplets of whole blood are dispensed from a reservoir and mixed with droplets of lysis buffer (containing 10 M NaOH) dispensed from another onchip reservoir, into a mixing reservoir in the ratio of 1:6 and mixed for about 10 seconds. Mixing was performed by dispensing a droplet and then merging the droplet back into the reservoir.

[0124] In another step, droplets of the cell lysate were then transported across the DNA capture beads in succession and the supernatant was pinched off while holding the beads.

[0125] In another step, droplets of wash buffer stored in separate on-chip reservoirs were then used to wash the beads to remove cell debris.

[0126] In another step, purified genomic DNA captured on the beads was then eluted and collected at the bead collection reservoir. The collected DNA can then be amplified either on the chip as part of an integrated sample-to-answer chip or in a commercial thermocycler for further DNA processing or diagnostic applications.

8.8 Operation Fluids

[0127] For examples of fluids that may be subjected to droplet operations using the approach of the invention, see the patents listed in section 6, especially International Patent Application No. PCT/US2006/047486, entitled, "Droplet-Based Biochemistry," filed on Dec. 11, 2006. In some embodiments, the fluid includes a biological sample, such as whole blood, lymphatic fluid, serum, plasma, sweat, tear, saliva, sputum, cerebrospinal fluid, amniotic fluid, seminal fluid, vaginal excretion, serous fluid, synovial fluid, pericardial fluid, peritoneal fluid, pleural fluid, transudates, exudates, cystic fluid, bile, urine, gastric fluid, intestinal fluid, fecal samples, fluidized tissues, fluidized organisms, biological swabs, biological washes, liquids with cells, tissues, multicellular organisms, single cellular organisms, protozoa, bacteria, fungal cells, viral particles, organelles. In some embodiments, the fluid includes a reagent, such as water, deionized water, saline solutions, acidic solutions, basic solutions, detergent solutions and/or buffers. In some embodiments, the fluid includes a reagent, such as a reagent for a biochemical protocol, such as a nucleic acid amplification protocol, an affinity-based assay protocol, a sequencing protocol, and/or a protocol for analyses of biological fluids.

[0128] The fluids may include one or more magnetically responsive and/or nonmagnetically responsive beads. Examples of droplet actuator techniques for immobilizing magnetically responsive beads and/or non-magnetically responsive beads are described in the foregoing international patent applications and in Sista, et al., U.S. Patent Application No. 60/900,653, entitled "Immobilization of Magnetically-responsive Beads During Droplet Operations," filed on Feb. 9, 2007; Sista et al., U.S. Patent Application No. 60/969,736, entitled "Droplet Actuator Assay Improvements," filed on Sep. 4, 2007; and Allen et al., U.S. Patent Application No. 60/957,717, entitled "Bead Washing Using Physical Barriers," filed on Aug. 24, 2007, the entire disclosures of which is incorporated herein by reference.

8.9 Example: Cytokine Immunoassay on a Droplet Actuator

[0129] FIGS. 16A and 16B illustrate top views of an example of a portion of a droplet actuator 1600 and show a process of cytokine detection on a droplet actuator. All steps involved in the immunoassay, including sample and reagent aliquoting, incubation with antibodies, bead washing, and enzymatic detection, are fully automated and under software control.

[0130] Droplet actuator 1600 may include a path or array of droplet operations electrodes 1610 (e.g., electrowetting

electrodes) and a wash reservoir **1612**. A magnet **1614** is arranged in close proximity to droplet operations electrodes **1610**. In particular, magnet **1614** is arranged such that a certain droplet operations electrode **1610** (e.g., droplet operations electrode **1610M**) is within the magnetic field thereof. Magnet **1614** may be a permanent magnet or an electromagnet. Droplet actuator **1600** may contain a droplet **1618** that may be transported along droplet operations electrodes **1610** and upon which droplet operations may be performed.

[0131] Droplet **1618** may, for example, be a 3× droplet, meaning that its footprint is approximately 3 times the area of one droplet operations electrode **1610**. Droplet **1618** may, for example, include 1 part magnetically responsive beads and 2 parts sample (e.g., an antigen to be evaluated).

[0132] Droplet **1618** may include one or more magnetically responsive beads **1622**. Magnetically responsive beads **1622** are coated with a primary antibody that has an affinity for a specific target antigen. In one example, magnetically responsive beads **1622** are coated with a primary antibody that has an affinity for IL-6. In another example, magnetically responsive beads **1622** are coated with a primary antibody that has an affinity for TNF- α .

[0133] An example of a process of cytokine detection on a droplet actuator may include, but is not limited to, the following steps:

[0134] Step A of FIG. **16A** shows a droplet **1618** that has magnetically responsive beads **1622** therein and is positioned at a certain droplet operations electrode **1610**. In one example, droplet **1618** includes 1 part beads **1622** and 2 parts sample.

[0135] Steps B and C of FIG. **16A** show an incubation process, in which droplet **1618** is repeatedly transported back and forth via droplet operations to adjacent electrodes **1610**. Repeated transporting of droplet **1618** is used during incubation of beads **1622** and sample in order to provide sufficient resuspension and mixing of magnetically responsive beads **1622** for optimal antibody and antigen binding. Typically, two droplet operations electrodes **1610** may be used to transport a 3× droplet **1618**, which takes on a slug shaped geometry. Elongation of droplet **1618** to a slug shape provides for sufficient flow of fluid within droplet **1618** to resuspend magnetically responsive beads **1622** therein. In one example, droplet **1618** may be incubated for 6 minutes using 2 droplet operations electrodes **1610** and transporting droplet **1618** over a span of 8 electrodes at a switching speed of 5 Hertz (Hz).

[0136] Step D of FIG. **16A** shows droplet **1618** that has magnetically responsive beads **1622** therein transported to droplet operations electrode **1610M**. A supernatant droplet **1624** is split off using droplet operations. Because magnetically responsive beads **1622** are attracted to magnet **1614**, they are retained at magnet **1614**. In one example, supernatant droplet **1624** is a 1× droplet and droplet **1618** is now a 2× droplet. Supernatant droplet **1624** that includes unbound antigen (i.e., cytokine) is discarded (not shown).

[0137] Step E of FIG. **16A** shows a reagent droplet **1628** that includes secondary antibody transported via electrowetting to droplet operations electrode **1610M**. Reagent droplet **1628** is merged with droplet **1618** (i.e., a 2× droplet) using droplet operations to form, for example, a 3× droplet.

[0138] In one example, reagent droplet **1628** is a 1× droplet that includes biotinylated secondary antibody that has an affinity to the target antigen. The antigen target is

captured by the primary antibody which is immobilized on the beads. Merged droplet **1618** is incubated for 4 minutes using droplet operations, as described in steps B and C. Following the incubation period, droplet **1618** is transported via electrowetting to droplet operations electrode **1610M** and a 1× supernatant droplet is split off using droplet operations, as described in step D, in order to yield a 2× droplet **1618**. The supernatant droplet (not shown) that includes unbound secondary antibody is discarded.

[0139] After incubation with the biotinylated secondary antibody, the beads may in some embodiments be washed and then incubated with the streptavidin-peroxidase. The entire complex thus consists of beads-primary antibody-antigen-secondary antibody-streptavidin-peroxidase. Streptavidin-peroxidase may be substituted with streptavidin-alkaline phosphatase.

[0140] Step F of FIG. **16B** shows a bead washing step, in which a wash droplet **1630** is transported from wash reservoir **1612** along droplet operations electrodes **1610** and across droplet **1618**, which is retained at droplet operations electrode **1610M**. As wash droplet **1630** passes across magnet **1614**, droplet merge and split operations occur with droplet **1618** (i.e., a 2× droplet). In one example, wash droplet **1630** is a 2× droplet that has a slug geometry and the washing protocol is repeated 5 times. Following bead washing, a 1× supernatant droplet is split off from droplet **1618**, as described in step D of FIG. **16A**, in order to yield a 1× droplet **1618**. The supernatant droplet (not shown) is discarded.

[0141] Step G of FIG. **16B** shows one or more reagent droplets **1632** (e.g., **1632a**, **1632b**) transported to droplet operations electrode **1610M**. In one example, reagent droplet **1632a** that includes a blocking agent (e.g., Synblock) and reagent droplet **1632b** that includes a streptavidin-enzyme conjugate (e.g., streptavidinalkaline phosphatase (ALP) or streptavidin-horseradish peroxidase) are transported to droplet operations electrode **1610M** and merged using droplet operations with droplet **1618**. Droplet **1618** is now a 3× droplet.

[0142] Merged droplet **1618** is incubated for 4 minutes using droplet operations, as described in steps B and C of FIG. **16A**. Following the incubation period, droplet **1618** is transported to droplet operations electrode **1610M** and a supernatant droplet (i.e., a 1× droplet) is split off using droplet operations, as described in step D of FIG. **16A**, in order to yield a 2× droplet **1618**. The supernatant droplet (not shown) that includes unbound streptavidin-enzyme conjugate is discarded.

[0143] Droplet **1618** is subsequently washed, for example 15 times, as described in step F of FIG. **16B**. Following bead washing, a 1× supernatant droplet is split off droplet **1618**, as described in step D of FIG. **16A**, in order to yield a 1× droplet **1618**. The supernatant droplet (not shown) is discarded. Droplet **1618** that includes antibody-antigen sandwich is now ready for detection.

[0144] Step H of FIG. **16B** shows droplet **1634** (1× droplet) that includes a detection substrate **1636** transported to droplet operations electrode **1610M** and merged using droplet operations with droplet **1618**. The detection substrate **1636** is converted by the enzyme conjugate into a fluorescent signal (product formation time about 1620 seconds). The chemiluminescent signal is measured by a detector (not shown) in order to determine the quantity of antigen that is present.

[0145] In some embodiments, wash buffer droplets may be transported across the detection window following each chemiluminescent droplet to clean up the detection window and the detection loop prior to the next detection.

8.9.1 IL-6 Results

[0146] In one embodiment, the method of the invention is used to detect IL-6. FIG. 17 shows a plot of two 5-point standard curves for cytokine IL-6. Data was generated using the cytokine detection protocol described in FIGS. 16A and 16B. In this example, two 5-point standard curves (0, 0.05, 0.5, 5, and 25 ng/mL of IL-6) were obtained in 2 runs for IL-6 performed on 2 separate droplet actuators.

8.9.2 TNF- α Results

[0147] In an alternative embodiment, the method of the invention is used to detect TNF- α . FIG. 18 shows a plot of two 6-point standard curves for cytokine TNF- α . Data was generated using the cytokine detection protocol described in FIGS. 16A and 16B. In this example, two 6-point standard curves (0, 0.01, 0.1, 1, 10, and 100 ng/mL of TNF- α) were obtained in 2 runs for TNF- α performed on 2 separate droplet actuators.

9 CONCLUDING REMARKS

[0148] The foregoing detailed description of embodiments refers to the accompanying drawings, which illustrate specific embodiments of the invention. Other embodiments having different structures and operations do not depart from the scope of the present invention. The term “the invention” or the like is used with reference to certain specific examples

of the many alternative aspects or embodiments of the applicants’ invention set forth in this specification, and neither its use nor its absence is intended to limit the scope of the applicants’ invention or the scope of the claims. This specification is divided into sections for the convenience of the reader only. Headings should not be construed as limiting of the scope of the invention. The definitions are intended as a part of the description of the invention. It will be understood that various details of the present invention may be changed without departing from the scope of the present invention. Furthermore, the foregoing description is for the purpose of illustration only, and not for the purpose of limitation.

1. A droplet actuator comprising:

- (i) droplet operations electrodes to conduct droplet operations on a droplet operations surface; and
- (ii) a magnet positioned relative to the droplet operations surface such that a droplet controlled by one or more of the droplet operations electrodes may be positioned within or away from a first region of the magnet’s magnetic field to attract magnetically responsive beads in the droplet;

wherein the magnet is positioned such that three or more droplet operations electrodes are within the magnetic field of the magnet.

2. The method of claim 1, wherein the magnet is an electromagnet.

3. The method of claim 1, wherein the magnetically responsive beads are coated with a primary antibody with an affinity for a specific target antigen.

* * * * *