



US 20230174391A9

(19) **United States**
(12) **Patent Application Publication**
YIP et al.

(10) **Pub. No.: US 2023/0174391 A9**
(48) **Pub. Date: Jun. 8, 2023**
CORRECTED PUBLICATION

(54) **TEMPERATURE SWING SOLVENT
EXTRACTION FOR DESCALING OF
FEEDSTREAMS**

63/024,954, filed on May 14, 2020, provisional ap-
plication No. 63/134,826, filed on Jan. 7, 2021.

Publication Classification

(71) Applicant: **THE TRUSTEES OF COLUMBIA
UNIVERSITY IN THE CITY OF
NEW YORK, NEW YORK, NY (US)**

(51) **Int. Cl.**
C02F 1/26 (2006.01)
C02F 1/04 (2006.01)
C02F 1/66 (2006.01)
C02F 1/44 (2006.01)

(72) Inventors: **Ngai Yin YIP**, Summit, NJ (US);
Chanhee BOO, Seoul (KR); **Kinnari
SHAH**, New York, NY (US); **Ian
BILLINGE**, New York, NY (US);
Robert WINTON, Seattle, WA (US);
Eliza DACH, New York, NY (US)

(52) **U.S. Cl.**
CPC **C02F 1/265** (2013.01); **C02F 1/042**
(2013.01); **C02F 1/66** (2013.01); **C02F 1/444**
(2013.01); **C02F 2103/10** (2013.01)

(73) Assignee: **THE TRUSTEES OF COLUMBIA
UNIVERSITY IN THE CITY OF
NEW YORK, NEW YORK, NY (US)**

(57) **ABSTRACT**

(21) Appl. No.: **17/348,139**

(22) Filed: **Jun. 15, 2021**

Prior Publication Data

(15) Correction of US 2021/0309540 A1 Oct. 7, 2021
See (60) Related U.S. Application Data.


(65) US 2021/0309540 A1 Oct. 7, 2021

Related U.S. Application Data

(63) Continuation of application No. PCT/US2020/
033403, filed on May 18, 2020.

(60) Provisional application No. 62/848,624, filed on May
16, 2019, provisional application No. 62/904,723,
filed on Sep. 24, 2019, provisional application No.

Systems and methods of performing temperature swing solvent extraction (TSSE) descaling of produced water and desalination of high-salinity brines, e.g., those having a total dissolved solids (TDS) greater than about 250,000 ppm are capable of producing descaled water products including less than about 5% weight percent TDS. The brine/produced water feedstreams and combined with a solvent having temperature-dependent water solubility at a temperature T_L . Water is extracted from the feedstream into the solvent to form a water-in-solvent extract component and a raffinate component, from which a solid phase can be precipitated as more water is portioned in the solvent and basicity increases. Heating of the water-in-solvent extract component reduces the solubility of the water therein, producing a biphasic mixture of dewatered solvent and descaled water that can be separated. Because these systems and methods do not require a phase change of water, these products are achieved with significantly higher energy efficiencies when compared to evaporation-based thermal methods.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 7




FIG. 8A




FIG. 8B

TEMPERATURE SWING SOLVENT EXTRACTION FOR DESCALING OF FEEDSTREAMS

CROSS REFERENCE TO RELATED APPLICATION(S)

[0001] This application is a continuation of International Application No. PCT/US2020/033403, filed May 18, 2020, which claims the benefit of U.S. Provisional Application Nos. 62/848,642, filed May 16, 2019, 62/904,723, filed Sep. 24, 2019, and 63/024,954, filed May 14, 2020, and this application further claims the benefit of U.S. Provisional Application No. 63/134,826, filed Jan. 7, 2021, which are incorporated by reference as if disclosed herein in their entireties.

STATEMENT ON FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

[0002] This invention was made with government support under R19AC00111 awarded by the United States Bureau of Reclamation. The government has certain rights in the invention.

BACKGROUND

[0003] Hypersaline brines from industrial processes are of growing environmental concern, but are technologically under-served by today's desalination methods. Prominent examples of such high-salinity brines include produced water (PW) from the oil and gas industry, waste streams of minimum/zero liquid discharge operations, inland desalination concentrate, landfill leachate, and flue gas desulfurization wastewater.

[0004] In many ways, the production of oil and gas from unconventional resources (tight shale) is a water problem. Between several hundred thousand and a million barrels of water are required just to open up hydraulic-induced fractures in a single reservoir to enable the production of hydrocarbons. But more importantly, in regions such as West Texas, once production begins, every barrel of oil produces up to 15 barrels of water, referred to as flowback. Typically, flowback is simply re-injected into the ground using deep well injection. However, this solution to the disposal of PW is increasingly unacceptable as the sheer volume has caused induced seismicity in some regions and the quality of water being injected can create groundwater contamination issues. As a result, the oil and gas industry has become increasingly efficient at reusing PW and avoiding disposal altogether.

[0005] These brines and produced waters exhibit very high total dissolved solids (TDS) >60,000 ppm, the removal of which pose considerable technical challenges. The composition of produced water varies considerably, depending on the location of the field, the age of the reservoir, the type of hydrocarbon produced, and other factors. Across the oil and gas industry, the following contaminants are of most concern for PW management: high levels of TDS, which can be as high as 400,000 mg/L, oil and grease, suspended solids, dispersed oil, dissolved and volatile organic compounds, heavy metals, radionuclides, dissolved gases and bacteria, and chemical additives used in production (e.g., biocides, scale/corrosion inhibitors, and emulsion/reverse-emulsion breakers). Reverse osmosis (RO) is the most energy-efficient and cost-effective desalination technique, e.g., for seawater. However, because osmotic pressure scales with TDS con-

centration, exceedingly high operating pressures are needed to overcome the osmotic pressure of hypersaline brines, precluding the application of RO. As a result, evaporation-based thermal methods, e.g., multiple effect distillation, thermal brine concentrator, and crystallizers, are the prevailing processes to desalinate or dewater highly concentrated brines. These processes achieve separation by phase-change (s) between liquid and vapor water. However, because the enthalpy of vaporization for water is large (≈ 630 kWh/m³), these evaporative phase-change methods are inherently very energy intensive.

[0006] In order to improve the quantity of produced water and flowback that is useable, either as replacement for fresh water resources that would normally be consumed or for other beneficial uses, new technology is needed to tailor the water quality for specific purposes. This 'fit-for-purpose' water treatment is unlike conventional water treatment or desalination, as the management of PW does not require achieving potable quality. In fact, in most oil basins, flowback water can be recycled with minimal or no treatment. It is in specific applications, e.g., agriculture, where innovative approaches to the removal of contaminants and impurities that would normally render the reuse of produced water uneconomical, is deserving of particular attention.

[0007] The removal of TDS in produced water has been identified among the highest priority objectives in PW treatment. However, conventional desalination techniques are precluded from treating most PW because of the high concentrations of scalants and foulants. Specifically, dissolved inorganic compounds can form mineral scales on heat exchange tubes and membranes in distillation and reverse osmosis, respectively, that severely deteriorates productivity. The presence of such scalants in produced water poses a major challenge for the feasibility of beneficial reuse. Without pretreatment, the most likely solids to form, defined by highest saturation index, are: CaCO₃, FeCO₃, MgCO₃, MnCO₃, SrCO₃, BaSO₄, CaSO₄, MgSO₄, and SrSO₄. In order to achieve beneficial reuse and fit-for-purpose reutilization, such scalants should be removed.

[0008] The presence of scalants is also a major problem for PW from the Permian Basin, with high concentrations of several metal-sulfate and -carbonate scales in the water chemistry. The high levels of hardness, Ca²⁺, Mg²⁺, and other divalent cations, as well as sulfate and carbonate (alkalinity), point to scaling being a major issue for the treatment of Permian Basin PW. Therefore, the development of cost-effective technologies for scalant removal is urgently needed.

[0009] Wastewater management strategies that eliminate liquid waste exiting the facility are termed zero liquid discharge (ZLD), often with the water recovered for reuse. Entirely abating liquid discharge lessens environmental impacts and diminishes pollution risks. The waste solids produced in ZLD can be more easily disposed in leach-proofed landfills or further processed to recover mineral byproducts of value. Where water recovery is applied, a nontraditional supply is generated for fit-for-purpose and even potable use. Increasingly stricter disposal regulations and financial incentives are motivating the development of ZLD technologies for waste brines. For example, all newly constructed coal-to-chemicals facilities in China must comply with ZLD rules for waste streams, to conserve local water resources and ecosystems. Stringent disposal regulations enforced by the Egyptian government to protect their

primary water resource, the River Nile, drove implementation of the country's first ZLD-integrated chemical manufacturing facility.

[0010] Conventional ZLD systems typically comprise a thermal brine concentrator to dewater the saline feedwater by evaporation to near saturation and a thermal crystallizer to vaporize more water and further concentrate the feed past saturation, precipitating mineral salts and other dissolved solids and contaminants (solar evaporation pond is another option but the method is land and capital intensive and often constrained by climate and hydrogeology). Eventually, almost all the water is removed to leave only a slurry of solids as waste. However, the thermally-driven brine concentrator and crystallizer are evaporative phase change processes with inherently very high energy intensities due to the exceedingly large vaporization enthalpy of water ($\approx 652\text{--}682\text{ kWh/m}^3$). Additionally, these methods require high-grade thermal energy, i.e., steam that is $>100^\circ\text{C}$., and often also high-quality electrical energy for mechanical vapor compression.

[0011] Solvent extraction is a separation method widely employed for chemical engineering processes. The relatively inexpensive, simple, and effective separation technique is used in a wide range of industries, including production of fine organic compounds, purification of natural products, and extraction of valuable metal complexes. Solvent extraction can be an alternative desalination approach that is radically different from conventional methods because it is membraneless and not based on evaporative phase change. Application of solvent extraction for desalination was first explored using amine solvents in the 1950s, but the effort was limited to desalting brackish water of relatively low salinity ($<10000\text{ ppm TDS}$). More recently, the technique was investigated for desalination of seawater simulated by a 3.5% (w/w) NaCl solution with decanoic acid as the solvent.

SUMMARY

[0012] Accordingly, some embodiments of the present disclosure relate to a method of performing temperature swing solvent extraction desalination of high-salinity brines. In some embodiments, the method includes providing a feedstream having a total dissolved solids greater than about 250,000 ppm; combining the feedstream with a solvent, wherein the solvent has temperature-dependent water solubility; bringing the combined feedstream and solvent to a temperature T_L ; extracting a liquid from the feedstream into the solvent to form a water-in-solvent extract component and a raffinate component at temperature T_L , wherein the raffinate component includes an aqueous phase, a solid phase, or combinations thereof; separating the water-in-solvent extract component from the raffinate component; heating the water-in-solvent extract component to a temperature T_H to produce a biphasic mixture of dewatered solvent and descaled water; and separating the dewatered solvent and the descaled water. In some embodiments, the descaled water includes less than about 5% weight percent total dissolved solids. In some embodiments, the feedstream includes brine, produced water, or combinations thereof. In some embodiments, the solvent includes diisopropylamine (DIPA), N-ethylcyclohexylamine (ECHA), and N,N-dimethylcyclohexylamine (DMCHA), triethylamine (TEA), N-methylcyclohexylamine (nMCHA), N,N-dimethylisopropylamine (DMIPA), or combinations thereof. In some

embodiments, T_L is below about 20°C . In some embodiments, T_L is about 5°C . In some embodiments, T_H is between about 40°C . and about 80°C . In some embodiments, T_H is about 70°C . In some embodiments, the feedstream has a total dissolved solids greater than about 290,000 ppm. In some embodiments, the feedstream to solvent ratio is less than about 15 mL/mol.

[0013] In some embodiments, the method includes cooling the dewatered solvent component from temperature T_H ; and combining the dewatered solvent component with the feedstream. In some embodiments, the method includes precipitating the solid phase; and sieving the solid phase from a liquid phase, the solid phase including one or more scalants from the feedstream. In some embodiments, the one or more scalants includes an alkali metal salts, $\text{Ca}(\text{OH})_2$, CaCO_3 , FeCO_3 , $\text{Mg}(\text{OH})_2$, MgCO_3 , MnCO_3 , SrCO_3 , BaSO_4 , CaSO_4 , MgSO_4 , SrSO_4 , or combinations thereof.

[0014] Some embodiments of the present disclosure relate to a method of producing a descaled water product. In some embodiments, the method includes combining a volume of produced water with a solvent with temperature-dependent water solubility, the volume of produced water having a total dissolved solids greater than about 250,000 ppm; raising the pH of the combined produced water and solvent to produce an elevated-pH composition; precipitating a solid phase from the elevated-pH composition, the solid phase including one or more scalants; separating the one or more scalants from the elevated-pH composition; heating the elevated-pH composition to a temperature T_H to demix a descaled water component from a dewatered solvent component; removing the dewatered solvent component to isolate a descaled water product, the descaled water product including less than about 5% weight percent total dissolved solids; cooling the dewatered solvent component to a temperature T_L ; and combining the dewatered solvent component with the volume of produced water.

[0015] Some embodiments of the present disclosure relate to a system of performing temperature swing solvent extraction desalination of high-salinity brines. In some embodiments, the system includes a feedstream in fluid communication with a fluid source, the fluid source including a fluid having a total dissolved solids greater than about 250,000 ppm. In some embodiments, the system includes a solvent source including one or more solvents with temperature-dependent water solubility. In some embodiments, the system includes an extractor in fluid communication with the feedstream and the solvent source, the extractor including at least a first outlet and a second outlet. In some embodiments, the extractor includes one or more microporous membranes configured to isolate the solid phase product. In some embodiments, the system includes a water-in-solvent extract outlet stream in communication with the first outlet. In some embodiments, the system includes a raffinate outlet stream in communication with the second outlet, wherein the raffinate outlet stream includes an aqueous phase, a solid phase, or combinations thereof. In some embodiments, the system includes a separator in fluid communication with the water-in-solvent extract outlet stream, the separator including at least a third outlet and a fourth outlet. In some embodiments, the system includes a descaled water component outlet stream in communication with the third outlet, the descaled water component including less than about 5% weight percent total dissolved solids. In some embodiments, the system includes a dewatered solvent component outlet

stream in communication with the fourth outlet. In some embodiments, the system includes a temperature controller in communication with the extractor and the water-in-solvent extract outlet stream, wherein the extractor is maintained at a temperature T_L and the water-in-solvent extract outlet stream is heated to a temperature T_H , wherein T_L is below about 20° C. and T_H is between about 40° C. and about 80° C. In some embodiments, the system includes a dewatered solvent recycle conduit in fluid communication with the dewatered solvent component outlet stream and the extractor, the dewatered solvent recycle conduit configured to direct the dewatered solvent component outlet stream to the extractor. In some embodiments, the system includes one or more heat exchangers in thermal communication with the water-in-solvent extract outlet stream, the separator, or combinations thereof.

[0016] Some embodiments of the present disclosure relate to a method of performing temperature swing solvent extraction-stepwise release (TSSE-SR) desalination of hypersaline brines including providing a feedstream including a concentration of dissolved salts, combining the feedstream with one or more solvents, wherein the one or more solvents has temperature-dependent water solubility, bringing the combined feedstream and solvent to a temperature T_1 , extracting water from the feedstream into the solvent to form a water-in-solvent component and a raffinate component at temperature T_1 , wherein the raffinate component includes an increased concentration of dissolved salts, separating the water-in-solvent component from the raffinate component, bringing a previous water-in-solvent component produced via a previous separation step to at least one new temperature T_N to produce a biphasic mixture of a subsequent water-in-solvent component and a subsequent raffinate component at temperature T_N , separating the subsequent water-in-solvent component from the subsequent raffinate component, bringing a subsequent water-in-solvent component to a temperature T_F to produce a biphasic mixture of dewatered solvent and descaled water, separating the dewatered solvent and the descaled water, and recycling the dewatered solvent to the combined feedstream and solvent. In some embodiments, the feedstream includes brines, produced waters, or combinations thereof. In some embodiments, the steps of bringing a previous water-in-solvent component produced via a previous separation step to at least one new temperature T_N to produce a biphasic mixture of a subsequent water-in-solvent component and a subsequent raffinate component at temperature T_N , and separating the subsequent water-in-solvent component from the subsequent raffinate component, is repeated 2 or more times. In some embodiments, the temperature swing from T_1 to T_F is a continuous temperature gradient. In some embodiments, the solvent includes aliphatic amines, cyclic amines, pyridines, piperidines, glycol ethers, or combinations thereof. In some embodiments, T_1 is below about 20° C. In some embodiments, T_1 is about 16° C. In some embodiments, T_F is between about 40° C. and about 80° C. In some embodiments, T_F is about 70° C.

BRIEF DESCRIPTION OF THE DRAWINGS

[0017] The drawings show embodiments of the disclosed subject matter for the purpose of illustrating the invention. However, it should be understood that the present application is not limited to the precise arrangements and instrumentalities shown in the drawings, wherein:

[0018] FIG. 1 is a chart of a method of performing temperature swing solvent extraction (TSSE) descaling of a feedstream according to some embodiments of the present disclosure;

[0019] FIG. 2 is a chart of a method of producing a descaled water product according to some embodiments of the present disclosure;

[0020] FIG. 3 is a schematic representation of a system of performing TSSE, e.g., descaling/desalination of high-salinity brines/produced waters according to some embodiments of the present disclosure;

[0021] FIG. 4 is a schematic representation of performing temperature swing solvent extraction-stepwise release (TSSE-SR) desalination of hypersaline brines according to some embodiments of the present disclosure;

[0022] FIG. 5 is a chart of a method of producing a descaled water product according to some embodiments of the present disclosure;

[0023] FIG. 6A is a graph portraying water recovery and precipitated salt capabilities of methods and systems according to some embodiments of the present disclosure;

[0024] FIG. 6B is a graph portraying compositions of product water treated with methods and systems according to some embodiments of the present disclosure;

[0025] FIG. 7 is a graph portraying solids removal capabilities of methods and systems according to some embodiments of the present disclosure;

[0026] FIG. 8A is a graph portraying the mass fraction of DIPA and NaCl in the aqueous phase of a TSSE-SR experiment using DIPA and NaCl with three stepwise extractions; and

[0027] FIG. 8B is a graph portraying mass of the aqueous phase that was released at each intermediate temperature in a TSSE-SR experiment on 1.0 mol/L NaCl using DIPA with three stepwise extractions.

DETAILED DESCRIPTION

[0028] Referring now to FIG. 1, some embodiments of the present disclosure are directed to a method 100 of performing temperature swing solvent extraction (TSSE) descaling of a feedstream. In some embodiments, the feedstream includes one or more liquids that include an undesired component dissolved therein. In some embodiments, the undesired component includes one or more scalants, as will be discussed in greater detail below. The feedstream can be from any suitable source, e.g., existing in the natural environment, effluent from industrial processes, etc. In some embodiments, the feedstream includes brines, produced waters, or combinations thereof. In some embodiments, the feedstream includes high-salinity brine, produced water and flowback from oil and gas industry, fluegas desulfurization wastewater, inland desalination concentrates, landfill leachate, waste streams of zero/minimum liquid discharge operations, waste effluents from thermoelectric power plants, discharges of coal-to-chemicals facilities, etc., or combinations thereof. As used herein, the term “descaling” is used to refer to removal of the undesired components dissolved in the feedstream, i.e., scalants including minerals, metals, etc. In some embodiments, descaling of the feedstream includes removal of one more metal salts, e.g., desalination.

[0029] At 102, the feedstream is provided. As discussed above, in some embodiments, the feedstream includes produced water for removal of soluble salt scalants, e.g.,

produced water and flowback from oil and gas industry, fluegas desulfurization wastewater, inland desalination concentrates, landfill leachate, waste streams of zero/minimum liquid discharge operations, waste effluents from thermoelectric power plants, discharges of coal-to-chemicals facilities, etc., or combinations thereof. In some embodiments, the feedstream includes a hypersaline solution, e.g., 1M-5M+NaCl solutions, for desalination. In the some embodiments, the total dissolved solids (TDS) in the feedstream is greater than about 60,000 ppm, 70,000 ppm, 80,000 ppm, 90,000 ppm, 100,000 ppm, 110,000 ppm, 120,000 ppm, 130,000 ppm, 140,000 ppm, 150,000 ppm, 160,000 ppm, 170,000 ppm, 180,000 ppm, 190,000 ppm, 200,000 ppm, 210,000 ppm, 220,000 ppm, 230,000 ppm, 240,000 ppm, 250,000 ppm, 260,000 ppm, 270,000 ppm, 280,000 ppm, 290,000 ppm, 300,000 ppm, etc. In some embodiments, the one or more scalants include minerals, metals, etc., or combinations thereof. In some embodiments, the scalants include hydroxides, carbonates, phosphates, sulfates, etc. In some embodiments, the scalants include $\text{Ca}(\text{OH})_2$, CaCO_3 , FeCO_3 , $\text{Mg}(\text{OH})_2$, MgCO_3 , MnCO_3 , SrCO_3 , BaSO_4 , CaSO_4 , MgSO_4 , SrSO_4 , alkali metal salts, e.g., NaCl, or combinations thereof.

[0030] At **104**, the feedstream is combined with one or more solvents. The one or more solvents have temperature-dependent water solubility, meaning that the solubility of water in the solvent decreases with an increase in temperature. In some embodiments, the solvent is basic. In some embodiments, the solvent includes one or more hydrophilic moieties in a mainly hydrophobic chemical structure. In some embodiments, the solvent is an amine solvent, e.g., a primary, secondary, or tertiary amine solvent. In some embodiments, the solvent includes diisopropylamine (DIPA), N-ethylcyclohexylamine (ECHA), and N,N-dimethylcyclohexylamine (DMCHA), triethylamine (TEA), N-methylcyclohexylamine (nMCHA), N,N-dimethylisopropylamine (DMIPA), or combinations thereof.

[0031] At **106**, the combined feedstream and solvent are brought to a temperature T_L . In some embodiments, the combined feedstream and solvent are maintained at temperature T_L via any suitable heat source or cooling system, including external heat sources, recycled heat, heat exchangers, etc., as will be discussed in greater detail below. In some embodiments, T_L is below about 20° C. In some embodiments, T_L is below about 10° C. In some embodiments, T_L is about 5° C. In some embodiments, the pH of the combined feedstream and solvent is increased, e.g., via the addition of a basic component, as will be discussed in greater detail below.

[0032] At **108**, liquid from the feedstream is extracted into the solvent to form a water-in-solvent extract component. In some embodiments, as discussed above, the one or more solvents have temperature-dependent water solubility where water is more soluble in the solvent at T_L than at higher temperatures. Without wishing to be bound by theory, at T_L , water from the feedstream favorably interacts with the hydrophilic moieties in the chemical structure of the solvents. Thus, at T_L , water favorably partitions from the feedstream into the solvent phase, leaving behind a raffinate component that retains the scalants from the liquid feedstream. In some embodiments, the raffinate component includes an aqueous phase, a solid phase, or combinations thereof.

[0033] In some embodiments, at **110**, the solid phase is precipitated. In some embodiments, at **112**, the solid phase is separated from a liquid phase, e.g., via sieve, membrane, etc. or combinations thereof. The solid phase includes one or more scalants from the feedstream. As the feedstream comes in contact with the solvent, more and more water is extracted into the water-in-solvent extract component, increasing the concentration of scalants/salts in the raffinate component. When the solubility of the scalants/salts is reached, they can precipitate out to form a solid phase in the raffinate component. In some embodiments, the feedstream to solvent ratio is less than about 25.3 mL/mol, 20.2 mL/mol, 15 mL/mol, 10.1 mL/mol, 5.1 mL/mol, 2.5 mL/mol, etc. In some embodiments, the feedstream to solvent ratio is about 15 mL/mol. In some embodiments, the feedstream to solvent ratio is about 15.2 mL/mol. In some embodiments, the scalants in the solid phase include hydroxides, carbonates, phosphates, sulfates, etc. In some embodiments, the scalants in the solid phase include $\text{Ca}(\text{OH})_2$, CaCO_3 , FeCO_3 , $\text{Mg}(\text{OH})_2$, MgCO_3 , MnCO_3 , SrCO_3 , BaSO_4 , CaSO_4 , MgSO_4 , SrSO_4 , alkali metal salts, e.g., NaCl, or combinations thereof. In some embodiments, the solid phase separated at step **112** is recycled or sold as a product, e.g., for use in other processes/products.

[0034] At **114**, the water-in-solvent extract component is separated from the raffinate component. In some embodiments, separation **114** occurs via a decanting process. At **116**, the water-in-solvent extract component is heated to a temperature T_H . In some embodiments, temperature T_H is between about 40° C. and about 80° C. In some embodiments, temperature T_H is about 70° C. In some embodiments, the water-in-solvent extract component is heated and/or maintained at temperature T_H via any suitable heat source, including external heat sources, recycled heat, heat exchangers, etc. In some embodiments, the heat source is a low-grade thermal source. In some embodiments, the heat source is waste heat, renewable energy sources, e.g., wind, solar, hydrothermal, etc., or combinations thereof. Because the solubility of the water in the water-in-solvent extract component decreases when temperature increases, the temperature swing from T_L to T_H drives a phase separation in the water-in-solvent extract component. The result is a biphasic mixture of dewatered solvent, the water having come out of solution by the increase in temperature, and descaled water, the scalants having been previously removed by precipitation and/or removal of the raffinate component. At **118**, the dewatered solvent is separated from the descaled water. In some embodiments, the descaled water includes less than about 15%, less than about 10%, or less than about 5% weight percent total dissolved solids. In some embodiments, the descaled water separated at step **118** is recycled or sold as a product for use in other processes. In some embodiments, the descaled water is further processed to further reduce total dissolved solids in the water, e.g., via a reverse osmosis process.

[0035] At **120**, the dewatered solvent component is cooled from temperature T_H . In some embodiments, the dewatered solvent component is cooled **120** from temperature T_H to temperature T_L . As will be discussed in greater detail below, in some embodiments, heat lost in the cooling of the dewatered solvent component (as well as the descaled water component) from T_H can be recycled. In some embodiments, the heat is recycled in method **100**, e.g., at step **116**, or a separate process. At **122**, the dewatered solvent component

is combined with the feedstream, e.g., for use at one of steps **104**, **106**, or **108**. In some embodiments, method **100** is a continuous or substantially continuous process. In some embodiments, method **100** is a semi-batch process. In some embodiments, method **100** is a batch or substantially batch process.

[0036] Referring now to FIG. 2, some embodiments of the present disclosure are directed to a method **200** of producing a descaled water product. In some embodiments, at **202**, a volume of produced water is combined with one or more solvents. In some embodiments, the volume of produced water to solvent ratio is less than about 25.3 mL/mol, 20.2 mL/mol, 15 mL/mol, 10.1 mL/mol, 5.1 mL/mol, 2.5 mL/mol, etc. As discussed above, the one or more solvents have temperature-dependent water solubility. In some embodiments, the solvent includes aliphatic amines, cyclic amines, pyridines, piperidines, glycol ethers, or combinations thereof. In some embodiments, the solvent includes diisopropylamine (DIPA), N-ethylcyclohexylamine (ECHA), and N,N-dimethylcyclohexylamine (DMCHA), triethylamine (TEA), N-methylcyclohexylamine (nMCHA), N,N-dimethylisopropylamine (DMIPA), or combinations thereof. As discussed above, in some embodiments, the volume of produced water includes a plurality of soluble scalants, e.g., salts. In some embodiments, the volume of produced water includes produced water and flowback from oil and gas industry, fluegas desulfurization wastewater, inland desalination concentrates, landfill leachate, waste streams of zero/minimum liquid discharge operations, waste effluents from thermoelectric power plants, discharges of coal-to-chemicals facilities, etc., or combinations thereof. In some embodiments, the volume of produced water includes a hypersaline solution, e.g., 1M-5M+NaCl solutions, for desalination. In the some embodiments, the total dissolved solids in the feedstream is greater than about 60,000 ppm, 70,000 ppm, 80,000 ppm, 90,000 ppm, 100,000 ppm, 110,000 ppm, 120,000 ppm, 130,000 ppm, 140,000 ppm, 150,000 ppm, 160,000 ppm, 170,000 ppm, 180,000 ppm, 190,000 ppm, 200,000 ppm, 210,000 ppm, 220,000 ppm, 230,000 ppm, 240,000 ppm, 250,000 ppm, 260,000 ppm, 270,000 ppm, 280,000 ppm, 290,000 ppm, 300,000 ppm, etc. In some embodiments, the one or more scalants include minerals, metals, etc., or combinations thereof. In some embodiments, the scalants include hydroxides, carbonates, phosphates, sulfates, etc. In some embodiments, the scalants include $\text{Ca}(\text{OH})_2$, CaCO_3 , FeCO_3 , $\text{Mg}(\text{OH})_2$, MgCO_3 , MnCO_3 , SrCO_3 , BaSO_4 , CaSO_4 , MgSO_4 , SrSO_4 , alkali metal salts, e.g., NaCl, or combinations thereof.

[0037] At **204**, the pH of the combined produced water and solvent is raised to produce an elevated-pH composition. In some embodiments, the pH is raised **204** by the solvent. In some embodiments, the pH is raised **204** via the addition of a supplemental basic component. Without wishing to be bound by theory, the solubility of scalants found in the produced water can be pH-dependent, e.g., with salts being less soluble in more alkaline conditions. Thus, as the pH of the solution increases, thermodynamic equilibrium is driven to induce formation of a solid phase.

[0038] At **206**, a solid phase is precipitated from the elevated-pH composition, the solid phase including one or more of the scalants. At **208**, the one or more scalants are separated from the elevated-pH composition, e.g., via sieving with a membrane. At **210**, the elevated-pH composition is heated to a temperature T_H to demix a descaled water

component from a dewatered solvent component. At **212**, the dewatered solvent component is removed to isolate a descaled water product. In some embodiments, the descaled water product includes less than about 15%, less than about 10%, or less than about 5% weight percent total dissolved solids.

[0039] At **214**, the dewatered solvent component is cooled. In some embodiments, the dewatered solvent component is cooled **214** to temperature T_L . As will be discussed in greater detail below, in some embodiments, heat lost in the cooling of the dewatered solvent component (as well as the descaled water component) from T_H can be recycled. In some embodiments, the heat is recycled in method **200**, e.g., at step **210**, or a separate process. At **216**, the dewatered solvent component is combined with the volume of produced water, e.g., for use in steps **202** and/or **204**. In some embodiments, method **200** is a continuous or substantially continuous process. In some embodiments, method **200** is a semi-batch process. In some embodiments, method **200** is a batch or substantially batch process.

[0040] Referring now to FIG. 3, some embodiments of the present disclosure are directed to a system **300** of performing temperature swing solvent extraction, e.g., descaling/desalination of produced water/high-salinity brine. In some embodiments, system **300** includes a feedstream **302** in fluid communication with a fluid source **304**. In some embodiments, fluid source **304** is from any suitable source, e.g., existing in the natural environment, effluent from industrial processes, etc. In some embodiments, fluid source **304**, and thus feedstream **302**, includes brines, produced waters, or combinations thereof. In some embodiments, fluid source **304** includes high-salinity brine, produced water and flowback from oil and gas industry, fluegas desulfurization wastewater, inland desalination concentrates, landfill leachate, waste streams of zero/minimum liquid discharge operations, waste effluents from thermoelectric power plants, discharges of coal-to-chemicals facilities, etc., or combinations thereof. In some embodiments, fluid source **304** includes a fluid having a total dissolved solids greater than about 60,000 ppm, 70,000 ppm, 80,000 ppm, 90,000 ppm, 100,000 ppm, 110,000 ppm, 120,000 ppm, 130,000 ppm, 140,000 ppm, 150,000 ppm, 160,000 ppm, 170,000 ppm, 180,000 ppm, 190,000 ppm, 200,000 ppm, 210,000 ppm, 220,000 ppm, 230,000 ppm, 240,000 ppm, 250,000 ppm, 260,000 ppm, 270,000 ppm, 280,000 ppm, 290,000 ppm, 300,000 ppm, etc.

[0041] In some embodiments, system **300** includes a solvent source **306**. In some embodiments, solvent source **306** includes one or more solvents with temperature-dependent water solubility. As discussed above, in some embodiments, the solvent is basic. In some embodiments, the solvent includes one or more hydrophilic moieties in a mainly hydrophobic structure. In some embodiments, the solvent is an amine solvent, e.g., a primary, secondary, or tertiary amine solvent. In some embodiments, the solvent includes diisopropylamine (DIPA), N-ethylcyclohexylamine (ECHA), and N,N-dimethylcyclohexylamine (DMCHA), triethylamine (TEA), N-methylcyclohexylamine (nMCHA), N,N-dimethylisopropylamine (DMIPA), or combinations thereof.

[0042] In some embodiments, system **300** includes an extractor **308** in fluid communication with feedstream **302** and solvent source **306**. In some embodiments, system **300** includes a plurality of extractors **308**, e.g., arranged in

parallel, arranged in series, or combinations thereof. In some embodiments, feedstream 302 and solvent from solvent source 306 are combined in extractor 308. In some embodiments, the ratio of feedstream 302 to solvent in extractor 308 is less than about 25.3 mL/mol, 20.2 mL/mol, 15 mL/mol, 10.1 mL/mol, 5.1 mL/mol, 2.5 mL/mol, etc. As discussed above, in some embodiments, feedstream 302 and solvent are combined at a temperature T_L . In some embodiments, feedstream 302 and solvent are combined at different temperatures and brought to a temperature T_L . In some embodiments, T_L is below about 20° C. In some embodiments, T_L is below about 10° C. In some embodiments, T_L is about 5° C. At temperature T_L , water from feedstream 302 favorably partitions into the solvent phase, producing a raffinate component that retains the scalants from the liquid feedstream. In some embodiments, the raffinate component includes an aqueous phase, a solid phase, or combinations thereof.

[0043] Further, as discussed above, upon combination feedstream 302 and solvent from solvent source 306, liquid from the feedstream is extracted into the solvent to form a water-in-solvent extract component. In some embodiments, extractor 308 includes at least a first outlet 308A. In some embodiments, extractor 308B includes a second outlet 308B. In some embodiments, a water-in-solvent extract outlet stream 310 is in communication with first outlet 308A. In some embodiments, a raffinate outlet stream 312 is in communication with second outlet 308B. In some embodiments, raffinate outlet stream 312 includes an aqueous phase, a solid phase, or combinations thereof. In some embodiments, extractor 308 includes one or more membranes 308C configured to isolate solid phase products, e.g., from the raffinate component. Membranes 308C can be of any suitable composition and pore-size to isolate the components of a particular solid phase. In some embodiments, membranes 308C are microporous, nanoporous, etc. In some embodiments, a membrane 308C is positioned in second outlet 308B. In some embodiments, raffinate outlet stream 312 includes an aqueous phase, any solid phase having been removed prior to exiting extractor 308, e.g., via 308B.

[0044] Extractor 308 can be of any suitable shape and volume to accommodate a desired volume of liquid, e.g., feedstream 302 in one or more solvents. In one exemplary embodiment, extractor 308 has a generally cylindrical shape, e.g., a liquid-liquid extraction column. Feedstream 302 is introduced at the top of extractor 108 and contacts solvent therein at temperature T_L . The solvent progressively extracts water from the denser aqueous phase as it sinks toward the bottom. Scalants precipitate out and ultimately settle at the bottom of extractor 308, and are subsequently sieved off by membranes 302C as liquid streams, e.g., 308A and 308B, exit the extractor.

[0045] In some embodiments, system 300 includes a separator 314 in fluid communication with water-in-solvent extract outlet stream 310. Separator 314 is configured to demix a descaled water component from a dewatered solvent component. In some embodiments, separator 314 includes at least a third outlet 316 and a fourth outlet 318. In some embodiments, a descaled water component outlet stream 320 is in communication with third outlet 316 to remove the descaled water component from separator 314. As discussed above, in some embodiments, descaled water component outlet stream 320 includes less than about 5% weight percent total dissolved solids. In some embodiments, a dewatered solvent component outlet stream 322 is in

communication with fourth outlet 318 to remove the dewatered solvent component from separator 314.

[0046] In some embodiments, system 300 includes a temperature controller 324A. In some embodiments, temperature controller 324A is in thermal communication with extractor 308 and/or water-in-solvent extract outlet stream 310, e.g., via a heat source, cooling system, etc. In some embodiments, temperature controller 324A is in thermal communication with raffinate outlet stream 312, separator 314, descaled water component outlet stream 320, dewatered solvent component outlet stream 322, dewatered solvent recycle conduit 326, feedstream 302, solvent stream, or combinations thereof. In some embodiments, temperature controller 324A is in thermal communication with water-in-solvent extract outlet stream 310 via separator 314. Temperature controller 324A is configured to maintain a predetermined temperature in extractor 308, e.g., temperature T_L , as well as in water-in-solvent extract outlet stream 310, e.g., temperature T_H . The heat input to system 100 can be supplied from low-grade thermal sources. In some embodiments, the heat is supplied from renewable energy sources, e.g., wind, solar, hydrothermal, etc., or combinations thereof.

[0047] In some embodiments, system 300 includes a pH controller 324B. In some embodiments, pH controller 324B is in communication with extractor 308. In some embodiments, pH controller 324B is in communication with water-in-solvent extract outlet stream 310, raffinate outlet stream 312, separator 314, descaled water component outlet stream 320, dewatered solvent component outlet stream 322, dewatered solvent recycle conduit 326, feedstream 302, solvent stream, or combinations thereof. pH controller 324B is configured to maintain a predetermined pH in components of system 300, e.g., a lower pH in raffinate outlet stream 312, but a higher pH in extractor 108. In some embodiments, pH controller 324B increases the pH in a component of system 300 via addition of additional solvent, a basic component, or combinations thereof.

[0048] In some embodiments, system 300 includes a dewatered solvent recycle conduit 326 in fluid communication with dewatered solvent component outlet stream 322 and extractor 308. Dewatered solvent recycle conduit 326 is configured to direct the dewatered solvent component outlet stream 322 to extractor 308 for recycling, e.g., in embodiments where extractor 108 is operated in a continuous or semi-continuous manner. In some embodiments, system 300 includes one or more heat exchangers 328. In some embodiments, heat exchangers 328 are in thermal communication with water-in-solvent extract outlet stream 310, raffinate outlet stream 312, separator 314, descaled water component outlet stream 320, dewatered solvent component outlet stream 322, dewatered solvent recycle conduit 326, extractor 308, feedstream 302, solvent stream, or combinations thereof. Heat exchangers 328 are configured to recycle heat to reduce the overall energy cost of system 100. By way of example, in some embodiments, heat exchanger 328 extracts heat from dewatered solvent component outlet stream 322 and returns it to water-in-solvent extract outlet stream 310 to help demix the water and solvent components of that stream.

[0049] System 300 is advantageous for use both in front of plant and back of plant implementations. By way of example, in front of plant implementations, system 300 can be used to treat fluids existing in nature to decontaminate those fluids, isolate impurities for subsequent sale as a

product, isolate impurities for use in industrial processes to produce other products, etc., or combinations thereof. By way of further example, in back of plant implementations, system **300** can be used to treat produced waters generated by industrial processes, either for reuse in the industrial processes, isolate byproduct impurities for subsequent sale as a product unto itself, decontaminate produced waters so as to provide less harmful wastes into the environment, etc., or combinations thereof.

[0050] Referring now to FIG. 4, some embodiments of the present disclosure are directed to a system **400** for desalinating a feedstream utilizing temperature swing solvent extraction-stepwise release (TSSE-SR). In some embodiments, system **400** includes a feedstream **402** in fluid communication with a fluid source **404**. As discussed above, in some embodiments, fluid source **404** is from any suitable source, e.g., existing in the natural environment, effluent from industrial processes, etc. In some embodiments, fluid source **404**, and thus feedstream **402**, includes brines, produced waters, or combinations thereof. In some embodiments, fluid source **404** includes high-salinity brine, produced water and flowback from oil and gas industry, fluegas desulfurization wastewater, inland desalination concentrates, landfill leachate, waste streams of zero/minimum liquid discharge operations, waste effluents from thermoelectric power plants, discharges of coal-to-chemicals facilities, etc., or combinations thereof.

[0051] In some embodiments, system **400** includes a solvent source **406**. As discussed above, in some embodiments, solvent source **406** includes one or more solvents with temperature-dependent water solubility. As discussed above, in some embodiments, the solvent is basic. In some embodiments, the solvent includes one or more hydrophilic moieties in a mainly hydrophobic structure. In some embodiments, the solvent is an amine solvent, e.g., a primary, secondary, or tertiary amine solvent. In some embodiments, the solvent includes diisopropylamine (DIPA), N-ethylcyclohexylamine (ECHA), and N,N-dimethylcyclohexylamine (DMCHA), triethylamine (TEA), N-methylcyclohexylamine (nMCHA), N,N-dimethylisopropylamine (DMIPA), or combinations thereof.

[0052] In some embodiments, system **400** includes an extractor **408** in fluid communication with feedstream **402** and solvent source **406**. In some embodiments, system **400** includes a plurality of extractors **408**, e.g., arranged in parallel, arranged in series, or combinations thereof. In some embodiments, feedstream **402** and solvent from solvent source **406** are combined, e.g., in a first extractor **408A**. In some embodiments, the ratio of feedstream **402** to solvent in first extractor **408A** is less than about 25.3 mL/mol, 20.2 mL/mol, 15 mL/mol, 10.1 mL/mol, 5.1 mL/mol, 2.5 mL/mol, etc.

[0053] In some embodiments, feedstream **402** and solvent are combined at a temperature T_1 . In some embodiments, T_1 is below about 20° C. In some embodiments, T_1 is about 16° C. In some embodiments, at the initial temperature, the solvent is hygroscopic and absorbs water while partially rejecting salt.

[0054] As discussed above, the water/solvent mixture separates into two immiscible liquid phases in first extractor **408A**, a water-in-solvent component E_1 and a raffinate component R_1 , that are physically separated. In some embodiments, the water-in-solvent component E_1 and raffinate component R_1 are separated via decanting, other suit-

able separation process, or combinations thereof. In some embodiments, the raffinate component at this stage, R_1 , is concentrated brine. In some embodiments, the water-in-solvent component at this stage, E_1 , is a mixture including solvent, water, small amounts of salts, etc.

[0055] In some embodiments, water-in-solvent component E_1 is then heated or cooled, e.g., from T_1 , to a final temperature T_F . In some embodiments, water-in-solvent component E_1 is first heated or cooled to a second temperature, e.g., to T_2 , and then subsequently heated or cooled to T_F . In some embodiments, the heating or cooling of E_1 occurs in a series of extractors, as will be discussed in greater detail below. In some embodiments, the change to the second temperature induces the formation of an additional aqueous raffinate component, e.g., R_2 . Without wishing to be bound by theory, salts are polar, and thus salts remaining in water-in-solvent component E_1 at T_1 preferentially partition into aqueous raffinate component at the second temperature, e.g., into R_2 at T_2 . In some embodiments, the additional raffinate component is then removed, leaving another water-in-solvent component, e.g., E_2 , with reduced salt content. In some embodiments, this subsequent water-in-solvent component E_2 is heated or cooled to induce formation of subsequent water-in-solvent components and raffinate components, e.g., E_3 and R_3 , as will be discussed in greater detail below.

[0056] Still referring to FIG. 4, in some embodiments, system **400** includes a plurality of extractors, e.g., **408A**, **408B**, **408C**, etc. In some embodiments, water-in-solvent component is heated or cooled in a series of those additional extractors. In some embodiments, the plurality of extractors are in fluid communication with each other via one or more conduits. As discussed above, upon combination of feedstream **402** and solvent from solvent source **406**, liquid from the feedstream is extracted into the solvent to form the water-in-solvent extract component, e.g., E_1 . In some embodiments, extractor **408**, e.g., **408A**, includes at least a first outlet **410A**. In some embodiments, extractor **408** includes a second outlet **410B**. In some embodiments, a water-in-solvent extract outlet stream **412** is in communication with first outlet **410A**. In some embodiments, a water-in-solvent extract outlet stream **412**, e.g., E_1 , is in communication with a subsequent extractor, e.g., **408B**. In some embodiments, a raffinate outlet stream **414** is in communication with second outlet **410B**. In some embodiments, raffinate outlet stream **414** includes an aqueous phase, a solid phase, or combinations thereof.

[0057] In some embodiments, the heating/cooling of the water-in-solvent component and removal raffinate component are performed one or more times, i.e., there are one or more “stages” of mixture heating in and raffinate component removal from a series of extractors, **408A**, **408B**, **408C**, etc., via a series of water-in-solvent extract outlet streams **412** to communicate water-in-solvent extract component, e.g., E_1 , E_2 , E_3 , etc., from extractor to extractor and a series of raffinate outlet streams **414** to remove raffinate components, e.g., R_1 , R_2 , R_3 , etc., from each extractor. In some embodiments, the heating/cooling of the water-in-solvent component and removal raffinate component are performed a plurality of times. In some embodiments, water-in-solvent component E_1 is heated or cooled, e.g., from T_1 , to at least one intermediate temperature T_N . In some embodiments, and as discussed above, T_N is chosen so that it induces the formation of an aqueous raffinate component, R_N . Salts

remaining in the mixture at T_N preferentially partition into R_N . R_N is then removed, leaving the extract, E_N . In some embodiments, E_N is then heated or cooled to another intermediate temperature T_N , forming yet another raffinate component R_N and another water-in-solvent component E_N , which are then separated, and so on. R_N stages include a small portion of the water remaining in the mixture but are concentrated in salts. Experiments have shown that R_N aqueous phases can be more concentrated than the first aqueous phase, R_1 , or the feedstream **402**. Removing R_N from the desalination process decreases the final product water salinity, thus producing higher quality product water.

[0058] In some embodiments, any number of heating or cooling stages to intermediate temperatures T_N can be used until finally the water-in-solvent component E_N arrives at final temperature T_F . In some embodiments, the temperature swing from T_1 to T_F can be accomplished as a series of discrete temperature steps. In some embodiments, the number of heating or cooling stages to intermediate temperatures T_N is greater than 1. In some embodiments, the number of heating or cooling stages to intermediate temperatures T_N is greater than 2. In some embodiments, the number of heating or cooling stages to intermediate temperatures T_N is greater than 3. In some embodiments, the number of heating or cooling steps to intermediate temperatures T_N is greater than 5. In some embodiments, the number of heating or cooling steps to intermediate temperatures T_N is greater than 10. In some embodiments, the temperature swing from T_1 to T_F can be accomplished as a continuous temperature gradient, e.g., in a single extractor or a series of extractors.

[0059] In some embodiments, extractor **408**, e.g., **408A**, includes one or more membranes **416** configured to isolate solid phase products, e.g., from the raffinate component. In some embodiments, a membrane **416** is positioned in second outlet **410B**. Membrane **416** can be of any suitable composition and pore-size to isolate the components of a particular solid phase. In some embodiments, membrane **416** is microporous, nanoporous, etc. In some embodiments, raffinate outlet stream **414** includes an aqueous phase, any solid phase having been removed prior to exiting extractor **408**, e.g., via **410B**, etc.

[0060] In some embodiments, system **400** includes a separator **418** in fluid communication with a water-in-solvent extract outlet stream **412**. Separator **418** is configured to demix a descaled water component from a dewatered solvent component. In some embodiments, separator **418** includes at least a third outlet **420** and a fourth outlet **422**. In some embodiments, a descaled water component outlet stream **424** is in communication with third outlet **420** to remove the descaled water component from separator **418**. As discussed above, in some embodiments, descaled water component outlet stream **424** includes less than about 5% weight percent total dissolved solids. In some embodiments, a dewatered solvent component outlet stream **426** is in communication with fourth outlet **422** to remove the dewatered solvent component from separator **418**. In some embodiments, at least a portion of dewatered solvent component outlet stream **426** is recycled back to extractors **408**, e.g., via solvent source **406**.

[0061] Additional aspects from system **300** not explicitly discussed with respect to system **400**, e.g., temperature controller **324**, heat exchangers **328**, etc., may also be configured for use with system **400**.

[0062] Referring now to FIG. 5, some embodiments of the present disclosure are directed to a method **500** of performing temperature swing solvent extraction-stepwise release (TSSE-SR) desalination of hypersaline brines. As discussed above, in some embodiments, the feedstream includes brines, produced waters, or combinations thereof. In some embodiments, the feedstream includes high-salinity brine, produced water and flowback from oil and gas industry, fluegas desulfurization wastewater, inland desalination concentrates, landfill leachate, waste streams of zero/minimum liquid discharge operations, waste effluents from thermoelectric power plants, discharges of coal-to-chemicals facilities, etc., or combinations thereof. At **502**, a feedstream including a concentration of dissolved salts is provided. At **504**, the feedstream is combined with one or more solvents. As discussed above, in some embodiments, the one or more solvents has temperature-dependent water solubility. In some embodiments, the solvent includes aliphatic amines, cyclic amines, pyridines, piperidines, glycol ethers, or combinations thereof. In some embodiments, the solvent includes diisopropylamine (DIPA), N-ethylcyclohexylamine (ECHA), and N,N-dimethylcyclohexylamine (DMCHA), triethylamine (TEA), N-methylcyclohexylamine (nMCHA), N,N-dimethylisopropylamine (DMIPA), or combinations thereof. At **506**, the combined feedstream and solvent is brought to a temperature T_1 . In some embodiments, T_1 is below about 20° C. In some embodiments, T_1 is about 16° C. At **508**, water is extracted from the feedstream into the solvent to form a water-in-solvent component and a raffinate component at temperature T_1 . As discussed above, the raffinate component includes an increased concentration of dissolved salts. At **510**, the water-in-solvent component is separated from the raffinate component. At **512**, a previous water-in-solvent component produced via a previous separation step is brought to at least one new temperature T_N to produce a biphasic mixture of a subsequent water-in-solvent component and a subsequent raffinate component at temperature T_N . At **514**, the subsequent water-in-solvent component is separated from the subsequent raffinate component. In some embodiments, steps **512** and **514** are repeated 2 or more times. At **516**, a subsequent water-in-solvent component is brought to a temperature T_F to produce a biphasic mixture of dewatered solvent and descaled water. In some embodiments, T_F is between about 40° C. and about 80° C. In some embodiments, T_F is about 70° C. In some embodiments, the temperature swing from T_1 to T_F is a continuous temperature gradient. At **518**, the dewatered solvent and the descaled water are separated. At **520**, the dewatered solvent is recycled to the combined feedstream and solvent.

EXAMPLE

[0063] Continuous operation of systems and methods of the present disclosure were simulated by semibatch experiments with repeated extraction cycles, using DIPA as the solvent and 5.0 M NaCl solution as the hypersaline feed. To simulate solvent regeneration in continuous operation, the DIPA solvent was preloaded with DI water at about 6.4 w/w % and consecutively reused in three repeated TSSE cycles. 1.5 mL of a fresh brine (5.0 M NaCl) was introduced into 60 g of DIPA solvent in each extraction cycle to achieve a brine to solvent ratio of 2.5 mL/mol. The precipitated solids were sieved off with a microporous membrane under vacuum filtration and then weighed after drying. The product water

collected from each extraction cycle was weighed to evaluate water recovery and analyzed for NaCl and solvent residue concentrations.

[0064] Referring now to FIGS. 6A-6B, water recovery, Y , and salt precipitated, P_{salt} , of each extraction cycle were evaluated to examine recyclability of the systems and methods of the present disclosure. Water recovery is defined as the weight percent of the product water relative to the initial brine feed. High Y of 91.2, 95.8, and 95.9% were obtained for the 1st, 2nd, and 3rd cycles, respectively. Measured water recoveries were marginally below 100%, even though all the water was extracted from the brine feed in each cycle. Without wishing to be bound by theory, this discrepancy is mainly attributed to conservative sampling of the product water during separation from the biphasic mixture to avoid contamination by the solvent and slight undersaturation of the solvent in the 1st cycle. Y remained practically constant when the solvent was reused for the 2nd and 3rd cycles, indicating that ability of the solvent to extract water from the hypersaline feed is preserved. Almost all the salt in the 5.0 M NaCl brines precipitated out after water was extracted by the solvent and high P_{salt} of ≈ 91 , 90, and 91% were maintained in the 1st, 2nd, and 3rd extraction cycles, respectively. At the end of the last cycle, the DIPA solvent was measured to hold ≈ 6.5 w/w % water, effectively identical to the initial water content, and thus, further highlighting solvent recyclability in continuous operation.

[0065] The product water quality in repeated extraction cycles was assessed for salt concentration and solvent residue content. NaCl concentrations in the product water from each extraction cycle were 0.26, 0.31, and 0.29 M. The product water salt concentrations are markedly lower than the hypersaline feed of 5.0 M NaCl brine (93.8-94.8% reduction) and the amount of salt in the product water corresponds to 4.3, 5.2, and 5.0 w/w % relative to NaCl in the initial brine. Solvent residues in the product water were comparable at about 0.2 mol/L between the extraction cycles investigated.

[0066] Osmotic pressure reductions of 93.1-93.9% were also achieved. With substantially lowered TDS concentration and osmotic pressure, the desalted product water can be further polished using conventional techniques, such as reverse osmosis, for post-treatment with much less energy demand and fewer technical constraints, to yield a fit-for-purpose reuse stream and even fresh drinking water. The trace amount of solvent residues can also be recovered from the product water and returned to the cycle to curtail solvent loss.

[0067] Referring now to FIG. 7, the potential of the systems and methods of the present disclosure was further evaluated with an actual field sample. Hypersaline feed was prepared by evaporative concentration of RO effluent from the San Luis plant, CA, which desalinates irrigation drainage water of San Joaquin Valley to reach TDS concentration of $\approx 295,000$ ppm, i.e., approximately equivalent to 5.0 M NaCl brine. Extraction of all the water from the brine sample precipitated $\approx 85.2\%$ of the dissolved solids, which were removed by filtration. Product water TDS concentration was substantially reduced by $\approx 88.8\%$ relative to the feed brine, from 295.4 g/L to 33.1 g/L. Total organic carbon (TOC) concentration of the product water (0.27 mol/L) was comparable to those obtained from semibatch TSSE-ZLD experiments with 5.0 M NaCl solution as brine feed, which had no initial organic content, indicating that TOC in the

product water is mostly attributable to the solvent that has partitioned to the aqueous phase.

[0068] Referring now to FIGS. 8A-8B, in an exemplary embodiment, a diisopropylamine (DIPA)-water-sodium chloride (NaCl) TSSE-SR desalination system was constructed. Experiments were performed using 100.0 g of DIPA mixed with 100.0 g of 5.6 wt % NaCl_(aq) solution (1 mol/L NaCl solution). Performing multiple releases, with $T_1=16^\circ\text{C}$., $T_2=22^\circ\text{C}$., $T_3=31^\circ\text{C}$., $T_4=35^\circ\text{C}$., $T_F=T_5=70^\circ\text{C}$., produced a final product water, R_5 , with 0.30 wt. % NaCl. A comparison TSSE system using the same feed and outer operating temperatures without multiple release steps produced water with 0.76 wt. % NaCl. Without wishing to be bound by theory, the stepwise release process was responsible for a greater than factor-of-two decrease in salt contents.

[0069] It is apparent that the intermediate aqueous phases, performed at 22°C ., 31°C ., and 35°C ., included substantially higher concentrations of salt than the final product water (see FIG. 8A). These intermediate aqueous phases were only a small portion of the overall mass of product water (see FIG. 8B). By removing the intermediate aqueous phases from the salt was removed, leading to superior quality product water.

[0070] Methods and system of the present disclosure are advantageous to treat feedstreams with high total TDS. Even feedstreams with TDS approaching 300,000 ppm can be treated, with final concentrations having less than 5% total dissolved solids. These results are achieved without the high-grade thermal energy requirements associated with evaporative phase change properties, i.e., steam that is $>100^\circ\text{C}$. Temperature swing solvent extraction is uniquely suited for the desalination of hypersaline brines, a segment of intensifying environmental importance but not accessible by RO and handicapped by intrinsically poor energy efficiencies of evaporative methods. The technology is not restricted by feed solution properties, unlike membrane-based RO with hydraulic/osmotic pressure limitation. Because TSSE does not require a phase change of water, the penalizing energy cost associated with the enthalpy of vaporization is sidestepped and significantly higher energy efficiencies are attainable. As only moderate temperatures are needed ($<70^\circ\text{C}$. in this study), the heat input can be supplied by low-grade thermal sources such as industrial waste heat, shallow-well geothermal heat, and low-concentration solar collectors, further enhancing the sustainability of TSSE. Other solvents with different chemical structures and properties can yield better performances to further expand the prospects of TSSE for energy-efficient and cost-effective desalination of high-salinity brines.

[0071] Among the solvents, DIPA exhibited the highest water extraction efficiency whereas ECHA and DMCHA produced water with the lowest salt content and solvent residue content, respectively. Specific performance objectives, such as, high water extraction efficiency, high salt removal, and low solvent loss, can be achieved by rational solvent selection. High water recovery $>50\%$ was demonstrated for TSSE desalination of 1.5 M NaCl brine in semi-batch experiments with multiple extraction cycles, highlighting the potential for a scaled-up continuous process. Substantial energy savings over conventional methods were achieved, drastically improving sustainability and enhancing economic feasibility. In some embodiments, the methods and systems of the present disclosure are applied to

desalination/dewatering/reuse of hypersaline brines, e.g., produced water from the oil and gas industry, waste streams of minimum/zero liquid discharge operations, inland desalination concentrate, landfill leachate, flue gas desulfurization wastewater, treatment of high-scaling propensity feedwaters, and the like.

[0072] Although the invention has been described and illustrated with respect to exemplary embodiments thereof, it should be understood by those skilled in the art that the foregoing and various other changes, omissions and additions may be made therein and thereto, without parting from the spirit and scope of the present invention.

What is claimed is:

1. A method of performing temperature swing solvent extraction (TSSE) desalination of high-salinity brines, comprising:

- providing a feedstream having a total dissolved solids greater than about 250,000 ppm;
- combining the feedstream with a solvent, wherein the solvent has temperature-dependent water solubility;
- bringing the combined feedstream and solvent to a temperature T_L ;
- extracting a liquid from the feedstream into the solvent to form a water-in-solvent extract component and a raffinate component at temperature T_L , wherein the raffinate component includes an aqueous phase, a solid phase, or combinations thereof;
- separating the water-in-solvent extract component from the raffinate component;
- heating the water-in-solvent extract component to a temperature T_H to produce a biphasic mixture of dewatered solvent and descaled water; and
- separating the dewatered solvent and the descaled water, wherein the descaled water includes less than about 5% weight percent total dissolved solids.

2. The method according to claim 1, wherein the feedstream includes brine, produced water, or combinations thereof.

3. The method according to claim 1, further comprising: cooling the dewatered solvent component from temperature T_H ; and combining the dewatered solvent component with the feedstream.

4. The method according to claim 1, further comprising: precipitating the solid phase; and sieving the solid phase from a liquid phase, the solid phase including one or more sealants from the feedstream.

5. The method according to claim 4, wherein the one or more sealants includes an alkali metal salts, $\text{Ca}(\text{OH})_2$, CaCO_3 , FeCO_3 , $\text{Mg}(\text{OH})_2$, MgCO_3 , MnCO_3 , SrCO_3 , BaSO_4 , CaSO_4 , MgSO_4 , SrSO_4 , or combinations thereof.

6. The method according to claim 1, wherein the solvent includes diisopropylamine (DIPA), N-ethylcyclohexylamine (ECHA), and N,N-dimethylcyclohexylamine (DMCHA), triethylamine (TEA), N-methylcyclohexylamine (nMCHA), N,N-dimethylisopropylamine (DMIPA), or combinations thereof.

7. The method according to claim 1, wherein T_L is below about 20° C.

8. (canceled)

9. The method according to claim 1, wherein T_H is between about 40° C. and about 80° C.

10. (canceled)

11. (canceled)

12. The method according to claim 1, wherein the feedstream to solvent ratio is less than about 15 mL/mol.

13. A method of performing temperature swing solvent extraction-stepwise release (TSSE-SR) desalination of hypersaline brines, comprising:

- providing a feedstream including a concentration of dissolved salts;
- combining the feedstream with one or more solvents, wherein the one or more solvents has temperature-dependent water solubility;
- bringing the combined feedstream and solvent to a temperature T_1 ;
- extracting water from the feedstream into the solvent to form a water-in-solvent component and a raffinate component at temperature T_1 , wherein the raffinate component includes an increased concentration of dissolved salts;
- separating the water-in-solvent component from the raffinate component;
- bringing a previous water-in-solvent component produced via a previous separation step to at least one new temperature T_N to produce a biphasic mixture of a subsequent water-in-solvent component and a subsequent raffinate component at temperature T_N ;
- separating the subsequent water-in-solvent component from the subsequent raffinate component;
- bringing a subsequent water-in-solvent component to a temperature T_F to produce a biphasic mixture of dewatered solvent and descaled water;
- separating the dewatered solvent and the descaled water, and
- recycling the dewatered solvent to the combined feedstream and solvent, wherein the feedstream includes brines, produced waters, or combinations thereof.

14. (canceled)

15. (canceled)

16. (canceled)

17. A system of performing temperature swing solvent extraction (TSSE) desalination of high-salinity brines, comprising:

- a feedstream in fluid communication with a fluid source, the fluid source including a fluid having a total dissolved solids greater than about 250,000 ppm;
- a solvent source including one or more solvents with temperature-dependent water solubility;
- one or more extractors in fluid communication with the feedstream and the solvent source, the extractor including at least a first outlet and a second outlet;
- a water-in-solvent extract outlet stream in communication with the first outlet;
- a raffinate outlet stream in communication with the second outlet, wherein the raffinate outlet stream includes an aqueous phase, a solid phase, or combinations thereof;
- a separator in fluid communication with the water-in-solvent extract outlet stream, the separator including at least a third outlet and a fourth outlet;
- a descaled water component outlet stream in communication with the third outlet, the descaled water component including less than about 5% weight percent total dissolved solids;
- a dewatered solvent component outlet stream in communication with the fourth outlet;

a temperature controller in communication with the one or more extractors and the water-in-solvent extract outlet stream; and

a dewatered solvent recycle conduit in fluid communication with the dewatered solvent component outlet stream and the one or more extractors, the dewatered solvent recycle conduit configured to direct the dewatered solvent component outlet stream to the extractor

wherein the one or more solvents include diisopropylamine (DHA), N-ethylcyclohexylamine (ECHA), and N,N-dimethylcyclohexylamine (DMCHA), triethylamine (TEA), N-methylcyclohexylamine (nMCHA), N,N-dimethylisopropylamine (DMIPA), or combinations thereof.

18. (canceled)

19. (canceled)

20. (canceled)

21. The method according to claim 13, wherein the steps of

bringing a previous water-in-solvent component produced via a previous separation step to at least one new temperature T_N to produce a biphasic mixture of a subsequent water-in-solvent component and a subsequent raffinate component at temperature T_N , and

separating the subsequent water-in-solvent component from the subsequent raffinate component,

is repeated 2 or more times.

22. The method according to claim 21, wherein the temperature swing from T_1 to T_F is a continuous temperature gradient.

23. The method according to claim 13, wherein T_1 is below about 20° C.

24. The method according to claim 23, wherein T_1 is about 16° C.

25. The method according to claim 13, wherein T_F is between about 40° C. and about 80° C.

26. The method according to claim 25, wherein T_F is about 70° C.

27. The method according to claim 13, wherein the solvent includes diisopropylamine (DIPA), N-ethylcyclohexylamine (ECHA), and N,N-dimethylcyclohexylamine (DMCHA), triethylamine (TEA), N-methylcyclohexylamine (nMCHA), N,N-dimethylisopropylamine (DMIPA), or combinations thereof.

28. The system according to claim 17, wherein a first extractor is maintained at a temperature T_L and the water-in-solvent extract outlet stream is heated to a temperature T_H , wherein T_L is below about 20° C. and T_H is between about 40° C. and about 80° C.

29. The system according to claim 28, further comprising at least a second extractor in fluid communication with the first extractor via water-in-solvent extract outlet stream, wherein at least a second extractor is maintained at an intermediate temperature between T_L and T_H and the water-in-solvent extract outlet stream is heated to the intermediate temperature.

* * * * *