



US 20230209880A1

(19) **United States**

(12) **Patent Application Publication**  
**Yang et al.**

(10) **Pub. No.: US 2023/0209880 A1**

(43) **Pub. Date: Jun. 29, 2023**

(54) **BORDERLESS DISPLAY WITH  
LIGHT-BENDING STRUCTURES**

*G02F 1/1335* (2006.01)

*H10K 50/84* (2006.01)

*H10K 50/842* (2006.01)

*H10K 59/40* (2006.01)

(71) Applicant: **Apple Inc.**, Cupertino, CA (US)

(72) Inventors: **Tseng-Mau Yang**, Mississauga (CA);  
**Christopher D. Prest**, Portola Valley,  
CA (US); **Dale N. Memering**, New  
York, NY (US)

(52) **U.S. Cl.**

CPC ..... *H10K 50/858* (2023.02); *G02F 1/133308*  
(2013.01); *G02F 1/133526* (2013.01); *H10K*  
*50/84* (2023.02); *H10K 50/8428* (2023.02);  
*H10K 59/40* (2023.02); *G02F 1/133331*  
(2021.01)

(21) Appl. No.: **18/177,676**

(22) Filed: **Mar. 2, 2023**

**Related U.S. Application Data**

(60) Division of application No. 17/481,751, filed on Sep. 22, 2021, now Pat. No. 11,626,578, which is a continuation of application No. 16/806,224, filed on Mar. 2, 2020, now Pat. No. 11,165,046, which is a continuation of application No. 15/234,955, filed on Aug. 11, 2016, now Pat. No. 10,600,997, which is a continuation of application No. 13/631,024, filed on Sep. 28, 2012, now abandoned.

**Publication Classification**


(51) **Int. Cl.**

*H10K 50/858* (2006.01)

*G02F 1/1333* (2006.01)

(57) **ABSTRACT**

An electronic device may be provided with a display mounted in a housing. The display may have an array of display pixels that provide image light to a user. The array of display pixels may form an active display structure with a rectangular shape. The rectangular active display structure may be surrounded by an inactive border region. Optical structures such as a sheet of glass or another optical member may have portions that are configured to bend light from the display pixels along the periphery of the active display structure. The optical member may have an area that is larger than the area of the active display structure, so that the presence of the optical member may serve to enlarge the apparent size of the display. Solidified liquid polymer may be used to support the optical structures and may be interposed between the optical structures and the active display structures.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5






FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10






FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17






FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25



## BORDERLESS DISPLAY WITH LIGHT-BENDING STRUCTURES

[0001] This application is a division of U.S. patent application Ser. No. 17/481,751, filed Sep. 22, 2021, which is a continuation of U.S. patent application Ser. No. 16/806,224, filed Mar. 2, 2020, now U.S. Pat. No. 11,165,046, which is a continuation of U.S. patent application Ser. No. 15/234,955, filed Aug. 11, 2016, now U.S. Pat. No. 10,600,997, which is a continuation of U.S. patent application Ser. No. 13/631,024, filed Sep. 28, 2012, which are hereby incorporated by reference herein in their entireties.

### BACKGROUND

[0002] This relates generally to electronic devices, and more particularly, to electronic devices with displays.

[0003] Electronic devices often include displays. For example, cellular telephones and portable computers often include displays for presenting information to a user. An electronic device may have a housing such as a housing formed from plastic or metal. Components for the electronic device such as display components may be mounted in the housing.

[0004] It can be challenging to incorporate a display into the housing of an electronic device. Size and weight are often important considerations in designing electronic devices. If care is not taken, displays may be bulky or may be surrounded by overly large borders. The housing of an electronic device can be adjusted to accommodate a bulky display with large borders, but this can lead to undesirable enlargement of the size and weight of the housing and unappealing device aesthetics.

[0005] It would therefore be desirable to be able to provide improved displays for electronic devices.

### SUMMARY

[0006] An electronic device may be provided with a display. The display may be mounted in a housing. The display may have an array of display pixels that provide image light to a user. Display pixels may be organic light-emitting diode pixels, may be backlit liquid crystal display pixels, or may be display pixels of other types.

[0007] The array of display pixels may form an active display structure with a rectangular shape. The rectangular active display structure may be surrounded by an inactive display structure border region. Optical structures such as a sheet of glass or other optical member may have portions that are configured to bend light from the display pixels that are located along the periphery of the active display structure.

[0008] The optical member may have an area that is larger than area of the active display structure. The presence of the optical member and the portions of the optical member that are configured to bend the light may serve to enlarge the apparent size of the display. Solidified liquid polymer may be used to support the optical structures and may be interposed between the optical structures and the active display structures. A display cover layer may overlap the optical member. A touch sensor and coating layers may be included in the display.

[0009] Further features of the invention, its nature and various advantages will be more apparent from the accompanying drawings and the following detailed description of the preferred embodiments.

### BRIEF DESCRIPTION OF THE DRAWINGS

[0010] FIG. 1 is a perspective view of an illustrative electronic device such as a laptop computer with a display in accordance with an embodiment of the present invention.

[0011] FIG. 2 is a perspective view of an illustrative electronic device such as a handheld electronic device with a display in accordance with an embodiment of the present invention.

[0012] FIG. 3 is a perspective view of an illustrative electronic device such as a tablet computer with a display in accordance with an embodiment of the present invention.

[0013] FIG. 4 is a schematic diagram of an illustrative electronic device with a display in accordance with an embodiment of the present invention.

[0014] FIG. 5 is a cross-sectional side view of an illustrative display in accordance with an embodiment of the present invention.

[0015] FIG. 6 is a top view of illustrative display layers in a display having an active region with an array of display pixels and an inactive border region in accordance with an embodiment of the present invention.

[0016] FIG. 7 is a diagram showing how a mold may be used to form display structures such as glass structures with curved surfaces in accordance with an embodiment of the present invention.

[0017] FIG. 8 is a diagram showing how a slumping process may be used to form display structures such as glass structures with curved surfaces in accordance with an embodiment of the present invention.

[0018] FIG. 9 is a diagram showing how a machining process may be used to form display structures such as glass structures with curved surfaces in accordance with an embodiment of the present invention.

[0019] FIG. 10 is a cross-sectional side view of an illustrative display with a glass layer having a curved portion along the edge of a lower surface for bending light produced by an array of display pixels and thereby creating a borderless appearance for the display in accordance with an embodiment of the present invention.

[0020] FIG. 11 is a cross-sectional side view of an illustrative display with a glass layer having curved upper and lower surfaces along the edge of the glass layer for bending light produced by an array of display pixels and thereby creating a borderless appearance for the display in accordance with an embodiment of the present invention.

[0021] FIG. 12 is a cross-sectional side view of an illustrative display with a glass layer having a convex curved upper surface for bending light produced by an array of display pixels and thereby creating a borderless appearance for the display in accordance with an embodiment of the present invention.

[0022] FIG. 13 is a cross-sectional side view of an illustrative display with a glass layer having edges with curved upper surfaces for bending light produced by an array of display pixels and thereby creating a borderless appearance for the display in accordance with an embodiment of the present invention.

[0023] FIG. 14 is a cross-sectional side view of an illustrative display with a glass layer having edges with curved upper surfaces for bending light produced by an array of display pixels that is separated from the glass layer by a gap and thereby creating a borderless appearance for the display in accordance with an embodiment of the present invention.



[0024] FIG. 15 is a cross-sectional side view of an illustrative display with a glass layer having a convex curved upper surface for bending light produced by an array of display pixels that is separated from the glass layer by a gap and thereby creating a borderless appearance for the display in accordance with an embodiment of the present invention.

[0025] FIG. 16 is a cross-sectional side view of an illustrative display with a display cover layer and optical structures with angled surfaces for bending light produced by an array of display pixels and thereby creating a borderless appearance for the display in accordance with an embodiment of the present invention.

[0026] FIG. 17 is a cross-sectional side view of an illustrative display with a glass layer that is covered with one or more coating layers and that has an upper surface with curved edge regions for bending light produced by an array of display pixels and thereby creating a borderless appearance for the display in accordance with an embodiment of the present invention.

[0027] FIG. 18 is a cross-sectional side view of an illustrative display having a glass layer with a curved upper surface for bending light produced by an array of display pixels and having a layer of clear material such as solidified liquid polymer interposed between the glass layer and array of display pixels in accordance with an embodiment of the present invention.

[0028] FIG. 19 is a cross-sectional side view of an illustrative display having a glass layer with a curved lower surface for bending light produced by an array of display pixels and having a layer of clear material such as solidified liquid polymer interposed between the glass layer and array of display pixels in accordance with an embodiment of the present invention.

[0029] FIG. 20 is a cross-sectional side view of an illustrative display having a glass layer with a curved surface for bending light produced by an array of display pixels and having a planar display cover layer in accordance with an embodiment of the present invention.

[0030] FIG. 21 is a cross-sectional side view of an illustrative display having a glass layer with a curved surface for bending light produced by an array of display pixels and having a touch sensor located on a lower surface of the glass layer in accordance with an embodiment of the present invention.

[0031] FIG. 22 is a cross-sectional side view of an illustrative display having a glass layer with a curved surface for bending light produced by an array of display pixels and having a touch sensor located on an upper surface of the array of display pixels in accordance with an embodiment of the present invention.

[0032] FIG. 23 is a cross-sectional side view of an illustrative display having a glass layer with a curved surface for bending light produced by an array of display pixels and having a touch sensor located on an upper surface of the glass layer in accordance with an embodiment of the present invention.

[0033] FIG. 24 is a cross-sectional side view of an illustrative display having a glass layer with a curved surface for bending light produced by an array of display pixels and having a touch sensor located on an upper surface of the glass layer under an associated display cover layer in accordance with an embodiment of the present invention.

[0034] FIG. 25 is a cross-sectional side view of an illustrative display having a glass layer with a curved surface for

bending light produced by an array of display pixels and having a touch sensor located on a lower surface of an associated display cover layer in accordance with an embodiment of the present invention.

#### DETAILED DESCRIPTION

[0035] Electronic devices may include displays. The displays may be used to display images to a user. Illustrative electronic devices that may be provided with displays are shown in FIGS. 1, 2, and 3.

[0036] FIG. 1 shows how electronic device 10 may have the shape of a laptop computer having upper housing 12A and lower housing 12B with components such as keyboard 16 and touchpad 18. Device 10 may have hinge structures 20 that allow upper housing 12A to rotate in directions 22 about rotational axis 24 relative to lower housing 12B. Display 14 may be mounted in upper housing 12A. Upper housing 12A, which may sometimes be referred to as a display housing or lid, may be placed in a closed position by rotating upper housing 12A towards lower housing 12B about rotational axis 24.

[0037] FIG. 2 shows how electronic device 10 may be a handheld device such as a cellular telephone, music player, gaming device, navigation unit, or other compact device. In this type of configuration for device 10, housing 12 may have opposing front and rear surfaces. Display 14 may be mounted on a front face of housing 12. Display 14 may, if desired, have a display cover layer or other exterior layer that includes openings for components such as button 26. Openings may also be formed in a display cover layer or other display layer to accommodate a speaker port (see, e.g., speaker port 28 of FIG. 2).

[0038] FIG. 3 shows how electronic device 10 may be a tablet computer. In electronic device 10 of FIG. 3, housing 12 may have opposing planar front and rear surfaces. Display 14 may be mounted on the front surface of housing 12. As shown in FIG. 3, display 14 may have a cover layer or other external layer with an opening to accommodate button 26 (as an example).

[0039] The illustrative configurations for device 10 that are shown in FIGS. 1, 2, and 3 are merely illustrative. In general, electronic device 10 may be a laptop computer, a computer monitor containing an embedded computer, a tablet computer, a cellular telephone, a media player, or other handheld or portable electronic device, a smaller device such as a wrist-watch device, a pendant device, a headphone or earpiece device, or other wearable or miniature device, a television, a computer display that does not contain an embedded computer, a gaming device, a navigation device, an embedded system such as a system in which electronic equipment with a display is mounted in a kiosk or automobile, equipment that implements the functionality of two or more of these devices, or other electronic equipment.

[0040] Housing 12 of device 10, which is sometimes referred to as a case, may be formed of materials such as plastic, glass, ceramics, carbon-fiber composites and other fiber-based composites, metal (e.g., machined aluminum, stainless steel, or other metals), other materials, or a combination of these materials. Device 10 may be formed using a unibody construction in which most or all of housing 12 is formed from a single structural element (e.g., a piece of machined metal or a piece of molded plastic) or may be formed from multiple housing structures (e.g., outer housing structures that have been mounted to internal frame elements or other internal housing structures).



[0041] Display 14 may be a touch sensitive display that includes a touch sensor or may be insensitive to touch. Touch sensors for display 14 may be formed from an array of capacitive touch sensor electrodes, a resistive touch array, touch sensor structures based on acoustic touch, optical touch, or force-based touch technologies, or other suitable touch sensor components.

[0042] Displays for device 10 may, in general, include image pixels formed from light-emitting diodes (LEDs), organic LEDs (OLEDs), plasma cells, electrowetting pixels, electrophoretic pixels, liquid crystal display (LCD) components, or other suitable image pixel structures. In some situations, it may be desirable to use LCD components to form display 14, so configurations for display 14 in which display 14 is a liquid crystal display are sometimes described herein as an example. It may also be desirable to provide displays such as display 14 with backlight structures, so configurations for display 14 that include a backlight unit may sometimes be described herein as an example. Other types of display technology may be used in device 10 if desired. The use of liquid crystal display structures and backlight structures in device 10 is merely illustrative.

[0043] A display cover layer may cover the surface of display 14 or a display layer such as a color filter layer or other portion of a display may be used as the outermost (or nearly outermost) layer in display 14. A display cover layer or other outer display layer may be formed from a transparent glass sheet, a clear plastic layer, or other transparent structures.

[0044] Touch sensor components such as an array of capacitive touch sensor electrodes formed from transparent materials such as indium tin oxide may be formed on the underside of a display cover layer, may be formed on a separate display layer such as a glass or polymer touch sensor substrate, or may be integrated into other display layers (e.g., substrate layers such as a thin-film transistor layer).

[0045] A schematic diagram of an illustrative configuration that may be used for electronic device 10 is shown in FIG. 4. As shown in FIG. 4, electronic device 10 may include control circuitry 29. Control circuitry 29 may include storage and processing circuitry for controlling the operation of device 10. Control circuitry 29 may, for example, include storage such as hard disk drive storage, nonvolatile memory (e.g., flash memory or other electrically-programmable-read-only memory configured to form a solid state drive), volatile memory (e.g., static or dynamic random-access-memory), etc. Control circuitry 29 may include processing circuitry based on one or more microprocessors, microcontrollers, digital signal processors, baseband processors, power management units, audio codec chips, application specific integrated circuits, etc.

[0046] Control circuitry 29 may be used to run software on device 10, such as operating system software and application software. Using this software, control circuitry 29 may present information to a user of electronic device 10 on display 14. Display 14 may contain an array of display pixels (e.g., liquid crystal display pixels) that are organized in rows and columns. Control circuitry 29 may be used to display content for a user of device 10 on the array of display pixels in display 14.

[0047] Input-output circuitry 30 may be used to allow data to be supplied to device 10 and to allow data to be provided from device 10 to external devices. Input-output circuitry 30

may include communications circuitry 32. Communications circuitry 32 may include wired communications circuitry for supporting communications using data ports in device 10. Communications circuitry 32 may also include wireless communications circuits (e.g., circuitry for transmitting and receiving wireless radio-frequency signals using antennas).

[0048] Input-output circuitry 30 may also include input-output devices 34. A user can control the operation of device 10 by supplying commands through input-output devices 34 and may receive status information and other output from device 10 using the output resources of input-output devices 34.

[0049] Input-output devices 34 may include sensors and status indicators 36 such as an ambient light sensor, a proximity sensor, a temperature sensor, a pressure sensor, a magnetic sensor, an accelerometer, and light-emitting diodes and other components for gathering information about the environment in which device 10 is operating and providing information to a user of device 10 about the status of device 10.

[0050] Audio components 38 may include speakers and tone generators for presenting sound to a user of device 10 and microphones for gathering user audio input.

[0051] Display 14 (e.g., the array of display pixels in display 14) may be used to present images for a user such as text, video, and still images. Sensors 36 may include a touch sensor array that is formed as one of the layers in display 14.

[0052] User input may be gathered using buttons and other input-output components 40 such as touch pad sensors, buttons, joysticks, click wheels, scrolling wheels, touch sensors such as sensors 36 in display 14, key pads, keyboards, vibrators, cameras, and other input-output components.

[0053] A cross-sectional side view of an illustrative configuration that may be used for display 14 of device 10 (e.g., for display 14 of the devices of FIG. 1, FIG. 2, or FIG. 3 or other suitable electronic devices) is shown in FIG. 5. As shown in FIG. 5, display 14 may include backlight structures such as backlight unit 42 for producing backlight 44. During operation, backlight 44 travels outwards (vertically upwards in dimension Z in the orientation of FIG. 5) and passes through display pixel structures in display layers 46. This illuminates any images that are being produced by the display pixels for viewing by a user. For example, backlight 44 may illuminate images on display layers 46 that are being viewed by viewer 48 in direction 50.

[0054] Display 14 may, if desired, have one or more optical structures that are located above display layers 46. For example, display 14 may have a display cover layer such as display cover layer 84. Display cover layer 84 may be formed from a layer of clear glass, a transparent sheet of plastic, or other transparent structure. Display cover layer 84 may be mounted in housing 12 (e.g., using housing side-walls). During operation, light 44 may pass through the array of display pixels formed from display layers 46 and display cover layer 84 for viewing by user 48.

[0055] Display layers 46 may be mounted in chassis structures such as a plastic chassis structure and/or a metal chassis structure to form a display module for mounting in housing 12 or display layers 46 may be mounted directly in housing 12 (e.g., by stacking display layers 46 into a recessed portion in housing 12). Display layers 46 may form a liquid crystal display or may be used in forming displays of other types. Display layers 46 may sometimes be referred



to as a display module, a display, or an array of display pixels. The image light (light 44) that passes through the array of display pixels is used in displaying content on display 14 for user 48.

[0056] In a configuration in which display layers 46 are used in forming a liquid crystal display, display layers 46 may include a liquid crystal layer such a liquid crystal layer 52. Liquid crystal layer 52 may be sandwiched between display layers such as display layers 58 and 56. Layers 56 and 58 may be interposed between lower polarizer layer 60 and upper polarizer layer 54.

[0057] Layers 58 and 56 may be formed from transparent substrate layers such as clear layers of glass or plastic. Layers 56 and 58 may be layers such as a thin-film transistor layer and/or a color filter layer. Conductive traces, color filter elements, transistors, and other circuits and structures may be formed on the substrates of layers 58 and 56 (e.g., to form a thin-film transistor layer and/or a color filter layer). Touch sensor electrodes may also be incorporated into layers such as layers 58 and 56 and/or touch sensor electrodes may be formed on other substrates.

[0058] With one illustrative configuration, layer 58 may be a thin-film transistor layer that includes an array of thin-film transistors and associated electrodes (display pixel electrodes) for applying electric fields to liquid crystal layer 52 and thereby displaying images on display 14. Layer 56 may be a color filter layer that includes an array of color filter elements for providing display 14 with the ability to display color images. If desired, layer 58 may be a color filter layer and layer 56 may be a thin-film transistor layer.

[0059] During operation of display 14 in device 10, control circuitry 29 (e.g., one or more integrated circuits such as components 68 on printed circuit 66 of FIG. 5) may be used to generate information to be displayed on display 14 (e.g., display data). The information to be displayed may be conveyed from circuitry 68 to display control circuitry such as display driver integrated circuit 62 using a signal path such as a signal path formed from conductive metal traces in flexible printed circuit 64 (as an example).

[0060] Display driver integrated circuit 62 may be mounted on thin-film-transistor layer driver ledge 82 or elsewhere in device 10. During operation of display 14, display driver circuitry 62 and/or other display control circuitry such as gate driver circuitry formed on substrate 58 or coupled to substrate 58 may be used in controlling the array of display pixels in layers 46 (e.g., using a grid of vertical data lines and horizontal gate lines).

[0061] A flexible printed circuit cable such as flexible printed circuit 64 may be used in routing signals between printed circuit 66 and thin-film-transistor layer 58. If desired, display driver integrated circuit 62 may be mounted on printed circuit 66 or flexible printed circuit 64. Printed circuit 66 may be formed from a rigid printed circuit board (e.g., a layer of fiberglass-filled epoxy) or a flexible printed circuit (e.g., a flexible sheet of polyimide or other flexible polymer layer).

[0062] Backlight structures 42 may include a light guide plate such as light guide plate 78. Light guide plate 78 may be formed from a transparent material such as clear glass or plastic. During operation of backlight structures 42, a light source such as light source 72 may generate light 74. Light source 72 may be, for example, an array of light-emitting diodes.

[0063] Light 74 from light source 72 may be coupled into edge surface 76 of light guide plate 78 and may be distributed in dimensions X and Y throughout light guide plate 78 due to the principal of total internal reflection. Light guide plate 78 may include light-scattering features such as pits or bumps. The light-scattering features may be located on an upper surface and/or on an opposing lower surface of light guide plate 78.

[0064] Light 74 that scatters upwards in direction Z from light guide plate 78 may serve as backlight 44 for display 14. Light 74 that scatters downwards may be reflected back in the upwards direction by reflector 80. Reflector 80 may be formed from a reflective material such as a layer of white plastic or other shiny materials.

[0065] To enhance backlight performance for backlight structures 42, backlight structures 42 may include optical films 70. Optical films 70 may include diffuser layers for helping to homogenize backlight 44 and thereby reduce hotspots, compensation films for enhancing off-axis viewing, and brightness enhancement films (also sometimes referred to as turning films) for collimating backlight 44. Optical films 70 may overlap the other structures in backlight unit 42 such as light guide plate 78 and reflector 80. For example, if light guide plate 78 has a rectangular footprint in the X-Y plane of FIG. 5, optical films 70 and reflector 80 may have a matching rectangular footprint. Display layers 46 and the other display structures of FIG. 5 typically have rectangular shapes with four peripheral edges, but display configurations with other shapes may be used in forming display 14 if desired.

[0066] As shown in FIG. 6, display structures 46 of display 14 may include a plurality of display pixels 86. Display pixels 86 may be organized in rows and columns. Display control circuitry may be used in controlling the operation of display pixels 86 using signal lines such as data lines 88 and gate lines 90. In liquid crystal displays, display pixels 86 may each contain an electrode for applying an electric field to an associated portion of liquid crystal layer 52 (FIG. 5) and a thin-film (amorphous silicon or polysilicon) transistor for controlling the magnitude of the signal applied to the electrode and therefore the magnitude of the electric field. In other types of displays, display pixels 86 may be formed from other types of structures (e.g., organic light-emitting diodes, etc.).

[0067] Lines 90 may be coupled to the gates of the thin-film transistors and may sometimes be referred to as gate lines. Lines 88 may be coupled to the sources of the thin-film transistors and may sometimes be referred to as source lines or data lines. Gate driver circuitry (e.g., thin-film transistor gate driver circuitry) may be coupled to gate lines 90. Display driver circuitry that produces data signals for lines 88 (e.g., a display driver integrated circuit) may be coupled to data lines 88.

[0068] Gate driver circuitry, one or more display driver integrated circuits, traces for distributing gate and data signals and other display control signals, and other display control circuitry may be formed in inactive region 461 of display 14 and display structures 46. As an example, a display driver integrated circuit may be mounted along the upper segment of inactive region 461, whereas gate driver thin-film circuitry may be formed along the left and right segments of inactive region 461. During operation of display 14, display pixels 86 may display images for a user, so the portion of display structures 46 containing display pixels 86



may sometimes be referred to as active display structures or the active area of display **14**. The metal traces and other display control circuit structures in inactive region **461** do not display any images, so this portion of structures **46** may sometimes be referred to as inactive display structures.

[0069] Inactive region **461** may form a border that surrounds some or all of active area **46A**. For example, inactive region **461** may have a rectangular ring shape of the type shown in FIG. **6** having opposing upper and lower border segments and left and right border segments. To provide display **14** with a borderless appearance, display **14** may be provided with optical structures such as glass layers with curved or angled surfaces. The optical structures may be configured to bend and therefore guide light that is emitted from the array of display pixels **86** in active area **46A** into a portion of display **14** that overlaps inactive area **461**. By using optical structures to bend light from active area **46A**, content may be displayed in portions of display **14** that overlap inactive regions **461**, providing display **14** with a borderless or near borderless appearance.

[0070] The optical structures that are used to enhance the apparent size of display **14** may be formed from transparent materials such as clear glass or plastic structures. As an example, the optical structures may be formed from sheets of clear glass or plastic material or from glass, plastic, or other transparent material of other shapes. Optical structures with curved surfaces for bending light may be formed using molding equipment, slumping equipment, machining equipment, or other tools for shaping clear material.

[0071] FIG. **7** is a diagram showing how a mold may be used to form optical structures with curved surfaces for bending light in display **14**. As shown in FIG. **7**, molding equipment **92** may include mold structures such as upper mold structures **94** and lower mold structures **98**. Structures such as mold structures **94** and **98** may be heated. Optical material **102** (e.g., glass, plastic, ceramic, etc.) may be molded between the opposing surfaces of mold structures **94** and **98** (e.g., when upper mold structure **94** is moved in direction **96** and/or when lower mold structures **98** is moved in direction **100**). If desired, molding operations may also involve injection molding techniques. By molding material **102** with molding equipment **92**, optical structures **104** that have curved or angle surfaces may be formed.

[0072] As shown in the illustrative configuration of FIG. **8**, a slumping process may be used in forming optical structures with curved surfaces for bending light in display **14**. Slumping equipment **106** may include a heated metal structure or other equipment with exposed curved surfaces such as curved surface **110**. Optical material **108** (e.g., glass, plastic, ceramic, etc.) may be placed on top of surface **110** while slumping equipment **106** is heated. When equipment **106** reaches a sufficiently high temperature, optical material **108** will slump under its own weight, thereby creating optical structures with curved surfaces such as optical structures **112**. Following cooling, structures **112** may be removed from slumping equipment **106**. As shown on the right-hand side of FIG. **8**, the resulting shape for optical structures **112** may have curved surfaces such as curved upper surface **114** and curved lower surface **116**.

[0073] FIG. **9** is a diagram showing how a machining process may be used to form display structures such as glass structures with curved surfaces. As shown in FIG. **9**, optical material **130** may be processed using machining equipment **118**. Machining equipment **118** may have a machining head

such as head **124** (e.g., a drill bit, milling cutter, or other machining tool). Actuator **120** may use shaft **122** to rotate head **124** in direction **126** about rotational axis **128**. Actuator **120** may include a motor for rotating shaft **122** and computer-controlled positioners for adjusting the location of shaft **122** and head **124** relative to optical material **130**. Following machining of the edges or other portions of optical structures **130**, optical structures **130** may have curved surfaces such as curved surfaces **132**, as shown on the right-hand side of FIG. **9**.

[0074] By providing optical structures in display **14** with curved edges or other curved or angled surfaces, the optical structures may bend light that is emitted from display pixels **86** in a way that allows the light to extend laterally outward over the otherwise inactive portions of the display. As a result, it will appear to a user of the display as if the display is borderless or nearly borderless.

[0075] An illustrative display of the type that may use curved optical structures to achieve a borderless or near borderless appearance to a viewer is shown in FIG. **10**. As shown in the cross-sectional side view of display **14** in FIG. **10**, display **14** may include active area display layers such as active display structures **46A**. Inactive display structures such as inactive display structures **461** of FIG. **6** are not shown. Active area display structures **46A** may contain a rectangular array of display pixels such as display pixels **86** with a rectangular peripheral edge. Light rays **44** associated with display pixels may be produced by a backlight unit (e.g., a backlight unit in a display such as a backlit liquid crystal display), may be produced by light reflected off of a reflector such as reflector **80** of FIG. **5**, or may be emitted by light-emitting diode structures or other light sources within display pixels **86**.

[0076] Optical structures **134** (e.g., optical structures of the type formed using the equipment of FIGS. **7**, **8**, and **9** or other equipment) may be formed from transparent optical members. For example, a display may be provided with an optical structure such as a transparent member formed from glass, plastic, ceramic, or other clear material. An optical member such as optical member **134** of FIG. **10** may have planar surfaces such as upper surface **136** (in the example of FIG. **10**) and may have curved surfaces such as curved surfaces **138**. Curved surfaces may be located on the upper and/or lower side of optical member **134**. As shown in FIG. **10**, for example, curved surfaces **138** may be located in peripheral edge portions of optical member **134** (e.g., the left and right edges of member **134** and, if desired, the upper and lower edges of member **134**, as viewed from above in direction **50** by viewer **48**).

[0077] Curved surfaces **138** may allow optical structures such as member **134** to serve as light bending structures to bend light **44** from active display structures **46A** so that the entire lateral expanse of display **14** appears to be filled with active image content. Display **14** may, for example, appear to have no left and right borders (when viewed in direction **50**) and/or may additionally have no upper and lower borders (when viewed in direction **50**). The lateral dimensions (in X and Y) for active display structures **46A** are less than the respective lateral dimensions X and Y of optical member **134**, so the apparent image size for display **14** is enlarged. By enlarging the apparent size of the display, the display may be made to appear borderless or nearly borderless, even if active display structures **46A** are surrounded by a border of inactive structures such as structures **46B**.



[0078] Rays of light from active display structures 46A such as light ray 44M are produced by display pixels 86 that are near to the center of display 14. In this portion of display 14, light may travel vertically upwards to viewer 48 without significant bending. Near to the peripheral edges of active display structures 46A, light rays such as light rays 44E are emitted that are bent by the curved nature of the edges of optical structures 134 (i.e., curved surfaces 138).

[0079] As shown by the bent trajectory of light rays 44E, light rays 44E that are emitted by display pixels 86 along the edges of active display structures 46A may, upon passing through optical structures 134, appear to viewer 48 as if they were emitted by display pixels located in inactive border region IA. The lateral extent (e.g., width W in FIG. 10) of display 14 over which light rays 44 are emitted and therefore the effective size of display 14 for displaying content to viewer 48 is enhanced by the presence of curved portions 138 of optical member 134, so it appears as if display 14 has an active area of lateral dimension W, rather than the more limited size of active area AA that is associated with the physical size of the array of display pixels 86 in structures 46A. In this way, surface 136 can be entirely covered with active display pixel content (e.g., graphics, text, video, etc.), providing display 14 with a borderless or nearly borderless appearance, despite the presence of display control circuitry and other inactive structures in inactive region 461 of display structures 46 (FIG. 6).

[0080] In the illustrative example of FIG. 10, optical structures 134 have curved surfaces 138 that are located on the lower side of structures 134 near the peripheral edge of structures 134. Structures 134 may have a rectangular shape when viewed in direction 50 (i.e., structures 134 may be formed from a rectangular sheet of optical material or other planar member with curved edge surfaces). One or more, two or more, three or more, or four of the edges of rectangular optical structures 134 may be provided with curved surfaces such as surfaces 138.

[0081] If desired, both the upper and lower sides of optical structures 134 may be provided with curved surfaces such as curved surfaces 138, as shown in FIG. 11. Curved surfaces 138 may cover some or all of the upper and lower surfaces of structures 134. In the example of FIG. 11, curved surfaces 138 are formed in peripheral portions of optical structures 134, but not in the central portions of structures 134. The center portions of the upper and lower surface of optical structures 134 may be planar.

[0082] FIG. 12 shows how the upper surface of optical structures 134 may be provided with a curved (convex) shape using upper curved surface 138. The lower surface of optical structures 134 in this type of configuration may be planar (as an example).

[0083] In the configuration of FIG. 13, display 14 has been provide with optical structures 134 that have an upper surface with a planar central region and curved peripheral edge portions 138. The lower surface of optical structures 134 may be planar.

[0084] Optical structures 134 may be mounted against active display structures 46A or may be mounted so that an air gap or a gap filled with materials other than air is formed between optical structures 134 and active display structures 46A. FIG. 14 is a cross-sectional side view of display 14 in a configuration in which optical structures 134 have been mounted so that there is an air gap G between optical structures 134 and display structures 46A. In FIG. 14, the

center of the upper surface of optical structures 134 is planar. FIG. 15 is a cross-sectional side view of display 14 in a configuration in which optical structures 134 with a curved upper surface (surface 138) have been separated from display structures 46A by an air gap of size G.

[0085] Optical structures 134 (e.g., glass, plastic, or ceramic optical members of the types described in connection FIGS. 10-15) may be mounted on the exterior of device 10 or in the interior of device 10. When mounted as the outermost structural display layer in device 10, optical structures 134 may sometimes be referred to as a display cover layer or display cover layer structures. When mounted in the interior of device 10, optical structures 134 may be covered by one or more additional layers of transparent material such as a display cover layer and/or other layers of clear material.

[0086] FIG. 16 is a cross-sectional side view of display 14 in an illustrative configuration in which optical structures 134 have been covered by additional optical structures such as display cover layer 140. Display cover layer 140 may be a layer of transparent material such as a clear layer of plastic, glass or ceramic (as examples). Light bending optical structures 134 of FIG. 16 have been formed from glass, plastic, or other clear material with a shape that exhibits a triangular cross-section (i.e. a shape with sloped surfaces 138). Sloped surfaces 138 may form planar or non-planar curved surfaces for bending light. Air gap G may separate the lower surface of display cover layer 140 and the upper surface of display structures 46A. Optical structures 134 of FIG. 16 may run along the right and left edges of display 14 (e.g., make display 14 appear borderless along its right and left edges), may run around the entire periphery of display 14 (e.g., structures 134 may have a rectangular ring shape with a central opening that makes display 14 appear borderless along all four of its edges), or may be configured to cover other portions of the edges of display 14.

[0087] As shown in FIG. 17, optical structures 134 may be provided with optical coating layers such as layers 142. Layers 142 may be formed from dielectrics such as sputtered oxides, from clear materials deposited using physical vapor deposition, chemical vapor deposition, or other deposition techniques (e.g., coatings of glass, polymer, ceramic, or other materials), or may be formed from other transparent coating layers on optical structures 134. There may be one or more layers 142, two or more layers 142, three or more layers 142, or four or more layers 142. Layers 142 may include layers such as antireflection layers, antismudge layers, antiscratch layers, or other layers to modify the properties of the upper and/or lower surface of optical structures 134.

[0088] It may be desirable to use optically clear support structures such as layers of cured clear adhesive (transparent solidified liquid polymer) to support optical structures 134. As shown in FIG. 18, for example, device 10 may have a clear polymer layer such as polymer structure 144 for supporting optical structures 134. Components 146 may be mounted within housing 12. Display structures 46 may be mounted on support structures such as portions of housing 12 or other structures. To provide display 14 with a borderless or nearly borderless appearance, optical structures 134 may have curved surfaces such as curved surfaces 138. Polymer material 144 may be formed from a cured optical adhesive (e.g., optically clear adhesive). Initially, when in an uncured liquid state, polymer 144 may be placed on top of



display structures **46** (e.g., by dripping, screen printing, spraying, etc.) Optical structures **134** may then be placed on top of the liquid polymer. Ultraviolet light curing or thermal curing techniques may then be used to cure the polymer material to form solid polymer support structures such as structures **144** of FIG. **18**.

[0089] Structures **144** of FIG. **18** may support optical structures **134** and may hold structures **134** at a desired distance from display structures **46** such as active display structures **46A** and may help attach optical structures **134** to device **10**. Polymer material **144** may, if desired, have a relatively low index of refraction compared to the index of refraction of optical structures **134**. For example, optical structures **134** may be formed from a material such as glass with an index of refraction of 1.4 or above (e.g., 1.4 to 1.8), whereas polymer material **144** may have an index of refraction of less than 1.4, less than 1.3, less than 1.2, or less than 1.1 (e.g., 1.0 to 1.2). In this way, polymer material **144** may behave optically as an air gap, allowing light **44** to be bent effectively by curved surfaces **138** of optical structures **134**.

[0090] FIG. **19** is a cross-sectional side view of device **10** in a configuration in which curved surfaces **138** of optical structures **134** have been formed on the lower surface of optical structures **134**, adjacent to solidified liquid polymer material **144**.

[0091] In the illustrative configuration of FIG. **20**, optical structures **134** have been covered with a layer of transparent material such as display cover layer **140**. Display cover layer **140** may be a planar sheet of glass, plastic, or ceramic. Optical structures **134** may have a planar upper surface such as upper surface **136**. Angled edge surfaces **138** may lie in planes that are not coplanar with upper surface **136** to allow the edges of optical structures **134** to bend light from display structures **46**. Air gaps such as gap **G** may separate optical structures such as optical structures **134** of FIG. **20** or other optical structures **134** from display cover layer **140** and/or polymer such as polymer **144** may be interposed between display cover layer **140** and optical structures **134** and/or between optical structures **134** and display structures **46**.

[0092] If desired, device **10** may be provided with touch sensor functionality. A touch sensor for device **10** may be implemented using an array of capacitive touch sensor electrodes (e.g., transparent conductive electrodes such as indium tin oxide electrodes), may use resistive touch technology, light-based touch sensors, acoustic touch sensor technology, or other touch sensor technology. As an example, a capacitive touch sensor for device **10** may be implemented using a one-sided or two-sided array of indium tin oxide electrodes. The electrodes may be formed on a touch sensor substrate such as a layer of glass or plastic that is separate from other layers in display **14** (e.g., a touch sensor substrate that is mounted within display **14** using adhesive) or may be formed on the surface of optical structures **134**, display cover layer **140**, or other structures in display **14**.

[0093] FIG. **21** is a cross-sectional side view of display **14** in a configuration in which touch sensor **146** has been formed on the lower surface of optical structures **134**. An air gap or polymer gap may separate touch sensor **146** from display structures **46A**. Touch sensor **146** may include capacitive touch sensor structures such as a one-layer or two-layer array of indium tin oxide electrodes. The indium tin oxide electrodes may be formed directly on the lower surface of optical structures **134** or may be formed on a

substrate (e.g., a sheet of glass or polymer) that is attached to the underside of optical structures **134** by adhesive (as examples). An air gap or a gap filled with polymer **144** may separate display structures **46A** from touch sensor **146**.

[0094] In the illustrative configuration of FIG. **22**, touch sensor **146** has been formed on the surface of display structures **46A** (e.g., by attaching a touch panel with a thin glass or polymer substrate to display structures **46A** with adhesive).

[0095] FIG. **23** is a cross-sectional side view of display **14** in a configuration in which touch sensor **146** has been formed on the upper surface of optical structures **134**. Touch sensor **146** may have portions that are bent to conform to the shape of curved surfaces **138** of optical structures **134**.

[0096] FIG. **24** is a cross-sectional side view of display **14** in a configuration in which touch sensor **146** has been formed on the upper surface of optical structures **134** and in which device **10** has a display cover layer such as cover layer **14**. Cover layer **140** may be separated by an air gap or a gap filled with polymer **144** from touch sensor **146** and optical structures **134**.

[0097] FIG. **25** is a cross-sectional side view of display **14** in a configuration in which touch sensor **146** has been formed on the underside of display cover layer **140** (either as layers deposited directly on display cover layer **140** or as a touch panel that is attached to display cover layer **140** with adhesive). An air gap or a gap filled with polymer **144** may separate touch sensor **146** of FIG. **25** from optical structures **134**.

The foregoing is merely illustrative of the principles of this invention and various modifications can be made by those skilled in the art without departing from the scope and spirit of the invention.

What is claimed is:

1. An electronic device comprising:
  - a housing having sidewalls;
  - a display layer comprising an array of pixels that form an active area and comprising an inactive border region that surrounds the active area; and
  - a transparent optical member that forms an outermost surface of the electronic device, wherein the transparent optical member has an inner surface with convex portions and an opposing outer surface, and wherein the convex portions overlap the sidewalls of the housing and the display layer.
2. The electronic device defined in claim 1 wherein the convex portions of the transparent optical member are configured to guide light emitted by the display layer to a portion of the outer surface of the transparent optical member that overlaps the inactive border region of the display layer.
3. The electronic device defined in claim 1 wherein the housing has a rear surface and sidewalls that extend from the rear surface in a given direction.
4. The electronic device defined in claim 3 wherein the convex portion of the transparent optical member overlap the sidewalls of the housing and the display layer in the given direction.
5. The electronic device defined in claim 1 wherein the active area of the display layer has a first width and wherein the convex portions of the transparent optical member are configured to redirect images produced by the display layer to have a second width that is greater than the first width.



6. The electronic device defined in claim 5 wherein a portion of the second width extends over at least a portion of the sidewalls of the housing.

7. The electronic device defined in claim 1 wherein the array of pixels comprises an array of organic light-emitting diode pixels.

8. The electronic device defined in claim 1 further comprising:

a transparent layer interposed between the active area and the transparent optical member, wherein the inactive border region of the display layer, at least one of the sidewalls of the housing, one of the convex portions of the transparent optical member, and the transparent layer all overlap.

9. The electronic device defined in claim 8 wherein the transparent layer is a layer of optically clear adhesive that adheres the organic light-emitting diode display layer to the inner surface of the transparent display cover layer.

10. The electronic device defined in claim 9 wherein the optically clear adhesive extends from a first one of the sidewalls to a second one of the sidewalls.

11. The electronic device defined in claim 8 wherein the transparent optical member has a first index of refraction, and wherein the transparent layer has a second index of refraction that is less than the first index of refraction.

12. The electronic device defined in claim 1 wherein the array of pixels has a first width and a first height, the convex portions redirect the image to have an apparent second width that is greater than the first width, and the convex portions redirect the image to have an apparent second height that is greater than the first height.

13. The electronic device defined in claim 12 wherein the apparent second height and the apparent second width extend at least partially over the sidewalls.

14. The electronic device defined in claim 1 wherein the opposing outer surface comprises a planar surface that the sidewalls and the display cover layer.

15. The electronic device defined in claim 1 wherein the opposing outer surface comprises a convex surface that the sidewalls and the display cover layer.

16. The electronic device defined in claim 1 further comprising:

a touch sensor in the housing, wherein the touch sensor is interposed between the transparent optical member and the display layer.

17. The electronic device defined in claim 16 wherein the touch sensor is coupled to the inner surface of the transparent optical member.

18. The electronic device defined in claim 16 wherein the touch sensor is separated from the transparent optical member by a gap.

19. An electronic device comprising:

a housing;

a display layer in the housing having an array of pixels configured to produce an image, wherein the array of pixels has a first width; and

a transparent optical member that overlaps the display layer, wherein the transparent optical member has a surface that faces the display layer with convex portions that redirect the image to have an apparent second width that is greater than the first width.

20. An electronic device comprising:

a housing having sidewalls;

a display layer comprising an array of pixels that form an active area and comprising an inactive border region that surrounds the active area; and

a transparent optical member comprising an inner surface with convex portions and an opposing outer surface, wherein the convex portions overlap the sidewalls of the housing and the display layer.

\* \* \* \* \*