

US 20230227305A1

(19) **United States**
(12) **Patent Application Publication**
Painter et al.

(10) **Pub. No.: US 2023/0227305 A1**
(43) **Pub. Date: Jul. 20, 2023**

(54) **TECHNIQUES FOR TRANSDUCTION AND STORAGE OF QUANTUM LEVEL SIGNALS**

(71) Applicant: **California Institute of Technology**,
Pasadena, CA (US)

(72) Inventors: **Oskar Painter**, Sierra Madre, CA (US);
Jie Luo, Pasadena, CA (US); **Michael T. Fang**, Pasadena, CA (US); **Alp Sipahigil**, Pasadena, CA (US); **Paul B. Dieterle**, Somerville, MA (US); **Mahmoud Kalae**, Pasadena, CA (US); **Johannes M. Fink**, Klosterneuburg (AT); **Andrew J. Keller**, Los Angeles, CA (US); **Gregory MacCabe**, Los Angeles, CA (US); **Hengjiang Ren**, Pasadena, CA (US); **Justin D. Cohen**, Ammandale, VA (US)

(73) Assignee: **California Institute of Technology**,
Pasadena, CA (US)

(21) Appl. No.: **18/187,419**

(22) Filed: **Mar. 21, 2023**

Related U.S. Application Data

(60) Continuation of application No. 17/087,316, filed on Nov. 2, 2020, now Pat. No. 11,649,160, which is a division of application No. 16/293,455, filed on Mar. 5, 2019, now Pat. No. 10,858,239.

(60) Provisional application No. 62/638,817, filed on Mar.


5, 2018, provisional application No. 62/638,829, filed on Mar. 5, 2018, provisional application No. 62/652,194, filed on Apr. 3, 2018, provisional application No. 62/652,197, filed on Apr. 3, 2018, provisional application No. 62/652,200, filed on Apr. 3, 2018.

Publication Classification

(51) **Int. Cl.**
G06N 10/40 (2006.01)
(52) **U.S. Cl.**
CPC **G06N 10/40** (2022.01)

(57) **ABSTRACT**

Embodiments described herein include systems and techniques for converting (i.e., transducing) a quantum-level (e.g., single photon) signal between the three wave forms (i.e., optical, acoustic, and microwave). A suspended crystalline structure is used at the nanometer scale to accomplish the desired behavior of the system as described in detail herein. Transducers that use a common acoustic intermediary transform optical signals to acoustic signals and vice versa as well as microwave signals to acoustic signals and vice versa. Other embodiments described herein include systems and techniques for storing a qubit in phonon memory having an extended coherence time. A suspended crystalline structure with specific geometric design is used at the nanometer scale to accomplish the desired behavior of the system.






FIG. 1




FIG. 2A




FIG. 2B




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D




FIG. 4E




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 10




FIG. 11A





FIG. 11B






FIG. 12




FIG. 13

TECHNIQUES FOR TRANSDUCTION AND STORAGE OF QUANTUM LEVEL SIGNALS

CROSS-REFERENCES TO RELATED APPLICATIONS

[0001] This application is a continuation under 35 U.S.C. §120 of U.S. Utility Pat. Application No. 17/087,316, filed on Nov. 2, 2020, by Oskar Painter, Jie Luo, Michael T. Fang, Alp Sipahigil, Paul. B. Dieterle, Mahmood Kalae, Johannes M. Fink, Amdrew Keller, Gregory MacCabe, Hengjiang Ren, and Justin D. Cohen, entitled “TECHNIQUES FOR TRANSDUCTION AND STORAGE OF QUANTUM LEVEL SIGNALS,” which application is a division of U.S. Non-Provisional Pat. Application No. 16/293,455, filed on Mar. 5, 2019, entitled “Techniques for Transduction and Storage of Quantum Level Signals,” which claims priority to U.S. Provisional Pat. Application No. 62/638,817, filed on Mar. 5, 2018, entitled “Integrated Acoustic and Superconducting Quantum Circuits,” U.S. Provisional Pat. Application No. 62/638,829, filed on Mar. 5, 2018, entitled “Silicon-on-insulator-based Platform for Low-loss Superconducting Microwave Circuits,” U.S. Provisional Pat. Application No. 62/652,194, filed on Apr. 3, 2018, entitled “Ultra-Coherent Thin-Film Microwave Acoustic Bandgap Quantum Phonon Memory,” U.S. Provisional Pat. Application No. 62/652,197, filed on Apr. 3, 2018, entitled “Parametric RF-Mems for Advanced Microwave Signal Processing,” and to U.S. Provisional Pat. Application No. 62/652,200, filed on Apr. 3, 2018, entitled “Electro-Opto-Mechanical Crystals: Parametric Metasurfaces for Classical Signal Processing and Thermal Management,” the disclosures of which are hereby incorporated by reference in their entirety for all purposes.

[0002] The following regular U.S. patent applications were filed concurrently with U.S. Non-Provisional Pat. Application No. 16/293,455, and the entire disclosure of the applications are incorporated by reference into this application for all purposes:

[0003] Application No. 16/293,455, filed Mar. 5, 2019, entitled “TECHNIQUES FOR TRANSDUCTION AND STORAGE OF QUANTUM LEVEL SIGNALS”;

[0004] Application No. 16/293,457, filed Mar. 5, 2019, entitled “TECHNIQUES FOR BIDIRECTIONAL TRANSDUCTION OF QUANTUM LEVEL SIGNALS BETWEEN OPTICAL AND MICROWAVE FREQUENCIES USING A COMMON ACOUSTIC INTERMEDIARY”; and

[0005] Application No. 16/293,416, filed Mar. 5, 2019, entitled “METAMATERIAL WAVEGUIDES AND SHIELDED BRIDGES FOR QUANTUM CIRCUITS”.

STATEMENT AS TO RIGHTS TO INVENTIONS MADE UNDER FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

[0006] This invention was made with government support under Grant No. PHY1125565 awarded by the National Science Foundation and Grant No(s). FA9550-16-1-0323 & FA9550-15-1-0015 awarded by the Air Force and Grant No. N00014-15-1-2761 awarded by the Office of Naval Research. The government has certain rights in the invention.

BACKGROUND

[0007] Quantum computing employs quantum bits called qubits to represent data and is of interest for modeling quantum systems and implementing quantum algorithms including performing complex and/or difficult computing tasks that may be beyond the capability of classical computers. Example computations in which a quantum computer may find application include simulation of quantum systems themselves, modeling of the chemical or biological properties of complex molecules, searching through large data sets, finding approximately optimal solutions to problems with many degrees of freedom, factoring large numbers, or distributing quantum information within a network. Quantum systems can include, for example, particles, atoms, molecules, and materials; dynamics such as chemical reactions may also be modeled. Quantum algorithms can include, for example, Grover’s algorithm to search efficiently through a large dataset. To perform quantum computations, the quantum state of one qubit (or an ensemble of qubits) must be able to modify the quantum state of another qubit or set of qubits. In a canonical quantum computing architecture, this interaction between qubits is mediated via a quantum bus, which is a loose analog to a traditional computing bus in which information is transferred between different parts of a computer.

[0008] Superconducting qubits based on Josephson junctions conventionally operate and communicate at microwave frequencies (e.g., 2-10 GHz) using extremely small quantities of energy and each qubit requires specialized coherent excitation and readout structures that also operate at similar frequencies. As the number of qubits in a quantum processor is increased, these characteristics result in complex interconnect and routing schemes that limit scalability of the quantum processor.

[0009] Despite the progress made related to the formation of quantum processors, there is a need in the art for improved methods and systems for converting quantum-level signals between optical, microwave, and acoustic forms. There is also a need in the art for improved methods and system for storing qubit quantum states in a memory.

SUMMARY

[0010] The described systems and techniques relate to the field of quantum mechanics for particular use in quantum computing. More specifically, systems and techniques are described for converting (i.e., transducing) a quantum-level (e.g., a single photon) signal between an optical signal and a microwave signal using a common acoustic bandgap resonator. Systems and techniques are also described for converting a quantum-level (e.g. a single photon) signal between a microwave-frequency electrical signal (i.e., a photon) and an acoustic signal (i.e., a phonon) for storing in a phonon memory.

[0011] A system can be configured to perform particular operations or actions by virtue of having software, firmware, hardware, or a combination of them installed on or incorporated in the system that in operation causes or cause the system to perform the actions. One general aspect includes a system for transducing and storing a qubit signal. The system may include a suspended crystalline transducer for converting the qubit signal between an electrical (e.g., microwave) form and an acoustic form when the suspended

crystalline transducer oscillates at a tuning frequency. The system may also include a suspended crystalline structure coupled to the suspended crystalline transducer, the suspended crystalline structure including acoustic cavities chained together, where the acoustic cavities are of differing sizes to store the qubit signal in acoustic form when the suspended crystalline transducer oscillates at the tuning frequency. Other embodiments of this aspect include corresponding computer systems, apparatus, and computer programs recorded on one or more computer storage devices, each configured to perform the actions of the methods.

[0012] Implementations may include one or more of the following features. The system may further include suspended crystalline structures, disposed in a geometric design to isolate the acoustic signal, surrounding the suspended crystalline transducer and the suspended crystalline structure. In some embodiments the suspended crystalline transducer includes a piezoelectric material overlay of a second suspended crystalline structure. The piezoelectric material may be, for example, Aluminum Nitride (AlN). In some embodiments, the system may include conductors that are electrically coupled to the piezoelectric material overlay of the second suspended crystalline structure, where the conductors form an interleaved pattern and provide alternating polarity electrical signals to the piezoelectric material to generate an oscillation at the tuning frequency.

[0013] In some embodiments, the suspended crystalline transducer includes a second suspended crystalline structure and conductors overlaying the second suspended crystalline structure. In some embodiments, the conductors are configured to form capacitive features. During transduction, the capacitive features may oscillate at the tuning frequency to generate a changing capacitance. The qubit signal in acoustic form may be generated based on the changing capacitance.

[0014] In some embodiments, the suspended crystalline transducer and the suspended crystalline structure each include silicon (Si). In some embodiments, the suspended crystalline transducer and the suspended crystalline structure are disposed in a single crystal silicon layer of a Silicon-on-insulator substrate. In some embodiments, the conductor is aluminum. In some embodiments, the qubit signal is swapped between the suspended crystalline transducer and the suspended crystalline structure when the suspended crystalline transducer oscillates at the tuning frequency. Implementations of the described techniques may include hardware, a method or process, or computer instructions usable by the system.

[0015] These and other embodiments of the invention along with many of its advantages and features are described in more detail in conjunction with the text below and attached figures.

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] FIG. 1 is a simplified block diagram of a quantum computing system according to an embodiment.

[0017] FIGS. 2A and 2B are example diagrams of opto-mechanical transducers according to an embodiment.

[0018] FIG. 3 is an example of a quantum level acoustic waveguide according to an embodiment.

[0019] FIGS. 4A - 4D are example diagrams of components of a capacitive electro-mechanical transducer according to an embodiment.

[0020] FIG. 4E illustrates a graph of the tone spectrum around the high-frequency LC resonance of the LC circuit of FIG. 4A.

[0021] FIG. 5 is an example diagram of a system including a capacitive electro-mechanical transducer according to an embodiment.

[0022] FIG. 6 is an example diagram of a piezoelectric electro-mechanical transducer according to an embodiment.

[0023] FIG. 7 is an example diagram of a transducing system for converting a microwave signal to an optical signal via a common acoustic signal according to an embodiment.

[0024] FIG. 8 is an example process for transducing a microwave signal to an optical signal via a common acoustic signal according to an embodiment.

[0025] FIG. 9 is an example of a phonon memory structure according to an embodiment.

[0026] FIG. 10 is an example of a system for transferring a qubit to a phonon memory according to an embodiment.

[0027] FIG. 11A is an example depiction of stages of transferring a qubit to a phonon memory according to an embodiment.

[0028] FIG. 11B is an energy level diagram of the virtual coupling scheme for connecting a superconducting qubit to a phonon memory according to an embodiment.

[0029] FIG. 11C is an example view of a layout of a phonon memory and a piezoelectric transducer according to an embodiment.

[0030] FIG. 12 is an example process for storing a qubit in a phonon memory according to an embodiment.

[0031] FIG. 13 is an example depiction of a process for creating a suspended crystalline structure according to an embodiment.

[0032] Unless otherwise indicated, elements using the same indicator number are the same elements between differing figures. For example, phonon memory 115 in FIG. 1 is the same phonon memory 115 depicted in FIG. 10. Some elements may include multiple of the same elements, which are indicated by a letter following the indicator number.

DETAILED DESCRIPTION

[0033] The non-linearity and size of quantum level bits (i.e., qubits) gives rise to specific problems for storage and conversion of the signals between the three wave types (i.e., optical, acoustic, and electrical). Qubits in the acoustic or electrical form are of such small amplitudes (e.g., single photon level) that the qubit may be lost in the thermal noise associated with standard room temperatures (e.g., sixty degrees Fahrenheit). For this reason, the systems that manipulate qubits in electrical or acoustic form typically operate at very cold temperatures (e.g., tens of millikelvin). However, optical waves do not suffer from the effects of thermal noise at room temperature, and optical waves travel much faster (i.e., the speed of light) than acoustic waves.

[0034] Embodiments described herein include the systems and techniques for converting (i.e., transducing) a quantum-level (e.g., single photon) signal between the three wave forms (i.e., optical, acoustic, and microwave). A suspended crystalline structure is used at the nanometer scale to accomplish the desired behavior of the system as described in detail herein. Transducers that use a common acoustic intermediary transform optical signals to acoustic signals and vice versa as well as microwave signals to acoustic signals and vice versa.

[0035] Embodiments described herein include systems and techniques for storing a qubit in phonon memory having an extended coherence time. A suspended crystalline structure with specific geometric design is used at the nanometer scale to accomplish the desired behavior of the system as described in detail herein.

[0036] Prior to discussing embodiments of the invention, it may be helpful to discuss some terms.

[0037] A “qubit” is the basic unit of information in a quantum computer. A specific form of qubit can be realized using superconducting microwave circuits employing a Josephson junction which acts as a highly non-linear inductor element. The superconducting qubits typically operate at microwave frequencies between approximately 2 - 10 GHz. That is, their quantum state is represented as a special mixture (called a superposition) of energy states in which the difference in energy corresponds to a frequency in the 2 - 10 GHz range. The energy difference of these qubit states is extremely small, correspondingly to the energy of a microwave-frequency ‘photon’, roughly 5 to 50 micro-electron Volts. As such, each qubit requires special excitation and read-out methods (also operated at microwave frequencies), and must be protected against tiny amounts of electrical noise in the environment. Further, the superconducting qubits can be converted to an acoustic qubit (e.g., single-phonon) or optical qubit (e.g., single-photon), each of which forms has useful properties. For example, an optical qubit may not get “lost” in thermal noise of a room temperature environment like an acoustic or superconducting qubit may. An acoustic qubit is transmitted at much slower rates, which allows for much smaller components for filters and the like. As the number of qubits in a quantum processor is increased, these characteristics result in complex interconnect and routing schemes that limit scalability of the quantum processor.

[0038] The three types of waves or signals discussed herein are microwave signals, acoustic signals, and optical signals. Each of these signals are discussed at the quantum-level (e.g., single photons or single phonons). Therefore, microwaves discussed herein generally include microwaves, optical signals discussed herein are generally not visible to the human eye, and acoustic signals as discussed herein are generally not audible to the human ear. Rather, for example, acoustic signals are mechanical vibrations.

[0039] The term “quantum-level” refers to the level at which quantum mechanical effects become important. For example, most of the devices and components described herein are very small (e.g., the nanometer scale) and have very low energy (e.g., single photon).

[0040] The term “suspended crystalline structure” refers to a type of structure that may be used in creating components described herein. The crystalline structure can be, for example, Silicon, and can be suspended through a process such as that depicted and described with respect to FIG. 13.

The Opto-Electro-Acoustic Conversion of a Qubit

[0041] FIG. 1 is a simplified block diagram of a quantum computing system 100 for performing the techniques discussed herein. Quantum computing system 100 includes quantum computers 105 and 110 as well as optical network 165.

[0042] Optical network 165 may be any suitable optical network. Optical network 165 may be, for example, a single

optical fiber cable connecting quantum computers 105 and 110. In some embodiments, optical network 165 may be a complex optical network connecting any number of quantum computers of which quantum computers 105 and 110 are two exemplary quantum computers.

[0043] Quantum computers 105 and 110 include phonon memories 115 and 160, electro-acoustic transducers 120a, 120b, 155a, and 155b, acoustic waveguides 125 and 150, opto-acoustic transducers 130 and 145, and optical transceivers 135 and 140. While each of quantum computers 105 and 110 comprise similar components, each may comprise more or fewer components than depicted herein. For example additional or fewer waveguides, including optical waveguides, acoustic waveguides, and electrical conductors may be included in quantum computers 105 and 110. The specific components included in quantum computers 105 and 110 are shown to provide a simplified view for ease of description.

[0044] Phonon memories 115 and 160 may be one or more acoustic cavities capable of storing a qubit for some period of time. The phonon memories 115 and 160 discussed herein are ultra-coherent phonon memories. Coherence of phonon memories 115 and 160 may be, for example, up to one (1) second. Phonon memories 115 and 160 use specific geometries to accomplish the ultra-coherency as described in more detail with respect to FIGS. 9, 10, 11A, 11B, and 11C.

[0045] Electro-acoustic transducers 120a, 120b, 155a, and 155b may be one or more transducers capable of converting a microwave to an electro-mechanical (e.g., acoustic) wave (and vice versa) at the quantum-level scale. For example, a qubit may be in the acoustic wave form and electro-acoustic transducers 120 and 155 may convert the qubit to a microwave form that may be transmitted on a conductor. Electro-acoustic transducers may be suspended crystalline structures configured with specific geometries as described in more detail with respect to FIGS. 4A - 4D, 5, and 6.

[0046] Acoustic waveguides 125 and 150 may be any quantum level acoustic waveguide capable of propagating a qubit in acoustic format. Acoustic waveguides 125 and 150 may be suspended crystalline structures with specific geometries as described with respect to FIG. 3.

[0047] Opto-acoustic transducers 130 and 145 may be one or more transducers capable of converting an optical wave to a mechanical (e.g., acoustic) wave (and vice versa) at the quantum-level scale. For example, a qubit may be in the acoustic wave form and opto-acoustic transducers 130 and 145 may convert the qubit to an optical form that may be transmitted via an optical waveguide or over an optical network. Because optical waves, even at the quantum scale, are not substantially impacted by thermal noise, qubits in optical wave form may be manipulated at room temperature. Qubits in acoustic or microwave form are each impacted by thermal noise such that at room temperature the qubit may be lost in the noise. Therefore, qubits in microwave or acoustic form are typically manipulated at very low temperatures (e.g., tens of millikelvin). Opto-acoustic transducers 130 and 150 may be suspended crystalline structures configured with specific geometries as described in more detail with respect to FIGS. 2A and 2B.

[0048] Optical transceivers 135 and 140 may be any suitable optical device that may send or receive an optical signal at the quantum level. For example, optical transceivers may send and receive optical qubits.

[0049] In use, quantum computing system **100** may manipulate one or more qubits to perform quantum computing. As a simplified example for explaining the components herein, a qubit in acoustic form may be stored in phonon memory **115** of quantum computer **105**. The electro-acoustic transducer **120a** may extract the qubit from the phonon memory **115** as described with respect to FIG. 11A. The qubit, now in microwave form, may propagate via a conductor, for example, to electro-acoustic transducer **120b**. The qubit, now in acoustic form, may propagate via acoustic waveguide **125** to opto-acoustic transducer **130**. Opto-acoustic transducer **130** may convert the qubit to optical form, and the qubit may propagate, for example, to optical transceiver **135** via an optical waveguide. As mentioned previously, the quantum computer **105** is typically operated at, for example, tens of millikelvin to ensure thermal noise does not impact the qubit.

[0050] The optical transceiver **135**, which may be at room temperature in some embodiments, may transmit the optical qubit to optical transceiver **140** of quantum computer **110**. The optical qubit may propagate, for example, via an optical waveguide to opto-acoustic transducer **145**. The opto-acoustic transducer **145** may convert the qubit into acoustic form. The acoustic qubit may propagate via acoustic waveguide **150** to electro-acoustic transducer **155b**, which may convert the qubit to a microwave form. The qubit may propagate via a conductor to electro-acoustic transducer **155a**, which may store the qubit in phonon memory **160**.

[0051] In some embodiments, quantum processors may further process the qubit within quantum computers **105** and **110**. This and many other features of quantum computers **105** and **110** are not shown herein for simplicity.

Transduction Between an Optical Signal and an Acoustic Signal

[0052] FIG. 2A depicts an opto-mechanical (e.g., opto-acoustic) transducer **200**. The opto-acoustic transducer **200** may be opto-acoustic transducer **130** or **145** of FIG. 1. The opto-acoustic transducer **200** is a patterned Silicon nanobeam opto-mechanical crystal. The opto-acoustic transducer **200** represents a new paradigm in metamaterials, incorporating nonlinear parametric interactions to provide inter-conversion between optical wave types and acoustic wave types. Wave fields of one wave type property provides dynamic control of wave fields of another type. Stated differently, by adjusting, for example, the optical frequency of a transducer, the optical qubit can convert to an acoustic qubit.

[0053] Parametric coupling in optomechanics is possible due to the inherent nonlinearity of radiation pressure (the coupling between light and mechanical motion is dependent upon the optical intensity, not the optical field). Confining optical and acoustic energy to the nanoscale results in a nonlinearity that can be many orders of magnitude larger than conventional optical nonlinearities and presents unique capabilities for optical signal control. Opto-acoustic transducer **200** relies on the natural hierarchy of higher frequency optical photons and lower frequency microwave phonons, which have matching spatial wavelength due to the large difference in the speed of light and the speed of sound. This hierarchy, along with the radiation pressure nonlinearity, allows one to use two-photon transitions to couple optical signals to microwave phonon signal. Opto-acoustic

transducer **200** is an engineered photonic and phononic bandgap structure which can be “printed” into the thin-film surface layer of a microchip.

[0054] Opto-acoustic transducer **200** may be a suspended crystalline structure. Opto-acoustic transducer **200** may be made from, for example, Silicon. As an example, a Silicon-on-insulator (SOI) substrate including single crystal silicon layer can be processed to form opto-acoustic transducer **200** having elements in the single crystal silicon layer. For example, the process used as described with respect to FIG. 13 may be used to fabricate opto-acoustic transducer **200**. The nanobeam design of opto-acoustic transducer **200** allows for conversion of an optical signal to an acoustic signal. The opto-acoustic transducer **200** includes multiple vacancies (i.e., holes) **202**, **204**, **206**, **208**, **210**, **212**, **214**, **216**, and **218** where the silicon is etched away to leave the vacancy. The vacancies are of differing sizes to “trap” the signal within the area and convert it between optical and acoustic wave forms. For example, vacancy **210** is the smallest, vacancies **208** and **212** are slightly larger than vacancy **210**, vacancies **206** and **214** are slightly larger still than vacancies **208** and **212**, and vacancies **204** and **216** are slightly larger still. Vacancies **218** and **202** are the largest. The differing vacancy sizes create a mirroring effect such that the signal becomes trapped near the smallest vacancy **210** and the opto-acoustic transducer **200** converts the signal between optical and acoustic forms. The conversion is possible because the displacement field of the acoustic resonance (e.g., 3.5 GHz) is coupled to the co-localized optical resonance.

[0055] The opto-acoustic transducer **200** is a nanometer scale device as shown by the scale **220**. Such small scale photonic crystals (i.e., the opto-acoustic transducer **200**) creates a means to localize light to such a degree that radiation pressure coupling to elastic waves of the dielectric photonic structure is strongly manifest. The physics of mechanical-light interactions in materials, although well understood in the bulk, are quite often much more subtle when more complex geometries are involved, such as the patterned opto-acoustic transducer **200**.

[0056] The radiation pressure nonlinearity utilized in the opto-acoustic transducer **200** described above is wavelength agnostic. The capacitive forces utilized in micro-electro-mechanical systems (MEMS) and nano-electro-mechanical systems (NEMS) devices are derived from a low frequency version of the optical radiation pressure effect. The opto-acoustic transducer **200** may be created using a silicon-on-insulator (SOI) material platform which has excellent microwave, acoustic, and optical properties. Nanoscale vacuum-gap capacitors with vacuum gaps of less than twenty (20) can be fabricated, which are sufficient to create high impedance microwave resonant circuits capable of strong coupling to RF (e.g., 100 MHz) acoustic resonances.

[0057] FIG. 2B illustrates a system **250** that includes a thin-film silicon two-dimensional (2D) optomechanical cavity **255**. The optomechanical cavity **255** can be a suspended crystalline structure as described herein. Suspended crystalline structures may be created using a process as described with respect to FIG. 13. The system **250** as shown includes nanoscale structures “printed” on a microchip. The optomechanical cavity **255** has an opto-acoustic transducer **200** running along the length of each side of the optomechanical cavity **255**. Accordingly, a microwave signal converted to an optical signal by one of the opto-acoustic transducers

200 can propagate through the optomechanical cavity **255**, which is an optical waveguide. The optomechanical cavity **255** may be a suspended crystalline optical waveguide manufactured using a process as described with respect to FIG. 13. The acoustic shield **270** around the opto-acoustic transducers **200** includes multiple star-shaped vacancies **260**. The acoustic shield **270** may be a suspended crystalline structure (e.g., implemented in the single crystal silicon layer of an SOI substrate and mechanically isolated from the underlying portions of the handle substrate) from which the star-shaped vacancies **260** may be etched. The acoustic shield **270** provides mirroring to isolate the acoustic signal within the optomechanical cavity **255** and the opto-acoustic transducers **200**. While star-shaped vacancies **260** are depicted, any shape vacancies may be used that generate a geometric pattern that provides mirroring to isolate the acoustic signal.

[0058] FIG. 3 illustrates a quantum level acoustic waveguide system **300**. The system **300** includes an acoustic bandgap waveguide **305**, acoustic shield **315** surrounding the acoustic bandgap waveguide **305**, cross-shaped vacancies **310**. The cross-shaped vacancies **310** create the geometric pattern of acoustic shield **315**. The acoustic shield **315** may be a suspended crystalline structure from which cross-shaped vacancies **310** are etched. In the middle of acoustic shield **315** is the acoustic bandgap waveguide **305**. The acoustic bandgap waveguide **305** may also be a suspended crystalline structure. Acoustic waves may propagate through acoustic bandgap waveguide **305**. The acoustic shield **315** may provide mirroring and dampening to isolate the acoustic bandgap waveguide **305** to isolate the acoustic signal and keep noise from entering the acoustic bandgap waveguide **305**. The acoustic bandgap waveguide **305** may be, for example, acoustic waveguide **125** and **150** of FIG. 1. The acoustic bandgap waveguide **305** may be coupled to, for example, an opto-acoustic transducer **200** for propagating acoustic signals to and from the opto-acoustic transducer **200**.

Transduction Between a Microwave Signal and an Acoustic Signal

[0059] FIG. 4A illustrates an example capacitive electro-acoustic transducer **400**. Capacitive electro-acoustic transducer **400** may include electro-acoustic transducer **120** or **155** of FIG. 1. Capacitive electro-acoustic transducer **400** may include elements that are suspended crystalline structures. In some embodiments, capacitive electro-acoustic transducer **400** may be formed using superconducting aluminum wiring (the electrodes **405** and **430**) on a patterned sub-micrometer-thick silicon membrane. Capacitive electro-acoustic transducer **400** may include capacitive structure **417**, and inductor-capacitor (LC) circuit **427**. The capacitive structure **417** may include electrodes **405** and **430**, multiple unit cells **410**, and central nanobeam phononic crystal cavity **415**. The LC circuit **427** may include capacitor **420** and inductor **425**. The central nanobeam phononic crystal cavity **415** may include a silicon-on-insulator substrate that is a suspended crystalline structure created using steps described with respect to FIG. 13. The suspended crystalline structure may support electrode **405**. The electrodes **405** and **430** form a top capacitor running along the top of the nanobeam phononic crystal cavity **415** and a bottom capacitor running along the bottom of the nanobeam phononic crystal cavity **415**. The top capacitor and bottom capacitor are capacitive

features of the capacitive electro-acoustic transducer **400**. The top capacitor and the bottom capacitor each have a nanoscale vacuum gap.

[0060] In the embodiment illustrated in FIG. 4A, electrode **405** formed on the top of the central nanobeam phononic crystal cavity **415** and is U-shaped with a width slightly wider than the width of ladder structure of the unit cells **410**. Although only illustrated at the right side of the central nanobeam phononic crystal cavity **415** in FIG. 4A, electrode **430** is formed on the top surface of central nanobeam phononic crystal cavity **415** and lies in the same plane as electrode **405** as illustrated in FIG. 4B. Thus, referring to both FIGS. 4A and 4B, U-shaped electrode **405** is positioned with the opening of the U-shape on the right side of FIG. 4A such that electrode **430**, which is also U-shaped, with the opening of the U-shape on the left side of FIG. 4A, is positioned between the two arms of electrode **405**. Central nanobeam phononic crystal cavity **415**, which supports electrode **405**, and the ladder structure formed by the unit cells **410**, which support electrode **430**, can be fabricated as suspended structures as described herein.

[0061] A unit cell **410** of the capacitive structure **417** is depicted in more detail in FIG. 4B. In FIG. 4A, the oscillation of each unit cell **410** caused by the acoustic (mechanical) vibrations during transduction is exaggeratedly illustrated. The ladder structure of the unit cells **410** (formed by joining multiple unit cells **410** in a row) support the electrode **430**. The oscillation of the unit cells **410** are stimulated by applying a microwave signal or an acoustic signal for transduction. The signal induces an oscillation of the unit cells **410**. This oscillation creates a change (i.e., variation) in capacitance of the top and bottom capacitors and modulates the resonance frequency of the LC circuit (inductor **425** and capacitor **420**). The change (i.e., variation) in distance between the electrodes **430** and **405** due to the oscillations generate the change in capacitance. In a parametric process, the application of a microwave tone that is detuned by the mechanical frequency converts the acoustic signal to a microwave signal and vice versa. Stated differently, the mechanical phonon causes an increase in the frequency of the microwave circuit by one mechanical frequency, which allows for the conversion of low frequency photons (one mechanical frequency below the microwave frequency) to photons at the microwave frequency. Similarly, a photon one mechanical frequency above the microwave frequency can be converted to a microwave frequency photon plus a mechanical frequency phonon.

[0062] A tuning frequency is set by the size and number of unit cells used in the central nanobeam phononic crystal cavity **415**. The unit cells **410** form a ladder shape, and the size of each unit cell must be small enough to generate the high frequencies needed for quantum scale signals. Therefore, dimensions (a_n , w_n , w_y , w_x) of the unit cell **410** are determined based on the desired tuning frequency for the capacitive electro-acoustic transducer **400**. The number of unit cells is selected to generate a capacitance large enough for the bottom and top capacitive features to couple the acoustic and microwave frequency elements. The tuning frequency is the microwave transition frequency of the qubit, also called a qubit frequency.

[0063] The oscillation is formed from an acoustic band near the Γ -point at wavevector $k_x = 0$. For a lattice constant of $a_n = 1.55 \mu\text{m}$, numerical finite-element method (FEM) simulations place the Γ -point frequency of the oscillation

mode band at $\omega_m/2\pi = 0.425$ GHz. A minimum motional mass (m_{eff}) is desired to increase the zeropoint amplitude $x_{zpf} = (\hbar/2m_{eff}\omega_m)^{1/2}$. In the case of the central nanobeam phononic crystal cavity **415**, this corresponds to minimizing both the thickness of the crystalline layer (e.g., silicon) and conductive layer (electrodes **405** and **430**, which may be aluminum) and the width of the beam features. Also, a large mechanical capacitance (C_m) is desired, owing to limits on the achievable stray capacitance **420**. The use of a Γ -point acoustic mode makes the electromechanical coupling from each unit cell **410** additive, and thus increasing the number of unit cells **410** in the central nanobeam phononic crystal cavity **415** results in an increased mechanical capacitance and participation ratio, $\eta = C_m/(C_m + C_s)$. Capacitor **420** is dominated by the stray capacitance of the planar spiral coil inductor **425** forming the LC resonator.

[0064] FIG. 4C illustrates a unit cell **435** of the acoustic shield **437**. Acoustic shield **437** provides additional acoustic isolation from the surrounding crystalline membrane and substrate, the central nanobeam phononic crystal cavity **415** and vacuum-gap capacitor may be embedded in the middle of a cross-pattern acoustic shield **437** as shown in system **440** of FIG. 4D. The acoustic shield **437** may be a suspended crystalline structure fabricated using the processes described herein. Each unit cell **435** of the acoustic shield **437** includes a large square plate region with four narrow connecting tethers. The dimensions (h_m , a_m , w_m) of the unit cell **435** of the acoustic shield **437** are selected to minimize the leakage of the mechanical (acoustic) vibrations from the capacitive electro-acoustic transducer **400**. The FEM-simulated acoustic band structure of an optimized acoustic shield **437** possesses a bandgap of, for example, 0.1 GHz around the central nanobeam phononic crystal cavity **415** during oscillation at the frequency of, for example, 0.425 GHz. The energy density of the central nanobeam phononic crystal cavity **415** during oscillation is well confined, dropping by, for example, 100 dB within the first two periods of the shield. In the embodiment illustrated in FIG. 4D, acoustic shield **437**, as well as central nanobeam phononic crystal cavity **415** are fabricated in the single crystal silicon layer of the SOI substrate, with electrodes deposited on the single crystal silicon layer. Because the underlying BOX layer is removed under the acoustic shield **437** and the nanobeam **415**, these elements are able to mechanically resonate at frequencies capable of supporting the quantum level microwaves and acoustic waves.

[0065] FIG. 4D illustrates a plot **450** of the measured probe tone spectrum around the high frequency LC resonance for a drive detuning at two-photon resonance.

[0066] FIG. 5 illustrates a double-cavity device **500** fabricated on, for example, a silicon-on-insulator silicon membrane. The two spiral coils **505**, may be shunted via the vacuum-gap capacitor of two independent nanobeam phononic crystal cavities **415** which may be embedded inside acoustic shields **437**. Inductive coupling between the two coils **505** may be set by the gap d . External coupling of the two coils **505** to a microwave drive line may be performed by shorting the end of a coplanar waveguide and splitting the current in the center trace into two paths (shunting wire **510**). The offset δ from the center of the coils **505** where the wire path **510** splits in two results in asymmetric coupling to the two coils **505**, allowing for an adjustable amount of coupling between the even and odd supermodes of the coupled LC resonators. Parameters for this device **500**

are, for example, $d = 12$ μm and $\delta = 16.5$ μm , resulting in a simulated coil coupling of $2J/2\pi = 415$ MHz and external coupling rates of $\kappa_e/2\pi = 9.6$ MHz ($\kappa_e/2\pi = 102$ kHz) for the odd (even) mode. The bare (decoupled) frequency of the LC resonators may be designed to be, for example, $\omega_{r,0}/2\pi = 10.86$ GHz for a capacitor vacuum gap of $s = 70$ nm.

[0067] FIG. 6 illustrates a top view of a piezoelectric electro-acoustic transducer **600**. The piezoelectric electro-acoustic transducer **600** may be formed using a crystalline on insulator (e.g., silicon-on-insulator) substrate. Piezoelectric electro-acoustic transducer **600** includes conductors **605**, a portion of acoustic cavity **610**, and transducer core **615**. The acoustic cavity **610** forms a phonon memory and is described in more detail with respect to FIG. 9.

[0068] Conductors **605** include a conductive material overlaying a suspended crystalline structure. The conductive material may be aluminum. Each of the conductors **605a**, **b**, **c**, **d**, **e**, and **f** are individual chains of crystalline cavities overlaid by the conductive material. The patterned crystalline structure is configured to block the acoustic signal that emits from the transducer core **615** (i.e., piezoelectric resonator) at its acoustic resonance frequency. The physical design of conductors **605** is implemented in compliance with bandgap engineering techniques to provide the desired mechanical isolation at the acoustic resonance frequency. The conductors **605a**, **b**, **c**, **d**, and **e** each overlay the transducer core **615**, such that they alternate directions. The polarity of the voltages on each of the conductors **605a**, **b**, and **c** are the same and the polarity of the voltages on each of the conductors **605d** and **e** are the same and the opposite of the polarity of conductors **605a**, **b**, and **c**. While five conductors are shown, more or fewer conductors may be used. At transducer core **615**, in an exemplary embodiment, the suspended crystalline structure (e.g., single crystal silicon) supports transducer core **615**, which, in turn, supports electrically isolated conductors **605** that are operable to apply a spatially varying electric field to the transducer core **615**. An alternating polarity on the conductors **605** (e.g., conductors **605a**, **b**, and **c** may provide a positive voltage and conductors **605d** and **e** may provide a negative voltage) can create a wave effect in the transducer core **615**, which, as a result of the piezoelectric properties of the transducer core **615**, excites a mechanical oscillation in the transducer core **615**. In some embodiments, the silicon chains **606** that do not provide voltage to the transducer core **615** may be removed during the manufacturing process.

[0069] The acoustic cavity **610** may be a suspended crystalline structure, and is depicted in more detail in FIG. 9. The acoustic cavity **610** may form a phonon memory. Transducer core **615** may be piezoelectric material overlaying a suspended crystalline structure. The piezoelectric material may be, for example, Aluminum Nitride deposited on the single crystal silicon layer of the SOI substrate.

[0070] In use, providing, for example, a positive voltage on conductors **605a**, **b**, and **c** and a negative voltage on conductors **605e** and **f**, can excite the mechanical oscillation because of the piezoelectric properties of the transducer core **615**. The mechanical oscillation is the acoustic form of the microwave signal.

[0071] FIG. 7 illustrates an electro-opto-mechanical system **700** for transducing an optical signal to a microwave signal and vice versa using a common acoustic intermediary. The system **700** incorporates nonlinear parametric interac-

tions to provide inter-conversion between all three wave types, enabling dynamic control of one wave type property with wave fields of another. System 700 includes piezoelectric electro-acoustic transducer 600 and opto-acoustic transducer 200. In some embodiments, an acoustic waveguide may be, for example, coupled between the piezoelectric electro-acoustic transducer 600 and opto-acoustic transducer 200. In some embodiments, capacitive electro-acoustic transducer 400 may be used instead of piezoelectric electro-acoustic transducer 600.

[0072] In use, opto-acoustic transducer 200 may convert an optical qubit into an acoustic qubit. The opto-acoustic transducer 200 will oscillate at a frequency associated with the acoustic signal. When the piezoelectric electro-acoustic transducer 600 is tuned to oscillate at a matching acoustic frequency, piezoelectric electro-acoustic transducer 600 can convert the acoustic qubit to superconducting qubit for transmitting on a conductor. The process also works to convert a qubit in microwave form to an acoustic form and then into an optical form.

[0073] FIG. 8 illustrates a method 800 for transducing a qubit between optical signal form and microwave signal form using a common acoustic signal form intermediary. The method 800 can be performed using, for example, quantum computing system 100 or electro-opto-mechanical system 700.

[0074] Method 800 begins at block 805 with a suspended crystalline optical waveguide receiving a single photon optical signal from an optical device. The optical waveguide may be, for example, optomechanical cavity 255. The optical device may be any suitable optical device for transceiving a single-photon optical signal.

[0075] At block 810 a first suspended crystalline transducer converts the single photon optical signal to an acoustic signal. The first suspended crystalline transducer may be, for example, opto-acoustic transducer 200. The opto-acoustic transducer oscillates at a tuning frequency to convert the single photon optical signal to a single-phonon acoustic signal. A photon pump may be used to excite the opto-acoustic transducer to oscillate at the tuning frequency.

[0076] At block 815 a second suspended crystalline transducer is tuned to oscillate at the tuning frequency. The second suspended crystalline transducer may be, for example, capacitive electro-acoustic transducer 400 or piezoelectric electro-acoustic transducer 600. The second suspended crystalline transducer may be excited by a microwave signal to oscillate at the tuning frequency. When excited to oscillate at the tuning frequency, the second suspended crystalline transducer may obtain or convert the single-phonon acoustic signal from the first suspended crystalline transducer to a single-photon microwave signal. In other words, in response to the tuning, the second suspended crystalline transducer may convert the single-phonon acoustic signal to a microwave signal at block 820.

[0077] At block 825, the second suspended crystalline transducer may transmit the microwave signal on a conductor.

Storing a Qubit in a Phonon Memory Structure

[0078] FIG. 9 is an example of a phonon memory structure 610 (also referred to as acoustic structure 610). The phonon memory structure may be, for example, phonon memory 115. The phonon memory structure 610 may be a suspended

crystalline structure. The phonon memory structure 610 may include, for example, silicon, such as the single crystal silicon layer of the SOI substrate in a suspended geometry after removal of the underlying buried oxide layer. The phonon memory structure 610 is a periodic crystalline structure made up of acoustic elements 905, 910, 915, 920, and 925 that form an acoustic cavity 610 (also called phonon memory 610). The acoustic elements 905, 910, 915, 920, and 925 are of differing sizes and are chained together. The differing size crystalline acoustic elements 905, 910, 915, 920, and 925 form a mirroring structure such that the single phonon acoustic signal may be trapped, in some embodiments, in the smallest crystalline acoustic element 910. The acoustic signal is transferred from, for example, a piezoelectric electro-acoustic transducer when the piezoelectric resonator of the electro-acoustic transducer oscillates at a tuned frequency as described in more detail herein. The chain of acoustic elements 905, 910, 915, 920, and 925 forming the acoustic cavity 610 as depicted in FIG. 9 are surrounded by a vacancy. The vacancy may be created when any crystalline structure in the vacancy areas is etched away, resulting in spatial isolation of the chain of acoustic elements 905, 910, 915, 920, and 925 in part also because of removal of the BOX that originally supported the single crystal silicon layer (i.e., isolation in the direction normal to the figure) as well as the removal of portions of the single crystal silicon layer above and below the chain of acoustic cavities as illustrated in FIG. 9 (i.e., isolation in the plane of the figure).

[0079] FIG. 10 is a perspective diagram illustrating an example of a system 1000 including an electro-acoustic transducer and an acoustic shield in which the system is configured to transfer a qubit to a phonon memory according to an embodiment. The system 1000 includes phonon memory structure 610, piezoelectric electro-acoustic transducer 600, conductor 1005, and acoustic shield 437. In use, a microwave signal may arrive on conductor 1005. As described with respect to FIG. 6, the individual chains of crystalline elements overlaid by the conductor 1005 may carry opposite charge voltage from differing directions to generate a wave-like response in the piezoelectric material of the transducer core. A superconducting qubit in microwave form may arrive on the conductor at the transducer core. The transducer core may be a piezoelectric resonator. The electric charge from the conductor may excite the mechanical oscillations of the piezoelectric resonator. When the piezoelectric resonator is tuned to the tuning frequency, the electro-acoustic transducer 600 may convert the superconducting qubit (i.e., single-photon qubit) to an acoustic qubit (i.e., single-phonon qubit). At the tuned frequency, the acoustic qubit transfers into the phonon memory structure 610. In some embodiments, at the tuned frequency, the acoustic qubit swaps between the electro-acoustic transducer 600 and the phonon memory structure 610. The storage may last, for example, up to one (1) second. One second represents ultra-long coherence for storage of an acoustic qubit in a phonon memory.

[0080] Gigahertz frequency acoustical waves have micron scale wavelengths, five orders of magnitude smaller than electrical waves of the same frequency. As such, storage, readout, and bus cavities in a circuit quantum acoustodynamics (CQAD) architecture can be much more compact than the equivalent in circuit quantum electrodynamics (CQED). Information stored in the acoustical domain is much more effectively isolated because, unlike electrical

signals, elastic waves don't propagate in vacuum. Coupling can only occur within the two-dimensional surface of the chip. Furthermore, the chip can be patterned with a micron-scale periodic structure (i.e., as utilized in the phonon memory) that creates a bandgap in the acoustical spectrum around the frequency of interest. Finally, the size of superconducting qubit circuits is comparable to or larger than acoustical wavelengths; thus, qubits don't couple to all parts of the acoustic spectrum through structureless dipole coupling, but only to specific wave vectors, chosen at the time of fabrication. As such, neighboring qubits can be effectively decoupled while remote qubits can be strongly coupled through virtual phonon exchange.

[0081] Phononic crystals and thin film piezoelectrics in the described architecture have the advantage of mitigating many of the issues associated with current piezo-acoustic technologies, such as Surface Acoustic Wave (SAW), Bulk Acoustic Wave (BAW), and thin-Film Bulk Acoustic Resonator (fBAR) devices. Geometric patterning of a thin surface layer film, such as the silicon device layer of silicon-on-insulator, are used to guide, trap, and diffract microwave acoustic waves with exquisite control, negligible loss, and utilizing small chip real estate. Coupling between the acoustic waves in the acoustic circuitry to electrical elements in the superconducting microwave circuits is realized using the spatially-selective employment of an additional ultra-thin layer of piezoelectric, such as Aluminum Nitride in the transducer core. The spatially-selective use of an ultra-thin layer of piezoelectric material reduces acoustic and electrical losses and noise while allowing for significant coupling between the two wave fields.

[0082] Acoustic energy damping lifetimes greater than one second ($Q = 5 \times 10^{10}$) are possible in, for example, a 5 GHz frequency silicon oscillator. Mechanical (acoustic) resonators can far exceed, by more than 3-orders of magnitude, the performance of chip-scale microwave components for quantum information storage. This performance boost is made possible due to a forbidden frequency gap (bandgap) that arises for acoustic waves of all polarizations in geometrically patterned thin films (thin-film phononic crystals). The shielding of phononic crystals protects localized phonons from tunneling (clamping loss) and Rayleigh scattering from impurities and defects. The high level of control over the dispersion of the propagation channels also enables dense packing of phononic circuits in various connection topologies while limiting cross-talk in large scale systems.

[0083] FIG. 11A is an example depiction of the stages of a system 1100 of transferring a qubit into a phonon memory. J_A is the bare vacuum coupling rate between the superconducting qubit 1125 (ω_{01} transition frequency) and a high impedance LC resonator 1130 (ω_r) which is detuned by $\Delta = \omega_{01} - \omega_r$. J_B is the resonant vacuum coupling rate of the high impedance resonator 1130 and a nearly resonant ($\delta = \omega_r - (\omega_{pa})$) piezo-acoustic cavity 1135 (ω_{pa}). J_C is the vacuum acoustic coupling rate between piezo-acoustic cavity 1135 and the phonon memory 115 (ω_m) which is detuned from the bare piezo-acoustic cavity 1135 by $\Delta' = \omega_m - \omega_{pa}$.

[0084] In the virtual coupling scenario of FIG. 11C, the phonon memory 115 may be designed to be highly detuned from the bare piezo-acoustic cavity 1135 and the superconducting qubit 1125 during the idle state of the phonon memory 115. In order to transfer the quantum state between superconducting qubit 1125 and phonon memory 115, the superconducting qubit 1125 is flux tuned into resonance

with the phonon memory 115 such that $\Delta \approx \Delta'$. In the limit that $\Delta \gg J_{A,B,C}$, the effective coupling rate between superconducting qubit 1125 and phonon memory 115 is given by $J_{eff} \approx ((J_A J_C) / \Delta^2) J_B$. The excitation of the "mediating" LC and piezo-acoustic resonators 1132 is virtual, and so the fractional amount of superconducting qubit 1125 or phonon memory 115 energy that is stored in the mediating resonator 1132 during the transfer process is suppressed. The phonon memory 115 is returned to an idle state by flux tuning the superconducting qubit 1125 out of resonance with the phonon memory 115. Thus, storage of the superconducting qubit 1125 in the phonon memory 115 as well as retrieval of the superconducting qubit 1125 from the phonon memory 115 are provided by embodiments of the present invention.

[0085] FIG. 11B depicts the energy level diagram of the virtual coupling scheme, as described with respect to FIG. 11A, for connecting a superconducting qubit to a hypersonic phonon memory.

[0086] FIG. 11C is a simplified schematic diagram of a system 1150 including a piezoacoustic transducer 1110 and phonon memory 115 for storing a qubit in a phonon memory.

[0087] As shown in FIG. 11C, both of the piezoacoustic transducer 1110 and phonon memory 115 are embedded in a "cross-structure" phononic bandgap crystal (i.e., acoustic shield) with, for example, bandgap $\omega_{BG}/2\pi = 4.6\text{-}5.3$ GHz. A piezo-acoustic coupling between the piezo-acoustic cavity and a LC coil resonator is, for example, $J_B/2\pi = 120$ MHz. Both the piezo-acoustic cavity and the LC coil only have a single mode, thus avoiding parasitic coupling to other unintended modes. The vacuum coupling between the piezo-acoustic resonator and the phonon memory cavity can be controlled by adjusting the number of lattice periods between the cavities. A coupling of, for example, $J_A/2\pi = 20$ MHz between the qubit and coil resonator.

[0088] Detuning can be chosen by considering the desired level of isolation from the mediating resonator. Assuming a superconducting (e.g., transmon) qubit $T_1 \approx 100$ μ s and a LC coil resonator Q-factor of $Q_e \approx 5 \times 10^5$ (which are typical single-photon numbers on silicon on Insulator), $(J_A/\Delta) < \sim 10^{-1}$ may ensure no added dephasing of the qubit by the coil resonator. Similarly, for a $T_1 \approx 100$ ms for the uncoupled phonon memory and an acoustic Q-factor of $Q_a \approx 10^5$ for the piezo-acoustic cavity, $(J_C/\Delta') < \sim 10^{-2}$. A suitable detuning in this case, for example, is $\Delta/2\pi \approx 200$ MHz. The corresponding virtual coupling rate is then $J_{eff} \approx 200$ kHz, corresponding to a qubit-to-memory transfer time of $T_t < \sim 1$ μ s, far faster than the assumed qubit or memory decoherence time.

[0089] The physical implementation shown in FIG. 10 can be compared to the schematic diagram illustrated in FIG. 11C. Accordingly, transducer core 615 and phonon memory 610 illustrated in FIG. 10 are analogous to piezo-acoustic transducer 1110 and phonon memory 115 illustrated in FIG. 11C. Moreover, in addition to the piezo-acoustic transducer 1110, the central nanobeam phononic crystal cavity shown in FIG. 4A can be utilized as the electro-acoustic transducer through the use of capacitance rather than through the piezo-electric effect and integrated into the system illustrated in FIG. 11C as well as the system illustrated in FIG. 10.

[0090] Although only three electrodes 1115, 1117, and 1119 are illustrated in FIG. 11C, it will be apparent to one of skill in the art that these three electrodes 1115, 1117, and

1119 correspond to conductors **605b**, **c**, and **d**, respectively, in FIG. **6** and voltages **+V** and **-V** correspond to the voltages applied to conductors **1005** and **1007**, respectively, in FIG. **10**.

[0091] Referring to FIG. **10**, conductor **1005** and conductor **1007** support electrical signals that are transmitted to electro-acoustic transducer (e.g., piezo-electro transducer **600**). The conductors **1005** are overlaid (not shown) on the acoustic shield **437** and chains **1010** such that every other chain **1010** contains an overlay of conductor **1005**. Similarly, conductor **1007** is overlaid (not shown) on acoustic shield **437** and chains **1012** such that every other chain **1012** contains an overlay of conductor **1007**. For example, the first, third, and fifth chain **1010** may have conductor **1005** overlay that couples to the piezoelectric material in piezo-electro transducer **600**, and the second and fourth chain **1012** may have conductor **1007** overlay that couples to the piezoelectric material in piezo-electro transducer **600**. Conductor **1005** and conductor **1007** can be formed using an aluminum metallization deposited on the underlying silicon layer of the SOI substrate. Adhesion and insulating layers may be utilized in some embodiments. Conductors **1005** and **1007** are overlain upon a silicon structure and are electrically connected to a plurality of conductors **605** described more fully in relation to FIG. **6**. Thus, conductor **1005** provides an electrical connection (of a first polarity oscillating at microwave frequencies) to a subset (e.g., odd numbered) conductors **605** (e.g., conductors **605a**, **b**, and **c**) and conductor **1007** provides an electrical connection (of a second polarity oscillating at microwave frequencies) to a second subset (e.g., even numbered) conductors **605** (e.g., conductors **605d** and **e**). Although FIG. **10** illustrates metallization that electrically connects all of the conductors on the top left portion of the figure to conductor **1005**, it will be appreciated that electrical opens can be implemented to prevent the conductors **606a**, **b**, **c**, **d**, and **e** from carrying current to the transducer core. Similarly, electrical opens can be introduced to prevent the conductors opposing conductors **605a**, **b**, and **c** (i.e., conductors **606c**, **d**, and **e**) from carrying current to the transducer core.

[0092] As illustrated in FIG. **10**, a phononic bandgap structure (i.e., acoustic shield) **437** is implemented as a two-dimensional array of silicon elements that have been mechanically isolated from the underlying handle substrate and the overlying BOX layer.

[0093] In one implementation, in order to fabricate the structure illustrated in FIG. **10**, Aluminum Nitride or other suitable piezoelectric material is deposited on the single crystal silicon layer of an SOI substrate. The structure is patterned and the Aluminum Nitride is removed in locations other than the piezoelectric transducer. The single crystal silicon layer is then patterned to define the two-dimensional shapes (i.e., in the plane of the figure) of the acoustic shield **437**, conductors **1005** and **1007**, and phonon memory **610**. A release process is then utilized to remove the BOX layer under acoustic shield **437**, conductors **1005** and **1007**, and phonon memory **610**, resulting in the suspension of the crystalline structures.

[0094] FIG. **12** is an example process **1200** for storing a qubit in a phonon memory. The process **1200** may be performed by, for example, system **1000** or system **1100**. The process **1200** begins at block **1205** with a suspended crystalline transducer (e.g., electro-mechanical transducer **600**) receiving the qubit signal in microwave form. As described

with respect to FIG. **10**, the qubit signal may arrive at the piezoelectric resonator from the conductor and voltages applied to the piezoelectric resonator at alternating polarities may excite the mechanical properties of the piezoelectric material causing it to oscillate and thereby converting the qubit to acoustic form at block **1210**. When the oscillation of the piezoelectric resonator is tuned to an acoustic band-gap frequency (tuning frequency) associated with the phonon memory, the qubit is transmitted and stored in the phonon memory at block **1215**.

Suspended Crystalline Structure Formation

[0095] FIG. **13** is an example depiction of a process **1300** for creating a suspended crystalline structure. The process **1300** is to create a piezoelectric resonator portion of a microchip. Silicon-on-insulator (SOI) substrates comprise a class of silicon-based substrates in which a silicon “device layer” covers a buried silicon oxide (BOX) layer, which is on top of a silicon handle wafer. High-resistivity bulk silicon may be used successfully for superconducting qubits. The fabrication process **1300** uses high-resistivity SOI for superconducting qubits, which enables qubits to be suspended on a mechanically compliant silicon membrane (the device layer), enabling electromechanical coupling and other important functionalities. While the specific process **1300** for creating a piezoelectric resonator is depicted, portions of the process, including the anhydrous HF vapor release to remove the underlying SiO₂ layer, forming a suspended crystalline structure, can be used to create any of the structures discussed herein on a microchip, including, for example, suspended crystalline structures that form acoustic shields, phonon memory, conductors, electro-acoustic transducers, opto-acoustic transducers, waveguides, and so forth.

[0096] The process begins with an initial structure **1305** including a bottom silicon handle having a layer of silicon oxide, over which another layer of silicon is grown, and the top layer is Aluminum Nitride. This is a silicon on insulator substrate.

[0097] A dry etch is performed to etch away the unwanted portions of Aluminum Nitride, which is shown at structure **1310**. A silicon oxide layer is grown over top of the structure, which is shown at structure **1315**. Another dry etch removes the new silicon oxide from portions of the Aluminum Nitride, which is shown at structure **1320**. A wet etch is then performed to remove the uncovered and unwanted Aluminum Nitride, which is shown at structure **1325**. A second wet etch is performed to remove the remaining top layer of silicon oxide, which is shown at structure **1330**. These steps ensure that the top layer of silicon is not damaged in the removal of the Aluminum Nitride.

[0098] Once the silicon is exposed having only the desired Aluminum Nitride remaining, a dry etch is performed to create small holes in the silicon at various locations to expose the underlying silicon oxide layer. The holes are approximately 50 nm diameter, and they are patterned into the resist using electron-beam lithography. This step is shown by structure **1335**. An aluminum evaporation is performed to place an aluminum conductor over portions of the structure as shown at structure **1340**. Josephson junctions and other bandaging is created as shown at structure **1345**. Finally, an anhydrous HF vapor release is performed to remove the underlying silicon oxide layer. The anhydrous HF vapor release can undercut the silicon device layer by

selectively removing the buried silicon oxide, without attacking the aluminum features and without destroying the Josephson junctions. As shown at structure **1350**, the top silicon layer is now a suspended crystalline structure.

[0099] In some embodiments, the SOI wafer consists of a 220-nm-thick silicon device layer with surface orientation and with a specified resistivity of, for example, $>3000 \Omega\text{cm}$. Underneath the device layer is a 3- μm buried silicon dioxide (SiO_2) BOX layer. The device and BOX layers sit atop a silicon (Si) handle wafer of thickness 675 μm and a specified resistivity of, for example, $3000 \Omega\text{cm}$. Both the Si device layer and the handle wafer may be grown using the Czochralski crystal growth method. The Si device layer may be grown using the float-zone method.

[0100] Each of the calculations or operations described herein may be performed using a computer or other processor having hardware, software, and/or firmware. The various method steps may be performed by modules, and the modules may comprise any of a wide variety of digital and/or analog data processing hardware and/or software arranged to perform the method steps described herein. The modules optionally comprising data processing hardware adapted to perform one or more of these steps by having appropriate machine programming code associated therewith, the modules for two or more steps (or portions of two or more steps) being integrated into a single processor board or separated into different processor boards in any of a wide variety of integrated and/or distributed processing architectures. These methods and systems will often employ a tangible media embodying machine-readable code with instructions for performing the method steps described above. Suitable tangible media may comprise a memory (including a volatile memory and/or a non-volatile memory), a storage media (such as a magnetic recording on a floppy disk, a hard disk, a tape, or the like; on an optical memory such as a CD, a CD-R/W, a CD-ROM, a DVD, or the like; or any other digital or analog storage media), or the like.

[0101] Different arrangements of the components depicted in the drawings or described above, as well as components and steps not shown or described are possible. Similarly, some features and sub-combinations are useful and may be employed without reference to other features and sub-combinations. Embodiments of the present disclosure have been described for illustrative and not restrictive purposes, and alternative embodiments will become apparent to readers of this patent. In certain cases, method steps or operations may be performed or executed in differing order, or operations may be added, deleted or modified. It can be appreciated that, in certain aspects of the present disclosure, a single component may be replaced by multiple components, and multiple components may be replaced by a single component, to provide an element or structure or to perform a given function or functions. Except where such substitution would not be operative to practice certain embodiments of the present disclosure, such substitution is considered within the scope of the present disclosure.

[0102] It is to be understood that the figures and descriptions of embodiments of the present disclosure have been simplified to illustrate elements that are relevant for a clear understanding of the present disclosure. Those of ordinary skill in the art will recognize, however, that these and other elements may be desirable. However, because such ele-

ments are well known in the art, and because they do not facilitate a better understanding of the present disclosure, a discussion of such elements is not provided herein. It should be appreciated that the figures are presented for illustrative purposes and not as construction drawings. Omitted details and modifications or alternative embodiments are within the purview of persons of ordinary skill in the art.

[0103] It can be appreciated that, in certain aspects of the present disclosure, a single component may be replaced by multiple components, and multiple components may be replaced by a single component, to provide an element or structure or to perform a given function or functions. Except where such substitution would not be operative to practice certain embodiments of the present disclosure, such substitution is considered within the scope of the present disclosure. A recitation of “a”, “an” or “the” is intended to mean “one or more” unless specifically indicated to the contrary.

[0104] The examples presented herein are intended to illustrate potential and specific implementations of the present disclosure. It can be appreciated that the examples are intended primarily for purposes of illustration of the present disclosure for those skilled in the art. There may be variations to these diagrams or the operations described herein without departing from the spirit of the present disclosure. For instance, in certain cases, method steps or operations may be performed or executed in differing order, or operations may be added, deleted or modified.

[0105] Furthermore, whereas particular embodiments of the present disclosure have been described herein for the purpose of illustrating the present disclosure and not for the purpose of limiting the same, it will be appreciated by those of ordinary skill in the art that numerous variations of the details, materials and arrangement of elements, steps, structures, and/or parts may be made within the principle and scope of the present disclosure without departing from the present disclosure as described in the claims.

APPENDICES

[0106] The present disclosure includes Appendix A, the entire contents of which is incorporated herein for all purposes and is considered part of this disclosure.

What is claimed is:

1. A system, comprising:
a mechanical resonator; and
a circuit coupled to the mechanical resonator;
wherein the circuit is configured to coherently excite hypersonic mechanical motion of the mechanical resonator so as to transfer a quantum level signal for storage in the mechanical resonator.
2. The system of claim 1, wherein the circuit is configured to coherently excite the hypersonic mechanical motion of the mechanical resonator so as to transfer the quantum level signal for storage in the mechanical resonator with a Q factor of at least 10^6 .
3. The system of claim 1, further comprising a waveguide coupled to the circuit, wherein phonons dissipate from the mechanical resonator via leakage of a photon from the circuit through the waveguide.
4. The system of claim 1, wherein the circuit comprises a microwave circuit, the hypersonic mechanical motion comprises a mode at a gigahertz frequency, and the microwave

circuit and the mechanical resonator are coupled via a cooperative coupling of at least 30.

5. The system of claim **1**, wherein the circuit comprises a superconducting microwave circuit and the quantum level signal comprises a superposition state.

6. The system of claim **1**, wherein the circuit controls a detuning of a drive tone relative to resonant modes of the circuit, so as to control the storage and a readout of the quantum level signal.

7. The system of claim **1**, wherein the circuit is configured to define an operating bandwidth of the system.

8. The system of claim **1**, wherein the mechanical resonator comprises a nano-mechanical resonator.

9. The system of claim **8** wherein the nano-mechanical resonator comprises a nanobeam.

10. The system of claim **1**, wherein the mechanical resonator comprises a chain of acoustic cavities or a linear resonator.

11. The system of claim **1**, wherein the mechanical resonator comprises a piezoelectric nanomechanical resonator.

12. The system of claim **1**, wherein the mechanical resonator comprises a phononic crystal comprising a phononic band-gap suppressing or eliminating acoustic radiation from the mechanical resonator other than via the circuit.

13. The system of claim **1**, wherein the circuit transfers the quantum level signal comprising a qubit suitable for processing in a quantum computer.

14. The system of claim **1**, wherein the circuit is configured to readout the qubit stored in the mechanical resonator.

15. The system of claim **1**, wherein the circuit is configured to transfer the quantum level signal via a parametric interaction.

16. The system of claim **1**, comprising a transducer transducing the quantum level signal between an electrical form in the circuit and an acoustic form in the mechanical resonator.

17. A network comprising the transducer of claim **16**, wherein the network distributes quantum information using the quantum level signal.

18. The system of claim **1**, comprising a transducer transducing the quantum level signal into an optical signal.

19. A network comprising the transducer of claim **18**, wherein the network distributes quantum information using the optical signal.

20. The system of claim **1**, further comprising a metamaterial.

21. A method of storing quantum level signals, comprising: coherently exciting a hypersonic mechanical motion of a mechanical resonator, so as to transfer a quantum level signal for storage in the mechanical resonator with a Q factor of at least 10^6 ; and

removing phonons from the mechanical resonator via leakage of photons from a circuit coupled to the mechanical resonator.

* * * * *