

US 20230242330A1

(19) **United States**

(12) **Patent Application Publication**

Forouzandeh et al.

(10) **Pub. No.: US 2023/0242330 A1**

(43) **Pub. Date:**

Aug. 3, 2023

(54) **MINIATURE PRESSURE-DRIVEN PUMPS**

F04B 43/06

(2006.01)

(71) Applicant: **UNIVERSITY OF SOUTH FLORIDA**, Tampa, FL (US)

(52) U.S. Cl.

CPC *B65D 83/14* (2013.01); *F04B 43/06*
(2013.01); *F04B 43/0054* (2013.01)

(72) Inventors: **Farzad Forouzandeh**, Rochester, NY (US); **David Borkholder**, Canandaigua, NY (US); **Robert Frisina**, Tampa, FL (US); **Joseph Walton**, Tampa, FL (US); **Xiaoxia Zhu**, Tampa, FL (US)

(57)

ABSTRACT

(21) Appl. No.: 18/121,511

(22) Filed: **Mar. 14, 2023**

Related U.S. Application Data


(63) Continuation of application No. 17/074,258, filed on Oct. 19, 2020, now Pat. No. 11,603,254.



(60) Provisional application No. 62/923,417, filed on Oct. 18, 2019.

Publication Classification

(51) **Int. Cl.**
B65D 83/14 (2006.01)
F04B 43/00 (2006.01)

A miniature pump including a first chamber, a second chamber, a deformable membrane provided within the second chamber that divides the second chamber into first and second sub-chambers, the second sub-chamber defining a reservoir configured to contain liquid to be dispensed, a passage that connects the first chamber to the first sub-chamber, and an outlet in fluid communication with the reservoir, wherein pressurized fluid within the first internal chamber flows through the passage and into the first sub-chamber to compress the deformable membrane and cause liquid contained within the reservoir to flow out from the reservoir through the outlet and wherein the deformable membrane does not generate significant restoring forces when it is deformed and, therefore, will not return to its initial undeformed shape unless the reservoir is refilled.








FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

MINIATURE PRESSURE-DRIVEN PUMPS**CROSS-REFERENCE TO RELATED APPLICATION**

[0001] This application is a continuation of, and claims priority to, co-pending U.S. Application Serial No. 17/074,258, filed Oct. 19, 2020, which claims priority to U.S. Provisional Application Serial No. 62/923,417, filed Oct. 18, 2019, both of which are hereby incorporated by reference herein in their entireties.

NOTICE OF GOVERNMENT-SPONSORED RESEARCH

[0002] This invention was made with Government support under grant contract number R01DC014568 awarded by the National Institutes of Health (NIH). The Government has certain rights in the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0003] The present disclosure may be better understood with reference to the following figures. Matching reference numerals designate corresponding parts throughout the figures, which are not necessarily drawn to scale.

[0004] FIG. 1 is a perspective view of an embodiment of a miniature pressure-driven pump.

[0005] FIG. 2 is a schematic view of a pump chamber of the pump of FIG. 1.

[0006] FIG. 3 is a perspective exploded view of a further embodiment of a miniature pressure-driven pump.

[0007] FIG. 4 is a graph that shows the effect of pressure on the flow rate of a miniature pressure-driven pump.

[0008] FIG. 5 is a graph that shows the effect of inclusion or exclusion of a pressure ring on a septum of a miniature pressure-driven pump.

[0009] FIG. 6 is a graph that shows the amount of backflow that occurs for miniature pressure-driven pumps of various reservoir capacities.

[0010] FIG. 7 is a graph that shows modeling results for the effect of fluid viscosity on flow rate for a miniature pressure-driven pump.

[0011] FIG. 8 is a graph that shows modeling results for the effect of downstream height on flow rate for a miniature pressure-driven pump.

[0012] FIG. 9 is a graph that shows modeling results for the effect of ambient temperature on flow rate for a miniature pressure-driven pump.

BACKGROUND

[0013] Fluid perfusion is required for various lab-on-chip (LOC) applications, such as maintaining viable cell cultures in microfluidic channels. Unfortunately, traditional pumping apparatus, such as characterization syringe pumps and constant pressure sources, are bulky and can be difficult to integrate with cell-based microfluidic systems that require incubation. It would be desirable to have pumps suitable for LOC applications that are less bulky and more easily integrated into microfluidic systems.

DETAILED DESCRIPTION

[0014] As expressed above, it would be desirable to have pumps suitable for lab-on-chip (LOC) applications that are

less bulky and more easily integrated into microfluidic systems than conventional pumps. Disclosed herein are examples of such pumps. In some embodiments, a miniature pump is configured as a zero-power, plug-and-play pump that comprises a refillable liquid reservoir defined at least in part by a deformable membrane. When external pressure is applied to the membrane, for pneumatic pressure, the membrane is compressed and liquid is discharged from the reservoir.

[0015] In the following disclosure, various specific embodiments are described. It is to be understood that those embodiments are example implementations of the disclosed inventions and that alternative embodiments are possible. Such alternative embodiments include hybrid embodiments that include features from different disclosed embodiments. All such embodiments are intended to fall within the scope of this disclosure.

[0016] Disclosed herein is a zero-power, plug-and-play pump that comprises a refillable liquid reservoir defined at least in part by a deformable membrane. When liquid is to be pumped by the pump, the membrane is compressed by regulated pneumatic pressure and at least some of the liquid is discharged from the reservoir. In some embodiments, the membrane generates little or no restoring forces such that little or no backflow occurs when the pump is off. In some embodiments, the pump can be directly connected to a modular microfluidic device to provide fluid pumping without the need for electrical power.

[0017] Test results described below reveal that the flow rate of the pump can be controlled by adjusting the pneumatic pressure and/or the size of a flow constrictor, such that, in some cases, flow rates ranging from 35 nL/mm to 100 μ L/mm can be achieved. For LOC applications, this range may be approximately 35 to 2,400 nL/mm. In some embodiments, a septum can be used to refill the reservoir. Testing of an experimental pump comprising such a septum showed no septum leakage after thousands of injections under up to approximately 15 psi of backpressure. Scalability of the reservoir was explored by fabricating multiple reservoirs of different capacities. The characterization of backflow in different capacities revealed less than 2% of the overall volume backflow and up to 95% fluid ejection. COMSOL Multiphysics® Modeling Software simulations were also performed and the results demonstrated minimal dependency on the flow rate to downstream height. Through the testing, it was concluded that the miniature pump provides robust long-term flows across a broad range of volumes from tens to thousands of nL/min. Due to the low-cost, biocompatible, and scalable fabrication methodology, as well as the plug-and-play usability of the pump, the device can be used in broad range of miniaturized (e.g., microfluidic) applications and, therefore, has the potential to replace traditional pumps for simple perfusion applications.

[0018] FIG. 1 illustrates an example configuration for a miniature pump 10 of the type discussed above. As shown in this figure, the pump 10 (or “pumping device”) comprises a substrate 12 (shown in partial view) upon which the remainder of the pump’s components are supported. The substrate 12 can be made of any suitably supportive material. In some embodiments, the substrate 12 is made of a polymer material, such as polymethyl methacrylate (PMMA), and can be formed using a deposition fabrication technique, such as three-dimensional (3D) printing.

[0019] Provided on a surface **14** of the substrate **12** is a pump body **16** that can also be made of a polymer material, such as a biocompatible resin. In some embodiments, the body **16** is coated with one or more layers of a durable biocompatible material, such as parylene C, using a suitable deposition process. In such cases, all surfaces of the body **16**, including those of internal features of the body, are covered in that material. In the illustrated example, the body **16** is shaped as a rectangular cuboid, although other shapes are possible.

[0020] Formed within the pump body **16** are an internal air chamber **18** and an internal pump chamber **20**. The air chamber **18** is in fluid communication with an air inlet port **22** that extends from the chamber to a top surface **24** of the body **16**. As described below, air (or another fluid) can be delivered to the chamber **18** via the port **22**. In some embodiments, the port **22** can include a valve **26** that enables air to be injected into (or withdrawn from) the chamber **18**. In other embodiments, the port **22** could comprise a septum, similar to the septum described below, instead of a valve. Also in fluid communication with the air chamber **18** is an internal lateral passage that connects the air chamber **18** to the pump chamber **20**. In some embodiments, this passage **28** comprises a bore that is formed through the pump body **16**. In some embodiments, a valve (not shown) can also be provided within the bore. In such cases, that valve could be used as a shut off valve that can be actuated to shut the pump **10** off.

[0021] In the illustrated embodiment, the pump chamber **20** is configured as a cylindrical chamber having a vertical central axis and an internal base **30**. Provided within the chamber **20** is a deformable pump membrane **32** that helps define the liquid reservoir. As is most clearly illustrated in the schematic representation of the chamber **20** of FIG. 2, the membrane **32** separates the chamber into an upper air sub-chamber **34** and a lower liquid sub-chamber **36**, the latter of which being used as (and being referable to as) a liquid reservoir of the pump **10**. The membrane **32** is made of a material and has a thickness that enable the membrane to easily deform when pressure is applied to it by the air sub-chamber. In the embodiment illustrated in FIGS. 1 and 2, the pump membrane **32** comprises a thin dome-shaped element that has a base or bottom rim **38** that is securely attached to the base **30** of the pump chamber **20** and that extends upward within the chamber. In some embodiments, the portion **39** of the substrate covered by the membrane **32** (the membrane and that portion together defining the volume of the liquid reservoir) is convex, as shown in FIG. 2. In further embodiments, the substrate portion **39** has the inverse shape of the membrane **32**, i.e., the magnitude of its concavity is equal to the magnitude of the membrane's convexity. In such cases, the substrate portion **39** and the membrane **32** have the same surface area and the membrane can lie flat on the substrate portion when all fluid has been discharged from the reservoir.

[0022] The membrane **32** can be made of one or more layers of a durable and flexible biocompatible polymer material. In some embodiments, the membrane **32** is made of a single layer of material that is no greater than 100 μm thick. By way of example, the layer can be approximately 2 to 20 μm thick. In some embodiments, the membrane is made of a silicone material having a Young's modulus of approximately 1 MPa. In other embodiments, the membrane **32** can be made of a parylene material, such as parylene C,

which has a Young's modulus of approximately 2 to 3 GPa. As will be appreciated by persons having skill in the art, both of these parameters (i.e., Young's modulus and thickness) impact the membrane's ability to create restoring forces. Accordingly, those parameters can be adjusted in order to minimize the generation of restoring forces. For example, if the Young's modulus of the material is relatively high, the membrane can be thinner to achieve that result. If, on the other hand, the Young's modulus is relatively low, the membrane may be thicker to achieve the result.

[0023] The material properties and thinness of the pump membrane **32** together ensure that, when the pump membrane **32** deforms (i.e., collapses) as fluid is discharged from the liquid reservoir defined in part by the membrane, little or no restoring forces are generated by the membrane and, therefore, little or no undesirable backflow of fluid away from the downstream destination for the fluid occurs. As such, once liquid is discharged from the liquid reservoir, the membrane **32** will not draw significant amounts of discharged fluid back into the reservoir. In some embodiments, less than 2% of the volume of discharged liquid undergoes backflow and is drawn back into the reservoir. In other embodiments, less than 0.5% of the volume of discharged liquid undergoes backflow and is drawn back into the reservoir. Accordingly, backflow can be limited to less than 0.5% of discharged liquid.

[0024] With further reference to FIG. 1, a fluid inlet port **40** is also formed in the pump body **16**. This port **40** extends from the top surface **24** of the body **16** to the liquid reservoir **36** of the pump chamber **20** and, therefore, can be used to deliver fluid to (or remove fluid from) the reservoir. Provided within the port **40** is a resealable septum **42** that can be pierced by a filling element configured to deliver liquid to the reservoir **36**, such as a needle, and that immediately reseals itself after the filling element has been withdrawn. In some embodiments, the septum **42** is made of a biocompatible material, such as a silicone material, and is firmly held in place by a compression ring (not visible) that induces lateral stress within the septum to enable the septum to be punctured thousands of times without leakage. Significantly, the port **40** and septum **42** are separate and independent of the pump membrane **32**, which enables the membrane to be extremely thin and, therefore, minimize the generation of restoring forces.

[0025] Formed on the exterior of the pump body **16** is an fluid outlet **44** that is in fluid communication with the liquid reservoir **36**. Accordingly, fluid can exit the reservoir **36** via the outlet **44**. Connected to the outlet **44** is an outlet tube **46** that is configured to deliver the fluid to one or more downstream devices. As shown in FIG. 1, these downstream devices can be integrated with the remainder of the pump components and likewise be provided on or formed within the substrate **12**. In the illustrated embodiment, the downstream devices include a platform **48** in which a debubbler **50** (configured to remove bubbles from the liquid) and a fluidic resistor **52** (configured to increase resistance of the output fluid flow to provide greater control over the flow rate) are provided. As shown in FIG. 1, connection between the outlet tube **46** and the platform **48** is facilitated with a connector mechanism **54** comprising a resilient O-ring that facilitates simple and fast connection of tubes to the platform. Fluid that flows through the outlet tube **46** passes through the connector mechanism **54** and to the debubbler **50**, which is immediately upstream of the fluidic resistor **52**.

After passing through the debubbler **50** and the fluidic resistor **52**, the liquid can exit the platform **48** and enter a further outlet tube **56** that is also connected to the platform with a connector mechanism **54**. The tube **56** can then deliver the fluid to one or more further downstream devices that are either integrated with the above-described components or independent of them.

[0026] It is noted that fluidic resistance can, alternatively, be achieved by providing a small diameter passage through which discharged liquid must pass. For instance, a small diameter tube can be connected to the outlet **44** of the pipe to provide resistance similar to that provided by the fluidic resistor **52**.

[0027] When the pump **10** is operated to deliver fluids, the pump membrane **32** is compressed so as to squeeze liquid out from the fluid reservoir **36**. This compression can be achieved using regulated pneumatic pressure. Specifically, the air chamber **18** can be supplied with compressed air (or another gas), which then travels through the passage **28** and into the upper air sub-chamber **34** of the pump chamber **20**. That air/gas pressurizes the air sub-chamber **34** and compresses the membrane **32** (downward in the embodiment of FIGS. **1** and **2**). Once equilibrium is achieved between the air and liquid sub-chambers **34**, **36**, no further liquid is dispensed. Moreover, backward flow of liquid toward and into the fluid reservoir **36** is minimized or even avoided because of the above-described parameters of the membrane **32**. Accordingly, the membrane **32** enables precision control for pumping and prevents backflow when the pump **10** is off. Because the pump is driven by pneumatic pressure, it can deliver fluid without any power being required.

[0028] Experimental pumps were fabricated and tests were performed on them to evaluate their operation. The body of the pump was 3D printed using a Formlab® Form 2™ stereolithography device with a biocompatible resin (Dental SG™), followed by 1-μm parylene deposition. 1000 μL of molten polyethylene glycol (PEG) at 60° C. was deposited within the pump chamber to solidify and define the reservoir shape and volume. This was followed by another parylene deposition to create the pump membrane. A gasket was fabricated using a long-term biocompatible silicone material (Nusil®, MED6215) that was micro-molded and placed within the pump chamber surrounding the PEG dome. A 3D-printed compression ring was then placed on the gasket and affixed using cyanoacrylate to reinforce the seal between the two parylene C layers. The device was placed on a hotplate at 60° C. to melt the PEG, which was then washed away using by gentle injection of 10 mL of deionized (DI) water at 60° C.

[0029] A 2.5-mm diameter, 1-mm-thick septum made of long-term implantable silicone rubber was micro-molded and coated with 1 μm of parylene C. The septum was then placed in the liquid inlet port, which was 2.5 mm in diameter. A 3D-printed cap with an extruded compression ring on the septum area (2.5 mm OD, 1.8 mm ID) and a pneumatic port was affixed on top of the pump with cyanoacrylate to: (a) compress the septum providing a sealing force on the bottom and sides while enhancing the self-healing properties when punctured with refilling needles, (b) provide a pneumatic connection to the air chamber to apply pneumatic pressure on the pump membrane for pumping, and (c) protect the membrane from mechanical stress.

[0030] An air chamber was 3D printed with an inlet port for providing compressed air and a pneumatic passage leading to the liquid reservoir formed by the pump membrane. An air-tight septum was placed on the inlet port and the sealing and self-healing properties of the septum were achieved using a cap with a compression ring to induce lateral stress in the septum. The air chamber and pump chamber were connected through the pneumatic passage and sealed using cyanoacrylate. The air chamber was provided with openings for magnets. Four magnets (1 mm thickness, 1/8" diameter) were then placed in the designated openings.

[0031] A 0.5-mm polymethyl methacrylate (PMMA) sheet was next cut to form a substrate supporting the air and liquid chambers, a debubbler, a fluidic resistor, and a microfluidic chip. A second layer of PMMA was created to provide fluidic channels/passages for fluid flow between those components. A polytetrafluoroethylene (PTFE) membrane was placed on the substrate in an area reserved for the debubbler/fluidic resistor and affixed in place using pressure-sensitive adhesive film. The fluidic resistor was then fabricated with a 0.5-mm polydimethylsiloxane (PDMS) layer having 20 × 100 μm serpentine channels formed using soft lithography. Inlet and outlet ports were formed using 0.5-mm biopsy punches. A second 0.5-mm layer of PDMS having openings for magnets was placed on and sealed to the first layer using corona treatment, and the PDMS layer was then affixed to the PMMA layer using corona treatment.

[0032] Another layer of PMMA having a 2 × 12 mm² opening was affixed on top of the PTFE membrane to form the debubbler. An O-ring (1 mm ID, 3 mm OD) was placed on the inlet of the channel. The same type of O-ring was placed on the outlet of the system and covered with a PMMA layer to affix it in place. Another PMMA layer was positioned to level the platform for microfluidic chips. The inlet O-ring was affixed using another PMMA layer. The PDMS channel was covered with a PMMA layer with openings for magnets to protect the channel from mechanical stress. Eight magnets (1 mm thickness, 1/8" diameter) were placed in their designated openings.

[0033] The air chamber and liquid chamber were placed on the fluidic resistor area with an air-tight sealed O-ring providing fluidic connection between the reservoir and the debubbler. The air chamber and liquid chamber were secured on top of the fluidic resistor area with the attraction forces of the magnets. FIG. **3** illustrates the device in exploded view.

[0034] When the experimental pump device is used, a working liquid is injected through the septum into the 1,000 μL reservoir. The air chamber is pressurized using a pressure regulator to a desired pressure and pneumatic pressure is then applied to the pump membrane to force the fluid from the reservoir. The integrated debubbler eliminates potential bubbles in the dispenses fluid, which is then propelled through the fluidic resistor, which controls the flow rate. The membrane also enables precise control over the flow rate through adjustment of the pneumatic pressure.

[0035] It is noted that different capacities and flow rates can be achieved due to the use of stereolithography and soft lithography for fabrication of device. Accordingly, the device can be easily scaled to suit various microfluidic applications. In addition, the above-described O-ring connector mechanism enables simple plug-and-play capability,

which provides for simple and quick connection of the reservoir to the debubbler.

[0036] Experiments were performed on the fabricated pumps and their components. First, fluidic resistors having an area of $20 \times 100 \mu\text{m}^2$ area and different numbers of serpentine ($n=10, 20$, each round 3 cm long) were tested. The results are presented in FIG. 4 and show that, by tuning the pneumatic pressure within the range of 1 to 10 psi, the flow rate can be tuned from approximately 35 nL/min to ~2400 nL/min ($N=4$, mean \pm SD).

[0037] Second, the septum samples were tested. The results are presented in FIG. 5 and show that the samples without a compression ring leaked at less than 0.7 PSI kPa backpressure with just one puncture with a 30 Ga needle. Adding a compression ring to the septum cap increased the number of punctures before failure to approximately 65,000 at 14.5 psi backpressure when puncturing with a 12° non-coring 30 Ga needle ($N=4$, mean \pm SD).

[0038] Third, the pumps were tested for backflow. The results are presented in FIG. 6 and identify backflow due to restoring force for three different reservoir capacities of 1, 10, and 100 μL normalized by the total volume of each reservoir. The results show that the overall backflow is not significant (2% average) and occurs quickly (< 2 min), suggesting stable behavior of the pump membrane long-term. The last step of the experiment showed that the average of the total extraction percentage among three reservoirs was 95% of the total volume ($N=27$, mean \pm SD).

[0039] The effects of different liquid viscosities were also studies using a COMSOL® model that was modified to cover a range of common fluids used in LOC applications. The results are presented in FIG. 7 and show that the flow rate is inversely related to the liquid viscosity. The COMSOL® model was also used to test flow rate as a function of downstream height within a common range of LOC applications. The results are presented in FIG. 8 and show that the flow rate can be almost independent of downstream height if higher driving pressures are used. Finally, the COMSOL® model was used to evaluate how the variation of the ambient temperature impacts liquid viscosity and pressurized gas pressure. The results are presented in FIG. 9 and show that changing from room temperature to an incubator temperature can impact the flow rate by approximately 50%.

[0040] While the disclosed pumps are well suited for LOC applications, it is noted that such pumps can be used in other applications. One such other application is drug delivery. For example, a pump in accordance with the above disclosure could be implanted under the skin or could be integrated into an external delivery device, such as a transdermal patch, to deliver drugs or other substances to a human or animal patient.

1. A miniature pump comprising:

a pump chamber comprising a first sub-chamber and a second sub-chamber;

a deformable membrane provided within the pump chamber, the deformable membrane dividing the pump chamber into the first sub-chamber and the second sub-chamber, the second sub-chamber defining a reservoir to contain a liquid to be dispensed, the reservoir configured to store the liquid when the reservoir is in an undeformed state with a second pressure being applied on the deformable membrane, the second pressure being equal to or greater than a first pressure of fluid in the first sub-

chamber being applied on the deformable membrane in the undeformed state;

a passage attached to the first sub-chamber, the passage configured to deliver the fluid into the first sub-chamber; and
an outlet connected to the reservoir of the second sub-chamber.

2. The miniature pump of claim 1, wherein the second sub-chamber is configured to, in a deformed state, dispense the liquid when the second pressure in the second sub-chamber being applied on the deformable membrane is less than the first pressure of the fluid in the first sub-chamber being applied on the deformable membrane.

3. The miniature pump of claim 1, further comprising:
an air chamber,

wherein the passage connects the air chamber to the first sub-chamber.

4. The miniature pump of claim 3, wherein the air chamber includes the fluid, and wherein the fluid comprises pressurized air.

5. The miniature pump of claim 4, further comprising an air inlet for supplying the pressurized air to the air chamber.

6. The miniature pump of claim 1, further comprising a liquid inlet connected to the second sub-chamber for filling the reservoir with the liquid.

7. The miniature pump of claim 6, further comprising a resealable septum associated with the liquid inlet for delivering the liquid to the reservoir.

8. The miniature pump of claim 7, further comprising a compression ring for compressing the resealable septum to induce lateral stress within the resealable septum that prevents leakage.

9. The miniature pump of claim 1, further comprising a debubbler in fluid communication with the outlet, the debubbler being configured to remove bubbles from dispensed liquid.

10. The miniature pump of claim 9, further comprising a fluidic resistor in fluid communication with the debubbler, the fluidic resistor being configured to control a rate of flow of the dispensed liquid.

11. A method for pumping via a miniature pump, comprising:

introducing liquid into a pump chamber, the pump chamber comprising a first sub-chamber, a second sub-chamber, and a deformable membrane, the deformable membrane dividing the pump chamber into the first sub-chamber and the second sub-chamber, the second sub-chamber defining a reservoir configured to contain the liquid to be dispensed;

introducing, via a passage, fluid to the first sub-chamber; pressurizing the fluid in the first sub-chamber to compress the deformable membrane; and

in response to the compressed deformable membrane, dispensing the liquid through an output connected to the second sub-chamber.

12. The method of claim 11, wherein introducing the liquid to the pump chamber comprises:

inserting the liquid into the second sub-chamber to generate a restoring force to the deformable membrane.

13. The method of claim 11, wherein pressurizing the fluid in the first sub-chamber comprises:

pressuring the fluid in the first sub-chamber with a first pressure in the first sub-chamber to be greater than a second pressure of the liquid in the second sub-chamber.

14. The method of claim 11, further comprising:

inserting the fluid into an air chamber being connected to the passage.

15. The method of claim **14**, further comprising: supplying, via an air inlet connected to the air chamber, the fluid to the air chamber.

16. The method of claim **11**, further comprising: filling, via a liquid inlet connected to the second sub-chamber, the reservoir with the liquid.

17. The method of claim **16**, further comprising: delivering, via a resealable septum associated with the liquid inlet, the liquid to the reservoir.

18. The method of claim **17**, further comprising: compressing, via a compression ring, the resealable septum to induce lateral stress within the resealable septum that prevents leakage.

19. The method of claim **11**, further comprising removing, via a debubbler in fluid communication with an outlet, bubbles from the dispensed liquid.

20. A miniature pressure-driven pump comprising: a pump body comprising an internal air chamber, an internal pump chamber, and an internal passage connecting the internal air chamber to the internal pump chamber, the pump body further comprising an air inlet in fluid communication with the air chamber, a liquid inlet in fluid communication with the pump chamber, and a

liquid outlet in fluid communication with the pump chamber;

a deformable membrane provided within the pump chamber that divides the pump chamber into an air sub-chamber and a liquid sub-chamber, the liquid sub-chamber defining a liquid reservoir configured to contain liquid to be dispensed, the liquid sub-chamber in an undeformed state containing the liquid with a first pressure in the liquid sub-chamber to the deformable membrane being equal to or greater than a second pressure of fluid in the air sub-chamber to the deformable membrane;

a valve provided within the air inlet through which air can pass to fill the air chamber with pressurized air;

a septum provided within the liquid inlet through which the liquid can pass to fill the liquid reservoir with the liquid;

a compression ring that compresses the septum to induce lateral stress within the septum that prevents liquid leakage;

a debubbler in fluid communication with the liquid outlet, the debubbler being configured to remove bubbles from dispensed liquid; and

a fluidic resistor in fluid communication with the debubbler, the fluidic resistor being configured to control a rate of flow of the dispensed liquid.

* * * * *