



(19) **United States**

(12) **Patent Application Publication**
GONION et al.

(10) **Pub. No.: US 2023/0252779 A1**

(43) **Pub. Date: Aug. 10, 2023**

(54) **PERSONAL COMPUTING DEVICE
CONTROL USING FACE DETECTION AND
RECOGNITION**

Publication Classification

(71) Applicant: **Apple Inc.**, Cupertino, CA (US)

(72) Inventors: **Jeff GONION**, Campbell, CA (US);
Duncan Robert KERR, San Francisco,
CA (US)

(21) Appl. No.: **18/136,819**

(22) Filed: **Apr. 19, 2023**

- (51) **Int. Cl.**
G06V 10/94 (2006.01)
G06F 1/3231 (2006.01)
G06F 21/32 (2006.01)
G06F 21/62 (2006.01)
G06V 40/16 (2006.01)
G06F 18/40 (2006.01)
G06F 3/00 (2006.01)
G06F 3/0482 (2006.01)
G06F 3/0485 (2006.01)
- (52) **U.S. Cl.**
 CPC *G06V 10/945* (2022.01); *G06F 1/3231*
 (2013.01); *G06F 21/32* (2013.01); *G06F*
21/629 (2013.01); *G06V 40/164* (2022.01);
G06V 40/16 (2022.01); *G06V 40/172*
 (2022.01); *G06F 18/40* (2023.01); *G06F*
3/005 (2013.01); *G06F 3/0482* (2013.01);
G06F 3/0485 (2013.01); *Y02D 10/00*
 (2018.01)


Related U.S. Application Data

(63) Continuation of application No. 16/938,362, filed on Jul. 24, 2020, now Pat. No. 11,676,373, which is a continuation of application No. 14/980,344, filed on Dec. 28, 2015, now Pat. No. 10,726,242, which is a continuation of application No. 14/090,344, filed on Nov. 26, 2013, now Pat. No. 9,223,397, which is a continuation of application No. 12/074,985, filed on Mar. 6, 2008, now Pat. No. 8,600,120.

(60) Provisional application No. 61/009,888, filed on Jan. 3, 2008.

(57) **ABSTRACT**

Systems and methods are provided for control of a personal computing device based on user face detection and recognition techniques.






FIG. 1A

150




FIG. 1B




FIG. 2




FIG 3




FIG. 4

500
↘

<u>502</u>	<u>504</u>	<u>506</u>	<u>508</u>	<u>510</u>	<u>512</u>	<u>514</u>	<u>516</u>
EYES	NOSE	MOUTH	CHIN	SHAPE	AREAS	DISTANCE/ ANGLE/ RELATION	COLOR

FIG. 5

600




FIG. 6




FIG. 7




FIG. 8

**PERSONAL COMPUTING DEVICE
CONTROL USING FACE DETECTION AND
RECOGNITION**

REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority to and the benefit of U.S. Provisional Application No. 61/009,888, filed on Jan. 3, 2008, having Attorney Docket No. 104677-0119-001, entitled "Personal Computing Device Control Using Face Detection and Recognition," the entire contents of which are incorporated herein by reference.

BACKGROUND

[0002] This invention relates to personal computing devices and, more particularly, to personal computing device control using face detection and recognition.

[0003] A personal computing device may include any computing device or computer-controlled device capable of interacting or interfacing with a person. Types of personal computing devices may include personal computers, consumer electronics, personal media devices, personal communications devices, personal display devices, vehicle control systems, financial transactions systems, and any like computing device capable of interfacing with a person. Consumer electronic devices may include, without limitations, televisions, stereo systems, video gaming systems, cameras, video cameras, and task-specific computing devices. Personal computers may include, without limitation, desktop computers, laptop computers, portable computers, workstations, server interfaces, and handheld computers. Personal media devices may include, without limitation, cellular telephones, MP3 players, portable video players, media capable cellular telephone, and satellite media players. Personal communications devices may include wireless communications devices, cellular telephones, satellite phones, personal digital assistants (PDA), and other like communications devices. Vehicle control systems may include, without limitation, consumer electronic devices, personal media devices, personal communication devices, vehicle operating systems, and vehicle monitoring systems. Financial transaction systems may include, without limitation, automatic teller machines (ATM), store purchase/check-out systems, credit card transaction systems, and remote purchase systems.

[0004] The proliferation of such personal computing devices is so extensive and pervasive that many tasks performed by individuals, in their daily lives, involve some form of interaction with one or more personal computing device. Typically, users can actively or passively interface with a personal computing device. Active interfacing may include typing words on a keyboard, saying words, scrolling through a list, using a mouse pointer to select an icon, pressing one or more control buttons, and any like active user interaction. Passive interfacing may include viewing a text file, viewing an image, viewing a movie, listening to a song, listening to audio, or feeling a vibration or motion.

[0005] One problem with existing personal computing devices is that such devices often perform certain functions regardless of whether users are passively interfacing with the devices. In other words, personal computer devices are not able to determine whether a non-active or passive user is present and, subsequently, unable to perform certain operations to accommodate the passive user. For example, a

PC may automatically activate a screen saver every five minutes regardless of whether a user is viewing the PC's display screen. Thus, a passive user is often inconveniently required to actively perform an interaction with the PC at least every five minutes to prevent the initiation of the screen saver or to deactivate the screen save after it is initiated. Accordingly, there is a need for providing a user interface for a personal computing device that is capable of determine when a passive user is present without the need for active user interaction with the device.

[0006] Another problem with personal computing devices is that such devices often cannot efficiently determine whether certain users have the authority to perform certain functions of the personal computing device. For example, to access a restricted computer application, a user may be required to actively enter a password. Accordingly, there is a need for a more efficient and reliable user access control mechanism for personal computing devices.

SUMMARY

[0007] The invention, in various embodiments, addresses deficiencies in the prior art by providing systems, methods and devices that enable a personal computing device to detect the presence of at least one user, without the need for receiving active user input information, and control certain device operations depending on whether a user is present.

[0008] In one aspect, a personal computing device includes a user interface that generates one or more user information outputs and receives one or more user information inputs. The device also includes an image sensor for capturing one or more images. The device further includes a processor that detects one or more faces in the captured images and controls the generation of the user information outputs and the receiving of the user information inputs in response to the detection of the one or more faces.

[0009] In one configuration, controlling is in response to identifying one or more detected faces in the captured images. In one feature, identifying includes determining that at least one of the detected faces in the captured images is associated with an authorized user of the device. Face detection may be based on a pattern recognition algorithm. The pattern recognition algorithm may include a statistical model.

[0010] In another configuration, detecting includes employing at least one of face detection, face recognition, object recognition, view-based recognition, computer vision, and machine learning. Face detection may be based on at least one of knowledge-based methods, feature invariant approaches, template matching methods, and appearance-based methods.

[0011] A user information output may be derived from displaying one or more images, displaying video, displaying text, outputting audio, moving a portion of the device, and vibrating a portion of the device. The process of controlling may include continuing to display one of more interface images for a period of time after detecting a face or faces. The process of controlling may include inhibiting, delaying, or re-setting the initiation of a screen saver application.

[0012] In another configuration, user information inputs may be derived from a user typing words on a keyboard, saying words, scrolling through a list, using a mouse pointer to select an element, and/or pressing one or more control buttons.

[0013] The process of controlling may include controlling the operation of one or more applications of the device. An operation may include logging into or out of an application, starting or launching one or more applications, stopping or ending one or more applications, selecting or de-selecting one or more elements, increasing or decreasing one or more settings, moving through a list of elements, initiating or ending a communications session, playing music or video, pausing music or video, and/or initiating or ending an audio or video recording session. An element may include a song, a video, a music file, an audio file, a video file, a photograph, a media file, a data file, spreadsheet, document, an application icon, an activation icon, a control button, a data file, and/or contact data.

[0014] In one configuration, the image sensor includes a camera which may be integrated with an image display of a personal computing device. The personal computing device may include a personal computer, a portable computer, a cellular telephone, a wireless communications device, a media player, an MP3 player, a video player, and a PDA.

[0015] In another aspect, a personal media device includes an image sensor that captures one or more images and generates associated image data. The device also includes a data store having face detection data associated with at least one of knowledge based face detection, feature invariant based face detection, template matching based face detection, and appearance based face detection. The device further includes a processor that receives the image data, receives the face detection data, and detects the presence of a face in the captured images by processing the image data and face detection data. Then, the device controls the operation of an application in response to detecting the presence of a face in the captured images.

[0016] In a further aspect, a personal media device includes an image sensor that captures one or more images. The device includes a data store having at least one known face pattern that is associated with an authorized user of the media device. The device includes a processor that detects one or more faces in the captured images, recognizes at least one of faces as the face of the authorized user by comparing the one or faces with the data store, and controlling the operation of an application of the device in response to recognizing at least one of the faces as the face of the authorized user.

[0017] In another aspect, a personal communications device includes a transceiver that sends and receives user communications. The device also includes an image sensor that captures one or more images and generates associated image data. The device also includes a data store having face detection data associated with knowledge based face detection, feature invariant based face detection, template matching based face detection, and/or appearance based face detection. The device further includes a processor that receives the image data, receives the face detection data, detects the presence of a face in the captured images by processing the image data and face detection data, and controls the sending or receiving of a communication of the device in response to detecting the presence of a face in the captured images. The communication may include an electronic mail (e-mail) message, instant message, video message, multi-media message, audio message, and/or user voice call.

[0018] In yet another aspect, a personal communications device includes a transceiver that sends and receives user

communications. The device includes an image sensor that captures one or more images. The device also includes a data store having at least one known face pattern that is associated with an authorized user of the media device. The device further includes a processor that detects one or more faces in the captured images, recognizes at least one of the captured faces as the face of the authorized user by comparing the one or faces with the data store, and controls the sending or receiving of a communication of the device in response to recognizing that at least one of the captured faces is the face of the authorized user.

[0019] Various advantages and applications using user presence detection and recognition for a personal computing device in accordance with principles of the present invention are discussed in more detail below.

BRIEF DESCRIPTION OF THE DRAWINGS

[0020] The above and other features of the present invention, its nature and various advantages will become more apparent upon consideration of the following detailed description, taken in conjunction with the accompanying drawings, in which like reference characters refer to like parts throughout, and in which:

[0021] FIG. 1A is a perspective view of a personal computing device according to an illustrative embodiment of the invention;

[0022] FIG. 1B is another perspective view of a personal computing device according to an illustrative embodiment of the invention;

[0023] FIG. 2 is a view of a handheld personal computing device according to an illustrative embodiment of the invention;

[0024] FIG. 3 shows a simplified functional block diagram of a personal computing device according to an illustrative embodiment of the invention;

[0025] FIG. 4 is a diagram of a computer processing environment including various applications or routines running within a personal computing device according to an illustrative embodiment of the invention;

[0026] FIG. 5 is a face vector including various face features according to an illustrative embodiment of the invention;

[0027] FIG. 6 is a diagram of a database or list associating face vectors or patterns with users according to an illustrative embodiment of the invention;

[0028] FIG. 7 is a flow diagram of a process for inputting and identifying face patterns based on one or more pattern recognition algorithms according to an illustrative embodiment of the invention; and

[0029] FIG. 8 is a flow diagram of an exemplary process whereby a personal computing device performs a face detection and/or face recognition to control the device's input/output interface and/or to control an application according to an illustrative embodiment of the invention.

DETAILED DESCRIPTION OF THE DISCLOSURE

[0030] FIG. 1A is a perspective view of a personal computing device **100** in the form of a personal media or display device according to an illustrative embodiment of the invention. The device **100** includes a housing **102**, a first housing portion **104**, a second housing portion **106**, a display **108**, a keypad **110**, a speaker housing aperture **112**, a microphone

housing aperture **114**, a headphone jack **116**, and frame sidewall **122**. In certain embodiments, the frame sidewall **122** is the exposed portion of a frame residing within or adjacent to the housing **102** that provides structural support for the media device **100** and various internal components. The housing **102** may also include various gaps **118** that may include openings, separations, vents, or other pathways between elements of the housing **102** which enable the passage of air or sound through the housing **102**.

[0031] In one embodiment, the housing **102** includes a first housing portion **104** and a second housing portion **106** that are fastened together and/or to the frame sidewall **122** to encase various components of the media device **100**. The housing **102** and its housing portions **104** and **106** may include polymer-based materials that are formed by, for example, injection molding to define the form factor of the media device **100**. In one embodiment, the housing **102** surrounds and/or supports internal components such as, for example, a display **108** with externally controlled, variable brightness, one or more circuit boards having integrated circuit components, internal radio frequency (RF) circuitry, an internal antenna, a speaker, a microphone, a hard drive, a processor, and other components. Further details regarding certain internal components are discussed herein with respect to FIG. **3**. The housing **102** provides for mounting of a display **108**, keypad **110**, external jack **116**, data connectors, or other external interface elements. The housing **102** may include one or more housing apertures **112** to facilitate delivery of sound, including voice and music, to a user from a speaker within the housing **102**. The housing **102** may include one or more housing apertures **114** to facilitate the reception of sounds, such as voice, for an internal microphone from a device user.

[0032] The device **100** may include a personal media device and/or wireless communications device such as a cellular telephone, satellite telephone, cordless telephone, personal digital assistant (PDA), pager, portable computer, or any other device capable of wireless communications. In certain embodiments, the personal computing device **100** may include any computing device, dedicated processing device, television, display unit, or like device that includes a user interface.

[0033] The personal computing device **100** may also be integrated within the packaging of other devices or structures such a vehicle, video game system, appliance, clothing, helmet, glasses, wearable apparel, stereo system, entertainment system, or other portable devices. In certain embodiments, device **100** may be docked or connected to a wireless enabling accessory system (e.g., a wi-fi docking system) that provides the device **100** with short-range communicating functionality. Alternative types of devices **100** may include, for example, a media player such as an iPod or iPhone that are made available by Apple Inc., of Cupertino, Calif., pocket-sized personal computers such as an iPAQ Pocket PC available by Hewlett Packard Inc., of Palo Alto, Calif. and any other device capable of communicating wirelessly (with or without the aid of a wireless enabling accessory system).

[0034] In certain embodiments, the personal computing device **100** may synchronize with, for example, a remote computing system or server to receive media (using either wireless or wireline communications paths). Wireless syncing enables the device **100** to transmit and receive media and data without requiring a wired connection. Media may include, without limitation, sound or audio files, music,

video, multi-media, and digital data, in streaming and/or discrete (e.g., files and packets) formats.

[0035] During synchronization, a host system may provide media to a client system or software application embedded within the device **100**. In certain embodiments, media and/or data is “downloaded” to the device **100**. In other embodiments, the device **100** is capable of uploading media to a remote host or other client system. Further details regarding the capabilities of certain embodiments of the device **100** are provided in U.S. patent application Ser. No. 10/423,490, filed on Apr. 25, 2003, the entire contents of which are incorporated herein by reference.

[0036] Personal computing devices of this type may include touchscreen remote controls, such as a Pronto made available by Royal Philips Electronics of the Netherlands or a handheld GPS receivers made available by Garmin International, Inc. of Olathe, Kans. In certain embodiments, the display **108** includes a graphical user interface (GUI) to enable a user to interact with the device **100**. The personal computing device **100** may also include an image sensor **124** that enables the device **100** to capture an image or series of images (e.g., video) continuously, periodically, at select times, and/or under select conditions. The image sensor **124** may include a camera capable of capturing photographic images and/or video images. The sensor may be integrated with and/or within the display **108**. In certain embodiments, the image sensor **124** may be located along the periphery of the display **108** or any other location of the housing **102**.

[0037] FIG. **1B** is a perspective view of another type of personal computing device, in the form of a desktop PC system **150**, according to an illustrative embodiment of the invention. In this embodiment, as opposed to the embodiment of FIG. **1A**, the PC system **150** includes a computing system housing **152**, a display assembly **154**, a camera **156**, keyboard **158**, and pointer device **160**, e.g., a mouse.

[0038] FIG. **2** is a view of a handheld personal computing device **200**, e.g., a personal media device, according to an illustrative embodiment of the invention. The device **200** includes a interactive display **210** capable of allowing a user to scroll through a listing **202** of elements **212** in a direction **208** while the device **200** is held in the hand **204** of a user.

[0039] FIG. **3** shows a simplified functional block diagram of personal computing device **300** according to an illustrative embodiment of the invention. The block diagram provides a generalized block diagram of a computer system such as may be employed, without limitation, by the personal computing devices **100**, **150**, and **200**. The personal computing device **300** may include a processor **302**, storage device **304**, user interface **308**, display **310**, CODEC **312**, bus **318**, memory **320**, communications circuitry **322**, a speaker or transducer **324**, a microphone **326**, and an image sensor **330**. Processor **302** may control the operation of many functions and other circuitry included in personal computing device **300**. Processor **302** may drive display **310** and may receive user inputs from the user interface **308**.

[0040] Storage device **304** may store media (e.g., music and video files), software (e.g., for implanting functions on device **300**), preference information (e.g., media playback preferences), lifestyle information (e.g., food preferences), personal information (e.g., information obtained by exercise monitoring equipment), transaction information (e.g., information such as credit card information), word processing information, personal productivity information, wireless connection information (e.g., information that may enable

media device to establish wireless communication with another device), subscription information (e.g., information that keeps tracks of podcasts or television shows or other media a user subscribes to), and any other suitable data. Storage device **304** may include one more storage mediums, including for example, a hard-drive, permanent memory such as ROM, semi-permanent memory such as RAM, or cache.

[0041] Memory **320** may include one or more different types of memory which may be used for performing device functions. For example, memory **320** may include cache, ROM, and/or RAM. Bus **318** may provide a data transfer path for transferring data to, from, or between at least storage device **304**, memory **320**, and processor **302**. Coder/decoder (CODEC) **112** may be included to convert digital audio signals into an analog signals for driving the speaker **324** to produce sound including voice, music, and other like audio. The CODEC **112** may also convert audio inputs from the microphone **326** into digital audio signals. The CODEC **112** may include a video CODEC for processing digital and/or analog video signals.

[0042] User interface **308** may allow a user to interact with the personal computing device **300**. For example, the user input device **308** can take a variety of forms, such as a button, keypad, dial, a click wheel, or a touch screen. Communications circuitry **322** may include circuitry for wireless communication (e.g., short-range and/or long range communication). For example, the wireless communication circuitry may be wi-fi enabling circuitry that permits wireless communication according to one of the 802.11 standards. Other wireless network protocols standards could also be used, either in alternative to the identified protocols or in addition to the identified protocol. Other network standards may include Bluetooth, the Global System for Mobile Communications (GSM), and code division multiple access (CDMA) based wireless protocols. Communications circuitry **322** may also include circuitry that enables device **300** to be electrically coupled to another device (e.g., a computer or an accessory device) and communicate with that other device.

[0043] In one embodiment, the personal computing device **300** may be a portable computing device dedicated to processing media such as audio and video. For example, the personal computing device **300** may be a media device such as media player (e.g., MP3 player), a game player, a remote controller, a portable communication device, a remote ordering interface, an audio tour player, or other suitable personal device. The personal computing device **300** may be battery-operated and highly portable so as to allow a user to listen to music, play games or video, record video or take pictures, communicate with others, and/or control other devices. In addition, the personal computing device **300** may be sized such that it fits relatively easily into a pocket or hand of the user. By being handheld, the personal computing device **300** (or media device **100** shown in FIG. 1) is relatively small and easily handled and utilized by its user and thus may be taken practically anywhere the user travels.

[0044] As discussed previously, the relatively small form factor of certain types of personal computing devices **300**, e.g., personal media devices, enables a user to easily manipulate the devices position, orientation, and movement. Accordingly, the personal computing device **300** may provide for improved techniques of sensing such changes in position, orientation, and movement to enable a user to

interface with or control the device **300** by affecting such changes. Further, the device **300** may include a vibration source, under the control of processor **302**, for example, to facilitate sending motion, vibration, and/or movement information to a user related to an operation of the device **300**. The personal computing device **300** may also include an image sensor **330** that enables the device **300** to capture an image or series of images (e.g., video) continuously, periodically, at select times, and/or under select conditions.

[0045] Face detection and recognition are different processes. Face detection includes the process of detection and/or locating a face or faces within an image. Face recognition includes the process of recognizing that a detected face is associated with a particular person or user. Face recognition, however, is typically perform along with and/or after face detection.

[0046] Face detection and recognition are known in technology fields such as robotics and computer vision. However, there are numerous advantageous applications of this technology that enable more efficient control and interaction between a user and a personal computing system. In certain embodiments, a personal computing device such as devices **100**, **150**, and **200**, include an image sensor, e.g., a camera, that is orientated such that it is capable of sensing the presence of a user's face while the user is interfacing, either passively or actively, with the personal computing device. For example, the image sensor may be embedded within a display of the device such as image sensor **124** of FIG. 1A. Alternatively, the image sensor may be connected with and/or mounted on a display such as image sensor **156** of FIG. 1B. Thus, the image sensor, in certain embodiments, operating with the personal computing device's processor, acts as a user presence sensor and/or user authenticator depending on the requirements of an application running on the personal computing device.

[0047] FIG. 4 is a diagram of a computer processing environment **400** including various applications or routines running within a personal computing device according to an illustrative embodiment of the invention. The processing environment **400** may include a detection decision application **402**, a face recognition decision application **404**, and an input/output and/or application control application **406**. The environment **400** may also include detection data **424** and recognition data **426**, a face vector database **420** and/or an input/output interface configuration database **422**. The detection data **424** may include, without limitation, data associated with knowledge-based detection techniques **428**, feature-based detection techniques **430**, template matching techniques **432**, and/or appearance-based detection techniques **434**.

[0048] In certain embodiments, the input/output control application **404** and/or another application configure the input and/or output characteristics of a personal computing device based on a determination of the presence of a face by the decision application **402**. The decision application **402** may determine the presence of a user's face by comparing received image data from an image sensor that is scanning an area where a user is expected to be with a known set of data associated with at least one of techniques **428**, **430**, **432**, and **434**. The decision application **402** may include a decision model **408**, a face detection application **410**, and/or a face detection training application **412**. In one embodiment, the model **408** includes a model based on at least one of the knowledge-based detection technique **428**, the feature-based

detection technique **430**, and template matching technique **432**, and the appearance-based technique **434**.

[0049] Knowledge-based techniques may be based on rule-based and/or top-down methods that encode prior knowledge of what is included in a typical human face. The rules may include relationships between facial features and may be advantageous for face localization.

[0050] Feature-based and/or Feature invariant techniques specify structural features of a face that exist under varying conditions such as changes in pose, viewpoint, image quality, and/or lighting. This technique may be advantageous for face localization. Feature invariant techniques may include, without limitation, facial feature data, facial texture data, facial skin color data, and/or a combination of color, size, and shape of a face.

[0051] Template matching techniques may include methods of storing standard features of a face and using a correlation between an input image and the stored patterns to detect a face or faces. Template matching may include, without limitation, pre-defined templates and/or deformable templates.

[0052] Appearance-based techniques may include models that are learned from a set of training images that capture the variability of facial features. Appearance-based techniques may include, without limitation, eigenface data, distribution-based data, neural networks, support vector machines, naïve bayes classifiers, hidden markov models, and information theoretical approaches.

[0053] The recognition decision application **404** may include a decision model **414**, a face recognition application **416**, and/or a face recognition training application **418**. In one embodiment, the model **414** includes a model based on at least one of the knowledge-based detection technique **428**, the feature-based detection technique **430**, template matching technique **432**, and the appearance-based technique **434**, and any other statistical and/or predictive analysis techniques. In certain embodiments, the recognition data **426** includes data associated with face features to enable identification a particular user's face such as, without limitation, eyes data **436**, nose data **438**, mouth data **440**, chin data **442**, face areas data **444**, face feature distance data **446**, face shape data **448**, and/or face feature angles data **450**.

[0054] FIG. 5 is a diagram of a face feature vector **500** including various facial features associated with a user or class of users according to an illustrative embodiment of the invention. The face feature vector **500** may include one or more elements such as, without limitation, eyes data **502**, nose data **504**, mouth data **506**, chin data **508**, face shape data **510**, face areas data **512**, face feature distance/angle/relation data **514**, and/or skin color data **516**. In certain embodiments, the face feature vector **500** may include other data associated with the detection data **424** and/or recognition data **426**. In one embodiment, with respect to face recognition, the vector **500** is derived from a detected face in an image, and used to identify a particular user's face. In another embodiment, with respect to face detection, the vector **500** is derived from a sensed image, and used to detect the presence of a face in the image.

[0055] In one embodiment, a personal computing device generates an image sensor signal and/or signals including detection data **424** and/or recognition data **426**. The various data **428**, **430**, **432**, **434**, **436**, **438**, **440**, **442**, **444**, **446**, **448**, and/or **450** from the various signals may be combined to form a received vector **500**. The decision application **402**

may compare the received vector **500** with one or more known vectors that are stored within the database and/or data store **420** to detect one or more faces within an image. Accordingly, the vector **500** may be representative of a received image vector formed from the detected and/or sensed image at a particular instant or over a particular period. Alternatively, the vector **500** may be representative of a known or stored image vector within the database **420**.

[0056] In another embodiment, the recognition application **404** may compare the received vector **500** with one or more known vectors that are stored within the database and/or data store **420** to identify a detected face within an image. Accordingly, the vector **500** may be representative of a detected face feature vector from the sensed image at a particular instant or over a particular period. Alternatively, the vector **500** may be representative of a known or stored face feature vector within the database **420**.

[0057] In one embodiment, the vector **500** includes one or more known and/or stored vectors that operate as a rule set and/or rule sets to determine input and/or output characteristics of a personal computing device, and/or the operation of an application running on the device. In certain embodiments, the input/output control application **406** determines an input interface feature and/or characteristic based on a decision signal from the decision application **402** and/or decision application **404**. In one embodiment, the input/output control application **406** determines an alert output characteristic based on a decision signal from the decision application **402**. For example, where the personal computing device is a cellular telephone, upon an incoming call, the device may sense whether the user is viewing its display. If the user's presence is detected, the device may only provide a visual alert via the device's display. If the user's presence is not detected, the device may initiate an audible alert, e.g., ringtone, to alert the user about the incoming call. In this instance, the device may only apply face detection to determine whether any face is present and/or any person is viewing the device's display.

[0058] Alternatively, if an incoming email is received by the device, the device, e.g., device **100**, may perform a face recognition to identify the user. If the face of the user is recognized and/or authenticated, then the user is alerted about the email and the email may be made available to the user for viewing. If the face of the user is not recognized and/or authenticated, the device **100** may not initiate an email alert, and may hide, suppress, and/or block the content of the email from the unauthorized user.

[0059] In one embodiment, any element of a known and/or stored vector **500** may include a range of values. Depending on the type of decision model employed by a model application, the model application could select a particular input and/or output characteristic based at least in part on whether a received/detected element was in the defined range of a known element of a known vector or rule set.

[0060] FIG. 6 is a diagram of a database **600** or list associating face vectors or patterns with users according to an illustrative embodiment of the invention. In certain embodiments, authorized users may be enrolled/configured for one or more applications **602**, **604**, and **606** within a personal computing device. In certain embodiments, control of an output interface configuration may include, without limitation, controlling a display setting, an audio setting, a GUI configuration, a video output setting, a vibration output

setting, a communications output setting, an RF output setting, and/or any other output from a media device.

[0061] Controlling an input configuration setting may include, without limitation, a display setting, a GUI configuration, an audio input setting, a video input setting, a communications input setting, an RF input setting, and/or any other form of input setting. A setting may include an intensity level setting, an on/off setting, a pattern arrangement, a sequence arrangement, type of protocol, and/or any other characteristic of an interface input or output signal or representation. For example, a screen saver application may include a timer that activates the screen saver after a period of user inactivity. However, a user may continue to passively interact with a personal computing device by, for example, viewing a text document. Thus, the input/output control application 406 may periodically or continuously receive user presence information from the detection application 402 to enable the control application to inhibit, delay, or reset the timer of the screen saver. Thus, a passive user is allowed to view the text document without the need to actively press any keys on a keypad or keyboard. In certain embodiments, the screen saver application, or any other application, may interact directly with the decision application 402 and/or 404 to determine whether a user is present and/or authorized to access certain application features.

[0062] In operation, in one embodiment, users 1 through N are associated with face vectors 1 through N respectively. Thus, when the application 602 is running, the application 602 may continuously compare received image sensor signals with the list of vectors associated with application 602 to determine when one or more of the input or output configurations is to be selected, adjusted, and/or configured depending on whether a face is detected and/or a particular user is recognized.

[0063] FIG. 7 is a flow diagram of a process 700 for inputting, identifying, and/or recognizing face patterns based on one or more pattern recognition algorithms according to an illustrative embodiment of the invention. In certain embodiments, the face pattern recognition application 416 and face pattern training application 418 employ one or more pattern recognition algorithms and/or techniques to identify users based on their face patterns. First, the personal computing device 100 is subjected to a surrounding physical environment where the device experiences various changes in environmental conditions [Step 702]. The device 100 employs one or more image sensors 124 to capture an image of the environment adjacent to the device 100. In certain embodiments, the applications 416 and 418 account for bandwidth, resolution, sensitivity, distortion, signal-to-noise ratio, latency, and other issues with regard to data acquisition using the one or more image sensors 124 [Step 704].

[0064] The applications 416 and 418 may perform pre-processing of the image sensor signals to remove noise and/or to isolate patterns of interest from background information [Steps 706 and 720]. Then, the applications 416 and 418 may perform feature extraction by finding new representations in terms of identified features of sensor signals [Steps 708 and 722]. Particular features of image and/or detected face sensor signals may be identified as being more relevant for pattern identification [Steps 712 and 724]. Feature selection may include identifying discriminative features of image sensor signals such as similar values for similar patterns or different values for different patterns. Feature selection may include identifying invariant features

such as with respect to translation, rotation, and/or scale of sensor signals. Feature selection may include identifying robust features with respect to occlusion, distortion, deformation, and variations in environment.

[0065] The training application 418 may capture training data in the form of an input from the user, e.g. user photographs [Step 718]. In one embodiment, an application may provide an option associated with an element that enables a user to input an image into the database 420 and/or 600 associated with the element. In another embodiment, the user is prompted to submit their facial image once, twice, thrice, or more times as part of a training process for the face pattern training application 418.

[0066] After pre-processing, feature extraction, and selection, the application 418 may then perform model learning and estimation whereby the application 418 learns to map between features and pattern groups and categories of sensor signals [Step 726]. The application 418 may select a pattern recognition model that is parametric or non-parametric. The application 418 may select a type of model that includes at least one of templates, decision-theoretic or statistical, syntactic or structural, neural, and hybrid forms of pattern recognition analysis [Step 728].

[0067] Once a particular model is selected, the face pattern recognition application 416 performs a classification and/or matching of the received sensor signal using features and learned models from the face pattern training application 418 to assign the received face pattern to a category of patterns. The application 416 may then compare the received sensor signal with the set of face patterns in the database 600 to find the closest match between the received sensor signal and the stored array of known face patterns [Step 712]. The application 416 may perform post-processing by evaluating its confidence in the decision [Step 714]. The application 416 may then decide which known pattern of the database 600 corresponds to the received sensor signal to identify the user.

[0068] In certain embodiments, the features of the known face patterns may be limited to minimize costs in processing power and storage. Accordingly, the selectivity of identifying a particular pattern may vary depending on the number of points or features stored or used for each known face pattern. In another embodiment, the known face pattern can be pre-generated and stored in the personal computing device by the manufacturer or another entity.

[0069] The face pattern recognition application 416 may perform pattern recognition based on at least one of Bayes Decision Theory, Generative methods, discriminative methods, non-metric methods, algorithm-independent machine learning, unsupervised learning and clustering, and like techniques. The Bayes Decision techniques may include, without limitation, at least one of Bayes Decision Rule, minimum error rate classification, normal density and discriminant functions, error integrals and bounds, Bayesian networks, and compound decision theory. The Generative methods may include, without limitation, at least one of maximum likelihood and Bayesian parameter estimation, sufficient statistics, various common statistical distributions, dimensionality and computational complexity, principal components analysis, fisher linear discriminant, expectation maximization, sequential data, hidden Markov models, and non-parametric techniques including density estimation. The discriminative methods may include, without limitation, distance-based methods, nearest neighbor classification,

metrics and tangent distance, fuzzy classification, linear discriminant functions (hyperplane geometry, gradient descent and perceptrons, minimum squared error procedures, and support vector machines), and artificial neural networks. The non-metric methods may include, without limitation, recognition with strings and string matching. The algorithm-independent machine learning techniques may include, without limitation, no-free lunch theorem, bias and variance, re-sampling for estimation, bagging and boosting, estimation of misclassification, and classifier combinations. [0070] While the above approaches have been described with respect to face recognition, it should be understood that these approaches may also be applied to certain face detection techniques also.

[0071] FIG. 8 is a flow diagram of an exemplary process 800 whereby a personal computing device performs face detection and/or face recognition to control the device's input/output interface and/or to control an application according to an illustrative embodiment of the invention. A face detection and/or recognition system may have a wide range of applications, such as biometric authentication and surveillance, human-computer interaction, and multimedia management.

[0072] A face detection and recognition system may perform the process 800 by first capturing an image from an image sensor such as sensor 124 of FIG. 1 (Step 802). Then, the system performs face detection which provides information about the location and scale of each detected face in the captured image. In the case of video, the found faces may be tracked (Step 804). If only face detection is needed, the system then controls its user interface or an application based on whether a face is detected or not detected within the captured image or images (Step 806).

[0073] If face recognition is desired, the system then performs a face alignment to account for tilt or aspect variations of the detected face or faces. Facial components, such as eyes, nose, and mouth, and facial outline are located, and thereby the input face image is normalized in geometry and photometry (Step 808). Next, the system performs feature extraction where features useful for distinguishing between different persons are extracted from the normalized face (Step 810). The system may include a database wherein user faces have been enrolled to enable user authorization and/or authentication (Step 814). Then, the system performs a face classification where the extracted feature vector of the input face is matched against those of enrolled faces in the database such as database 600. The system outputs the identity of the face when a match is found with a sufficient confidence or as an unknown face otherwise (Step 812). Then, the system controls the user interface and/or an application based on whether a user's face is recognized or not recognized (Step 816).

[0074] The personal computing device may support user presence sensing control for numerous applications including, without limitation, e-mail, texting, word processing, interface navigation, data searching, web surfing, database management, remote control systems, multimedia applications, or any application operating with a personal computing device.

[0075] It will be apparent to those of ordinary skill in the art that methods involved in the present invention may be embodied in a computer program product that includes a computer usable and/or readable medium. For example, such a computer usable medium may consist of a read only

memory device, such as a CD ROM disk or conventional ROM devices, or a random access memory, such as a hard drive device or a computer diskette, or flash memory device having a computer readable program code stored thereon.

[0076] It is understood that the various features, elements, or processes of the foregoing figures and description are interchangeable or combinable to realize or practice the invention describe herein. Those skilled in the art will appreciate that the invention can be practiced by other than the described embodiments, which are presented for purposes of illustration rather than of limitation, and the invention is limited only by the claims which follow.

1. (canceled)
2. A computing device, comprising:
 - a display;
 - one or more sensors;
 - one or more processors; and
 - memory storing one or more programs configured to be executed by the one or more processors, the one or more programs including instructions for:
 - while displaying, via the display, a first user interface, determining whether a rule set is met, wherein the rule set includes a rule that is met when a face of a user is not detected via the one or more sensors for a predetermined period of time;
 - in accordance with a determination that the rule set is met, ceasing to display the first user interface; and
 - in accordance with a determination that the rule set is not met, continuing to display the first user interface.
3. The computing device of claim 2, wherein the one or more sensors include an image sensor.
4. The computing device of claim 2, wherein detecting the face of a user includes detecting an authorized face.
5. The computing device of claim 2, wherein ceasing to display the first user interface includes displaying a screen saver.
6. The computing device of claim 2, wherein ceasing to display the first user interface includes turning off the display.
7. The computing device of claim 2, wherein the rule set includes a rule that is met when the user is not viewing the first user interface.
8. The computing device of claim 2, wherein the rule set includes a rule that is met when a user has not interacted with the computing device for a predetermined period of time.
9. A method for controlling a computing device with a display and one or more sensors, the method comprising:
 - while displaying, via the display, a first user interface, determining whether a rule set is met, wherein the rule set includes a rule that is met when a face of a user is not detected via the one or more sensors for a predetermined period of time;
 - in accordance with a determination that the rule set is met, ceasing to display the first user interface; and
 - in accordance with a determination that the rule set is not met, continuing to display the first user interface.
10. A non-transitory computer-readable storage medium storing one or more programs configured to be executed by one or more processors of a computing device with a display and one or more sensors, the one or more programs including instructions for:
 - while displaying, via the display, a first user interface, determining whether a rule set is met, wherein the rule

set includes a rule that is met when a face of a user is not detected via the one or more sensors for a predetermined period of time;
in accordance with a determination that the rule set is met, ceasing to display the first user interface; and
in accordance with a determination that the rule set is not met, continuing to display the first user interface.

* * * * *