

US 20230303244A1

(19) **United States**

(12) **Patent Application Publication**

Claridge et al.

(10) **Pub. No.: US 2023/0303244 A1**

(43) **Pub. Date: Sep. 28, 2023**

(54) **HIGH SPEED MULTI-ROTOR VERTICAL
TAKEOFF AND LANDING AIRCRAFT**

Publication Classification

(71) Applicant: **xCraft Enterprises, Inc.**, Coeur d'Alene,
ID (US)

(51) **Int. Cl.**
B64C 29/02 (2006.01)
B64C 39/02 (2006.01)

(72) Inventors: **Jerry Daniel Claridge**, Sandpoint, ID
(US); **Charles Fischer Manning**,
Sandpoint, ID (US)

(52) **U.S. Cl.**
CPC *B64C 29/02* (2013.01); *B64C 39/024*
(2013.01); *B64U 10/13* (2023.01)

(21) Appl. No.: **17/892,602**


(57) **ABSTRACT**

(22) Filed: **Aug. 22, 2022**

This disclosure is generally directed to a High Speed vertical takeoff and landing (VTOL) aircraft that includes fixed wing flight capabilities. The High Speed VTOL aircraft may include at least two thrust producing rotors located equidistant from a longitudinal axis of the aircraft on a main wing, and at least two thrust producing rotors located equidistant from a longitudinal axis of the aircraft on a vertical wing. The rotors may be driven by electric motors. However, other power sources may be used such as combustion or hybrid engines. By adjusting the speed and/or the pitch of the rotors, the aircraft can transition from a vertical flight configuration to a horizontal flight configuration and back.

Related U.S. Application Data

(63) Continuation of application No. 17/119,113, filed on Dec. 11, 2020, now Pat. No. 11,420,737, which is a continuation of application No. 16/005,345, filed on Jun. 11, 2018, now abandoned, which is a continuation of application No. 14/554,892, filed on Nov. 26, 2014, now Pat. No. 9,994,313.






FIG. 1A




FIG. 1B




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4

40X




FIG. 5




FIG. 6




FIG. 7

800




FIG. 8A

800




FIG. 8B

800




FIG. 8C

FIG. 8




FIG. 9




FIG. 10




FIG. 11A




FIG. 11B




FIG. 11C

FIG. 11




FIG. 12A





FIG. 12B






FIG. 14




FIG. 15

HIGH SPEED MULTI-ROTOR VERTICAL TAKEOFF AND LANDING AIRCRAFT

RELATED APPLICATIONS

[0001] This Application is a continuation of U.S. Pat. Application No. 17/119,113, filed Dec. 11, 2020, which is a continuation of U.S. Pat. Application No. 16/005,345, filed Jun. 11, 2018, which is a continuation of and claims priority to U.S. Pat. Application No. 14/554,892, now U.S. Pat. No. 9,994,313, filed Nov. 26, 2014, which are incorporated herein by reference.

BACKGROUND

[0002] The field of aviation encompasses many different versions of manned and unmanned aircraft. The vast majority of readily accessible, affordable manned and unmanned aircraft are fixed wing designs that require the use of a hangar or ramp space for storage, and an air strip for takeoff and landing. To obviate this need, in some cases, tools are used to minimize the need for ramps or landing areas through the use of sling-shot mechanisms (for takeoff) or landing catches (for landing). In either case, the ease and efficiency of fixed wing design is often off-set by the need of ramp space or these additional tools. These requirements increase the overall cost of operating the aircraft, and can render it inaccessible to the average citizen. In addition, most manned and unmanned aircraft rely on traditional controls and require training and expertise to operate them. The degree of difficulty and knowledge required to operate these aircraft is often multiple times that of driving a traditional automobile, which may limit access to and growth in the industry.

[0003] In contrast, High Speed vertical takeoff and landing (VTOL) aircraft can be operated without use of an air strip. A large number of VTOL aircraft in use today are in the form of tilt-rotor, ducted, and dedicated lift system aircraft, and are employed by various militaries throughout the world. The overall complexity of the tilt-rotor aircraft generally limits their use to well trained, professional pilots. However, the many advantages of the tilt-rotor platform, including vertical lifting capabilities combined with the speed and efficiency of a conventional fixed wing aircraft, if available to the general public, could revolutionize the aviation industry.

BRIEF DESCRIPTION OF THE DRAWINGS

[0004] The detailed description is described with reference to the accompanying figures. In the figures, the left-most digit(s) of a reference number identifies the figure in which the reference number first appears. The same reference numbers in different figures indicate similar or identical items.

[0005] FIGS. 1A and 1B are perspective views of an illustrative High Speed Multi-Rotor vertical takeoff and landing (VTOL) aircraft.

[0006] FIG. 2 is a schematic diagram showing a transition of flight of an illustrative High Speed Multi-Rotor VTOL aircraft from takeoff to a transitional mode to a forward flight mode.

[0007] FIGS. 3A and 3B are side elevation views of an illustrative High Speed Multi-Rotor VTOL aircraft in forward flight mode. FIG. 3A shows the VTOL aircraft with

main wing loading. FIG. 3B shows the VTOL aircraft with vertical wing loading.

[0008] FIG. 4 is a top view of the illustrative High Speed Multi-Rotor VTOL aircraft shown in FIG. 1A.

[0009] FIG. 5 is a top view of an illustrative High Speed VTOL aircraft with an illustrative propulsion system.

[0010] FIG. 6 is a top view of the illustrative High Speed Multi-Rotor VTOL aircraft shown in FIG. 1A, showing various components that may be selectively included in the High Speed Multi-Rotor VTOL aircraft.

[0011] FIG. 7 is a side view of an illustrative manned High Speed Multi-Rotor VTOL aircraft with pusher-type rotors. FIG. 7 depicts the VTOL aircraft in a landed position.

[0012] FIG. 8 are vertical views of an unmanned version of the illustrative High Speed Multi-Rotor VTOL aircraft shown in FIG. 7, in flight. FIG. 8A depicts the VTOL aircraft in the vertical flight configuration. FIG. 8B depicts the VTOL aircraft in the horizontal flight configuration with main wing-loading. FIG. 8C depicts the VTOL aircraft in the horizontal flight configuration with vertical wing-loading.

[0013] FIG. 9 is a side view of the illustrative High Speed Multi-Rotor VTOL aircraft shown in FIG. 8 in the vertical flight configuration. FIG. 9 depicts the VTOL aircraft hovering in a nose-down configuration.

[0014] FIG. 10 is a schematic diagram showing a transition of flight of an illustrative High Speed Multi-Rotor VTOL aircraft from the horizontal flight mode to a transition mode to landing.

[0015] FIG. 11 are various views of a foldable rotor. FIG. 11A is a perspective view of an illustrative High Speed Multi-Rotor VTOL aircraft in forward flight, with two rotors folded and two rotors extended. FIG. 11B is perspective view of the foldable rotor in the extended position. FIG. 11C is a perspective view of a foldable rotor in a folded position.

[0016] FIGS. 12A and 12B are perspective views of a variable pitch rotor, such as the rotors depicted in FIGS. 1-4 and 6-11, mounted on a High Speed Multi-Rotor VTOL aircraft.

[0017] FIGS. 13A-13D are isometric views of an illustrative rotating assembly that connects a cockpit to the fuselage, the main wing, and/or the vertical wing of the illustrative VTOL aircraft.

[0018] FIG. 14 is a flow diagram showing a transition from takeoff, through a transition mode, to a forward flight mode.

[0019] FIG. 15 is an illustrative environment in which the VTOL aircraft, such as VTOL aircraft 100 may operate.

DETAILED DESCRIPTION

Overview

[0020] This disclosure is generally directed to a vertical takeoff and landing (VTOL) aircraft that includes fixed wing flight capabilities. As discussed above, various types of VTOL aircraft exist in the aviation industry. Some types, such as the V-22 Osprey, employ large rotating nacelles to effect a transition from a vertical to a horizontal flight configuration. Other embodiments employ rotating exhaust ports to effect the transition. Still others, such as tail sitters use thrust generating sources across different planes to effect a transition from vertical to horizontal flight. However, various embodiments described herein provide an

improved design in the VTOL aircraft market. For example, in at least one embodiment, the VTOL aircraft may include multiple variable speed and variable pitch rotors mounted on the same plane, equidistant from each other. Each of the multiple rotors may adjust speed and pitch independently of the other rotors, allowing for rotation and control about any aircraft axis. Various embodiments of the VTOL aircraft described herein may also transition between different orientations, such as, for example, between a primary wing loading orientation and a secondary wing loading orientation, which may permit different aircraft limits, such as, for example, an increased airspeed limitation in the secondary wing loading orientation.

[0021] Various embodiments of the VTOL aircraft may include a propulsion system comprising at least two engines and/or motors located equidistant from a longitudinal axis of the aircraft on a main wing, and at least two engines and/or motors located equidistant from a longitudinal axis of the aircraft on a vertical wing. The propulsion system may be driven by electric motors. However, other power sources may be used such as combustion or hybrid engines. By adjusting the power generated by each motor and/or engine, the aircraft may transition from a vertical flight configuration to a horizontal flight configuration and back. The aircraft may take off without use of an airstrip by liftoff into the vertical flight configuration. While in the vertical flight configuration, the propulsion system may generate thrust that is directed primarily perpendicular to the horizon. Once the aircraft has gained altitude in the vertical flight configuration, the aircraft may transition to a forward-flight mode where the propulsion system generates centerline thrust directed primarily toward the aft end of the aircraft. The propulsion system may later transition back to the vertical flight configuration to enable the aircraft to land without use of an airstrip.

[0022] The VTOL aircraft may be a manned aircraft, an unmanned aerial vehicle (UAV) or a remote-controlled aircraft. The VTOL aircraft may include main (i.e., primary) and vertical (i.e., secondary) wings to enable prolonged forward flight with lift generated by the wings. The main and vertical wings may have a symmetrical or asymmetrical camber. The aircraft may sustain the forward flight with the main wings as the primary lift surface. In some embodiments, the aircraft may transition from the main wing to the vertical wing as the primary lift surface, for example, by rotating approximately 90 degrees about a centerline axis. The rotors may provide directed thrust to provide pitch, roll, and yaw control of the aircraft. In some embodiments, the wings may include control surfaces such as ailerons, elevators, rudders, elevons, flaps, flaperons, and any other control surfaces necessary to control the aircraft in forward flight.

[0023] In accordance with various embodiments, the VTOL aircraft may employ a control management system that controls and sustains flight in various flight configurations (including, but not limited to, vertical flight, transition, horizontal flight, and combinations thereof). The VTOL aircraft may be flown in both semi-autonomous and fully autonomous flight modes. In semi-autonomous flight, operation of the aircraft may be performed by providing simple directional commands from operator controls to the control management system, which in turn executes the commands while taking other necessary action to sustain flight and/or avoid objects in the surrounding environment.

Thus, control of the aircraft from the operator's perspective may be akin to control of an aircraft in a video game, and may be made possible with minimal training or aviation expertise.

[0024] In various embodiments of fully autonomous flight, the VTOL aircraft may have a flight plan loaded into the control management system, the flight plan directing the configuration and/or navigation of the VTOL aircraft. Additionally or alternatively, the VTOL aircraft may be capable of fully autonomous flight in an emergency situation. For example, if an operator becomes incapacitated, the VTOL aircraft may be configured for an automatic recovery function in which the aircraft may establish a hover and land in the vertical flight configuration without input from an operator. For another example, the VTOL aircraft may enable the automatic recovery function upon lost contact with a remote operator.

[0025] The apparatuses, systems, and techniques described herein may be implemented in a number of ways. Example embodiments are provided below with reference to the following figures.

[0026] It is understood that the vertical flight configuration may encompass a hover and/or hovering the VTOL aircraft. The terms may vertical flight configuration, vertical flight mode, and hover mode may be used interchangeably. Additionally, or alternatively, the horizontal flight configuration is equivalent to a forward flight mode, and the two terms may be used interchangeably.

Illustrative Embodiment

[0027] FIGS. 1A and 1B are perspective views of an illustrative High Speed Multi-Rotor vertical takeoff and landing (VTOL) aircraft.

[0028] FIG. 1A is a perspective view of an illustrative High Speed Multi-Rotor VTOL aircraft **100** while the aircraft is in a vertical flight configuration. The aircraft in FIG. 1 has a main wing **102** (i.e., a first wing) and a vertical wing **104** (i.e., a second wing). The structure of the VTOL aircraft **100** may be monocoque, semi-monocoque, or may include trusses, unibodies, and/or stressed skin. The VTOL aircraft **100** may be made of carbon fiber, titanium, aluminum, or any other material appropriate for aircraft construction. The aircraft skin may be a low friction surface that may include built-in solar cells.

[0029] In various embodiments, the VTOL aircraft **100** may include storage pod **106** on the aircraft. In such embodiments, the storage pod **106** may be used to house cameras (i.e., still, video, digital, forward-looking infra-red, range, electronically stabilized platforms, etc.), communication equipment (i.e., computers, antennae, etc.), collision avoidance systems, or any other reasonable payload. In the illustrative example, the storage pod **106** is located at the nose of the aircraft. However, the storage pod may be located at another position in the VTOL aircraft **100**, such as in a wing, in a fuselage, at an aft end, etc.

[0030] In various embodiments, storage pod **106** may be encapsulated by a canopy. In such embodiments, the canopy may be made of a plastic material (e.g., high-density polyethylene, acrylic, melamine, polycarbonate, etc.), a glass material, or any other transparent material capable of withstanding a potential impact. The canopy may provide a weatherproof environment to protect the equipment in the storage pod **106**. In some embodiments, the storage pod

106 may be encapsulated by the aircraft skin, and may include a window for the camera, antennae, etc.

[0031] FIGS. 1A and 1B depict VTOL aircraft **100** configured for unmanned flight. In some embodiments, the VTOL aircraft **100** may include a cockpit. In such embodiments, the cockpit may include space for one or more passengers and/or other payload. The cockpit may include a cockpit canopy that provides a weatherproof and relatively quiet environment. The cockpit canopy may be formed of a plastic material, a glass material, or any other transparent material capable of withstanding a potential impact.

[0032] As illustrated in FIGS. 1A and 1B, VTOL aircraft **100** may include at least four motors **108**, two on the main wing and two on the vertical wing. In some embodiments, aircraft **100** may include more than two motors on the main wing and more than two motors on the vertical wing. In some embodiments, aircraft **100** may include fewer than two motors on the main wing and fewer than two motors on the vertical wing. In various embodiments, motors **108** may comprise electric motors. However, other propulsion systems are imagined, such as full combustion engines (e.g., gas turbine, jet engine, diesel engine, etc.), or hybrid engines (i.e., an engine used to convert liquid fuel to electrical energy to drive an electric motor and/or a fuel powered generator used to provide electrical power to the electric motors).

[0033] In various embodiments, motors **108** may be coupled to rotors **110** via a rotor shaft. In such embodiments, the motors **108** may produce power which is transmitted to rotors **110** via the rotor shaft in order to produce thrust for propulsion. The rotor shaft may be made of a metal material (e.g., aluminum, steel, stainless steel, titanium, alloys thereof, etc.), a plastic material (e.g., high-density polyethylene, acrylic, melamine, polycarbonate, etc.), a composite material (e.g., fiberglass, carbon fiber, etc.), and combinations of the foregoing, among others.

[0034] The rotors **110** may be made of a composite material, a wood material, a plastic material, a nylon material, a metallic material, or a combination thereof. In various embodiments, rotors **110** may be variable speed, fixed pitch rotors. In other embodiments, rotors **110** may be variable speed, variable pitch rotors. In yet other embodiments, rotors **110** may be fixed speed, variable pitch rotors. Additionally or alternatively, various embodiments may include one or more of the foregoing rotors used in combination with one or more of a different foregoing rotor, or other propulsion systems.

[0035] As discussed above, the rotors **110** may be variable pitch rotors. In such embodiments, the rotors **110** may reverse thrust to hover inverted and/or slow down rapidly during horizontal flight. Additionally, the rotors **110** may be set to a high angle of attack to increase flight speed in the horizontal flight configuration.

[0036] In the illustrative example, rotors **110** is coupled to motors **108** in a pull configuration. In other embodiments, rotors **110** may be coupled to motors **108** in a push configuration. In yet other embodiments, two rotors **110** may be coupled to each motor **108** in a push-pull configuration.

[0037] In various embodiments, the rotors **110** coupled to the motors **108** on the main wing **102** may rotate clockwise, while the rotors **110** coupled to the motors **108** on the vertical wing **104** may rotate counter-clockwise, or vice versa. In other embodiments, the rotors on either end of the main wing **102** may be counter rotating, such that one rotates

clockwise and the other rotates counter-clockwise. In such embodiments, the rotors **110** on either end of the vertical wing **104** may also be counter-rotating.

[0038] FIG. 1A depicts aircraft **100** in the hover mode. In the hover mode, each rotor **110** may spin at substantially the same speed and at substantially the same pitch in order to produce similar lift at each position of the rotors **110**. However, each rotor **110** may adjust pitch and/or speed independently of one another, based on signals from a control management system. The control management system, as depicted in FIG. 6, may comprise a computer system capable of receiving and processing signals from an operator (on board operator, remote operator, or both) and a plurality of sensors (e.g., accelerometers, gyroscopes, distance sensors, cameras, etc.). In some embodiments, the control management system may send output signals to each of the rotors **110**, directing each of the rotors **110** to increase and/or decrease speed and/or pitch as necessary to maintain the desired flight regime. In some embodiments, the control management system may send output signals to each motor **108**, directing the motors to turn on, turn off, idle, fold, feather, increase or decrease power. In some embodiments, the control management system may adjust and/or control the orientation of the VTOL aircraft **100** via the speed and/or pitch of the rotors **110** and/or via adjustments to the control surfaces (i.e., flaps, elevons, etc.).

[0039] In various embodiments, the components of the VTOL aircraft **100** may be manufactured via traditional manufacturing techniques. In some embodiments, the components may be manufactured by 3-D manufacturing techniques, injection molding, composite manufacturing, or any other method of manufacturing.

[0040] FIG. 1B shows the illustrative VTOL aircraft **100** in a forward flight mode. To transition from the hover mode as depicted in FIG. 1A to the forward flight mode depicted in FIG. 1B, an operator may send a signal and/or provide an input to the control management system indicating the desire to make the transition. In various embodiments, the control management system may then send a signal to the propulsion systems oriented along an axis to increase and/or decrease the speed and/or pitch of the opposing rotors. In the illustrative example, the control management system sends signals to the propulsion systems on the main wing **102** to effect a rotation about a lateral axis **112**. In various embodiments, the control management system may also send signals to the control surfaces to aid in and/or effect the rotation about the lateral axis **112**.

[0041] In some embodiments, the control management system may send signals to increase and/or decrease the rotor speed of the propulsion systems on the vertical wing **104** to affect a rotation about a longitudinal axis. In some embodiments, the transition may be effected by the control management system sending signals to increase and/or decrease the pitch of the rotors along the lateral axis **112** or the longitudinal axis **114**. In various embodiments, the control management system may also send signals to the control surfaces to aid in and/or effect the rotation about the lateral axis **112** or the longitudinal axis **114**.

[0042] While in the forward flight mode depicted in FIG. 1B, the aircraft may rotate about a centerline axis **116** by adjusting the speed and/or the pitch of opposing rotors along an axis. The rotation along the centerline axis **116** may enable the VTOL aircraft **100** to fly with the main

wing **102** as the primary lifting surface or with the vertical wing **104** as the primary lifting surface.

[0043] FIG. 2 is a schematic diagram showing an illustrative transition of flight of an illustrative VTOL aircraft from takeoff to a transitional mode to a forward flight mode.

[0044] At position **202**, the VTOL aircraft **100**, such as High Speed Multi-Rotor VTOL aircraft, may be in a grounded (i.e., landed) position. In the grounded position, the rotors, such as rotors **110**, may be spinning, with engines, such as engines **108**, in an idle position. In the grounded position, the rotors may produce little to no thrust. Additionally, in the grounded position, the rotors may produce a downward thrust to keep the VTOL aircraft **100** grounded and/or stable in certain situations, such as in strong or gusting winds.

[0045] At position **204**, the VTOL aircraft launches, departing from the landing surface and beginning the transition to the horizontal flight configuration. In the illustrative example, the rotors on the main wing may be stationary rotors and the rotors on the vertical wing may be transitioning rotors. In various embodiments, the stationary rotors may increase speed and/or pitch simultaneously at substantially the same rate to produce relatively equal thrust. The relatively equal thrust produced by the stationary rotors may provide a consistent thrust for takeoff, hover, climb, and to establish and maintain forward flight. The stationary rotors may also provide for roll control while in a hover, during the transition, or in forward flight.

[0046] Transitioning rotors may adjust speed and/or pitch to effect a transition from a vertical flight regime in which the VTOL aircraft is oriented substantially perpendicular to the horizon to a horizontal flight configuration in which the VTOL aircraft is oriented substantially parallel to the horizon. In some embodiments, the transition may be effected by a pitching motion about the longitudinal axis, such that the main wing becomes the primary lift generating surface in horizontal flight. In some embodiments, the transition may be effected by a rolling motion about the lateral axis, such that the vertical wing becomes the primary lift generating surface in horizontal flight.

[0047] In some embodiments, the transition may be effected by increasing the speed and/or pitch of one transitioning rotor. In some embodiments the transition may be effected by increasing the speed and/or pitch of one transitioning rotor, while simultaneously decreasing the speed and/or pitch of the opposite transitioning rotor.

[0048] In various embodiments, the VTOL aircraft may takeoff into a hover prior to beginning the transition to the vertical flight configuration. In such embodiments, the transitioning and stationary rotors may spin at substantially the same rate and/or pitch.

[0049] At position **206**, the VTOL aircraft continues through the transition to the horizontal flight regime. At this position, one transitioning rotor maintains a different rate and/or pitch than the other. As the VTOL aircraft progresses through the transition, the thrust generated by the stationary rotors transitions from a vertical thrust to a horizontal thrust. At position **206**, the vectors of vertical and horizontal thrust generated by the stationary rotors may be substantially equal.

[0050] At position **208**, the VTOL aircraft is close to completing the transition to the horizontal flight configuration. In various embodiments, the transitioning rotors may be set to relatively equivalent speeds and/or pitches, allowing the

momentum to carry the VTOL aircraft through last few degrees of transition. In some embodiments, the transitioning rotors may make adjustments to increase and/or decrease speed and/or pitch to effectively stop the pitching or rolling motion, and establish the VTOL aircraft in the horizontal flight configuration.

[0051] At position **210**, the VTOL aircraft has completed the transition to the horizontal flight configuration. At this position, the transitioning and stationary rotors may be set to substantially equivalent speed and/or pitch to maintain constant thrust in a direction substantially parallel to the horizon.

[0052] FIGS. 3A and 3B are side elevation views of an illustrative High Speed Multi-Rotor VTOL aircraft in forward flight mode. FIG. 3A shows the VTOL aircraft with main wing loading. FIG. 3B shows the VTOL aircraft with vertical wing loading.

[0053] VTOL aircraft **300**, like VTOL aircraft **100**, comprises a main wing **302** and a vertical wing **304**. The main wing **302** may have a larger, smaller, or identical wingspan as compared to the vertical wing **304**. In some embodiments, the main wing **302** and the vertical wing **304** may have identical symmetry and/or camber. In various embodiments, the main wing **302** and the vertical wing **304** may have different symmetry. For example, the main wing **302** may be a delta wing design, and the vertical wing **304** may be a high aspect ratio design.

[0054] In the illustrative example, main wing **302** and vertical wing **304** have thrust-producing rotors **306**, such as rotor **106**, mounted to the main wing **302** and the vertical wing **304**. As shown in FIG. 3, the rotors are pull-type rotors mounted to the leading edge of the wings. In some embodiments, the rotors **306** may be push-type rotors mounted to the trailing edge of the wings. In some embodiments, rotors **306** may be mounted to the leading edge and the trailing edge of the wings in a push-pull type configuration.

[0055] In the illustrative example, rotors **306** are mounted to the ends of each wing. However, the rotors **306** may be mounted at any position along the wing. In some embodiments, opposing rotors **306** on the same wing, such as rotors **306(1)** and **306(2)**, may be mounted equidistant from a centerline axis. In some embodiments, all rotors **306** may be mounted the same distance from the centerline axis.

[0056] In the illustrative example, each rotor **306** is coupled to a motor **308**. As shown in FIGS. 3A and 3B, the motor(s) **308** are coupled directly to the rotor(s) **306**, at the end of each wing. However, it is imagined that the rotor(s) **306** may be coupled to one or more motors located in a separate position. For example, one or more motor(s) **308** may be located inside the skin of the VTOL aircraft. In such an example, one motor **308** may drive one or more rotor(s) **306**.

[0057] In some embodiments, motor **308** may be an electric motor. In some embodiments, motor **308** may be a combustion engine or a hybrid engine. For example, motor **308** may be a jet engine, which may produce thrust. In such an example, the jet engine may replace the rotor **306**.

[0058] FIG. 3A depicts the VTOL aircraft **300** in the horizontal flight configuration, with the main wing **302** acting as the primary lift-generating source. In the horizontal flight configuration, rotors **306** driven by motors **308** may produce thrust in a direction substantially parallel to the horizon. In some embodiments, adjustments to the speed and/or pitch of each rotor may provide for pitch, roll, and yaw control of the

aircraft. For example, yaw control may be effected by adjusting the thrust of rotors **306(1)** and/or **306(2)**. In some embodiments, VTOL aircraft **300** may comprise flight control surfaces (e.g., ailerons, elevons, flaperons, rudders, etc.) to assist in the pitch, roll, and/or yaw control of the aircraft. **[0059]** In various embodiments, the VTOL aircraft **300** may transition from main wing loading orientation shown in FIG. 3A to vertical wing loading orientation shown in FIG. 3B. In some embodiments, the VTOL aircraft may transition by adjusting the speed and/or pitch of two or more rotors to effect a rolling motion about the centerline axis. In various embodiments, the VTOL aircraft may transition by adjusting the control surfaces. In some embodiments, the VTOL aircraft may transition by adjusting the speed and/or pitch of two or more rotors and by adjusting the control surfaces. The roll may be a 90 degrees roll clockwise or counter-clockwise. In some embodiments, flight control surfaces, such as ailerons may assist in the rolling motion to establish the aircraft in a vertical wing loading orientation. The vertical wing loading orientation may allow VTOL aircraft **300** to achieve higher speeds than the main wing loading orientation, due at least in part to reduced induced drag.

[0060] FIG. 4 is a top view of the illustrative High Speed Multi-Rotor VTOL aircraft shown in FIG. 1A. As depicted, the VTOL aircraft is in a vertical flight configuration.

[0061] The VTOL aircraft **400**, such as VTOL aircraft **100**, may comprise a main wing **402** and a vertical wing **404**. In the illustrative example, the main wing **402** may have a longer wingspan and a larger root than vertical wing **404**. In other examples, the main wing **402** may have the same wingspan and/or root as the vertical wing **404**.

[0062] VTOL aircraft **400** may have a plurality of rotors **406** coupled to and driven by at least one motor, such as motor **108**. The rotors **406** may be variable speed and/or variable pitch rotors. In the illustrative example, rotors **406(1)**, **406(2)**, **406(3)** and **406(4)** are the same size and shape. In some embodiments, rotors **406(1)** and **406(2)** may be of a different wingspan and/or shape than rotors **406(3)** and **406(4)**.

[0063] As illustrated in FIG. 4, rotors **406(1)** and **406(2)** are mounted on the main wing, and rotors **406(3)** and **406(4)** are mounted on the vertical wing. In various embodiments, rotors **406(1)** and **406(2)** may be mounted a distance X from the centerline axis, while rotors **406(3)** and **406(4)** may be mounted a distance Y from the centerline axis, where $X > Y$. In some embodiments, $X = Y$, such that each of the rotors **406** is mounted equidistant from the centerline axis. In various embodiments, it may be beneficial to mount each of the rotors **406** equidistant from the centerline axis. However, in other embodiments, it may be beneficial to mount the rotors **406** on opposing wings at different distances from the centerline axis.

[0064] In the illustrative example, the rotors **406(1)** and **406(2)** rotate counterclockwise, while the rotors **406(3)** and **406(4)** rotate clockwise. In other examples, the rotors **406(1)** and **406(2)** may rotate clockwise, and the rotors **406(3)** and **406(4)** may rotate counterclockwise. In still yet other examples, the rotors **406(1)** and **406(2)** may counter-rotate, such that one rotates clockwise and the other rotates counterclockwise, or vice versa. In such examples, the rotors **406(3)** and **406(4)** may also counter-rotate. In various embodiments, two rotors **406** may counter-rotate, and two rotors **406** may rotate in the same direction.

[0065] FIG. 5 is a top view of the illustrative High Speed Multi-Rotor VTOL aircraft in a horizontal flight configuration, with jet engines as the propulsion system. As depicted, the VTOL aircraft is in a horizontal flight configuration.

[0066] VTOL aircraft **500** may include a main wing **502** and a vertical wing **504**. In some embodiments, the vertical wing **504** may be offset 90 degrees from the main wing **502**. In some embodiments, the vertical wing **504** may be offset at an angle less than 90 degrees from the main wing **502**. In such examples, the offset angle may be between 80-90 degrees, between 60-80 degrees, or between 45-60 degrees.

[0067] The VTOL aircraft **500** may include a propulsion system. In the illustrative example, the propulsion system comprises four jet engines **506**. In other examples, the propulsion system may comprise one or more rotor systems coupled to and driven by an electric motor, a turbo propeller engine, a hybrid engine, or the like. Each jet engine **506** may generate thrust independently or in conjunction with one or more other jet engine **506**.

[0068] In various embodiments, VTOL aircraft **500** may takeoff into a vertical flight configuration by increasing the thrust generated by one or more of the jet engines **506**. VTOL aircraft **500** may transition from the vertical flight configuration to the horizontal flight configuration depicted in FIG. 5 by varying the thrust generated by one or more jet engines **506**. For example, the vertical wing of VTOL aircraft **500** may have a first and a second jet engine mounted at opposite ends. The VTOL aircraft **500** may transition by increasing the thrust generated by the first jet engine, while maintaining a constant thrust with the second jet engine. The VTOL aircraft **500** may transition by increasing the thrust generated by the first jet engine and decreasing the thrust generated by the second jet engine. In some embodiments, the VTOL aircraft **500** may transition by maintaining a constant thrust from the first jet engine, and decreasing the thrust generated by second jet engine. Additionally, the transition may facilitated by increasing and/or decreasing the thrust generated by a third and a fourth jet engine, the third and fourth jet engines being mounted on a different wing than the first and second jet engines (i.e., if the first and second jet engines may be mounted on the vertical wing, the third and fourth jet engines may be mounted on the main wing, or vice versa).

[0069] In various embodiments, jet engine **506** may comprise a thrust vectoring system **508**. In some embodiments, the thrust vectoring system **508** may be mounted in the exhaust of the jet engine **506**. In some embodiments, the thrust vectoring system **508** may be mounted outside the jet engine **506**. In various embodiments, the thrust vectoring system **508** may direct the flow of the exhaust generated by jet engine **506**, thereby adjusting the thrust vector. The thrust vectoring system **508** may provide increased stability and maneuvering while in the vertical and horizontal flight configurations.

[0070] In the illustrative example, thrust vectoring system **508** may include multiple vanes **510**, each of the vanes being adjustable together to direct the exhaust in a particular direction. In some embodiments, the thrust vectoring system **508** may comprise an adjustable nozzle which can direct the exhaust. In some embodiments the adjustable nozzle may be mounted on a gimbal in the exhaust.

[0071] The VTOL aircraft **500** may include landing gear **512** that is fixed or retractable. In the illustrative example,

the landing gear **512** is rigid-type landing gear. In various embodiments, the landing gear **512** may comprise a tire and/or a strut system.

[0072] FIG. 6 is a top view of the illustrative High Speed Multi-Rotor VTOL aircraft shown in FIG. 1A, showing various components that may be selectively included in the High Speed Multi-Rotor VTOL aircraft.

[0073] VTOL aircraft **600**, similar to VTOL aircraft **100**, may comprise a main wing and a vertical wing, with rotor systems mounted at the end of each of the main wing and the vertical wing. The rotor systems may be coupled to and driven by one or more motors powered by electricity.

[0074] In various embodiments, VTOL aircraft **600** may comprise solar panels **602** to provide electricity to power the motors. In such embodiments, the solar panels may be incorporated into the skin of the VTOL aircraft **600** (i.e., glued or painted on, manufactured with the skin), and/or mounted on the aircraft. In some embodiments, VTOL aircraft **600** may comprise an alternator, a wind turbine generator, or any other method for generating electricity. In such embodiments, VTOL aircraft **600** may comprise a turbine configured to spin in the ram air to generate electricity. In some embodiments, the VTOL aircraft **600** may utilize a disengaged spinning rotor to generate electricity. The electricity to power the motors may be stored in one or more batteries **604** inside VTOL aircraft **600**. The batteries **604** may be nickel-cadmium, lead-acid, zinc-bromine, lithium-ion, nickel hydrogen, or any other type of rechargeable battery.

[0075] In various embodiments, VTOL aircraft **600** may comprise a cockpit **606**. In some embodiments, cockpit **606** may include space for one or more passengers and/or other payload. The cockpit **606** may be made of a metal material, a plastic material, a glass material, or a combination thereof. The cockpit **606** may include a canopy that provides a weatherproof and relatively quiet environment. The canopy may be formed of acrylic, plastic, glass, or any other transparent material.

[0076] In various embodiments, the cockpit **606** may be mounted in a rotating assembly, thereby allowing the cockpit **606** to rotate about a cockpit axis **608** in a transition from the vertical flight configuration to the horizontal flight configuration. In some embodiments, the rotating assembly may allow cockpit **606** to rotate about the cockpit axis **608** and about a second axis to maintain an upright position of the cockpit **606** upon transition from main wing loading horizontal flight configuration to a vertical wing loading horizontal flight configuration.

[0077] In some embodiments, the cockpit **606** may be mounted on a gimbaled chassis and/or a pivoting chassis. Each of the rotating assembly, gimbaled chassis, and pivoting chassis may allow freedom of movement between a first position in the vertical flight configuration and a second position in the horizontal flight configuration. The first position may be 90 degrees offset from the second position. In some embodiments, the first position may allow the one or more passengers to sit upright in the VTOL aircraft during the vertical flight configuration. In some embodiments, the second position may allow the one or more passengers to sit upright in the VTOL aircraft during the horizontal flight configuration.

[0078] In various embodiments, the VTOL aircraft **600** may include one or more stability augmentation sensors **610** that monitor a position, angle, acceleration, and/or

orientation of a portion of the VTOL aircraft. For example, the stability augmentation sensors **610** may comprise gyroscopes and/or accelerometers that monitor the pitch, roll, and yaw of the VTOL aircraft **600**, and changes of each over time. The stability augmentation sensors **610** may provide input via signals to a control management system **612**. [0079] The control management system **612** may comprise a computer system with one or more processor(s) **614**, one or more memories **616**, an operating system **618**, control logic **620**, and/or one or more parameters **622**. The control management system **612** may process the signals from the stability augmentation sensors **610**, input from an operator (pilot) via operator controls, and/or input stored in the one or more memories **616** to determine how to direct and power the rotors to maintain flight in the vertical flight mode, the transition mode **204-206**, and the forward-flight mode **210**.

[0080] For example, the stability augmentation sensors **610** may detect a sudden tilt of the aircraft due to a gust of wind or other force exerted on the VTOL aircraft **600**. In response, the stability augmentation sensors **610** may transmit a signal to the control management system **612**. The control management system **612** may cause an increase or decrease in thrust generated by one or more rotors to cancel the exerted force, and thus stabilize flight of the VTOL aircraft **600**. Meanwhile, the control management system **612** may also process commands from the operator. The control management system **612** may prioritize control input from the stability augmentation sensors **610** and the operator to maintain stable flight. For example, when an operator provides a command that may compromise sustained flight, the control management system **612** may ignore the command and/or only execute the command for a limited duration before issuing another command (possibly in response to a signal from the stability augmentation sensors **610**) to take action to sustain flight.

[0081] The operator, using flight controls, sends input signals to the control management system **612**. In turn, the control management system **612** receives the signals from the flight controls and/or the stability augmentation sensors **610**. The control management system **612** prioritizes the inputs from the stability augmentation sensors **610** and inputs from the operator and then adjusts a thrust and/or direction/orientation of the thrust generated by each rotor.

[0082] The control management system **612** may adjust the orientation and/or control of the VTOL aircraft **600** semi-autonomously and/or fully autonomously. In semi-autonomous flight, operation of the aircraft may be performed by providing simple directional commands from operator controls to the control management system **612**, as well as input from the stability augmentation sensors **610**. In the semi-autonomous mode, the inputs may mixed, and the control management system **612** may apply the proper signals to the rotors and/or control surfaces to effect the desired flight configuration and/or orientation.

[0083] In fully autonomous flight, the VTOL aircraft **600** may have a flight plan loaded into the control management system, the flight plan directing the configuration and/or navigation of the VTOL aircraft **600**. Additionally, the VTOL aircraft **600** may be capable of fully autonomous flight in an emergency situation. For example, if an operator becomes incapacitated, the VTOL aircraft **600** may be configured for an automatic recovery function in which the aircraft may establish a hover and land in the vertical flight

configuration without input from an operator. For another example, the VTOL aircraft **600** may enable the automatic recovery function upon lost contact with a remote operator. **[0084]** FIG. 7 is a side view of an illustrative manned High Speed Multi-Rotor VTOL aircraft with pusher-type rotors. FIG. 7 depicts the VTOL aircraft in a landed position.

[0085] VTOL aircraft **700** may comprise a monocoque structure, made of carbon fiber and/or other composite material, titanium, aluminum, or any other material appropriate for aircraft construction. In another embodiment, the structure may comprise a semi-monocoque design, with a shell and longerons made of carbon fiber, titanium, aluminum, or any other material appropriate for aircraft construction. The aircraft skin is a low friction surface that may include built-in solar cells.

[0086] In various embodiments, VTOL aircraft **700** may comprise a fuselage **702**, a main wing **704**, and a vertical wing **706**. The fuselage **702** may include a cockpit **708** configured to hold one or more passengers and/or other payload. In some embodiments, the cockpit **708** may be mounted on a rotating assembly, a gimbaled and/or a pivoting chassis, thereby allowing movement about its own axis. In the illustrative example, the passengers in the cockpit **708** are seated in a first position, the first position being substantially upright while the aircraft is in the landed position. The cockpit **708** may remain this position while in the vertical flight configuration. However, when the VTOL aircraft **700** transitions to forward flight, such as through positions **204-210**, the cockpit may rotate about its axis to a second position, wherein the first and the second positions are substantially similar in that the passengers remain in the substantially upright position in the horizontal flight configuration.

[0087] In some embodiments, the cockpit **708** may be mounted in the fuselage **702**. In some embodiments, the cockpit **708** may be mounted in the main wing **704** and/or vertical wing **706**.

[0088] In various embodiments, motors **710** may be mounted in the main wing **704** and the vertical wing **706**. In the illustrative example, motors **710** are each mounted equidistant from a centerline axis. The motors **710** may be electrically driven, gas driven, or a hybrid of electric and gas.

[0089] The motors **712** may be coupled to and may drive rotors **712**. In the illustrative example, rotors **712** are pusher-type rotors. In other examples, the rotors **712** may be pull-type rotors.

[0090] VTOL aircraft **700** may include flight control surfaces **714**, such as ailerons, flaperons, elevons, rudders, etc. The flight control surfaces **714** may facilitate pitch, roll, and/or yaw control of the aircraft.

[0091] VTOL aircraft **700** may also include landing gear **716**. The landing gear **716** may be fixed or retractable. As illustrated in FIG. 7, the landing gear **716** may be a rigid pole-type landing system. In various embodiments, the pole-type landing system may be telescopic, thereby allowing it to retract. In some embodiments, the rigid pole-type landing system may include a skid as a landing surface. In some embodiments, the landing gear **716** may comprise a strut and tire system.

[0092] In various embodiments with retractable landing gear, the landing gear **716** may comprise a backup system to deploy the gear in an emergency situation. For example, if power is lost to the landing gear system, a hydraulic system may provide the force enough to deploy the landing gear

716. In some embodiments, the VTOL aircraft **700** may comprise an emergency parachute system, deploying a parachute to allow for recovery of the aircraft in an emergency, such as a total power loss. In such embodiments, the emergency parachute system may work in conjunction with the landing gear, thereby providing a stable landing platform after a descent controlled by the parachute.

[0093] FIG. 8 depicts the unmanned version of the illustrative High Speed Multi-Rotor VTOL aircraft shown in FIG. 7 while in the vertical and horizontal flight configurations. FIG. 8A is a vertical view of the VTOL aircraft in the vertical flight configuration. FIG. 8B is a vertical view of the VTOL aircraft in the horizontal flight configuration with main wing-loading. FIG. 8C is a vertical view of the VTOL aircraft in the horizontal flight configuration with vertical wing-loading.

[0094] As previously discussed, VTOL aircraft **800** may comprise a main wing, and a vertical wing. A propulsion system of VTOL aircraft **800** may comprise four rotors, such as rotors **712**, coupled to and driven by four motors, such as motor **710**. As illustrated in FIGS. 8A-8C, two of the motors are mounted on the main wing and two of the motors are mounted on the vertical wing.

[0095] In the illustrative example, each of the rotors are mounted equidistant from a centerline axis. In other examples, the rotors on the main wing may be mounted a different distance from the centerline axis than the rotors on the main wing, such as shown in FIG. 4. The rotors may be push or pull type rotors. The rotors may be variable speed and/or variable pitch rotors.

[0096] FIG. 8A is a vertical view of the VTOL aircraft **800** in the vertical flight configuration. In the vertical flight configuration, each of the rotors may produce substantially the same thrust, so as to lift the VTOL aircraft **800** in a direction perpendicular to the horizon. However, each of the motors and rotors may act independently of the others.

[0097] A flight control management system may receive signals from the plurality of stability augmentation sensors, and may adjust the thrust produced by each rotor in order to maintain stability. In various embodiments, the flight control management system may also receive signals from an operator, such as a signal to transition from the vertical flight configuration to the horizontal flight configuration depicted in FIGS. 8B and 8C.

[0098] VTOL aircraft **800** may in the horizontal flight configuration with main wing loading and/or vertical wing loading. FIG. 8B shows the VTOL aircraft **800** with main wing loading, while FIG. 8C shows the VTOL aircraft **800** with vertical wing loading. The VTOL aircraft may transition between main wing and vertical wing loading, by rotating the aircraft 90 degrees about the centerline axis. The vertical wing loading may allow for higher velocities.

[0099] FIG. 9 is a side view of the illustrative High Speed Multi-Rotor VTOL aircraft shown in FIG. 8 in the vertical flight configuration. FIG. 9 depicts the VTOL aircraft hovering in a nose-down configuration.

[0100] In the horizontal flight configuration, VTOL aircraft **800** may rotate about the lateral and/or longitudinal axes 180 degrees to effect a nose-down hover. In various embodiments, the rotors may adjust pitch to switch from a push-type rotor to a pull-type rotor.

[0101] VTOL aircraft **800** may include storage pod **902**, such as storage pod **106**, at the nose of the aircraft. In such embodiments, the storage pod **902** may be used to house

cameras, communication equipment, collision avoidance systems, electronically stabilized platforms, or any other reasonable payload. In various embodiments, storage pod **902** may be encapsulated by a canopy. In such embodiments, the canopy may be made of a plastic material, a glass material, or any other transparent material capable of withstanding a potential impact. The canopy may provide a weatherproof environment to protect the equipment in the storage pod **902**. In some embodiments, the storage pod **902** may be encapsulated by the same material as the aircraft skin. In such embodiments, the storage pod **902** may include one or more windows.

[0102] FIG. **10** is a schematic diagram showing a transition of flight of the illustrative High Speed Multi-Rotor VTOL aircraft shown in FIG. **1** from the horizontal flight mode to a transitional mode to landing.

[0103] At position **1002**, the VTOL aircraft **100** is established in the horizontal flight configuration. In the horizontal flight configuration, each of the rotors may produce substantially equivalent thrust. The VTOL aircraft **100** may fly with main wing loading or vertical wing loading, and may transition between the two while in flight. As depicted, the VTOL aircraft **100** is in the horizontal flight configuration with vertical wing loading. Thus, the rotors on the main wing are the transitioning rotors and the rotors on the vertical wing are the stationary rotors. However, the VTOL aircraft is not limited to this configuration, and the transition to land may be made from the main wing loading configuration. From the main wing loading configuration, the rotors on the vertical wing are the transitioning rotors and the rotors on the main wing are the stationary rotors.

[0104] At position **1004**, the VTOL aircraft adjusts speed and/or pitch of the transitioning rotors. In various embodiments, one transitioning rotor may increase thrust while the opposing transitioning rotor may decrease thrust to effect a rotation about a lateral or longitudinal axis. In some embodiments, one of the transitioning rotors may increase or decrease thrust to effect the rotation about the lateral or longitudinal axes.

[0105] The stationary rotors may maintain, increase, or decrease thrust as necessary to maintain the desired flight path. Each of the stationary rotors may generate substantially the same amount of thrust, thereby maintaining a stable heading.

[0106] At position **1006**, the VTOL aircraft continues through the transition mode, with the horizontal and vertical thrust vectors produced by the stationary rotors being substantially equivalent. In this position, if a transition to a high hover is desired, the stationary rotors may increase thrust to maintain altitude. However, the VTOL aircraft is not limited to a high hover. In some embodiments, the VTOL aircraft may transition to land on a glideslope, such as in a no-hover landing.

[0107] At position **1008**, the VTOL aircraft is in a vertical configuration. The VTOL aircraft may stabilize in this position, or the horizontal momentum may carry the aircraft through position **1008** to position **1010** before stabilizing back in the vertical configuration at position **1012**. In some embodiments, the VTOL aircraft may be positioned to cancel out the horizontal momentum, such as in position **1010**, using reverse thrust to decelerate down to, but not past, zero horizontal speed.

[0108] The VTOL aircraft fly vertically from position **1012** to a landing at position **1014**. While flying vertically,

each of the rotors may produce substantially the same thrust. The control management system may adjust the thrust produced by each of the rotors independently to maintain stability in vertical flight. In various embodiments, the landing may be flown by the control management system and/or an operator. From position **1012** to position **1014**, the thrust produced by the rotors may decrease to an idle position at position **1014**, in which the rotors produce little to no thrust. At position **1014**, the VTOL aircraft **100** rests on landing gear, such as landing gear **512**.

[0109] FIGS. **11A-11C** are various views of an illustrative foldable rotor. FIG. **11A** is a perspective view of an illustrative High Speed Multi-Rotor VTOL aircraft in forward flight, with two rotors folded and two rotors extended. FIG. **11B** is perspective view of the foldable rotor in the extended position. FIG. **11C** is a perspective view of a foldable rotor in a folded position.

[0110] While in the horizontal flight configuration, VTOL aircraft **1100** may disengage one or more rotors. Various embodiments contemplate that this may help to save electricity and/or fuel. In the illustrative example, the engaged rotors **1102** may continue to spin, thereby producing thrust for VTOL aircraft **1100**, and the disengaged rotors **1104** may fold backward toward an aft end of the aircraft. In such examples, the control management system may adjust control surfaces in order to control the VTOL aircraft **1100**. In some embodiments, the disengaged rotors **1104** may be locked in the folded position. In some embodiments, the disengaged rotors **1104** may be free to spin in the folded position.

[0111] As shown in FIG. **11A**, VTOL aircraft **1100** may have two rotors disengaged, and two rotors engaged. However, other combinations of engaged and disengaged rotors are imagined. For example, VTOL aircraft **1100** may have one rotor disengaged and the remaining rotors engaged. For another example, VTOL aircraft **1100** may have one rotor engaged, and the remaining rotors disengaged.

[0112] In various embodiments, the one or more disengaged rotors may be free to spin in a feathered position. In the feathered position, the disengaged rotors may produce minimal amount of drag. In some embodiments, the rotors may produce electricity to charge one or more batteries when they spin in the feathered position.

[0113] As depicted in FIG. **11A**, the VTOL aircraft **1100** is flying in a main wing loading horizontal flight configuration. As such, the engaged rotors **1102** are the rotors mounted on the main wing, and the disengaged rotors **1104** are the rotors mounted on the vertical wing. However, the VTOL aircraft **1100** may fly in the vertical wing loading horizontal flight configuration, with the rotors on the vertical wing engaged and the rotors on the main wing disengaged.

[0114] VTOL aircraft **1100** may fold and unfold the rotors while in flight, in the horizontal flight configuration. FIG. **11B** shows a rotor, such as **1102** and **1104**, in the unfolded position. FIG. **11C** shows a rotor, such as **1102** and **1104**, in the folded position. The rotor system may include a locking mechanism (i.e., a locking pin) which may secure rotor **1104** in the folded position depicted in FIG. **11C**. The rotor system may also include an emergency system to destroy the locking mechanism in case of an emergency. The emergency system may include a shearing system, a localized explosive charge, etc.

[0115] FIGS. **12A-12B** are perspective views of a variable pitch rotor. In various embodiments, the rotors, such as rotor

110, may be variable pitch. As discussed above with respect to FIG. 9, the rotors may adjust pitch to change from a push-type rotor to a pull-type rotor.

[0116] In various embodiments the rotors **1202** and **1204** may move in the equivalent but opposite directions. In some embodiments, the rotors **1202** and **1204** may move independently of one another. Each rotor **1202** and **1204** may be free to rotate 360 degrees about its own axis.

[0117] FIGS. 13A-13D are isometric views of an illustrative rotating assembly **1300** that moveably couples a rotor unit to the fuselage **102** of the illustrative VTOL aircraft **700**.

[0118] FIG. 13A shows the illustrative rotating assembly **1300** including a cockpit **1302**. The cockpit **1302** is mounted in a rotating chassis **1304**, which allows rotation about its lateral and longitudinal axis. The rotating chassis **1304** may include a pivot joint **1108**, which holds the cockpit **1302** in place. The pivot joint **1308** may include a locking mechanism to lock cockpit **1302** in one position. The dashed line depicts the cockpit in the transition mode **204-208**.

[0119] As illustrated in FIG. 13B, the rotating assembly may include a second pivot joint **1312**, which may allow rotation about the longitudinal axis of the cockpit **1302**. The rotation about the longitudinal axis may be desired during a transition from a main wing loading horizontal flight configuration to a vertical wing loading horizontal flight configuration, in which case, the cockpit **1302** may rotate about the longitudinal axis to maintain an upright position.

[0120] FIG. 13C shows the illustrative rotating assembly **1300** with an outer frame **1314** supporting the cockpit **1302**. The outer frame **1314** and the cockpit **1302** are rotatable with respect to each other about the lateral axis, as shown in FIG. 13D. The fuselage, the main wing, and/or the vertical wing of the VTOL aircraft **700** may provide the outer frame **1314**, or the outer frame **1314** may be coupled to the fuselage, the main wing, and/or the vertical wing. In some embodiments, the rotating chassis may be a gimbaled chassis and/or a pivoting chassis.

[0121] FIG. 14 is a flow diagram showing a transition from takeoff, through a transition mode, to a forward flight mode.

[0122] At block **1402**, the VTOL aircraft rotates a first variable speed rotor and a second variable speed rotor. The first and the second variable speed rotors may rotate at substantially the same speed. However, the first and the second variable speed rotors may rotate independently of one another.

[0123] At block **1404**, the VTOL aircraft rotates a third variable speed rotor and a fourth variable speed rotor. The third variable speed rotors may rotate at substantially the same speed as the fourth variable speed rotor. However, the third and the fourth variable speed rotors may rotate independently of one another, and independently of the first and the second variable speed rotors. In some embodiments, the third and the fourth variable speed rotors may rotate at substantially the same speed as the first and second variable speed rotors. In some embodiments, the third and the fourth variable speed rotors may rotate at a different speed than the first and the second variable speed rotor.

[0124] Prior to takeoff, the first, second, third and fourth variable speed rotors may rotate at a speed to produce minimal thrust (i.e., not enough thrust to overcome the weight of the VTOL aircraft). In various embodiments, at least two of the first, second, third, and fourth variable speed rotors may

be configured to produce downward thrust to keep the aircraft grounded and/or stable.

[0125] At block **1406**, the VTOL aircraft may increase the speed of the first, second, third, and fourth variable speed rotors to induce a hover. The speed of the rotors may be sufficient to provide thrust to overcome the weight of the VTOL aircraft. While in a hover, the first, second, third, and fourth variable speed rotors may rotate at substantially the same speed. The speed of each of the first, second, third, and fourth variable speed rotors may be adjusted by the control management system to maintain a stable hover with little to no horizontal movement.

[0126] At block **1408** the control management system may adjust the speed of at least one variable speed rotor to effect a transition to forward flight. In some embodiments, the control management system may increase or decrease the speed of one variable speed rotor to effect a roll about the lateral or longitudinal axis of the VTOL aircraft. In some embodiments, the control management system may increase the speed of one rotor while decreasing the speed of the opposite rotor on the same wing to effect a roll about the lateral or longitudinal axis. For example, the third variable speed rotor may increase rotation speed while the fourth variable speed rotor may decrease rotation speed, thereby effecting the transition.

[0127] At block **1410**, the control management system may adjust the speed of the at least one variable speed rotor from block **1408** to substantially the same speed as the other variable speed rotors. In some embodiments, the rotor opposite the at least one variable speed rotor adjusted in block **1408** may rotate at a speed necessary to counter the rotation of the VTOL aircraft about the longitudinal or lateral axis.

[0128] At block **1412**, the VTOL aircraft may stabilize in the forward flight mode, with the first, second, third and fourth variable speed rotors rotating at substantially the same speed and producing thrust substantially parallel with the horizon.

[0129] FIG. 15 is an illustrative environment in which the VTOL aircraft, such as VTOL aircraft **100** may operate.

[0130] As illustrated in FIG. 15, the VTOL aircraft **1502** may communicate with an operator **1504** via one or more networks **1506**. The network may be controlled by one or more servers, such as server **1508**. The network **1506** can include public networks such as the Internet, private networks such as an institutional and/or personal intranet, or some combination of private and public networks. Network(s) **1506** can also include any type of wired and/or wireless network, including but not limited to local area networks (LANs), wide area networks (WANs), personal area networks (PANs), near field communications (NFC), cable networks, Wi-Fi networks, WiMax networks, mobile communication networks (e.g., 3G, 4G, and so forth), or any combination thereof.

[0131] Communication between the operator **1504** and the VTOL aircraft **1502** may be possible via a wired or a wireless signal, including but not limited to, Bluetooth, radio control, voice control, electromagnetic waves, Wi-Fi signals, cell phone signals, or some combination thereof. Operator **1504** may send the signals via network **1506** to a control management system, such as control management system **612**. Upon receiving the signals, control management system may adjust the propulsion system and/or flight

controls as necessary to reflect the desire of the operator 1504.

Conclusion

[0132] Although the subject matter has been described in language specific to structural features and/or methodological acts, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the specific features or acts described. Rather, the specific features and acts are disclosed as illustrative forms of implementing the claims.

What is claimed is:

1. A vertical take-off and landing (VTOL) aircraft comprising:

a plurality of wings ;

a plurality of propulsion systems coupled to the plurality of wings, the plurality of propulsion systems configured to produce vertical lift while the aircraft is in the hover regime, longitudinal thrust when the aircraft is in the forward flight regime, thrust vectoring, and thrust control ; and

a control management system configured to direct the thrust control to adjust the orientation of the aircraft.

2. The aircraft as claim 1 recites, at least one of the plurality of propulsion systems comprising:

a power system; and

a rotor coupled to the power system, the rotor being a variable speed rotor.

3. The aircraft as claim 2 recites, wherein the power system comprises:

an electric motor; and

a power source to provide power to the electric motor.

4. The aircraft as claim 3 recites, wherein the power source comprises at least one of:

a battery;

a solar panel;

a fuel cell; or

a wind turbine generator.

5. The aircraft as claim 2 recites, wherein the power system comprises one of a combustion engine or a hybrid engine.

6. The aircraft as claim 2 recites, wherein the aircraft is configured to transition between the hover and the forward flight regime by adjusting a speed of at least one of the variable speed rotors of the plurality of propulsion systems.

7. The aircraft as claim 2 recites, wherein the rotor is a variable pitch rotor.

8. The aircraft as claim 7 recites, wherein the aircraft is configured to transition between the hover and the forward flight regime by adjusting a pitch of at least one of the variable pitch rotors.

9. The aircraft as claim 1 recites, wherein the thrust control from the plurality of propulsion systems adjusts at least one of the pitch, roll, and yaw of the aircraft.

10. The aircraft as claim 1 recites, wherein the plurality of wings includes a first wing and a second wing, the second wing being coupled to the first wing at a 90-degree angle, wherein the second wing has a smaller wingspan than the first wing, the aircraft being configured to fly:

with the first wing producing lift in the forward flight regime; or

with the second wing producing lift in the forward flight regime.

11. The aircraft as claim 1 recites, further comprising at least one of:

an elevon; and

a rudder;

wherein the control management system is further configured to adjust the at least one elevon and the at least one rudder.

12. The aircraft as claim 1 recites, the control management system further comprising one or more of:

an accelerometer;

a gyro;

a magnetometer;

a GPS receiver; or

an optical sensor, wherein the accelerometer, the gyro, the magnetometer, the GPS receiver, and the optical sensor provide input to the control management system to allow autonomous flight.

13. The aircraft as claim 1 recites, wherein the plurality of propulsion systems further comprise:

a first propulsion system;

a second propulsion system;

a third propulsion system coupled to the plurality of wings; and

a fourth propulsion system coupled to the plurality of wings;

wherein the first, second, third, and fourth propulsion systems each comprises an engine and at least one rotor, and each of the first, second, third and fourth propulsion systems being configured to operate independently.

14. The aircraft as claim 13 recites, wherein the rotors of the first, second, third, and fourth propulsion systems are pusher-type rotors.

15. The aircraft as claim 1 recites, further comprising a passenger compartment configured to hold at least one person.

16. The aircraft as claim 1 recites, further comprising a storage pod, the storage pod housing at least one camera configured to transmit imagery to at least an operator of the aircraft.

17. A method for flying a vertical takeoff and landing (VTOL) aircraft comprising:

independently rotating a first plurality of variable speed rotors, the first plurality of variable speed rotors coupled to a main wing;

independently rotating a second plurality of variable speed rotors, the second plurality of variable speed rotors coupled to a vertical wing;

inducing a hover mode by rotating the first and second plurality of variable speed rotors at a rate sufficient to create lift to overcome a weight of the aircraft;

transitioning from the hover mode to a forward flight mode by adjusting the speed of at least the second plurality of variable speed rotors;

and upon approaching the forward flight mode, adjusting the speed of at least of the second plurality of variable speed rotors to substantially match the speed of the first plurality of variable speed rotors.

18. The method as claim 17 recites, further comprising: transitioning from the forward flight mode to the hover mode by adjusting the speed of at least one of the second plurality of speed rotors; and

landing the aircraft by reducing the speed of the first and second plurality of variable speed rotors when the aircraft is in the hover mode.

19. The method as claim 17 recites, further comprising: inducing a yaw motion by varying the speed of at least one of the first plurality of variable speed rotors; and

inducing a pitch motion by varying the speed of at least one
of the second plurality of variable speed rotors.

20. (canceled)

* * * * *