US 20230409179A1

(19) **United States**

(12) **Patent Application Publication**

LIANG et al.

(10) **Pub. No.: US 2023/0409179 A1**

(43) **Pub. Date: Dec. 21, 2023**

(54) **HOME AUTOMATION DEVICE CONTROL AND DESIGNATION**

(71) Applicant: **Apple Inc.**, Cupertino, CA (US)

(72) Inventors: **Eddy Zexin LIANG**, Seattle, WA (US); **Xinze WANG**, Sunnyvale, CA (US); **Madhu CHINTHAKUNTA**, Saratoga, CA (US); **William CARUSO**, Saratoga, CA (US)

(21) Appl. No.: **17/951,851**

(22) Filed: **Sep. 23, 2022**

Related U.S. Application Data

(60) Provisional application No. 63/352,548, filed on Jun. 15, 2022.

Publication Classification

(51) **Int. Cl.**

G06F 3/04847	(2006.01)
G06F 3/04815	(2006.01)
G06F 3/0482	(2006.01)
G06F 3/01	(2006.01)
G06F 9/451	(2006.01)
G05B 15/02	(2006.01)

(52) **U.S. Cl.**

CPC ***G06F 3/04847*** (2013.01); ***G06F 3/04815*** (2013.01); ***G06F 3/0482*** (2013.01); ***G06F 3/017*** (2013.01); ***G06F 3/013*** (2013.01); ***G06F 9/453*** (2018.02); ***G05B 15/02*** (2013.01); *G06F 3/165* (2013.01)

(57) **ABSTRACT**

Systems and processes for operating an intelligent automated digital assistant on an electronic device are provided. In particular, this paper describes how the intelligent automated digital assistant can be leveraged with other types of commands to control a household having multiple home automation devices. A portable electronic device is used to provide a user an extended reality environment within which the user can both manage and control the home automation devices.




System
100
Server System
108
Digital Assistant Server
106
Processing Modules
114
Data & Models
116
I/O Interface to External Services
118
I/O Interface to DA Client
112
Network(s)
110
External Services
120
Navigation Service(s)
Messaging Service(s)
Information Service(s)
Calendar Service
Telephony Service
122
DA
102
104

FIG. 1


Memory 202
Operating System
226
Communication Module
228
Contact/Motion Module
230
Graphics Module
232
Haptic Feedback Module
233
Text Input Module
234
GPS Module
235
Digital Assistant Client Module
229
User Data and Models
231
Applications
236
Contacts Module
237
Telephone Module
238
Video Conference Module
239
E-mail Client Module
240
Instant Messaging Module
241
Workout Support Module
242
Camera Module
243
Image Management Module
244
Video & Music Player Module
252
Notes Module
253
Portable Multifunction Device 200
Applications (continued)
236
Map Module
254
Browser Module
247
Calendar Module
248
Widget Modules
249
Weather Widget(s)
249-1
Stocks Widget
249-2
Calculator Widget
249-3
Alarm Clock Widget
249-4
Dictionary Widget
249-5
User-Created Widget(s)
249-6
Widget Creator Module
250
Search Module
251
Online Video Module
255
Device/Global Internal State
257
Power System
262
External Port
224
RF Circuitry 208
Speaker 211
Audio Circuitry 210
Microphone 213
Proximity Sensor
266
Accelerometer(s) 268
Peripherals Interface
Controller
Processor(s)
204
222
220
218
203
206
I/O Subsystem
Display Controller 256
Optical Sensor(s) Controller 258
Intensity Sensor(s) Controller 259
Haptic Feedback Controller 261
Other Input Controller(s) 260
Touch-Sensitive Display System 212
Optical Sensor(s) 264
Contact Intensity Sensor(s) 265
Tactile Output Generator(s) 267
Other Input Control Devices 216

FIG. 2A


Event Sorter
270
Event Monitor
271
Hit View Determination Module
272
Active Event Recognizer Determination Module
273
Event Dispatcher Module
274
Application 236-1
Application
Application View 291
...
Application View 291
Event Handler 290
Data Updater 276
Object Updater 277
GUI Updater 278
...
Event Handler 290
...
Application Internal State 292
Event Recognizer 280
...
Event Recognizer 280
Event Data 279
Event Recognizer
280
Event Receiver
282
Event Comparator
284
Event Definitions
286
Event 1
287-1
Event 2
287-2
...
Metadata
283
Event Delivery
288

FIG. 2B


Portable Multifunction Device 200
306
310
312
308
Speaker 211
Optical Sensor 264
Proximity Sensor 266
300
310 is SIM card slot
312 is headphone jack
308
302
Touch Screen 212
Contact Intensity Sensor(s) 265
Tactile Output Generator(s) 267
303
Microphone 213
Home 304
Accelerometer(s) 268
External Port 224

FIG. 3


Device 400
410
CPU(s)
420
430
I/O Interface
Display
440
Keyboard/Mouse
450
Touchpad
455
Tactile Output Generator(s)
457
Sensor(s)
459
460
Network Communications Interface
Memory 470
Operating System
226
Communication Module
228
Contact/Motion Module
230
Graphics Module
232
Haptic Feedback Module
233
Text Input Module
234
Digital Assistant Client Module
229
User Data and Models
231
Applications
236
Contacts Module
237
Telephone Module
238
Video Conference Module
239
E-mail Client Module
240
Instant Messaging Module
241
Workout Support Module
242
Camera Module
243
Image Management Module
244
Browser Module
247
Calendar Module
248
Widget Modules
249
Weather Widget
249-1
Stocks Widget
249-2
Calculator Widget
249-3
Alarm Clock Widget
249-4
Dictionary Widget
249-5
User-Created Widget(s)
249-6
Widget Creator Module
250
Search Module
251
Video & Music Player Module
252
Drawing Module
480
Presentation Module
482
Word Processing Module
484
Website Creation Module
486
Disk Authoring Module
488
Spreadsheet Module
490
Device/Global Internal State
257

FIG. 4


Portable Multifunction Device
200
306
308
500
Speaker 211
Optical Sensor 264
Proximity Sensor 266
505
502
Current Time 504
506
Messages 524
Tuesday 30
Calendar 526
Photos 528
Camera 530
Online Video 532
Stocks 534
Maps 536
Weather 538
Clock 540
Workout Support 542
Notes 544
Settings 546
App Store
iTunes
Voice Memos
Utilities
514
510
4
6
Phone 516
Mail 518
Browser 520
iPod 522
508
Touch Screen 212
Microphone 213
Accelerometer(s) 268
304

FIG. 5A


550
568
570
553


551
560
562
Tactile Output Generator(s) 457
Contact Intensity Sensor(s) 459
552

FIG. 5B



FIG. 6A


600
604
DISPLAY
622
TOUCH
624
INTENSITY
606
608
INPUT
610
COMMUNICATION
614
I/O
616
PROCESSOR(S)
618
MEMORY
612
BUS
630
632
GPS SENSOR
634
ACCELEROMETER
636
GYROSCOPE
638
MOTION SENSOR
640
DIRECTIONAL SENSOR

FIG. 6B


Digital Assistant System
700
Memory 702
Operating System
718
Communication Module
720
User Interface Module
722
Applications
724
Digital Assistant Module
726
I/O Processing Module
728
STT Processing Module
730
ASR Systems
758
Natural Language Processing Module
732
Ontology
760
Vocabulary
744
User Data
748
Dialogue Flow Processing Module
734
Task Flow Processing Module
736
Task Flow Models
754
Service Processing Module
738
Service Models
756
Speech Synthesis Processing Module
740
704
Processor(s)
710
706
I/O Interface
I/O Devices
716
708
Network Communications Interface
712
Wired Communications Port
714
Wireless Circuitry

FIG. 7A


Digital Assistant
728
Speech
Text String
I/O Processing Module
Speech Input
Text String
726
730
STT Processing Module
731
Phonetic Alphabet Conversion Module
Phonetic Representation
744
Vocabulary
748
User Data
Context
Text Representations
732
Natural Language Processing Module
760
Ontology
Structured Queries
736
Task Flow Processing Module
754
Task Flow Models
738
Service Processing Module
756
Service Models
734
Dialogue Flow Processing Module
740
Speech Synthesis Processing Module
Follow-Up
Responses
Delayed Responses

FIG. 7B


760
762
764
Restaurant Reservation Domain
Restaurant
Party Size
Date/Time
Cuisine
Price Range
Location
Phone#
Restaurant Reservation Domain
Set Reminder
Subject
Reminder Domain

FIG. 7C


800
Light 1
808
Light 2
810
Speaker 2
812
804
814
802
806

FIG. 8A


Light 1
808
Light 2
810
Speaker 2
812
802
814
806

FIG. 8B


Light 2
810
Speaker 2
812
802
814
806
Light 1
808

FIG. 8C


Light 2
810
Speaker 2
812
802
814
806
Desk Lamp
808

FIG. 8D


900
Light 2
810
Speaker 2
812
804
902
802
806
Desk Lamp
808

FIG. 9A


Light 2
810
Speaker 2
812
902
804
806
Desk Lamp
808

FIG. 9B


Light 2
810
804
902
812
Speaker 2
802
Desk Lamp
808

FIG. 9C


Light 2
810
804
902
812
Office Speaker
802
Desk Lamp
808

FIG. 9D



FIG. 10A



FIG. 10B



FIG. 10C



FIG. 10D


1100
1102
1118
1120
1106
1108
1104
1122
1116
1124
1112
1114
1110
1124

FIG. 11


1200
DISPLAYING, AT A PORTABLE ELECTRONIC DEVICE, DESIGNATORS FOR HOME AUTOMATION DEVICES IN A THREE DIMENSIONAL SPACE VIEWABLE USING THE PORTABLE ELECTRONIC DEVICE
1202
DETECTING, AT THE PORTABLE ELECTRONIC DEVICE, A FIRST INPUT SELECTING A HOME AUTOMATION DEVICE OF THE PLURALITY OF HOME AUTOMATION DEVICES
1204
IN RESPONSE TO RECEIVING THE FIRST INPUT, DISPLAYING A VISUAL INDICIUM WITHIN THE THREE DIMENSIONAL SPACE REPRESENTING A CURRENT STATE OF THE HOME AUTOMATION DEVICE
1206
RECEIVING, AT THE PORTABLE ELECTRONIC DEVICE, A SECOND INPUT COMPRISING A GESTURE INPUT REQUESTING A CHANGE IN THE STATE OF THE HOME AUTOMATION DEVICE;
1208
IN RESPONSE TO RECEIVING THE SECOND INPUT, UPDATING THE VISUAL INDICIUM TO REPRESENT THE REQUESTED CHANGE IN THE STATE OF THE HOME AUTOMATION DEVICE
1210
TRANSMITTING A CONTROL SIGNAL DIRECTING THE REQUESTED CHANGE IN THE STATE OF THE HOME AUTOMATION DEVICE
1212

FIG. 12


1300
RECEIVING, AT A PORTABLE ELECTRONIC DEVICE, A FIRST USER INPUT INDICATING A LOCATION AND DESIGNATION OF AN ELECTRONIC DEVICE SEPARATE FROM THE PORTABLE ELECTRONIC DEVICE
1302
DISPLAYING THE DESIGNATION INFORMATION FOR THE ELECTRONIC DEVICE IN A THREE DIMENSIONAL SPACE VIEWABLE USING THE PORTABLE ELECTRONIC DEVICE
1304
RECEIVING A SECOND INPUT REQUESTING A CHANGE IN STATE OF THE ELECTRONIC DEVICE AT THE PORTABLE ELECTRONIC DEVICE
1306

FIG. 13

HOME AUTOMATION DEVICE CONTROL AND DESIGNATION

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority to U.S. patent application Ser. No. 63/352,548, entitled "HOME AUTOMATION DEVICE CONTROL AND DESIGNATION," filed on Jun. 15, 2022, the content of which is hereby incorporated by reference in its entirety.

FIELD

[0002] This relates generally to mechanisms for controlling and annotating home automation devices. In particular, mechanisms and methods are described for allowing a user to identify, label and control a variety of different home automation devices.

BACKGROUND

[0003] Intelligent automated assistants (or digital assistants) can provide a beneficial interface between human users and electronic devices. Such assistants can allow users to interact with devices or systems using natural language in spoken and/or text forms. For example, a user can provide a speech input containing a user request to a digital assistant operating on an electronic device. The digital assistant can interpret the user's intent from the speech input and operationalize the user's intent into tasks. The tasks can then be performed by executing one or more services of the electronic device, and a relevant output responsive to the user request can be returned to the user.

[0004] Digital assistants are sometimes used to interact with and control the operation of home automation devices. Unfortunately, the degree of control provided for any particular device by the digital assistants can be limited and often relies upon the user to remember the name and/or location of the home automation devices to exercise effective control of one or more of the home automation devices. This can become increasingly problematic as a number of home automation devices owned by a user increase. For this reason improved methods for allowing a user to access and control home automation devices is desired.

SUMMARY

[0005] Systems and processes for managing home automation devices are described. The systems and processes allow a user to provide a designation and location for various home automation devices using a portable electronic device that provides the user an extended reality environment to work from.

[0006] Example methods are disclosed herein. An example method includes, at a portable electronic device having one or more processors: displaying designators for a plurality of home automation devices in a three dimensional space viewable using the portable electronic device, wherein the plurality of home automation devices share a geographical area with the portable electronic device; detecting a first input selecting a home automation device of the plurality of home automation devices; in response to receiving the first input, displaying a visual indicium within the three dimensional space representing a current state of the home automation device; receiving, at the portable electronic device, a second input comprising a gesture input requesting a change in the state of the home automation device; in response to receiving the second input, updating the visual indicium to represent the requested change in the state of the home automation device; and transmitting a control signal directing the requested change in the state of the home automation device.

[0007] Another example method includes receiving, at a portable electronic device, a first user input indicating a location and designation of an electronic device separate from the portable electronic device; displaying the designation information for the electronic device in a three dimensional space viewable using the portable electronic device; and receiving a second input requesting a change in state of the electronic device at the portable electronic device.

[0008] Example non-transitory computer-readable media are disclosed herein. An example non-transitory computer-readable storage medium stores one or more programs. The one or more programs comprise instructions, which when executed by one or more processors of a portable electronic device, cause the portable electronic device to: display designators for a plurality of home automation devices in a three dimensional space viewable using the portable electronic device, wherein the plurality of home automation devices share a geographical area with the portable electronic device; detect a first input selecting a home automation device of the plurality of home automation devices; in response to receiving the first input, display a visual indicium within the three dimensional space representing a current state of the home automation device; receive a second input comprising a gesture input requesting a change in the state of the home automation device; in response to receiving the second input, update the visual indicium to represent the requested change in the state of the home automation device; and transmit a control signal directing the requested change in the state of the home automation device.

[0009] Another example non-transitory computer-readable storage medium stores one or more programs. The one or more programs comprise instructions, which when executed by one or more processors of a portable electronic device, cause the portable electronic device to: receiving a first user input indicating a location and designation of an electronic device separate from the portable electronic device; display the designation information for the electronic device in a three dimensional space viewable using the portable electronic device; and receive a second input requesting a change in state of the electronic device at the portable electronic device.

[0010] Example electronic devices are disclosed herein. An example portable electronic device comprises one or more processors; a memory; and one or more programs, where the one or more programs are stored in the memory and configured to be executed by the one or more processors, the one or more programs including instructions for displaying, at the portable electronic device, designators for a plurality of home automation devices in a three dimensional space viewable using the portable electronic device, wherein the plurality of home automation devices share a geographical area with the portable electronic device; detecting, at the portable electronic device, a first input selecting a home automation device of the plurality of home automation devices; in response to receiving the first input, displaying a visual indicium within the three dimensional space representing a current state of the home automation

device; receiving, at the portable electronic device, a second input comprising a gesture input requesting a change in the state of the home automation device; in response to receiving the second input, updating the visual indicium to represent the requested change in the state of the home automation device; and transmitting a control signal directing the requested change in the state of the home automation device.

[0011] An example electronic device comprises means for means for detecting, at the portable electronic device, a first input selecting a home automation device of the plurality of home automation devices; means for in response to receiving the first input, displaying a visual indicium within the three dimensional space representing a current state of the home automation device; means for receiving, at the portable electronic device, a second input comprising a gesture input requesting a change in the state of the home automation device; means for in response to receiving the second input, updating the visual indicium to represent the requested change in the state of the home automation device; and means for transmitting a control signal directing the requested change in the state of the home automation device.

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] FIG. **1** is a block diagram illustrating a system and environment for implementing a digital assistant, according to various examples.

[0013] FIG. **2**A is a block diagram illustrating a portable multifunction device implementing the client-side portion of a digital assistant, according to various examples.

[0014] FIG. **2**B is a block diagram illustrating exemplary components for event handling, according to various examples.

[0015] FIG. **3** illustrates a portable multifunction device implementing the client-side portion of a digital assistant, according to various examples.

[0016] FIG. **4** is a block diagram of an exemplary multifunction device with a display and a touch-sensitive surface, according to various examples.

[0017] FIG. **5**A illustrates an exemplary user interface for a menu of applications on a portable multifunction device, according to various examples.

[0018] FIG. **5**B illustrates an exemplary user interface for a multifunction device with a touch-sensitive surface that is separate from the display, according to various examples.

[0019] FIG. **6**A illustrates a personal electronic device, according to various examples.

[0020] FIG. **6**B is a block diagram illustrating a personal electronic device, according to various examples.

[0021] FIG. **7**A is a block diagram illustrating a digital assistant system or a server portion thereof, according to various examples.

[0022] FIG. **7**B illustrates the functions of the digital assistant shown in FIG. **7**A, according to various examples.

[0023] FIG. **7**C illustrates a portion of an ontology, according to various examples.

[0024] FIGS. **8**A-**8**D include a series of illustrations showing how a user can designate a location and name for a home automation device.

[0025] FIGS. **9**A-**9**D illustrate a process similar to the one illustrated in FIGS. **8**A-**8**D leveraging a modified method of designation.

[0026] FIGS. **10**A-**10**D show a series of illustrations showing methods for controlling a home automation device using a user interface displayed by an electronic device.

[0027] FIG. **11** shows a floor layout for an exemplary home utilizing multiple home automation devices.

[0028] FIG. **12** illustrates a process for interacting with and making changes to a home automation device.

[0029] FIG. **13** illustrates a process for identifying and locating a home automation device.

DETAILED DESCRIPTION

[0030] In the following description of examples, reference is made to the accompanying drawings in which are shown by way of illustration specific examples that can be practiced. It is to be understood that other examples can be used and structural changes can be made without departing from the scope of the various examples.

[0031] Home automation devices can vary greatly in their operations and feature sets. This can make control and management of home automation devices challenging. This can be particularly challenging when a user is employing a large number of home automation devices. One solution to help with management of home automation devices is to provide a user with straightforward mechanisms for viewing, renaming and controlling the home automation devices. The disclosed mechanisms include an interface that allows the user to view information for home automation devices on an extended reality device. The extended reality device allows the user to view digital information about the home automation devices overlaid upon the home automation devices. An intuitive way for controlling the home automation devices using a combination of hand gestures, voice commands and gaze tracking is described herein.

[0032] Although the following description uses terms "first," "second," etc. to describe various elements, these elements should not be limited by the terms. These terms are only used to distinguish one element from another. For example, a first input could be termed a second input, and, similarly, a second input could be termed a first input, without departing from the scope of the various described examples. The first input and the second input are both inputs and, in some cases, are separate and different inputs.

[0033] The terminology used in the description of the various described examples herein is for the purpose of describing particular examples only and is not intended to be limiting. As used in the description of the various described examples and the appended claims, the singular forms "a," "an," and "the" are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will also be understood that the term "and/or" as used herein refers to and encompasses any and all possible combinations of one or more of the associated listed items. It will be further understood that the terms "includes," "including," "comprises," and/or "comprising," when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

[0034] The term "if" may be construed to mean "when" or "upon" or "in response to determining" or "in response to detecting," depending on the context. Similarly, the phrase "if it is determined" or "if [a stated condition or event] is detected" may be construed to mean "upon determining" or "in response to determining" or "upon detecting [the stated condition or event]" or "in response to detecting [the stated condition or event]," depending on the context.

1. System and Environment

[0035] FIG. **1** illustrates a block diagram of system **100** according to various examples. In some examples, system **100** implements a digital assistant. The terms "digital assistant," "virtual assistant," "intelligent automated assistant," or "automatic digital assistant" refer to any information processing system that interprets natural language input in spoken and/or textual form to infer user intent, and performs actions based on the inferred user intent. For example, to act on an inferred user intent, the system performs one or more of the following: identifying a task flow with steps and parameters designed to accomplish the inferred user intent, inputting specific requirements from the inferred user intent into the task flow; executing the task flow by invoking programs, methods, services, APIs, or the like; and generating output responses to the user in an audible (e.g., speech) and/or visual form.

[0036] Specifically, a digital assistant is capable of accepting a user request at least partially in the form of a natural language command, request, statement, narrative, and/or inquiry. Typically, the user request seeks either an informational answer or performance of a task by the digital assistant. A satisfactory response to the user request includes a provision of the requested informational answer, a performance of the requested task, or a combination of the two. For example, a user asks the digital assistant a question, such as "Where am I right now?" Based on the user's current location, the digital assistant answers, "You are in Central Park near the west gate." The user also requests the performance of a task, for example, "Please invite my friends to my girlfriend's birthday party next week." In response, the digital assistant can acknowledge the request by saying "Yes, right away," and then send a suitable calendar invite on behalf of the user to each of the user's friends listed in the user's electronic address book. During performance of a requested task, the digital assistant sometimes interacts with the user in a continuous dialogue involving multiple exchanges of information over an extended period of time. There are numerous other ways of interacting with a digital assistant to request information or performance of various tasks. In addition to providing verbal responses and taking programmed actions, the digital assistant also provides responses in other visual or audio forms, e.g., as text, alerts, music, videos, animations, etc.

[0037] As shown in FIG. **1**, in some examples, a digital assistant is implemented according to a client-server model. The digital assistant includes client-side portion **102** (hereafter "DA client **102**") executed on user device **104** and server-side portion **106** (hereafter "DA server **106**") executed on server system **108**. DA client **102** communicates with DA server **106** through one or more networks **110**. DA client **102** provides client-side functionalities such as user-facing input and output processing and communication with DA server **106**. DA server **106** provides server-side functionalities for any number of DA clients **102** each residing on a respective user device **104**.

[0038] In some examples, DA server **106** includes client-facing I/O interface **112**, one or more processing modules **114**, data and models **116**, and I/O interface to external services **118**. The client-facing I/O interface **112** facilitates the client-facing input and output processing for DA server **106**. One or more processing modules **114** utilize data and models **116** to process speech input and determine the user's intent based on natural language input. Further, one or more processing modules **114** perform task execution based on inferred user intent. In some examples, DA server **106** communicates with external services **120** through network(s) **110** for task completion or information acquisition. I/O interface to external services **118** facilitates such communications.

[0039] User device **104** can be any suitable electronic device. In some examples, user device **104** is a portable multifunctional device (e.g., device **200**, described below with reference to FIG. **2**A), a multifunctional device (e.g., device **400**, described below with reference to FIG. **4**), or a personal electronic device (e.g., device **600**, described below with reference to FIGS. **6**A-**6**B). A portable multifunctional device is, for example, a mobile telephone that also contains other functions, such as PDA and/or music player functions. Specific examples of portable multifunction devices include the Apple Watch®, iPhone®, iPod Touch®, and iPad® devices from Apple Inc. of Cupertino, California. Other examples of portable multifunction devices include, without limitation, earphones/headphones, speakers, and laptop or tablet computers. Further, in some examples, user device **104** is a non-portable multifunctional device. In particular, user device **104** is a desktop computer, a game console, a speaker, a television, or a television set-top box. In some examples, user device **104** includes a touch-sensitive surface (e.g., touch screen displays and/or touchpads). Further, user device **104** optionally includes one or more other physical user-interface devices, such as a physical keyboard, a mouse, and/or a joystick. Various examples of electronic devices, such as multifunctional devices, are described below in greater detail.

[0040] Examples of communication network(s) **110** include local area networks (LAN) and wide area networks (WAN), e.g., the Internet. Communication network(s) **110** is implemented using any known network protocol, including various wired or wireless protocols, such as, for example, Ethernet, Universal Serial Bus (USB), FIREWIRE, Global System for Mobile Communications (GSM), Enhanced Data GSM Environment (EDGE), code division multiple access (CDMA), time division multiple access (TDMA), Bluetooth, Wi-Fi, voice over Internet Protocol (VoIP), Wi-MAX, or any other suitable communication protocol.

[0041] Server system **108** is implemented on one or more standalone data processing apparatus or a distributed network of computers. In some examples, server system **108** also employs various virtual devices and/or services of third-party service providers (e.g., third-party cloud service providers) to provide the underlying computing resources and/or infrastructure resources of server system **108**.

[0042] In some examples, user device **104** communicates with DA server **106** via second user device **122**. Second user device **122** is similar or identical to user device **104**. For example, second user device **122** is similar to devices **200**, **400**, or **600** described below with reference to FIGS. **2**A, **4**, and **6**A-**6**B. User device **104** is configured to communicatively couple to second user device **122** via a direct communication connection, such as Bluetooth, NFC, BTLE, or the like, or via a wired or wireless network, such as a local Wi-Fi network. In some examples, second user device **122** is configured to act as a proxy between user device **104** and DA server **106**. For example, DA client **102** of user device **104** is configured to transmit information (e.g., a user request received at user device **104**) to DA server **106** via second user device **122**. DA server **106** processes the infor-

mation and returns relevant data (e.g., data content responsive to the user request) to user device **104** via second user device **122**.

[0043] In some examples, user device **104** is configured to communicate abbreviated requests for data to second user device **122** to reduce the amount of information transmitted from user device **104**. Second user device **122** is configured to determine supplemental information to add to the abbreviated request to generate a complete request to transmit to DA server **106**. This system architecture can advantageously allow user device **104** having limited communication capabilities and/or limited battery power (e.g., a watch or a similar compact electronic device) to access services provided by DA server **106** by using second user device **122**, having greater communication capabilities and/or battery power (e.g., a mobile phone, laptop computer, tablet computer, or the like), as a proxy to DA server **106**. While only two user devices **104** and **122** are shown in FIG. **1**, it should be appreciated that system **100**, in some examples, includes any number and type of user devices configured in this proxy configuration to communicate with DA server system **106**.

[0044] Although the digital assistant shown in FIG. **1** includes both a client-side portion (e.g., DA client **102**) and a server-side portion (e.g., DA server **106**), in some examples, the functions of a digital assistant are implemented as a standalone application installed on a user device. In addition, the divisions of functionalities between the client and server portions of the digital assistant can vary in different implementations. For instance, in some examples, the DA client is a thin-client that provides only user-facing input and output processing functions, and delegates all other functionalities of the digital assistant to a backend server.

2. Electronic Devices

[0045] Attention is now directed toward embodiments of electronic devices for implementing the client-side portion of a digital assistant. FIG. **2**A is a block diagram illustrating portable multifunction device **200** with touch-sensitive display system **212** in accordance with some embodiments. Touch-sensitive display **212** is sometimes called a "touch screen" for convenience and is sometimes known as or called a "touch-sensitive display system." Device **200** includes memory **202** (which optionally includes one or more computer-readable storage mediums), memory controller **222**, one or more processing units (CPUs) **220**, peripherals interface **218**, RF circuitry **208**, audio circuitry **210**, speaker **211**, microphone **213**, input/output (I/O) subsystem **206**, other input control devices **216**, and external port **224**. Device **200** optionally includes one or more optical sensors **264**. Device **200** optionally includes one or more contact intensity sensors **265** for detecting intensity of contacts on device **200** (e.g., a touch-sensitive surface such as touch-sensitive display system **212** of device **200**). Device **200** optionally includes one or more tactile output generators **267** for generating tactile outputs on device **200** (e.g., generating tactile outputs on a touch-sensitive surface such as touch-sensitive display system **212** of device **200** or touchpad **455** of device **400**). These components optionally communicate over one or more communication buses or signal lines **203**.

[0046] As used in the specification and claims, the term "intensity" of a contact on a touch-sensitive surface refers to the force or pressure (force per unit area) of a contact (e.g., a finger contact) on the touch-sensitive surface, or to a substitute (proxy) for the force or pressure of a contact on the touch-sensitive surface. The intensity of a contact has a range of values that includes at least four distinct values and more typically includes hundreds of distinct values (e.g., at least 256). Intensity of a contact is, optionally, determined (or measured) using various approaches and various sensors or combinations of sensors. For example, one or more force sensors underneath or adjacent to the touch-sensitive surface are, optionally, used to measure force at various points on the touch-sensitive surface. In some implementations, force measurements from multiple force sensors are combined (e.g., a weighted average) to determine an estimated force of a contact. Similarly, a pressure-sensitive tip of a stylus is, optionally, used to determine a pressure of the stylus on the touch-sensitive surface. Alternatively, the size of the contact area detected on the touch-sensitive surface and/or changes thereto, the capacitance of the touch-sensitive surface proximate to the contact and/or changes thereto, and/or the resistance of the touch-sensitive surface proximate to the contact and/or changes thereto are, optionally, used as a substitute for the force or pressure of the contact on the touch-sensitive surface. In some implementations, the substitute measurements for contact force or pressure are used directly to determine whether an intensity threshold has been exceeded (e.g., the intensity threshold is described in units corresponding to the substitute measurements). In some implementations, the substitute measurements for contact force or pressure are converted to an estimated force or pressure, and the estimated force or pressure is used to determine whether an intensity threshold has been exceeded (e.g., the intensity threshold is a pressure threshold measured in units of pressure). Using the intensity of a contact as an attribute of a user input allows for user access to additional device functionality that may otherwise not be accessible by the user on a reduced-size device with limited real estate for displaying affordances (e.g., on a touch-sensitive display) and/or receiving user input (e.g., via a touch-sensitive display, a touch-sensitive surface, or a physical/mechanical control such as a knob or a button).

[0047] As used in the specification and claims, the term "tactile output" refers to physical displacement of a device relative to a previous position of the device, physical displacement of a component (e.g., a touch-sensitive surface) of a device relative to another component (e.g., housing) of the device, or displacement of the component relative to a center of mass of the device that will be detected by a user with the user's sense of touch. For example, in situations where the device or the component of the device is in contact with a surface of a user that is sensitive to touch (e.g., a finger, palm, or other part of a user's hand), the tactile output generated by the physical displacement will be interpreted by the user as a tactile sensation corresponding to a perceived change in physical characteristics of the device or the component of the device. For example, movement of a touch-sensitive surface (e.g., a touch-sensitive display or trackpad) is, optionally, interpreted by the user as a "down click" or "up click" of a physical actuator button. In some cases, a user will feel a tactile sensation such as an "down click" or "up click" even when there is no movement of a physical actuator button associated with the touch-sensitive surface that is physically pressed (e.g., displaced) by the user's movements. As another example, movement of the touch-sensitive surface is, optionally, interpreted or sensed

by the user as "roughness" of the touch-sensitive surface, even when there is no change in smoothness of the touch-sensitive surface. While such interpretations of touch by a user will be subject to the individualized sensory perceptions of the user, there are many sensory perceptions of touch that are common to a large majority of users. Thus, when a tactile output is described as corresponding to a particular sensory perception of a user (e.g., an "up click," a "down click," "roughness"), unless otherwise stated, the generated tactile output corresponds to physical displacement of the device or a component thereof that will generate the described sensory perception for a typical (or average) user.

[0048] It should be appreciated that device **200** is only one example of a portable multifunction device, and that device **200** optionally has more or fewer components than shown, optionally combines two or more components, or optionally has a different configuration or arrangement of the components. The various components shown in FIG. **2**A are implemented in hardware, software, or a combination of both hardware and software, including one or more signal processing and/or application-specific integrated circuits.

[0049] Memory **202** includes one or more computer-readable storage mediums. The computer-readable storage mediums are, for example, tangible and non-transitory. Memory **202** includes high-speed random access memory and also includes non-volatile memory, such as one or more magnetic disk storage devices, flash memory devices, or other non-volatile solid-state memory devices. Memory controller **222** controls access to memory **202** by other components of device **200**.

[0050] In some examples, a non-transitory computer-readable storage medium of memory **202** is used to store instructions (e.g., for performing aspects of processes described below) for use by or in connection with an instruction execution system, apparatus, or device, such as a computer-based system, processor-containing system, or other system that can fetch the instructions from the instruction execution system, apparatus, or device and execute the instructions. In other examples, the instructions (e.g., for performing aspects of the processes described below) are stored on a non-transitory computer-readable storage medium (not shown) of the server system **108** or are divided between the non-transitory computer-readable storage medium of memory **202** and the non-transitory computer-readable storage medium of server system **108**.

[0051] Peripherals interface **218** is used to couple input and output peripherals of the device to CPU **220** and memory **202**. The one or more processors **220** run or execute various software programs and/or sets of instructions stored in memory **202** to perform various functions for device **200** and to process data. In some embodiments, peripherals interface **218**, CPU **220**, and memory controller **222** are implemented on a single chip, such as chip **204**. In some other embodiments, they are implemented on separate chips.

[0052] RF (radio frequency) circuitry **208** receives and sends RF signals, also called electromagnetic signals. RF circuitry **208** converts electrical signals to/from electromagnetic signals and communicates with communications networks and other communications devices via the electromagnetic signals. RF circuitry **208** optionally includes well-known circuitry for performing these functions, including but not limited to an antenna system, an RF transceiver, one or more amplifiers, a tuner, one or more oscillators, a digital signal processor, a CODEC chipset, a subscriber identity module (SIM) card, memory, and so forth. RF circuitry **208** optionally communicates with networks, such as the Internet, also referred to as the World Wide Web (WWW), an intranet and/or a wireless network, such as a cellular telephone network, a wireless local area network (LAN) and/or a metropolitan area network (MAN), and other devices by wireless communication. The RF circuitry **208** optionally includes well-known circuitry for detecting near field communication (NFC) fields, such as by a short-range communication radio. The wireless communication optionally uses any of a plurality of communications standards, protocols, and technologies, including but not limited to Global System for Mobile Communications (GSM), Enhanced Data GSM Environment (EDGE), high-speed downlink packet access (HSDPA), high-speed uplink packet access (HSDPA), Evolution, Data-Only (EV-DO), HSPA, HSPA+, Dual-Cell HSPA (DC-HSPDA), long term evolution (LTE), near field communication (NFC), wideband code division multiple access (W-CDMA), code division multiple access (CDMA), time division multiple access (TDMA), Bluetooth, Bluetooth Low Energy (BTLE), Wireless Fidelity (Wi-Fi) (e.g., IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, and/or IEEE 802.11ac), voice over Internet Protocol (VoIP), Wi-MAX, a protocol for e mail (e.g., Internet message access protocol (IMAP) and/or post office protocol (POP)), instant messaging (e.g., extensible messaging and presence protocol (XMPP), Session Initiation Protocol for Instant Messaging and Presence Leveraging Extensions (SIMPLE), Instant Messaging and Presence Service (IMPS)), and/or Short Message Service (SMS), or any other suitable communication protocol, including communication protocols not yet developed as of the filing date of this document.

[0053] Audio circuitry **210**, speaker **211**, and microphone **213** provide an audio interface between a user and device **200**. Audio circuitry **210** receives audio data from peripherals interface **218**, converts the audio data to an electrical signal, and transmits the electrical signal to speaker **211**. Speaker **211** converts the electrical signal to human-audible sound waves. Audio circuitry **210** also receives electrical signals converted by microphone **213** from sound waves. Audio circuitry **210** converts the electrical signal to audio data and transmits the audio data to peripherals interface **218** for processing. Audio data are retrieved from and/or transmitted to memory **202** and/or RF circuitry **208** by peripherals interface **218**. In some embodiments, audio circuitry **210** also includes a headset jack (e.g., **312**, FIG. **3**). The headset jack provides an interface between audio circuitry **210** and removable audio input/output peripherals, such as output-only headphones or a headset with both output (e.g., a headphone for one or both ears) and input (e.g., a microphone).

[0054] I/O subsystem **206** couples input/output peripherals on device **200**, such as touch screen **212** and other input control devices **216**, to peripherals interface **218**. I/O subsystem **206** optionally includes display controller **256**, optical sensor controller **258**, intensity sensor controller **259**, haptic feedback controller **261**, and one or more input controllers **260** for other input or control devices. The one or more input controllers **260** receive/send electrical signals from/to other input control devices **216**. The other input control devices **216** optionally include physical buttons (e.g., push buttons, rocker buttons, etc.), dials, slider switches, joysticks, click wheels, and so forth. In some alternate embodiments, input controller(s) **260** are, option-

ally, coupled to any (or none) of the following: a keyboard, an infrared port, a USB port, and a pointer device such as a mouse. The one or more buttons (e.g., **308**, FIG. **3**) optionally include an up/down button for volume control of speaker **211** and/or microphone **213**. The one or more buttons optionally include a push button (e.g., **306**, FIG. **3**).

[0055] A quick press of the push button disengages a lock of touch screen **212** or begin a process that uses gestures on the touch screen to unlock the device, as described in U.S. patent application Ser. No. 11/322,549, "Unlocking a Device by Performing Gestures on an Unlock Image," filed Dec. 23, 2005, U.S. Pat. No. 7,657,849, which is hereby incorporated by reference in its entirety. A longer press of the push button (e.g., **306**) turns power to device **200** on or off. The user is able to customize a functionality of one or more of the buttons. Touch screen **212** is used to implement virtual or soft buttons and one or more soft keyboards.

[0056] Touch-sensitive display **212** provides an input interface and an output interface between the device and a user. Display controller **256** receives and/or sends electrical signals from/to touch screen **212**. Touch screen **212** displays visual output to the user. The visual output includes graphics, text, icons, video, and any combination thereof (collectively termed "graphics"). In some embodiments, some or all of the visual output correspond to user-interface objects.

[0057] Touch screen **212** has a touch-sensitive surface, sensor, or set of sensors that accepts input from the user based on haptic and/or tactile contact. Touch screen **212** and display controller **256** (along with any associated modules and/or sets of instructions in memory **202**) detect contact (and any movement or breaking of the contact) on touch screen **212** and convert the detected contact into interaction with user-interface objects (e.g., one or more soft keys, icons, web pages, or images) that are displayed on touch screen **212**. In an exemplary embodiment, a point of contact between touch screen **212** and the user corresponds to a finger of the user.

[0058] Touch screen **212** uses LCD (liquid crystal display) technology, LPD (light emitting polymer display) technology, or LED (light emitting diode) technology, although other display technologies may be used in other embodiments. Touch screen **212** and display controller **256** detect contact and any movement or breaking thereof using any of a plurality of touch sensing technologies now known or later developed, including but not limited to capacitive, resistive, infrared, and surface acoustic wave technologies, as well as other proximity sensor arrays or other elements for determining one or more points of contact with touch screen **212**. In an exemplary embodiment, projected mutual capacitance sensing technology is used, such as that found in the iPhone® and iPod Touch® from Apple Inc. of Cupertino, California.

[0059] A touch-sensitive display in some embodiments of touch screen **212** is analogous to the multi-touch sensitive touchpads described in the following U.S. Pat. No. 6,323,846 (Westerman et al.), U.S. Pat. No. 6,570,557 (Westerman et al.), and/or U.S. Pat. No. 6,677,932 (Westerman), and/or U.S. Patent Publication 2002/0015024A1, each of which is hereby incorporated by reference in its entirety. However, touch screen **212** displays visual output from device **200**, whereas touch-sensitive touchpads do not provide visual output.

[0060] A touch-sensitive display in some embodiments of touch screen **212** is as described in the following applications: (1) U.S. patent application Ser. No. 11/381,313, "Multipoint Touch Surface Controller," filed May 2, 2006; (2) U.S. patent application Ser. No. 10/840,862, "Multipoint Touchscreen," filed May 6, 2004; (3) U.S. patent application Ser. No. 10/903,964, "Gestures For Touch Sensitive Input Devices," filed Jul. 30, 2004; (4) U.S. patent application Ser. No. 11/048,264, "Gestures For Touch Sensitive Input Devices," filed Jan. 31, 2005; (5) U.S. patent application Ser. No. 11/038,590, "Mode-Based Graphical User Interfaces For Touch Sensitive Input Devices," filed Jan. 18, 2005; (6) U.S. patent application Ser. No. 11/228,758, "Virtual Input Device Placement On A Touch Screen User Interface," filed Sep. 16, 2005; (7) U.S. patent application Ser. No. 11/228,700, "Operation Of A Computer With A Touch Screen Interface," filed Sep. 16, 2005; (8) U.S. patent application Ser. No. 11/228,737, "Activating Virtual Keys Of A Touch-Screen Virtual Keyboard," filed Sep. 16, 2005; and (9) U.S. patent application Ser. No. 11/367,749, "Multi-Functional Hand-Held Device," filed Mar. 3, 2006. All of these applications are incorporated by reference herein in their entirety.

[0061] Touch screen **212** has, for example, a video resolution in excess of 100 dpi. In some embodiments, the touch screen has a video resolution of approximately 160 dpi. The user makes contact with touch screen **212** using any suitable object or appendage, such as a stylus, a finger, and so forth. In some embodiments, the user interface is designed to work primarily with finger-based contacts and gestures, which can be less precise than stylus-based input due to the larger area of contact of a finger on the touch screen. In some embodiments, the device translates the rough finger-based input into a precise pointer/cursor position or command for performing the actions desired by the user.

[0062] In some embodiments, in addition to the touch screen, device **200** includes a touchpad (not shown) for activating or deactivating particular functions. In some embodiments, the touchpad is a touch-sensitive area of the device that, unlike the touch screen, does not display visual output. The touchpad is a touch-sensitive surface that is separate from touch screen **212** or an extension of the touch-sensitive surface formed by the touch screen.

[0063] Device **200** also includes power system **262** for powering the various components. Power system **262** includes a power management system, one or more power sources (e.g., battery, alternating current (AC)), a recharging system, a power failure detection circuit, a power converter or inverter, a power status indicator (e.g., a light-emitting diode (LED)) and any other components associated with the generation, management and distribution of power in portable devices.

[0064] Device **200** also includes one or more optical sensors **264**. FIG. **2**A shows an optical sensor coupled to optical sensor controller **258** in I/O subsystem **206**. Optical sensor **264** includes charge-coupled device (CCD) or complementary metal-oxide semiconductor (CMOS) phototransistors. Optical sensor **264** receives light from the environment, projected through one or more lenses, and converts the light to data representing an image. In conjunction with imaging module **243** (also called a camera module), optical sensor **264** captures still images or video. In some embodiments, an optical sensor is located on the back of device **200**, opposite touch screen display **212** on the front of the device so that the touch screen display is used as a viewfinder for still and/or video image acquisition. In some embodiments, an optical sensor is located on the front of the

device so that the user's image is obtained for video conferencing while the user views the other video conference participants on the touch screen display. In some embodiments, the position of optical sensor **264** can be changed by the user (e.g., by rotating the lens and the sensor in the device housing) so that a single optical sensor **264** is used along with the touch screen display for both video conferencing and still and/or video image acquisition.

[0065] Device **200** optionally also includes one or more contact intensity sensors **265**. FIG. **2**A shows a contact intensity sensor coupled to intensity sensor controller **259** in I/O subsystem **206**. Contact intensity sensor **265** optionally includes one or more piezoresistive strain gauges, capacitive force sensors, electric force sensors, piezoelectric force sensors, optical force sensors, capacitive touch-sensitive surfaces, or other intensity sensors (e.g., sensors used to measure the force (or pressure) of a contact on a touch-sensitive surface). Contact intensity sensor **265** receives contact intensity information (e.g., pressure information or a proxy for pressure information) from the environment. In some embodiments, at least one contact intensity sensor is collocated with, or proximate to, a touch-sensitive surface (e.g., touch-sensitive display system **212**). In some embodiments, at least one contact intensity sensor is located on the back of device **200**, opposite touch screen display **212**, which is located on the front of device **200**.

[0066] Device **200** also includes one or more proximity sensors **266**. FIG. **2**A shows proximity sensor **266** coupled to peripherals interface **218**. Alternately, proximity sensor **266** is coupled to input controller **260** in I/O subsystem **206**. Proximity sensor **266** is performed as described in U.S. patent application Ser. No. 11/241,839, "Proximity Detector In Handheld Device"; Ser. No. 11/240,788, "Proximity Detector In Handheld Device"; Ser. No. 11/620,702, "Using Ambient Light Sensor To Augment Proximity Sensor Output"; Ser. No. 11/586,862, "Automated Response To And Sensing Of User Activity In Portable Devices"; and Ser. No. 11/638,251, "Methods And Systems For Automatic Configuration Of Peripherals," which are hereby incorporated by reference in their entirety. In some embodiments, the proximity sensor turns off and disables touch screen **212** when the multifunction device is placed near the user's ear (e.g., when the user is making a phone call).

[0067] Device **200** optionally also includes one or more tactile output generators **267**. FIG. **2**A shows a tactile output generator coupled to haptic feedback controller **261** in I/O subsystem **206**. Tactile output generator **267** optionally includes one or more electroacoustic devices such as speakers or other audio components and/or electromechanical devices that convert energy into linear motion such as a motor, solenoid, electroactive polymer, piezoelectric actuator, electrostatic actuator, or other tactile output generating component (e.g., a component that converts electrical signals into tactile outputs on the device). Contact intensity sensor **265** receives tactile feedback generation instructions from haptic feedback module **233** and generates tactile outputs on device **200** that are capable of being sensed by a user of device **200**. In some embodiments, at least one tactile output generator is collocated with, or proximate to, a touch-sensitive surface (e.g., touch-sensitive display system **212**) and, optionally, generates a tactile output by moving the touch-sensitive surface vertically (e.g., in/out of a surface of device **200**) or laterally (e.g., back and forth in the same plane as a surface of device **200**). In some embodiments, at least one tactile output generator sensor is located on the back of device **200**, opposite touch screen display **212**, which is located on the front of device **200**.

[0068] Device **200** also includes one or more accelerometers **268**. FIG. **2**A shows accelerometer **268** coupled to peripherals interface **218**. Alternately, accelerometer **268** is coupled to an input controller **260** in I/O subsystem **206**. Accelerometer **268** performs, for example, as described in U.S. Patent Publication No. 20050190059, "Acceleration-based Theft Detection System for Portable Electronic Devices," and U.S. Patent Publication No. 20060017692, "Methods And Apparatuses For Operating A Portable Device Based On An Accelerometer," both of which are incorporated by reference herein in their entirety. In some embodiments, information is displayed on the touch screen display in a portrait view or a landscape view based on an analysis of data received from the one or more accelerometers. Device **200** optionally includes, in addition to accelerometer(s) **268**, a magnetometer (not shown) and a GPS (or GLONASS or other global navigation system) receiver (not shown) for obtaining information concerning the location and orientation (e.g., portrait or landscape) of device **200**.

[0069] In some embodiments, the software components stored in memory **202** include operating system **226**, communication module (or set of instructions) **228**, contact/motion module (or set of instructions) **230**, graphics module (or set of instructions) **232**, text input module (or set of instructions) **234**, Global Positioning System (GPS) module (or set of instructions) **235**, Digital Assistant Client Module **229**, and applications (or sets of instructions) **236**. Further, memory **202** stores data and models, such as user data and models **231**. Furthermore, in some embodiments, memory **202** (FIG. **2**A) or **470** (FIG. **4**) stores device/global internal state **257**, as shown in FIGS. **2**A and **4**. Device/global internal state **257** includes one or more of: active application state, indicating which applications, if any, are currently active; display state, indicating what applications, views or other information occupy various regions of touch screen display **212**; sensor state, including information obtained from the device's various sensors and input control devices **216**; and location information concerning the device's location and/or attitude.

[0070] Operating system **226** (e.g., Darwin, RTXC, LINUX, UNIX, OS X, iOS, WINDOWS, or an embedded operating system such as VxWorks) includes various software components and/or drivers for controlling and managing general system tasks (e.g., memory management, storage device control, power management, etc.) and facilitates communication between various hardware and software components.

[0071] Communication module **228** facilitates communication with other devices over one or more external ports **224** and also includes various software components for handling data received by RF circuitry **208** and/or external port **224**. External port **224** (e.g., Universal Serial Bus (USB), FIREWIRE, etc.) is adapted for coupling directly to other devices or indirectly over a network (e.g., the Internet, wireless LAN, etc.). In some embodiments, the external port is a multi-pin (e.g., 30-pin) connector that is the same as, or similar to and/or compatible with, the connector used on iPod® (trademark of Apple Inc.) devices.

[0072] Contact/motion module **230** optionally detects contact with touch screen **212** (in conjunction with display controller **256**) and other touch-sensitive devices (e.g., a

touchpad or physical click wheel). Contact/motion module **230** includes various software components for performing various operations related to detection of contact, such as determining if contact has occurred (e.g., detecting a finger-down event), determining an intensity of the contact (e.g., the force or pressure of the contact or a substitute for the force or pressure of the contact), determining if there is movement of the contact and tracking the movement across the touch-sensitive surface (e.g., detecting one or more finger-dragging events), and determining if the contact has ceased (e.g., detecting a finger-up event or a break in contact). Contact/motion module **230** receives contact data from the touch-sensitive surface. Determining movement of the point of contact, which is represented by a series of contact data, optionally includes determining speed (magnitude), velocity (magnitude and direction), and/or an acceleration (a change in magnitude and/or direction) of the point of contact. These operations are, optionally, applied to single contacts (e.g., one finger contacts) or to multiple simultaneous contacts (e.g., "multitouch"/multiple finger contacts). In some embodiments, contact/motion module **230** and display controller **256** detect contact on a touchpad.

[0073] In some embodiments, contact/motion module **230** uses a set of one or more intensity thresholds to determine whether an operation has been performed by a user (e.g., to determine whether a user has "clicked" on an icon). In some embodiments, at least a subset of the intensity thresholds are determined in accordance with software parameters (e.g., the intensity thresholds are not determined by the activation thresholds of particular physical actuators and can be adjusted without changing the physical hardware of device **200**). For example, a mouse "click" threshold of a trackpad or touch screen display can be set to any of a large range of predefined threshold values without changing the trackpad or touch screen display hardware. Additionally, in some implementations, a user of the device is provided with software settings for adjusting one or more of the set of intensity thresholds (e.g., by adjusting individual intensity thresholds and/or by adjusting a plurality of intensity thresholds at once with a system-level click "intensity" parameter).

[0074] Contact/motion module **230** optionally detects a gesture input by a user. Different gestures on the touch-sensitive surface have different contact patterns (e.g., different motions, timings, and/or intensities of detected contacts). Thus, a gesture is, optionally, detected by detecting a particular contact pattern. For example, detecting a finger tap gesture includes detecting a finger-down event followed by detecting a finger-up (liftoff) event at the same position (or substantially the same position) as the finger-down event (e.g., at the position of an icon). As another example, detecting a finger swipe gesture on the touch-sensitive surface includes detecting a finger-down event followed by detecting one or more finger-dragging events, and subsequently followed by detecting a finger-up (liftoff) event.

[0075] Graphics module **232** includes various known software components for rendering and displaying graphics on touch screen **212** or other display, including components for changing the visual impact (e.g., brightness, transparency, saturation, contrast, or other visual property) of graphics that are displayed. As used herein, the term "graphics" includes any object that can be displayed to a user, including, without limitation, text, web pages, icons (such as user-interface objects including soft keys), digital images, videos, animations, and the like.

[0076] In some embodiments, graphics module **232** stores data representing graphics to be used. Each graphic is, optionally, assigned a corresponding code. Graphics module **232** receives, from applications etc., one or more codes specifying graphics to be displayed along with, if necessary, coordinate data and other graphic property data, and then generates screen image data to output to display controller **256**.

[0077] Haptic feedback module **233** includes various software components for generating instructions used by tactile output generator(s) **267** to produce tactile outputs at one or more locations on device **200** in response to user interactions with device **200**.

[0078] Text input module **234**, which is, in some examples, a component of graphics module **232**, provides soft keyboards for entering text in various applications (e.g., contacts **237**, email **240**, IM **241**, browser **247**, and any other application that needs text input).

[0079] GPS module **235** determines the location of the device and provides this information for use in various applications (e.g., to telephone **238** for use in location-based dialing; to camera **243** as picture/video metadata; and to applications that provide location-based services such as weather widgets, local yellow page widgets, and map/navigation widgets).

[0080] Digital assistant client module **229** includes various client-side digital assistant instructions to provide the client-side functionalities of the digital assistant. For example, digital assistant client module **229** is capable of accepting voice input (e.g., speech input), text input, touch input, and/or gestural input through various user interfaces (e.g., microphone **213**, accelerometer(s) **268**, touch-sensitive display system **212**, optical sensor(s) **264**, other input control devices **216**, etc.) of portable multifunction device **200**. Digital assistant client module **229** is also capable of providing output in audio (e.g., speech output), visual, and/or tactile forms through various output interfaces (e.g., speaker **211**, touch-sensitive display system **212**, tactile output generator(s) **267**, etc.) of portable multifunction device **200**. For example, output is provided as voice, sound, alerts, text messages, menus, graphics, videos, animations, vibrations, and/or combinations of two or more of the above. During operation, digital assistant client module **229** communicates with DA server **106** using RF circuitry **208**.

[0081] User data and models **231** include various data associated with the user (e.g., user-specific vocabulary data, user preference data, user-specified name pronunciations, data from the user's electronic address book, to-do lists, shopping lists, etc.) to provide the client-side functionalities of the digital assistant. Further, user data and models **231** include various models (e.g., speech recognition models, statistical language models, natural language processing models, ontology, task flow models, service models, etc.) for processing user input and determining user intent.

[0082] In some examples, digital assistant client module **229** utilizes the various sensors, subsystems, and peripheral devices of portable multifunction device **200** to gather additional information from the surrounding environment of the portable multifunction device **200** to establish a context associated with a user, the current user interaction, and/or the current user input. In some examples, digital assistant client module **229** provides the contextual information or a subset thereof with the user input to DA server **106** to help infer the user's intent. In some examples, the digital assistant

also uses the contextual information to determine how to prepare and deliver outputs to the user. Contextual information is referred to as context data.

[0083] In some examples, the contextual information that accompanies the user input includes sensor information, e.g., lighting, ambient noise, ambient temperature, images or videos of the surrounding environment, etc. In some examples, the contextual information can also include the physical state of the device, e.g., device orientation, device location, device temperature, power level, speed, acceleration, motion patterns, cellular signals strength, etc. In some examples, information related to the software state of DA server **106**, e.g., running processes, installed programs, past and present network activities, background services, error logs, resources usage, etc., and of portable multifunction device **200** is provided to DA server **106** as contextual information associated with a user input.

[0084] In some examples, the digital assistant client module **229** selectively provides information (e.g., user data **231**) stored on the portable multifunction device **200** in response to requests from DA server **106**. In some examples, digital assistant client module **229** also elicits additional input from the user via a natural language dialogue or other user interfaces upon request by DA server **106**. Digital assistant client module **229** passes the additional input to DA server **106** to help DA server **106** in intent deduction and/or fulfillment of the user's intent expressed in the user request.

[0085] A more detailed description of a digital assistant is described below with reference to FIGS. **7**A-**7**C. It should be recognized that digital assistant client module **229** can include any number of the sub-modules of digital assistant module **726** described below.

[0086] Applications **236** include the following modules (or sets of instructions), or a subset or superset thereof:

[0087] Contacts module **237** (sometimes called an address book or contact list);

[0088] Telephone module **238**;

[0089] Video conference module **239**;

[0090] E-mail client module **240**;

[0091] Instant messaging (IM) module **241**;

[0092] Workout support module **242**;

[0093] Camera module **243** for still and/or video images;

[0094] Image management module **244**;

[0095] Video player module;

[0096] Music player module;

[0097] Browser module **247**;

[0098] Calendar module **248**;

[0099] Widget modules **249**, which includes, in some examples, one or more of: weather widget **249-1**, stocks widget **249-2**, calculator widget **249-3**, alarm clock widget **249-4**, dictionary widget **249-5**, and other widgets obtained by the user, as well as user-created widgets **249-6**;

[0100] Widget creator module **250** for making user-created widgets **249-6**;

[0101] Search module **251**;

[0102] Video and music player module **252**, which merges video player module and music player module;

[0103] Notes module **253**;

[0104] Map module **254**; and/or

[0105] Online video module **255**.

[0106] Examples of other applications **236** that are stored in memory **202** include other word processing applications, other image editing applications, drawing applications, presentation applications, JAVA-enabled applications, encryption, digital rights management, voice recognition, and voice replication.

[0107] In conjunction with touch screen **212**, display controller **256**, contact/motion module **230**, graphics module **232**, and text input module **234**, contacts module **237** are used to manage an address book or contact list (e.g., stored in application internal state **292** of contacts module **237** in memory **202** or memory **470**), including: adding name(s) to the address book; deleting name(s) from the address book; associating telephone number(s), e-mail address(es), physical address(es) or other information with a name; associating an image with a name; categorizing and sorting names; providing telephone numbers or e-mail addresses to initiate and/or facilitate communications by telephone **238**, video conference module **239**, e-mail **240**, or IM **241**; and so forth.

[0108] In conjunction with RF circuitry **208**, audio circuitry **210**, speaker **211**, microphone **213**, touch screen **212**, display controller **256**, contact/motion module **230**, graphics module **232**, and text input module **234**, telephone module **238** are used to enter a sequence of characters corresponding to a telephone number, access one or more telephone numbers in contacts module **237**, modify a telephone number that has been entered, dial a respective telephone number, conduct a conversation, and disconnect or hang up when the conversation is completed. As noted above, the wireless communication uses any of a plurality of communications standards, protocols, and technologies.

[0109] In conjunction with RF circuitry **208**, audio circuitry **210**, speaker **211**, microphone **213**, touch screen **212**, display controller **256**, optical sensor **264**, optical sensor controller **258**, contact/motion module **230**, graphics module **232**, text input module **234**, contacts module **237**, and telephone module **238**, video conference module **239** includes executable instructions to initiate, conduct, and terminate a video conference between a user and one or more other participants in accordance with user instructions.

[0110] In conjunction with RF circuitry **208**, touch screen **212**, display controller **256**, contact/motion module **230**, graphics module **232**, and text input module **234**, e-mail client module **240** includes executable instructions to create, send, receive, and manage e-mail in response to user instructions. In conjunction with image management module **244**, e-mail client module **240** makes it very easy to create and send e-mails with still or video images taken with camera module **243**.

[0111] In conjunction with RF circuitry **208**, touch screen **212**, display controller **256**, contact/motion module **230**, graphics module **232**, and text input module **234**, the instant messaging module **241** includes executable instructions to enter a sequence of characters corresponding to an instant message, to modify previously entered characters, to transmit a respective instant message (for example, using a Short Message Service (SMS) or Multimedia Message Service (MMS) protocol for telephony-based instant messages or using XMPP, SIMPLE, or IMPS for Internet-based instant messages), to receive instant messages, and to view received instant messages. In some embodiments, transmitted and/or received instant messages include graphics, photos, audio files, video files and/or other attachments as are supported in an MMS and/or an Enhanced Messaging Service (EMS). As used herein, "instant messaging" refers to both telephony-

based messages (e.g., messages sent using SMS or MMS) and Internet-based messages (e.g., messages sent using XMPP, SIMPLE, or IMPS).

[0112] In conjunction with RF circuitry **208**, touch screen **212**, display controller **256**, contact/motion module **230**, graphics module **232**, text input module **234**, GPS module **235**, map module **254**, and music player module, workout support module **242** includes executable instructions to create workouts (e.g., with time, distance, and/or calorie burning goals); communicate with workout sensors (sports devices); receive workout sensor data; calibrate sensors used to monitor a workout; select and play music for a workout; and display, store, and transmit workout data.

[0113] In conjunction with touch screen **212**, display controller **256**, optical sensor(s) **264**, optical sensor controller **258**, contact/motion module **230**, graphics module **232**, and image management module **244**, camera module **243** includes executable instructions to capture still images or video (including a video stream) and store them into memory **202**, modify characteristics of a still image or video, or delete a still image or video from memory **202**.

[0114] In conjunction with touch screen **212**, display controller **256**, contact/motion module **230**, graphics module **232**, text input module **234**, and camera module **243**, image management module **244** includes executable instructions to arrange, modify (e.g., edit), or otherwise manipulate, label, delete, present (e.g., in a digital slide show or album), and store still and/or video images.

[0115] In conjunction with RF circuitry **208**, touch screen **212**, display controller **256**, contact/motion module **230**, graphics module **232**, and text input module **234**, browser module **247** includes executable instructions to browse the Internet in accordance with user instructions, including searching, linking to, receiving, and displaying web pages or portions thereof, as well as attachments and other files linked to web pages.

[0116] In conjunction with RF circuitry **208**, touch screen **212**, display controller **256**, contact/motion module **230**, graphics module **232**, text input module **234**, e-mail client module **240**, and browser module **247**, calendar module **248** includes executable instructions to create, display, modify, and store calendars and data associated with calendars (e.g., calendar entries, to-do lists, etc.) in accordance with user instructions.

[0117] In conjunction with RF circuitry **208**, touch screen **212**, display controller **256**, contact/motion module **230**, graphics module **232**, text input module **234**, and browser module **247**, widget modules **249** are mini-applications that can be downloaded and used by a user (e.g., weather widget **249-1**, stocks widget **249-2**, calculator widget **249-3**, alarm clock widget **249-4**, and dictionary widget **249-5**) or created by the user (e.g., user-created widget **249-6**). In some embodiments, a widget includes an HTML (Hypertext Markup Language) file, a CSS (Cascading Style Sheets) file, and a JavaScript file. In some embodiments, a widget includes an XML (Extensible Markup Language) file and a JavaScript file (e.g., Yahoo! Widgets).

[0118] In conjunction with RF circuitry **208**, touch screen **212**, display controller **256**, contact/motion module **230**, graphics module **232**, text input module **234**, and browser module **247**, the widget creator module **250** are used by a user to create widgets (e.g., turning a user-specified portion of a web page into a widget).

[0119] In conjunction with touch screen **212**, display controller **256**, contact/motion module **230**, graphics module **232**, and text input module **234**, search module **251** includes executable instructions to search for text, music, sound, image, video, and/or other files in memory **202** that match one or more search criteria (e.g., one or more user-specified search terms) in accordance with user instructions.

[0120] In conjunction with touch screen **212**, display controller **256**, contact/motion module **230**, graphics module **232**, audio circuitry **210**, speaker **211**, RF circuitry **208**, and browser module **247**, video and music player module **252** includes executable instructions that allow the user to download and play back recorded music and other sound files stored in one or more file formats, such as MP3 or AAC files, and executable instructions to display, present, or otherwise play back videos (e.g., on touch screen **212** or on an external, connected display via external port **224**). In some embodiments, device **200** optionally includes the functionality of an MP3 player, such as an iPod (trademark of Apple Inc.).

[0121] In conjunction with touch screen **212**, display controller **256**, contact/motion module **230**, graphics module **232**, and text input module **234**, notes module **253** includes executable instructions to create and manage notes, to-do lists, and the like in accordance with user instructions.

[0122] In conjunction with RF circuitry **208**, touch screen **212**, display controller **256**, contact/motion module **230**, graphics module **232**, text input module **234**, GPS module **235**, and browser module **247**, map module **254** are used to receive, display, modify, and store maps and data associated with maps (e.g., driving directions, data on stores and other points of interest at or near a particular location, and other location-based data) in accordance with user instructions.

[0123] In conjunction with touch screen **212**, display controller **256**, contact/motion module **230**, graphics module **232**, audio circuitry **210**, speaker **211**, RF circuitry **208**, text input module **234**, e-mail client module **240**, and browser module **247**, online video module **255** includes instructions that allow the user to access, browse, receive (e.g., by streaming and/or download), play back (e.g., on the touch screen or on an external, connected display via external port **224**), send an e-mail with a link to a particular online video, and otherwise manage online videos in one or more file formats, such as H.264. In some embodiments, instant messaging module **241**, rather than e-mail client module **240**, is used to send a link to a particular online video. Additional description of the online video application can be found in U.S. Provisional Patent Application No. 60/936,562, "Portable Multifunction Device, Method, and Graphical User Interface for Playing Online Videos," filed Jun. 20, 2007, and U.S. patent application Ser. No. 11/968,067, "Portable Multifunction Device, Method, and Graphical User Interface for Playing Online Videos," filed Dec. 31, 2007, the contents of which are hereby incorporated by reference in their entirety.

[0124] Each of the above-identified modules and applications corresponds to a set of executable instructions for performing one or more functions described above and the methods described in this application (e.g., the computer-implemented methods and other information processing methods described herein). These modules (e.g., sets of instructions) need not be implemented as separate software programs, procedures, or modules, and thus various subsets of these modules can be combined or otherwise rearranged in various embodiments. For example, video player module

can be combined with music player module into a single module (e.g., video and music player module **252**, FIG. **2**A). In some embodiments, memory **202** stores a subset of the modules and data structures identified above. Furthermore, memory **202** stores additional modules and data structures not described above.

[0125] In some embodiments, device **200** is a device where operation of a predefined set of functions on the device is performed exclusively through a touch screen and/or a touchpad. By using a touch screen and/or a touchpad as the primary input control device for operation of device **200**, the number of physical input control devices (such as push buttons, dials, and the like) on device **200** is reduced.

[0126] The predefined set of functions that are performed exclusively through a touch screen and/or a touchpad optionally include navigation between user interfaces. In some embodiments, the touchpad, when touched by the user, navigates device **200** to a main, home, or root menu from any user interface that is displayed on device **200**. In such embodiments, a "menu button" is implemented using a touchpad. In some other embodiments, the menu button is a physical push button or other physical input control device instead of a touchpad.

[0127] FIG. **2**B is a block diagram illustrating exemplary components for event handling in accordance with some embodiments. In some embodiments, memory **202** (FIG. **2**A) or **470** (FIG. **4**) includes event sorter **270** (e.g., in operating system **226**) and a respective application **236-1** (e.g., any of the aforementioned applications **237-251**, **255**, **480-490**).

[0128] Event sorter **270** receives event information and determines the application **236-1** and application view **291** of application **236-1** to which to deliver the event information. Event sorter **270** includes event monitor **271** and event dispatcher module **274**. In some embodiments, application **236-1** includes application internal state **292**, which indicates the current application view(s) displayed on touch-sensitive display **212** when the application is active or executing. In some embodiments, device/global internal state **257** is used by event sorter **270** to determine which application(s) is (are) currently active, and application internal state **292** is used by event sorter **270** to determine application views **291** to which to deliver event information.

[0129] In some embodiments, application internal state **292** includes additional information, such as one or more of: resume information to be used when application **236-1** resumes execution, user interface state information that indicates information being displayed or that is ready for display by application **236-1**, a state queue for enabling the user to go back to a prior state or view of application **236-1**, and a redo/undo queue of previous actions taken by the user.

[0130] Event monitor **271** receives event information from peripherals interface **218**. Event information includes information about a sub-event (e.g., a user touch on touch-sensitive display **212**, as part of a multi-touch gesture). Peripherals interface **218** transmits information it receives from I/O subsystem **206** or a sensor, such as proximity sensor **266**, accelerometer(s) **268**, and/or microphone **213** (through audio circuitry **210**). Information that peripherals interface **218** receives from I/O subsystem **206** includes information from touch-sensitive display **212** or a touch-sensitive surface.

[0131] In some embodiments, event monitor **271** sends requests to the peripherals interface **218** at predetermined intervals. In response, peripherals interface **218** transmits event information. In other embodiments, peripherals interface **218** transmits event information only when there is a significant event (e.g., receiving an input above a predetermined noise threshold and/or for more than a predetermined duration).

[0132] In some embodiments, event sorter **270** also includes a hit view determination module **272** and/or an active event recognizer determination module **273**.

[0133] Hit view determination module **272** provides software procedures for determining where a sub-event has taken place within one or more views when touch-sensitive display **212** displays more than one view. Views are made up of controls and other elements that a user can see on the display.

[0134] Another aspect of the user interface associated with an application is a set of views, sometimes herein called application views or user interface windows, in which information is displayed and touch-based gestures occur. The application views (of a respective application) in which a touch is detected correspond to programmatic levels within a programmatic or view hierarchy of the application. For example, the lowest level view in which a touch is detected is called the hit view, and the set of events that are recognized as proper inputs is determined based, at least in part, on the hit view of the initial touch that begins a touch-based gesture.

[0135] Hit view determination module **272** receives information related to sub events of a touch-based gesture. When an application has multiple views organized in a hierarchy, hit view determination module **272** identifies a hit view as the lowest view in the hierarchy which should handle the sub-event. In most circumstances, the hit view is the lowest level view in which an initiating sub-event occurs (e.g., the first sub-event in the sequence of sub-events that form an event or potential event). Once the hit view is identified by the hit view determination module **272**, the hit view typically receives all sub-events related to the same touch or input source for which it was identified as the hit view.

[0136] Active event recognizer determination module **273** determines which view or views within a view hierarchy should receive a particular sequence of sub-events. In some embodiments, active event recognizer determination module **273** determines that only the hit view should receive a particular sequence of sub-events. In other embodiments, active event recognizer determination module **273** determines that all views that include the physical location of a sub-event are actively involved views, and therefore determines that all actively involved views should receive a particular sequence of sub-events. In other embodiments, even if touch sub-events were entirely confined to the area associated with one particular view, views higher in the hierarchy would still remain as actively involved views.

[0137] Event dispatcher module **274** dispatches the event information to an event recognizer (e.g., event recognizer **280**). In embodiments including active event recognizer determination module **273**, event dispatcher module **274** delivers the event information to an event recognizer determined by active event recognizer determination module **273**. In some embodiments, event dispatcher module **274** stores in an event queue the event information, which is retrieved by a respective event receiver **282**.

[0138] In some embodiments, operating system **226** includes event sorter **270**. Alternatively, application **236-1** includes event sorter **270**. In yet other embodiments, event sorter **270** is a stand-alone module, or a part of another module stored in memory **202**, such as contact/motion module **230**.

[0139] In some embodiments, application **236-1** includes a plurality of event handlers **290** and one or more application views **291**, each of which includes instructions for handling touch events that occur within a respective view of the application's user interface. Each application view **291** of the application **236-1** includes one or more event recognizers **280**. Typically, a respective application view **291** includes a plurality of event recognizers **280**. In other embodiments, one or more of event recognizers **280** are part of a separate module, such as a user interface kit (not shown) or a higher level object from which application **236-1** inherits methods and other properties. In some embodiments, a respective event handler **290** includes one or more of: data updater **276**, object updater **277**, GUI updater **278**, and/or event data **279** received from event sorter **270**. Event handler **290** utilizes or calls data updater **276**, object updater **277**, or GUI updater **278** to update the application internal state **292**. Alternatively, one or more of the application views **291** include one or more respective event handlers **290**. Also, in some embodiments, one or more of data updater **276**, object updater **277**, and GUI updater **278** are included in a respective application view **291**.

[0140] A respective event recognizer **280** receives event information (e.g., event data **279**) from event sorter **270** and identifies an event from the event information. Event recognizer **280** includes event receiver **282** and event comparator **284**. In some embodiments, event recognizer **280** also includes at least a subset of: metadata **283**, and event delivery instructions **288** (which include sub-event delivery instructions).

[0141] Event receiver **282** receives event information from event sorter **270**. The event information includes information about a sub-event, for example, a touch or a touch movement. Depending on the sub-event, the event information also includes additional information, such as location of the sub-event. When the sub-event concerns motion of a touch, the event information also includes speed and direction of the sub-event. In some embodiments, events include rotation of the device from one orientation to another (e.g., from a portrait orientation to a landscape orientation, or vice versa), and the event information includes corresponding information about the current orientation (also called device attitude) of the device.

[0142] Event comparator **284** compares the event information to predefined event or sub-event definitions and, based on the comparison, determines an event or sub event, or determines or updates the state of an event or sub-event. In some embodiments, event comparator **284** includes event definitions **286**. Event definitions **286** contain definitions of events (e.g., predefined sequences of sub-events), for example, event **1** (**287-1**), event **2** (**287-2**), and others. In some embodiments, sub-events in an event (**287**) include, for example, touch begin, touch end, touch movement, touch cancellation, and multiple touching. In one example, the definition for event **1** (**287-1**) is a double tap on a displayed object. The double tap, for example, comprises a first touch (touch begin) on the displayed object for a predetermined phase, a first liftoff (touch end) for a predetermined phase, a second touch (touch begin) on the displayed object for a predetermined phase, and a second liftoff (touch end) for a predetermined phase. In another example, the definition for event **2** (**287-2**) is a dragging on a displayed object. The dragging, for example, comprises a touch (or contact) on the displayed object for a predetermined phase, a movement of the touch across touch-sensitive display **212**, and liftoff of the touch (touch end). In some embodiments, the event also includes information for one or more associated event handlers **290**.

[0143] In some embodiments, event definition **287** includes a definition of an event for a respective user-interface object. In some embodiments, event comparator **284** performs a hit test to determine which user-interface object is associated with a sub-event. For example, in an application view in which three user-interface objects are displayed on touch-sensitive display **212**, when a touch is detected on touch-sensitive display **212**, event comparator **284** performs a hit test to determine which of the three user-interface objects is associated with the touch (sub-event). If each displayed object is associated with a respective event handler **290**, the event comparator uses the result of the hit test to determine which event handler **290** should be activated. For example, event comparator **284** selects an event handler associated with the sub-event and the object triggering the hit test.

[0144] In some embodiments, the definition for a respective event (**287**) also includes delayed actions that delay delivery of the event information until after it has been determined whether the sequence of sub-events does or does not correspond to the event recognizer's event type.

[0145] When a respective event recognizer **280** determines that the series of sub-events do not match any of the events in event definitions **286**, the respective event recognizer **280** enters an event impossible, event failed, or event ended state, after which it disregards subsequent sub-events of the touch-based gesture. In this situation, other event recognizers, if any, that remain active for the hit view continue to track and process sub-events of an ongoing touch-based gesture.

[0146] In some embodiments, a respective event recognizer **280** includes metadata **283** with configurable properties, flags, and/or lists that indicate how the event delivery system should perform sub-event delivery to actively involved event recognizers. In some embodiments, metadata **283** includes configurable properties, flags, and/or lists that indicate how event recognizers interact, or are enabled to interact, with one another. In some embodiments, metadata **283** includes configurable properties, flags, and/or lists that indicate whether sub-events are delivered to varying levels in the view or programmatic hierarchy.

[0147] In some embodiments, a respective event recognizer **280** activates event handler **290** associated with an event when one or more particular sub-events of an event are recognized. In some embodiments, a respective event recognizer **280** delivers event information associated with the event to event handler **290**. Activating an event handler **290** is distinct from sending (and deferred sending) sub-events to a respective hit view. In some embodiments, event recognizer **280** throws a flag associated with the recognized event, and event handler **290** associated with the flag catches the flag and performs a predefined process.

[0148] In some embodiments, event delivery instructions **288** include sub-event delivery instructions that deliver

event information about a sub-event without activating an event handler. Instead, the sub-event delivery instructions deliver event information to event handlers associated with the series of sub-events or to actively involved views. Event handlers associated with the series of sub-events or with actively involved views receive the event information and perform a predetermined process.

[0149] In some embodiments, data updater **276** creates and updates data used in application **236-1**. For example, data updater **276** updates the telephone number used in contacts module **237**, or stores a video file used in video player module. In some embodiments, object updater **277** creates and updates objects used in application **236-1**. For example, object updater **277** creates a new user-interface object or updates the position of a user-interface object. GUI updater **278** updates the GUI. For example, GUI updater **278** prepares display information and sends it to graphics module **232** for display on a touch-sensitive display.

[0150] In some embodiments, event handler(s) **290** includes or has access to data updater **276**, object updater **277**, and GUI updater **278**. In some embodiments, data updater **276**, object updater **277**, and GUI updater **278** are included in a single module of a respective application **236-1** or application view **291**. In other embodiments, they are included in two or more software modules.

[0151] It shall be understood that the foregoing discussion regarding event handling of user touches on touch-sensitive displays also applies to other forms of user inputs to operate multifunction devices **200** with input devices, not all of which are initiated on touch screens. For example, mouse movement and mouse button presses, optionally coordinated with single or multiple keyboard presses or holds; contact movements such as taps, drags, scrolls, etc. on touchpads; pen stylus inputs; movement of the device; oral instructions; detected eye movements; biometric inputs; and/or any combination thereof are optionally utilized as inputs corresponding to sub-events which define an event to be recognized.

[0152] FIG. **3** illustrates a portable multifunction device **200** having a touch screen **212** in accordance with some embodiments. The touch screen optionally displays one or more graphics within user interface (UI) **300**. In this embodiment, as well as others described below, a user is enabled to select one or more of the graphics by making a gesture on the graphics, for example, with one or more fingers **302** (not drawn to scale in the figure) or one or more styluses **303** (not drawn to scale in the figure). In some embodiments, selection of one or more graphics occurs when the user breaks contact with the one or more graphics. In some embodiments, the gesture optionally includes one or more taps, one or more swipes (from left to right, right to left, upward and/or downward), and/or a rolling of a finger (from right to left, left to right, upward and/or downward) that has made contact with device **200**. In some implementations or circumstances, inadvertent contact with a graphic does not select the graphic. For example, a swipe gesture that sweeps over an application icon optionally does not select the corresponding application when the gesture corresponding to selection is a tap.

[0153] Device **200** also includes one or more physical buttons, such as "home" or menu button **304**. As described previously, menu button **304** is used to navigate to any application **236** in a set of applications that is executed on device **200**. Alternatively, in some embodiments, the menu button is implemented as a soft key in a GUI displayed on touch screen **212**.

[0154] In one embodiment, device **200** includes touch screen **212**, menu button **304**, push button **306** for powering the device on/off and locking the device, volume adjustment button(s) **308**, subscriber identity module (SIM) card slot **310**, headset jack **312**, and docking/charging external port **224**. Push button **306** is, optionally, used to turn the power on/off on the device by depressing the button and holding the button in the depressed state for a predefined time interval; to lock the device by depressing the button and releasing the button before the predefined time interval has elapsed; and/or to unlock the device or initiate an unlock process. In an alternative embodiment, device **200** also accepts verbal input for activation or deactivation of some functions through microphone **213**. Device **200** also, optionally, includes one or more contact intensity sensors **265** for detecting intensity of contacts on touch screen **212** and/or one or more tactile output generators **267** for generating tactile outputs for a user of device **200**.

[0155] FIG. **4** is a block diagram of an exemplary multifunction device with a display and a touch-sensitive surface in accordance with some embodiments. Device **400** need not be portable. In some embodiments, device **400** is a laptop computer, a desktop computer, a tablet computer, a multimedia player device, a navigation device, an educational device (such as a child's learning toy), a gaming system, or a control device (e.g., a home or industrial controller). Device **400** typically includes one or more processing units (CPUs) **410**, one or more network or other communications interfaces **460**, memory **470**, and one or more communication buses **420** for interconnecting these components. Communication buses **420** optionally include circuitry (sometimes called a chipset) that interconnects and controls communications between system components. Device **400** includes input/output (I/O) interface **430** comprising display **440**, which is typically a touch screen display. I/O interface **430** also optionally includes a keyboard and/or mouse (or other pointing device) **450** and touchpad **455**, tactile output generator **457** for generating tactile outputs on device **400** (e.g., similar to tactile output generator(s) **267** described above with reference to FIG. **2**A), sensors **459** (e.g., optical, acceleration, proximity, touch-sensitive, and/or contact intensity sensors similar to contact intensity sensor(s) **265** described above with reference to FIG. **2**A). Memory **470** includes high-speed random access memory, such as DRAM, SRAM, DDR RAM, or other random access solid state memory devices; and optionally includes non-volatile memory, such as one or more magnetic disk storage devices, optical disk storage devices, flash memory devices, or other non-volatile solid state storage devices. Memory **470** optionally includes one or more storage devices remotely located from CPU(s) **410**. In some embodiments, memory **470** stores programs, modules, and data structures analogous to the programs, modules, and data structures stored in memory **202** of portable multifunction device **200** (FIG. **2**A), or a subset thereof. Furthermore, memory **470** optionally stores additional programs, modules, and data structures not present in memory **202** of portable multifunction device **200**. For example, memory **470** of device **400** optionally stores drawing module **480**, presentation module **482**, word processing module **484**, website creation module **486**, disk authoring module **488**, and/or spreadsheet module **490**,

while memory **202** of portable multifunction device **200** (FIG. **2**A) optionally does not store these modules.

[0156] Each of the above-identified elements in FIG. **4** is, in some examples, stored in one or more of the previously mentioned memory devices. Each of the above-identified modules corresponds to a set of instructions for performing a function described above. The above-identified modules or programs (e.g., sets of instructions) need not be implemented as separate software programs, procedures, or modules, and thus various subsets of these modules are combined or otherwise rearranged in various embodiments. In some embodiments, memory **470** stores a subset of the modules and data structures identified above. Furthermore, memory **470** stores additional modules and data structures not described above.

[0157] Attention is now directed towards embodiments of user interfaces that can be implemented on, for example, portable multifunction device **200**.

[0158] FIG. **5**A illustrates an exemplary user interface for a menu of applications on portable multifunction device **200** in accordance with some embodiments. Similar user interfaces are implemented on device **400**. In some embodiments, user interface **500** includes the following elements, or a subset or superset thereof:

[0159] Signal strength indicator(s) **502** for wireless communication(s), such as cellular and Wi-Fi signals;

[0160] Time **504**;

[0161] Bluetooth indicator **505**;

[0162] Battery status indicator **506**;

[0163] Tray **508** with icons for frequently used applications, such as:

[0164] Icon **516** for telephone module **238**, labeled "Phone," which optionally includes an indicator **514** of the number of missed calls or voicemail messages;

[0165] Icon **518** for e-mail client module **240**, labeled "Mail," which optionally includes an indicator **510** of the number of unread e-mails;

[0166] Icon **520** for browser module **247**, labeled "Browser;" and

[0167] Icon **522** for video and music player module **252**, also referred to as iPod (trademark of Apple Inc.) module **252**, labeled "iPod;" and

[0168] Icons for other applications, such as:

[0169] Icon **524** for IM module **241**, labeled "Messages;"

[0170] Icon **526** for calendar module **248**, labeled "Calendar;"

[0171] Icon **528** for image management module **244**, labeled "Photos;"

[0172] Icon **530** for camera module **243**, labeled "Camera;"

[0173] Icon **532** for online video module **255**, labeled "Online Video;"

[0174] Icon **534** for stocks widget **249-2**, labeled "Stocks;"

[0175] Icon **536** for map module **254**, labeled "Maps;"

[0176] Icon **538** for weather widget **249-1**, labeled "Weather;"

[0177] Icon **540** for alarm clock widget **249-4**, labeled "Clock;"

[0178] Icon **542** for workout support module **242**, labeled "Workout Support;"

[0179] Icon **544** for notes module **253**, labeled "Notes;" and

[0180] Icon **546** for a settings application or module, labeled "Settings," which provides access to settings for device **200** and its various applications **236**.

[0181] It should be noted that the icon labels illustrated in FIG. **5**A are merely exemplary. For example, icon **522** for video and music player module **252** is optionally labeled "Music" or "Music Player." Other labels are, optionally, used for various application icons. In some embodiments, a label for a respective application icon includes a name of an application corresponding to the respective application icon. In some embodiments, a label for a particular application icon is distinct from a name of an application corresponding to the particular application icon.

[0182] FIG. **5**B illustrates an exemplary user interface on a device (e.g., device **400**, FIG. **4**) with a touch-sensitive surface **551** (e.g., a tablet or touchpad **455**, FIG. **4**) that is separate from the display **550** (e.g., touch screen display **212**). Device **400** also, optionally, includes one or more contact intensity sensors (e.g., one or more of sensors **459**) for detecting intensity of contacts on touch-sensitive surface **551** and/or one or more tactile output generators **457** for generating tactile outputs for a user of device **400**.

[0183] Although some of the examples which follow will be given with reference to inputs on touch screen display **212** (where the touch-sensitive surface and the display are combined), in some embodiments, the device detects inputs on a touch-sensitive surface that is separate from the display, as shown in FIG. **5**B. In some embodiments, the touch-sensitive surface (e.g., **551** in FIG. **5**B) has a primary axis (e.g., **552** in FIG. **5**B) that corresponds to a primary axis (e.g., **553** in FIG. **5**B) on the display (e.g., **550**). In accordance with these embodiments, the device detects contacts (e.g., **560** and **562** in FIG. **5**B) with the touch-sensitive surface **551** at locations that correspond to respective locations on the display (e.g., in FIG. **5**B, **560** corresponds to **568** and **562** corresponds to **570**). In this way, user inputs (e.g., contacts **560** and **562**, and movements thereof) detected by the device on the touch-sensitive surface (e.g., **551** in FIG. **5**B) are used by the device to manipulate the user interface on the display (e.g., **550** in FIG. **5**B) of the multifunction device when the touch-sensitive surface is separate from the display. It should be understood that similar methods are, optionally, used for other user interfaces described herein.

[0184] Additionally, while the following examples are given primarily with reference to finger inputs (e.g., finger contacts, finger tap gestures, finger swipe gestures), it should be understood that, in some embodiments, one or more of the finger inputs are replaced with input from another input device (e.g., a mouse-based input or stylus input). For example, a swipe gesture is, optionally, replaced with a mouse click (e.g., instead of a contact) followed by movement of the cursor along the path of the swipe (e.g., instead of movement of the contact). As another example, a tap gesture is, optionally, replaced with a mouse click while the cursor is located over the location of the tap gesture (e.g., instead of detection of the contact followed by ceasing to detect the contact). Similarly, when multiple user inputs are simultaneously detected, it should be understood that multiple computer mice are, optionally, used simultaneously, or a mouse and finger contacts are, optionally, used simultaneously.

[0185] FIG. **6**A illustrates exemplary personal electronic device **600**. Device **600** includes body **602**. In some embodiments, device **600** includes some or all of the features described with respect to devices **200** and **400** (e.g., FIGS. **2**A-**4**). In some embodiments, device **600** has touch-sensitive display screen **604**, hereafter touch screen **604**. Alternatively, or in addition to touch screen **604**, device **600** has a display and a touch-sensitive surface. As with devices **200** and **400**, in some embodiments, touch screen **604** (or the touch-sensitive surface) has one or more intensity sensors for detecting intensity of contacts (e.g., touches) being applied. The one or more intensity sensors of touch screen **604** (or the touch-sensitive surface) provide output data that represents the intensity of touches. The user interface of device **600** responds to touches based on their intensity, meaning that touches of different intensities can invoke different user interface operations on device **600**.

[0186] Techniques for detecting and processing touch intensity are found, for example, in related applications: International Patent Application Serial No. PCT/US2013/040061, titled "Device, Method, and Graphical User Interface for Displaying User Interface Objects Corresponding to an Application," filed May 8, 2013, and International Patent Application Serial No. PCT/US2013/069483, titled "Device, Method, and Graphical User Interface for Transitioning Between Touch Input to Display Output Relationships," filed Nov. 11, 2013, each of which is hereby incorporated by reference in their entirety.

[0187] In some embodiments, device **600** has one or more input mechanisms **606** and **608**. Input mechanisms **606** and **608**, if included, are physical. Examples of physical input mechanisms include push buttons and rotatable mechanisms. In some embodiments, device **600** has one or more attachment mechanisms. Such attachment mechanisms, if included, can permit attachment of device **600** with, for example, hats, eyewear, earrings, necklaces, shirts, jackets, bracelets, watch straps, chains, trousers, belts, shoes, purses, backpacks, and so forth. These attachment mechanisms permit device **600** to be worn by a user.

[0188] FIG. **6**B depicts exemplary personal electronic device **600**. In some embodiments, device **600** includes some or all of the components described with respect to FIGS. **2**A, **2**B, and **4**. Device **600** has bus **612** that operatively couples I/O section **614** with one or more computer processors **616** and memory **618**. I/O section **614** is connected to display **604**, which can have touch-sensitive component **622** and, optionally, touch-intensity sensitive component **624**. In addition, I/O section **614** is connected with communication unit **630** for receiving application and operating system data, using Wi-Fi, Bluetooth, near field communication (NFC), cellular, and/or other wireless communication techniques. Device **600** includes input mechanisms **606** and/or **608**. Input mechanism **606** is a rotatable input device or a depressible and rotatable input device, for example. Input mechanism **608** is a button, in some examples.

[0189] Input mechanism **608** is a microphone, in some examples. Personal electronic device **600** includes, for example, various sensors, such as GPS sensor **632**, accelerometer **634**, directional sensor **640** (e.g., compass), gyroscope **636**, motion sensor **638**, and/or a combination thereof, all of which are operatively connected to I/O section **614**.

[0190] Memory **618** of personal electronic device **600** is a non-transitory computer-readable storage medium, for storing computer-executable instructions, which, when executed by one or more computer processors **616**, for example, cause the computer processors to perform the techniques and processes described below. The computer-executable instructions, for example, are also stored and/or transported within any non-transitory computer-readable storage medium for use by or in connection with an instruction execution system, apparatus, or device, such as a computer-based system, processor-containing system, or other system that can fetch the instructions from the instruction execution system, apparatus, or device and execute the instructions. Personal electronic device **600** is not limited to the components and configuration of FIG. **6**B, but can include other or additional components in multiple configurations.

[0191] As used here, the term "affordance" refers to a user-interactive graphical user interface object that is, for example, displayed on the display screen of devices **200**, **400**, and/or **600** (FIGS. **2**A, **4**, and **6**A-**6**B). For example, an image (e.g., icon), a button, and text (e.g., hyperlink) each constitutes an affordance.

[0192] As used herein, the term "focus selector" refers to an input element that indicates a current part of a user interface with which a user is interacting. In some implementations that include a cursor or other location marker, the cursor acts as a "focus selector" so that when an input (e.g., a press input) is detected on a touch-sensitive surface (e.g., touchpad **455** in FIG. **4** or touch-sensitive surface **551** in FIG. **5**B) while the cursor is over a particular user interface element (e.g., a button, window, slider or other user interface element), the particular user interface element is adjusted in accordance with the detected input. In some implementations that include a touch screen display (e.g., touch-sensitive display system **212** in FIG. **2**A or touch screen **212** in FIG. **5**A) that enables direct interaction with user interface elements on the touch screen display, a detected contact on the touch screen acts as a "focus selector" so that when an input (e.g., a press input by the contact) is detected on the touch screen display at a location of a particular user interface element (e.g., a button, window, slider, or other user interface element), the particular user interface element is adjusted in accordance with the detected input. In some implementations, focus is moved from one region of a user interface to another region of the user interface without corresponding movement of a cursor or movement of a contact on a touch screen display (e.g., by using a tab key or arrow keys to move focus from one button to another button); in these implementations, the focus selector moves in accordance with movement of focus between different regions of the user interface. Without regard to the specific form taken by the focus selector, the focus selector is generally the user interface element (or contact on a touch screen display) that is controlled by the user so as to communicate the user's intended interaction with the user interface (e.g., by indicating, to the device, the element of the user interface with which the user is intending to interact). For example, the location of a focus selector (e.g., a cursor, a contact, or a selection box) over a respective button while a press input is detected on the touch-sensitive surface (e.g., a touchpad or touch screen) will indicate that the user is intending to activate the respective button (as opposed to other user interface elements shown on a display of the device).

[0193] As used in the specification and claims, the term "characteristic intensity" of a contact refers to a character-

istic of the contact based on one or more intensities of the contact. In some embodiments, the characteristic intensity is based on multiple intensity samples. The characteristic intensity is, optionally, based on a predefined number of intensity samples, or a set of intensity samples collected during a predetermined time period (e.g., 0.05, 0.1, 0.2, 0.5, 1, 2, 5, 10 seconds) relative to a predefined event (e.g., after detecting the contact, prior to detecting liftoff of the contact, before or after detecting a start of movement of the contact, prior to detecting an end of the contact, before or after detecting an increase in intensity of the contact, and/or before or after detecting a decrease in intensity of the contact). A characteristic intensity of a contact is, optionally based on one or more of: a maximum value of the intensities of the contact, a mean value of the intensities of the contact, an average value of the intensities of the contact, a top 10 percentile value of the intensities of the contact, a value at the half maximum of the intensities of the contact, a value at the 90 percent maximum of the intensities of the contact, or the like. In some embodiments, the duration of the contact is used in determining the characteristic intensity (e.g., when the characteristic intensity is an average of the intensity of the contact over time). In some embodiments, the characteristic intensity is compared to a set of one or more intensity thresholds to determine whether an operation has been performed by a user. For example, the set of one or more intensity thresholds includes a first intensity threshold and a second intensity threshold. In this example, a contact with a characteristic intensity that does not exceed the first threshold results in a first operation, a contact with a characteristic intensity that exceeds the first intensity threshold and does not exceed the second intensity threshold results in a second operation, and a contact with a characteristic intensity that exceeds the second threshold results in a third operation. In some embodiments, a comparison between the characteristic intensity and one or more thresholds is used to determine whether or not to perform one or more operations (e.g., whether to perform a respective operation or forgo performing the respective operation) rather than being used to determine whether to perform a first operation or a second operation.

[0194] In some embodiments, a portion of a gesture is identified for purposes of determining a characteristic intensity. For example, a touch-sensitive surface receives a continuous swipe contact transitioning from a start location and reaching an end location, at which point the intensity of the contact increases. In this example, the characteristic intensity of the contact at the end location is based on only a portion of the continuous swipe contact, and not the entire swipe contact (e.g., only the portion of the swipe contact at the end location). In some embodiments, a smoothing algorithm is applied to the intensities of the swipe contact prior to determining the characteristic intensity of the contact. For example, the smoothing algorithm optionally includes one or more of: an unweighted sliding-average smoothing algorithm, a triangular smoothing algorithm, a median filter smoothing algorithm, and/or an exponential smoothing algorithm. In some circumstances, these smoothing algorithms eliminate narrow spikes or dips in the intensities of the swipe contact for purposes of determining a characteristic intensity.

[0195] The intensity of a contact on the touch-sensitive surface is characterized relative to one or more intensity thresholds, such as a contact-detection intensity threshold, a light press intensity threshold, a deep press intensity threshold, and/or one or more other intensity thresholds. In some embodiments, the light press intensity threshold corresponds to an intensity at which the device will perform operations typically associated with clicking a button of a physical mouse or a trackpad. In some embodiments, the deep press intensity threshold corresponds to an intensity at which the device will perform operations that are different from operations typically associated with clicking a button of a physical mouse or a trackpad. In some embodiments, when a contact is detected with a characteristic intensity below the light press intensity threshold (e.g., and above a nominal contact-detection intensity threshold below which the contact is no longer detected), the device will move a focus selector in accordance with movement of the contact on the touch-sensitive surface without performing an operation associated with the light press intensity threshold or the deep press intensity threshold. Generally, unless otherwise stated, these intensity thresholds are consistent between different sets of user interface figures.

[0196] An increase of characteristic intensity of the contact from an intensity below the light press intensity threshold to an intensity between the light press intensity threshold and the deep press intensity threshold is sometimes referred to as a "light press" input. An increase of characteristic intensity of the contact from an intensity below the deep press intensity threshold to an intensity above the deep press intensity threshold is sometimes referred to as a "deep press" input. An increase of characteristic intensity of the contact from an intensity below the contact-detection intensity threshold to an intensity between the contact-detection intensity threshold and the light press intensity threshold is sometimes referred to as detecting the contact on the touch-surface. A decrease of characteristic intensity of the contact from an intensity above the contact-detection intensity threshold to an intensity below the contact-detection intensity threshold is sometimes referred to as detecting liftoff of the contact from the touch-surface. In some embodiments, the contact-detection intensity threshold is zero. In some embodiments, the contact-detection intensity threshold is greater than zero.

[0197] In some embodiments described herein, one or more operations are performed in response to detecting a gesture that includes a respective press input or in response to detecting the respective press input performed with a respective contact (or a plurality of contacts), where the respective press input is detected based at least in part on detecting an increase in intensity of the contact (or plurality of contacts) above a press-input intensity threshold. In some embodiments, the respective operation is performed in response to detecting the increase in intensity of the respective contact above the press-input intensity threshold (e.g., a "down stroke" of the respective press input). In some embodiments, the press input includes an increase in intensity of the respective contact above the press-input intensity threshold and a subsequent decrease in intensity of the contact below the press-input intensity threshold, and the respective operation is performed in response to detecting the subsequent decrease in intensity of the respective contact below the press-input threshold (e.g., an "up stroke" of the respective press input).

[0198] In some embodiments, the device employs intensity hysteresis to avoid accidental inputs sometimes termed "jitter," where the device defines or selects a hysteresis

intensity threshold with a predefined relationship to the press-input intensity threshold (e.g., the hysteresis intensity threshold is X intensity units lower than the press-input intensity threshold or the hysteresis intensity threshold is 75%, 90%, or some reasonable proportion of the press-input intensity threshold). Thus, in some embodiments, the press input includes an increase in intensity of the respective contact above the press-input intensity threshold and a subsequent decrease in intensity of the contact below the hysteresis intensity threshold that corresponds to the press-input intensity threshold, and the respective operation is performed in response to detecting the subsequent decrease in intensity of the respective contact below the hysteresis intensity threshold (e.g., an "up stroke" of the respective press input). Similarly, in some embodiments, the press input is detected only when the device detects an increase in intensity of the contact from an intensity at or below the hysteresis intensity threshold to an intensity at or above the press-input intensity threshold and, optionally, a subsequent decrease in intensity of the contact to an intensity at or below the hysteresis intensity, and the respective operation is performed in response to detecting the press input (e.g., the increase in intensity of the contact or the decrease in intensity of the contact, depending on the circumstances).

[0199] For ease of explanation, the descriptions of operations performed in response to a press input associated with a press-input intensity threshold or in response to a gesture including the press input are, optionally, triggered in response to detecting either: an increase in intensity of a contact above the press-input intensity threshold, an increase in intensity of a contact from an intensity below the hysteresis intensity threshold to an intensity above the press-input intensity threshold, a decrease in intensity of the contact below the press-input intensity threshold, and/or a decrease in intensity of the contact below the hysteresis intensity threshold corresponding to the press-input intensity threshold. Additionally, in examples where an operation is described as being performed in response to detecting a decrease in intensity of a contact below the press-input intensity threshold, the operation is, optionally, performed in response to detecting a decrease in intensity of the contact below a hysteresis intensity threshold corresponding to, and lower than, the press-input intensity threshold.

3. Digital Assistant System

[0200] FIG. **7**A illustrates a block diagram of digital assistant system **700** in accordance with various examples. In some examples, digital assistant system **700** is implemented on a standalone computer system. In some examples, digital assistant system **700** is distributed across multiple computers. In some examples, some of the modules and functions of the digital assistant are divided into a server portion and a client portion, where the client portion resides on one or more user devices (e.g., devices **104**, **122**, **200**, **400**, or **600**) and communicates with the server portion (e.g., server system **108**) through one or more networks, e.g., as shown in FIG. **1**. In some examples, digital assistant system **700** is an implementation of server system **108** (and/or DA server **106**) shown in FIG. **1**. It should be noted that digital assistant system **700** is only one example of a digital assistant system, and that digital assistant system **700** can have more or fewer components than shown, can combine two or more components, or can have a different configuration or arrangement of the components. The various components shown in FIG. **7**A are implemented in hardware, software instructions for execution by one or more processors, firmware, including one or more signal processing and/or application specific integrated circuits, or a combination thereof.

[0201] Digital assistant system **700** includes memory **702**, one or more processors **704**, input/output (I/O) interface **706**, and network communications interface **708**. These components can communicate with one another over one or more communication buses or signal lines **710**.

[0202] In some examples, memory **702** includes a non-transitory computer-readable medium, such as high-speed random access memory and/or a non-volatile computer-readable storage medium (e.g., one or more magnetic disk storage devices, flash memory devices, or other non-volatile solid-state memory devices).

[0203] In some examples, I/O interface **706** couples input/output devices **716** of digital assistant system **700**, such as displays, keyboards, touch screens, and microphones, to user interface module **722**. I/O interface **706**, in conjunction with user interface module **722**, receives user inputs (e.g., voice input, keyboard inputs, touch inputs, etc.) and processes them accordingly. In some examples, e.g., when the digital assistant is implemented on a standalone user device, digital assistant system **700** includes any of the components and I/O communication interfaces described with respect to devices **200**, **400**, or **600** in FIGS. **2**A, **4**, **6**A-**6**B, respectively. In some examples, digital assistant system **700** represents the server portion of a digital assistant implementation, and can interact with the user through a client-side portion residing on a user device (e.g., devices **104**, **200**, **400**, or **600**).

[0204] In some examples, the network communications interface **708** includes wired communication port(s) **712** and/or wireless transmission and reception circuitry **714**. The wired communication port(s) receives and send communication signals via one or more wired interfaces, e.g., Ethernet, Universal Serial Bus (USB), FIREWIRE, etc. The wireless circuitry **714** receives and sends RF signals and/or optical signals from/to communications networks and other communications devices. The wireless communications use any of a plurality of communications standards, protocols, and technologies, such as GSM, EDGE, CDMA, TDMA, Bluetooth, Wi-Fi, VoIP, Wi-MAX, or any other suitable communication protocol. Network communications interface **708** enables communication between digital assistant system **700** with networks, such as the Internet, an intranet, and/or a wireless network, such as a cellular telephone network, a wireless local area network (LAN), and/or a metropolitan area network (MAN), and other devices.

[0205] In some examples, memory **702**, or the computer-readable storage media of memory **702**, stores programs, modules, instructions, and data structures including all or a subset of: operating system **718**, communications module **720**, user interface module **722**, one or more applications **724**, and digital assistant module **726**. In particular, memory **702**, or the computer-readable storage media of memory **702**, stores instructions for performing the processes described below. One or more processors **704** execute these programs, modules, and instructions, and reads/writes from/to the data structures.

[0206] Operating system **718** (e.g., Darwin, RTXC, LINUX, UNIX, iOS, OS X, WINDOWS, or an embedded operating system such as VxWorks) includes various software components and/or drivers for controlling and manag-

ing general system tasks (e.g., memory management, storage device control, power management, etc.) and facilitates communications between various hardware, firmware, and software components.

[0207] Communications module **720** facilitates communications between digital assistant system **700** with other devices over network communications interface **708**. For example, communications module **720** communicates with RF circuitry **208** of electronic devices such as devices **200**, **400**, and **600** shown in FIGS. **2**A, **4**, **6**A-**6**B, respectively. Communications module **720** also includes various components for handling data received by wireless circuitry **714** and/or wired communications port **712**.

[0208] User interface module **722** receives commands and/or inputs from a user via I/O interface **706** (e.g., from a keyboard, touch screen, pointing device, controller, and/or microphone), and generate user interface objects on a display. User interface module **722** also prepares and delivers outputs (e.g., speech, sound, animation, text, icons, vibrations, haptic feedback, light, etc.) to the user via the I/O interface **706** (e.g., through displays, audio channels, speakers, touch-pads, etc.).

[0209] Applications **724** include programs and/or modules that are configured to be executed by one or more processors **704**. For example, if the digital assistant system is implemented on a standalone user device, applications **724** include user applications, such as games, a calendar application, a navigation application, or an email application. If digital assistant system **700** is implemented on a server, applications **724** include resource management applications, diagnostic applications, or scheduling applications, for example.

[0210] Memory **702** also stores digital assistant module **726** (or the server portion of a digital assistant). In some examples, digital assistant module **726** includes the following sub-modules, or a subset or superset thereof: input/output processing module **728**, speech-to-text (STT) processing module **730**, natural language processing module **732**, dialogue flow processing module **734**, task flow processing module **736**, service processing module **738**, and speech synthesis processing module **740**. Each of these modules has access to one or more of the following systems or data and models of the digital assistant module **726**, or a subset or superset thereof: ontology **760**, vocabulary index **744**, user data **748**, task flow models **754**, service models **756**, and ASR systems **758**.

[0211] In some examples, using the processing modules, data, and models implemented in digital assistant module **726**, the digital assistant can perform at least some of the following: converting speech input into text; identifying a user's intent expressed in a natural language input received from the user; actively eliciting and obtaining information needed to fully infer the user's intent (e.g., by disambiguating words, games, intentions, etc.); determining the task flow for fulfilling the inferred intent; and executing the task flow to fulfill the inferred intent.

[0212] In some examples, as shown in FIG. **7**B, I/O processing module **728** interacts with the user through I/O devices **716** in FIG. **7**A or with a user device (e.g., devices **104**, **200**, **400**, or **600**) through network communications interface **708** in FIG. **7**A to obtain user input (e.g., a speech input) and to provide responses (e.g., as speech outputs) to the user input. I/O processing module **728** optionally obtains contextual information associated with the user input from the user device, along with or shortly after the receipt of the user input. The contextual information includes user-specific data, vocabulary, and/or preferences relevant to the user input. In some examples, the contextual information also includes software and hardware states of the user device at the time the user request is received, and/or information related to the surrounding environment of the user at the time that the user request was received. In some examples, I/O processing module **728** also sends follow-up questions to, and receive answers from, the user regarding the user request. When a user request is received by I/O processing module **728** and the user request includes speech input, I/O processing module **728** forwards the speech input to STT processing module **730** (or speech recognizer) for speech-to-text conversions.

[0213] STT processing module **730** includes one or more ASR systems **758**. The one or more ASR systems **758** can process the speech input that is received through I/O processing module **728** to produce a recognition result. Each ASR system **758** includes a front-end speech pre-processor. The front-end speech pre-processor extracts representative features from the speech input. For example, the front-end speech pre-processor performs a Fourier transform on the speech input to extract spectral features that characterize the speech input as a sequence of representative multi-dimensional vectors. Further, each ASR system **758** includes one or more speech recognition models (e.g., acoustic models and/or language models) and implements one or more speech recognition engines. Examples of speech recognition models include Hidden Markov Models, Gaussian-Mixture Models, Deep Neural Network Models, n-gram language models, and other statistical models. Examples of speech recognition engines include the dynamic time warping based engines and weighted finite-state transducers (WFST) based engines. The one or more speech recognition models and the one or more speech recognition engines are used to process the extracted representative features of the front-end speech pre-processor to produce intermediate recognitions results (e.g., phonemes, phonemic strings, and sub-words), and ultimately, text recognition results (e.g., words, word strings, or sequence of tokens). In some examples, the speech input is processed at least partially by a third-party service or on the user's device (e.g., device **104**, **200**, **400**, or **600**) to produce the recognition result. Once STT processing module **730** produces recognition results containing a text string (e.g., words, or sequence of words, or sequence of tokens), the recognition result is passed to natural language processing module **732** for intent deduction. In some examples, STT processing module **730** produces multiple candidate text representations of the speech input. Each candidate text representation is a sequence of words or tokens corresponding to the speech input. In some examples, each candidate text representation is associated with a speech recognition confidence score. Based on the speech recognition confidence scores, STT processing module **730** ranks the candidate text representations and provides the n-best (e.g., n highest ranked) candidate text representation(s) to natural language processing module **732** for intent deduction, where n is a predetermined integer greater than zero. For example, in one example, only the highest ranked (n=1) candidate text representation is passed to natural language processing module **732** for intent deduction. In another example, the

five highest ranked (n=5) candidate text representations are passed to natural language processing module **732** for intent deduction.

[0214] More details on the speech-to-text processing are described in U.S. Utility application Ser. No. 13/236,942 for "Consolidating Speech Recognition Results," filed on Sep. 20, 2011, the entire disclosure of which is incorporated herein by reference.

[0215] In some examples, STT processing module **730** includes and/or accesses a vocabulary of recognizable words via phonetic alphabet conversion module **731**. Each vocabulary word is associated with one or more candidate pronunciations of the word represented in a speech recognition phonetic alphabet. In particular, the vocabulary of recognizable words includes a word that is associated with a plurality of candidate pronunciations. For example, the vocabulary includes the word "tomato" that is associated with the candidate pronunciations of/tə'meɪɾoʊ /and /tə'mɑtoʊ /. Further, vocabulary words are associated with custom candidate pronunciations that are based on previous speech inputs from the user. Such custom candidate pronunciations are stored in STT processing module **730** and are associated with a particular user via the user's profile on the device. In some examples, the candidate pronunciations for words are determined based on the spelling of the word and one or more linguistic and/or phonetic rules. In some examples, the candidate pronunciations are manually generated, e.g., based on known canonical pronunciations.

[0216] In some examples, the candidate pronunciations are ranked based on the commonness of the candidate pronunciation. For example, the candidate pronunciation/ tə'meɪɾoʊ /is ranked higher than/tə'mɑtoʊ /, because the former is a more commonly used pronunciation (e.g., among all users, for users in a particular geographical region, or for any other appropriate subset of users). In some examples, candidate pronunciations are ranked based on whether the candidate pronunciation is a custom candidate pronunciation associated with the user. For example, custom candidate pronunciations are ranked higher than canonical candidate pronunciations. This can be useful for recognizing proper nouns having a unique pronunciation that deviates from canonical pronunciation. In some examples, candidate pronunciations are associated with one or more speech characteristics, such as geographic origin, nationality, or ethnicity. For example, the candidate pronunciation/tə'meɪɾoʊ /is associated with the United States, whereas the candidate pronunciation/tə'mɑtoʊ /is associated with Great Britain. Further, the rank of the candidate pronunciation is based on one or more characteristics (e.g., geographic origin, nationality, ethnicity, etc.) of the user stored in the user's profile on the device. For example, it can be determined from the user's profile that the user is associated with the United States. Based on the user being associated with the United States, the candidate pronunciation /tə'meɪɾoʊ /(associated with the United States) is ranked higher than the candidate pronunciation /tə'mɑtoʊ /(associated with Great Britain). In some examples, one of the ranked candidate pronunciations is selected as a predicted pronunciation (e.g., the most likely pronunciation).

[0217] When a speech input is received, STT processing module **730** is used to determine the phonemes corresponding to the speech input (e.g., using an acoustic model), and then attempt to determine words that match the phonemes (e.g., using a language model). For example, if STT processing module **730** first identifies the sequence of phonemes/tə'meɪɾoʊ /corresponding to a portion of the speech input, it can then determine, based on vocabulary index **744**, that this sequence corresponds to the word "tomato."

[0218] In some examples, STT processing module **730** uses approximate matching techniques to determine words in an utterance. Thus, for example, the STT processing module **730** determines that the sequence of phonemes/ tə'meɪɾoʊ /corresponds to the word "tomato," even if that particular sequence of phonemes is not one of the candidate sequence of phonemes for that word.

[0219] Natural language processing module **732** ("natural language processor") of the digital assistant takes the n-best candidate text representation(s) ("word sequence(s)" or "token sequence(s)") generated by STT processing module **730**, and attempts to associate each of the candidate text representations with one or more "actionable intents" recognized by the digital assistant. An "actionable intent" (or "user intent") represents a task that can be performed by the digital assistant, and can have an associated task flow implemented in task flow models **754**. The associated task flow is a series of programmed actions and steps that the digital assistant takes in order to perform the task. The scope of a digital assistant's capabilities is dependent on the number and variety of task flows that have been implemented and stored in task flow models **754**, or in other words, on the number and variety of "actionable intents" that the digital assistant recognizes. The effectiveness of the digital assistant, however, also dependents on the assistant's ability to infer the correct "actionable intent(s)" from the user request expressed in natural language.

[0220] In some examples, in addition to the sequence of words or tokens obtained from STT processing module **730**, natural language processing module **732** also receives contextual information associated with the user request, e.g., from I/O processing module **728**. The natural language processing module **732** optionally uses the contextual information to clarify, supplement, and/or further define the information contained in the candidate text representations received from STT processing module **730**. The contextual information includes, for example, user preferences, hardware, and/or software states of the user device, sensor information collected before, during, or shortly after the user request, prior interactions (e.g., dialogue) between the digital assistant and the user, and the like. As described herein, contextual information is, in some examples, dynamic, and changes with time, location, content of the dialogue, and other factors.

[0221] In some examples, the natural language processing is based on, e.g., ontology **760**. Ontology **760** is a hierarchical structure containing many nodes, each node representing either an "actionable intent" or a "property" relevant to one or more of the "actionable intents" or other "properties." As noted above, an "actionable intent" represents a task that the digital assistant is capable of performing, i.e., it is "actionable" or can be acted on. A "property" represents a parameter associated with an actionable intent or a sub-aspect of another property. A linkage between an actionable intent node and a property node in ontology **760** defines how a parameter represented by the property node pertains to the task represented by the actionable intent node.

[0222] In some examples, ontology **760** is made up of actionable intent nodes and property nodes. Within ontology **760**, each actionable intent node is linked to one or more

property nodes either directly or through one or more intermediate property nodes. Similarly, each property node is linked to one or more actionable intent nodes either directly or through one or more intermediate property nodes. For example, as shown in FIG. **7**C, ontology **760** includes a "restaurant reservation" node (i.e., an actionable intent node). Property nodes "restaurant," "date/time" (for the reservation), and "party size" are each directly linked to the actionable intent node (i.e., the "restaurant reservation" node).

[0223] In addition, property nodes "cuisine," "price range," "phone number," and "location" are sub-nodes of the property node "restaurant," and are each linked to the "restaurant reservation" node (i.e., the actionable intent node) through the intermediate property node "restaurant." For another example, as shown in FIG. **7**C, ontology **760** also includes a "set reminder" node (i.e., another actionable intent node). Property nodes "date/time" (for setting the reminder) and "subject" (for the reminder) are each linked to the "set reminder" node. Since the property "date/time" is relevant to both the task of making a restaurant reservation and the task of setting a reminder, the property node "date/time" is linked to both the "restaurant reservation" node and the "set reminder" node in ontology **760**.

[0224] An actionable intent node, along with its linked property nodes, is described as a "domain." In the present discussion, each domain is associated with a respective actionable intent, and refers to the group of nodes (and the relationships there between) associated with the particular actionable intent. For example, ontology **760** shown in FIG. **7**C includes an example of restaurant reservation domain **762** and an example of reminder domain **764** within ontology **760**. The restaurant reservation domain includes the actionable intent node "restaurant reservation," property nodes "restaurant," "date/time," and "party size," and sub-property nodes "cuisine," "price range," "phone number," and "location." Reminder domain **764** includes the actionable intent node "set reminder," and property nodes "subject" and "date/time." In some examples, ontology **760** is made up of many domains. Each domain shares one or more property nodes with one or more other domains. For example, the "date/time" property node is associated with many different domains (e.g., a scheduling domain, a travel reservation domain, a movie ticket domain, etc.), in addition to restaurant reservation domain **762** and reminder domain **764**.

[0225] While FIG. **7**C illustrates two example domains within ontology **760**, other domains include, for example, "find a movie," "initiate a phone call," "find directions," "schedule a meeting," "send a message," and "provide an answer to a question," "read a list," "providing navigation instructions," "provide instructions for a task" and so on. A "send a message" domain is associated with a "send a message" actionable intent node, and further includes property nodes such as "recipient(s)," "message type," and "message body." The property node "recipient" is further defined, for example, by the sub-property nodes such as "recipient name" and "message address."

[0226] In some examples, ontology **760** includes all the domains (and hence actionable intents) that the digital assistant is capable of understanding and acting upon. In some examples, ontology **760** is modified, such as by adding or removing entire domains or nodes, or by modifying relationships between the nodes within the ontology **760**.

[0227] In some examples, nodes associated with multiple related actionable intents are clustered under a "super domain" in ontology **760**. For example, a "travel" super-domain includes a cluster of property nodes and actionable intent nodes related to travel. The actionable intent nodes related to travel includes "airline reservation," "hotel reservation," "car rental," "get directions," "find points of interest," and so on. The actionable intent nodes under the same super domain (e.g., the "travel" super domain) have many property nodes in common. For example, the actionable intent nodes for "airline reservation," "hotel reservation," "car rental," "get directions," and "find points of interest" share one or more of the property nodes "start location," "destination," "departure date/time," "arrival date/time," and "party size."

[0228] In some examples, each node in ontology **760** is associated with a set of words and/or phrases that are relevant to the property or actionable intent represented by the node. The respective set of words and/or phrases associated with each node are the so-called "vocabulary" associated with the node. The respective set of words and/or phrases associated with each node are stored in vocabulary index **744** in association with the property or actionable intent represented by the node. For example, returning to FIG. **7**B, the vocabulary associated with the node for the property of "restaurant" includes words such as "food," "drinks," "cuisine," "hungry," "eat," "pizza," "fast food," "meal," and so on. For another example, the vocabulary associated with the node for the actionable intent of "initiate a phone call" includes words and phrases such as "call," "phone," "dial," "ring," "call this number," "make a call to," and so on. The vocabulary index **744** optionally includes words and phrases in different languages.

[0229] Natural language processing module **732** receives the candidate text representations (e.g., text string(s) or token sequence(s)) from STT processing module **730**, and for each candidate representation, determines what nodes are implicated by the words in the candidate text representation. In some examples, if a word or phrase in the candidate text representation is found to be associated with one or more nodes in ontology **760** (via vocabulary index **744**), the word or phrase "triggers" or "activates" those nodes. Based on the quantity and/or relative importance of the activated nodes, natural language processing module **732** selects one of the actionable intents as the task that the user intended the digital assistant to perform. In some examples, the domain that has the most "triggered" nodes is selected. In some examples, the domain having the highest confidence value (e.g., based on the relative importance of its various triggered nodes) is selected. In some examples, the domain is selected based on a combination of the number and the importance of the triggered nodes. In some examples, additional factors are considered in selecting the node as well, such as whether the digital assistant has previously correctly interpreted a similar request from a user.

[0230] User data **748** includes user-specific information, such as user-specific vocabulary, user preferences, user address, user's default and secondary languages, user's contact list, and other short-term or long-term information for each user. In some examples, natural language processing module **732** uses the user-specific information to supplement the information contained in the user input to further define the user intent. For example, for a user request "invite my friends to my birthday party," natural language process-

ing module **732** is able to access user data **748** to determine who the "friends" are and when and where the "birthday party" would be held, rather than requiring the user to provide such information explicitly in his/her request.

[0231] It should be recognized that in some examples, natural language processing module **732** is implemented using one or more machine learning mechanisms (e.g., neural networks). In particular, the one or more machine learning mechanisms are configured to receive a candidate text representation and contextual information associated with the candidate text representation. Based on the candidate text representation and the associated contextual information, the one or more machine learning mechanisms are configured to determine intent confidence scores over a set of candidate actionable intents. Natural language processing module **732** can select one or more candidate actionable intents from the set of candidate actionable intents based on the determined intent confidence scores. In some examples, an ontology (e.g., ontology **760**) is also used to select the one or more candidate actionable intents from the set of candidate actionable intents.

[0232] Other details of searching an ontology based on a token string are described in U.S. Utility application Ser. No. 12/341,743 for "Method and Apparatus for Searching Using An Active Ontology," filed Dec. 22, 2008, the entire disclosure of which is incorporated herein by reference.

[0233] In some examples, once natural language processing module **732** identifies an actionable intent (or domain) based on the user request, natural language processing module **732** generates a structured query to represent the identified actionable intent. In some examples, the structured query includes parameters for one or more nodes within the domain for the actionable intent, and at least some of the parameters are populated with the specific information and requirements specified in the user request. For example, the user says "Make me a dinner reservation at a sushi place at **7**." In this case, natural language processing module **732** is able to correctly identify the actionable intent to be "restaurant reservation" based on the user input. According to the ontology, a structured query for a "restaurant reservation" domain includes parameters such as {Cuisine}, {Time}, {Date}, {Party Size}, and the like. In some examples, based on the speech input and the text derived from the speech input using STT processing module **730**, natural language processing module **732** generates a partial structured query for the restaurant reservation domain, where the partial structured query includes the parameters {Cuisine="Sushi"} and {Time="7 pm"}. However, in this example, the user's utterance contains insufficient information to complete the structured query associated with the domain. Therefore, other necessary parameters such as {Party Size} and {Date} are not specified in the structured query based on the information currently available. In some examples, natural language processing module **732** populates some parameters of the structured query with received contextual information. For example, in some examples, if the user requested a sushi restaurant "near me," natural language processing module **732** populates a {location} parameter in the structured query with GPS coordinates from the user device.

[0234] In some examples, natural language processing module **732** identifies multiple candidate actionable intents for each candidate text representation received from STT processing module **730**. Further, in some examples, a respective structured query (partial or complete) is generated for each identified candidate actionable intent. Natural language processing module **732** determines an intent confidence score for each candidate actionable intent and ranks the candidate actionable intents based on the intent confidence scores. In some examples, natural language processing module **732** passes the generated structured query (or queries), including any completed parameters, to task flow processing module **736** ("task flow processor"). In some examples, the structured query (or queries) for the m-best (e.g., m highest ranked) candidate actionable intents are provided to task flow processing module **736**, where m is a predetermined integer greater than zero. In some examples, the structured query (or queries) for the m-best candidate actionable intents are provided to task flow processing module **736** with the corresponding candidate text representation(s).

[0235] Other details of inferring a user intent based on multiple candidate actionable intents determined from multiple candidate text representations of a speech input are described in U.S. Utility application Ser. No. 14/298,725 for "System and Method for Inferring User Intent From Speech Inputs," filed Jun. 6, 2014, the entire disclosure of which is incorporated herein by reference.

[0236] Task flow processing module **736** is configured to receive the structured query (or queries) from natural language processing module **732**, complete the structured query, if necessary, and perform the actions required to "complete" the user's ultimate request. In some examples, the various procedures necessary to complete these tasks are provided in task flow models **754**. In some examples, task flow models **754** include procedures for obtaining additional information from the user and task flows for performing actions associated with the actionable intent.

[0237] As described above, in order to complete a structured query, task flow processing module **736** needs to initiate additional dialogue with the user in order to obtain additional information, and/or disambiguate potentially ambiguous utterances. When such interactions are necessary, task flow processing module **736** invokes dialogue flow processing module **734** to engage in a dialogue with the user. In some examples, dialogue flow processing module **734** determines how (and/or when) to ask the user for the additional information and receives and processes the user responses. The questions are provided to and answers are received from the users through I/O processing module **728**. In some examples, dialogue flow processing module **734** presents dialogue output to the user via audio and/or visual output, and receives input from the user via spoken or physical (e.g., clicking) responses. Continuing with the example above, when task flow processing module **736** invokes dialogue flow processing module **734** to determine the "party size" and "date" information for the structured query associated with the domain "restaurant reservation," dialogue flow processing module **734** generates questions such as "For how many people?" and "On which day?" to pass to the user. Once answers are received from the user, dialogue flow processing module **734** then populates the structured query with the missing information, or pass the information to task flow processing module **736** to complete the missing information from the structured query.

[0238] Once task flow processing module **736** has completed the structured query for an actionable intent, task flow processing module **736** proceeds to perform the ultimate task associated with the actionable intent. Accordingly, task

flow processing module **736** executes the steps and instructions in the task flow model according to the specific parameters contained in the structured query. For example, the task flow model for the actionable intent of "restaurant reservation" includes steps and instructions for contacting a restaurant and actually requesting a reservation for a particular party size at a particular time. For example, using a structured query such as: {restaurant reservation, restaurant=ABC Café, date=3/12/2012, time=7 pm, party size=5}, task flow processing module **736** performs the steps of: (1) logging onto a server of the ABC Café or a restaurant reservation system such as OPENTABLE®, (2) entering the date, time, and party size information in a form on the website, (3) submitting the form, and (4) making a calendar entry for the reservation in the user's calendar.

[0239] In some examples, task flow processing module **736** employs the assistance of service processing module **738** ("service processing module") to complete a task requested in the user input or to provide an informational answer requested in the user input. For example, service processing module **738** acts on behalf of task flow processing module **736** to make a phone call, set a calendar entry, invoke a map search, invoke or interact with other user applications installed on the user device, and invoke or interact with third-party services (e.g., a restaurant reservation portal, a social networking website, a banking portal, etc.). In some examples, the protocols and application programming interfaces (API) required by each service are specified by a respective service model among service models **756**. Service processing module **738** accesses the appropriate service model for a service and generates requests for the service in accordance with the protocols and APIs required by the service according to the service model.

[0240] For example, if a restaurant has enabled an online reservation service, the restaurant submits a service model specifying the necessary parameters for making a reservation and the APIs for communicating the values of the necessary parameter to the online reservation service. When requested by task flow processing module **736**, service processing module **738** establishes a network connection with the online reservation service using the web address stored in the service model, and sends the necessary parameters of the reservation (e.g., time, date, party size) to the online reservation interface in a format according to the API of the online reservation service.

[0241] In some examples, natural language processing module **732**, dialogue flow processing module **734**, and task flow processing module **736** are used collectively and iteratively to infer and define the user's intent, obtain information to further clarify and refine the user intent, and finally generate a response (i.e., an output to the user, or the completion of a task) to fulfill the user's intent. The generated response is a dialogue response to the speech input that at least partially fulfills the user's intent. Further, in some examples, the generated response is output as a speech output. In these examples, the generated response is sent to speech synthesis processing module **740** (e.g., speech synthesizer) where it can be processed to synthesize the dialogue response in speech form. In yet other examples, the generated response is data content relevant to satisfying a user request in the speech input.

[0242] In examples where task flow processing module **736** receives multiple structured queries from natural language processing module **732**, task flow processing module **736** initially processes the first structured query of the received structured queries to attempt to complete the first structured query and/or execute one or more tasks or actions represented by the first structured query. In some examples, the first structured query corresponds to the highest ranked actionable intent. In other examples, the first structured query is selected from the received structured queries based on a combination of the corresponding speech recognition confidence scores and the corresponding intent confidence scores. In some examples, if task flow processing module **736** encounters an error during processing of the first structured query (e.g., due to an inability to determine a necessary parameter), the task flow processing module **736** can proceed to select and process a second structured query of the received structured queries that corresponds to a lower ranked actionable intent. The second structured query is selected, for example, based on the speech recognition confidence score of the corresponding candidate text representation, the intent confidence score of the corresponding candidate actionable intent, a missing necessary parameter in the first structured query, or any combination thereof.

[0243] Speech synthesis processing module **740** is configured to synthesize speech outputs for presentation to the user. Speech synthesis processing module **740** synthesizes speech outputs based on text provided by the digital assistant. For example, the generated dialogue response is in the form of a text string. Speech synthesis processing module **740** converts the text string to an audible speech output. Speech synthesis processing module **740** uses any appropriate speech synthesis technique in order to generate speech outputs from text, including, but not limited, to concatenative synthesis, unit selection synthesis, diphone synthesis, domain-specific synthesis, formant synthesis, articulatory synthesis, hidden Markov model (HMM) based synthesis, and sinewave synthesis. In some examples, speech synthesis processing module **740** is configured to synthesize individual words based on phonemic strings corresponding to the words. For example, a phonemic string is associated with a word in the generated dialogue response. The phonemic string is stored in metadata associated with the word. Speech synthesis processing module **740** is configured to directly process the phonemic string in the metadata to synthesize the word in speech form.

[0244] In some examples, instead of (or in addition to) using speech synthesis processing module **740**, speech synthesis is performed on a remote device (e.g., the server system **108**), and the synthesized speech is sent to the user device for output to the user. For example, this can occur in some implementations where outputs for a digital assistant are generated at a server system. And because server systems generally have more processing power or resources than a user device, it is possible to obtain higher quality speech outputs than would be practical with client-side synthesis.

[0245] Additional details on digital assistants can be found in the U.S. Utility application Ser. No. 12/987,982, entitled "Intelligent Automated Assistant," filed Jan. 10, 2011, and U.S. Utility application Ser. No. 13/251,088, entitled "Generating and Processing Task Items That Represent Tasks to Perform," filed Sep. 30, 2011, the entire disclosures of which are incorporated herein by reference.

4. Designating, Locating and Controlling Home-Automation Devices

[0246] FIGS. **8**A-**8**D include a series of illustrations showing how a user can designate a location and name for a home

automation device. FIG. **8**A shows a user interface **800** running on an electronic device that assists a user in identifying a location of one or more home automation devices. In particular, user interface **800** overlays digital content over real-world content that can include home automation devices. In the example displayed in FIG. **8**A, the real-world content includes desk lamp **802** and smart speaker **804** sitting atop desk **806**. The digital content includes designation tags **808-812** corresponding to home automation devices that share a geographical area with the electronic device displaying user interface **800**. Designation tags **808-812** can be created or established when a user adds home automation devices to a home automation platform running on a local data network, such as a Wi-Fi network and/or through cloud-based services. In some embodiments, the initial addition of the home automation devices to the home automation platform can include a designation of an area or room of a home or building in which the smart device is intended to be operated, which can then be associated with its respective designation tag. Many home automation platforms require a user to specify a room designation when adding home automation devices to a platform. Examples of home automation platforms include Apple HomeKit®, Google Home, Philips Hue® and the like. While home automation devices are often added manually to a home automation platform, devices can also be configured to join or initiate a joining process for a home automation platform in response to certain stimuli. For example, a home automation device can be configured to join the home automation system when first powered on or activated. In some embodiments, a general location of the home automation device can also be determined automatically based on the signal strength and/or direction of arrival of wireless signals being emitted by other home automation devices operating from known locations.

[0247] As depicted, designation tags **808-812** can include designation information helping a user to identify the home automation device a respective designation tag is associated with. In some embodiments, the designation information can initially correspond to a generic designation established by a manufacturer of the home automation device. Designation tags **808-812** can be located in a corner of user interface **800** when a location of the home automation devices associated with designation tags **808-812** are not currently located within user interface **800** or when a user has not yet identified the location of the home automation devices associated with designation tags **808-812**. While a corner location is depicted in FIG. **8**A, it should be appreciated that any peripheral portion of a user's field of view could be used to store designation tags **808-812**.

[0248] A designation region **814** of user interface **800** is identified by a digital shaded region overlayed on the real-world content. Designation region **814** allows a user to visually designate real-world or virtual content the user wishes to interact with and/or designate. Designation region **814** is generally translucent to prevent designation region **814** from obscuring visibility of the real-world content. While designation region **814** is identified as a shaded region it should be appreciated that designation region **814** can take other forms. For example, designation region can also be designated by a dashed box or a colored overlay. A size of designation region **814** can also vary. In certain cases, a smaller designation region **814** can be advantageous as it can provide more accuracy with regards to what real-world content is intended to be accessed but the smaller area can also be frustrating to a user if made so small that it become challenging to position and/or see the designation region **808** on the desired real-world or virtual content.

[0249] A location of designation region **814** can be positioned in different ways. In FIGS. **8**A-**8**D, a location of designation region **814** within user interface **800** remains centered within user interface **800**. As illustrated in FIG. **8**B, for a user to designate or identify desk lamp **802** with designation region **814**, the user would generally shift an orientation of the electronic device displaying user interface **800** in order to position designation region **814** over desk lamp **802**. Shifting the orientation of the electronic device results in a shift in the real-world content displayed within user interface **800** because imaging devices of the electronic device do not generally include mechanisms for independently orienting their field of view and are instead reliant on reorientation of the electronic device itself to establish a desired field of view for real-world content.

[0250] Once designation region **814** is positioned over a desired real-world object, a user can issue a voice command designating various details to be associated with the real-world object in the real-world object's designation tag. In the event the user wishes to designate a home automation device corresponding to one of designation tags **808-812**, the user can include the designation information displayed on a respective one of the designation tags in the voice command. A voice command designating desk lamp **802** as corresponding to designation tag **808** can be, e.g., "Light 1 is located here," "Light 1 is here," "This is Light 1," or "Here is Light 1". It should be appreciated these exemplary commands are not the only way to make this designation and that the digital assistant can also recognize and apply similar voice commands leveraging natural language processing and/or alternative pre-defined voice command recognition phrases.

[0251] After receiving the voice command designating desk lamp **802** as corresponding to designation tag **808**, a location of light 1 is defined in three dimensional space as shown in FIG. **8**C based on the present position of designation region **814**. The electronic device can identify a precise location of the home automation device designated using on-board sensors of the electronic device. In some embodiments, on-board sensors of the electronic device include one or more positioning and orientation sensors, such as GPS modules, magnetometers and gyroscopes that help the electronic device continuously track its own position within a three dimensional space. In some embodiments, the electronic device can use raycasting techniques to identify a location of a designated home automation device. The racycasting techniques can also be augmented when the electronic device includes one or more ranging sensors such as a LIDAR (light detection and ranging) sensor that is capable of precisely determining a distance between the electronic device and other nearby objects. Range information for a home automation device can also be determined using received signal strength (RSSI) based on Wi-Fi and/or Bluetooth signals sensed by the home automation device or by using information provided by an ultrawideband processor responsible for providing a location of a particular device. When the voice command to locate Light 1 is issued, the electronic device can be configured to leverage raycasting techniques and the LIDAR sensor, which emits infrared light at real-world objects located within designation region

814, to determine a location of the real-world object within designation region **814**. Infrared light reflected back at the LIDAR sensor can be used to determine a precise distance to the home automation device, which when combined with the location of the electronic device, can be used to determine a position of the home automation in three dimensional space.

[0252] FIG. **8**C also shows how designation tag **808** can be located directly over desk lamp **802**. Because a location in three dimensional space of desk lamp **802** is now determined, a user can walk around desk lamp **802** and designation tag **808** will remain in place over desk lamp **802** regardless of a relative orientation between the electronic device and desk lamp **802**. In some embodiments, the electronic device may provide a warning to the user if the electronic device determines using one of its onboard sensors that the correlation may be incorrect the user can receive a warning. For example, if the LIDAR sensor determines a shape of the device is inconsistent with manufacturer information about the device the warning message can be provided. In some embodiments, the warning can include the reason behind the potential correlation mistake.

[0253] FIG. **8**D shows how designation information associated with designation tag **808** can be updated to include information that more intuitively identifies a particular home automation device. Updating the name of the home automation device can be performed in many different ways. With designation region **814** located above designation tag **808** a user does not need to identify the tag when using a voice command to update the designation information of designation tag **808**. For example, a user could issue a voice command stating "Change the designation of this device to Desk Lamp" or "Rename this device as Desk Lamp". If the user did not position designation tag **808** within designation region **814** a change in the designation could still be effected but a user would typically be required to provide both the existing designation for designation tag **808** and the new name or designation information desired to designation tag **808**. It should be noted that this interface can also be configured to change or update other information about a respective device and the designation information can include other information such as manufacturer name or other specifications that a user may or may not decide to have displayed in a designation tag.

[0254] FIGS. **9**A-**9**D illustrate how a process similar to the one illustrated in FIGS. **8**A-**8**D leveraging a modified method of designation. In particular, FIG. **9**A shows a user interface **900** that includes desk lamp **802** and smart speaker **804** positioned on desk **806**. In this exemplary embodiment, a location of desk lamp **802** has already been designated and designation information associated with designation tag **802** has been customized to refer to it as desk light. User interface **900** differs from user interface **800** since it is able to monitor and track eye movement of a user of the electronic device on which it runs. This allows for movement of designation region **902** without any reorientation of the electronic device displaying user interface **900**. Eye tracking can be performed by one or more gaze tracking sensors on the electronic device that can take the form of infrared or RGB based sensors. Infrared sensors are typically used to perform fovea-tracking while RGB based sensors typically rely on machine learning techniques to determine a user's gaze based on pupil movement. In either case, the gaze tracking sensors are positioned on the electronic device in a manner allowing them line of sight to the user's eyes. This type of sensor configuration would generally be employed on a device configured to be head-mounted.

[0255] FIG. **9**B shows how designation region **902** can be moved to designate smart speaker **804** without changing what real-world content is currently located within a field of view provided by user interface **900**. It should be noted that while a shape of designation region **902** is different from designation region **814**, in some configurations it can be desirable to maintain the designation region size and shape regardless of weather foveal tracking is enabled. In other embodiments, it may be advantageous to change the shape and/or size of the designation region depending on whether foveal tracking is enabled. The change in shape can help a user quickly determine whether the tracking feature is activated so that a user is not left wondering whether there is a problem with the foveal tracking feature. Furthermore, a size of the designation region can vary as a user may need a smaller or larger region for designation depending on how steady they can keep their eyes oriented and/or how steady they can maintain the orientation of the electronic device displaying the user interface.

[0256] FIGS. **9**C and **9**D illustrate in a similar manner to FIGS. **8**C-**8**D how a designation tag is positioned over the designated automation device, smart speaker **804** and then renamed from device **2** to office speaker. FIGS. **9**C-**9**D also illustrate how multiple designation tags can be present and track a position of multiple automation devices within a particular field of view of the electronic device displaying user interface **900**. As depicted in user interface **900**, designation tag **810**, generically marked as light 2 as either not yet designated or not within the field of view visible in user interface **900**. In the event, a user turned the electronic device away from desk lamp **802** and smart speaker **804**, designation tags **808** and **812** would return to the upper corner until desk lamp **802** and smart speaker **804** came back into the frame. This allows a user to keep track of nearby automation devices regardless of whether they are present within the user interface.

[0257] FIGS. **10**A-**10**D show a series of illustrations showing methods for controlling a home automation device using a user interface **1000** displayed by an electronic device. In particular and as shown in FIG. **10**A, placing designation region **1002** over designation tag **808** results in the display of visual indicium **1004**, which graphically illustrates at least one operating parameter of desk lamp **802**. In the depicted embodiment, visual indicium **1004** indicates an intensity of light being emitted by desk lamp **802** both in terms of a visual meter and a number that provides an intensity value representing the amount of light emitted by desk lamp **802**. Other exemplary visual indicium could include a color picker for desk lamp **802**, where the color picker shows a range of selectable colors capable of display by desk lamp **802**. Furthermore, a visual indicium for smart speaker **804** (not depicted) could include a volume control and/or a audio equalizer. A smart speaker device that includes multiple discrete speakers could allow for cycling through controls for each speaker making up the smart speaker device.

[0258] FIG. **10**B shows how the use of a hand gesture can be implemented to effect a change in the parameter depicted by visual indicium **1004**. The exemplary hand gesture depicted in FIG. **10**B can be referred to as a pinch gesture and is recognized when the electronic device displaying user

interface **1000** detects a user's forefinger contacting a user's thumb. Recognition of the hand gesture can be indicated by a shaded region **1006** appearing in the field of view and is useful for informing a user that further movement of the user's hand can effect changes to the parameter depicted by visual indicium **1004**. Shaded region **1006** can also include text describing either the type of gesture recognized and/or the parameter being adjusted by the gesture. While shaded region **1006** is depicted at a top side of the field of view it could also be located in other portions of the screen and/or simply be a tinted background to reflect activation of changes in the operating parameter or state. As depicted, the parameter gets changed in accordance with a location where the user's thumber and forefinger meet. In some embodiments, the use of other types of hand gestures can allow a user to adjust different operating parameters. In some embodiments, a user can use a different hand gesture to adjust each available adjustable operating parameter. In some embodiments, a first hand gesture is used for adjusting an active operating parameter and a second hand gesture can be used specifically for selecting which operating parameter to make the active operating parameter. For example, the second hand gesture can be used to retrieve a list of adjustable attributes from which the user can select using either voice or gesture based commands. Upon selection of the new adjustable attribute the first hand gesture can be used to make adjustment to the newly selected adjustable attribute. More complex home automation devices such as smart televisions and refrigerators can have a broad variety of adjustable operating parameters making a mechanism for efficiently sorting through various available parameters important.

[0259] FIG. **10**C shows how moving the hand gesture up vertically results in a visual change to the meter and numeric identifier of visual indicium **1004**. FIG. **10**D shows how separation of the user's forefinger and thumb results in the electronic device ceasing to recognize the gesture and ceasing further changes to the value identified by visual indicium **1004** and removal of shaded region **1006** so that the user has positive feedback that no further changes will be made in response to movement of the user's hand. Another way of ending adjustment to the operating parameter would be to remove designation region **1002** from designation tag **808**. Removal of designation region **1002** from designation tag **808** will also result in the removal of visual indicium **1004**. Additional hand gestures recognizable by the electronic device can include a gesture in which a user places a flat hand with all fingers aligned together in a field of view of the sensor responsible for detecting real-world content and then initiating the gesture by spreading the fingers apart. Movement of the hand horizontally can effect changes in an active operating parameter.

[0260] FIG. **11** shows a floor layout **1100** for an exemplary home utilizing multiple home automation devices. In this exemplary embodiment, each home automation device will take the form of a smart bulb; however, it should be appreciated that a home can include any number of different types of home automation devices and the focus on lighting is not meant to narrow the scope of the described embodiments. Floor layout **1100** includes multiple rooms, including rooms **1102-1116**. Each of the rooms includes at least one home automation device. In particular, living room **1102** includes three smart bulbs **1118-1122** and kitchen **1104** includes smart bulb **1124**. In the event a user is trying to operate and/or change operating settings of one or more of the smart bulbs trying to depict designation tags for each of the smart bulbs in an entirety of the house represented by floor layout **1100** can be overwhelming and degrade the overall user experience since devices hidden behind a wall could still wind up being displayed to a user.

[0261] In some embodiments, an electronic device displaying one of the exemplary user interfaces depicted in FIGS. **8**A-**10**D, can be configured to omit designation tags for any home automation devices located outside a room currently occupied by a user. This filtering process can be based on the electronic device having access to mapping information for the house and being capable of determining the location of each room in the house. This mapping information could be created manually by a user or at least in part in an automated manner by on-board sensors of the electronic device as a user walks around a home or business. In some embodiments, the electronic device could allow for the display of designation tags for home automation devices located in multiple rooms. For example, in a house with an open floor plan design a user might have line of site to home automation devices in multiple rooms at once. A user positioned in kitchen **1104** could reasonably be effected by the operation of smart bulbs **1118-1122** in addition to the smart bulb **1124**. For at least this reason, the electronic device could also be configured to capture sensor data from a sensor that allows it to characterize the presence of various obstructions, such as walls in the house and instead of basing the list of available designation tags only to the room a user occupies it could also make the filtering determination based on whether the electronic device can determine whether the user has a clear line of site to a respective home automation device. For example, a user occupying bedroom **1110** would only see a designation tag for home automation devices located in bedroom **1110** since it's walls effectively preclude line of site to any of the other home automation devices depicted within floor layout **1100**. In some embodiments, instead of completely omitting home automation devices outside of line of site designation tags for devices out of line of site could instead be dimmed and not readily selectable when a designation region is placed over it. In this way, a user could still use the dimmed designation tags to locate a home automation device located in another room.

[0262] It should be noted that the aforementioned embodiments can be implemented using an electronic device similar to the aforementioned portable multi-function device **200**. Implementing the user interface depicted in FIGS. **8**A-**8**D the electronic device could be interacted with in a handheld position or alternatively in a head-mounted position. Since portable multi-function device **200** is described as including optical sensors **264** on both the front and rear of portable multi-function device **200**, optical sensors **264** could be configured to display the mixed reality user interfaces shown in any of FIGS. **8**A-**10**D. In the particular case of the user interface depicted in FIGS. **9**A-**9**D the front-facing optical sensor **264** can be used to track eye movement of a user to allow for the steering of the designation region by eye movement alone. It should also be appreciated that other types of electronic devices can implement the user interfaces shown in FIGS. **8**A-**10**D. In particular, the electronic device can also take the form of a more traditional virtual reality (VR) or augmented reality (AR) device designed to be head mounted and worn over a user's eyes. These types of devices often include multiple world-facing optical sensors capable

of monitoring a user's surroundings and providing the user with a broad field of view to observe the user's surroundings. In VR embodiments, a display of the electronic device shows a video feed of the user's surroundings as recorded by one or more optical sensors overlayed by virtual content while in AR embodiments the display is translucent and allows a user to view the user's surroundings with their own eyes and overlays virtual content over the user's surroundings. The optical sensors of a respective electronic device can also include one or more infrared or RGB sensors for monitoring eye movement of a user. Eye movement data generated by these sensors allows for movement of a designation region in accordance with movement of a user's eyes as depicted in FIGS. **9**A-**9**D. The aforementioned portable multi-function device **200**, which can take the form of a smartphone or tablet device can also operate as mixed reality device. This application provides multiple examples of what components are typically included in an exemplary portable multifunction electronic device that can take the form of at least a tablet or smartphone device. See FIGS. **3** and **5**A-**6**A along with their accompanying description. Each of these devices could be broadly characterized as an extended reality (XR) device when running any of the user interfaces depicted in FIGS. **8**A-**10**D. An XR device generally refers to a device capable of combining real and virtual environments and is generally deemed to include virtual reality, mixed reality and virtual reality devices.

[0263] FIG. **12** illustrates a process **1200** for interacting with and making changes to a home automation device. At step **1202**, designators for home automation devices are displayed by a portable electronic device in a three dimensional space viewable using the portable electronic device. The home automation devices share a geographical area with the portable electronic device, where the geographical area generally includes devices within a predetermined distance or within a predefined area and movement of the user can change which designators are displayed to the user. At step **1204** a first input is detected at the portable electronic device that selects a home automation device. Selection of the home automation device is generally performed by selecting a designation tag associated with a home automation device however, the home automation device selection could also be performed by a voice command that includes a name or designator of the home automation device.

[0264] At step **1206**, a visual indicium representing a current state or attribute value of the selected home automation device is displayed to the user in response to the selection of the home automation device. The visual indicium is generally depicted proximate or adjacent to the home automation device. At step **1208**, a second input is received that includes a gesture input, where the gesture input is recognized by the electronic device as a request to initiate a change in state of the home automation device. In some embodiments, the electronic device can be configured to receive multiple different types of gesture inputs that have different effects on the selected home automation device.

[0265] At step **1210**, the visual indicium is updated to represent the requested change in state of the home automation device. In some embodiments the change in visual indicium is performed in real time as the user moves the gesture within a field of view of the electronic device. At step **1212**, a control signal directing the requested change in the state of the home automation device is transmitted. In some embodiments, multiple control signals can be sent so that changes to the state of the home automation device are manifested while the second input is being provided. In other embodiments, changes are only made after completion of the second input. The control signal or signals can be sent either directly to the home automation device in question via some form of near field communication or routed through a home automation platform such as, e.g. Apple HomeKit®, Google Home™, Samsung SmartThings™, etc.

[0266] FIG. **13** illustrates a process **1300** for identifying and locating a home automation device. At step **1302**, receiving at a portable electronic device, a first user input indicating a location and designation of an electronic device separate from the portable electronic device. The user input is typically a multimodal input that includes both a gesture based selection for identifying a location of the electronic device and a voice command for indicating a designation for the electronic device. The portable electronic device will typically take the form of an extended reality (XR) device. At step **1304**, displaying the designation information for the electronic device in a three dimensional space viewable using the portable electronic device. The designation information can be a user-defined name that helps a user identify the portable electronic device in the future. The electronic device can be a home automation device such as a smart bulb, smart speaker, smart TV, smart refrigerator, smart door lock, or the like. The described embodiments could also be applied to registration and localization of other electronic devices not used specifically for home automation. At step **1306**, a second input is received that requests a change in state of the electronic device. The requested change of state is described in greater detail in the material accompanying FIGS. **10**A-**10**D and **12**.

[0267] The operations described above with reference to FIGS. **12** and **13** are optionally implemented by components depicted in FIGS. **1-4**, **6**A-**6**B, and **7**A-**7**C. It would be clear to a person having ordinary skill in the art how other processes are implemented based on the components depicted in FIGS. **1-4**, **6**A-**6**B, and **7**A-**7**C.

[0268] In accordance with some implementations, a computer-readable storage medium (e.g., a non-transitory computer readable storage medium) is provided, the computer-readable storage medium storing one or more programs for execution by one or more processors of an electronic device, the one or more programs including instructions for performing any of the methods or processes described herein.

[0269] In accordance with some implementations, an electronic device (e.g., a portable electronic device) is provided that comprises means for performing any of the methods or processes described herein.

[0270] In accordance with some implementations, an electronic device (e.g., a portable electronic device) is provided that comprises a processing unit configured to perform any of the methods or processes described herein.

[0271] In accordance with some implementations, an electronic device (e.g., a portable electronic device) is provided that comprises one or more processors and memory storing one or more programs for execution by the one or more processors, the one or more programs including instructions for performing any of the methods or processes described herein.

[0272] The foregoing description, for purpose of explanation, has been described with reference to specific embodiments. However, the illustrative discussions above are not

intended to be exhaustive or to limit the invention to the precise forms disclosed. Many modifications and variations are possible in view of the above teachings. The embodiments were chosen and described in order to best explain the principles of the techniques and their practical applications. Others skilled in the art are thereby enabled to best utilize the techniques and various embodiments with various modifications as are suited to the particular use contemplated.

[0273] Although the disclosure and examples have been fully described with reference to the accompanying drawings, it is to be noted that various changes and modifications will become apparent to those skilled in the art. Such changes and modifications are to be understood as being included within the scope of the disclosure and examples as defined by the claims.

[0274] As described above, one aspect of the present technology is the gathering and use of data available from various sources to improve a speed with which a user is able to access certain functionality through a digital assistant running on an electronic device. The present disclosure contemplates that in some instances, this gathered data may include personal information data that uniquely identifies or can be used to contact or locate a specific person. Such personal information data can include demographic data, location-based data, telephone numbers, email addresses, twitter IDs, home addresses, data or records relating to a user's health or level of fitness (e.g., vital signs measurements, medication information, exercise information), date of birth, or any other identifying or personal information.

[0275] The present disclosure recognizes that the use of such personal information data, in the present technology, can be used to the benefit of users. For example, the personal information data can be used to deliver targeted voice-activated shortcuts that are of greater applicability to functionality available through applications installed on an electronic device. Accordingly, use of such personal information data enables users to calculated control of the delivered content. Further, other uses for personal information data that benefit the user are also contemplated by the present disclosure. For instance, health and fitness data may be used to provide insights into a user's general wellness, or may be used as positive feedback to individuals using technology to pursue wellness goals.

[0276] The present disclosure contemplates that the entities responsible for the collection, analysis, disclosure, transfer, storage, or other use of such personal information data will comply with well-established privacy policies and/or privacy practices. In particular, such entities should implement and consistently use privacy policies and practices that are generally recognized as meeting or exceeding industry or governmental requirements for maintaining personal information data private and secure. Such policies should be easily accessible by users, and should be updated as the collection and/or use of data changes. Personal information from users should be collected for legitimate and reasonable uses of the entity and not shared or sold outside of those legitimate uses. Further, such collection/sharing should occur after receiving the informed consent of the users. Additionally, such entities should consider taking any needed steps for safeguarding and securing access to such personal information data and ensuring that others with access to the personal information data adhere to their privacy policies and procedures. Further, such entities can subject themselves to evaluation by third parties to certify their adherence to widely accepted privacy policies and practices. In addition, policies and practices should be adapted for the particular types of personal information data being collected and/or accessed and adapted to applicable laws and standards, including jurisdiction-specific considerations. For instance, in the US, collection of or access to certain health data may be governed by federal and/or state laws, such as the Health Insurance Portability and Accountability Act (HIPAA); whereas health data in other countries may be subject to other regulations and policies and should be handled accordingly. Hence different privacy practices should be maintained for different personal data types in each country.

[0277] Despite the foregoing, the present disclosure also contemplates embodiments in which users selectively block the use of, or access to, personal information data. That is, the present disclosure contemplates that hardware and/or software elements can be provided to prevent or block access to such personal information data. For example, in the case of data input into an application and then used to subsequently generate voice-activated shortcuts, the present technology can be configured to allow users to select to "opt in" or "opt out" of participation in the collection of personal information data during registration for services or anytime thereafter. In another example, users can select not to provide data for targeted voice-activated shortcut creation. In yet another example, users can select to limit the length of time user-specific shortcut data is maintained or entirely prohibit the development of a baseline set of voice-activated shortcuts associated with a particular user. In addition to providing "opt in" and "opt out" options, the present disclosure contemplates providing notifications relating to the access or use of personal information. For instance, a user may be notified upon downloading an app that their personal information data will be accessed and then reminded again just before personal information data is accessed by the app.

[0278] Moreover, it is the intent of the present disclosure that personal information data should be managed and handled in a way to minimize risks of unintentional or unauthorized access or use. Risk can be minimized by limiting the collection of data and deleting data once it is no longer needed. In addition, and when applicable, including in certain health related applications, data de-identification can be used to protect a user's privacy. De-identification may be facilitated, when appropriate, by removing specific identifiers (e.g., date of birth, etc.), controlling the amount or specificity of data stored (e.g., collecting location data at a city level rather than at an address level), controlling how data is stored (e.g., aggregating data across users), and/or other methods.

[0279] Therefore, although the present disclosure broadly covers use of personal information data to implement one or more various disclosed embodiments, the present disclosure also contemplates that the various embodiments can also be implemented without the need for accessing such personal information data. That is, the various embodiments of the present technology are not rendered inoperable due to the lack of all or a portion of such personal information data. For example, voice-activated shortcuts can be established based on typical use of an applications entire user base while minimizing the amount of personal information relied upon and collected by application developers.

1. A method, comprising:

at a portable electronic device:

displaying designators for a plurality of home automation devices in a three dimensional space viewable using the portable electronic device, wherein the plurality of home automation devices share a geographical area with the portable electronic device;

detecting a first input selecting a home automation device of the plurality of home automation devices;

in response to receiving the first input, displaying a visual indicium within the three dimensional space, wherein the visual indicium represents a current state of the home automation device, and wherein the display of the visual indicium occupies a first area;

receiving a hand gesture input performed by a hand, wherein the hand gesture input requests a change in the current state of the home automation device;

in response to receiving the hand gesture input, displaying an overlay within the three dimensional space, wherein at least a portion of the overlay occupies a second area different from the first area, and wherein the overlay includes a description of a parameter to be adjusted by the hand gesture input;

while displaying the overlay:

detecting movement of the hand; and

updating, based on the movement of the hand, the visual indicium to represent the requested change in the current state of the home automation device; and

transmitting a control signal directing the requested change in the current state of the home automation device.

2. The method of claim 1, wherein updating the visual indicium comprises updating the visual indicium concurrently with the change in the current state of the home automation device.

3. The method of claim 1, wherein the requested change in the current state of the home automation device is a change in a volume parameter of the home automation device.

4. The method of claim 1, wherein the current state of the home automation device is governed by a plurality of operating parameters and wherein the requested change in state corresponds to a change in a first operating parameter of the plurality of operating parameters.

5. The method of claim 4, further comprising:

receiving a second hand gesture input requesting a change in a second operating parameter of the plurality of operating parameters, wherein the second hand gesture input is different from the hand gesture input; and

in response to receiving the second hand gesture input, displaying a second visual indicium corresponding to the requested change in the second operating parameter.

6. (canceled)

7. The method of claim 5, wherein the hand gesture input is distinguished from the second hand gesture input by a detected positioning of fingers of the hand of a user of the portable electronic device.

8. The method of claim 1, wherein the first input is detected by a gaze-tracking sensor that is an inward-facing optical sensor of the portable electronic device.

9. The method of claim 1, wherein the first input is detected by a gaze-tracking sensor that is configured to track eye movement of a user of the portable electronic device.

10. The method of claim 1, wherein the plurality of home automation devices are all the home automation devices determined to be within a threshold distance from the portable electronic device.

11. The method of claim 1, wherein the portable electronic device is located in a room of a building and the plurality of home automation devices are all the home automation devices determined to be located within the room.

12. The method of claim 1, wherein the portable electronic device is an extended reality (XR) device.

13. The method of claim 1, wherein the first input is detected by a gaze-tracking sensor of the portable electronic device and wherein the portable electronic device is a head-mounted portable electronic device.

14. A portable electronic device, comprising:

one or more processors;

a memory; and

one or more programs, wherein the one or more programs are stored in the memory and configured to be executed by the one or more processors, the one or more programs including instructions for:

displaying designators for a plurality of home automation devices in a three dimensional space viewable using the portable electronic device, wherein the plurality of home automation devices share a geographical area with the portable electronic device;

detecting a first input selecting a home automation device of the plurality of home automation devices;

in response to receiving the first input, displaying a visual indicium within the three dimensional space, wherein the visual indicium represents a current state of the home automation device, and wherein the display of the visual indicium occupies a first area;

receiving a hand gesture input performed by a hand, wherein the hand gesture input requests a change in the current state of the home automation device;

in response to receiving the hand gesture input, displaying an overlay within the three dimensional space, wherein at least a portion of the overlay occupies a second area different from the first area, and wherein the overlay includes a description of a parameter to be adjusted by the hand gesture input;

while displaying the overlay:

detecting movement of the hand; and

updating, based on the movement of the hand, the visual indicium to represent the requested change in the current state of the home automation device; and

transmitting a control signal directing the requested change in the current state of the home automation device.

15. The portable electronic device of claim 14, wherein updating the visual indicium comprises updating the visual indicium concurrently with the change in the current state of the home automation device.

16. The portable electronic device of claim 14, wherein the requested change in the current state of the home automation device is a change in a volume parameter of the home automation device.

17. The portable electronic device of claim 14, wherein the current state of the home automation device is governed

by a plurality of operating parameters and wherein the requested change in state corresponds to a change in a first operating parameter of the plurality of operating parameters.

18. A non-transitory computer-readable storage medium storing one or more programs, the one or more programs comprising instructions, which when executed by one or more processors of a portable electronic device, cause the portable electronic device to:

display designators for a plurality of home automation devices in a three dimensional space viewable using the portable electronic device, wherein the plurality of home automation devices share a geographical area with the portable electronic device;

detect a first input selecting a home automation device of the plurality of home automation devices;

in response to receiving the first input, display a visual indicium within the three dimensional space, wherein the visual indicium represents a current state of the home automation device, and wherein the display of the visual indicium occupies a first area;

receive a hand gesture input performed by a hand, wherein the hand gesture input requests a change in the current state of the home automation device;

in response to receiving the hand gesture input, display an overlay within the three dimensional space, wherein at least a portion of the overlay occupies a second area different from the first area, and wherein the overlay includes a description of a parameter to be adjusted by the hand gesture input;

while displaying the overlay:

detect movement of the hand; and

update, based on the movement of the hand, the visual indicium to represent the requested change in the current state of the home automation device; and

transmit a control signal directing the requested change in the current state of the home automation device.

19. The non-transitory computer-readable storage medium of claim **18**, wherein updating the visual indicium comprises updating the visual indicium concurrently with the change in the current state of the home automation device.

20. The non-transitory computer-readable storage medium of claim **18**, wherein the requested change in the current state of the home automation device is a change in a volume parameter of the home automation device.

21. The method of claim **1**, further comprising:

in accordance with a determination that the hand gesture input has ended, ceasing to display the overlay within the three dimensional space.

22. The method of claim **1**, wherein the hand gesture input is received while displaying the visual indicium within the three dimensional space.

23. The portable electronic device of claim **17**, wherein the one or more programs further include instructions for:

receiving a second hand gesture input requesting a change in a second operating parameter of the plurality of operating parameters, wherein the second hand gesture input is different from the hand gesture input; and

in response to receiving the second hand gesture input, displaying a second visual indicium corresponding to the requested change in the second operating parameter.

24. (canceled)

25. The portable electronic device of claim **23**, wherein the hand gesture input is distinguished from the second hand gesture input by a detected positioning of fingers of the hand of a user of the portable electronic device.

26. The portable electronic device of claim **14**, wherein the first input is detected by a gaze-tracking sensor that is an inward-facing optical sensor of the portable electronic device.

27. The portable electronic device of claim **14**, wherein the first input is detected by a gaze-tracking sensor that is configured to track eye movement of a user of the portable electronic device.

28. The portable electronic device of claim **14**, wherein the plurality of home automation devices are all the home automation devices determined to be within a threshold distance from the portable electronic device.

29. The portable electronic device of claim **14**, wherein the portable electronic device is located in a room of a building and the plurality of home automation devices are all the home automation devices determined to be located within the room.

30. The portable electronic device of claim **14**, wherein the portable electronic device is an extended reality (XR) device.

31. The portable electronic device of claim **14**, wherein the first input is detected by a gaze-tracking sensor of the portable electronic device and wherein the portable electronic device is a head-mounted portable electronic device.

32. The portable electronic device of claim **14**, wherein the one or more programs further include instructions for:

in accordance with a determination that the hand gesture input has ended, ceasing to display the overlay within the three dimensional space.

33. The portable electronic device of claim **14**, wherein the hand gesture input is received while displaying the visual indicium within the three dimensional space.

34. The non-transitory computer-readable storage medium of claim **18**, wherein the current state of the home automation device is governed by a plurality of operating parameters and wherein the requested change in state corresponds to a change in a first operating parameter of the plurality of operating parameters.

35. The non-transitory computer-readable storage medium of claim **34**, wherein the one or more programs further comprise instructions, which when executed by the one or more processors, cause the portable electronic device to:

receive a second hand gesture input requesting a change in a second operating parameter of the plurality of operating parameters, wherein the second hand gesture input is different from the hand gesture input; and

in response to receiving the second hand gesture input, display a second visual indicium corresponding to the requested change in the second operating parameter.

36. (canceled)

37. The non-transitory computer-readable storage medium of claim **35**, wherein the hand gesture input is distinguished from the second hand gesture input by a detected positioning of fingers of the hand of a user of the portable electronic device.

38. The non-transitory computer-readable storage medium of claim **18**, wherein the first input is detected by a gaze-tracking sensor that is an inward-facing optical sensor of the portable electronic device.

39. The non-transitory computer-readable storage medium of claim **18**, wherein the first input is detected by a gaze-tracking sensor that is configured to track eye movement of a user of the portable electronic device.

40. The non-transitory computer-readable storage medium of claim **18**, wherein the plurality of home automation devices are all the home automation devices determined to be within a threshold distance from the portable electronic device.

41. The non-transitory computer-readable storage medium of claim **18**, wherein the portable electronic device is located in a room of a building and the plurality of home automation devices are all the home automation devices determined to be located within the room.

42. The non-transitory computer-readable storage medium of claim **18**, wherein the portable electronic device is an extended reality (XR) device.

43. The non-transitory computer-readable storage medium of claim **18**, wherein the first input is detected by a gaze-tracking sensor of the portable electronic device and wherein the portable electronic device is a head-mounted portable electronic device.

44. The non-transitory computer-readable storage medium of claim **18**, wherein the one or more programs further comprise instructions, which when executed by the one or more processors, cause the portable electronic device to:

in accordance with a determination that the hand gesture input has ended, cease to display the overlay within the three dimensional space.

45. The non-transitory computer-readable storage medium of claim **18**, wherein the hand gesture input is received while displaying the visual indicium within the three dimensional space.

46. The method of claim **1**, wherein:

the current state of the home automation device is governed by a plurality of operating parameters that includes each operating parameter available to be adjusted;

the requested change in the current state of the home automation device corresponds to a change in a first operating parameter of the plurality of operating parameters;

the hand gesture input is received while displaying the visual indicium; and

the hand gesture input corresponds to a first type of hand gesture; and

the method further comprising:

while displaying the visual indicium, receiving a second hand gesture input, wherein the second hand gesture input corresponds to a second type of hand gesture different from the first type of hand gesture; and

in response to receiving the second hand gesture input, displaying, within the three dimensional space, a list of each operating parameter of the plurality of operating parameters.

* * * * *