



US 20230415021A1

(19) **United States**

(12) **Patent Application Publication**  
**Karafin et al.**

(10) **Pub. No.: US 2023/0415021 A1**

(43) **Pub. Date: Dec. 28, 2023**

(54) **LIGHT FIELD DISPLAY SYSTEM FOR SPORTING EVENTS**

*H04N 19/20* (2006.01)

*G02B 30/56* (2006.01)

(71) Applicant: **Light Field Lab, Inc.**, San Jose, CA (US)

(52) **U.S. Cl.**

CPC ..... *A63B 71/0622* (2013.01); *G03H 1/0005* (2013.01); *H04N 13/302* (2018.05); *H04N 19/20* (2014.11); *G02B 30/56* (2020.01); *G03H 2226/04* (2013.01); *A63B 2071/0636* (2013.01); *A63B 2071/0625* (2013.01); *A63B 2071/0655* (2013.01); *G03H 2001/0088* (2013.01)

(72) Inventors: **Jonathan Sean Karafin**, San Jose, CA (US); **Brendan Elwood Bevenssee**, San Jose, CA (US)

(21) Appl. No.: **18/201,910**

(22) Filed: **May 25, 2023**

**Related U.S. Application Data**

(63) Continuation of application No. 17/193,824, filed on Mar. 5, 2021, now Pat. No. 11,691,066, which is a continuation of application No. 16/630,258, filed on Jan. 10, 2020, now Pat. No. 10,981,046, filed as application No. PCT/US2019/048143 on Aug. 26, 2019.

**Publication Classification**

(51) **Int. Cl.**

*A63B 71/06* (2006.01)

*G03H 1/00* (2006.01)

*H04N 13/302* (2006.01)

(57) **ABSTRACT**

A light field (LF) display system for displaying holographic content (e.g., a holographic sporting event or holographic content to augment a holographic sporting event) to viewers in an arena. The LF display system in the arena includes LF display modules tiled together to form an array of LF modules. The array of LF modules create a holographic object volume for displaying the holographic content in the arena. The array of LF modules displays the holographic content to viewers in the viewing volumes. The LF display system can be included in a LF sporting event network. The LF sporting event network allows holographic content to be created at one location and presented at another location. The LF sporting event network includes a network system to manage the digital rights of the holographic sporting event content.





Diagram  
100



**FIG. 1**




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B






FIG. 4C






FIG. 4D



**FIG. 4E**



**FIG. 4F**





FIG. 5A



**FIG. 5B**




FIG. 6




FIG. 7






FIG. 8



**FIG. 9**





**FIG. 10**

## LIGHT FIELD DISPLAY SYSTEM FOR SPORTING EVENTS

### CROSS REFERENCE TO RELATED APPLICATIONS

**[0001]** This application is related to International Application Nos. PCT/US2017/042275, PCT/US2017/042276, PCT/US2017/042418, PCT/US2017/042452, PCT/US2017/042462, PCT/US2017/042466, PCT/US2017/042467, PCT/US2017/042468, PCT/US2017/042469, PCT/US2017/042470, and PCT/US2017/042679, all of which are incorporated by reference herein in their entirety.

### BACKGROUND

**[0002]** The present disclosure relates to presenting sporting events in an arena, and specifically relates to light field display systems for presenting sporting events in an arena.

**[0003]** Traditionally, arenas (e.g., baseball stadiums, basketball arenas, etc.) are configured to allow viewers (e.g., fans, crowds, patrons, etc.) attending the area to view a sporting event (e.g., a baseball game, a tennis match, etc.) in real-time. Unfortunately, in some cases, hosting a sporting event in an arena limits the ability of a viewer who wants to view the sporting event from doing so. For example, the sporting event may be sold out, may be at an inconvenient time, or may be located far from the viewer. Sometimes sporting events are recorded and, subsequently, reproduced on two-dimensional surfaces such as movie screens or televisions, but these reproductions hardly reproduce the atmosphere and excitement present in an arena of a live sporting event. As such, presentation spaces configured to present sporting events such that viewers can perceive the sporting event as if they were at the live sporting event in an arena would be beneficial.

### SUMMARY

**[0004]** A light field (LF) display system for displaying holographic content of a sporting event in a presentation space (e.g., an area, a home theater, a public venue such as a bar, etc.). The LF display system includes LF display modules that form a surface (e.g., a court, a floor, a table-top, etc.) in the presentation space, the LF display modules each have a display area and are tiled together to form a seamless display surface that has an effective display area that is larger than the display area. The LF display modules display holographic content of a sporting event from a sporting volume such that viewers in the presentation space can perceive the sporting event.

**[0005]** In some embodiments, the holographic content of a sporting event may be a reproduction of a sporting event occurring concurrently at another presentation space, created for display in the presentation space by a content creation system, and/or accessed for display in the presentation space from a data store. The holographic content can be managed by a network system responsible for managing the digital rights of the holographic content. For example, viewers in the presentation space may pay a transaction fee to access holographic content for display in the presentation space.

**[0006]** In some embodiments, the LF display system includes a tracking system and/or a viewer profiling system. The tracking system and profiling system can monitor and store characteristics of viewers in the presentation space, a

viewer profile describing a viewer, and/or responses of viewers to the holographic content in the presentation space. The holographic content created for display in a presentation space can be based on any of the monitored or stored information.

**[0007]** In some embodiments, a user may interact with the holographic content, and the interaction can act as input for the holographic content creation system. For example, in some embodiments, some or all of the LF display system includes a plurality of ultrasonic speakers. The plurality of ultrasonic speakers are configured to generate a haptic surface that coincides with at least a portion of the holographic content. The tracking system is configured to track an interaction of a user with the holographic object (e.g., via images captured by imaging sensors of the LF display modules and/or some other cameras). And the LF display system is configured to provide to create holographic content based on the interaction.

### BRIEF DESCRIPTION OF THE DRAWINGS

**[0008]** FIG. 1 is a diagram of a light field display module presenting a holographic object, in accordance with one or more embodiments.

**[0009]** FIG. 2A is a cross section of a portion of a light field display module, in accordance with one or more embodiments.

**[0010]** FIG. 2B is a cross section of a portion of a light field display module, in accordance with one or more embodiments.

**[0011]** FIG. 3A is a perspective view of a light field display module, in accordance with one or more embodiments.

**[0012]** FIG. 3B is a cross-sectional view of a light field display module which includes interleaved energy relay devices, in accordance with one or more embodiments.

**[0013]** FIG. 4A is a perspective view of portion of a light field display system that is tiled in two dimensions to form a single-sided seamless surface environment, in accordance with one or more embodiments.

**[0014]** FIG. 4B is a perspective view of a portion of light field display system in a multi-sided seamless surface environment, in accordance with one or more embodiments.

**[0015]** FIG. 4C is a top-down view of a light field display system with an aggregate surface in a winged configuration, in accordance with one or more embodiments.

**[0016]** FIG. 4D is a side view of a light field display system with an aggregate surface in a sloped configuration, in accordance with one or more embodiments.

**[0017]** FIG. 4E is a top-down view of a light field display system with an aggregate surface on a front wall of a room, in accordance with one or more embodiments.

**[0018]** FIG. 4F is a side view of a side view of a LF display system with an aggregate surface on the front wall of the room, in accordance with one or more embodiments.

**[0019]** FIG. 5A is a block diagram of a light field display system, in accordance with one or more embodiments.

**[0020]** FIG. 5B illustrates an example LF film network 550, in accordance with one or more embodiments.

**[0021]** FIG. 6 illustrates a side view of a venue 600 which is a traditional theater which has been augmented with a LF display system, in accordance with one or more embodiments.

**[0022]** FIG. 7 illustrates a cross-section of a first venue including a LF display system for displaying a sporting

event to viewers at viewing locations in viewing volumes, in accordance with one or more embodiments.

[0023] FIG. 8 illustrates a venue that also acts as a home theater in the living room of a viewer, in accordance with one or more embodiments.

[0024] FIG. 9 is a flow diagram illustrating a method for displaying holographic content of a sporting event within a LF sporting event distribution network.

[0025] FIG. 10 is a process flow diagram illustrating a method for displaying holographic content.

[0026] The figures depict various embodiments of the present invention for purposes of illustration only. One skilled in the art will readily recognize from the following discussion that alternative embodiments of the structures and methods illustrated herein may be employed without departing from the principles of the invention described herein.

## DETAILED DESCRIPTION

### Overview

[0027] A light field (LF) display system is implemented in a presentation space that acts as a setting for a sporting event. For example, a sporting event may be a baseball game, a basketball game, a hockey game, a gymnastics event, a cricket match, a field hockey game, a table tennis game, a rugby match, a golf game, a track and field meet, a football game, a soccer game, a car racing event, a tennis match, a boxing match, a martial arts bout, an Olympics event, and a world championship event. The LF display system comprises a LF display assembly configured to present holographic content including one or more holographic objects that would be visible to one or more viewers in a viewing volume of the LF display system. The holographic objects may be sporting content and may include a coach, a player, an official, a medical professional, a fan, or a participant. A LF display assembly may form a multi-sided seamless surface over some or all of one or more surfaces (e.g., a court) in the presentation space. The LF display system can present holographic content to viewers in the presentation space. A viewer generally attends a sporting event at the presentation space, but may be any person in a location that can view the holographic content in the presentation space.

[0028] A holographic object of the holographic content may also be augmented with other sensory stimuli (e.g., tactile and/or audio). For example, ultrasonic emitters in the LF display system may emit ultrasonic pressure waves that provide a tactile surface for some or all of the holographic object. Holographic content may include additional visual content (i.e., 2D or 3D visual content). The coordination of emitters to ensure that a cohesive experience is enabled is part of the system in multi-emitter implementations (i.e., holographic objects providing the correct haptic feel and sensory stimuli at any given point in time.)

[0029] In some embodiments, the LF display system includes a plurality of LF display modules that form a sporting display area (e.g., a court, a field, a table-top, etc.) in the presentation space. The LF display modules forming the sporting display area may be configured to project holographic content of a sporting event to viewers in the viewing volume of the LF display within the presentation space. In this disclosure, it is assumed that a ‘viewer in the presentation space’ refers to a viewer in one of the viewing volumes of the LF display system within the presentation

space. Viewing volumes are described in greater detail below. In this manner, a viewer in the presentation space can perceive a holographic sporting event on the sporting display area. For example, the LF display system may display two combatants in a martial arts bout, two teams playing a basketball game, two players in a tennis match, or any other content associated with a sporting event. In some embodiments, the LF display system may create holographic content for display to viewers in the presentation space. For example, the LF display system may create a cheering section in the presentation space that cheers for one of the teams participating in the presented sporting event. In an embodiment, the presentation space reproduces a portion of a sporting arena. For example, the LF display within the presentation space may generate sporting content representing a portion of a stadium or arena (e.g. a hockey ice rink and a portion of the audience), a field, a court, a gymnasium, or a portion of an amphitheater. In an embodiment, the presentation space may be located in an arena itself, or may be located at a bar, a home entertainment system, a table-top presentation system, or a public presentation system.

[0030] In some embodiments, the LF display system may include elements that enable the system to simultaneously emit at least one type of energy, and, simultaneously, absorb at least one type of energy (for creating holographic content). For example, a LF display system can emit both holographic objects for viewing as well as ultrasonic waves for haptic perception. Simultaneously, the LF display system can absorb both imaging information for tracking of viewers and other scene analysis and ultrasonic waves to detect touch response by the users. As an example, such a system may project a holographic ball that is thrown into the audience in the presentation space. When the holographic ball is virtually “touched” by a viewer, the LF display system gives the viewer the illusion that the ball is in their hands. The display system components that perform energy sensing of the environment may be integrated into the display surface via bidirectional energy elements that both emit and absorb energy, or they may be dedicated sensors that are separate from the display surface. For example, the LF display system may include dedicated ultrasonic speakers and image capture devices.

[0031] The LF display system can be part of a LF sporting event network. The LF sporting event network allows LF data to be recorded in one location (e.g., a first arena), encoded, transmitted to a different location (e.g., a second arena), decoded, and displayed as holographic content to viewers in a presentation space in the different location. This allows viewers in multiple locations to perceive a live-sporting event occurring in a different location. In some embodiments, the LF display system includes a network system that manages the digital rights of the holographic content.

### Light Field Display System

[0032] FIG. 1 is a diagram 100 of a light field (LF) display module 110 presenting a holographic object 120, in accordance with one or more embodiments. The LF display module 110 is part of a light field (LF) display system. The LF display system presents holographic content including at least one holographic object using one or more LF display modules. The LF display system can present holographic content to one or multiple viewers. In some embodiments, the LF display system may also augment the holographic

content with other sensory content (e.g., touch, audio, smell, temperature, etc.). For example, as discussed below, the projection of focused ultrasonic sound waves may generate a mid-air tactile sensation that can simulate a surface of some or all of a holographic object. The LF display system includes one or more LF display modules **110**, and is discussed in detail below with regard to FIGS. **2-4**.

[0033] The LF display module **110** is a holographic display that presents holographic objects (e.g., the holographic object **120**) to one or more viewers (e.g., viewer **140**). The LF display module **110** includes an energy device layer (e.g., an emissive electronic display or acoustic projection device) and an energy waveguide layer (e.g., an optical lens array). Additionally, the LF display module **110** may include an energy relay layer for combining multiple energy sources or detectors together to form a single surface. At a high-level, the energy device layer generates energy (e.g., holographic content) that is then directed using the energy waveguide layer to a region in space in accordance with one or more four-dimensional (4D) light field functions. The LF display module **110** may also project and/or sense one or more types of energy simultaneously. For example, LF display module **110** may be able to project a holographic image as well as an ultrasonic tactile surface in a viewing volume, while simultaneously detecting imaging data from the viewing volume. The operation of the LF display module **110** is discussed in more detail below with regard to FIGS. **2-3**.

[0034] The LF display module **110** generates holographic objects within a holographic object volume **160** using one or more 4D light field functions (e.g., derived from a plenoptic function). The holographic objects can be three-dimensional (3D), two-dimensional (2D), or some combination thereof. Moreover, the holographic objects may be polychromatic (e.g., full color). The holographic objects may be projected in front of the screen plane, behind the screen plane, or split by the screen plane. A holographic object **120** can be presented such that it is perceived anywhere within the holographic object volume **160**. A holographic object within the holographic object volume **160** may appear to a viewer **140** to be floating in space.

[0035] A holographic object volume **160** represents a volume in which holographic objects may be perceived by a viewer **140**. The holographic object volume **160** can extend in front of the surface of the display area **150** (i.e., towards the viewer **140**) such that holographic objects can be presented in front of the plane of the display area **150**. Additionally, the holographic object volume **160** can extend behind the surface of the display area **150** (i.e., away from the viewer **140**), allowing for holographic objects to be presented as if they are behind the plane of the display area **150**. In other words, the holographic object volume **160** may include all the rays of light that originate (e.g., are projected) from a display area **150** and can converge to create a holographic object. Herein, light rays may converge at a point that is in front of the display surface, at the display surface, or behind the display surface. More simply, the holographic object volume **160** encompasses all of the volume from which a holographic object may be perceived by a viewer.

[0036] A viewing volume **130** is a volume of space from which holographic objects (e.g., holographic object **120**) presented within a holographic object volume **160** by the LF display system are fully viewable. The holographic objects may be presented within the holographic object volume **160**,

and viewed within a viewing volume **130**, such that they are indistinguishable from actual objects. A holographic object is formed by projecting the same light rays that would be generated from the surface of the object were it physically present.

[0037] In some cases, the holographic object volume **160** and the corresponding viewing volume **130** may be relatively small—such that it is designed for a single viewer, as described in detail below with regard to FIGS. **10** and **11**. In other embodiments, the LF display modules may be enlarged and/or tiled to create larger holographic object volumes and corresponding viewing volumes that can accommodate a large range of viewers (e.g., **1** to thousands), as described in detail below with regard to, e.g., FIGS. **4A-4F**, **6A-6B**, **7A-7B**, **8**, and **9A-9B**. The LF display modules presented in this disclosure may be built so that the full surface of the LF display contains holographic imaging optics, with no inactive or dead space, and without any need for bezels. In these embodiments, the LF display modules may be tiled so that the imaging area is continuous across the seam between LF display modules, and the connection points between the tiled modules is virtually undetectable using the visual acuity of the eye. Notably, in some configurations, some portion of the display surface may not include holographic imaging optics, although they are not described in detail herein.

[0038] The flexible size and/or shape of a viewing volume **130** allows for viewers to be unconstrained within the viewing volume **130**. For example, a viewer **140** can move to a different position within a viewing volume **130** and see a different view of the holographic object **120** from the corresponding perspective. To illustrate, referring to FIG. **1**, the viewer **140** is at a first position relative to the holographic object **120** such that the holographic object **120** appears to be a head-on view of a dolphin. The viewer **140** may move to other locations relative to the holographic object **120** to see different views of the dolphin. For example, the viewer **140** may move such that he/she sees a left side of the dolphin, a right side of the dolphin, etc., much like if the viewer **140** was looking at an actual dolphin and changed his/her relative position to the actual dolphin to see different views of the dolphin. In some embodiments, the holographic object **120** is visible to all viewers within the viewing volume **130** that have an unobstructed line (i.e., not blocked by an object/person) of sight to the holographic object **120**. These viewers may be unconstrained such that they can move around within the viewing volume to see different perspectives of the holographic object **120**. Accordingly, the LF display system may present holographic objects such that a plurality of unconstrained viewers may simultaneously see different perspectives of the holographic objects in real-world space as if the holographic objects were physically present.

[0039] In contrast, conventional displays (e.g., stereoscopic, virtual reality, augmented reality, or mixed reality) generally require each viewer to wear some sort of external device (e.g., 3-D glasses, a near-eye display, or a head-mounted display) to see content. Additionally and/or alternatively, conventional displays may require that a viewer be constrained to a particular viewing position (e.g., in a chair that has fixed location relative to the display). For example, when viewing an object shown by a stereoscopic display, a viewer always focuses on the display surface, rather than on the object, and the display will always present just two views

of an object that will follow a viewer who attempts to move around that perceived object, causing distortions in the perception of that object. With a light field display, however, viewers of a holographic object presented by the LF display system do not need to wear an external device, nor be confined to a particular position, in order to see the holographic object. The LF display system presents the holographic object in a manner that is visible to viewers in much the same way a physical object would be visible to the viewers, with no requirement of special eyewear, glasses, or a head-mounted accessory. Further, the viewer may view holographic content from any location within a viewing volume.

**[0040]** Notably, potential locations for holographic objects within the holographic object volume **160** are limited by the size of the volume. To increase the size of the holographic object volume **160**, a size of a display area **150** of the LF display module **110** may be increased, and/or multiple LF display modules may be tiled together in a manner that forms a seamless display surface. The seamless display surface has an effective display area that is larger than the display areas of the individual LF display modules. Some embodiments relating to tiling LF display modules are discussed below with regard to FIGS. **4A-4F**, **6A-6B**, **7A-7B**, **8**, and **9A-9B**. As illustrated in FIG. **1**, the display area **150** is, for example, rectangular resulting in a holographic object volume **160** that is a pyramid. In other embodiments, the display area may have some other shape (e.g., hexagonal), which also affects the shape of the corresponding viewing volume.

**[0041]** Additionally, while the above discussion focuses on presenting the holographic object **120** within a portion of the holographic object volume **160** that is between the LF display module **110** and the viewer **140**, the LF display module **110** can additionally present content in the holographic object volume **160** behind the plane of the display area **150**. For example, the LF display module **110** may make the display area **150** appear to be a surface of the ocean that the holographic object **120** is jumping out of. And the displayed content may be such that the viewer **140** is able to look through the displayed surface to see marine life that is under the water. Moreover, the LF display system can generate content that seamlessly moves around the holographic object volume **160**, including behind and in front of the plane of the display area **150**.

**[0042]** FIG. **2A** illustrates a cross section **200** of a portion of a LF display module **210**, in accordance with one or more embodiments. The LF display module **210** may be the LF display module **110**. In other embodiments, the LF display module **210** may be another LF display module with a different display area shape than display area **150**. In the illustrated embodiment, the LF display module **210** includes an energy device layer **220**, an energy relay layer **230**, and an energy waveguide layer **240**. Some embodiments of the LF display module **210** have different components than those described here. For example, in some embodiments, the LF display module **210** does not include the energy relay layer **230**. Similarly, the functions can be distributed among the components in a different manner than is described here.

**[0043]** The display system described here presents an emission of energy that replicates the energy normally surrounding an object in the real world. Here, emitted energy is directed towards a specific direction from every coordinate on the display surface. In other words, the various

coordinates on the display surface act as projection locations for emitted energy. The directed energy from the display surface enables convergence of many rays of energy, which, thereby, can create holographic objects. For visible light, for example, the LF display will project a very large number of light rays from the projection locations that may converge at any point in the holographic object volume so they will appear to come from the surface of a real-world object located in this region of space from the perspective of a viewer that is located further away than the object being projected. In this way, the LF display is generating the rays of reflected light that would leave such an object's surface from the perspective of the viewer. The viewer perspective may change on any given holographic object, and the viewer will see a different view of that holographic object.

**[0044]** The energy device layer **220** includes one or more electronic displays (e.g., an emissive display such as an OLED) and one or more other energy projection and/or energy receiving devices as described herein. The one or more electronic displays are configured to display content in accordance with display instructions (e.g., from a controller of a LF display system). The one or more electronic displays include a plurality of pixels, each with an intensity that is individually controlled. Many types of commercial displays, such as emissive LED and OLED displays, may be used in the LF display.

**[0045]** The energy device layer **220** may also include one or more acoustic projection devices and/or one or more acoustic receiving devices. An acoustic projection device generates one or more pressure waves that complement the holographic object **250**. The generated pressure waves may be, e.g., audible, ultrasonic, or some combination thereof. An array of ultrasonic pressure waves may be used for volumetric tactile sensation (e.g., at a surface of the holographic object **250**). An audible pressure wave is used for providing audio content (e.g., immersive audio) that can complement the holographic object **250**. For example, assuming the holographic object **250** is a dolphin, one or more acoustic projection devices may be used to (1) generate a tactile surface that is collocated with a surface of the dolphin such that viewers may touch the holographic object **250**; and (2) provide audio content corresponding to noises a dolphin makes such as clicks, chirping, or chatter. An acoustic receiving device (e.g., a microphone or microphone array) may be configured to monitor ultrasonic and/or audible pressure waves within a local area of the LF display module **210**.

**[0046]** The energy device layer **220** may also include one or more imaging sensors. An imaging sensor may be sensitive to light in a visible optical band, and in some cases may be sensitive to light in other bands (e.g., infrared). The imaging sensor may be, e.g., a complementary metal oxide semi-conductor (CMOS) array, a charged coupled device (CCD), an array of photodetectors, some other sensor that captures light, or some combination thereof. The LF display system may use data captured by the one or more imaging sensor for position location tracking of viewers.

**[0047]** In some configurations, the energy relay layer **230** relays energy (e.g., electromagnetic energy, mechanical pressure waves, etc.) between the energy device layer **220** and the energy waveguide layer **240**. The energy relay layer **230** includes one or more energy relay elements **260**. Each energy relay element includes a first surface **265** and a second surface **270**, and it relays energy between the two

surfaces. The first surface **265** of each energy relay element may be coupled to one or more energy devices (e.g., electronic display or acoustic projection device). An energy relay element may be composed of, e.g., glass, carbon, optical fiber, optical film, plastic, polymer, or some combination thereof. Additionally, in some embodiments, an energy relay element may adjust magnification (increase or decrease) of energy passing between the first surface **265** and the second surface **270**. If the relay offers magnification, then the relay may take the form of an array of bonded tapered relays, called tapers, where the area of one end of the taper may be substantially larger than the opposite end. The large end of the tapers can be bonded together to form a seamless energy surface **275**. One advantage is that space is created on the multiple small ends of each taper to accommodate the mechanical envelope of multiple energy sources, such as the bezels of multiple displays. This extra room allows the energy sources to be placed side-by-side on the small taper side, with each energy source having their active areas directing energy into the small taper surface and relayed to the large seamless energy surface. Another advantage to using tapered relays is that there is no non-imaging dead space on the combined seamless energy surface formed by the large end of the tapers. No border or bezel exists, and so the seamless energy surfaces can then be tiled together to form a larger surface with virtually no seams according to the visual acuity of the eye.

**[0048]** The second surfaces of adjacent energy relay elements come together to form an energy surface **275**. In some embodiments, a separation between edges of adjacent energy relay elements is less than a minimum perceptible contour as defined by a visual acuity of a human eye having, for example, 20/40 vision, such that the energy surface **275** is effectively seamless from the perspective of a viewer **280** within a viewing volume **285**.

**[0049]** In some embodiments, the second surfaces of adjacent energy relay elements are fused together with processing steps that may include one or more of pressure, heat, and a chemical reaction, in such a way no seam exists between them. And still in other embodiments, an array of energy relay elements is formed by molding one side of a continuous block of relay material into an array of small taper ends, each configured to transport energy from an energy device attached to the small tapered end into a single combined surface with a larger area which is never subdivided.

**[0050]** In some embodiments, one or more of the energy relay elements exhibit energy localization, where the energy transport efficiency in the longitudinal direction substantially normal to the surfaces **265** and **270** is much higher than the transport efficiency in the perpendicular transverse plane, and where the energy density is highly localized in this transverse plane as the energy wave propagates between surface **265** and surface **270**. This localization of energy allows an energy distribution, such as an image, to be efficiently relayed between these surfaces without any significant loss in resolution.

**[0051]** The energy waveguide layer **240** directs energy from a location (e.g., a coordinate) on the energy surface **275** into a specific energy propagation path outward from the display surface into the holographic viewing volume **285** using waveguide elements in the energy waveguide layer **240**. The energy propagation path is defined by two angular dimensions determined at least by the energy surface coordinate location relative to the waveguide. The waveguide is

associated with a spatial 2D coordinate. Together, these four coordinates form a four-dimensional (4D) energy field. As an example, for electromagnetic energy, the waveguide elements in the energy waveguide layer **240** direct light from positions on the seamless energy surface **275** along different propagation directions through the viewing volume **285**. In various examples, the light is directed in accordance with a 4D light field function to form the holographic object **250** within the holographic object volume **255**.

**[0052]** Each waveguide element in the energy waveguide layer **240** may be, for example, a lenslet composed of one or more elements. In some configurations, the lenslet may be a positive lens. The positive lens may have a surface profile that is spherical, aspherical, or freeform. Additionally, in some embodiments, some or all of the waveguide elements may include one or more additional optical components. An additional optical component may be, e.g., an energy-inhibiting structure such as a baffle, a positive lens, a negative lens, a spherical lens, an aspherical lens, a freeform lens, a liquid crystal lens, a liquid lens, a refractive element, a diffractive element, or some combination thereof. In some embodiments, the lenslet and/or at least one of the additional optical components is able to dynamically adjust its optical power. For example, the lenslet may be a liquid crystal lens or a liquid lens. Dynamic adjustment of a surface profile the lenslet and/or at least one additional optical component may provide additional directional control of light projected from a waveguide element.

**[0053]** In the illustrated example, the holographic object volume **255** of the LF display has boundaries formed by light ray **256** and light ray **257**, but could be formed by other rays. The holographic object volume **255** is a continuous volume that extends both in front (i.e., towards the viewer **280**) of the energy waveguide layer **240** and behind it (i.e., away from the viewer **280**). In the illustrated example, ray **256** and ray **257** are projected from opposite edges of the LF display module **210** at the highest angle relative to the normal to the display surface **277** that may be perceived by a user, but these could be other projected rays. The rays define the field-of-view of the display, and, thus, define the boundaries for the holographic viewing volume **285**. In some cases, the rays define a holographic viewing volume where the full display can be observed without vignetting (e.g., an ideal viewing volume). As the field of view of the display increases, the convergence point of ray **256** and ray **257** will be closer to the display. Thus, a display having a larger field of view allows a viewer **280** to see the full display at a closer viewing distance. Additionally, ray **256** and **257** may form an ideal holographic object volume. Holographic objects presented in an ideal holographic object volume can be seen anywhere in the viewing volume **285**.

**[0054]** In some examples, holographic objects may be presented to only a portion of the viewing volume **285**. In other words, holographic object volumes may be divided into any number of viewing sub-volumes (e.g., viewing sub-volume **290**). Additionally, holographic objects can be projected outside of the holographic object volume **255**. For example, holographic object **251** is presented outside of holographic object volume **255**. Because the holographic object **251** is presented outside of the holographic object volume **255** it cannot be viewed from every location in the viewing volume **285**. For example, holographic object **251** may be visible from a location in viewing sub-volume **290**, but not visible from the location of the viewer **280**.

[0055] For example, we turn to FIG. 2B to illustrate viewing holographic content from different viewing sub-volumes. FIG. 2B illustrates a cross section 200 of a portion of a LF display module, in accordance with one or more embodiments. The cross-section of FIG. 2B is the same as the cross-section of FIG. 2A. However, FIG. 2B illustrates a different set of light rays projected from the LF display module 210. Ray 256 and ray 257 still form a holographic object volume 255 and a viewing volume 285. However, as shown, rays projected from the top of the LF display module 210 and the bottom of the LF display module 210 overlap to form various viewing sub-volumes (e.g., view sub-volumes 290A, 290B, 290C, and 290D) within the viewing volume 285. A viewer in the first viewing sub-volume (e.g., 290A) may be able to perceive holographic content presented in the holographic object volume 255 that viewers in the other viewing sub-volumes (e.g., 290B, 290C, and 290D) are unable to perceive.

[0056] More simply, as illustrated in FIG. 2A, holographic object volume 255 is a volume in which holographic objects may be presented by LF display system such that they may be perceived by viewers (e.g., viewer 280) in viewing volume 285. In this way, the viewing volume 285 is an example of an ideal viewing volume, while the holographic object volume 255 is an example of an ideal object volume. However, in various configurations, viewers may perceive holographic objects presented by LF display system 200 in other example holographic object volumes. More generally, an “eye-line guideline” applies when viewing holographic content projected from an LF display module. The eye-line guideline asserts that the line formed by a viewer’s eye position and a holographic object being viewed must intersect a LF display surface.

[0057] When viewing holographic content presented by the LF display module 210, each eye of the viewer 280 sees a different perspective of the holographic object 250 because the holographic content is presented according to a 4D light field function. Moreover, as the viewer 280 moves within the viewing volume 285 he/she would also see different perspectives of the holographic object 250 as would other viewers within the viewing volume 285. As will be appreciated by one of ordinary skill in the art, a 4D light field function is well known in the art and will not be elaborated further herein.

[0058] As described in more detail herein, in some embodiments, the LF display can project more than one type of energy. For example, the LF display may project two types of energy, such as, for example, mechanical energy and electromagnetic energy. In this configuration, energy relay layer 230 may include two separate energy relays which are interleaved together at the energy surface 275, but are separated such that the energy is relayed to two different energy device layers 220. Here, one relay may be configured to transport electromagnetic energy, while another relay may be configured to transport mechanical energy. In some embodiments, the mechanical energy may be projected from locations between the electromagnetic waveguide elements on the energy waveguide layer 240, helping form structures that inhibit light from being transported from one electromagnetic waveguide element to another. In some embodiments, the energy waveguide layer 240 may also include waveguide elements that transport focused ultrasound along specific propagation paths in accordance with display instructions from a controller.

[0059] Note that in alternate embodiments (not shown), the LF display module 210 does not include the energy relay layer 230. In this case, the energy surface 275 is an emission surface formed using one or more adjacent electronic displays within the energy device layer 220. And in some embodiments, with no energy relay layer, a separation between edges of adjacent electronic displays is less than a minimum perceptible contour as defined by a visual acuity of a human eye having 20/40 vision, such that the energy surface is effectively seamless from the perspective of the viewer 280 within the viewing volume 285.

#### LF Display Modules

[0060] FIG. 3A is a perspective view of a LF display module 300A, in accordance with one or more embodiments. The LF display module 300A may be the LF display module 110 and/or the LF display module 210. In other embodiments, the LF display module 300A may be some other LF display module. In the illustrated embodiment, the LF display module 300A includes an energy device layer 310, and energy relay layer 320, and an energy waveguide layer 330. The LF display module 300A is configured to present holographic content from a display surface 365 as described herein. For convenience, the display surface 365 is illustrated as a dashed outline on the frame 390 of the LF display module 300A, but is, more accurately, the surface directly in front of waveguide elements bounded by the inner rim of the frame 390. The display surface 365 includes a plurality of projection locations from which energy can be projected. Some embodiments of the LF display module 300A have different components than those described here. For example, in some embodiments, the LF display module 300A does not include the energy relay layer 320. Similarly, the functions can be distributed among the components in a different manner than is described here.

[0061] The energy device layer 310 is an embodiment of the energy device layer 220. The energy device layer 310 includes four energy devices 340 (three are visible in the figure). The energy devices 340 may all be the same type (e.g., all electronic displays), or may include one or more different types (e.g., includes electronic displays and at least one acoustic energy device).

[0062] The energy relay layer 320 is an embodiment of the energy relay layer 230. The energy relay layer 320 includes four energy relay devices 350 (three are visible in the figure). The energy relay devices 350 may all relay the same type of energy (e.g., light), or may relay one or more different types (e.g., light and sound). Each of the relay devices 350 includes a first surface and a second surface, the second surface of the energy relay devices 350 being arranged to form a singular seamless energy surface 360. In the illustrated embodiment, each of the energy relay devices 350 are tapered such that the first surface has a smaller surface area than the second surface, which allows accommodation for the mechanical envelopes of the energy devices 340 on the small end of the tapers. This also allows the seamless energy surface to be borderless, since the entire area can project energy. This means that this seamless energy surface can be tiled by placing multiple instances of LF display module 300A together, without dead space or bezels, so that the entire combined surface is seamless. In other embodiments, the first surface and the second surface have the same surface area.

[0063] The energy waveguide layer **330** is an embodiment of the energy waveguide layer **240**. The energy waveguide layer **330** includes a plurality of waveguide elements **370**. As discussed above with respect to FIG. 2, the energy waveguide layer **330** is configured to direct energy from the seamless energy surface **360** along specific propagation paths in accordance with a 4D light field function to form a holographic object. Note that in the illustrated embodiment the energy waveguide layer **330** is bounded by a frame **390**. In other embodiments, there is no frame **390** and/or a thickness of the frame **390** is reduced. Removal or reduction of thickness of the frame **390** can facilitate tiling the LF display module **300A** with additional LF display modules.

[0064] Note that in the illustrated embodiment, the seamless energy surface **360** and the energy waveguide layer **330** are planar. In alternate embodiments, not shown, the seamless energy surface **360** and the energy waveguide layer **330** may be curved in one or more dimensions.

[0065] The LF display module **300A** can be configured with additional energy sources that reside on the surface of the seamless energy surface, and allow the projection of an energy field in addition to the light field. In one embodiment, an acoustic energy field may be projected from electrostatic speakers (not illustrated) mounted at any number of locations on the seamless energy surface **360**. Further, the electrostatic speakers of the LF display module **300A** are positioned within the light field display module **300A** such that the dual-energy surface simultaneously projects sound fields and holographic content. For example, the electrostatic speakers may be formed with one or more diaphragm elements that are transmissive to some wavelengths of electromagnetic energy, and driven with one or more conductive elements (e.g., planes which sandwich the one or more diaphragm elements). The electrostatic speakers may be mounted on to the seamless energy surface **360**, so that the diaphragm elements cover some of the waveguide elements. The conductive electrodes of the speakers may be co-located with structures designed to inhibit light transmission between electromagnetic waveguides, and/or located at positions between electromagnetic waveguide elements (e.g., frame **390**). In various configurations, the speakers can project an audible sound and/or many sources of focused ultrasonic energy that produces a haptic surface.

[0066] In some configurations an energy device **340** may sense energy. For example, an energy device may be a microphone, a light sensor, an acoustic transducer, etc. As such, the energy relay devices may also relay energy from the seamless energy surface **360** to the energy device layer **310**. That is, the seamless energy surface **360** of the LF display module forms a bidirectional energy surface when the energy devices and energy relay devices **340** are configured to simultaneously emit and sense energy (e.g., emit light fields and sense sound).

[0067] More broadly, an energy device **340** of a LF display module **340** can be either an energy source or an energy sensor. The LF display module **300A** can include various types of energy devices that act as energy sources and/or energy sensors to facilitate the projection of high quality holographic content to a user. Other sources and/or sensors may include thermal sensors or sources, infrared sensors or sources, image sensors or sources, mechanical energy transducers that generate acoustic energy, feedback sources, etc. Many other sensors or sources are possible. Further, the LF display modules can be tiled such that the LF display module

can form an assembly that projects and senses multiple types of energy from a large aggregate seamless energy surface

[0068] In various embodiments of LF display module **300A**, the seamless energy surface **360** can have various surface portions where each surface portion is configured to project and/or emit specific types of energy. For example, when the seamless energy surface is a dual-energy surface, the seamless energy surface **360** includes one or more surface portions that project electromagnetic energy, and one or more other surface portions that project ultrasonic energy. The surface portions that project ultrasonic energy may be located on the seamless energy surface **360** between electromagnetic waveguide elements, and/or co-located with structures designed to inhibit light transmission between electromagnetic waveguide elements. In an example where the seamless energy surface is a bidirectional energy surface, the energy relay layer **320** may include two types of energy relay devices interleaved at the seamless energy surface **360**. In various embodiments, the seamless energy surface **360** may be configured such that portions of the surface under any particular waveguide element **370** are all energy sources, all energy sensors, or a mix of energy sources and energy sensors.

[0069] FIG. 3B is a cross-sectional view of a LF display module **300B** which includes interleaved energy relay devices, in accordance with one or more embodiments. Energy relay device **350A** transports energy between the energy relay first surface **345A** connected to energy device **340A**, and the seamless energy surface **360**. Energy relay **350B** transports energy between the energy relay first surface **345B** connected to energy device **340B**, and the seamless energy surface **360**. Both relay devices are interleaved at interleaved energy relay device **352**, which is connected to the seamless energy surface **360**. In this configuration, surface **360** contains interleaved energy locations of both energy devices **340A** and **340B**, which may be energy sources or energy sensors. Accordingly, the LF display module **300B** may be configured as either a dual energy projection device for projecting more than one type of energy, or as a bidirectional energy device for simultaneously projecting one type of energy and sensing another type of energy. The LF display module **300B** may be the LF display module **110** and/or the LF display module **210**. In other embodiments, the LF display module **300B** may be some other LF display module.

[0070] The LF display module **300B** includes many components similarly configured to those of LF display module **300A** in FIG. 3A. For example, in the illustrated embodiment, the LF display module **300B** includes an energy device layer **310**, energy relay layer **320**, a seamless energy surface **360**, and an energy waveguide layer **330** including at least the same functionality of those described in regard to FIG. 3A. Additionally, the LF display module **300B** may present and/or receive energy from the display surface **365**. Notably, the components of the LF display module **300B** are alternatively connected and/or oriented than those of the LF display module **300A** in FIG. 3A. Some embodiments of the LF display module **300B** have different components than those described here. Similarly, the functions can be distributed among the components in a different manner than is described here. FIG. 3B illustrates the design of a single LF display module **300B** that may be tiled to produce a dual energy projection surface or a bidirectional energy surface with a larger area.



[0071] In an embodiment, the LF display module **300B** is a LF display module of a bidirectional LF display system. A bidirectional LF display system may simultaneously project energy and sense energy from the display surface **365**. The seamless energy surface **360** contains both energy projecting and energy sensing locations that are closely interleaved on the seamless energy surface **360**. Therefore, in the example of FIG. **3B**, the energy relay layer **320** is configured in a different manner than the energy relay layer of FIG. **3A**. For convenience, the energy relay layer of LF display module **300B** will be referred to herein as the “interleaved energy relay layer.”

[0072] The interleaved energy relay layer **320** includes two legs: a first energy relay device **350A** and a second energy relay device **350B**. Each of the legs are illustrated as a lightly shaded area in FIG. **3B**. Each of the legs may be made of a flexible relay material, and formed with a sufficient length to use with energy devices of various sizes and shapes. In some regions of the interleaved energy relay layer, the two legs are tightly interleaved together as they approach the seamless energy surface **360**. In the illustrated example, the interleaved energy relay devices **352** are illustrated as a darkly shaded area.

[0073] While interleaved at the seamless energy surface **360**, the energy relay devices are configured to relay energy to/from different energy devices. The energy devices are at energy device layer **310**. As illustrated, energy device **340A** is connected to energy relay device **350A** and energy device **340B** is connected to energy relay device **350B**. In various embodiments, each energy device may be an energy source or energy sensor.

[0074] An energy waveguide layer **330** includes waveguide elements **370** to steer energy waves from the seamless energy surface **360** along projected paths towards a series of convergence points. In this example, a holographic object **380** is formed at the series of convergence points. Notably, as illustrated, the convergence of energy at the holographic object **380** occurs on the viewer side (i.e., the front side), of the display surface **365**. However, in other examples, the convergence of energy may be anywhere in the holographic object volume, which extends both in front of the display surface **365** and behind the display surface **365**. The waveguide elements **370** can simultaneously steer incoming energy to an energy device (e.g., an energy sensor), as described below.

[0075] In one example embodiment of LF display module **300B**, an emissive display is used as an energy source (e.g., energy device **340A**) and an imaging sensor is used as an energy sensor (e.g., energy device **340B**). In this manner, the LF display module **300B** can simultaneously project holographic content and detect light from the volume in front of the display surface **365**. In this manner, this embodiment of the LF display module **300B** functions as both a LF display and an LF sensor.

[0076] In an embodiment, the LF display module **300B** is configured to simultaneously project a light field from projection locations on the display surface to the front of the display surface and capture a light field from front of the display surface at the projection locations. In this embodiment, the energy relay device **350A** connects a first set of locations at the seamless energy surface **360** positioned under the waveguide elements **370** to an energy device **340A**. In an example, energy device **340A** is an emissive display having an array of source pixels. The energy relay

device **340B** connects a second set of locations at the seamless energy surface **360** positioned under waveguide elements **370** to an energy device **340B**. In an example, the energy device **340B** is an imaging sensor having an array of sensor pixels. The LF display module **300B** may be configured such that the locations at the seamless energy surface **365** that are under a particular waveguide element **370** are all emissive display locations, all imaging sensor locations, or some combination of these locations. In other embodiments, the bidirectional energy surface can project and receive various other forms of energy.

[0077] In another example embodiment of the LF display module **300B**, the LF display module is configured to project two different types of energy. For example, in an embodiment, energy device **340A** is an emissive display configured to emit electromagnetic energy and energy device **340B** is an ultrasonic transducer configured to emit mechanical energy. As such, both light and sound can be projected from various locations at the seamless energy surface **360**. In this configuration, energy relay device **350A** connects the energy device **340A** to the seamless energy surface **360** and relays the electromagnetic energy. The energy relay device is configured to have properties (e.g. varying refractive index) which make it efficient for transporting electromagnetic energy. Energy relay device **350B** connects the energy device **340B** to the seamless energy surface **360** and relays mechanical energy. Energy relay device **350B** is configured to have properties for efficient transport of ultrasound energy (e.g. distribution of materials with different acoustic impedance). In some embodiments, the mechanical energy may be projected from locations between the waveguide elements **370** on the energy waveguide layer **330**. The locations that project mechanical energy may form structures that serve to inhibit light from being transported from one electromagnetic waveguide element to another. In one example, a spatially separated array of locations that project ultrasonic mechanical energy can be configured to create three-dimensional haptic shapes and surfaces in mid-air. The surfaces may coincide with projected holographic objects (e.g., holographic object **380**). In some examples, phase delays and amplitude variations across the array can assist in creating the haptic shapes.

[0078] In various embodiments, the LF display module **300B** with interleaved energy relay devices may include multiple energy device layers with each energy device layer including a specific type of energy device. In these examples, the energy relay layers are configured to relay the appropriate type of energy between the seamless energy surface **360** and the energy device layer **310**.

#### Tiled LF Display Modules

[0079] FIG. **4A** is a perspective view of a portion of LF display system **400** that is tiled in two dimensions to form a single-sided seamless surface environment, in accordance with one or more embodiments. The LF display system **400** includes a plurality of LF display modules that are tiled to form an array **410**. More explicitly, each of the small squares in the array **410** represents a tiled LF display module **412**. The LF display module **412** may be the same as LF display module **300A** or **300B**. The array **410** may cover, for example, some or all of a surface (e.g., a wall) of a room. The LF array may cover other surfaces, such as, for example, a table top, a billboard, a rotunda, etc.

**[0080]** The array **410** may project one or more holographic objects. For example, in the illustrated embodiment, the array **410** projects a holographic object **420** and a holographic object **422**. Tiling of the LF display modules **412** allows for a much larger viewing volume as well as allows for objects to be projected out farther distances from the array **410**. For example, in the illustrated embodiment, the viewing volume is, approximately, the entire area in front of and behind the array **410** rather than a localized volume in front of (and behind) a LF display module **412**.

**[0081]** In some embodiments, the LF display system **400** presents the holographic object **420** to a viewer **430** and a viewer **434**. The viewer **430** and the viewer **434** receive different perspectives of the holographic object **420**. For example, the viewer **430** is presented with a direct view of the holographic object **420**, whereas the viewer **434** is presented with a more oblique view of the holographic object **420**. As the viewer **430** and/or the viewer **434** move, they are presented with different perspectives of the holographic object **420**. This allows a viewer to visually interact with a holographic object by moving relative to the holographic object. For example, as the viewer **430** walks around a holographic object **420**, the viewer **430** sees different sides of the holographic object **420** as long as the holographic object **420** remains in the holographic object volume of the array **410**. Accordingly, the viewer **430** and the viewer **434** may simultaneously see the holographic object **420** in real-world space as if it is truly there. Additionally, the viewer **430** and the viewer **434** do not need to wear an external device in order to see the holographic object **420**, as the holographic object **420** is visible to viewers in much the same way a physical object would be visible. Additionally, here, the holographic object **422** is illustrated behind the array because the viewing volume of the array extends behind the surface of the array. In this manner, the holographic object **422** may be presented to the viewer **430** and/or viewer **434**.

**[0082]** In some embodiments, the LF display system **400** may include a tracking system that tracks positions of the viewer **430** and the viewer **434**. In some embodiments, the tracked position is the position of a viewer. In other embodiments, the tracked position is that of the eyes of a viewer. The position tracking of the eye is different from gaze tracking which tracks where an eye is looking (e.g., uses orientation to determine gaze location). The eyes of the viewer **430** and the eyes of the viewer **434** are in different locations.

**[0083]** In various configurations, the LF display system **400** may include one or more tracking systems. For example, in the illustrated embodiment of FIG. 4A, LF display system includes a tracking system **440** that is external to the array **410**. Here, the tracking system may be a camera system coupled to the array **410**. External tracking systems are described in more detail in regard to FIG. 5A. In other example embodiments, the tracking system may be incorporated into the array **410** as described herein. For example, an energy device (e.g., energy device **340**) of one or more LF display modules **412** containing a bidirectional energy surface included in the array **410** may be configured to capture images of viewers in front of the array **410**. In whichever case, the tracking system(s) of the LF display system **400** determines tracking information about the viewers (e.g., viewer **430** and/or viewer **434**) viewing holographic content presented by the array **410**.

**[0084]** Tracking information describes a position in space (e.g., relative to the tracking system) for the position of a viewer, or a position of a portion of a viewer (e.g. one or both eyes of a viewer, or the extremities of a viewer). A tracking system may use any number of depth determination techniques to determine tracking information. The depth determination techniques may include, e.g., structured light, time of flight, stereo imaging, some other depth determination technique, or some combination thereof. The tracking system may include various systems configured to determine tracking information. For example, the tracking system may include one or more infrared sources (e.g., structured light sources), one or more imaging sensors that can capture images in the infrared (e.g., red-blue-green-infrared camera), and a processor executing tracking algorithms. The tracking system may use the depth estimation techniques to determine positions of viewers. In some embodiments, the LF display system **400** generates holographic objects based on tracked positions, motions, or gestures of the viewer **430** and/or the viewer **434** as described herein. For example, the LF display system **400** may generate a holographic object responsive to a viewer coming within a threshold distance of the array **410** and/or a particular position.

**[0085]** The LF display system **400** may present one or more holographic objects that are customized to each viewer based in part on the tracking information. For example, the viewer **430** may be presented with the holographic object **420**, but not the holographic object **422**. Similarly, the viewer **434** may be presented with the holographic object **422**, but not the holographic object **420**. For example, the LF display system **400** tracks a position of each of the viewer **430** and the viewer **434**. The LF display system **400** determines a perspective of a holographic object that should be visible to a viewer based on their position relative to where the holographic object is to be presented. The LF display system **400** selectively projects light from specific pixels that correspond to the determined perspective. Accordingly, the viewer **434** and the viewer **430** can simultaneously have experiences that are, potentially, completely different. In other words, the LF display system **400** may present holographic content to viewing sub-volumes of the viewing volume (i.e., similar to the viewing sub-volumes **290A**, **290B**, **290C**, and **290D** shown in FIG. 2B). For example, as illustrated, because the LF display system **400** can track the position of the viewer **430**, the LF display system **400** may present space content (e.g., holographic object **420**) to a viewing sub-volume surrounding the viewer **430** and safari content (e.g., holographic object **422**) to a viewing sub-volume surrounding the viewer **434**. In contrast, conventional systems would have to use individual headsets to provide a similar experience.

**[0086]** In some embodiments the LF display system **400** may include one or more sensory feedback systems. The sensory feedback systems provide other sensory stimuli (e.g., tactile, audio, or smell) that augment the holographic objects **420** and **422**. For example, in the illustrated embodiment of FIG. 4A, the LF display system **400** includes a sensory feedback system **442** external to the array **410**. In one example, the sensory feedback system **442** may be an electrostatic speaker coupled to the array **410**. External sensory feedback systems are described in more detail in regard to FIG. 5A. In other example embodiments, the sensory feedback system may be incorporated into the array **410** as described herein. For example, an energy device

(e.g., energy device **340A** in FIG. **3B**) of a LF display module **412** included in the array **410** may be configured to project ultrasonic energy to viewers in front of the array and/or receive imaging information from viewers in front of the array. In whichever case, the sensory feedback system presents and/or receives sensory content to/from the viewers (e.g., viewer **430** and/or viewer **434**) viewing holographic content (e.g., holographic object **420** and/or holographic object **422**) presented by the array **410**.

[0087] The LF display system **400** may include a sensory feedback system **442** that includes one or more acoustic projection devices external to the array. Alternatively or additionally, the LF display system **400** may include one or more acoustic projection devices integrated into the array **410** as described herein. The acoustic projection devices may consist of an array of ultrasonic sources configured to project a volumetric tactile surface. In some embodiments, the tactile surface may be coincident with a holographic object (e.g., at a surface of the holographic object **420**) for one or more surfaces of a holographic object if a portion of a viewer gets within a threshold distance of the one or more surfaces. The volumetric tactile sensation may allow the user to touch and feel surfaces of the holographic object. The plurality of acoustic projection devices may also project an audible pressure wave that provides audio content (e.g., immersive audio) to viewers. Accordingly, the ultrasonic pressure waves and/or the audible pressure waves can act to complement a holographic object.

[0088] In various embodiments, the LF display system **400** may provide other sensory stimuli based in part on a tracked position of a viewer. For example, the holographic object **422** illustrated in FIG. **4A** is a lion, and the LF display system **400** may have the holographic object **422** roar both visually (i.e., the holographic object **422** appears to roar) and audibly (i.e., one or more acoustic projection devices project a pressure wave that the viewer **430** perceives as a lion's roar emanating from the holographic object **422**).

[0089] Note that, in the illustrated configuration, the holographic viewing volume may be limited in a manner similar to the viewing volume **285** of the LF display system **200** in FIG. **2**. This can limit the amount of perceived immersion that a viewer will experience with a single wall display unit. One way to address this is to use multiple LF display modules that are tiled along multiple sides as described below with respect to FIG. **4B-4F**.

[0090] FIG. **4B** is a perspective view of a portion of a LF display system **402** in a multi-sided seamless surface environment, in accordance with one or more embodiments. The LF display system **402** is substantially similar to the LF display system **400** except that the plurality of LF display modules are tiled to create a multi-sided seamless surface environment. More specifically, the LF display modules are tiled to form an array that is a six-sided aggregated seamless surface environment. In FIG. **4B**, the plurality of LF display modules cover all the walls, the ceiling, and the floor of a room. In other embodiments, the plurality of LF display modules may cover some, but not all of a wall, a floor, a ceiling, or some combination thereof. In other embodiments, a plurality of LF display modules are tiled to form some other aggregated seamless surface. For example, the walls may be curved such that a cylindrical aggregated energy environment is formed. Moreover, as described below with

regard to FIGS. **6-9**, in some embodiments, the LF display modules may be tiled to form a surface in a presentation space (e.g., walls, etc.).

[0091] The LF display system **402** may project one or more holographic objects. For example, in the illustrated embodiment the LF display system **402** projects the holographic object **420** into an area enclosed by the six-sided aggregated seamless surface environment. In this example, the viewing volume of the LF display system is also contained within the six-sided aggregated seamless surface environment. Note that, in the illustrated configuration, the viewer **434** may be positioned between the holographic object **420** and a LF display module **414** that is projecting energy (e.g., light and/or pressure waves) that is used to form the holographic object **420**. Accordingly, the positioning of the viewer **434** may prevent the viewer **430** from perceiving the holographic object **420** formed from energy from the LF display module **414**. However, in the illustrated configuration there is at least one other LF display module, e.g., a LF display module **416**, that is unobstructed (e.g., by the viewer **434**) and can project energy to form the holographic object **420** and be observed by viewer **430**. In this manner, occlusion by viewers in the space can cause some portion of the holographic projections to disappear, but the effect is much less than if only one side of the volume was populated with holographic display panels. Holographic object **422** is illustrated "outside" the walls of the six-sided aggregated seamless surface environment because the holographic object volume extends behind the aggregated surface. Thus, the viewer **430** and/or the viewer **434** can perceive the holographic object **422** as "outside" of the enclosed six-sided environment which they can move throughout.

[0092] As described above in reference to FIG. **4A**, in some embodiments, the LF display system **402** actively tracks positions of viewers and may dynamically instruct different LF display modules to present holographic content based on the tracked positions. Accordingly, a multi-sided configuration can provide a more robust environment (e.g., relative to FIG. **4A**) for providing holographic objects where unconstrained viewers are free to move throughout the area enclosed by the multi-sided seamless surface environment.

[0093] Notably, various LF display systems may have different configurations. Further, each configuration may have a particular orientation of surfaces that, in aggregate, form a seamless display surface ("aggregate surface"). That is, the LF display modules of a LF display system can be tiled to form a variety of aggregate surfaces. For example, in FIG. **4B**, the LF display system **402** includes LF display modules tiled to form a six-sided aggregate surface that approximates the walls of a room. In some other examples, an aggregate surface may only occur on a portion of a surface (e.g., half of a wall) rather than a whole surface (e.g., an entire wall). Some examples are described herein.

[0094] In some configurations, the aggregate surface of a LF display system may include an aggregate surface configured to project energy towards a localized viewing volume. Projecting energy to a localized viewing volume allows for a higher quality viewing experience by, for example, increasing the density of projected energy in a specific viewing volume, increasing the FOV for the viewers in that volume, and bringing the viewing volume closer to the display surface.

[0095] For example, FIG. **4C** illustrates top down view of a LF display system **450A** with an aggregate surface in a

“winged” configuration. In this example, the LF display system 450A is located in a room with a front wall 452, a rear wall 454, a first sidewall 456, a second sidewall 458, a ceiling (not shown), and a floor (not shown). The first sidewall 456, the second sidewall 458, the rear wall 454, floor, and the ceiling are all orthogonal. The LF display system 450A includes LF display modules tiled to form an aggregate surface 460 covering the front wall. The front wall 452, and thus the aggregate surface 460, includes three portions: (i) a first portion 462 approximately parallel with the rear wall 454 (i.e., a central surface), (ii) a second portion 464 connecting the first portion 462 to the first sidewall 456 and placed at an angle to project energy towards the center of the room (i.e., a first side surface), and (iii) a third portion 466 connecting the first portion 462 to the second sidewall 458 and placed at an angle to project energy towards the center of the room (i.e., a second side surface). The first portion is a vertical plane in the room and has a horizontal and a vertical axis. The second and third portions are angled towards the center of the room along the horizontal axis.

[0096] In this example, the viewing volume 468A of the LF display system 450A is in the center of the room and partially surrounded by the three portions of the aggregate surface 460. An aggregate surface that at least partially surrounds a viewer (“surrounding surface”) increases the immersive experience of the viewers.

[0097] To illustrate, consider, for example, an aggregate surface with only a central surface. Referring to FIG. 2A, the rays that are projected from either end of the display surface create an ideal holographic volume and ideal viewing volumes as described above. Now consider, for example, if the central surface included two side surfaces angled towards the viewer. In this case, ray 256 and ray 257 would be projected at a greater angle from a normal of the central surface. Thus, the field of view of the viewing volume would increase. Similarly, the holographic viewing volume would be nearer the display surface. Additionally, because the two second and third portions tilted nearer the viewing volume, the holographic objects that are projected at a fixed distance from the display surface are closer to that viewing volume.

[0098] To simplify, a display surface with only a central surface has a planar field of view, a planar threshold separation between the (central) display surface and the viewing volume, and a planar proximity between a holographic object and the viewing volume. Adding one or more side surfaces angled towards the viewer increases the field of view relative to the planar field of view, decreases the separation between the display surface and the viewing volume relative to the planar separation, and increases the proximity between the display surface and a holographic object relative to the planar proximity. Further angling the side surfaces towards the viewer further increases the field of view, decreases the separation, and increases the proximity. In other words, the angled placement of the side surfaces increases the immersive experience for viewers.

[0099] Additionally, as described below in regards to FIG. 6, deflection optics may be used to optimize the size and position of the viewing volume for LF display parameters (e.g., dimensions and FOV).

[0100] Returning to FIG. 4D, in a similar example, FIG. 4D illustrates a side view of a LF display system 450B with an aggregate surface in a “sloped” configuration. In this example, the LF display system 450B is located in a room with a front wall 452, a rear wall 454, a first sidewall (not

shown), a second sidewall (not shown), a ceiling 472, and a floor 474. The first sidewall, the second sidewall, the rear wall 454, floor 474, and the ceiling 472 are all orthogonal. The LF display system 450B includes LF display modules tiled to form an aggregate surface 460 covering the front wall. The front wall 452, and thus the aggregate surface 460, includes three portions: (i) a first portion 462 approximately parallel with the rear wall 454 (i.e., a central surface), (ii) a second portion 464 connecting the first portion 462 to the ceiling 472 and angled to project energy towards the center of the room (i.e., a first side surface), and (iii) a third portion 466 connecting the first portion 462 to the floor 474 and angled to project energy towards the center of the room (i.e., a second side surface). The first portion is a vertical plane in the room and has a horizontal and a vertical axis. The second and third portions are angled towards the center of the room along the vertical axis.

[0101] In this example, the viewing volume 468B of the LF display system 450B is in the center of the room and partially surrounded by the three portions of the aggregate surface 460. Similar to the configuration shown in FIG. 4C, the two side portions (e.g., second portion 464, and third portion 466) are angled to surround the viewer and form a surrounding surface. The surrounding surface increases the viewing FOV from the perspective of any viewer in the holographic viewing volume 468B. Additionally, the surrounding surface allows the viewing volume 468B to be closer to the surface of the displays such that projected objects appear closer. In other words, the angled placement of the side surfaces increases the field of view, decreases the separation, and increases the proximity of the aggregate surface, thereby increasing the immersive experience for viewers. Further, as will be discussed below, deflection optics may be used to optimize the size and position of the viewing volume 468B.

[0102] The sloped configuration of the side portions of the aggregate surface 460 enables holographic content to be presented closer to the viewing volume 468B than if the third portion 466 was not sloped. For example, the lower extremities (e.g., legs) of a character presented from a LF display system in a sloped configuration may seem closer and more realistic than if a LF display system with a flat front wall were used.

[0103] Additionally, the configuration of the LF display system and the environment which it is located may inform the shape and locations of the viewing volumes and viewing sub-volumes.

[0104] FIG. 4E, for example, illustrates a top down view of a LF display system 450C with an aggregate surface 460 on a front wall 452 of a room. In this example, the LF display system 450D is located in a room with a front wall 452, a rear wall 454, a first sidewall 456, a second sidewall 458, a ceiling (not shown), and a floor (not shown).

[0105] LF display system 450C projects various rays from the aggregate surface 460. From each position on the display surface, light rays are projected in an angular range that is centered on the viewing volume. The rays projected from the left side of the aggregate surface 460 have horizontal angular range 481, rays projected from the right side of the aggregate surface have horizontal angular range 482, and rays projected from the center of the aggregate surface 460 have horizontal angular range 483. In between these points, the projected rays may take on intermediate values of angle ranges as described below in regard to FIG. 6. Having a

gradient deflection angle in the projected rays across the display surface in this manner creates a viewing volume **468C**. Further, this configuration avoids wasting resolution of the display on projecting rays into the side walls **456** and **458**.

[0106] FIG. 4F illustrates a side view of a LF display system **450D** with an aggregate surface **460** on a front wall **452** of a room. In this example, the LF display system **450E** is located in a room with a front wall **452**, a rear wall **454**, a first sidewall (not shown), a second sidewall (not shown), a ceiling **472**, and a floor **474**. In this example, the floor is tiered such that each tier rises in steps moving from the front wall to the back wall. Here, each tier of the floor includes a viewing sub-volume (e.g., viewing sub volume **470A** and **470B**). A tiered floor allows for viewing sub-volumes that do not overlap. That is, each viewing sub-volume has a line of sight from the viewing sub-volume to the aggregate surface **460** that does not pass through another viewing sub-volume. In other words, this orientation produces a “stadium seating” effect in which the vertical offset between tiers allows an unobstructed line of sight which allows each tier to “see over” the viewing sub-volumes of other tiers. LF display systems including viewing sub-volumes that do not overlap may provide a higher quality viewing experience than LF display systems that have viewing volumes that do overlap. For example, in the configuration shown in FIG. 4F, different holographic content may be projected to the audiences in viewing sub-volumes **470A** and **470B**.

#### Control of a LF Display System

[0107] FIG. 5A is a block diagram of a LF display system **500**, in accordance with one or more embodiments. The LF display system **500** comprises a LF display assembly **510** and a controller **520**. The LF display assembly **510** includes one or more LF display modules **512** which project a light field. A LF display module **512** may include a source/sensor system **514** that includes an integrated energy source(s) and/or energy sensor(s) which project and/or sense other types of energy. The controller **520** includes a datastore **522**, a network interface **524**, and a LF processing engine **530**. The controller **520** may also include a tracking module **526**, and a viewer profiling module **528**. In some embodiments, the LF display system **500** also includes a sensory feedback system **570** and a tracking system **580**. The LF display systems described in the context of FIGS. 1, 2, 3, and 4 are embodiments of the LF display system **500**. In other embodiments, the LF display system **500** comprises additional or fewer modules than those described herein. Similarly, the functions can be distributed among the modules and/or different entities in a different manner than is described here. Applications of the LF display system **500** are also discussed in detail below with regard to FIGS. 6-9.

[0108] The LF display assembly **510** provides holographic content in a holographic object volume that may be visible to viewers located within a viewing volume. The LF display assembly **510** may provide holographic content by executing display instructions received from the controller **520**. The holographic content may include one or more holographic objects that are projected in front of an aggregate surface the LF display assembly **510**, behind the aggregate surface of the LF display assembly **510**, or some combination thereof. Generating display instructions with the controller **520** is described in more detail below.

[0109] The LF display assembly **510** provides holographic content using one or more LF display modules (e.g., any of the LF display module **110**, the LF display system **200**, and LF display module **300**) included in an LF display assembly **510**. For convenience, the one or more LF display modules may be described herein as LF display module **512**. The LF display module **512** can be tiled to form a LF display assembly **510**. The LF display modules **512** may be structured as various seamless surface environments (e.g., single sided, multi-sided, a wall of a presentation space, a curved surface, etc.). That is, the tiled LF display modules form an aggregate surface. As previously described, a LF display module **512** includes an energy device layer (e.g., energy device layer **220**) and an energy waveguide layer (e.g., energy waveguide layer **240**) that present holographic content. The LF display module **512** may also include an energy relay layer (e.g., energy relay layer **230**) that transfers energy between the energy device layer and the energy waveguide layer when presenting holographic content.

[0110] The LF display module **512** may also include other integrated systems configured for energy projection and/or energy sensing as previously described. For example, a light field display module **512** may include any number of energy devices (e.g., energy device **340**) configured to project and/or sense energy. For convenience, the integrated energy projection systems and integrated energy sensing systems of the LF display module **512** may be described herein, in aggregate, as the source/sensor system **514**. The source/sensor system **514** is integrated within the LF display module **512**, such that the source/sensor system **514** shares the same seamless energy surface with LF display module **512**. In other words, the aggregate surface of an LF display assembly **510** includes the functionality of both the LF display module **512** and the source/sensor module **514**. That is, an LF assembly **510** including a LF display module **512** with a source/sensor system **514** may project energy and/or sense energy while simultaneously projecting a light field. For example, the LF display assembly **510** may include a LF display module **512** and source/sensor system **514** configured as a dual-energy surface or bidirectional energy surface as previously described.

[0111] In some embodiments, the LF display system **500** augments the generated holographic content with other sensory content (e.g., coordinated touch, audio, or smell) using a sensory feedback system **570**. The sensory feedback system **570** may augment the projection of holographic content by executing display instructions received from the controller **520**. Generally, the sensory feedback system **570** includes any number of sensory feedback devices external to the LF display assembly **510** (e.g., sensory feedback system **442**). Some example sensory feedback devices may include coordinated acoustic projecting and receiving devices, aroma projecting devices, temperature adjustment devices, force actuation devices, pressure sensors, transducers, etc. In some cases, the sensory feedback system **570** may have similar functionality to the light field display assembly **510** and vice versa. For example, both a sensory feedback system **570** and a light field display assembly **510** may be configured to generate a sound field. As another example, the sensory feedback system **570** may be configured to generate haptic surfaces while the light field display **510** assembly is not.

[0112] To illustrate, in an example embodiment of a light field display system **500**, a sensory feedback system **570**

may include one or more acoustic projection devices. The one or more acoustic projection devices are configured to generate one or more pressure waves that complement the holographic content when executing display instructions received from the controller **520**. The generated pressure waves may be, e.g., audible (for sound), ultrasonic (for touch), or some combination thereof. Similarly, the sensory feedback system **570** may include an aroma projecting device. The aroma projecting device may be configured to provide scents to some, or all, of the target area when executing display instructions received from the controller. The aroma devices may be tied into an air circulation system (e.g., ducting, fans, or vents) to coordinate air flow within the target area. Further, the sensory feedback system **570** may include a temperature adjustment device. The temperature adjustment device is configured to increase or decrease temperature in some, or all, of the target area when executing display instructions received from the controller **520**.

[0113] In some embodiments, the sensory feedback system **570** is configured to receive input from viewers of the LF display system **500**. In this case, the sensory feedback system **570** includes various sensory feedback devices for receiving input from viewers. The sensory feedback devices may include devices such as acoustic receiving devices (e.g., a microphone), pressure sensors, joysticks, motion detectors, transducers, etc. The sensory feedback system may transmit the detected input to the controller **520** to coordinate generating holographic content and/or sensory feedback.

[0114] To illustrate, in an example embodiment of a light field display assembly, a sensory feedback system **570** includes a microphone. The microphone is configured to record audio produced by one or more viewers (e.g., gasps, screams, laughter, etc.). The sensory feedback system **570** provides the recorded audio to the controller **520** as viewer input. The controller **520** may use the viewer input to generate holographic content. Similarly, the sensory feedback system **570** may include a pressure sensor. The pressure sensor is configured to measure forces applied by viewers to the pressure sensor. The sensory feedback system **570** may provide the measured forces to the controller **520** as viewer input.

[0115] In some embodiments, the LF display system **500** includes a tracking system **580**. The tracking system **580** includes any number of tracking devices configured to determine the position, movement and/or characteristics of viewers in the target area. Generally, the tracking devices are external to the LF display assembly **510**. Some example tracking devices include a camera assembly (“camera”), a depth sensor, structured light, a LIDAR system, a card scanning system, or any other tracking device that can track viewers within a target area.

[0116] The tracking system **580** may include one or more energy sources that illuminate some or all of the target area with light. However, in some cases, the target area is illuminated with natural light and/or ambient light from the LF display assembly **510** when presenting holographic content. The energy source projects light when executing instructions received from the controller **520**. The light may be, e.g., a structured light pattern, a pulse of light (e.g., an IR flash), or some combination thereof. The tracking system may project light in the visible band (~380 nm to 750 nm), in the infrared (IR) band (~750 nm to 1700 nm), in the ultraviolet band (10 nm to 380 nm), some other portion of

the electromagnetic spectrum, or some combination thereof. A source may include, e.g., a light emitted diode (LED), a micro LED, a laser diode, a TOF depth sensor, a tunable laser, etc.

[0117] The tracking system **580** may adjust one or more emission parameters when executing instructions received from the controller **520**. An emission parameter is a parameter that affects how light is projected from a source of the tracking system **580**. An emission parameter may include, e.g., brightness, pulse rate (to include continuous illumination), wavelength, pulse length, some other parameter that affects how light is projected from the source assembly, or some combination thereof. In one embodiment, a source projects pulses of light in a time-of-flight operation.

[0118] The camera of the tracking system **580** captures images of the light (e.g., structured light pattern) reflected from the target area. The camera captures images when executing tracking instructions received from the controller **520**. As previously described, the light may be projected by a source of the tracking system **580**. The camera may include one or more cameras. That is, a camera may be, e.g., an array (1D or 2D) of photodiodes, a CCD sensor, a CMOS sensor, some other device that detects some or all of the light project by the tracking system **580**, or some combination thereof. In an embodiment, the tracking system **580** may contain a light field camera external to the LF display assembly **510**. In other embodiments, the cameras are included as part of the LF display source/sensor module **514** included in the LF display assembly **510**. For example, as previously described, if the energy relay element of a light field module **512** is a bidirectional energy layer which interleaves both emissive displays and imaging sensors at the energy device layer **220**, the LF display assembly **510** can be configured to simultaneously project light fields and record imaging information from the viewing area in front of the display. In one embodiment, the captured images from the bidirectional energy surface form a light field camera. The camera provides captured images to the controller **520**.

[0119] The camera of the tracking system **580** may adjust one or more imaging parameters when executing tracking instructions received from the controller **520**. An imaging parameter is a parameter that affects how the camera captures images. An imaging parameter may include, e.g., frame rate, aperture, gain, exposure length, frame timing, rolling shutter or global shutter capture modes, some other parameter that affects how the camera captures images, or some combination thereof.

[0120] The controller **520** controls the LF display assembly **510** and any other components of the LF display system **500**. The controller **520** comprises a data store **522**, a network interface **524**, a tracking module **526**, a viewer profiling module **528**, and a light field processing engine **530**. In other embodiments, the controller **520** comprises additional or fewer modules than those described herein. Similarly, the functions can be distributed among the modules and/or different entities in a different manner than is described here. For example, the tracking module **526** may be part of the LF display assembly **510** or the tracking system **580**.

[0121] The data store **522** is a memory that stores information for the LF display system **500**. The stored information may include display instructions, tracking instructions, emission parameters, imaging parameters, a virtual model of a target area, tracking information, images captured by the

camera, one or more viewer profiles, calibration data for the light field display assembly 510, configuration data for the LF display system 510 including resolution and orientation of LF modules 512, desired viewing volume geometry, content for graphics creation including 3D models, scenes and environments, materials and textures, other information that may be used by the LF display system 500, or some combination thereof. The data store 522 is a memory, such as a read only memory (ROM), dynamic random access memory (DRAM), static random access memory (SRAM), or some combination thereof.

[0122] The network interface 524 allows the light field display system to communicate with other systems or environments via a network. In one example, the LF display system 500 receives holographic content from a remote light field display system via the network interface 524. In another example, the LF display system 500 transmits holographic content to a remote data store using the network interface 524.

[0123] The tracking module 526 tracks viewers viewing content presented by the LF display system 500. To do so, the tracking module 526 generates tracking instructions that control operation of the source(s) and/or the camera(s) of the tracking system 580, and provides the tracking instructions to the tracking system 580. The tracking system 580 executes the tracking instructions and provides tracking input to the tracking module 526.

[0124] The tracking module 526 may determine a position of one or more viewers within the target area (e.g., sitting in the seats of a presentation space). The determined position may be relative to, e.g., some reference point (e.g., a display surface). In other embodiments, the determined position may be within the virtual model of the target area. The tracked position may be, e.g., the tracked position of a viewer and/or a tracked position of a portion of a viewer (e.g., eye location, hand location, etc.). The tracking module 526 determines the position using one or more captured images from the cameras of the tracking system 580. The cameras of the tracking system 580 may be distributed about the LF display system 500, and can capture images in stereo, allowing for the tracking module 526 to passively track viewers. In other embodiments, the tracking module 526 actively tracks viewers. That is, the tracking system 580 illuminates some portion of the target area, images the target area, and the tracking module 526 uses time of flight and/or structured light depth determination techniques to determine position. The tracking module 526 generates tracking information using the determined positions.

[0125] The tracking module 526 may also receive tracking information as inputs from viewers of the LF display system 500. The tracking information may include body movements that correspond to various input options that the viewer is provided by the LF display system 500. For example, the tracking module 526 may track a viewer's body movement and assign any various movement as an input to the LF processing engine 530. The tracking module 526 may provide the tracking information to the data store 522, the LF processing engine 530, the viewer profiling module 528, any other component of the LF display system 500, or some combination thereof.

[0126] To provide context for the tracking module 526, consider an example embodiment of an LF display system 500 that displays a play in which a performer in the play scores a winning touchdown. In response to the scene, a

viewer first pumps the air to show their excitement. The tracking system 580 may record the movement of the viewer's hands and transmit the recording to the tracking module 526. This may be achieved with a tracking system 580 comprised of cameras, depth sensors, or other devices that are external to the light field display assembly 510, or with a display surface which simultaneously projects light field images and records images, wherein the images recorded from the display surface may be light field images, or any combination of these devices, as previously described. The tracking module 526 tracks the motion of the viewer's hands in the recording and sends the input to LF processing engine 530. The viewer profiling module 528, as described below, determines that information in the image indicates that motion of the viewer's hands are associated with a positive response. Accordingly, if enough viewers are recognized having a positive response, the LF processing engine 530 generates appropriate holographic content to celebrate the touchdown. For example, the LF processing engine 530 may project confetti in the scene.

[0127] The LF display system 500 includes a viewer profiling module 528 configured to identify and profile viewers. The viewer profiling module 528 generates a profile of a viewer (or viewers) that views holographic content displayed by a LF display system 500. The viewer profiling module 528 generates a viewer profile based, in part, on viewer input and monitored viewer behavior, actions, and reactions. The viewer profiling module 528 can access information obtained from tracking system 580 (e.g., recorded images, videos, sound, etc.) and process that information to determine various information. In various examples, viewer profiling module 528 can use any number of machine vision or machine hearing algorithms to determine viewer behavior, actions, and reactions. Monitored viewer behavior can include, for example, smiles, cheering, clapping, laughing, fright, screams, excitement levels, recoiling, other changes in gestures, or movement by the viewers, etc.

[0128] More generally, a viewer profile may include any information received and/or determined about a viewer viewing holographic content from the LF display system. For example, each viewer profile may log actions or responses of that viewer to the content displayed by the LF display system 500. Some example information that can be included in a viewer profile are provided below.

[0129] In some embodiments, a viewer profile may describe a response of a viewer within the presentation space with respect to a person displayed in the holographic content (e.g., an athlete, a player, etc.). For example, a viewer profile may indicate that a viewer generally has positive response to athletes of particular teams that have a mascot of a Cowboy.

[0130] In some embodiments, a viewer profile can indicate characteristics of a viewer viewing a sporting event. For example, a viewer in a presentation space is wearing a sweatshirt displaying a university logo. In this case, the viewer profile can indicate that the viewer is wearing a sweatshirt and may prefer holographic content associated with the university whose logo is on the sweatshirt. More broadly, viewer characteristics that can be indicated in a viewer profile may include, for example, age, sex, ethnicity, clothing, viewing location in the presentation space, etc.

[0131] In some embodiments, a viewer profile can indicate preferences for a viewer in regard to desirable sporting event and/or presentation space characteristics. For example, a

viewer profile may indicate that a viewer prefers only to view holographic content that is age appropriate for everyone in their family. In another example, a viewer profile may indicate holographic object volumes to display holographic content (e.g., on a wall) and holographic object volumes to not display holographic content (e.g., above their head). The viewer profile may also indicate that the viewer prefers to have haptic interfaces presented near them, or prefers to avoid them.

**[0132]** In another example, a viewer profile indicates a history of sporting events viewed for a particular viewer. For instance, viewer profiling module **528** determines that a viewer, or group of viewers, has previously attended a sporting event. As such the LF display system **500** may display holographic content that is different than the previous time the viewers attended the sporting event. As one example, a sporting event including holographic content may have three different holographic advertisements during game intermissions, and LF display system **500** may display different advertisements based on the viewers in attendance. In another example, each of the three advertisements may be presented to different viewing volumes in the same presentation space.

**[0133]** In some embodiments, a viewer profile may also describe characteristics and preferences for a group of viewers rather than a particular viewer. For example, viewer profiling module **528** may generate a viewer profile for the audience viewing a sporting event in the presentation space. In one example, viewer profiling module **528** creates a viewer profile for viewers viewing a sporting event such as beach volleyball. The profile indicates that 54.3% of the viewers are women between the age of 20 and 35 and have a positive response to the sporting event. The profile also indicates that the remaining 46.7% of the viewers are men between the ages of 20 and 35 and are having a mediocre response to the sporting event. Any of the previously described information and characteristics may be applied to a group of viewers.

**[0134]** The viewer profiling module **528** may also access a profile associated with a particular viewer (or viewers) from a third-party system or systems to build a viewer profile. For example, a viewer purchases a ticket for a sporting event using a third-party vendor that is linked to that viewer's social media account. Thus, the viewer's ticket is linked to his social media account. When the viewer enters a presentation space for the sporting event using their ticket, the viewer profiling module **528** can access information from his social media account to build (or augment) a viewer profile.

**[0135]** In some embodiments, the data store **522** includes a viewer profile store that stores viewer profiles generated, updated, and/or maintained by the viewer profiling module **528**. The viewer profile can be updated in the data store at any time by the viewer profiling module **528**. For example, in an embodiment, the viewer profile store receives and stores information regarding a particular viewer in their viewer profile when the particular viewer views holographic content provided by the LF display system **500**. In this example, the viewer profiling module **528** includes a facial recognition algorithm that may recognize viewers and positively identify them as they view presented holographic content. To illustrate, as a viewer enters the target area of the LF display system **500**, the tracking system **580** obtains an image of the viewer. The viewer profiling module **528** inputs

the captured image and identifies the viewer's face using the facial recognition algorithm. The identified face is associated with a viewer profile in the profile store and, as such, all input information obtained about that viewer may be stored in their profile. The viewer profiling module may also utilize card identification scanners, voice identifiers, a radio-frequency identification (RFID) chip scanners, barcode scanners, etc. to positively identify a viewer.

**[0136]** In embodiments where the viewer profiling module **528** can positively identify viewers, the viewer profiling module **528** can determine each visit of each viewer to the LF display system **500**. The viewer profiling module **528** may then store the time and date of each visit in the viewer profile for each viewer. Similarly, the viewer profiling module **528** may store received inputs from a viewer from any combination of the sensory feedback system **570**, the tracking system **580**, and/or the LF display assembly **510** each time they occur. The viewer profile system **528** may additionally receive further information about a viewer from other modules or components of the controller **520** which can then be stored with the viewer profile. Other components of the controller **520** may then also access the stored viewer profiles for determining subsequent content to be provided to that viewer.

**[0137]** The LF processing engine **530** generates holographic content comprised of light field data, as well as data for all of the sensory domains supported by a LF display system **500**. For example, LF processing engine **530** may generate 4D coordinates in a rasterized format ("rasterized data") that, when executed by the LF display assembly **510**, cause the LF display assembly **510** to present holographic content. The LF processing engine **530** may access the rasterized data from the data store **522**. Additionally, the LF processing engine **530** may construct rasterized data from a vectorized data set. Vectorized data is described below. The LF processing engine **530** can also generate sensory instructions required to provide sensory content that augments the holographic objects. As described above, sensory instructions may generate, when executed by the LF display system **500**, haptic surfaces, sound fields, and other forms of sensory energy supported by the LF display system **500**. The LF processing engine **530** may access sensory instructions from the data store **522**, or construct the sensory instructions from a vectorized data set. In aggregate, the 4D coordinates and sensory data represent holographic content as display instructions executable by a LF display system to generate holographic and sensory content. More generally, holographic content can take the form of CG content with ideal light field coordinates, live action content, rasterized data, vectorized data, electromagnetic energy transported by a set of relays, instructions sent to a group of energy devices, energy locations on one or more energy surfaces, the set of energy propagation paths that are projected from the display surface, a holographic object that is visible to a viewer or an audience, and many other similar forms.

**[0138]** The amount of rasterized data describing the flow of energy through the various energy sources in a LF display system **500** is incredibly large. While it is possible to display the rasterized data on a LF display system **500** when accessed from a data store **522**, it is untenable to efficiently transmit, receive (e.g., via a network interface **524**), and subsequently display the rasterized data on a LF display system **500**. Take, for example, rasterized data representing a short sporting event for holographic projection by a LF



display system **500**. In this example, the LF display system **500** includes a display containing several gigapixels and the rasterized data contains information for each pixel location on the display. The corresponding size of the rasterized data is vast (e.g., many gigabytes per second of sporting event display time), and unmanageable for efficient transfer over commercial networks via a network interface **524**. The efficient transfer problem may be amplified for applications including live streaming of holographic content. An additional problem with merely storing rasterized data on data store **522** arises when an interactive experience is desired using inputs from the sensory feedback system **570** or the tracking module **526**. To enable an interactive experience, the light field content generated by the LF processing engine **530** can be modified in real-time in response to sensory or tracking inputs. In other words, in some cases, LF content cannot simply be read from the data store **522**.

[0139] Therefore, in some configurations, data representing holographic content for display by a LF display system **500** may be transferred to the LF processing engine **530** in a vectorized data format (“vectorized data”). Vectorized data may be orders of magnitude smaller than rasterized data. Further, vectorized data provides high image quality while having a data set size that enables efficient sharing of the data. For example, vectorized data may be a sparse data set derived from a denser data set. Thus, vectorized data may have an adjustable balance between image quality and data transmission size based on how sparse vectorized data is sampled from dense rasterized data. Tunable sampling to generate vectorized data enables optimization of image quality for a given network speed. Consequently, vectorized data enables efficient transmission of holographic content via a network interface **524**. Vectorized data also enables holographic content to be live-streamed over a commercial network.

[0140] In summary, the LF processing engine **530** may generate holographic content derived from rasterized data accessed from the data store **522**, vectorized data accessed from the data store **522**, or vectorized data received via the network interface **524**. In various configurations, vectorized data may be encoded by an encoder before data transmission, and decoded by a decoder within the LF controller **520** after reception. The encoder and decoder pair may be part of the same proprietary system codec. In some examples, the vectorized data is encoded for added data security and sporting event improvements related to data compression. For example, vectorized data received by the network interface may be encoded vectorized data received from a holographic streaming application. In some examples, vectorized data may require a decoder, the LF processing engine **530**, or both of these to access information content encoded in vectorized data. The encoder and/or decoder systems may be available to customers or licensed to third-party vendors. Other example encoding and/or decoding schemes can be employed to transmit and/or present holographic content.

[0141] Vectorized data contains all the information for each of the sensory domains supported by a LF display system **500** in way that may support an interactive experience. For example, vectorized data for an interactive holographic experience may include any vectorized properties that can provide accurate physics for each of the sensory domains supported by a LF display system **500**. Vectorized properties may include any properties that can be synthetically programmed, captured, computationally assessed, etc.

A LF processing engine **530** may be configured to translate vectorized properties in vectorized data to rasterized data. The LF processing engine **530** may then project holographic content translated from the vectorized data using the LF display assembly **510**. In various configurations, the vectorized properties may include one or more red/green/blue/alpha channel (RGBA)+depth images, multi view images with or without depth information at varying resolutions that may include one high-resolution center image and other views at a lower resolution, material properties such as albedo and reflectance, surface normals, other optical effects, surface identification, geometrical object coordinates, virtual camera coordinates, display plane locations, lighting coordinates, tactile stiffness for surfaces, tactile ductility, tactile strength, amplitude and coordinates of sound fields, environmental conditions, somatosensory energy vectors related to the mechanoreceptors for textures or temperature, audio, and any other sensory domain property. Many other vectorized properties are also possible.

[0142] The LF display system **500** may also generate an interactive viewing experience. That is, holographic content may be responsive to input stimuli containing information about viewer locations, gestures, interactions, interactions with holographic content, or other information derived from the viewer profiling module **528**, and/or tracking module **526**. For example, in an embodiment, a LF processing system **500** creates an interactive viewing experience using vectorized data of a real-time sporting event received via a network interface **524**. In another example, if a holographic object needs to move in a certain direction immediately in response to a viewer interaction, the LF processing engine **530** may update the render of the scene so the holographic object moves in that required direction. This may require the LF processing engine **530** to use a vectorized data set to render light fields in real time based a 3D graphical scene with the proper object placement and movement, collision detection, occlusion, color, shading, lighting, etc., correctly responding to the viewer interaction. The LF processing engine **530** converts the vectorized data into rasterized data for presentation by the LF display assembly **510**. The LF display system **500** may employ various other encoding/decoding techniques that allow the LF display system to present holographic content in an approximately real time.

[0143] The rasterized data includes holographic content instructions and sensory instructions (display instructions) representing the real-time sporting event. The LF display assembly **510** simultaneously projects holographic and sensory content of the real-time sporting event by executing the display instructions. The LF display system **500** monitors viewer interactions (e.g., vocal response, touching, etc.) with the presented real-time sporting event with the tracking module **526** and viewer profiling module **528**. In response to the viewer interactions, the LF processing engine may create an interactive experience by generating additional holographic and/or sensory content for display to the viewers.

[0144] To illustrate, consider an example embodiment of an LF display system **500** including a LF processing engine **530** that generates a plurality of holographic objects representing balloons falling from the ceiling of a presentation space during a sporting event. A viewer may move to touch the holographic object representing the balloon. Correspondingly, the tracking system **580** tracks movement of the viewer’s hands relative to the holographic object. The movement of the viewer is recorded by the tracking system **580**

and sent to the controller **520**. The tracking module **526** continuously determines the motion of the viewer's hand and sends the determined motions to the LF processing engine **530**. The LF processing engine **530** determines the placement of the viewer's hand in the scene, adjusts the real-time rendering of the graphics to include any required change in the holographic object (such as position, color, or occlusion). The LF processing engine **530** instructs the LF display assembly **510** (and/or sensory feedback system **570**) to generate a tactile surface using the volumetric haptic projection system (e.g., using ultrasonic speakers). The generated tactile surface corresponds to at least a portion of the holographic object and occupies substantially the same space as some or all of an exterior surface of the holographic object. The LF processing engine **530** uses the tracking information to dynamically instruct the LF display assembly **510** to move the location of the tactile surface along with a location of the rendered holographic object such that the viewer is given both a visual and tactile perception of touching the balloon. More simply, when a viewer views his hand touching a holographic balloon, the viewer simultaneously feels haptic feedback indicating their hand touches the holographic balloon, and the balloon changes position or motion in response to the touch. In some examples, rather than presenting and interactive balloon in a sporting event accessed from a data store **522**, the interactive balloon may be received as part of holographic content received from a live-streaming application via a network interface **524**. In other words, the holographic content displayed by the LF display system **500** may be a holographic content live-stream.

[0145] LF processing engine **530** may provide holographic content to display to viewers in a presentation space before, during, and/or after a sporting event to augment the presentation space experience. The holographic content may be provided by the publisher of the sporting event, provided by the presentation space, provided by an advertiser, generated by a LF processing engine **530**, etc. The holographic content may be content associated with the sporting event, the genre of the sporting event, the location of the presentation space, advertisements, etc. In any case, the holographic content may be stored in the data store **522**, or streamed to the LF display system **500** in vectorized format through the network interface **524**. For example, a sporting event may be shown in a presentation space augmented with LF display modules on the walls. The distributor of the sporting event may provide holographic content to present on the wall displays before the sporting event begins. The LF processing engine **530** accesses the holographic content and presents the accessed content from the displays on the walls of the presentation space before the sporting event begins. In another example, a presentation space with an LF display system **500** is located in San Francisco. The LF display system of a presentation space stores a holographic representation of the Golden Gate Bridge to present before a sporting event if no sporting event specific content is provided. Here, as no sporting event-specific holographic content is provided, the LF processing engine **530** accesses and presents the Golden Gate Bridge in the presentation space. In another example, an advertiser has provided holographic content of its products as advertisements to a presentation space to display after a sporting event. After the sporting event concludes, the LF processing engine **530** presents the advertisements to the viewers as they leave the presentation

space. In other examples, as described below, a LF processing engine may dynamically generate holographic content to display on the walls of the theater.

[0146] The LF processing engine **500** may also modify holographic content to suit the presentation space that is presenting the holographic content. For example, not every presentation space is the same size, has the same number of seats, or has the same technical configuration. As such, LF processing engine **530** may modify holographic content such that it will be appropriately displayed in a presentation space. In an embodiment, the LF processing engine **530** may access a configuration file of a presentation space including the layout, resolution, field-of-view, other technical specifications, etc. of the presentation space. The LF processing engine **530** may render and present the holographic content based on information included in the configuration file.

[0147] The LF processing engine **530** may also create holographic content for display by the LF display system **500**. Importantly, here, creating holographic content for display is different from accessing, or receiving, holographic content for display. That is, when creating content, the LF processing engine **530** generates entirely new content for display rather than accessing previously generated and/or received content. The LF processing engine **530** can use information from the tracking system **580**, the sensory feedback system **570**, the viewer profiling module **528**, the tracking module **526**, or some combination thereof, to create holographic content for display. In some examples, LF processing engine **530** may access information from elements of the LF display system **500** (e.g., tracking information and/or a viewer profile), create holographic content based on that information, and display the created holographic content using the LF display system **500** in response. The created holographic content may be augmented with other sensory content (e.g., touch, audio, or smell) when displayed by the LF display system **500**. Further, the LF display system **500** may store created holographic content such that it may be displayed in the future.

#### Dynamic Content Generation for a LF Display System

[0148] In some embodiments, the LF processing engine **530** incorporates an artificial intelligence (AI) model to create holographic content for display by the LF display system **500**. The AI model may include supervised or unsupervised learning algorithms including but not limited to regression models, neural networks, classifiers, or any other AI algorithm. The AI model may be used to determine viewer preferences based on viewer information recorded by the LF display system **500** (e.g., by tracking system **580**) which may include information on a viewer's behavior.

[0149] The AI model may access information from the data store **522** to create holographic content. For example, the AI model may access viewer information from a viewer profile or profiles in the data store **522** or may receive viewer information from the various components of the LF display system **500**. To illustrate, the AI model may determine a viewer enjoys seeing holographic content in which a performer wears a bow tie. The AI model may determine the preference based on a group of viewer's positive reactions or responses to previously viewed holographic content including a bow-tie wearing actor. That is, the AI model may create holographic content personalized to a set of viewers according to the learned preferences of those viewers. So, for example, the AI model may create bow-ties for actors

displayed in the holographic content viewed by a group of viewers using the LF display system **500**. The AI model may also store the learned preferences of each viewer in the viewer profile store of the data store **522**. In some examples, the AI model may create holographic content for an individual viewer rather than a group of viewers.

**[0150]** One example of an AI model that can be used to identify characteristics of viewers, identify reactions, and/or generate holographic content based on the identified information is a convolutional neural network model with layers of nodes, in which values at nodes of a current layer are a transformation of values at nodes of a previous layer. A transformation in the model is determined through a set of weights and parameters connecting the current layer and the previous layer. For example, an AI model may include five layers of nodes: layers A, B, C, D, and E. The transformation from layer A to layer B is given by a function  $W_1$ , the transformation from layer B to layer C is given by  $W_2$ , the transformation from layer C to layer D is given by  $W_3$ , and the transformation from layer D to layer E is given by  $W_4$ . In some examples, the transformation can also be determined through a set of weights and parameters used to transform between previous layers in the model. For example, the transformation  $W_4$  from layer D to layer E can be based on parameters used to accomplish the transformation  $W_1$  from layer A to B.

**[0151]** The input to the model can be an image taken by tracking system **580** encoded onto the convolutional layer A and the output of the model is holographic content decoded from the output layer E. Alternatively or additionally, the output may be a determined characteristic of a viewer in the image. In this example, the AI model identifies latent information in the image representing viewer characteristics in the identification layer C. The AI model reduces the dimensionality of the convolutional layer A to that of the identification layer C to identify any characteristics, actions, responses, etc. in the image. In some examples, the AI model then increases the dimensionality of the identification layer C to generate holographic content.

**[0152]** The image from the tracking system **580** is encoded to a convolutional layer A. Images input in the convolutional layer A can be related to various characteristics and/or reaction information, etc. in the identification layer C. Relevance information between these elements can be retrieved by applying a set of transformations between the corresponding layers. That is, a convolutional layer A of an AI model represents an encoded image, and identification layer C of the model represents a smiling viewer. Smiling viewers in a given image may be identified by applying the transformations  $W_1$  and  $W_2$  to the pixel values of the image in the space of convolutional layer A. The weights and parameters for the transformations may indicate relationships between information contained in the image and the identification of a smiling viewer. For example, the weights and parameters can be a quantization of shapes, colors, sizes, etc. included in information representing a smiling viewer in an image. The weights and parameters may be based on historical data (e.g., previously tracked viewers).

**[0153]** Smiling viewers in the image are identified in the identification layer C. The identification layer C represents identified smiling viewers based on the latent information about smiling viewers in the image.

**[0154]** Identified smiling viewers in an image can be used to generate holographic content. To generate holographic

content, the AI model starts at the identification layer C and applies the transformations  $W_2$  and  $W_3$  to the value of the given identified smiling viewers in the identification layer C. The transformations result in a set of nodes in the output layer E. The weights and parameters for the transformations may indicate relationships between an identified smiling viewers and specific holographic content and/or preferences. In some cases, the holographic content is directly output from the nodes of the output layer E, while in other cases the content generation system decodes the nodes of the output layer E into a holographic content. For example, if the output is a set of identified characteristics, the LF processing engine can use the characteristics to generate holographic content.

**[0155]** Additionally, the AI model can include layers known as intermediate layers. Intermediate layers are those that do not correspond to an image, identifying characteristics/reactions, etc., or generating holographic content. For example, in the given example, layer B is an intermediate layer between the convolutional layer A and the identification layer C. Layer D is an intermediate layer between the identification layer C and the output layer E. Hidden layers are latent representations of different aspects of identification that are not observed in the data, but may govern the relationships between the elements of an image when identifying characteristics and generating holographic content. For example, a node in the hidden layer may have strong connections (e.g., large weight values) to input values and identification values that share the commonality of “laughing people smile.” As another example, another node in the hidden layer may have strong connections to input values and identification values that share the commonality of “scared people scream.” Of course, any number of linkages are present in a neural network. Additionally, each intermediate layer is a combination of functions such as, for example, residual blocks, convolutional layers, pooling operations, skip connections, concatenations, etc. Any number of intermediate layers B can function to reduce the convolutional layer to the identification layer and any number of intermediate layers D can function to increase the identification layer to the output layer.

**[0156]** In one embodiment, the AI model includes deterministic methods that have been trained with reinforcement learning (thereby creating a reinforcement learning model). The model is trained to increase the quality of the sporting event using measurements from tracking system **580** as inputs, and changes to the created holographic content as outputs.

**[0157]** Reinforcement learning is a machine learning system in which a machine learns ‘what to do’—how to map situations to actions—so as to maximize a numerical reward signal. The learner (e.g. LF processing engine **530**) is not told which actions to take (e.g., generating prescribed holographic content), but instead discovers which actions yield the most reward (e.g., increasing the quality of holographic content by making more people cheer) by trying them. In some cases, actions may affect not only the immediate reward but also the next situation and, through that, all subsequent rewards. These two characteristics—trial-and-error search and delayed reward—are two distinguishing features of reinforcement learning.

**[0158]** Reinforcement learning is defined not by characterizing learning methods, but by characterizing a learning problem. Basically, a reinforcement learning system captures those important aspects of the problem facing a learn-

ing agent interacting with its environment to achieve a goal. That is, in the example of generating a song for a performer, the reinforcement learning system captures information about viewers in the presentation space (e.g., age, disposition, etc.). Such an agent senses the state of the environment and takes actions that affect the state to achieve a goal or goals (e.g., creating a pop song for which the viewers will cheer). In its most basic form, the formulation of reinforcement learning includes three aspects for the learner: sensation, action, and goal. Continuing with the song example, the LF processing engine 530 senses the state of the environment with sensors of the tracking system 580, displays holographic content to the viewers in the environment, and achieves a goal that is a measure of the viewer's reception of that song.

[0159] One of the challenges that arises in reinforcement learning is the trade-off between exploration and exploitation. To increase the reward in the system, a reinforcement learning agent prefers actions that it has tried in the past and found to be effective in producing reward. However, to discover actions that produce reward, the learning agent selects actions that it has not selected before. The agent 'exploits' information that it already knows in order to obtain a reward, but it also 'explores' information in order to make better action selections in the future. The learning agent tries a variety of actions and progressively favors those that appear to be best while still attempting new actions. On a stochastic task, each action is generally tried many times to gain a reliable estimate to its expected reward. For example, if the LF processing engine creates holographic content that the LF processing engine knows will result in a viewer laughing after a long period of time, the LF processing engine may change the holographic content such that the time until a viewer laughs decreases.

[0160] Further, reinforcement learning considers the whole problem of a goal-directed agent interacting with an uncertain environment. Reinforcement learning agents have explicit goals, can sense aspects of their environments, and can choose actions to receive high rewards (i.e., a roaring crowd). Moreover, agents generally operate despite significant uncertainty about the environment they face. When reinforcement learning involves planning, the system addresses the interplay between planning and real-time action selection, as well as the question of how environmental elements are acquired and improved. For reinforcement learning to make progress, important sub problems have to be isolated and studied, the sub problems playing clear roles in complete, interactive, goal-seeking agents.

[0161] The reinforcement learning problem is a framing of a machine learning problem where interactions are processed and actions are carried out to achieve a goal. The learner and decision-maker is called the agent (e.g., LF processing engine 530). The thing it interacts with, comprising everything outside the agent, is called the environment (e.g., viewers in a presentation space, etc.). These two interact continually, the agent selecting actions (e.g., creating holographic content) and the environment responding to those actions and presenting new situations to the agent. The environment also gives rise to rewards, special numerical values that the agent tries to maximize over time. In one context, the rewards act to maximize viewer positive reactions to holographic content. A complete specification of an environment defines a task which is one instance of the reinforcement learning problem.

[0162] To provide more context, an agent (e.g., LF processing engine 530) and environment interact at each of a sequence of discrete time steps, i.e.  $t=0, 1, 2, 3, \dots$ . At each time step  $t$  the agent receives some representation of the environment's state  $s_t$  (e.g., measurements from tracking system 580). The states  $s_t$  are within  $S$ , where  $S$  is the set of possible states. Based on the state  $s_t$  and the time step  $t$ , the agent selects an action  $a_t$  (e.g., making the performer do the splits). The action  $a_t$  is within  $A(s_t)$ , where  $A(s_t)$  is the set of possible actions. One time state later, in part as a consequence of its action, the agent receives a numerical reward  $r_{t+1}$ . The states  $r_{t+1}$  are within  $R$ , where  $R$  is the set of possible rewards. Once the agent receives the reward, the agent selects in a new state  $s_{t+1}$ .

[0163] At each time step, the agent implements a mapping from states to probabilities of selecting each possible action. This mapping is called the agent's policy and is denoted  $\pi_t$ , where  $\pi_t(s,a)$  is the probability that  $a_t=a$  if  $s_t=s$ . Reinforcement learning methods can dictate how the agent changes its policy as a result of the states and rewards resulting from agent actions. The agent's goal is to maximize the total amount of reward it receives over time.

[0164] This reinforcement learning framework is flexible and can be applied to many different problems in many different ways (e.g. generating holographic content). The framework proposes that whatever the details of the sensory, memory, and control apparatus, any problem (or objective) of learning goal-directed behavior can be reduced to three signals passing back and forth between an agent and its environment: one signal to represent the choices made by the agent (the actions), one signal to represent the basis on which the choices are made (the states), and one signal to define the agent's goal (the rewards).

[0165] Of course, the AI model can include any number of machine learning algorithms. Some other AI models that can be employed are linear and/or logistic regression, classification and regression trees, k-means clustering, vector quantization, etc. Whatever the case, generally, the LF processing engine 530 takes an input from the tracking module 526 and/or viewer profiling module 528 and a machine learning model creates holographic content in response. Similarly, the AI model may direct the rendering of holographic content.

[0166] In an example, the LF processing engine 530 creates a virtual athlete. The LF processing engine 530 creates the virtual athlete using information included in the viewer profiles stored in the data store 522. For example, information included in stored viewer profiles indicates that a large number of viewers enjoy high quality soccer from a woman athlete in her early thirties with artificially colored hair. As such, the LF processing engine 530 creates an athlete that is displayed by the LF display system 500 as a female soccer player. More explicitly, LF processing engine 530 accesses the viewer profiles of the viewers in a presentation space. LF processing engine 530 parameterizes (e.g., quantifies) information in each viewer profile. For example, LF processing engine 530 can quantify characteristics such as the age, location, sex, etc. of a viewer. Further, LF processing engine 530 can parameterize other information included in a viewer profile. For example, if a viewer profile indicates that a viewer has attended four sporting events of female athletes, the content creation module may quantify this tendency (e.g., generates a score indicating a viewer's interest in female athletes). LF processing engine 530 inputs

the parameterized user profiles into an AI model (e.g., a neural network) configured to generate characteristics of a virtual athlete based on input parameters and receives characteristics for the athlete in response. LF processing engine 530 then inputs the characteristics for the virtual athlete into an AI model (e.g., a procedural generation algorithm) configured to generate an athlete given a set of characteristics and generates a virtual female athlete. Further the LF processing engine 530 can create holographic content (e.g., abilities, sporting events, teams, uniforms, etc.) that would adhere to the persona of the virtual athlete. For example, the content generation module 530 may create a training regimen for the virtual athlete adherent to her playing style. More explicitly, LF processing engine 530 may access the characteristics of the virtual athlete and information about the viewers and input that information into an AI model (e.g., a recurrent neural network “RNN”). Again, the characteristics and information may be parameterized (e.g., using a classification and regression tree) and input into the RNN. Here, the RNN may be trained using training regimens with similar input parameters. As such, the RNN generates a training regimen for the virtual athlete for the viewers in the presentation space that shares similar characteristics to the training regimens of other female soccer athletes.

[0167] LF processing engine 530 can create holographic content based on a sporting event being shown in the presentation space. For example, a sporting event being shown in the presentation space may be associated with a set of metadata describing the sporting event’s characteristics. The metadata may include, for example, the setting, genre, coaches, players, statistics, sporting event type, themes, titles, run-times, etc. LF processing engine 530 may access any of the metadata describing the sporting event and generate holographic content to present in the presentation space in response. For example, a sporting event titled “The Excellent Bowl” is a play about to be played in a presentation space augmented with a LF display system 500. The LF processing engine 530 accesses the metadata of the sporting event to create holographic content for the walls of the presentation space before the sporting event begins. Here, the metadata includes a vibrant stadium setting appropriate for The Excellent Bowl. The LF processing engine 530 inputs the metadata into an AI model and receives holographic content to display on the walls of the presentation space in response. In this example, the LF processing engine 530 creates a beachside sunset to display on the walls of the presentation space before the sporting event begins to play.

[0168] In an example, the LF processing engine 530 creates holographic content based on the viewers present at a presentation space including a LF display system 500. For example, a group of viewers enters a presentation space to view a sporting event augmented by holographic content displayed by the LF display system 500. Viewer profiling module 528 generates a viewer profile for the viewers in the presentation space and an aggregate viewer profile representing all of the viewers in the presentation space. LF processing engine 530 accesses the aggregate viewer profile and creates holographic content to display to the viewers in the presentation space. For example, the viewers in a presentation space are a group of fans viewing a team working towards a championship, and, therefore, the aggregate viewer profile includes information indicating that they may

enjoy holographic content commensurate with super-fans for a sports team (e.g., through parameterization and input into an AI model). As such, the LF processing engine 530 generates holographic content such that the presentation space is a more rowdy atmosphere (e.g., foam fingers, chants, noise makers, etc.).

[0169] In some examples, the LF processing engine 530 may create holographic content based on previously existing content. Here, previously existing can be a previously existing team, athlete, etc. For example, a viewer’s favorite athlete is “Baby Ruthie” and they wish to view a baseball game starring their idol. As such, LF processing engine 530 creates augmented content for a sporting event of the Babe Ruthie smashing home run after home run. In this example, LF processing engine 530 may access existing box-scores, images, and statistics of Babe Ruthie (e.g., stored in data store 522) and use that content to create sporting event content for display by the LF display system 500. More explicitly, the content creation system can access the previous content from the data store 522. The LF processing engine 530 inputs favorite athletes, favorite teams, and favorite plays, and any other viewer data into an AI model (e.g., a procedural generation algorithm) configured to create, for example, a collage of multiple favorite athletes making plays, and in response the AI model outputs this holographic content to show during a sporting event. In some instances, because LF processing engine 530 is creating holographic content based on copyrighted content, the viewers and/or the LF processing engine 530 may pay a fee to the copyright holders.

[0170] In an example, the LF processing engine 530 creates holographic content based on the responses of viewers viewing a sporting event. For example, viewers in a presentation space are viewing a sporting event in a presentation space augmented by a LF display system 500. The tracking module 526 and the viewer profiling module 528 monitor the reaction of the viewers viewing the sporting event. For example, tracking module 526 may obtain images of viewers as they view the sporting event. Tracking module 526 identifies the viewer, and viewer profiling module 528 may use machine vision algorithms to determine a reaction of the viewer based on information included in the image. For example, an AI model can be used to identify if a viewer viewing the sporting event is smiling and, accordingly, viewer profiling module 528 can indicate in the viewer profile if the viewer has a positive or negative response to the sporting event based on the smile. Other reactions may also be determined. The tracking module may determine information about viewers including the position of the viewer, a movement of the viewer, a gesture of the viewer, an expression of the viewer, an age of the viewer, a sex of the viewer, an ethnicity of the viewer, or a clothing worn by the viewer. This information may be shared with the viewer profiling module 528 to generate a viewer profile.

[0171] The LF processing engine 530 may create holographic content based on previously existing or provided advertisement content. That is, for example, the LF processing engine 530 can request an advertisement from a network system via network interface 524, the network system provides the holographic content in response, and the LF processing engine 530 creates holographic content for display including the advertisement. Some examples of advertisement can include, products, text, videos, etc. Advertisements may be presented to specific viewing volumes based

on the viewers in that viewing volume. Similarly, holographic content may augment a sporting event with an advertisement (e.g., a product placement). Most generally, the LF processing engine 530 can create advertisement content based on any of the characteristics and/or reactions of the viewers in the presentation space as previously described.

[0172] The preceding examples of creating content are not limiting. Most broadly, LF processing engine 530 creates holographic content for display to viewers of a LF display system 500. The holographic content can be created based on any of the information included in the LF display system 500.

#### Holographic Content Distribution Networks

[0173] FIG. 5B illustrates an example LF sporting event network 550, in accordance with one or more embodiments. One or more LF display systems may be included in the LF sporting event network 550. The LF sporting event network 550 includes any number of LF display systems (e.g., 500A, 500B, and 500C), a LF generation system 554, and a networking system 556 that are coupled to each other via a network 552. The network may be a satellite network, an IP-based network, or a cable system network. In other embodiments, the LF sporting event network 550 comprises additional or fewer entities than those described herein. Similarly, the functions can be distributed among the different entities in a different manner than is described here.

[0174] In the illustrated embodiment, the LF sporting event network 550 includes LF display systems 500A, 500B, and 500C that may receive holographic content via the network 552 and display the holographic content to viewers. The LF display systems 500A, 500B, and 500C are collectively referred to as LF display systems 500.

[0175] The LF generation system 554 is a system that generates holographic content for display in a sporting event presentation space including a LF display system. In other words, the LF generation system is configured to generate any of the LF content described herein. The holographic content may be a sporting event or may be holographic content that augments a traditional sporting event.

[0176] In one example, the augmenting content is audio content that can be displayed concurrently to the holographic content. For example, the audio content may include an announcer, a music track, a jingle, a sound effect, or a translation.

[0177] In another example, the augmenting content is any of an overlay for a sporting area in the sporting arena, an informational overlay, or an augmentation of holographic content included in a holographic content livestream.

[0178] In another example, the augmenting content is an advertisement comprising any holographic, video, audio, or tactile content. In this case the advertisement may be based on any of a location of the LF display system presenting the advertisement, the sporting arena where the content was recorded and/or is being presented, a sponsor of the sporting event, or a configuration of the LF display system. In some cases, for viewers paying a higher fee for viewing the holographic content, viewer advertisements may be inserted into the holographic livestream.

[0179] A LF generation system 554 may include a light field recording assembly comprised of any number of sensors and/or processors to record energy data of an event, as well as a processing engine configured to convert this

recorded energy data into holographic content. For example, the sensors of the light field recording assembly can include cameras for recording images, microphones for recording audio, pressure sensors for recording interactions with objects, etc. In some examples, the light field recording assembly of the LF generation system 554 includes one or more recording modules (e.g., a LF display module configured to record energy data from an event, or a simple 2D camera to capture images of an event) positioned around an area (e.g., a sporting event presentation space) to record an event from multiple viewpoints. In this case, the processing engine of the LF generation system 554 is configured to convert the energy from multiple viewpoints into holographic content. In some examples, the light field recording assembly includes two or more two-dimensional recording systems, which are used by the processing engine to convert multiple viewpoints of an event into three-dimensional holographic content. The light field recording assembly can also include other sensors, such as, for example, depth sensors and/or plenoptic cameras.

[0180] More broadly, the LF generation system 554 generates holographic content for display in a presentation space by using any recorded sensory data or synthetic data of an event that may be projected by a LF display system when showing a sporting event. For example, the sensory data may include recorded audio, recorded images, recorded interactions with objects, etc. Many other types of sensory data may be used. To illustrate, the recorded visual content may include: 3D graphics scenes, 3D models, object placement, textures, color, shading, and lighting; 2D sporting event data which can be converted to a holographic form using an AI model and a large data set of similar sporting event conversions; multi-view camera data from a camera rig with many cameras with or without a depth channel; plenoptic camera data; CG content; or other types of recorded sensory data of an event as described herein.

[0181] In various examples, the sporting event that is recorded with one or more sensors over one or more energy domains may be any type of sporting event. The sporting event presentation space may include one or more of a field, a portion of an arena, etc.

[0182] In some configurations, the LF generation system 554 may use a proprietary encoder to perform the encoding operation that reduces the sensory data recorded for a sporting event into a vectorized data format as described above. That is, encoding data to vectorized data may include image processing, audio processing, or any other computations that may result in a reduced data set that is easier to transmit over the network 552. The encoder may support formats used by sporting event-making industry professionals. In other configurations, the LF generation system may transmit the sporting event content to the network system 556 and or LF display system without encoding the content.

[0183] Each LF display system (e.g., 500A, 500B, 500C) may receive the encoded data from the network 552 via a network interface 524. In this example, each LF display system includes a decoder to decode the encoded LF display data. More explicitly, a LF processing engine 530 generates rasterized data for the LF display assembly 510 by applying decoding algorithms provided by the decoder to the received encoded data. In some examples, the LF processing engine may additionally generate rasterized data for the LF display assembly using input from the tracking module 526, the viewer profiling module 528, and the sensory feedback

system **570** as described herein. Rasterized data generated for the LF display assembly **510** reproduces the holographic content recorded by the LF generation system **554**. Importantly, each LF display system **500A**, **500B**, and **500C** generates rasterized data suitable for the particular configuration of the LF display assembly in terms of geometry, resolution, etc. In some configurations, the encoding and decoding process is part of a proprietary encoding/decoding system pair (or ‘codec’) which may be offered to display customers or licensed by third parties. In some instances, the encoding/decoding system pair may be implemented as a proprietary API that may offer content creators a common programming interface.

**[0184]** In some configurations, various systems in the LF sporting event network **550** (e.g., LF display system **500**, the LF generation system **554**, etc.) may have different hardware configurations. Hardware configurations can include arrangement of physical systems, energy sources, energy sensors, haptic interfaces, sensory capabilities, resolutions, fields-of-view, LF display module configurations, or any other hardware description of a system in the LF sporting event network **550**. Each hardware configuration may generate, or utilize, sensory data in different data formats. As such, a decoder system may be configured to decode encoded data for the LF display system on which it will be presented. For example, a LF display system (e.g., LF display system **500A**) having a first hardware configuration receives encoded data from a LF generation system (e.g., LF generation system **554**) having a second hardware configuration. The decoding system accesses information describing the first hardware configuration of the LF display system **500A**. The decoding system decodes the encoded data using the accessed hardware configuration such that the decoded data can be processed by the LF processing engine **530** of the receiving LF display system **500A**. The LF processing engine **530** generates and presents rasterized content for the first hardware configuration despite being recorded in the second hardware configuration. In a similar manner, holographic content recorded by the LF generation system **554** can be presented by any LF display system (e.g., LF display system **500B**, LF display system **500C**) whatever the hardware configurations. Various other aspects that may be included in the hardware configuration may include: a resolution, a number of projected rays per degree, a field of view, a deflection angle on the display surface, and a dimensionality of the display surface, etc. Additionally, the hardware configuration may also include, a number of display panels of the LF display assembly, a relative orientation of the display panels, a height of the display panels, a width of the display panels, and a layout of the display panels.

**[0185]** Similarly, various systems in the LF sporting event network **550** may have different geometric orientations. Geometric orientations reflect the physical size, layout, and arrangement of the various modules and system included in an LF display system. As such, a decoder system may be configured to decode encoded data for the LF display system in the geometric configuration on which it will be presented. For example, a LF display system (e.g., LF display system **500A**) having a first geometric configuration receives encoded data from a LF generation system (e.g., LF generation system **554**) having a second geometric configuration. The decoding system accesses information describing the first geometric configuration of the LF display system

**500A**. The decoding system decodes the encoded data using the accessed geometric configuration such that the decoded data can be processed by the LF processing engine **530** of the receiving LF display system **500A**. The LF processing engine **530** generates and presents content for the first geometric configuration despite being recorded in the second geometric configuration. In a similar manner, holographic content recorded by the LF generation system **554** can be presented by any LF display system (e.g., LF display system **500B**, LF display system **500C**) whatever the geometric configurations. Various other aspects that may be included in the geometric configuration may include: a number of display panels (or surfaces) of the LF display assembly, a relative orientation of the display panels.

**[0186]** Similarly, various presentation spaces in the LF sporting event network **550** may have different configurations. Presentation space configurations reflect any of the number and/or position of holographic object volumes, the number and/or position of viewing volumes, and a number and/or position of viewing locations relative to a LF display system. As such, a decoder system may be configured to decode encoded data for the LF display system in the presentation space in which it will be presented. For example, a LF display system (e.g., LF display system **500A**) having in a first presentation space receives encoded data from a LF generation system (e.g., LF generation system **554**) recorded in a different presentation space (or some other space). The decoding system accesses information describing the presentation space. The decoding system decodes the encoded data using the accessed presentation space configuration such that the decoded data can be processed by the LF processing engine **530** installed in the presentation space. The LF processing engine **530** generates and presents content for the presentation space despite being recorded in a different location.

**[0187]** The network system **556** is any system configured to manage the transmission of holographic content between systems in a LF sporting event network **550**. For example, the network system **556** may receive a request for holographic content from a LF display system **500A** and facilitate transmission of the holographic content to the LF display system **500A** from the LF generation system **554**. The network system **556** may also store holographic content, viewer profiles, holographic content, etc. for transmission to, and/or storage by, other LF display systems **500** in the LF sporting event network **550**. The network system **556** may also include a LF processing engine **530** that can create holographic content as previously described.

**[0188]** The network system **556** may include a digital rights management (DRM) module to manage the digital rights of the holographic content. For example, the LF generation system **554** may transmit the holographic content to the network system **556** and the DRM module may encrypt the holographic content using a digital encryption format. In other examples, the LF generation system **554** encodes recorded light field data into a holographic content format that can be managed by the DRM module. The network system **556** may provide a key to the digital encryption key to a LF display system such that each LF display system **500** can decrypt and, subsequently, display the holographic content to viewers. Most generally, the network system **556** and/or the LF generation system **554** encodes the holographic content and a LF display system may decode the holographic content.

[0189] The network system **556** may act as a repository for previously recorded and/or created holographic content. Each piece of holographic content may be associated with a transaction fee that, when received, causes the network system **556** to transmit the holographic content to the LF display system **500** that provides the transaction fee. For example, A LF display system **500A** may request access to the holographic content via the network **552**. The request includes a transaction fee for the holographic content. In response, network system **556** transmits the holographic content to the LF display system for display to viewers. In other examples, the network system **556** can also function as a subscription service for holographic content stored in the network system. In another example, LF generation system **554** is recording light field data of a sporting event in real-time and generating holographic content representing that sporting event. A LF display system **500** transmits a request for the holographic content to the LF generation system **554**. The request includes a transaction fee for the holographic content. In response, the LF generation system **554** transmits the holographic content for concurrent display on the LF display system **500**. The network system **556** may act as a mediator in exchanging transaction fees and/or managing holographic content data flow across the network **552**. Additionally, in some cases, the network system is capable of modifying holographic content such that it is presentable by the LF display system receiving the holographic content.

[0190] In some examples, the network system **556** may be a local distribution hub. That is a network system **556** responsible for distributing a holographic content to LF display system in a local market. For example, the local distribution hub may be a Dallas station responsible for distributing holographic content to LF display systems **500** in the Dallas area. In this case, the network system **556** may augment the holographic content with additional holographic content, audio content, video content, and/or tactile content.

[0191] The network **552** represents the communication pathways between systems in a LF sporting event network **550**. In one embodiment, the network is the Internet, but can also be any network, including but not limited to a local area network (LAN), a metropolitan area network (MAN), a wide area network (WAN), a mobile, wired or wireless network, a cloud computing network, a private network, or a virtual private network, and any combination thereof. In addition, all or some of links can be encrypted using conventional encryption technologies such as the secure sockets layer (SSL), Secure HTTP and/or virtual private networks (VPNs). In another embodiment, the entities can use custom and/or dedicated data communications technologies instead of, or in addition to, the ones described above.

### III. Example Arenas

[0192] FIGS. 6A-9B illustrate several example presentation spaces that may display holographic content using a LF display system (e.g., LF display system **500**). The holographic content can be a recorded sporting event, a sporting event occurring concurrently in another arena, and/or holographic content that augments a presented sporting event. In this disclosure, this content is referred to as holographic sporting event content, or simply holographic sporting content. Within a presentation space, any number of viewers are located at viewing locations within any number of viewing

volumes. The LF display system is configured to display the holographic sporting content in a holographic object volume (“holographic sporting event volume”) such that viewers in the viewing volume(s) perceive this holographic sporting content. In this disclosure we often use the terms “holographic sporting event volume,” and “holographic object volume,” interchangeably, to refer to the region of space where the holographic sporting content is projected (e.g. the holographic object volume **255** shown in FIG. 2B). Generally, a LF display system in a venue includes an array of light field modules **210** around the holographic sporting event volume that generate a seamless multisided LF display. As such, the holographic sporting event volume may be the aggregate holographic object volume of the array of LF display modules **210**.

[0193] FIG. 6 illustrates a side view of a presentation space which is a traditional arena **600** which has been augmented with a LF display system, in accordance with one or more embodiments. In the arena **600**, a back wall and the floors are lined with an array **640** of LF display modules such that the area above the floor is the holographic sporting event volume **610** of the LF display system. In some examples, the arena **600** may include elements in the holographic sporting event volume that allow for easier presentation of holographic sporting content. For example, a holographic sporting event volume may include a tennis court such that the LF display system need not render the court when presenting a tennis match. The holographic sporting event volume **610** (e.g., holographic object volume **255**) is illustrated as a bounded square for clarity, but the illustrated holographic sporting event volume **610** is only a portion of the actual holographic sporting event volume. For example, the holographic sporting event volume may extend into the back wall or the floor **602**. In FIG. 6, the LF display system is an embodiment of the LF display system **500**. Further, the LF display modules in the array **640** are an embodiment of the LF display assembly **510**.

[0194] Here, the arena **600** is three tiered, but could include any number of tiers. Each tier includes a number of viewing locations (e.g., viewing location **622A**, **622B**) for viewers to view holographic sporting event content **630** in the holographic sporting event volume **610**. The viewing locations **622** in each tier are included in a viewing volume (e.g., **620A**, **620B**, and **620C**) of the LF display system. The LF display system may display the same, or different, sporting event content **630** to viewers in each viewing sub-volume **620** (similar to viewing sub-volumes **290** in FIG. 2B). For example, as described below, viewers in the viewing locations **622A** located in the viewing volume **620A** of the bottom tier may see different sporting event content **630** than viewers in the viewing location **622B** in the viewing volume **620B** of the middle tier.

[0195] In other embodiments, the arena **600** may configured in a different manner. For example, the walls and floor may take some other shape appropriate for the sporting content to be presented. Any of the surfaces in the arena **600** may be included in the array **640** of LF display modules. Additionally, the arena **600** may have additional tiers and viewing volumes and those tiers and viewing volumes may be arranged in any number of configurations.

[0196] As a contextual example, the illustrated arena **600** is a presentation space in San Francisco billed to concurrently show the finals to a tennis match “Bumbledon.” Notably, however, the tennis match is occurring in London,



England. The arena in London includes a LF generation system (e.g., LF generation system **554**) for recording and transmitting the tennis match as holographic sporting event content **630** to other venues via a network (e.g., via network **552**). The arena **600** in San Francisco includes a LF display system configured to display the received holographic sporting event content **630** to viewers at viewing locations **622** in the viewing sub-volumes **620**. A transaction fee is paid (e.g., to network system **556** or LF generation system **554**) to receive the sporting event content. In various examples, the owner of the arena **600**, attendees to the arena **600**, a sporting event manager, or any other agent may pay the fee. The holographic sporting event content **630** allows viewers in San Francisco to perceive the tennis match as if they were viewing the match live in the holographic sporting event volume **610** in front of them. This allows viewers in San Francisco to see the live sporting event in a nearly identical way to the viewers in London, without travelling to London.

[0197] In some embodiments, the venue **600** charges an entrance fee to see the tennis match live-stream displayed by the LF display system **500**. Each viewing location **622** can have a different entrance fee and, generally, the entrance fee for the bottom viewing volume **620A** is more expensive than the top viewing volume **620C**. The LF display system can display different holographic sporting event content **630** to each viewing volume **620** based on the entrance fee for the viewing volumes **620**. For example, fully rendering the match in San Francisco may be costlier (e.g., processing power, energy, etc.) than partially rendering the match. As such, a LF processing engine (e.g., LF processing engine **530**) may only display a portion of the sporting content to the viewing volume **620C** on the top tier of the theater while playing all of the sporting content **630** to the viewing volume **620A** on the bottom tier of the theater. For example, when displaying only a portion of the holographic sporting event content **630**, the LF processing engine may only display sporting event content **630** in a portion of the holographic sporting event volume **610** rather than the whole holographic sporting event volume **610**, the LF processing engine may remove aspects of the holographic sporting event content **630** (e.g., cheerleaders, portions of the fans or spectators, etc.), the LF processing engine **530** may render the holographic sporting event content **630** at a lower resolution for the top viewing volume **620C** than the bottom viewing volume **620A**, and the like.

[0198] Alternatively or additionally, LF processing engine **530** can create holographic content to augment the holographic sporting event content **630** based on the entrance fee for the viewing volumes **620**. For example, the LF processing engine may create (or access from a network system **556**) an advertisement to display concurrently with the sporting content **630**. The advertisement may be based on the information obtained by a viewer profiling system (e.g., viewer profiling system **590**) or a tracking system (e.g., tracking system **580**). For example, the LF processing engine may access viewer profiles including viewer characteristics and responses to holographic content. The LF processing engine accesses an advertisement from the data store (e.g., data store **522**) that is associated with the characteristics and responses of the viewers and displays that advertisement. The venue may receive payment from the advertiser for displaying the advertisement when displaying the holographic sporting content **630**. In another example, rather than an overtly displayed advertisement, LF

processing engine can augment the holographic sporting event content **630** with sponsored holographic content (e.g., product placements). For example, LF processing engine may replace courtside advertisements for viewers in London with advertisements targeting viewers in San Francisco.

[0199] FIG. 7 illustrates a cross-section of another arena **700** including a LF display system for displaying sporting content to viewers at viewing locations in viewing volumes, in accordance with one or more embodiments. The arena **700** is designed and built to display sporting content **730** rather than augmenting an already-existing arena. As illustrated, FIG. 7 is a cross-section of arena **700**. In FIG. 7, the LF display system **740** is an embodiment of the LF display system **500**.

[0200] In the illustrated example, the arena **700** resembles a judo presentation space where the viewing locations **722** circle a fighting ring **702**. The floor of the fighting ring **702** is covered with an array of LF display modules such that the area above the stage forms a holographic sporting event volume (e.g., sporting event volume **710**). The LF display **740** presents sporting content **730** in the holographic sporting event volume **710** such that viewers in the arena **700** may perceive the holographic sporting event content **730**. In the arena **700**, the viewing locations **722** are positioned with a rake such that the sightline for each viewing location allows unobstructed viewing of sporting content **730** from a viewing volume (e.g., viewing volume **720A**). Here, the arena includes one viewing volume which surrounds the fighting ring **702**, including viewing volumes **720A** and **720B**, such that all the viewers are presented with the same sporting event. In other configurations there may be more than one viewing volume.

[0201] More generally, the LF display system may have a display surface that is substantially horizontal, or approximately horizontal. In several examples, the LF display system may include a display surface that is (i) at least some part of the floor of the arena, (ii) at least some part of a fighting ring (e.g., fighting ring **702**), gymnastics floor, tennis court, field, or other sporting event surface in an arena and/or (iii) at least some portion of a raised viewing platform in an arena. Other types of horizontal surfaces are also possible. For these configurations, the viewers may be elevated relative to the display surface and look downward to view the holographic sporting content that is projected from the display surface, and the viewers may partially or fully surround the display surface. There are many other configurations for a light field display surface, including a vertically-mounted display surface with viewing locations that are arrayed approximately in front of the LF display surface and is described elsewhere in this disclosure (**450A** shown in FIG. 4C, **450B** shown in FIG. 4D, and **450C** shown in FIG. 4E), as well as a curved LF display surface.

[0202] The holographic sporting event volume **710** is illustrated as a bounded square for clarity, but the holographic sporting event volume **710** may only be a portion of the actual sporting event volume where holographic sporting event objects may be projected. For example, the holographic sporting event volume **710** may extend further towards the top of the arena **700**. Additionally, a portion of the sporting event volume **710** and viewing volume **720** (e.g. **720A** and **720B**) overlap spatially. While illustrated as a partial overlap, the holographic sporting event volume and viewing volume may wholly overlap spatially. The spatial

overlap are areas in which viewers may interact with holographic sporting content **730** as previously described.

[0203] A presentation space can also be a much smaller location. For example, FIG. **8** illustrates a presentation space that also acts as a home theater **800** in the living room **802** of a viewer, in accordance with one or more embodiments. Here, the home theater includes a LF display system **840** comprised of an array of LF display modules on one wall. In FIG. **8**, the LF display system **840** is an embodiment of the LF display system **500**.

[0204] The LF display system **840** may be configured such that the sporting event volume (e.g., holographic object volume **255**) and the viewing volume wholly overlap within the living room **802**. That is, at any viewing location (e.g., viewing location **822**) within the living room **802** a viewer may view and interact with sporting content **830**. While the viewing location **822** is illustrated as a chair, a viewer may move through the living room and view the sporting content **830**. That is, the viewing location **822** may be the location of the viewer in the living room **802**.

[0205] In some embodiments, the LF display system **840** creates (or modifies) sporting content **830** based on viewer interactions with the holographic sporting content **830**. For example, a viewer can fist-bump a performer in the holographic sporting content **830**. In this situation, a viewer may interact with a cheerleader and move his hand as if to high-five the cheerleader in the holographic sporting content **830**. The tracking system (e.g., tracking system **580**) monitors the viewer and identifies (e.g., via machine hearing, machine vision, neural networks, etc.) that the viewer wishes to fist-bump the performer in the holographic sporting content **830**. The content generation system (e.g., content generation **530**) creates (e.g., using machine learning, neural networks, or some combination thereof) holographic sporting content representing the cheerleader reciprocating the high-five based using the monitored viewer information. The tracking system **580** monitors the position of the viewer's hand and when the viewers hand and cheerleaders hand spatially overlap, the sensory feedback assembly (e.g., sensor feedback assembly **570**) creates a sensation for the viewer that he has high-fived the performer in the holographic sporting content **830**. This may be accomplished with a focused ultrasonic projection system which generates a volumetric tactile surface which generates the sensation of a high-five being returned to the viewer. In an embodiment, the ultrasonic projection system is integrated into the LF display system as a dual energy display surface, as previously described.

[0206] In some cases, the viewer may interact with network system (e.g., network system **556**) to procure sporting content **830** for their living room **802**. Continuing the example described in regard to FIG. **6**, and referring to the LF sporting event distribution network shown in FIG. **5B**, a viewer may send a transaction fee to network system **556** and the LF generation system **554** sends the presentation space **800** the holographic sporting content **830** of the tennis match being played in London.

[0207] FIG. **9** illustrates a home theater **900** in the living room **902** of a viewer, in accordance with one or more embodiments. Here, the home theater includes a LF display system **940** built into a table **904**, with an array of LF display modules ("LF array") on the top surface of the table **904**. While the illustrated home theater is built into a table, it could be built into any other element of a living room having

a surface. The LF array **920** is configured to present holographic sporting content **930** to viewers in viewing locations that can view the top surface of the table **904**. In the illustrated example, an example viewing location **922** is a chair positioned such that a viewer sitting in the chair can perceive holographic content presented by the LF array **920**. As previously described, viewers in other viewing locations may also perceive the holographic sporting content **930** presented by the LF array **920**. In FIG. **10**, the LF array **920** is an embodiment of the LF display assembly **510**. Further, the LF display system **940** is an embodiment of the LF display system **500**.

[0208] The LF array **920** presents holographic sporting content **930** of a sporting event such that it appears on the top surface of the table **904**. A viewer in the viewing location **922** may be able to perceive and interact with the presented holographic content **930**. In this example, the LF display system inputs holographic content from a network system **556**, converts the holographic content for display on the top of the table **904**, and presents the holographic content **930** to viewers in one or more viewing volumes of the LF display system **940**.

[0209] In some embodiments, a viewer can interact with the LF display system to change the presented holographic sporting content **930**. For example, the LF display system can be configured to receive auditory cues, visual cues, etc. and change the holographic content **930** in response. As an illustration, a viewer in the living room **902** can state "Pause Match," the LF display system records the audio, recognizes the audio, and pauses playback of the holographic sporting content **930** in response. Similarly, a viewer in the living room **902** can interact with the holographic content **930** to rotate the view displayed by the table. As an illustration, a viewer can touch a player in the presented holographic content **930** with one hand and make a rotation gesture with the other hand. In this case, the LF display system captures an image of the viewer making the gesture, recognizes the gesture, and rotates the holographic content in response.

#### IV. Displaying Sporting Event Content to Viewers in an Arena

[0210] FIG. **10** is a flow diagram of a method **1000** for displaying holographic content to viewers in a sports event presentation space (e.g., arena **600**) in the context of a LF sports network (e.g., LF sports network **550**). The method **1000** may include additional or fewer steps and the steps may occur in a different order. Further, various steps, or combinations of steps, can be repeated any number of times during execution of the method.

[0211] To begin, an arena including a LF display system (e.g., LF display system **500**) transmits **1010** a request for a live-stream (or previously recorded) of holographic sporting event content (e.g., holographic sporting event content **630**) to a network system (e.g., network system **556**) system via a network (e.g., network **552**). The request may include a transaction fee sufficient for payment to display the holographic sporting event content.

[0212] A LF generation system (e.g., LF generation system **554**) records the LF data of a live sporting event and transmits the corresponding holographic sporting event content to the network system. The network system transmits the holographic sporting event content to the LF display system such that it can be displayed at approximately the same time as it is being recorded by the LF generation

system. In other embodiments, the network system (e.g. network system **556**) may transmit pre-recorded holographic sporting event content.

[**0213**] The LF display system receives **1020** the holographic sporting event content from the network system via the network.

[**0214**] The LF display system determines **1030** a configuration of the LF display system and/or the presentation space in the arena. For example, the LF display system may access a configuration file including a number of parameters describing the HW configuration of the LF display, including the resolution, projected rays per degree, fields-of-view, deflection angles on the display surface, or a dimensionality of the LF display surface. The configuration file may also contain information about the geometrical orientation of the LF display assembly, including the number of LF display panels, relative orientation, width, height, and the layout of the LF display panels. Further, the configuration file may contain configuration parameters of the performance venue, including holographic object volumes, viewing volumes, and a location of the audience relative to the display panels.

[**0215**] To illustrate through an example, the LF display system determines **1030** viewing volumes (e.g., viewing volume **620A**, **620B**, and **620C**) for displaying the holographic sporting event content. For example, the LF display system **500** may access information in the LF display system describing the layout, geometric configuration, and/or hardware configuration of the presentation space (e.g., arena **600**). To illustrate, the layout may include the locations, separations, and sizes of viewing locations (e.g., viewing locations **622**) in the presentation space. As such, LF display system may determine that viewing locations in the first tier of the presentation space are in a first viewing volume, viewing locations in the second tier of the venue are in a second viewing volume, and viewing locations in the third tier of the venue are in a third viewing volume. In various other embodiments, a LF display system may determine any number and configuration of viewing volumes at any location within a venue.

[**0216**] The LF display system generates **1040** the holographic content (and other sensory content) for presenting on the LF display system, based on the hardware configuration of the LF display system within the performance venue, and the particular layout and configuration of the presentation space. Determining the holographic sporting event content for display can include appropriately rendering the holographic sporting event content for the presentation space or viewing volumes. For example, the LF display system may: (i) augment the holographic sporting event content for display to the viewing volume in the third tier with an advertisement and remove aspects of the live performance from the holographic sporting event content, (ii) decrease the fidelity of the holographic sporting event content for display to the viewing volume in the second tier of the presentation space, and (iii) fully render holographic sporting event content for display to the viewing volume in the third tier of the presentation space.

[**0217**] The LF display system presents **1050** the holographic sporting event content in the holographic sporting event volume of the presentation space such that viewers at viewing locations in each viewing volume perceive the appropriate holographic sporting event content. That is, viewers in the top viewing volume perceive the holographic sporting event content with an advertisement, viewers in the

middle viewing volume perceive the holographic sporting event content at lower resolution, and viewers in the bottom viewing volume perceive the fully rendered holographic sporting event content.

[**0218**] The LF display system may determine information about viewers in the viewing volumes while the viewers view the holographic sporting event content at any time. For example, the tracking system may monitor the facial responses of viewers in the viewing volumes and the viewer profiling system may access information regarding characteristics of the viewers in the viewing volumes.

[**0219**] The LF display system may create (or modify) holographic sporting event content for concurrent display based on the determined information. For example, the LF processing engine may create a light show for concurrent display by the LF display system based on determined information that the viewers enjoy fireworks or electronic music festivals.

#### V. Additional Configuration Information

[**0220**] The foregoing description of the embodiments of the disclosure has been presented for the purpose of illustration; it is not intended to be exhaustive or to limit the disclosure to the precise forms disclosed. Persons skilled in the relevant art can appreciate that many modifications and variations are possible in light of the above disclosure.

[**0221**] Some portions of this description describe the embodiments of the disclosure in terms of algorithms and symbolic representations of operations on information. These algorithmic descriptions and representations are commonly used by those skilled in the data processing arts to convey the substance of their work effectively to others skilled in the art. These operations, while described functionally, computationally, or logically, are understood to be implemented by computer programs or equivalent electrical circuits, microcode, or the like. Furthermore, it has also proven convenient at times, to refer to these arrangements of operations as modules, without loss of generality. The described operations and their associated modules may be embodied in software, firmware, hardware, or any combinations thereof.

[**0222**] Any of the steps, operations, or processes described herein may be performed or implemented with one or more hardware or software modules, alone or in combination with other devices. In one embodiment, a software module is implemented with a computer program product comprising a computer-readable medium containing computer program code, which can be executed by a computer processor for performing any or all of the steps, operations, or processes described.

[**0223**] Embodiments of the disclosure may also relate to an apparatus for performing the operations herein. This apparatus may be specially constructed for the required purposes, and/or it may comprise a general-purpose computing device selectively activated or reconfigured by a computer program stored in the computer. Such a computer program may be stored in a non-transitory, tangible computer readable storage medium, or any type of media suitable for storing electronic instructions, which may be coupled to a computer system bus. Furthermore, any computing systems referred to in the specification may include a single processor or may be architectures employing multiple processor designs for increased computing capability.

**[0224]** Embodiments of the disclosure may also relate to a product that is produced by a computing process described herein. Such a product may comprise information resulting from a computing process, where the information is stored on a non-transitory, tangible computer readable storage medium and may include any embodiment of a computer program product or other data combination described herein.

**[0225]** Finally, the language used in the specification has been principally selected for readability and instructional purposes, and it may not have been selected to delineate or circumscribe the inventive subject matter. It is therefore intended that the scope of the disclosure be limited not by this detailed description, but rather by any claims that issue on an application based hereon. Accordingly, the disclosure of the embodiments is intended to be illustrative, but not limiting, of the scope of the disclosure, which is set forth in the following claims.

1. A light field (LF) sports content network system comprising:

- a light field recording assembly configured to record one or more types of energy representing a sporting event at a sporting arena;
- a processing engine configured to convert the recorded energy into a holographic content livestream representing the sporting event; and
- a network interface configured to transmit the holographic content livestream to one or more LF display systems via a network.

2. The LF sports content network system of claim 1, wherein the network is any of:

- a cable system network;
- an IP-based network; and
- a satellite network.

3. The LF sports content network system of claim 1, wherein the processing engine is configured to add additional content to the holographic content livestream.

4. The LF sports content network system of claim 3, wherein the additional content is audio content, the audio content presented simultaneously to the holographic content livestream by a LF display system.

5. The LF sports content network system of claim 4, wherein the audio content is any of:

- an announcer;
- a music track;
- a jingle;
- a sound effect; or
- a translation.

6. The LF sports content network system of claim 3, wherein the additional content is presented simultaneously to the holographic content livestream by a LF display system.

7. The LF sports content network system of claim 6, wherein the additional holographic content is any of:

- an overlay for a sporting area in the sporting area;
- an informational overlay; and
- an augmentation of holographic content included in the holographic content livestream.

8. The LF sports content network system of claim 3, wherein the additional content is an advertisement, the advertisement presented simultaneously to the holographic content livestream.

9. The LF sports content network system of claim 8, wherein the advertisement includes any of:

- holographic content;
- video content;
- tactile content.

10. The LF sports content network system of claim 8, wherein the advertisement presented by the LF display system is based on any of:

- a location of the LF display system;
- the sporting arena;
- a sponsor of the sporting event;
- a configuration of the LF display system;
- a transaction fee provided by the LF display system to the LF sports content network system for the holographic content live stream;
- a type of the sporting event represented the holographic content livestream;
- a time of day that the holographic content livestream is presented; and
- a player, a team, a participant, a contestant, a contender, or a coach participating in the sporting event.

11. The LF sports content network system of claim 6, wherein the additional content is tactile content.

12. The LF sports content network system of claim 1, wherein the processing engine comprises an encoder to encode the holographic content livestream to an encoded holographic content livestream, and the encoded holographic content livestream is transmitted via the network interface.

13. The LF sports content network system of claim 12, wherein the encoded holographic content livestream is configured to be decoded by a decoder of a LF display system.

14. The LF sports content network system of claim 12, wherein the encoder encodes the encoded holographic livestream in approximately real time.

15. The LF sports content network system of claim 12, wherein:

- the encoder employs a proprietary codec to encode the holographic content livestream, and
- a decoder employing the proprietary codec decodes the encoded holographic content livestream.

16. The LF sports content network system of claim 12, wherein the holographic content livestream is a first data format, and the encoded holographic content livestream is a second data format.

17. The LF sports content network system of claim 16, wherein:

- the first data format is a rasterized data format, and
- the second data format is a vectorized data format.

18. The LF sports content network system of claim 1, wherein:

- the network interface transmits the holographic content livestream to a local holographic content distribution hub, and
- the local holographic content distribution hub transmits the holographic content livestream to at least one LF display system of the one or more LF display systems.

19. The LF sports content network system of claim 18, wherein

- the local holographic content distribution hub adds additional content to holographic content livestream.

20. The LF sports content network system of claim 19, wherein the additional content includes any of:

- local content;
- local advertisements;
- holographic content;
- audio content;

video content; and  
tactile content.  
21.-97. (canceled)

\* \* \* \* \*