



(19) **United States**

(12) **Patent Application Publication**
Dabush et al.

(10) **Pub. No.: US 2024/0337459 A1**

(43) **Pub. Date: Oct. 10, 2024**

(54) **ENHANCED WIRELESS TRACKING DEVICE**

Publication Classification

(71) Applicant: **V-Armed Inc.**, New York, NY (US)

(51) **Int. Cl.**
F41A 33/00 (2006.01)

(72) Inventors: **Elad Dabush**, New York, NY (US);
Rotem Shiffman, Brooklyn, NY (US)

F41A 33/02 (2006.01)

(73) Assignee: **V-Armed Inc.**, New York, NY (US)

F41G 3/26 (2006.01)

(21) Appl. No.: **18/539,570**

G06F 3/01 (2006.01)

(22) Filed: **Dec. 14, 2023**

G09B 9/00 (2006.01)


(52) **U.S. Cl.**
CPC *F41A 33/00* (2013.01); *F41A 33/02*
(2013.01); *F41G 3/2622* (2013.01); *F41G*
3/2694 (2013.01); *G06F 3/012* (2013.01);
G06F 3/013 (2013.01); *G09B 9/003* (2013.01)

Related U.S. Application Data

(63) Continuation-in-part of application No. 18/219,100, filed on Jul. 7, 2023, which is a continuation of application No. 17/751,694, filed on May 24, 2022, now abandoned, which is a continuation of application No. 17/015,425, filed on Sep. 9, 2020, now Pat. No. 11,371,794, which is a continuation of application No. 15/865,731, filed on Jan. 9, 2018, now Pat. No. 10,922,992.

(57) **ABSTRACT**

Disclosed embodiments provide systems and methods for training participants in simulation of firearm discharge and training of armed forces, law enforcement personnel, or the like. A motion tracking system tracks motion of one or more training participants. A wireless independent tracking system (WITS) device is coupled firmly to a simulated weapon in a virtual reality (VR) training environment.






FIG. 1




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D




FIG. 5




FIG. 6




FIG. 7




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 8D




FIG.8E




FIG. 8F




FIG. 8G




FIG.8H




FIG. 81




FIG. 9A




FIG. 9B




FIG. 10

1100
↓




FIG. 11




FIG. 12




FIG. 13




FIG. 14A




FIG. 14B




FIG. 14C




FIG. 14D




FIG. 14E



FIG. 15



FIG. 16




FIG. 17



FIG. 18




FIG. 19

ENHANCED WIRELESS TRACKING DEVICE

CROSS-REFERENCE TO RELATED APPLICATIONS SECTION

[0001] This is a continuation in part of application Ser. No. 18/219,100 filed Jul. 7, 2023, which is a continuation of application Ser. No. 17/751,694 filed on May 24, 2022, which is a continuation of application Ser. No. 17/015,425 filed Sep. 9, 2020 and issued on Jun. 8, 2022 as U.S. Pat. No. 11,371,794, which is a continuation of application Ser. No. 15/865,731 filed Jan. 9, 2018 and issued on Jan. 27, 2021 as U.S. Pat. No. 10,922,992, all of which are hereby incorporated by reference herein in their entirety.

FIELD OF THE EMBODIMENTS

[0002] Disclosed embodiments relate to firearm simulation and training, and more particularly to firearm simulation and training utilizing motion tracking.

BACKGROUND

[0003] Military training programs of the US Armed Forces are vital for mission success. Military training, aimed at the accomplishment of tasks associated with a military mission, is an important part of troop readiness. Without proper training, soldiers may be unprepared for an actual battle. Similarly, law enforcement personnel benefit from training for various situations they may encounter during their patrols. In law enforcement, personnel may not have much advance notice of when they will be in a dangerous situation. Thus, periodic training exercises are important for law enforcement to maintain a state of readiness. It is therefore desirable to have improvements in the training of military and law enforcement personnel.

SUMMARY

[0004] In one embodiment, there is provided a computer-implemented method for conducting a firearm usage simulation, comprising: determining a position of a user; determining an initial physiological orientation of the user; detecting a simulated firearm discharge; and determining a reaction of the user in response to the simulated firearm discharge.

[0005] In another embodiment, determining a physiological orientation of the user comprises determining a position of one or more limbs of the user.

[0006] In another embodiment, determining a physiological orientation of the user comprises determining a facial direction of the user.

[0007] In another embodiment, determining a physiological orientation of the user comprises determining an eye gaze direction of the user.

[0008] Another embodiment includes comparing a second physiological orientation of the user to an expected physiological orientation of the user; and generating a user score based on the comparison.

[0009] In another embodiment, comparing the second physiological orientation of the user to an expected physiological orientation of the user includes comparing a position of one or more limbs.

[0010] In another embodiment, comparing the second physiological orientation of the user to an expected physiological orientation of the user includes comparing a facial direction of the user to an expected facial direction.

[0011] Another embodiment includes measuring a duration from a time of the simulated firearm discharge to a time of detecting the second physiological orientation.

[0012] In another embodiment, generating the user score is further based on the duration.

[0013] In another embodiment, generating the user score is further based on a weapon draw time.

[0014] In another embodiment, generating the user score is further based on a weapon discharge time.

[0015] Embodiments include a weapon usage evaluation system, comprising: a motion tracking system, configured and disposed to track one or more users; a scenario management system, configured and disposed to receive motion information from the motion tracking system; and a weapon simulator, wherein the weapon simulator is configured and disposed to provide discharge information and position information to the scenario management system.

[0016] In another embodiment, the system includes an inertial tracking device affixed to the weapon simulator.

[0017] In another embodiment, the system includes a shock mount configured and disposed between the weapon simulator and the inertial tracking device.

[0018] In another embodiment, the shock mount comprises: a top plate; a bottom plate; and a plurality of resilient members configured and disposed between the top plate and the bottom plate.

[0019] In another embodiment, the weapon simulator comprises: a trigger; a motor configured and disposed to generate a vibration in response to activation of the trigger; a communication module configured and disposed to wirelessly transmit a trigger indication to the scenario management system in response to activation of the trigger.

[0020] In another embodiment, the system includes an inverse kinematic solver.

[0021] In another embodiment, the system includes: a processor; a memory coupled to the processor, wherein the memory contains instructions, that when executed by the processor, cause the processor to perform steps of: determining a position of a user; determining an initial physiological orientation of the user; detecting a simulated firearm discharge; and determining a reaction of the user in response to the simulated firearm discharge.

[0022] In another embodiment, the memory further contains instructions, that when executed by the processor, cause the processor to perform the step of determining a position of one or more limbs of the user.

[0023] In another embodiment, the memory further contains instructions, that when executed by the processor, cause the processor to perform the step of determining a facial direction of the user.

BRIEF DESCRIPTION OF THE DRAWINGS

[0024] FIG. 1 is a diagram of a system in accordance with embodiments of the present invention.

[0025] FIG. 2 is a diagram of a client device in accordance with embodiments of the present invention.

[0026] FIG. 3 is a block diagram of components in accordance with embodiments of the present invention.

[0027] FIG. 4A-4D show a shock mount in accordance with embodiments of the present invention.

[0028] FIG. 5 illustrates an example of a shock mount in use.

[0029] FIG. 6 illustrates a weapon simulator in accordance with embodiments of the present invention.

[0030] FIG. 7 illustrates a weapon simulator in accordance with additional embodiments of the present invention.

[0031] FIG. 8A-8I illustrate examples of inverse kinematic solver computations.

[0032] FIG. 9A is a front view of a wearable sensor in accordance with embodiments of the present invention.

[0033] FIG. 9B is a rear view of the wearable sensor of FIG. 9A.

[0034] FIG. 10 is a flowchart indicating process steps for embodiments of the present invention.

[0035] FIG. 11 is a flowchart indicating additional process steps for embodiments of the present invention.

[0036] FIG. 12 is an exemplary user interface in accordance with embodiments of the present invention.

[0037] FIG. 13 shows an additional embodiment of a weapon simulator.

[0038] FIG. 14A is a side view of an example embodiment of a Wireless Independent Tracking System (WITS) device coupled to a simulated gun.

[0039] FIGS. 14B, 14C, 14D, and 14E are different views of the WITS device shown in FIG. 14A.

[0040] FIG. 15 is a perspective view of a WITS device coupled to a simulated gun.

[0041] FIG. 16 is a close up view of buttons for turning on and off a flashlight of the WITS device, and the location of the buttons on the simulated gun.

[0042] FIG. 17 is a close up view of a sensor opening within the trigger guard, and the location of the sensor.

[0043] FIG. 18 illustrated the position of IR LEDs included in the example WITS device embodiment shown in FIG. 15, coupled to the gun.

[0044] FIG. 19 shows the location of a rechargeable battery as the bottom of the WITS device embodiment shown in FIG. 15, coupled to the gun.

[0045] The structure, operation, and advantages of disclosed embodiments will become further apparent upon consideration of the following description taken in conjunction with the accompanying figures (FIGS.). The figures are intended to be illustrative, not limiting. Certain elements in some of the figures may be omitted, or illustrated not-to-scale, for illustrative clarity.

DETAILED DESCRIPTION

[0046] Disclosed embodiments provide systems and methods for conducting a firearm usage simulation including simulated firearm discharge, enabling enhanced training of armed forces and/or law enforcement personnel. A motion tracking system tracks motion of one or more users. In embodiments, the users wear one or more sensors, transponders, or other wearable devices on their bodies to allow tracking by the motion tracking system. A scenario management system utilizes position, orientation, and motion information provided by the motion tracking system to evaluate user performance during a scenario. A weapon simulator includes sensors that indicate position of the weapon and/or orientation of the weapon. The weapon simulator may further provide trigger activation indications to the scenario management system. In embodiments, the scenario management system generates, plays, reviews, and/or evaluates simulations. The evaluation can include scoring based on reaction times, posture, body position, body orientation, and/or other attributes. Thus, disclosed embodiments provide a safe and cost-effective way to train personnel in the use of a weapon in various scenarios, and evaluate the users

based on information provided by the motion tracking system and/or weapon simulator.

[0047] FIG. 1 is a diagram of a system 100 in accordance with embodiments of the present invention. System 100 includes a scenario management system 102. The scenario management system 102 can be implemented in an electronic computing device that includes a processor 140, a memory 142 coupled to the processor, and storage 144, also coupled to the processor 140. Memory 142 contains instructions 147, that when executed by the processor 140, cause the scenario management system 102 to perform steps in accordance with embodiments of the present invention. Memory 142 may be a non-transitory computer readable medium. Memory 142 may include, but is not limited to, flash, read-only memory (ROM), static random-access memory (SRAM), magnetic storage, optical storage, or other suitable storage mechanism. Storage 144 may include one or more magnetic hard disk drives (HDD), solid state disk drives (SSD), optical storage devices, tape drives, and/or other suitable storage devices.

[0048] In embodiments, storage 144 may include multiple hard disk drives configured in a RAID (redundant array of independent disks) configuration. In embodiments, the RAID configuration can include a RAID 1 configuration in which data is copied seamlessly and simultaneously, from one disk to another, creating a replica, or mirror. If one hard disk drive becomes inoperable, another hard disk drive continues to operate, providing a level of fault tolerance.

[0049] The processor 140 may include multiple cores. In embodiments, the scenario management system 102 may include multiple processors, where each processor includes multiple cores. Embodiments may schedule tasks and threads over multiple processors and/or cores to achieve a level of parallelism in execution of various tasks such as computations, rendering, and/or scenario generation.

[0050] Embodiments may include additional redundancy through failover mechanisms. In embodiments, the scenario management system 102 may be instantiated as a virtual machine operating in a cloud environment. In embodiments, multiple instantiations of the scenario management system 102 may be implemented in the cloud environment. Scenario management system 102 is in communication with network 124. Network 124 may be the Internet, a local area network (LAN), wide area network (WAN), or another suitable network.

[0051] The term "Internet" as used herein refers to a network of networks which uses certain protocols, such as the TCP/IP protocol, and possibly other protocols such as the hypertext transfer protocol (HTTP) for hypertext markup language (HTML) documents that make up the World Wide Web (web). The physical connections of the Internet and the protocols and communication procedures of the Internet are well known to those of skill in the art. Access to the Internet can be provided by Internet service providers (ISP). Users on client systems, such as client 116, obtain access to the Internet through the Internet service providers. Access to the Internet allows users of the client computer systems to exchange information, receive and send e-mails, and view documents, such as documents which have been prepared in the HTML format. These documents are often provided by web servers which are considered to be "on" the Internet. Often these web servers are provided by the ISPs, although

a computer system can be set up and connected to the Internet without that system being also an ISP as is well known in the art.

[0052] System 100 further includes motion tracking system 130. Motion tracking system 130 includes a processor 132, a memory 134 coupled to the processor, and storage 136, also coupled to the processor 132. Memory 134 contains instructions, that when executed by the processor 132, cause the motion tracking system 130 to perform steps in accordance with embodiments of the present invention. Memory 134 may be a non-transitory computer readable medium. Memory 134 may include, but is not limited to, flash, read-only memory (ROM), static random-access memory (SRAM), magnetic storage, optical storage, or other suitable storage mechanism. Storage 136 may include one or more magnetic hard disk drives (HDD), solid state disk drives (SSD), optical storage devices, tape drives, and/or other suitable storage devices. In embodiments, memory 134 includes at least 32 gigabytes of RAM. Motion tracking system 130 further includes one or more cameras 137. The cameras may be configured to detect visible and/or infrared light. The motion tracking system 130 may further include one or more sensors. These sensors may include, but are not limited to, temperature sensors, proximity sensors, noise sensors, and/or other suitable sensors. In some embodiments, processor 132 may include an Intel i7 CPU or higher. The motion tracking system 130 may include a graphics processor such as the Nvidia GTX 1070 or higher, and include a high-performance network card.

[0053] A client device, indicated as 116 may be connected to network 124 via a wired or wireless interface. Client device 116 may include a mobile computing device such as a smartphone or tablet, a laptop computer, a desktop computer, or other suitable computing device. The client-server architecture allows a user to remotely access features of the scenario management system 102. In embodiments, the client device 116 may include an Intel i7 CPU or higher, an Nvidia GTX 1080 graphics processing unit or higher, and 16 GB of ram or more.

[0054] Embodiments of the present invention may utilize a JavaScript Object Notation (JSON) web service to make a JSON call to the scenario management system. In some examples, the JSON call is made using XML HTTP, which implements an XML HTTP object that has functionality enabling the exchange of Extensible Markup Language (XML) data directly over the Internet using the Hypertext Transfer Protocol (HTTP). The XML HTTP object allows access of the scenario management system data from a server, parsing the data using an XML Document Object Model (DOM), and posting XML data through a standard firewall directly to an HTTP server.

[0055] The cameras 137 and/or sensors 138 of motion tracking system 130 may be deployed in a venue such as a room, building, or outdoor area, such that they can track the motion of one or more users (200A, 200B, 200C, and 200D). Note that while four users are shown in FIG. 1, in practice, more or fewer users may be present. Referring now to user 200A, additional detail is shown. Each user may utilize one or more wearable sensors 206. The wearable sensors can be used to detect motion and position of a user. By having sensors on the limbs of a user, the position and/or orientation of a user can be more precisely determined. Each user may further wear a helmet 205. The helmet 205 may include a sensor 207 that can be used to determine head location

and/or head orientation of the wearer (user). Each user may further wear goggles 204. The goggles 204 may include virtual reality goggles, augmented reality goggles, or other suitable eyewear. The goggles 204 may further include speakers that provide audible feedback to a user. In embodiments, the goggles 204 may include a forward-facing camera to enable recording and/or monitoring of the user's point of view. In embodiments, the goggles 204 may include a user-facing camera to monitor the eye gaze of a user. In this way, the direction of eye gaze, even if different from head orientation, can be ascertained.

[0056] Each user may further utilize a weapon simulator 202. The weapon simulator may be in the form of a firearm, and may include a recoil simulation mechanism such as compressed air or a mechanical spring to simulate the recoil associated with discharging a real firearm. The weapon simulator 202 may further include an inertial tracker 208 affixed to the weapon simulator 202. The inertial tracker 208 may include one or more accelerometers and/or gyroscopes to track motion of the weapon simulator 202. Sometimes, motion associated with recoil can adversely affect the inertial tracker 208. Therefore, embodiments may further include a shock mount 210 disposed between the weapon simulator 202 and the inertial tracker 208. This allows the position of the weapon simulator to be tracked as the user moves it, while preventing the adverse effects of recoil motion, since the shock mount absorbs some of the recoil motion.

[0057] FIG. 2 is a block diagram of a client device 300 in accordance with embodiments of the present invention. In embodiments, client device 300 is an electronic device that may include a desktop computer, laptop computer, tablet computer, smartphone, and/or other suitable client device. Client device 300 may be similar to client device 116 as shown in FIG. 1. Client device 300 includes a processor 302, a memory 304 coupled to the processor 302, and storage 306. The memory 304 may be a non-transitory computer readable medium. Memory 304 may include RAM, ROM, flash, EEPROM, or other suitable storage technology. The memory 304 contains instructions, that when executed by processor 302, enable communication to/from scenario management system 102 of FIG. 1. Client device 300 further includes a network communication interface 310 for performing this communication. In embodiments, network communication interface 310 includes a wireless communications interface such as a cellular data interface and/or a Wi-Fi interface. In embodiments, the storage 306 includes flash, SRAM, one or more hard disk drives (HDDs) and/or solid state disk drives (SDDs).

[0058] Device 300 may further include a user interface 308. User interface 308 may include a keyboard, monitor, mouse, and/or touchscreen, and provides a user with the ability to enter information as necessary to utilize embodiments of the present invention. In embodiments, a user uses the device 300 to access the scenario management system 102.

[0059] FIG. 3 is a block diagram 400 of components in accordance with embodiments of the present invention. Components include, but are not limited to, motion tracker 402, weapons interface 404, inverse kinematic solver 406, client communication component 408, scenario management component 410, and/or data analysis 412. The motion tracker 402 may be a commercially available motion tracker such as OptiTrack™ by NatrualPoint, of Corvallis, Oregon.

The motion tracker **402** may include multiple cameras installed within a room, building, or other venue where a scenario is to be executed. The cameras may be adapted to track wearable sensors that emit infrared light. As a user, wearing the wearable sensors moves, his/her motion is tracked by the motion tracker **402**. The weapons interface **404** may implement recoil simulation, gun flash simulation, trigger activation notifications, and/or other weapons-related simulation functions. The inverse kinematic (IK) solver **406** may be used to create an inverse kinematic solution to rotate and position links in a chain. This can be used to model human movement to create virtual targets and/or model the motion of live users.

[0060] The scenario management component **410** may be implemented as a computer system such as system **102** of FIG. 1. Alternatively, the scenario management component **410** may be implemented as multiple computers in a distributed or cloud computing environment. The scenario management component may be used for generating scenarios, executing scenarios, and/or playback of previously executed scenarios. The data analysis component **412** may be used for analyzing an executed scenario. This can include performing numerous assessments on users that are tracked by the motion tracker **402**. Assessments can include reaction time, location analysis, physiological orientation of the user, orientation of the user's head, eye gaze, limb position, and others.

[0061] For example, in a given scenario, upon hearing a gunshot, a user may be trained to drop to a crouched position, turn his head towards the direction of the gunshots, and draw his weapon. To provide a training experience for a user, a scenario is executed by the scenario management component **410**. This component may generate the virtual environment, including audiovisual information rendered by goggles **204**. A gunshot sound is rendered on the speaker of goggles **204** worn by the user, and the scenario management component **410** records this time. The user starts to move, and the motion tracker determines how long it takes to get into a crouched position, how long it takes for the user to draw his weapon, and if his head is oriented in the proper position. In embodiments, after a predetermined time (e.g. 2 seconds), the user orientation and weapon orientation are evaluated. In embodiments, a user score is generated based on the time required for the user to achieve the proper position. In this way, the user can continually practice, and review his performance to achieve an optimal reaction time. Other, more complex examples are possible, such as scenarios utilizing multiple friends and foes. In embodiments, one or more of the friends and/or foes may be virtual.

[0062] FIGS. 4A-4D show a shock mount in accordance with embodiments of the present invention.

[0063] FIG. 4A is a perspective view of a shock mount **500** in accordance with embodiments of the present invention. Shock mount **500** includes a top plate **503**, a bottom plate **506**, and a plurality of resilient members **504** configured and disposed between the top plate **503** and the bottom plate **506**, and terminated at the top with end caps, indicated generally as **541**. This reduces the amount of shock imparted to the inertial tracker **508** from the handle **526** of a weapon simulator as a result of a recoil simulation. The weapon simulator may utilize compressed air, solenoids, springs, or other electromechanical mechanisms to simulate a recoil that occurs when a firearm is discharged. The shock mount **500** reduces the shock imparted on the inertial tracker **508**,

which helps improve the reliability of data returned by the inertial tracker. In embodiments, the inertial tracker may be a commercially available inertial tracker such as Vive™ tracker by HTC corporation. In some embodiments, the resiliency of the resilient members **504** may be adjustable to accommodate different types of weapon simulators and/or inertial trackers. Shock mount **500** may be similar to shock mount **210** shown in FIG. 1. FIG. 4B is a top view of the shock mount **500**, illustrating the mounting shoe **543** configured and disposed to receive a weapon simulator. FIG. 4C is a front view of the shock mount **500**, illustrating a plurality of coupling pins **545** for interfacing to an inertial tracker. In embodiments, the coupling pins **545** may be spring loaded “Pogo” pins. FIG. 4D is a bottom view of the shock mount **500**, indicating a linear arrangement of the coupling pins **545**.

[0064] FIG. 5 illustrates an example of a shock mount in use. A weapon simulator **520** has a handle **526**. In embodiments, the weapon simulator **520** may be in the form factor of a pistol. The shock mount **500** is affixed to the bottom of the handle (grip) **526**. The inertial tracker **508** is affixed to the shock mount **500**. The weapon simulator **520** shown is a Glock simulator. In embodiments, the weapon simulator **520** is configured to use compressed gas in order to create haptic feedback (or recoil) that creates a strong vibration to the inertial tracker **508** tracker. The shock mount **500** of disclosed embodiments connects the inertial tracker **508** to the handle **526** while also reducing the shock from simulated recoil which could possibly ruin the tracking data of the inertial tracker **508**. In embodiments, a small pressure-sensitive button is placed behind the trigger to send the trigger activation information through electronic circuitry that connects to an interface of the inertial tracker. The inertial tracker may then use a wireless interface such as Bluetooth™ to send the trigger activation signal to the computer for further processing.

[0065] FIG. 6 illustrates a weapon simulator **600** in accordance with embodiments of the present invention. Weapon simulator **600** is in the form factor of an automatic rifle. A motor **602** embedded in the grip is configured to generate haptic feedback upon activation of the trigger **604**. A battery **612** in the stock of the weapon simulator **600** provides power for the motor **602**. Additionally, a wireless transmitter **606** is configured and disposed to provide discharge information to the scenario management system. The wireless transmitter **606** may communicate with a wireless receiver **608** attached to a computer **610**. In embodiments, computer **610** is part of the scenario management system. Thus, embodiments include a communication module configured and disposed to wirelessly transmit a trigger indication to the scenario management system in response to activation of the trigger.

[0066] FIG. 7 illustrates a weapon simulator **700** in accordance with additional embodiments of the present invention. Weapon simulator may be in the form factor of a pistol. An optical tracker **702** may be installed on the weapon simulator **700**. One or more light sources, indicated as **704** and **706** may be tracked by the motion tracking system to provide information on the position and/or orientation of the weapon simulator to the scenario management system.

[0067] In embodiments, the tracker **702** orients one or more LEDs in specific locations for optimal tracking. A pressure sensitive button is placed behind the handgun trigger and that passes a signal to a computer via a wireless communication protocol such as Bluetooth™, WiFi, Zigbee,

or other suitable protocol upon activation of the trigger **708** of the weapon simulator. In embodiments, the unit is self-contained with its own LIPO battery, voltage converter, charger port, and on/off button.

[**0068**] FIGS. **8A-8 i** illustrate examples of inverse kinematic solver computations. In embodiments, a full body IK solver allows animation of a human body model in real time based on animations of 5 control points. In embodiments, a body skeleton is divided into the following five bone chains. A spine chain starts with a pelvis bone and ends with a head bone. A left leg chain starts with a pelvis bone and ends with a left foot bone. A right leg chain starts with a pelvis bone and ends with a right foot bone. A left arm chain starts with a left shoulder bone and ends with a left palm bone. A right arm chain starts with a right shoulder bone and ends with a right palm bone. Each chain of bones is solved using a Backward/Forward IK solver gets as an input, two 3D matrices and calculates transform of bones in a chain in 3D space. Changing locations or rotations of either start or end input will change transformation of the bones in the chain. Each chain can consist of any number of bones. Referring now to FIG. **8A**, a bone chain **800** is shown in an extended bone state. Three bones (**802**, **803**, and **804**) are extended fully such that endpoint **801** and endpoint **805** are at a maximum possible distance.

[**0069**] Referring now to FIGS. **8B**, **8C**, and **8D**, there are shown examples of non-extended bone states. Referring to FIG. **8B**, bone chain **810** is oriented such that the distance **D** between first endpoint (start) **811** and second endpoint (end) **812** is less than the sum of the lengths of all bones in the bone chain. A similar case exists for bone chain **814** of FIG. **8C** and bone chain **815** of FIG. **8D**.

[**0070**] Referring now to FIG. **8E** there is a bone chain with a force vector **UP** applied to it. In order to bend the chain in the known direction, the **UP** direction has to be defined for the chain. **UP** direction is a 3D vector. **UP** direction gets applied to the initial pose and changes it. In the diagram, the **UP** direction is to the left, which means the chain **819** will bend to the right.

[**0071**] Referring now to FIG. **8F**, forward solving computations are shown. Starting from the current state of the chain, positions of each bone in the chain are found using the forward solving equation:

$$A' = End' - (End' - A)$$

[**0072**] Starting from the bone closest to the end, this equation is repeated for each bone by replacing End' vector with the location of previous bone in the chain.

[**0073**] For finding B' for example, the following equation is used:

$$B' = A' - (A' - B)$$

[**0074**] Similarly, for C' :

$$C' = B' - (B' - C)$$

[**0075**] Referring now to FIG. **8G**, a chain rigidity factor is applied. In embodiments, each bone has a rigidity factor which determines how easily a given bone will change its position when start or end transforms change. A value from 0 to 1 determines where the bone will be placed between the initial pose and the current pose. In this example, bone **821** has a rigidity factor of 0.5 and so it is moved to halfway between points **B** and B' .

[**0076**] Referring now to FIG. **8H**, backward solving is performed. Starting from the current state of the chain, positions of each bone in the chain are found using a backward solving equation. The process starts from the bone closest to the start input, and the equations below are applied:

$$C'' = C$$

$$B'' = C'' + (B' - C'')$$

$$A'' = B'' + (A' - B'')$$

[**0077**] Referring now to FIG. **8i**, the orientation of the bones is calculated. Bone chain **823** shows an initial position, and bone chain **825** shows a final position. In embodiments, orientation of the bones gets calculated after positions are solved for, and it is known where each bone is located and where this bone was in the initial pose. In embodiments, in the initial pose a rotational matrix is constructed for each bone. In the solved pose there is constructed a new rotational matrix for each bone using the same axis order. One axis is parallel to the length of the bone (**Z** in the diagram). A second axis is linearly interpolated between the upnode (**UP**) chain vector multiplied by start and upnode chain vector multiplied by end transform (**Y** in the diagram). Linear interpolation of this axis allows simulation of twisting of bones along their long axis (**z**) if end or start transform is twisted. This approach allows adjusting of the extent of the twist for each bone easily by changing one numeric value. Once there are derived two rotational matrices for the bone, then the offset between them is calculated and this transform offset is applied to the bone. This approach allows rotation of bones independently of their initial orientation. Orientation of bones can be inconsistent in the initial chain pose.

[**0078**] FIG. **9A** is a front view of a wearable sensor **900** in accordance with embodiments of the present invention. Wearable sensor **900** includes light emitting diode **902** installed therein. A battery within the sensor (not shown) applied power to the light emitting diode **902**. In embodiments, the light emitting diode (LED) **902** emits infrared light and does not emit substantial visible light. This allows the LED **902** of sensor **900** to be detected by the motion tracking system, and yet not be noticeable to the users.

[**0079**] FIG. **9B** is a rear view of the wearable sensor **900** of FIG. **9A**. In this view, the adjustable strap **904** can be seen. This strap **904** is used to secure the wearable sensor around a limb (arm, leg) of a user. In embodiments, the strap **904** may have a fastener such as a snap, hook and loop fastener, or other suitable fastening mechanism. Wearable sensor **900** may be similar to sensors **206** shown in FIG. **1**.

[**0080**] FIG. **10** is a flowchart **1000** indicating process steps for embodiments of the present invention. At process step **1002**, a user position is determined. The user may be

wearing one or more wearable devices such as position sensors and/or position indicators. The wearable devices may emit infrared light that is tracked by a motion tracking system. In process step **1004**, an initial physiological orientation is determined. In some embodiments, a wearable device is worn on each limb, allowing the motion tracking system to determine physiological orientation. The physiological orientation can include a stance (e.g. standing, crouching, prone), and may further including a direction the user is facing. In process step **1006**, a simulated firearm discharge is detected. In embodiments, this can include a weapon simulator in the form factor of a firearm. The weapon simulator includes a power source (battery) and a wireless transmitter that is configured and disposed to transmit a trigger activation indication to a computer to indicate that the weapon simulator has discharged (e.g. a user pulled the trigger on the weapon simulator). The weapon simulator may or may not actually shoot a projectile. In process step **1008**, a user reaction is determined. This can include determining a second physiological orientation of the user at some predetermined time after the detection of the simulated firearm discharge. The second physiological orientation can include a position of a person, position of the limbs of that person, orientation of the torso of the person (which way the torso is facing), and/or orientation of the head of the person (which way the head of the user is facing). Thus, in embodiments, determining a physiological orientation of the user comprises determining a facial direction of the user.

[0081] Additionally, in embodiments with a user-facing camera (e.g. included in virtual or augmented reality goggles), an eye gaze direction may further be included in the physiological orientation. Various attributes can then be evaluated, including, but not limited to, the time required for the user to achieve the second physiological orientation (e.g. a measure of how long did it take the user to get into a crouch position in response to hearing and/or seeing a simulated firearm discharge), the correctness of the second physiological orientation as compared to a known orientation (e.g. a measure of if the user's crouch is sufficiently low), and/or the time required to draw a weapon (e.g. a measure of the time required for the user to pull a weapon simulator from a holster and orient it in a position to fire). Other attributes of user reaction may be evaluated instead of, or in addition to the aforementioned attributes in embodiments of the present invention.

[0082] FIG. **11** is a flowchart **1100** indicating additional process steps for embodiments of the present invention. In process step **1102**, a final position time is determined. This may include determining a time where the user's level of motion is below a predetermined threshold. Thus, embodiments include further comprising measuring a duration from a time of the simulated firearm discharge to a time of detecting the determined physiological orientation. As an example, when a user is in the process of quickly moving from a standing position to a crouched position, there is a relatively large amount of motion. Once the user is stabilized in the crouched position, there is relatively less motion. The time when the user is substantially still may be recorded as a final position time. At process step **1104**, a final position quality is determined. This may include utilization of motion tracking data to determine how close the user's physiological orientation is to an expected physiological orientation. This can include an assessment of if the user is in a proper stance/position, facing the proper direction, appropriately

drawing his weapon simulator, and/or other factors. In process step **1106**, the final position time is compared to average times. In process step **1108**, a score is generated based on the comparison to the average time. In some embodiments, the score may be generated using the formula:

$$K(1-X)$$

[0083] Where:

[0084] K is a constant;

[0085] X is the final position time in seconds.

[0086] As an example, if an average time for a law enforcement professional to go from standing to crouched is 400 milliseconds, then the final position time may be compared against the average time using the above formula. If K is 116, then the following score is achieved for different crouch times:

Crouch time (milliseconds)	Score
400	69.6
500	50
600	46.4
200	92.8
300	81.2

[0087] As can be seen from the table above, the formula returns a score such that a user with an average time of 400 milliseconds earns a score of about 70, while a user with a score of 300 returns a higher score (81.2). Similarly, a user with a relatively slow time of 600 milliseconds returns a low score of 46.4. This concept can also be applied to other attributes, such as position quality, weapon draw time, weapon discharge time, and/or other attributes. In embodiments, the score for each attribute may be combined into an overall score.

[0088] FIG. **12** is an exemplary user interface **1200** in accordance with embodiments of the present invention. User interface **1200** may be implemented on a client device such as client device **116** of FIG. **1**. The user interface may be used to allow users and/or trainers and coaches to review performance. User interface **1200** includes a video window **1202** that may show video and/or a virtual animated rendition of the user performance. In some embodiments, real video and animated graphics may be composited together in video window **1202**. User interface **1200** further includes a name field **1204**, a scenario name **1206**, a final position score **1208**, a reaction time **1210**, a weapon draw time **1214**, and a weapon discharge time **1216**. In embodiments, the weapon draw time **1216** may be the time required by the user to move his weapon simulator from a holstered position to a ready position as determined by the motion tracking system. In embodiments, the weapon discharge time may be the time required by the user to fire the weapon simulator after getting the weapon simulator into the ready position (e.g. aimed at a target). The data analysis component (**412** of FIG. **3**) may further provide computer-generated recommendations, which may be rendered in field **1218**. The recommendations can be based on scores and/or times for one or more attributes during a scenario execution. The user interface **1200** is merely exemplary, and other user interfaces are possible showing more, fewer, or different fields in some embodiments.

[0089] FIG. **13** shows an additional embodiment. Weapon simulator **1300** includes additional stock **1302** affixed to the

rear end of the weapon simulator. This enables users wearing a head-mounted display (HMD) to get into a shooting position without having the HMD bump into the stock end of the weapon simulator, thereby allowing for a more unencumbered user experience.

[0090] Some embodiments may provide an untethered experience with computers mounted in backpacks. Such embodiments may include, but are not limited to, an MSR V1 with a GTX 1070, or an HP ZVR with a GTX 1070. The computers may be configured with an Intel i7 processor and at least 16 GB of RAM. Other backpack computers are possible in embodiments of the present invention.

[0091] As can now be appreciated, disclosed embodiments provide an improved training system for firearm usage. A motion tracking system tracks the motion of one or more users. Users use a weapon simulator that integrates with a scenario management system. The scenario management system thus obtains information about weapon position and weapon discharge, as well as position of the users. The scenario management system can generate scenarios where live participants, virtual participants, and/or computer-generated targets work together or against each other to conduct training drills. Through the use of virtual reality, augmented reality, or both, various landscapes, terrain, buildings, and other factors can be simulated. The reactions of users can be timed and assessed, allowing for improved review of the performance of users such as military and law enforcement personnel. In this way, the effectiveness and safety of these people can be continuously monitored and improved.

[0092] Turning now to FIGS. 14, a device 140 is illustrated for use in conjunction with a simulated weapon 145 in a Wireless Independent Tracking System (WITS). In FIG. 14A, the WITS device is shown firmly coupled to a simulated gun 145 that may be used in training scenarios. The coupling may be realized using any coupler able to firmly connect the WITS device to the gun, such as screws, glue, or the like. FIG. 14B shows a front view of the WITS device; FIG. 14C shows a side view, FIG. 14D shows a rear view, and FIG. 14F shows a side perspective view of the device. FIG. 15 shows a perspective view of the gun with the WITS device coupled to it. It is noted similar WITS systems and devices have been the subject of previous patent application (s) with common inventor(s) and/or common ownership. Although the WITS device is shown coupled to the front of the gun, other positions may be used. The WITS device may also be used with other types of simulated manually operated weapons. However, certain modifications and improvements have been incorporated into the WITS device compared with previous models. The new capabilities the WITS device may incorporate include any or all of the following features. FIG. 15 shows a perspective view of the WITS device coupled to the gun. FIGS. 16-19 are close up views of FIG. 15 showing an example position of these aspects, although other positions, switches, and the like may be used.

[0093] In embodiments, the WITS device may include an integrated vibrator, primarily for safety purposes. As shown in the embodiments illustrated in the figures, the vibrator may be incorporated inside the WITS device case and out of view. Preferably, the vibration is sufficiently pronounced, and the coupling of the WITS module so firmly coupled to the gun, that the vibrations can be felt by the person holding the gun. In an embodiment, when participants approach the boundary of the training area they may hear warning beeps from the weapon, and the weapon may vibrate in sync,

providing both an auditory and a tactile cue. Alternatively or in addition, one or more other cues may be included, such as a flashing LED or the like to add a visual cue. In embodiments, the training area boundary may be defined by a remote operator, and it may be adjusted to mimic a particular real world environment. However, other aspects of the WITS module may not be adjustable. For example, in embodiments the warning beeps cannot be modified.

[0094] In embodiments, the WITS device may include a virtual reality (VR) flashlight arranged to shine a light in a forward direction. The light and an on-off switch may be of any appropriate type, and may be placed together or separately at any convenient location on the gun. For example, in an example implementation illustrated in FIG. 16, two switch buttons 160, one on either side of the gun, may be added next to the trigger to simulate a tactical flashlight in the virtual reality environment. This enhances immersion and realism during training scenarios.

[0095] In embodiments, as illustrated in FIG. 17, the WITS device may include a sensor 170 located in the trigger guard. This may be desirable, for example, in a training environment, in which the training methodology emphasizes that the finger should enter the trigger guard area only when intending to pull the trigger. If the finger remains on the trigger without the intention to shoot, it may lead to unintentional firing. Accordingly, the presence sensor provides a signal that may be received by an external receiver when a training participant's trigger finger is detected within the trigger guard for a select or a default time period. Previously after training, an After Action Review (AAR) was conducted that indicated if a participant kept their finger on the trigger without shooting for more than a select or default duration, such as S seconds. Because of the sensor, that information is available immediately and may be addressed promptly. The received presence sensor signal may be used to generate immediate feedback to the gun to alert the training participant that their trigger finger is within the trigger guard, or to generate training review data for use in assessing the participant's training performance, or both. Additionally, the weapon may be made to vibrate every time this violation occurs, providing feedback and helping participants learn proper trigger discipline.

[0096] In embodiments, the WITS device may include an improved tracking capability. For example, as illustrated in FIG. 18, two additional IR LEDs 180 have been incorporated to enhance tracking. This may be particularly desirable when the weapon is holstered. This ensures more accurate and reliable tracking of the weapon's position and movements.

[0097] As illustrated in FIG. 19, in embodiments the WITS device may feature a larger battery 190 for extended battery life. In a currently preferred embodiment, the battery 190 may be firmly coupled to the bottom of the WITS device case, such as with screws, although other arrangements may be used. The battery may be powered by removable batteries or a rechargeable battery. This WITS device when fully charged should remain active for up to 8 hours continuously, while keeping the outer shell the same size. This extended battery life ensures uninterrupted training sessions without the need for frequent recharging.

[0098] In embodiments, the WITS device may include an Inertial Measurement Unit (IMU) sensor. With the incorporation of an IMU sensor, the device may be configured to automatically enter a sleep mode if it is not powered down

for a select or default time period. This feature helps conserve battery power for extended periods, ensuring longer usability. In a currently preferred embodiment, the design of the printed circuit board (PCB) has been updated to incorporate the IMU on the PCB.

[0099] In addition to a device that may be coupled to a simulated weapon for use in training, some or all of the described features and aspects of the present invention may be included in a system, a method, and/or a computer program product at any possible technical detail level of integration. The computer program product may include a non-transitory computer readable storage medium (or media) having computer readable program instructions thereon for causing a processor to carry out aspects of the present invention.

[0100] Each of the above methods may be executed on one or more processors on one or more computer systems. Embodiments may include various forms of distributed computing, client/server computing, and cloud based computing. Further, it will be understood that the depicted steps or boxes contained in the disclosed flowcharts are solely illustrative and explanatory. The steps may be modified, omitted, repeated, or re-ordered without departing from the scope of this disclosure. Further, each step may contain one or more sub-steps. While the foregoing drawings and description set forth functional aspects of the disclosed systems, no particular implementation or arrangement of software and/or hardware should be inferred from these descriptions unless explicitly stated or otherwise clear from the context. All such arrangements of software and/or hardware are intended to fall within the scope of this disclosure.

[0101] The block diagrams and flowchart illustrations may depict methods, devices, systems, and computer program products. Any and all such functions, generally referred to herein as a “circuit,” “module,” or “system” may be implemented by computer program instructions, by special-purpose hardware-based computer systems, by combinations of special purpose hardware and computer instructions, by combinations of general purpose hardware and computer instructions, and so on.

[0102] It will be understood that a computer may include a computer program product from a computer-readable storage medium and that this medium may be internal or external, removable and replaceable, or fixed. In addition, a computer may include a Basic Input/Output System (BIOS), firmware, an operating system, a database, or the like that may include, interface with, or support the software and hardware described herein.

[0103] Embodiments of the present invention are neither limited to conventional computer applications nor the programmable apparatus that run them. To illustrate: the embodiments of the presently claimed invention could include an optical computer, quantum computer, analog computer, or the like. A computer program may be loaded onto a computer to produce a particular machine that may perform any and all of the depicted functions. This particular machine provides a means for carrying out any and all of the depicted functions.

[0104] Any combination of one or more computer readable media may be utilized including but not limited to: a non-transitory computer readable medium for storage; an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor computer readable storage medium or any suitable combination of the foregoing; a portable computer

diskette; a hard disk; a random access memory (RAM); a read-only memory (ROM), an erasable programmable read-only memory (EPROM, Flash, MRAM, FeRAM, or phase change memory); an optical fiber; a portable compact disc; an optical storage device; a magnetic storage device; or any suitable combination of the foregoing. In the context of this document, a computer readable storage medium may be any tangible medium that can contain or store a program for use by or in connection with an instruction execution system, apparatus, or device.

[0105] Computer readable program instructions described herein can be downloaded to respective computing/processing devices from a computer readable storage medium or to an external computer or external storage device via a network, for example, the Internet, a local area network, a wide area network and/or a wireless network. The network may comprise copper transmission cables, optical transmission fibers, wireless transmission, routers, firewalls, switches, gateway computers and/or edge servers. A network adapter card or network interface in each computing/processing device receives computer readable program instructions from the network and forwards the computer readable program instructions for storage in a computer readable storage medium within the respective computing/processing device. Program data may also be received via the network adapter or network interface.

[0106] These computer readable program instructions may be provided to a processor of a computer, or other programmable data processing apparatus to produce a machine, such that the instructions, which execute via the processor of the computer or other programmable data processing apparatus, create means for implementing the functions/acts specified in the flowchart and/or block diagram block or blocks. These computer readable program instructions may also be stored in a computer readable storage medium that can direct a computer, a programmable data processing apparatus, and/or other devices to function in a particular manner, such that the computer readable storage medium having instructions stored therein comprises an article of manufacture including instructions which implement aspects of the function/act specified in the flowchart and/or block diagram block or blocks.

[0107] It will be appreciated that computer program instructions may include computer executable code. A variety of languages for expressing computer program instructions may include without limitation C, C++, Java, JavaScript™, assembly language, Perl, Python, Ruby, hardware description languages, database programming languages, functional programming languages, imperative programming languages, and so on. In embodiments, computer program instructions may be stored, compiled, or interpreted to run on a computer, a programmable data processing apparatus, a heterogeneous combination of processors or processor architectures, and so on. Without limitation, embodiments of the present invention may take the form of web-based computer software, which includes client/server software, software-as-a-service, peer-to-peer software, or the like.

[0108] In embodiments, a computer may enable execution of computer program instructions including multiple programs or threads. The multiple programs or threads may be processed approximately simultaneously to enhance utilization of the processor and to facilitate substantially simultaneous functions. By way of implementation, any and all

methods, program codes, program instructions, and the like described herein may be implemented in one or more threads which may in turn spawn other threads, which may themselves have priorities associated with them. In some embodiments, a computer may process these threads based on priority or other order.

[0109] Unless explicitly stated or otherwise clear from the context, the verbs “execute” and “process” may be used interchangeably to indicate execute, process, interpret, compile, assemble, link, load, or a combination of the foregoing. Therefore, embodiments that execute or process computer program instructions, computer-executable code, or the like may act upon the instructions or code in any and all of the ways described. Furthermore, the method steps shown are intended to include any suitable method of causing one or more parties or entities to perform the steps.

[0110] The terminology used herein is for describing particular aspects only and is not intended to be limiting of the invention. As used herein, the singular forms “a”, “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “include” and “including” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof. Certain examples and elements described in the present specification, including in the claims and as illustrated in the figures, may be distinguished or otherwise identified from others by unique adjectives (e.g. a “first” element distinguished from another “second” or “third” of a plurality of elements, a “primary” distinguished from a “secondary” one or “another” item, etc.) Such identifying adjectives are generally used to reduce confusion or uncertainty, and are not to be construed to limit the claims to any specific illustrated element or embodiment, or to imply any precedence, ordering or ranking of any claim elements, limitations or process steps.

[0111] While the invention has been disclosed in connection with preferred embodiments shown and described in detail, various modifications and improvements thereon will become apparent to those skilled in the art. Accordingly, the foregoing examples should not limit the spirit and scope of the present invention; rather it should be understood in the broadest sense allowable by law.

What is claimed is:

1. A wireless independent tracking system (WITS) device for use with a simulated weapon in a virtual reality (VR) environment, the WITS device comprising:

at least one tag for use in tracking a simulated weapon (gun) the WITS device is coupled to;

a coupler configured to firmly couple the WITS device to the gun.

2. The WITS device of claim **1**, wherein the coupler is one of an adhesive or screws.

3. The WITS device of claim **1**, further comprising a vibrator within an outer case of the WITS device.

4. The WITS device of claim **3**, wherein the gun vibrates in conjunction with a warning beep when the gun is brought within a predetermined distance from a training area boundary in which the gun is used by a participant.

5. The WITS device of claim **4**, wherein the boundary is defined by a remote operator of a training scenario controller.

6. The WITS device of claim **1**, further comprising a virtual reality (VR) flashlight.

7. The WITS device of claim **6**, wherein:

the VR flashlight shines in a forward direction, and

the WITS device is operatively coupled to at least one flashlight on/off switch located on a side of the gun.

8. The WITS device of claim **1**, further comprising a presence sensor located in the gun’s trigger guard arranged to detect a trigger finger present in within the trigger guard in close proximity to the gun’s trigger.

9. The WITS device of claim **8**, wherein the presence sensor provides a presence sensor signal when a training participant’s trigger finger is detected within the trigger guard for a select or a default time period.

10. The WITS device of claim **9**, wherein the presence sensor signal is used to generate immediate feedback to the gun to alert the training participant that their trigger finger is within the trigger guard.

11. The WITS device of claim **9**, wherein the presence sensor signal is used to generate training review data for use in assessing the participant’s training performance.

12. The WITS device of claim **1**, further comprising at least one IR LED located on both the left and right sides of the gun.

13. The WITS device of claim **1**, further comprising a rechargeable battery coupled to a WITS device outer case as a bottom of the WITS device.

14. The WITS device of claim **13**, wherein the battery is firmly coupled to a bottom of a WITS device outer case using screws or glue.

15. The WITS device of claim **13**, wherein the WITS device when fully charged and powered on remains active for up to 8 hours continuously.

16. The WITS device of claim **12**, further comprising an inertial measurement unit (IMU) that compensates for loss of tracking of the LEDs when they are occluded.

17. The WITS device of claim **16**, wherein the IMU is configured to automatically enter a sleep mode if it is not powered down for a select or default time period.

18. The WITS device of claim **16**, wherein the IMU is incorporated into or firmly coupled to a printed circuit board (PCB) of the WITS device.

* * * * *