

Jan. 6, 1953

R. B. BOURNE

2,624,418

MUFFLER WITH PLURAL PASSAGES

Filed Aug. 1, 1951




Fig. 1

Fig. 2

Fig. 3

Fig. 4

Fig. 5

Fig. 6

Fig. 7

Fig. 8

Fig. 9

Fig. 10

Fig. 11

Fig. 12

Fig. 13

Fig. 14

Fig. 15

Fig. 16

Fig. 17

Fig. 18

Fig. 19

Fig. 20

Fig. 21

Fig. 22

Fig. 23

Fig. 24

Fig. 25

Fig. 26

Fig. 27

Fig. 28

Fig. 29

Fig. 30

Fig. 31

Fig. 32

Fig. 33

Fig. 34

Fig. 35

Fig. 36

Fig. 37

Fig. 38

Fig. 39

Fig. 40

Fig. 41

Fig. 42

Fig. 43

Fig. 44

Fig. 45

Fig. 46

Fig. 47

Fig. 48

Fig. 49

Fig. 50

Fig. 51

Fig. 52

Fig. 53

Fig. 54

Fig. 55

Fig. 56

Fig. 57

Fig. 58

Fig. 59

Fig. 60

Fig. 61

Fig. 62

Fig. 63

Fig. 64

Fig. 65

Fig. 66

Fig. 67

Fig. 68

Fig. 69

Fig. 70

Fig. 71

Fig. 72

Fig. 73

Fig. 74

Fig. 75

Fig. 76

Fig. 77

Fig. 78

Fig. 79

Fig. 80

Fig. 81

Fig. 82

Fig. 83

Fig. 84

Fig. 85

Fig. 86

Fig. 87

Fig. 88

Fig. 89

Fig. 90

Fig. 91

Fig. 92

Fig. 93

Fig. 94

Fig. 95

Fig. 96

Fig. 97

Fig. 98

Fig. 99

Fig. 100

Fig. 101

Fig. 102

Fig. 103

Fig. 104

Fig. 105

Fig. 106

Fig. 107

Fig. 108

Fig. 109

Fig. 110

Fig. 111

Fig. 112

Fig. 113

Fig. 114

Fig. 115

Fig. 116

Fig. 117

Fig. 118

Fig. 119

Fig. 120

Fig. 121

Fig. 122

Fig. 123

Fig. 124

Fig. 125

Fig. 126

Fig. 127

Fig. 128

Fig. 129

Fig. 130

Fig. 131

Fig. 132

Fig. 133

Fig. 134

Fig. 135

Fig. 136

Fig. 137

Fig. 138

Fig. 139

Fig. 140

Fig. 141

Fig. 142

Fig. 143

Fig. 144

Fig. 145

Fig. 146

Fig. 147

Fig. 148

Fig. 149

Fig. 150

Fig. 151

Fig. 152

Fig. 153

Fig. 154

Fig. 155

Fig. 156

Fig. 157

Fig. 158

Fig. 159

Fig. 160

Fig. 161

Fig. 162

Fig. 163

Fig. 164

Fig. 165

Fig. 166

Fig. 167

Fig. 168

Fig. 169

Fig. 170

Fig. 171

Fig. 172

Fig. 173

Fig. 174

Fig. 175

Fig. 176

Fig. 177

Fig. 178

Fig. 179

Fig. 180

Fig. 181

Fig. 182

Fig. 183

Fig. 184

Fig. 185

Fig. 186

Fig. 187

Fig. 188

Fig. 189

Fig. 190

Fig. 191

Fig. 192

Fig. 193

Fig. 194

Fig. 195

Fig. 196

Fig. 197

Fig. 198

Fig. 199

Fig. 200

Fig. 201

Fig. 202

Fig. 203

Fig. 204

Fig. 205

Fig. 206

Fig. 207

Fig. 208

Fig. 209

Fig. 210

Fig. 211

Fig. 212

Fig. 213

Fig. 214

Fig. 215

Fig. 216

Fig. 217

Fig. 218

Fig. 219

Fig. 220

Fig. 221

Fig. 222

Fig. 223

Fig. 224

Fig. 225

Fig. 226

Fig. 227

Fig. 228

Fig. 229

Fig. 230

Fig. 231

Fig. 232

Fig. 233

Fig. 234

Fig. 235

Fig. 236

Fig. 237

Fig. 238

Fig. 239

Fig. 240

Fig. 241

Fig. 242

Fig. 243

Fig. 244

Fig. 245

Fig. 246

Fig. 247

Fig. 248

Fig. 249

Fig. 250

Fig. 251

Fig. 252

Fig. 253

Fig. 254

Fig. 255

Fig. 256

Fig. 257

Fig. 258

Fig. 259

Fig. 260

Fig. 261

Fig. 262

Fig. 263

Fig. 264

Fig. 265

Fig. 266

Fig. 267

Fig. 268

Fig. 269

Fig. 270

Fig. 271

Fig. 272

Fig. 273

Fig. 274

Fig. 275

Fig. 276

Fig. 277

Fig. 278

Fig. 279

Fig. 280

Fig. 281

Fig. 282

Fig. 283

Fig. 284

Fig. 285

Fig. 286

Fig. 287

Fig. 288

Fig. 289

Fig. 290

Fig. 291

Fig. 292

Fig. 293

Fig. 294

Fig. 295

Fig. 296

Fig. 297

Fig. 298

Fig. 299

Fig. 300

Fig. 301

Fig. 302

Fig. 303

Fig. 304

Fig. 305

Fig. 306

Fig. 307

Fig. 308

Fig. 309

Fig. 310

Fig. 311

Fig. 312

Fig. 313

Fig. 314

Fig. 315

UNITED STATES PATENT OFFICE

2,624,418

MUFFLER WITH PLURAL PASSAGES

Roland B. Bourne, West Hartford, Conn., assignor
to The Maxim Silencer Company, Hartford,
Conn., a corporation of Connecticut

Application August 1, 1951, Serial No. 239,674

2 Claims. (Cl. 181-46)

1

This invention relates to silencing devices for internal combustion engines, and in particular to silencers which are mounted in confined spaces which require holding the diameter of the shell of the silencer to a minimum. One object is to produce a silencer which comprises an expansion chamber into and out of which the exhaust gas passes through two sets of tubes each located in general near the periphery of the casing, but with the open ends of the tubes in the two sets out of alignment with each other both radially and circumferentially, so that the possibility of direct transfer of gas pulses and sound waves from a tube of one set to a tube of the other set is prevented. A further object is to provide a silencer capable of withstanding high external hydraulic pressure and so constructed as to reduce greatly the transmission of sound from the silencer to the surrounding water.

The invention will now be described with reference to the accompanying drawing, in which

Fig. 1 is a median section through the silencer, taken on line 1-1 of Figs. 2 to 6 inclusive;

Fig. 2 is a section on line 2-2 of Fig. 1;

Fig. 3 is a section on line 3-3 of Fig. 1;

Fig. 4 is a section on line 4-4 of Fig. 1;

Fig. 5 is a section on line 5-5 of Fig. 1; and

Fig. 6 is a section on line 6-6 of Fig. 1.

The silencer is enclosed primarily in a cylindrical pressure shell 10, preferably of circular cross-section and formed of stainless steel about one inch thick so that it will withstand a pressure of 700 p. s. i. g. Within the pressure shell are cylindrical laminations of sheet metal 11 and 12, here shown as two in number, but which may be varied in number in different chambers of the silencer if desired. These laminations are not relied on so much for strength as for deadening sound transmission through the outer shell, and in combination with a pressure shell which is relatively massive prove remarkably and unexpectedly efficient in that regard. An inlet conduit 13 passes through one end of the pressure shell into a chamber 14 defined by the shell and an intermediate transverse partition 15. The inlet conduit terminates with an open end at approximately the midpoint of the chamber 14. An outlet conduit 16 enters the other end of the pressure shell and terminates with an open end within and about halfway along a chamber 17 defined by the pressure shell and a second intermediate transverse partition 18. The inlet and outlet conduits preferably have antiresonance slots 19 and 20 respectively.

A plurality of intermediate tubes 21, preferably

2

having their entrance ends flared as at 22, are circumferentially spaced as best shown in Fig. 3 and extend from a point in chamber 14 adjacent the terminus of the inlet conduit through the partition 15 and open into the chamber 23 formed between partitions 15 and 18. A second circular series of tubes 24 pass through the partition 18, and have open ends in both chamber 23 and chamber 17, terminating in the latter adjacent the entrance end of the outlet conduit. The entrance ends of the tubes 24 are preferably flared at 25 and that of the outlet conduit flared at 26.

It will be noted that the series of tubes 21 are located radially outwardly of the inlet conduit so that there can be no direct gas or sound passage from one to the other, and that a similar relationship exists between tubes 24 and the outlet conduit 16. Tubes 21 and tubes 24 are both arranged in sets adjacent the shell of the silencer, and in order to prevent direct transmission the ends of tubes 21 are bent inwardly towards the center of the chamber 23 as is shown in Figs. 1 and 4. The two sets of tubes 21 and 24 are preferably provided with anti-resonance holes 27 as described in my Patent 2,297,046, September 29, 1942.

What I claim is:

1. A silencer having a substantially cylindrical shell, a pair of spaced partitions dividing the interior of the shell into three chambers, an inlet conduit leading into the first chamber and terminating with an open end near the center thereof, a circumferentially spaced series of tubes located radially outwardly of the inlet conduit each having open ends one substantially in the plane of the open end of the inlet conduit and the other near the center of the second chamber, said tubes passing through the first partition into the second chamber and slanting radially inwardly towards the axis thereof, a second circumferentially spaced series of tubes circumferentially staggered with relation to the tubes of the first series, said second series of tubes extending substantially straight through the second partition into the second and third chambers and having open ends at substantially the mid-points of said chambers, and an outlet conduit entering the third chamber through the shell and terminating with an open end substantially in the plane of the open ends of the second series of tubes but located radially inwardly thereof.

2. A silencer having a substantially cylindrical shell, a pair of transverse partitions dividing the interior of the shell into three chambers, a pair of conduits coaxial with the shell and entering

3

each end chamber respectively with an open end at a point intermediate its length, two series of circumferentially spaced tubes located adjacent the peripheries of said end chambers and staggered circumferentially with respect to each other, the tubes in each series terminating at substantially the midpoint of the middle chamber with open ends, the tubes of one series being bent inwardly at one end to open into the middle chamber closer to the axis of the cylindrical shell than the tubes in the other series.

ROLAND B. BOURNE.

4

REFERENCES CITED

The following references are of record in the file of this patent:

UNITED STATES PATENTS

Number	Name	Date
2,265,342	Bourne	Dec. 9, 1941

FOREIGN PATENTS

Number	Country	Date
139,369	Great Britain	Mar. 4, 1920
882,317	France	May 31, 1943
124,755	Australia	Jan. 27, 1944