


[72] Inventor **Alexandru Vas**
Timisoara, Romania
 [21] Appl. No. **721,843**
 [22] Filed **Apr. 16, 1968**
 [45] Patented **July 20, 1971**
 [73] Assignee **Ministerul Industrii Constructiilor De**
Masini Calea Victoriei
Bucharest, Romania
 [32] Priority **Apr. 17, 1967**
 [33] **Romania**
 [31] **53571**


[56] **References Cited**
UNITED STATES PATENTS
 2,941,063 6/1960 Ducati et al. 219/75
 3,048,736 8/1962 Emmerich..... 313/161
 3,360,682 12/1967 Moore..... 313/161 X
FOREIGN PATENTS
 1,175,374 8/1964 Germany..... 219/123
Primary Examiner—Raymond F. Hossfeld
Attorney—Karl F. Ross

[54] **PLASMA GENERATOR WITH MAGNETIC FOCUSING AND WITH ADDITIONAL ADMISSION OF GAS**
3 Claims, 6 Drawing Figs.

[52] U.S. Cl..... 315/111,
 219/75, 219/121 P, 219/123, 313/161
 [51] Int. Cl..... H05b 31/28
 [50] Field of Search..... 219/74, 75,
 121, 123; 315/111; 313/161

ABSTRACT: This invention relates to a plasma arc generator, operating with a DC or AC supply and having improved characteristics by virtue of arrangements for rotating the arc and the injected gas, which may be air or nitrogen for example. The plasma arc generator, is suitable for cutting, welding, built-up welding, (i.e. welding, in which a deposit of metals is built-up), metallizing and promoting chemical reactions.





ALEXANDRU VAS
INVENTOR.

PLASMA GENERATOR WITH MAGNETIC FOCUSING AND WITH ADDITIONAL ADMISSION OF GAS

Numerous types of plasma arc generators are known and utilized for cutting, buildup welding or metallizing, with or without a transferred arc. These generators, if utilized in systems with a transferred arc, present the disadvantage that they require the use of gas mixtures without oxygen or, in order to protect the cathode, the simultaneous utilization of an inert shielding gas, e.g. argon. For this reason the known methods for cutting or buildup welding or metallization have a reduced economical efficiency and due to the reduced concentration of the plasma arc, especially if utilized for the cutting of metals, they need a high consumption of electrical energy, and their efficiency and productivity is low.

There are also known plasma arc generators with magnetic focusing, the magnetic field being generated by coils placed on the body of the generator over the combustion chamber or at the output end of the nozzle.

These types of plasma generators have the disadvantage that, because of the high dispersion of the magnetic flux and of the lack of field concentrators, their focusing efficiency is low, or the disadvantage that due to the position of the coil at the output end of the nozzle, protection of the electrode is not realized.

There are further known plasma generators fed with single-phase alternating-current, these generators having the disadvantage of the instability of the arc, thereby requiring in the arc circuit, a high frequency oscillator with high-voltage pulses. These generators load the distribution net work asymmetrically and cannot be utilized in systems with a transferred arc.

Known three-phase plasma arc generators need two or three electrodes, and for this reason the gas utilized must not contain oxygen and the thermal plasma obtained has a low degree of ionization. It must also be mentioned that the efficiency of such an installation, as used especially for promoting chemical reactions, is relatively low. As the electrodes are placed on different axes, which cannot coincide with the axis of the nozzle, this nozzle can have only a limited contraction; thus the degree of concentration of the thermal plasma produced in this way is also reduced.

Such generators cannot be satisfactorily utilized for welding, buildup welding or metallization, being suited only for special chemical reactions and they are characterized by a low efficiency and a rapid consumption of the electrodes.

The present invention enables all these disadvantages to be avoided or reduced.

According to the present invention there is provided a plasma arc generator comprising a nozzle, means for feeding gas through the nozzle and also through a peripheral passage around the nozzle, current supply means for establishing an arc between the nozzle and an electrode within the nozzle, the current supply means including a coil which carries the whole of the nozzle current and embraces a ferromagnetic core surrounding the nozzle, and a second coil embracing a second ferromagnetic core for creating a low-pressure zone at the said electrode to protect the same.

The two coils cause simultaneous rotation of the plasma arc inside as well as outside the nozzle and the introduction of air and other gases through the nozzle as well as outside the nozzle can be effected as to impart rotary motion to the gases. The relative senses of rotation can be so chosen as to increase the enthalpy and increase or reduce the consumption of energy, as appropriate for each application. Since air, instead of other gases, can be used in the case of cutting the economic efficiency is increased also.

The generator can readily be modified for AC use with a single electrode by using two mutually insulated nozzles, both coaxial with the jet axis. The phases of a three-phase supply arc connected to the electrode and two nozzles respectively. This permits gas mixture containing oxygen to be used without causing consumption of the electrode. Due to the rotation of

the arc and to the direct injection of additional turbulent gas in the arc zone after the first nozzle, the efficiency of the generator is very high.

The invention will be described in more detail, by way of example, with reference to the accompanying drawings, in which:

FIG. 1 is a sectional view of a plasma arc generator embodying the invention, for direct-current operation;

FIG. 2 is a fragmentary lateral view taken in the direction of an arrow II in FIG. 1;

FIGS. 3 to 5 are sections taken on lines III-III, IV-IV and V-V respectively in FIG. 1; and

FIG. 6 illustrates the principles as applied to three-phase AC operation, of the generator shown in FIG. 1.

In the following will be described the functioning of the generator embodying the invention, in the case of cutting.

The generator of FIG. 1 generates an electric arc between a tungsten electrode 1 and a nozzle 2, electrically isolated by a ceramic insulator 3 and a textolite insulator 4. The air Q_p (or other gaseous mixture) is introduced through a pipe connector 5 into an equalization chamber 6. Helical channels 6a provided around an electrode holder 7a, cause the gas to execute a turbulent motion, with a speed increasing as the electrode holder 7b tapers downwardly within a correspondingly tapered passage through the insulator 4. The maximum speed is reached at the lower end, in the zone between the ceramic insulator 3 and the cone of the electrode holder 7b. An adiabatic expansion then takes place in the zone of the nozzle 2. Due to the rotation of the air Q_p and especially to that of the electric arc, caused by a magnetic field generated by a coil 8 and concentrated by a core 9, upon which is superposed a second field generated by a coil 10 and a core 11, a low-pressure zone is produced around the electrode, which protects the electrode from oxidation.

In the case of cutting of metals, the sense of rotation created electromagnetically by the two coils 8 and 10 is identical with the sense of rotation of the gas Q_p .

The rotation of the plasma jet caused by the intense magnetic field generated in the outside zone of the nozzle 2 by the coil 10, through which passes the entire current of the nozzle 2 create a low-pressure zone outside the nozzle 2, too.

In this low-pressure zone, a jet of air Q_s+Q_E or of other gaseous mixture is injected through a pipe connection 12 (methane gas, hydrogen etc.), this jet having also a turbulent character, due to the action of helical channels a, provided round the nozzle 2, in the zone between the nozzle and a copper ring 13 shrouding the end of the nozzle. The superposition of the effects due to the intense magnetic field in the burning zone, generated by the coil 10 and concentrated by the core 11 and also due to the turbulent jet of air (or gas) Q_s+Q_E , causes a pronounced concentration of the electric arc between the electrode 1 and a metal workpieces P. In the case of welding the rotation of the arc caused by the coil 10 is in the opposite sense to the rotation of the gas Q_s+Q_E outside the nozzle imparted by the channels a.

The high rotation speed of the electric arc and of the plasma jet outside the nozzle 2 which causes the displacement also of the unionized particles of gas, in the entire zone of the electrical discharge, increases the vacuum surrounding the electrode 1, which prevents its consumption in the presence of oxygen, contained by the gas Q_p .

Due to the electromagnetic forces, generated by the coil 10 at the lower part of the generator and to the mechanical forces generated by the turbulent motion of the jet of air, Q_s+Q_E issuing through the passages a, the electric arc rotates outside the nozzle too (the direction of the arc rotation being the same as that of the gas Q_s+Q_E in the case of the cutting of metals) maintaining its position on the geometrical axis or axis of the generator.

When the generator is used for cutting, all rotations are made in the same sense both inside and outside the nozzle. Then the kinetic energy of the particles from the peripheral zone of the arc reaches a very high value which blows the mol-

rotation, inside and outside the nozzle, in a sense contrary to the rotation of the gas.

As a consequence of the rotation of the arc and of the gas and because of the vacuum caused around the cathode resulting from the partial direct evacuation of a quantity of the gas, at the level of the electrode without the evacuate gas trans-
versing the nozzle and as a consequence of the recycling of this gas which is reintroduced into the channels *a* around the nozzle 2, the generator can work in the case of cutting, with air or with gas mixture, with a high content of oxygen, without utilizing inert gases for the protection of the cathode.

2. As the electrode is also cooled by a part of the gas Q_p and by the simultaneous creation of a low pressure in the zone of the cathode and as the reutilization of the same gas in the zone outside the nozzle causes cooling around the nozzle, the quantity of cooling water may be dispensed with.

3. The introduction in a zone outside the nozzle of some gas mixtures, in whatever proportion, for increasing the enthalpy of the plasma arc, or for intensifying the restitution of the stored energy into the cutting zone, contributes not only to the increasing of the efficiency but it intensifies to a high degree the penetration in the metal to be worked and in the case of utilizing the plasma arc for the cutting of plates it may be utilized for plates of a higher thickness.

4. The introduction of gas mixtures Q_s+Q_E in a zone outside the nozzle and the electromagnetic rotation of the arc, in this zone, caused by the series coil, determines a low-pressure and an intense local cooling of the nozzle, thus permitting a very high concentration of the arc.

5. In a system with a transferred arc, the utilization of a series coil prevents entirely the possibility of the formation of a secondary arc between nozzle and workpiece.

For this reason, the space between the nozzle 2 (FIG. 1) and

the workpiece P can be very much reduced so that a considerable increase of the efficiency and safety in utilization is obtained.

6. The generator can be utilized with alternating single-, two- or three-phase current.

I claim:

1. A plasma arc generator comprising a nozzle (2) forming a frustoconical nozzle chamber converging in the direction of a nozzle mouth from which a plasma emerges; means (6a) for feeding an ionizable gas (Q_p) into said chamber and along the exterior of said nozzle and therearound; and electrode (1) extending into said chamber; current supply means connected across said nozzle and said electrode for striking an arc within said chamber; and an electromagnetic coil (10) surrounding said nozzle and connected in series with said current supply means, said electrode and said nozzle for traverse by the entire current of said arc, and a ferromagnetic core (11) surrounding said nozzle and cooperating with said coil for generating a magnetic field causing the plasma issuing from said nozzle to rotate about the axis thereof; and a second electromagnetic coil (8) and a second ferromagnetic core (9) coaxial with said nozzle, said coils and said cores generating within said chamber a low-pressure zone around said electrode.

2. The plasma arc generator defined in claim 1, further comprising means for evacuating a portion of the gas from said chamber immediately around said electrode, and helical channels (b) formed in the space between said electrode and the body of said nozzle communicating with the last mentioned means, and a sleeve surrounding said electrode and communicating with said chamber and channels.

3. The plasma arc generator defined in claim 2 wherein the last-mentioned means includes an ejector.

35

40

45

50

55

60

65

70

75

United States Patent

[11] 3,596,045

[72] Inventors **Karl-Heinz Steigerwald
Lochham;
Dieter Konig, Munich; Joachim Geissler,
Vaterstetten, all of, Germany**

[21] Appl. No. **536,617**

[22] Filed **Mar. 23, 1966**

[45] Patented **July 27, 1971**

[73] Assignee **K. H. Steigerwald GmbH**

[32] Priority **Mar. 30, 1965**

[33] **Germany**

[31] **St 23 592**

[56] **References Cited**

UNITED STATES PATENTS

2,622,053	12/1952	Clowe et al.	219/347 UX
3,147,366	9/1964	Dreyfoos.....	219/338 X
3,410,979	11/1968	Larsson.....	219/68
3,293,652	12/1966	Roshon et al.	219/121 L UX

OTHER REFERENCES

Title page (p. 66) IEEE Spectrum July 1964, copy in Group 213, class 219-121 Laser (copies made in Group 213)

Primary Examiner—R. F. Staubly
Attorney—Sandoe, Hopgood and Calimafde

[54] **MACHINING PROCESS USING RADIANT ENERGY**
6 Claims, No Drawings

[52] U.S. Cl..... **219/121 EB,**
219/121 L, 219/347

[51] Int. Cl..... **B23k 15/00,**
B23k 27/00

[50] Field of Search..... **219/121 L,**
121 EB, 69 R, 68, 70, 347—349, 338

ABSTRACT: A process using a beam of radiant energy, such as electron beams and laser beams, for removing material from a workpiece wherein the workpiece is made of a material which has a low degree of energy absorption for the kind of radiant energy used consists in finely distributing an auxiliary material having a high beam absorbing characteristic within the workpiece material in at least the portion thereof from which material by absorbing heat builds up vapor pressure which carries the adjacent molten material out of the work zone.