Greenwald

Sept. 6, 1977 [45]

[54]	SUBSTITU	NYL SILVER HALIDE SOLVENTS JTED WITH PIPERAZINE AT ONE L GROUP	[58] Field	d of Searc 96/6	h	09;
[75]	Inventor:	Richard B. Greenwald, Cambridge,	[56]	I	References Cited	
		Mass.		U.S. PA	TENT DOCUMENTS	
[73]	Assignee:	Polaroid Corporation, Cambridge, Mass.	3,169,992 3,769,014 3,976,647	2/1965 10/1973 8/1976	Henn	R
[21]	Appl. No.:	706,462	•	-	David Klein	K
[22]	Filed:	July 19, 1976	Assistant E.	xaminer-	-Richard L. Schilling "irm—Sybil A. Campbell	
	Relat	ted U.S. Application Data	[57]		ABSTRACT	
[63]			Alkanes containing an intralinear sulfonyl group and an intralinear 1-piperazinylsulfonamido group separated			b
[51]	, and a second of the contract		by a single carbon substituted with at least one hydrogen atom are employed as silver halide solvents in pho-			
[52]	U.S. Cl	G03C 1/48; G03C 1/40 96/29 R; 96/61 R;	tographic p	rocesses a	and compositions.	
		96/61 M; 96/76 R; 96/76 C; 96/77		49 Cl	aims, No Drawings	

DISULFONYL SILVER HALIDE SOLVENTS SUBSTITUTED WITH PIPERAZINE AT ONE SULFONYL GROUP

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation-in-part of my copending application Ser. No. 564,167 filed Apr. 1, 1975, now abandoned.

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates to photography and, in particular, it is concerned with a new class of silver halide 15 solvents and with photographic products, processes and compositions employing the same.

2. Description of the Prior Art

Photographic processing composition capable of forming water-soluble complex silver salts are known to 20 be useful in many types of silver halide photography. To obtain a relatively stable image in an exposed and developed photosensitive silver halide emulsion, the silver halide remaining in the unexposed and undeveloped areas of the emulsion should be converted to a 25 soluble silver complex that can be removed by washing or converted to a stable silver complex that will not "print-out" upon prolonged exposure to light. In conventional or "tray" development, it is customary to fix the developed silver halide emulsion by applying a 30 solution of silver halide solvent, i.e., silver halide complexing agent which forms a water-soluble silver complex with the residual silver halide. The water-soluble silver comlex thus formed and excess silver halide solvent are then removed from the developed and fixed 35 emulsion by washing with water.

Silver halide solvents also have been employed in monobaths where a single processing compositions containing a silver halide developing agent in addition to the silver halide solvent is utilized for both develop- 40 ing and fixing an exposed photosensitive silver halide layer. Silver halide solvents also have been employed in diffusion transfer photographic processes. Such processes are now well known in the art; see for example, U.S. Pats. Nos. 2,543,181; 2,647,056; 2,983,606; etc. In 45 processes of this type, an exposed silver halide emulsion is treated with a processing composition whereby the exposed silver halide emulsion is developed and an imagewise distribution of diffusible image-forming components is formed in the unexposed and undeveloped 50 portions of the silver halide emulsion. This distribution of image-forming components is transferred by imbibition to an image-receiving stratum in superposed relationship with the silver halide emulsion to provide the desired transfer image. In diffusion transfer processes 55 where a silver transfer image is formed, processing is effected in the presence of a silver halide solvent which forms a diffusible complex with the undeveloped silver halide. The soluble silver complex thus formed diffuses to the superposed image-receiving layer where the 60 transferred silver ions are deposited as metallic silver to provide the silver transfer image. In preparing silver prints in this manner, the image-receiving element preferably includes a silver precipitating agent, for example, heavy metal sulfides and selenides as described in U.S. 65 Pat. No. 2,698,237 of Edwin H. Land.

Various compounds have been employed as silver halide solvents in the photographic processes described

above. One of the most commonly employed is sodium thiosulfate. Other silver halide solvents that have been used include thiocyanates, such as potassium and sodium thiocyanate; and cyclic imides, such as barbituric acid and uracil. U.S. Pat. No. 3,769,014 disclosed still another class of silver halide solvents, namely, 1,1-bis-sulfonyl alkanes.

The present invention is concerned with a new class of silver halide solvents comprising alkanes that contain both a sulfonyl group and a tertiary sulfonamido group.

SUMMARY OF THE INVENTION

It is, therefore, the primary object of the present invention to provide photographic products, processes and compositions employing a new class of silver halide solvents.

Other objects of this invention will in part be obvious and will in part appear hereinafter.

The invention accordingly comprises and processes involving the several steps and the relation and order of one or more of such steps with respect to each of the others, and the products and compositions possessing the features, properties and the relation of elements which are exemplified in the following detailed disclosure, and the scope of the application of which will be indicated in the claims.

For a fuller understanding of the nature and objects of the invention, reference should be had to the following detailed description.

DETAILED DESCRIPTION OF THE INVENTION

According to the present invention, it has now been found that open-chain alkanes containing (a) an intralinear sulfonyl group and (b) an intralinear 1-piperazinyl sulfonamido group wherein said groups are separated by a single carbon, substituted with at least one hydrogen atom are useful for complexing silver ion, i.e., undeveloped silver halide in photographic processes. Compounds of this type found particularly useful in both conventional and diffusion transfer photography are those represented by the following formula:

$$R^{2}$$

$$| R^{2} - SO_{2} - CH - SO_{2}X$$
(I)

wherein R¹ is lower alkyl; R² is hydrogen, lower alkyl or $+CH_2$ $+CH_2$ $+CH_3$ $+CH_3$ +

$$-N$$
 $N-R^3$ or $-N$
 $+N$
 R^4
 R^5 .A

wherein A is a halide or sulfonate, R³ is hydrogen or lower alkyl and R⁴ and R⁵ each are lower alkyl. As used herein, the term "lower alkyl" is intended to mean alkyl groups containing one or four carbon atoms, for example, methyl, ethyl, propyl, isopropyl, s-butyl and n-butyl, which groups may be unsubstituted or substituted preferably in the omega position with, for example, —OH and —COOR wherein R is H or alkyl having 1 to 4 carbon atoms.

(II) 5

(4)

(5)

(6)

(7)

45

Typical of the compounds containing -OH and -COOR substituents are those represented by the following formula:

$$R^{1}-SO_{2}-CH-SO_{2}-X$$

wherein R^1 is alkyl having 1 to 4 carbon atoms; R^2 is 10 hydrogen, alkyl having 1 to 4 carbon atoms or $-(CH_2)_m$ $S-(CH_2)_m$ Y wherein m is a whole number 2 to 5, n is a whole number 1 to 4 and Y is hydrogen, —OH or —COOR wherein R is hydrogen or alkyl having 1 to 4 carbon atoms; and X is

$$-N N-R^3 \quad \text{or} \quad -N + N < R^4 \quad A$$

wherein A is a halide or sulfonate, R^3 is hydrogen or $+CH_{\frac{1}{2}n}Y$ wherein n and Y have the same meaning given above, R^4 is $+CH_{\frac{1}{2}n}Y$ wherein n and Y have the same meaning given above and R^5 is alkyl having 1 to 4 25 carbon atoms.

Specific examples of compounds useful as silver halide solvents in accordance with the present invention are those set out in the following formulas:

$$CH_{3}SO_{2}CHSO_{2}N NCH_{2}CH_{3}$$

$$(CH_{2})_{2}S(CH_{2})_{2}OH .$$

$$(2) 35$$

$$CH_3$$

$$CH_3SO_2CHSO_2N + N-(CH_3)_2 .FSO_3$$

$$CH_1CH_2SO_2CH_2SO_2N + N-(CH_3)_2 .FSO_3$$

$$CH_3SO_2CH_2SO_2N + N-(CH_3)_2 .FSO_3$$

$$CH_3SO_2CHSO_2N + N < CH_2COOC_2H_5$$

$$(CH_2)_2SCH_3$$

$$(14)$$

$$CH_3$$

$$CH_3COOC_2H_5$$

$$CH_{3}SO_{2}CHSO_{2}N \longrightarrow N-CH_{3}$$

$$(CH_{2})_{2}SCH_{3}$$
(15)

(8) 60
$$CH_1SO_2CH_2SO_2N N-CH_2COOC_2H_5$$

5

The silver halide solvents of the present invention are per se novel compounds and comprise the subject matter of copending U.S. Pat. application Ser. No. 681,583 of Richard B. Greenwald filed Apr. 29, 1976, now U.S. Pat. No. 4,009,167 which is a continuation-in-part of application Ser. No. 564,166 filed Apr. 1, 1975, now U.S. Pat. No. 3,976,647. For convenience, the specification of said applications are specifically incorporated herein.

In preparing the non-quaternized compounds, the 10 non-S-substituted compounds may be synthesized, for example, by reacting a sulfene with the selected piperazine in accordance with the procedure described by G. Opitz et al., Angew. Chem. internat. Edit., Vol. 5 (1966), p. 594-5. The compounds substituted with the 15—S-containing moiety may be prepared, for example, by reacting the non-S-substituted sulfonyl-sulfonamido alkanes with the chloro-substituted derivative of the selected R² substituent, i.e., R⁰—S—(CH₂)_m—Cl. The quaternized compounds may be synthesized by reacting 20 the non-S-substituted or the S-substituted compounds usually as a tertiary amine, i.e., R³ is other than hydrogen, with an alkyl halide or sulfonate.

As an example, the compound of the formula

was prepared as follows:

A. A solution of triethylamine (31 g., 300 mmoles) in 200 mls of acetonitrile was chilled in dry ice/alcohol to about -50° C. Methanesulfonylchloride (23 g., 200 mmoles) was added dropwise to the cooled solution over 10 minutes with stirring. Stirring was continued 35 for 20 minutes, and N-methylpiperazine (10 g., 100 mmoles) was added over 10 minutes. The reaction mixture was allowed to stand for about 2 days at room temperature and then stripped on a rotovac. The residue was triturated with water and the title compound 40 collected (15.3 g., melting range 195°-198° C.)

The above compound was substituted with an S-containing moiety to give the compound:

B. The compound of Step (A) (5 g., 19.4 mmoles) was dissolved in N,N-dimethylformamide by heating to 60° C. Sodium hydride (57% by weight dispersion in oil; 1 g.) was added to the solution and the mixture heated at about 70° C. for 1.25 hours. The chloride, 55 $Cl-(CH_2)_2S(CH_2)_2CO_2C_2H_5$ (4.6 g., 23.3 mmoles) was then added over 15 minutes and the reaction mixture heated to 100° C. Heating at about 85° C. was continued overnight and then the reaction mixture was heated at 105° C. for about 2 hours. After cooling, the mixture 60 was poured onto ice, and the filtrate decanted from a tacky gray solid. The remaining filtrate was stripped on a rotovac and the residue taken up in 50 mls. ethanol. A white solid (1.2 g.) was collected by filtration and the filtrate stripped to give a sticky white solid (4.8 g.) 65 which was triturated briefly with ether. The title compound was separated from the white solid by chromatography using about 100 g. of silica gel which was

6

eluted with chloroform, 2% methanol and 5% methanol in 200 ml fractions. Fraction 6 contained about 1.4 g. of the title compound, essentially homogeneous by NMR (> 95% purity, melting range 124°-126° C.)

The compound of step (B) was converted to the corresponding carboxy-substituted compound

as follows:

C. The compound of Step (B) (1.2 g., 2.9 mmoles) was dissolved in 25 mls. of 6N hydrochloric acid and heated at reflux for 2.5 hours. The solution was allowed to stand overnight at room temperature and then stripped on a rotovac yielding the title compound as a white powder (1.1 g., melting point about 100° C.)

The compound prepared in Step (A) was quaternized as follows to give the compound of the formula

CH₁SO₂CH₂SO₂N
$$N-(CH_3)_2$$
. FSO₃:

D. The compound of Step (A) (1.25 g., 4.9 mmoles) was dissolved in 25 mls of acetonitrile by warming and the solution allowed to cool to room temperature. Methylfluorosulfonate (0.56 g., 4.9 mmoles) was added to the cooled solution and the reaction mixture was warmed briefly. A white solid separated, and after about 15 minutes when the reaction mixture had cooled to room temperature, the white solid was collected to give 1.4 g. of the title compound.

In formulating photographic processing compositions utilizing the above-described compounds, the above-described compounds may be used singly or in admixture with each other. The total amount employed may vary widely depending upon the particular photographic system and should be used, for example, in a quantity sufficient for fixing a developed negative in conventional tray processing or in a quantity sufficient to give a satisfactory transfer print in diffusion transfer processes under the particular processing conditions employed.

Though the silver halide solvents of the present in-50 vention are broadly useful in a variety of photographic processes of the type in which water-soluble silver complexes are formed from the unreduced silver halide of a photoexposed and at least partially developed silver halide stratum, they find particular utility in diffusion transfer processes. A composition embodying the present invention specifically suitable for use in the production of transfer images comprises, in addition to the silver halide complexing agents of the above-described type, a suitable silver halide developing agent, preferably an organic developing agent. Examples of developing agents that may be employed include hydroquinone and substituted hydroquinones, such as tertiary butyl hydroquinone, 2,5-dimethyl hydroquinone, methoxyhydroquinone, ethoxyhydroquinone, chlorohydroquinone; pyrogallol and catechols, such as catechol, 4-phenyl catechol and tertiary butyl catechol; aminophenols, such as 2,4,6-triamino-orthocresol; 1,4-diaminobenzenes, such as p-phenylenediamine, 1,2,4-triaminoben7

zene and 4-amino-2-methyl-N,N-diethylaniline; ascorbic acid and its derivatives, such as ascorbic acid, iso-ascorbic acid and 5,6-isopropylidene ascorbic acid and other enediols, such as tetramethyl reductic acid; and hydroxylamines, such as N,N-di-(2-ethoxyethyl)hydroxylamine and N,N-di-(2-methoxyethoxyethyl)hydroxylamine.

In diffusion transfer processes, the processing composition, if it is to be applied to the emulsion by being spread thereon in a thin layer, also usually includes a 10 viscosity-imparting reagent. The processing composition may comprise, for example, one or more silver halide solvents of the present invention; one or more conventional developing agents such as those enumerated above; an alkali, such as sodium hydroxide or potassium hydroxide; and a viscosity-imparting reagent, such as a high molecular weight polymer, e.g., sodium carboxymethyl cellulose or hydroxyethyl cellulose.

In one such transfer process, the processing solution is applied in a uniformly thin layer between the super- 20 posed surfaces of a photoexposed photosensitive element and an image-receiving element, for example, by advancing the elements between a pair of pressureapplying rollers. The elements are maintained in superposed relation for a predetermined period, preferably 25 for a duration of 15 to 120 seconds, during which exposed silver halide is reduced to silver and unreduced silver halide forms a water-soluble, complex salt which diffuses through the layer of solution to the imagereceiving element, there to be reduced to an argental 30 image. At the end of this period, the silver halide element is separated from the image-receiving element. Materials useful in such a transfer process are described in U.S. Pat. No. 2,543,181, issued in the name of Edwin H. Land on Feb. 27, 1951, and in numerous other pa- 35 tents.

The photosensitive element may be any of those conventionally used in silver diffusion transfer processes and generally comprises a silver halide emulsion carried on a base, e.g., glass, paper or plastic film. The silver 40 halide may be a silver chloride, iodide, bromide, iodobromide, chlorobromide, etc. The binder for the halide, though usually gelatin, may be a suitable polymer such as polyvinyl alcohol, polyvinyl pyrrolidone and their copolymers.

The image-receiving element preferably includes certain materials, the presence of which, during the transfer process has a desirable effect on the amount and character of silver precipitated on the image-receiving element. Materials of this type are specifically described in U.S. Pats. Nos. 2,690,237 and 2,698,245, both issued in the name of Edwin H. Land on Dec. 28, 1954 and U.S. Pat. No. 3,671,241 of Edwin H. Land issued on June 20, 1972.

Separating of the silver halide element from the image-receiving element may be controlled so that the layer of processing composition is removed from the image-receiving element or the layer of processing composition is caused to remain in contact with the image-receiving element, e.g., to provide it with a protective coating. Techniques which enable such results to be accomplished as desired are described in U.S. Pat. No. 2,647,054 issued to Edwin H. Land on July 28, 1953. In general, the processing reagents are selected so that traces remaining after the solidified processing 65 layer has been separated from the silver image or which remain in said layer adhered as a protective coating on the silver image, as indicated above, are colorless or

pale, so as not be appreciably affect the appearance of the image and to have little or no tendency to adversely react with the silver image.

The silver halide solvents of the present invention also may be employed in diffusion transfer processes adapted to provide positive silver transfer images which may be viewed as positive transparencies without being separated from the developed negative silver image including such processes adapted for use in forming additive color projection positive images. Diffusion transfer processes of this type are described in U.S. Pat. No. 3,536,488 of Edwin H. Land and U.S. Pat. No. 3,615,428 of Lucretia J. Weed and in U.S. Pat. application Ser. No. 383,196 of Edwin H. Land filed July 27, 1973, now U.S. Pat. No. 3,894,871. The subject compounds also find utility as silver halide solvents in diffusion transfer processes utilizing the properties of the imagewise distribution of silver ions in the soluble silver complex made available in the undeveloped and partially developed areas of a silver halide emulsion to liberate a reagent, e.g., a dye in an imagewise fashion, as described in U.S. Pat. No. 3,719,489 of Ronald F. W. Cieciuch, Robert R. Luhowy, Frank A. Meneghini and Howard G. Rogers.

To illustrate the utility of the above-defined compounds as photographic silver halide solvents, a photosensitive silver halide emulsion on a support was exposed to a step wedge and processed by spreading a layer of processing composition approximately 1.2 mils. thick between the exposed emulsion and a superposed image-receiving element comprising a layer of regenerated cellulose containing colloidal palladium sulfide carried on a transparent support. The processing composition was prepared by adding a silver solvent of the present invention in a concentration of 5% by weight to the following formulation:

Water	814.0 g.
Potassium hydroxide (Aqueous 50% w/w solution)	348.0 g.
Hydroxyethyl cellulose	35.0 g.
Zinc acetate Triethanolamine	15.0 g 5.6 g.
Bis-N,N-methoxyethyl	
hydroxylamine	50.0 g.

After an imbibition period of approximately 1 minute, the developed silver halide emulsion was separated from the image-receiving element, and the maximum and minimum transmission densities were measured for the positive image.

The compounds added to the base formulation as silver halide solvents, and the density measurements for the positive image obtained with each of the compounds are set forth in the following table:

TABLE

Compound	Density		
Compound (Formula No.)	Maximum	Minimum	
(9)	2.32	0.26	
(ìó)	0.98	0.30	
(11)	1.70	0.09	
(12)	1.67	0.08	

Though other open-chain alkanes containing a sulfonyl group and a t-sulfonamido group are also useful as silver halide complexing agents, the compounds of the present invention have been found to give higher maximum densities than the corresponding compound with other heterocyclic groups in place of the 1-piperazinyl group. For example, the foregoing procedure was repeated using

The density measurements for the positive image obtained, i.e., D_{max}/D_{min} were 0.55/0.7, 0.08/0.02 and 0.49/0.06, respectively.

It will be apparent that the relative proportions of the subject silver halide solvents and of the other ingredients of the processing compositions may be varied to suit the requirements of a given photographic system. Also, it is within the scope of this invention to modify the formulations set forth above by the substitution of alkalies, antifoggants and so forth other than those specifically mentioned. Where desirable, it is also contemplated to include in the processing compositions, other components as commonly used in the photographic art.

Rather than being dissolved in the aqueous alkaline 25 processing composition prior to application thereof to an exposed silver halide emulsion, it is also contemplated that the silver halide solvents of the present invention may be disposed prior to exposure in a layer or layers of the photographic film unit, e.g., by placing 30 them behind a silver halide emulsion layer in the photosensitive element. In this instance, the processing composition containing the silver halide solvent is formed by application to the photosensitive element of an aqueous alkaline solution capable of solubilizing the silver 35 halide solvent. In diffusion transfer processes, the subject silver halide solvents may be disposed in a layer or layers of the film unit but usually are contained in the processing composition.

As noted above, in diffusion transfer film units the 40 negative component comprising at least one photosensitive layer and the positive component comprising an image-receiving layer may be in separate sheet-like elements which are brought together during processing and thereafter either retained together as the final print 45 or separated following image formation.

Rather than the photosensitive layer and the image-receiving layer being in separate elements, they may be in the same element. In such a film unit, the image-receiving layer is coated on a support and the photosensitive layer is coated on the upper surface of the image-receiving layer. The liquid processing composition is applied between the combined negative-positive element and a second sheet-like element or spreading sheet which assists in spreading the liquid composition in a 55 uniform layer adjacent the surface of the photosensitive layer.

Still other film units are those where the negative and positive components together may comprise a unitary structure wherein the image-receiving layer carrying 60 the transfer image is not separated from the developed photosensitive layer(s) after processing but both components are retained together as a permanent laminate. Such film units include those for providing positive silver transfer images which may be viewed as positive 65 color transparencies, such as, those described in aforementioned U.S. Pat. No. 3,894,871. Film units of this type also include those adapted for forming a transfer

image viewable by reflected rather than by transmitted light. In addition to the aforementioned photosensitive layer(s) and image-receiving layer, such film units include means for providing a reflecting layer between the image-receiving and photosensitive layer(s) in order to mask the developed photosensitive layer(s) and to provide a white background for viewing the transfer image. This reflecting layer may comprise a preformed layer of a reflecting agent included in the film unit or the reflecting agent may be provided subsequent to photoexposure, for example, by including the reflecting agent in the processing composition. In addition to these layers, the laminate usually includes dimensionally stable outer layers or supports, at least one of which is transparent so that the resulting transfer image may be viewed by reflection against the background provided by the light-reflecting layer. Integral negative-positive film units wherein the photosensitive and image-receiving layers are retained as a permanent laminate after processing are described, for example, in U.S. Pat. No. 3,415,644 issued Dec. 10, 1968 and U.S. Pat. No. 3,647,437 issued Mar. 7, 1972, both to Edwin H. Land and in U.S. Pat. No. 3,594,165 issued July 20, 1971 to Howard G. Rogers.

It will be appreciated that in the formation of color transfer images, a dye image-providing material such as the compounds of aforementioned U.S. Pat. No. 3,719,489 may be associated with the photosensitive silver halide layer or layers of the negative component, and, usually, these and the other diffusion transfer film units described above are employed in conjunction with means, such as, a rupturable container containing the requisite processing composition and adapted upon application of pressure of applying its contents to develop the imagewise exposed film unit.

As mentioned previously, the silver halide solvents of the present invention may be initially disposed in an alkali permeable, i.e., processing composition permeable layer or layers of the film unit, for example, in the negative component in a layer other than the photosensitive silver halide layer and usually in a layer behind the photosensitive layer(s), and/or in the image-receiving component in the image-receiving layer or in another layer thereof. Usually, however, the silver halide solvent is included in the aqueous alkaline processing composition.

Since certain changes may be made in the above compositions and processes without departing from the scope of the invention herein involved, it is intended that all matter contained in the above description should be interpreted as illustrative and not in a limiting sense.

What is claimed is:

1. A photographic processing composition comprising an aqueous alkaline processing solution having dissolved therein a silver halide developing agent and as a silver halide solvent, a compound of the formula

$$R^{1}$$
 R^{1}
 CH
 SO_{2}
 CH
 SO_{2}

wherein R^1 is lower alkyl, R^2 is hydrogen, lower alkyl or $-(CH_2)_mS-R^o$ wherein R^o is lower alkyl and m is a whole number 2 to 5; and X represents the residue of a 1-piperazine.

2. A photographic processing composition as defined in claim 1 wherein said X represents

$$-N \longrightarrow N-R^3 \quad \text{or} \quad -N \longrightarrow +N \searrow_{R^5}^{R^4} \quad .A$$

wherein A is a halide or a sulfonate, R³ is hydrogen or lower alkyl and R⁴ and R⁵ each are lower alkyl.

- 3. A photographic processing composition as defined in claim 2 wherein said R² is hydrogen.
- 4. A photographic processing composition as defined in claim 2 wherein said R^2 is $-(CH_2)_mS-R^o$.
- 5. A photographic processing composition as defined 15 in claim 4 wherein m is 2.
- 6. A photographic processing composition as defined in claim 4 wherein m is 3.
- 7. A photographic processing composition as defined in claim 3 wherein said silver halide solvent is

8. A photographic processing composition as defined in claim 3 wherein said siliver halide solvent is

9. A photographic processing composition as defined ³⁵ in claim 3 wherein said silver halide solvent is

10. A photographic processing composition as defined in claim 3 wherein said silver halide solvent is

11. A photographic processing composition as defined in claim 4 wherein said silver halide solvent is

12. A photographic processing composition as de- 60 fined in claim 1 which additionally includes a viscosity-increasing reagent.

13. A photographic process for forming a water-soluble complex silver salt with the unexposed and undeveloped silver halide of an imagewise exposed and developed but unfixed photosensitive silver halide layer carried on a support which comprises treating said silver halide layer with an aqueous alkaline processing com-

position including therein as a silver halide solvent, a compound of the formula

$$R^2$$

$$R^1 - SO_2 - CH - SO_2 X$$

wherein R¹ is lower alkyl, R² is hydrogen, lower alkyl or $-(CH_2)_mS-R^o$ wherein R^o is lower alkyl and *m* is a whole number 2 to 5; and X represents the residue of a 1-piperazine.

14. A photographic process as defined in claim 13 wherein said X represents

$$-N \sum_{N=R^3 \text{ or } -N + N \le R^4} A$$

wherein A is a halide or a sulfonate, R³ is hydrogen or lower alkyl and R⁴ and R⁵ each are lower alkyl.

- 15. A photographic process as defined in claim 13 wherein R² is hydrogen.
- 16. A photographic process as defined in claim 13 wherein R^2 is $-(CH_2)_mS-R^o$.
- wherein \mathbb{R}^2 is $-(\mathbb{C}H_2)_m \mathbb{S} \mathbb{R}^o$. 17. A photographic process as defined in claim 16 wherein m is 2.
 - 18. A photographic process as defined in claim 16 wherein m is 3.
 - 19. A photographic process as defined in claim 15 wherein said silver halide solvent is

20. A photographic process as defined in claim 15 wherein said silver halide solvent is

21. A photographic process as defined in claim 15 wherein said silver halide solvent is

22. A photographic process as defined in claim 15 wherein said silver halide solvent is

23. A photographic process as defined in claim 16 wherein said silver halide solvent is

10

14

24. A diffusion transfer photographic process comprising the steps of:

- 1. reacting exposed silver halide of an imagewise exposed photosensitive silver halide emulsion layer carried on a support with a silver halide developing agent in aqueous alkaline solution;
- 2. reacting unreduced silver halide of said photosensitive emulsion with as a silver halide solvent, a compound of the formula

$$\begin{array}{c} \cdot R^{2} \\ \mid \\ R^{3}-SO_{2}-CH-SO_{2}\end{array}$$

wherein R1 is lower alkyl, R2 is hydrogen, lower alkyl or -(-CH₂)S-Rowherein Rois lower alkyl and m is a whole number 2 to 5; and X represents the residue of a 1-piperazine to form a complex silver salt that is soluble in said alkaline solution;

- 3. transferring said complex silver salt to a superposed image-receiving layer; and
- 4. reducing said transferred complex silver salt to provide a silver image.
- wherein said X represents

$$-N N-R^3 \quad \text{or} \quad -N + N < R^4 \quad A$$

wherein A is a halide or a sulfonate; R³ is hydrogen or lower alkyl and R4 and R5 each are lower alkyl.

- 26. A photographic process as defined in claim 25 35 wherein R² is hydrogen.
- 27. A photgraphic process as defined in claim 25 wherein \mathbb{R}^2 is $-(\mathbb{C}H_2)_{\overline{m}}\mathbb{S}-\mathbb{R}^{\varrho}$.
- 28. A photographic process as defined in claim 27 wherein m is 2.
- 29. A photographic process as defined in claim 27 wherein m is 3.
- 30. A photographic process as defined in claim 26 wherein said silver halide solvent is

31. A photographic process as defined in claim 26 wherein said silver halide solvent is

32. A photographic process as defined in claim 26 wherein aid silver halide solvent is

33. A photographic process as defined in claim 26 wherein said silver halide solvent is

34. A photographic process as defined in claim 27 wherein said silver halide solvent is

35. A photographic process as defined in claim 24 with additionally includes a viscosity-increasing reagent in said aqueous alkaline solution.

36. A photographic product which comprises a first sheet-like element comprising a photosensitive silver halide emulsion layer on a support; a second sheet-like element adapted to be superposed with said first sheetlike element and means for retaining an aqueous alkaline processing solution so positioned as to distribute said 25. A photographic process as defined in claim 24 25 processing solution between said first and second sheetlike elements, at least one of said elements and said processing solution containing a silver halide solvent which forms a silver complex soluble in said aqueous alkaline solution, said silver halide solvent being a com-30 pound of the formula

$$R^{2}$$

$$| R^{1}-SO_{2}-CH-SO_{2}X$$

wherein R1 is lower alkyl, R2 is hydrogen, lower alkyl or $-(CH_2)_mS-R^o$ wherein R^o is lower alkyl and m is a whole number 2 to 5; and X represents the residue of a 1-piperazine, said product including a silver halide developing agent in said processing composition.

37. A photographic product as defined in claim 36 wherein said X represents

$$-N N-R^{2} \quad \text{or} \quad -N + N < R^{4} \quad A$$

wherein A is a halide or a sulfonate, R³ is hydrogen or 50 lower alkyl and R4 and R5 each are lower alkyl.

- 38. A photographic product as fined in claim 37 wherein R² is hydrogen.
- 39. A photographic product as defined in claim 37 wherein \mathbb{R}^2 is $-(\mathbb{CH}_2)_m \mathbb{S} - \mathbb{R}$.
- 40. A photographic product as defined in claim 39 wherein m is 2.
- 41. A photographic product as defined in claim 39 wherein m is 3.
- 42. A photographic product as defined in claim 38 wherein said silver halide solvent is

43. A photographic product as defined in claim 38 wherein said silver halide solvent is

44. A photographic product as defined in claim 38 wherein said silver halide solvent is

45. A photographic product as defined in claim 38 wherein said silver halide solvent is

46. A photographic product as defined in claim 39 wherein said silver halide solvent is

47. A photographic product as defined in claim 36 wherein one of said first and second sheet-like elements additionally includes an image-receiving layer.

48. A photographic product as defined in claim 47 wherein said image-receiving layer is included in said second sheet-like element.

49. A photographic product as defined in claim 48 wherein said image-receiving layer is a dye image-receiving layer and said first sheet-like element additionally includes a photographically inert compound capable of undergoing cleavage in the presence of silver ions and/or soluble silver complex to liberate a diffusible dye.

25

30

35

40

45

SΩ

55

60