

[54] INTEGRATED AMMONIA-UREA PROCESS

[75] Inventors: Vincenzo Lagana, Milan; Francesco Saviano, Segrate, both of Italy

[73] Assignee: Snamprogetti S.p.A., Milan, Italy

[21] Appl. No.: 18,729

[22] Filed: Mar. 8, 1979

[51] Int. Cl.³ C07C 126/00

[52] U.S. Cl. 564/72

[58] Field of Search 562/555; 260/555 A; 423/359

[56] References Cited

U.S. PATENT DOCUMENTS

3,120,563	2/1964	Bongard	260/555 A
3,310,376	3/1967	Cook	260/555 A
3,674,847	7/1972	Kassenbrood	562/555
3,684,442	8/1972	Konoki	260/555 A
4,012,443	3/1977	Bonetti	260/555 A
4,013,718	3/1977	Guadalupi	260/555 A
4,138,434	2/1979	Lagana	260/555 A


Primary Examiner—Brian E. Hearn


Attorney, Agent, or Firm—Morgan, Finnegan, Pine, Foley & Lee

[57] ABSTRACT

An integrated ammonia-urea process is disclosed which uses as the starting gas mixture a stream coming, for example, from steam reforming of hydrocarbons, carbon dioxide being stripped from the stream by the action of a very concentrated ammonia solution (above 70% by wt) first and then the action of an ammoniated solution of ammonium carbonate secondly, a solution of ammonium carbamate being obtained together with a gas stream composed of nitrogen and hydrogen; sending the carbamate solution to the urea reactor, discharging from the urea reactor the urea solution containing unconverted carbamate and excess ammonia, decomposing said carbamate and sending evolved ammonia to the urea reactor again along with carbon dioxide, discharging the urea solution having now 50% of the original carbamate to an adiabatic stripper in which the stripping gas is essentially composed of hydrogen and nitrogen, removing ammonia and carbon dioxide with water from the adiabatic stripper and condensing ammonia and carbon dioxide by heat exchange, sending the stream of hydrogen and nitrogen to methanization and ammonia synthesis and concentrating the urea solution directly until obtaining a urea melt.

3 Claims, 1 Drawing Figure





INTEGRATED AMMONIA-UREA PROCESS

This invention relates to an integrated ammonia-urea process.

A number of integrated processes are known for the synthesis of urea in combination with the synthesis of ammonia.

One of these is, more particularly, the one disclosed in the U.S. Patent application Ser. No. 857,185 filed on Dec. 2, 1977, now U.S. Pat. No. 4,138,434.

The method described in the patent application aforementioned comprises the steps of feeding to a urea-synthesis reactor a stream of anhydrous ammonia and/or an aqueous solution of ammonia and a stream containing ammonium carbamate, reacting carbon dioxide with the ammonia in the urea-synthesis reactor, discharging from the urea-synthesis reactor a solution of urea which contains unconverted ammonium carbamate, thermally decomposing about the 50% of the carbamate contained in the urea solution and separating the decomposition products, recycling the decomposition products to the urea-synthesis reactor, adiabatically decomposing, i.e. without administering heat from an external source, the ammonium carbamate still contained in the urea solution in an adiabatic stripper in which there is introduced, as the stripping agent, the gas stream obtained by steam-reforming or partial oxidation of liquid or gaseous hydrocarbons, essentially composed of CO_2 , N_2 and H_2 to be used generally for the synthesis of ammonia, removing from the adiabatic stripper both CO_2 and the NH_3 derived from the decomposition of the residual ammonium carbamate and the stripping agent, feeding the gas mixture aforesaid to a CO_2 -absorber in which the CO_2 is absorbed by an ammoniacal solution thus obtaining a stream containing ammonium carbamate to be fed to the urea-synthesis reactor, discharging from the adiabatic stripper the solution of urea substantially devoid of carbamate, and sending the solution of urea through subsequent treatments of low-pressure decomposition and concentration under vacuum.

A shortcoming of the method outlined above is that the content of CO_2 in the solution going from the bottom of the adiabatic stripper to the low-pressure decomposition stage, is rather high (10% to 15% by wt.) the result being the necessity of employing an oversized decomposition stage and an increase in the consumption in the same apparatus.

On the other hand, the run of the adiabatic stripper according to the patent application aforementioned was bound to the use of CO_2 among other stripping agents, inasmuch as the CO_2 permitted, by its partial reaction with the ammonia contained in the urea solution, the supply of at least partially, the heat which is required for the decomposition of the ammonium carbamate contained in the urea solution. Regrettably, as outlined above, the CO_2 content remains high so that the low-pressure decomposition stage must be significantly oversized.

It has been surprisingly found that it is possible to dispense with CO_2 as the stripping agent, and consequently to have an end product substantially free of CO_2 without giving up the adiabatic stripping.

This achievement is made possible by selecting appropriate ratios between H_2O and CO_2 and between NH_3 and CO_2 in the urea synthesis reactor.

An object of the present invention is to provide an integrated ammonia-urea process comprising the following stages:

(a) to send the gaseous stream as obtained from steam-reforming or partial oxidation of liquid or gaseous hydrocarbons which make up the raw gas stream for the synthesis of ammonia, and which essentially comprise H_2 , N_2 and CO_2 , to a CO_2 -absorption system using a concentrated aqueous solution of ammonia and which is more particularly composed of two serially arranged discrete absorption stages, in the first of which the absorbing liquor is a concentrated aqueous solution of ammonia (concentration above 70% by wt of ammonia, 80% being preferred), whereas in the second stage the absorption liquor is an aqueous ammoniated solution of ammonium carbonate as obtained from the low-pressure decomposition stage, or, in the case in which the latter is not provided, from the stage of decomposition under vacuum of the urea solution;

(b) to discharge from the CO_2 -absorption section a gas stream which is essentially composed of N_2 and H_2 (with possible traces of NH_3 and CO_2) together with a liquid stream which essentially comprises an aqueous solution of ammonium carbamate;

(c) to feed the aqueous solution of ammonium carbamate to a urea-synthesis reactor wherein the ammonium carbamate is partially converted into urea;

(d) to discharge from the urea-synthesis reactor an aqueous solution of urea which contains the unconverted ammonium carbamate and the excess of ammonia over the stoichiometric amount and possibly a gaseous stream from the reactor top, the stream essentially comprising inerts and a certain amount of NH_3 and CO_2 ;

(e) to feed the aqueous solution of urea from stage (d) to a decomposer in which the ammonium carbamate is decomposed into ammonia and carbon dioxide, the latter being both with drawn from said decomposer together with the water which evaporates off, to be recycled in the vapor phase to the urea-synthesis reactor;

(f) to discharge from the decomposer an aqueous solution of urea which contains about the 50% of the carbamate originally contained in the urea solution exiting the synthesis reactor and to feed said aqueous solution to an adiabatic stripper wherein it is employed as a stripping agent of the gaseous stream of (b) above;

(g) to discharge through the bottom of the adiabatic stripper the solution of urea substantially devoid of ammonium carbamate, and to discharge from the top of the stripper the stripping agent ($\text{N}_2 + \text{H}_2$) with the products of decomposition of the carbamate ($\text{NH}_3 + \text{CO}_2$) and the evaporated water;

(h) to introduce the gaseous mixture withdrawn from the top of the adiabatic stripper to a condenser wherein the ammonia and the carbon dioxide are condensed by cooling as a result of an indirect heat exchange with a cold fluid in the presence of an ammoniated solution of ammonium carbonate coming from the low-pressure decomposition stage whereas the stream with H_2 and N_2 is discharged at the top and fed, upon methanization, to the ammonia synthesis together with the inert gases N_2 and H_2 exiting the CO_2 -absorption system;

(i) to send the condensate from (h) to the CO_2 -absorber;

(l) to send the urea solution of stage (g) to the vacuum concentration stage either directly or through a previous low-pressure decomposition stage (4 to 5 atmo-

BRIEF DESCRIPTION OF THE DRAWING

The urea solution, along with the carbamate which has not been decomposed, is sent via the piping 10 to the

A practical example will now be given in order that the invention may be better illustrated but without limiting it in any way.

TABLES 1 and 2 report the working conditions, the concentrations and the rates of flow.

[illegible]

TABLE 1-continued

TOTAL	85868	100	78233	100	137539	100	73408	100	32409	100	122550	100	159469	100
-------	-------	-----	-------	-----	--------	-----	-------	-----	-------	-----	--------	-----	--------	-----

SYNGAS = synthesis gas.

TABLE 2

Drawing item	9		10		11		12		15	
FLUID TYPE	HEAD (22)		UREA SOLN.		UREA SOLN.		CARBONATE SOLN.		CARBONATE SOLN.	
Temp. °C.	195		210		110		60			
Press.atm			196.5				195			
	FLOW WT.		FLOW WT.		FLOW WT.		FLOW WT.		FLOW WT.	
	kg/h	% wt	kg/h	% wt	kg/h	% wt	kg/h	% wt	kg/h	% wt
N ₂										
H ₂										
CO ₂	6698	18.1	7353	6	933	1.4	7080	11.1	660	18
NH ₃	25835	70	45343	37	2177	3.3	48422	75.6	1540	42
H ₂ O	4386	11.9	28187	23	21119	32.1	8535	13.3	1467	40
UREA			41667	63.2	41667	63.2				
TOTAL	36919	100	122550	100	65896	100	64037	100	3667	100

We claim:

1. An integrated ammonia-urea process comprising the steps of:

- Sending the gaseous stream obtained from steam 25 reforming or partial oxidation of liquid or gaseous hydrocarbons, containing H₂, N₂ and CO₂, to a CO₂-absorption system in which CO₂ is absorbed by a concentrated aqueous solution of ammonia,
- discharging from the CO₂-absorption system a 30 gaseous stream composed essentially by H₂ and N₂ and a liquid stream essentially composed by an aqueous solution of ammonium carbamate,
- feeding with the aqueous solution of ammonium carbamate a urea synthesis reactor wherein the 35 carbamate is partially converted into urea,
- discharging from the urea synthesis reactor an aqueous solution of urea containing the unconverted ammonium carbamate and the excess of ammonia relative to the stoichiometric amount, 40
- feeding the aqueous solution of urea which contains the unconverted carbamate to a decomposer and thermally decomposing therein about the 50% of said carbamate, discharging a solution of urea containing carbamate and the decomposition products, the latter being recycled in the vapor phase to the urea synthesis reactor, 45
- decomposing the carbamate contained in the solution of urea exiting the decomposer of the carbamate of stage (e) in an adiabatic stripper in which 50 the gaseous stream of stage (b) is used as the stripping agent, a urea solution substantially devoid of

carbamate being obtained at the bottom, whereas the decomposition products, the stripping agent and the evaporated water are obtained at the stripper head,

- condensing the decomposition products and the evaporated water in the presence of an ammoniated solution of ammonium carbonate by indirect heat exchange with a cold fluid, the inert gases (H₂+N₂) to be used for the ammonia synthesis upon methanization being discharged through the condenser head,
- sending the condensate as produced in stage (g) to the CO₂-absorption stage,
- sending the solution of urea exiting the bottom of the adiabatic stripper to a concentration stage and discharging melted urea from the latter, wherein, in the urea reactor the ratio of H₂O to CO₂ being in the range of from 0.9 and 1.3 to 1 and the ratio of NH₃ to CO₂ being in the range of from 4.5 and 6.5 to 1.

2. A process according to claim 1 wherein the CO₂-absorption system is composed of two serially arranged absorption stages, in the first of which the absorption liquor is a concentrated aqueous solution of ammonia containing more than 70% by weight of ammonia, and in the second of which the absorption liquor is an ammoniated aqueous solution of ammonium carbonate.

3. A process according to claim 1 wherein the ratio of H₂O to CO₂ is 1.1 to 1.0, and the ratio of NH₃ to CO₂ is 5.5 to 1.0.

* * * * *

55

60

65