

[54] MULTI-LAYERED LIQUID CRYSTAL PANEL WITH TWISTED NEMATIC LIQUID CRYSTAL MATERIAL HAVING POLARIZERS DISPLACED FOR SHARP-RISING CHARACTERISTIC

[75] Inventors: Fumiaki Funada, Yamatokoriyama; Masataka Matsuura, Tenri; Tomio Wada, Nara, all of Japan

[73] Assignee: Sharp Kabushiki Kaisha, Osaka, Japan

[*] Notice: The portion of the term of this patent subsequent to Sep. 9, 2003 has been disclaimed.

[21] Appl. No.: 309,027

[22] Filed: Feb. 7, 1989

Related U.S. Application Data

[63] Continuation of Ser. No. 244,820, Mar. 17, 1981, abandoned.

[30] Foreign Application Priority Data

Mar. 17, 1980 [JP] Japan 55-34539

[51] Int. Cl.⁴ G02F 1/13

[52] U.S. Cl. 350/335; 350/334; 350/337

[58] Field of Search 350/334, 335, 337, 341, 350/346, 347 E

[56] References Cited

U.S. PATENT DOCUMENTS

- 3,941,454 3/1976 Maezawa 350/334
3,977,767 8/1976 Okuma et al. 350/335 X
4,231,639 11/1980 Banda 350/335
4,231,640 11/1980 Funada et al. 350/335 X

FOREIGN PATENT DOCUMENTS

52-49854 4/1977 Japan .

Primary Examiner—Stanley D. Miller
Assistant Examiner—Richard Gallivan
Attorney, Agent, or Firm—Birch, Stewart, Kolasch & Birch

[57] ABSTRACT

A multi-layered liquid crystal display device is disclosed, which includes a stack of liquid crystal layers in which the longitudinal axes of the liquid crystal molecules extend spirally, the liquid crystal layers being disposed in parallel with the spiral axes. A voltage supply is provided for supplying a voltage to at least a portion of the liquid crystal layers for conversion of the molecular alignment. Also provided is a pair of polarizers for making visible the conversion of the molecular alignment. More particularly, the polarization direction of the polarizers or direction normal to the polarization direction is deflected within the range of 3° to 15° with respect to the longitudinal direction of the liquid crystal molecules in a sense to reduce the spiral angle of the liquid crystal layers and the deflection angle is substantially in alignment with the longitudinal direction of the liquid crystal molecules.

8 Claims, 2 Drawing Sheets





FIG. 1




FIG. 2




FIG. 4




FIG. 3(A)
PRIOR ART




FIG. 5(A)




FIG. 3(B)
PRIOR ART





FIG. 5(B)



MULTI-LAYERED LIQUID CRYSTAL PANEL WITH TWISTED NEMATIC LIQUID CRYSTAL MATERIAL HAVING POLARIZERS DISPLACED FOR SHARP-RISING CHARACTERISTIC

This application is a continuation of application Ser. No. 06/244,820 filed on Mar. 17, 1981, now abandoned.

BACKGROUND OF THE INVENTION

This invention relates to an improved structure of a multi-layered liquid crystal display panel having a stack of liquid crystal display cells each including a so-called twisted nematic liquid crystal material wherein its spiral axis is oriented within two supports in a direction normal to planes containing the two supports and the longitudinal axes of the liquid crystal molecules are twisted substantially by 90°.

As the quantity of information to be displayed continues to increase, the demand for matrix displays as the substitution of the conventional segmented displays becomes increasingly acute. Matrix displays with a high degree of multiplexing are highly desirable in the field of liquid crystal displays. It is however believed that the display properties of the liquid crystal displays are incompatible with multiplex driving as contrasted with other flat displays including a plasma display panel (PDP) and an electroluminescence display panel (ELDP). In other words, this is because the display contrast-applied voltage properties are broad and dull.

Accordingly, it is an object of the present invention to provide a new and useful multi-layered liquid crystal display panel which exhibits improved display properties

It is another object of the present invention to provide a new and useful multi-layered liquid crystal display panel which bears sharp rising properties suitable for multiplex driving.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a scheme of a two-layered liquid crystal display panel having twisted nematic liquid crystal cells;

FIG. 2 is a view showing the definition of vector r_j^j ;

FIGS. 3(A) and 3(B) are views for illustrating the conventional way for installation of polarizers;

FIG. 4 is a view showing the definitions of V_{th} and V_{sat} ; and

FIGS. 5(A) and 5(B) are views showing installation of polarizers in accordance with an embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Referring to FIG. 1, there is shown a schematic construction of a two-layer twisted nematic liquid crystal display panel. Three transparent plates 1_a , 1_b and 1_c of glass or the like are disposed as indicated and nematic liquid crystal layers (or cholesteric liquid crystal layers with a long pitch, i.e., $P_0 \gtrsim 10d$) 2_a and 2_b are dispersed between the spacings of the respective transparent plates 1_a , 1_b and 1_c . In order to apply an enabling voltage to the liquid crystal layers 2_a and 2_b , the transparent plates 1_a , 1_b and 1_c are coated with transparent electrodes 3_a , 3_b , 3_c and 3_d of In_2O_3 or the like, which in turn are connected to an external driving source (not shown). Insulation layers 4_a , 4_b , 4_c and 4_d are deposited on those portions of the major surfaces of the transparent sup-

ports 1_a , 1_b and 1_c where the transparent electrodes 3_a , 3_b , 3_c and 3_d are not disposed, for concealing reflected light on the transparent electrodes 1_a , 1_b and 1_c from view. Alignment layers 5_a , 5_b , 5_c and 5_d which are subject to priority alignment technique such as rubbing or slant evaporation are set up at the interfacial surfaces between the transparent electrodes 3_a , 3_b , 3_c and 3_d , the insulation layers 4_a , 4_b , 4_c and 4_d and the liquid crystal material.

The directions of the longitudinal axes of the liquid crystal molecules on these alignment layers are generally denoted r_j^j and more particularly r_1^1 , r_1^2 and r_2^1 in the order counting from the side where a light scattering reflector 8 is disposed. The transparent plates 1_a , 1_b and 1_c are sealed to confine the liquid crystal layers 2_a and 2_b on its peripheral edges by means of proper sealants 6_a and 6_b such as epoxy resin and frit glass.

Linear polarizer filters 7_a and 7_b of iodine systems, polyene systems, dye systems or the like are disposed outside the transparent plates 1_a and 1_b . It is noted that the direction of polarization by the polarizer 7_a is represented by vector A and the polarization by the polarizer 7_b is represented by vector P. The viewer is labeled 9. See FIGS. 3 and 5 for vector representation.

FIG. 2 illustrates the definition of the above-mentioned vector r_j^j wherein the liquid crystal molecule alignment layer is labeled 5 and the liquid crystal molecules are labeled 2.

FIG. 3 shows the conventional way to install the linear polarizers 7_a and 7_b . Assuming an angle defined by r_1^1 and P the polarization by the polarizer 7_a is represented by $\langle r_1^1, P = 0^\circ$. Similarly, $\langle r_2^2, A = 0^\circ$. It is noted that a value characteristic of V_{sat}/V_{th} is identical even when $\langle r_1^1, P = 90^\circ$, $\langle r_2^2, A = 90^\circ$ and so on. For the sake of illustration only it is assumed that $\langle r_1^1, P = 0^\circ$, $\langle r_2^2, A = 0^\circ$.

The present invention provides an improved contrast property curve through a proper selection of particular directions of polarization by the polarizers 7_a and 7_b . More particularly, the present invention is to provide a new and useful multi-layered liquid crystal display which offers improved display properties with an increased capacity of information display by giving sharp "rising" properties suitable for multiplex driving.

So-called optimum voltage averaging is recommended as a driving technique for twisted nematic liquid crystal displays from a viewpoint of a circuit design. In this case the voltage margin of the effective voltage values at selected points and non-selected points are defined below:

$$\frac{V_{on}}{V_{off}} = \frac{(N-1)^{\frac{1}{2}}}{(N+1)^{\frac{1}{2}}} \quad (1)$$


where V_{on} and V_{off} are the effective voltage values for the selected points and non-selected points and N is the degree of multiplexing.

For example, $V_{on}/V_{off} = 1.39$ with $N = 10$. This implies that good display contrast is not available when the ratio of V_{sat} to V_{th} in the contrast property curve is greater than V_{on}/V_{off} . Accordingly, how to decrease the value V_{sat}/V_{th} is material for the properties of the displays. FIG. 4 illustrates the definitions of V_{th} and V_{sat} . The horizontal axis denotes the direction of the molecular alignment in the first liquid crystal or bottom layer and the vertical axis denotes the direction of mo-

lecular alignment in the second liquid crystal or top layer.

FIG. 5 is an illustration of an embodiment of the present invention. The distinctions over FIG. 3 are that the directions of P and A are out of alignment with r_1^1 and r_2^2 by $\Delta\theta_1$ and $\Delta\theta_2$ (within the range of 3° to 15° , preferably within the range of 5° to 10° in the given example), such disalignment oriented to reduce the spiral angle of a spiral liquid crystal material constituting the liquid crystal layers 2_a and 2_b , and the absolute values of $\Delta\theta_1$ and $\Delta\theta_2$ are substantially identical. This is because the difference between $\Delta\theta_1$ and $\Delta\theta_2$ results in differences in electrooptical properties of the liquid crystal layers 2_a and 2_b , especially V_{sat}/V_{th} , and non-uniformity of display quality between the two layers.

Table 1 shows the results of applicants' experiments on the foregoing aspects. Materials were used as follows: The transparent supports 1_a , 1_b and 1_c were 2 mm thick, 0.7 mm thick and 1 mm thick soda glass sheets. The liquid crystal layer 2_a was nematic liquid crystal ROTN-403 by Roche including about 0.1 wt% of cholesteryl nonanoate with left-handed spiral direction. The liquid crystal layer 2_b , on the other hand, included ROTN 403 with about 0.1 wt% of



with right-handed spiral direction. The thickness of the liquid crystal layers 2_a and 2_b was about 6 μm . Furthermore, r_1^2 is substantially in reverse parallel with r_2^1 and $r_1^1 \cdot r_1^2 \approx 90^\circ$, $< r_2^1 \cdot r_2^2 \approx 90^\circ$. The transparent electrodes 3_a , 3_b and 3_c were In_2O_3 with a thickness of about 500 \AA deposited by electron-beam evaporation. The insulation layers 4_a , 4_b , 4_c and 4_d were substantially of the same index of refraction as In_2O_3 and typically comprised Nb_2O_3 made by electron-beam evaporation with the same thickness as the transparent electrodes (In_2O_3). The alignment layers 5_a , 5_b , 5_c and 5_d were subject to rubbing after being overcoated with a silane surfactant (C-600 by Torei Silicone). The sealants 6_a and 6_b were made up of epoxy solder resist printing resin (R2401-HC11 by Somal). The polarizers 7_a and 7_b were linear polarizers L-83-18 by Sanritsu Electric and the scattering reflector 8 was made up of sandblasted aluminum plate.

TABLE 1

$\Delta\theta_1$	$\Delta\theta_2$	V_{sat}/V_{th}
0°	0°	1.55
0°	10°	1.52
10°	0°	1.42
10°	10°	1.36
-10°	0°	1.99

It is noted that observation was made along the normal line with respect to the supports 1_a , 1_b and 1_c . The symbol of $\Delta\theta$ was designated minus when it reduced the twisting angle and voltage was applied to the liquid crystal layer 2_b .

It is clear from the foregoing that the present invention greatly decreases the value V_{sat}/V_{th} and optimizes the properties of the liquid crystal displays for multiplex driving.

However, in connection with the ranges of $\Delta\theta_1$, $\Delta\theta_2$, no superiority is appreciable to the conventional properties because less than 3° falls within the range of mea-

suring error. On the other hand, more than 15° reduces the absolute contrast value and makes interfering color significant. It is therefore preferable that $\Delta\theta_1$, $\Delta\theta_2$ be within the range of 5° to 10° .

Although in the foregoing description the liquid crystal layers 2_a and 2_b are left-twisted and right-twisted, it is obvious that the present invention is equally applicable when the two layers have the same twisting direction. It has been confirmed that better properties are available even when the orientation of r_1^2 and r_1^1 are deflected within the range of 0° to 15° in a sense to be reduced with respect to the spiral direction. In this case it is also preferable that P and r_1^1 and A and r_2^2 be correlated $|\Delta\theta_1| \approx |\Delta\theta_2|$ where $\Delta\theta_1$ and $\Delta\theta_2$ are the reducing spiral angles of the liquid crystal molecules. This is true when A is increased by 90° (or P is increased by 90°). Also, the scattering reflector 8 may be eliminated if desired from the present invention.

The invention being thus described, it will be obvious that the same may be varied in many ways. Such variations are not to be regarded as a departure from the spirit and scope of the invention, and all such modifications are intended to be included within the scope of the following claims.

What is claimed is:

1. A multilayer liquid crystal display comprising:

- two liquid crystal cells disposed adjacent to each other so as to include a common middle substrate plate disposed therebetween and upper and bottom substrate plates disposed on either side thereof, wherein each cell contains twisted nematic liquid crystal material with molecules that are oriented
- in the direction r_2^2 at the underside of said upper substrate plate,
 - in a direction r_2^1 at an angle of 90° against r_2^2 at the topside of said middle substrate plate,
 - in a direction r_1^2 which is opposite to r_2^1 at the underside of said middle substrate plate, and
 - in a direction r_1^1 which is opposite to r_2^2 at the topside of said bottom substrate plate; an analyzer above the liquid crystal cells; and

a polarizer underneath the liquid crystal cells, wherein the analyzer is twisted by an angle of $\Delta\theta_1$ against r_2^2 , the polarizer is twisted by an angle $\Delta\theta_2$ against r_1^1 in the same direction as the analyzer, and $\Delta\theta_1$ and $\Delta\theta_2$ are essentially the same and are between 3° and 15° .

2. A liquid crystal display device comprising:

- a stack of liquid crystal layers each containing liquid crystal molecules having axes which progressively twist throughout the thickness of the layer, and a polarizer disposed above and below the stack of layers,

wherein the axes of the molecules most closely adjacent each polarizer extend at an angle, measured in the same sense as the twist of the molecules in the direction approaching the polarizer, of from 3° to 15° to the polarization direction of the polarizer, or the normal to the polarization direction.

3. A device as claimed in claim 2, wherein the liquid crystal molecules of each layer have axes which twist through an angle of substantially 90° throughout the thickness of the layer.

4. A device as claimed in claim 3, wherein each liquid crystal layer is formed of nematic liquid crystal material.

5

5. A device as claimed in claim 3, wherein each liquid crystal layer is formed of cholesteric liquid crystal material.

6. A device as claimed in claim 3, including electrode means for applying a voltage across each said liquid crystal layer.

6

7. A device as claimed in claim 3, in which there are two liquid crystal layers.

8. A device as claimed in claim 3, wherein the axes of the molecules most closely adjacent each polarizer extend at an angle, measured in the same sense as the twist of the molecules in the direction approaching the polarizer, of from 5° to 10° to the polarization direction of the polarizer, or the normal to the polarization direction.

* * * * *

10

15

20

25

30

35

40

45

50

55

60

65