



US005144931A

United States Patent [19]

[11] Patent Number: **5,144,931**

Miyashita et al.

[45] Date of Patent: **Sep. 8, 1992**

[54] **AIR-FUEL RATIO CONTROL METHOD FOR INTERNAL COMBUSTION ENGINES**

4,864,999 9/1989 Fujisawa 123/492
4,913,120 4/1990 Fujimoto et al. 123/492 X
5,014,672 5/1991 Fujii et al. 123/489 X

[75] Inventors: **Yukio Miyashita; Hiroshi Mifune; Atsushi Matsubara; Kunio Noguchi,** all of Wako, Japan

FOREIGN PATENT DOCUMENTS

62-251443 11/1987 Japan .

[73] Assignee: **Honda Giken Kogyo Kabushiki Kaisha,** Tokyo, Japan

Primary Examiner—Tony M. Argenbright
Attorney, Agent, or Firm—Armstrong & Kubovcik

[21] Appl. No.: **770,257**

[22] Filed: **Oct. 3, 1991**

[57] ABSTRACT

[30] Foreign Application Priority Data

Oct. 5, 1990 [JP] Japan 2-268097

An air-fuel ratio control method for an internal combustion engine, in which the air-fuel ratio of a mixture supplied to the engine is feedback-controlled to a desired air-fuel ratio in response to output from an exhaust gas ingredient concentration sensor. When the engine is in a predetermined accelerating condition, fuel supply to the engine is increased. The rate of correction of the air-fuel ratio of the mixture by the feedback control is set to a smaller value when the engine is in the predetermined accelerating condition, than values to be set when the engine is in other operating conditions.

[51] Int. Cl.⁵ **F02D 41/14**

[52] U.S. Cl. **123/682; 123/492**


[58] Field of Search **123/440, 489, 492, 493**

[56] References Cited

U.S. PATENT DOCUMENTS

4,627,404 12/1986 Saito et al. 123/440 X
4,633,841 1/1987 Matsuura et al. 123/492
4,711,200 12/1987 Kinoshita 123/492
4,754,736 7/1988 Yamato et al. 123/492

9 Claims, 5 Drawing Sheets






FIG. 1




FIG.2

FIG.3a





FIG.3b






FIG.4

AIR-FUEL RATIO CONTROL METHOD FOR INTERNAL COMBUSTION ENGINES

BACKGROUND OF THE INVENTION

The present invention relates to a method of controlling the air-fuel ratio of an internal combustion engine, and more particularly, to a method of this kind wherein the air-fuel mixture supplied to the engine is feedback-controlled to a desired air-fuel ratio in response to the output of an exhaust gas ingredient concentration sensor having output characteristics in approximate proportion to the exhaust gas ingredient concentration.

Among conventional methods of feedback-controlling the air-fuel ratio of an air-fuel mixture supplied to an internal combustion engine (referred to hereinafter as "supply air-fuel ratio") to a desired air-fuel ratio in response to the output of an exhaust gas ingredient concentration sensor having output characteristics proportional to the exhaust gas ingredient concentration, there is a method proposed e.g. by Japanese Provisional Patent Publication (Kokai) No. 62-251443, in which a proportional term (P term), an integral term (I term), and a differential term (D term) are calculated based on a difference between an actual air-fuel ratio detected by the exhaust gas ingredient concentration sensor and a desired air-fuel ratio, and by the use of these calculated P, I, and D terms the supply air-fuel ratio is feedback-controlled.

However, according to this conventional method, feedback gains applied to calculation of the P, I, and D terms are set based on the engine rotational speed and the difference between the actual air-fuel ratio and the desired air-fuel ratio, but not set with other operating parameters of the engine taken into consideration. Therefore, the proposed method has the following disadvantage:

When the engine is in a predetermined accelerating condition, supply of an increased amount of fuel suitable for the accelerating condition (hereinafter referred to as "increased fuel supply for acceleration") is carried out. During increased fuel supply for acceleration, the actual air-fuel ratio detected by the exhaust gas ingredient concentration sensor is deviated toward the richer side relative to the desired air-fuel ratio. However, if the amount of fuel supplied to the engine is rapidly decreased in response to this deviation, the supply air-fuel ratio is largely deviated in a leaning direction immediately after termination of increased fuel supply for acceleration, which results in degraded driveability of the engine.

SUMMARY OF THE INVENTION

It is the object of the invention to provide an air-fuel ratio control method for an internal combustion engine, which is capable of properly feedback-controlling the air-fuel ratio during increased fuel supply for acceleration to thereby prevent degradation of driveability, especially immediately after termination of increased fuel supply for acceleration.

To attain the above object, the present invention provides an air-fuel ratio control method for an internal combustion engine having an exhaust passage, and an exhaust gas ingredient concentration sensor arranged in the exhaust passage for detecting the concentration of an ingredient in exhaust gases from the engine, wherein an amount of fuel to be supplied to the engine is calculated by the use of output from the exhaust gas ingredi-

ent concentration sensor to thereby feedback-control the air-fuel ratio of a mixture supplied to the engine to a desired air-fuel ratio, and when the engine is in a predetermined accelerating condition, the amount of fuel to be supplied to the engine is cut off.

The air-fuel ratio control method according to the invention is characterized by comprising the steps of:

(1) determining whether or not the engine is in the predetermined accelerating condition; and

(2) setting a rate of correction of the air-fuel ratio of the mixture by the feedback control to a smaller value when the engine is in the predetermined accelerating condition, than values to be set when the engine is in operating conditions other than the predetermined accelerating condition.

The exhaust gas ingredient concentration sensor has output characteristics approximately proportionate to the concentration of the ingredient in the exhaust gases.

Preferably, the amount of fuel to be supplied to engine is determined by multiplying a basic fuel amount by a desired air-fuel ratio coefficient representing the desired air-fuel ratio, and an air-fuel ratio correction coefficient calculated based on the desired air-fuel ratio coefficient and an equivalent ratio representing an actual air-fuel ratio which is commensurate with the output from the exhaust gas ingredient concentration sensor, the rate of correction of the air-fuel ratio of the mixture by the feedback control being determined by a rate of correction of the air-fuel ratio correction coefficient.

More specifically, the air-fuel ratio correction coefficient is obtained by adding up a proportional term, an integral term, and a differential term, the proportional, integral and differential terms being calculated by the use of respective predetermined coefficients and a difference between the desired air-fuel ratio coefficient and the equivalent ratio representing the actual air-fuel ratio, the rate of correction of the air-fuel ratio correction coefficient being determined by the predetermined coefficients.

The proportional, integral and differential terms are calculated by multiplying the respective predetermined coefficients by the difference between the desired air-fuel ratio coefficient and the equivalent ratio, the respective predetermined coefficients being set to smaller values when the engine is in the predetermined accelerating condition, than values to be set when the engine is in the operating conditions other than the predetermined accelerating condition.

Preferably, the desired air-fuel ratio coefficient having a value thereof assumed a second predetermined time period earlier than a present time is applied to the calculation of the proportional, integral and differential terms.

Specifically, the second predetermined time period is determined by a number of TDC signal pulses generated during a time period from the time fuel injection is effected to the time the resulting exhaust gases reach the exhaust gas ingredient concentration sensor.

In the meanwhile, the air-fuel ratio correction coefficient is renewed whenever a predetermined number of TDC signal pulses are generated, the predetermined number of TDC signal pulses being dependent on operating conditions of the engine, the rate of correction of the air-fuel ratio correction coefficient being also determined by the predetermined number of TDC signal pulses.

More specifically, the predetermined number of TDC signal pulses is set to a larger value when the engine is in the predetermined accelerating condition, than values to be set when the engine is in the operating conditions other than the predetermined accelerating condition.

The above and other objects, features and advantages of the invention will be more apparent from the ensuing detailed description taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram illustrating the whole arrangement of a fuel supply control system for carrying out the control method of the invention;

FIG. 2 is a flowchart of a program for calculating an air-fuel ratio correction coefficient K_{LAF};

FIGS. 3a and 3b are flowcharts of a program for setting a thinning-out number (NI) and gains (KI, KP, KD) of feedback control; and

FIG. 4 is a diagram showing results of setting of NI, KI, KP, and KD effected by the program of FIG. 3.

DETAILED DESCRIPTION

The method according to the invention will now be described in detail with reference to the drawings showing an embodiment thereof.

Referring first to FIG. 1, there is shown the whole arrangement of a fuel supply control system which is adapted to carry out the control method of this invention. In an intake pipe 2 of an engine 1, there is arranged a throttle body 3 accommodating a throttle valve 3' therein. A throttle valve opening (θ_{TH}) sensor 4 is connected to the throttle valve 3' for generating an electric signal indicative of the sensed throttle valve opening and supplying same to an electronic control unit (hereinafter referred to as "the ECU") 5.

Fuel injection valves 6 are each provided for each cylinder and arranged in the intake pipe between the engine 1 and the throttle valve 3, and at a location slightly upstream of an intake valve, not shown. The fuel injection valves 6 are connected to a fuel pump, not shown, and electrically connected to the ECU 5 to have their valve opening periods controlled by signals therefrom.

In the meanwhile, an intake pipe absolute pressure (PBA) sensor 8 is provided in communication with the interior of the intake pipe 2 via a conduit 7 at a location immediately downstream of the throttle valve 3' for supplying an electric signal indicative of the sensed absolute pressure to the ECU 5. An intake temperature (TA) sensor 9 is inserted into the intake pipe 2 at a location downstream of the intake pipe absolute pressure sensor 8 for supplying an electric signal indicative of the sensed intake temperature TA to the ECU 5.

An engine coolant temperature (TW) sensor 10, which may be formed of a thermistor or the like, is mounted in the cylinder block of the engine 1 for supplying an electric signal indicative of the sensed engine coolant temperature TW to the ECU 5. An engine rotational speed (NE) sensor 11 and a cylinder-discriminating (CYL) sensor 12 are arranged in facing relation to a camshaft or a crankshaft of the engine 1, neither of which is shown. The engine rotational speed sensor 11 generates a pulse as a TDC signal pulse at each of predetermined crank angles whenever the crankshaft rotates through 180 degrees, while the cylinder-discriminating sensor 12 generates a pulse at a predeter-

mined crank angle of a particular cylinder of the engine, both of the pulses being supplied to the ECU 5.

A three-way catalyst 14 is arranged within an exhaust pipe 13 connected to the cylinder block of the engine 1 for purifying noxious components such as HC, CO and NO_x. An O₂ sensor 15 as an exhaust gas ingredient concentration sensor (referred to hereinafter as an "LAF sensor") is mounted in the exhaust pipe 13 at a location upstream of the three-way catalyst 14, for supplying an electric signal having a level approximately proportional to the oxygen concentration in the exhaust gases to the ECU 5.

The ECU 5 comprises an input circuit 5a having the functions of shaping the waveforms of input signals from various sensors, shifting the voltage levels of sensor output signals to a predetermined level, converting analog signals from analog-output sensors to digital signals, and so forth, a central processing unit (hereinafter referred to as "the CPU") 5b, memory means 5c storing various operational programs which are executed in the CPU 5b and for storing results of calculations therefrom, etc., and an output circuit 5d which outputs driving signals to the fuel injection valves 6.

The CPU 5b operates in response to the above-mentioned signals from the sensors to determine operating conditions in which the engine 1 is operating such as an air-fuel ratio feedback control region and open-loop control regions, and calculates, based upon the determined operating conditions, the valve opening period or fuel injection period T_{OUT} over which the fuel injection valves 6 are to be opened by the use of the following equation (1) in synchronism with inputting of TDC signal pulses to the ECU 5:

$$T_{OUT} = T_i \times K_{CMDM} \times K_{LAF} \times K_1 + K_2 \quad (1)$$

where T_i represents a basic fuel amount, more specifically a basic fuel injection period which is determined according to the engine rotational speed N_e and the intake pipe absolute pressure PBA. The value of T_i is determined by a T_i map stored in the memory means 5c.

K_{CMDM} is a modified desired air-fuel ratio coefficient which is calculated by multiplying a desired air-fuel ratio coefficient K_{CMD} set according to engine operating conditions and representing a desired air-fuel ratio by a fuel cooling correction coefficient K_{ETV} . The correction coefficient K_{ETV} is intended to apply a prior correction to the fuel injection amount in view of the fact that the supply air-fuel ratio varies due to the cooling effect produced when fuel is actually injected, and its value is set according to the value of the desired air-fuel ratio coefficient K_{CMD} . Further, as will be clear from the aforementioned equation (1), the fuel injection period T_{OUT} increases if the desired air-fuel ratio coefficient K_{CMD} increases, so that the values of K_{CMD} and K_{CMDM} will be in direct proportion to the reciprocal of the air-fuel ratio A/F.

K_{LAF} is an air-fuel ratio correction coefficient which is calculated by a program described hereinafter with reference to FIG. 2 and set such that during feedback control the air-fuel ratio detected by the LAF sensor 15 will become equal to the desired air-fuel ratio, and is set to predetermined values depending on engine operating conditions during open-loop control.

K_1 and K_2 are other correction coefficients and correction variables, respectively, which are calculated based on various engine parameter signals to such values as to optimize characteristics of the engine such as

fuel consumption and accelerability depending on engine operating conditions.

The CPU 5b performs calculations as described heretofore, and supplies the fuel injection valves 6 with driving signals based on the calculation results through the output circuit 5d.

FIG. 2 shows a program which calculates the air-fuel ratio correction coefficient KLAf. This program is carried out in synchronism with inputting of each TDC signal pulse to the ECU 5.

At a step S21, a time lag TDC variable PTDC which indicates a time lag before exhaust gases reach the LAF sensor 15, by the number of TDC signal pulses, is read from a PTDC table set in accordance with the intake pipe absolute pressure PBA. The PTDC table is set based on the fact that the time period from the time fuel is injected into the intake pipe 2 to the time the resulting exhaust gases reach the LAF sensor 15 varies with the intake pipe absolute pressure PBA. According to the PTDC table, the time lag TDC variable is set to a smaller value as the intake pipe absolute pressure PBA is higher.

At a step S22, it is determined whether or not a flag FLAFB, which is set to a value of 1 when the air-fuel ratio feedback control is being performed, assumed a value of 1 when an immediately preceding TDC signal pulse was generated (i.e. in the last loop of the present program). If the answer to this question is affirmative (Yes), the program immediately proceeds to a step S24, whereas if the answer is negative (No), an immediately preceding value (i.e. a value obtained in the last loop) $DKAF_{N-1}$ of a difference between an equivalent ratio (hereinafter referred to as the "actual air-fuel ratio") representing an air-fuel ratio detected by the LAF sensor 15 and a desired air-fuel ratio coefficient $KCMD$ is set to a value of 0, and at the same time a value $KCMD_{N,P}$ of the desired air-fuel ratio coefficient assumed P loops before the present loop is set to a present value $KACT_N$ of the actual air-fuel ratio, at a step S23, followed by the program proceeding to the step S24. Here, "P" is equal to a value of the time lag TDC variable PTDC calculated at the step S21.

At the step S24, a present value $DKAF_N$ of the difference between the actual air-fuel ratio and the desired air-fuel ratio coefficient $KCMD$ is calculated by subtracting a present value $KACT_N$ of the actual air-fuel ratio from the value $KCMD_{N,P}$ of the desired air-fuel ratio assumed P loops before the present loop. If this step is reached by way of the step 23, $KCMD_{N,P} = KACT_N$, so that $DKAF_N = 0$.

At the following step S25, it is determined whether or not a thinning-out TDC variable NITDC is equal to 0. If the answer to this question is negative (No), the thinning-out TDC variable NITDC is decreased by a decrement of 1 at a step S26, followed by terminating the present program. The thinning-out TDC variable NITDC is used for renewing the air-fuel ratio correction coefficient KLAf whenever a thinning-out number NI of TDC signal pulses have been generated, the thinning-out number NI being set depending on operating conditions of the engine. If the answer to the question of the step S25 is affirmative (Yes), i.e. if $NITDC = 0$, the program proceeds to a step S27 et seq. where the air-fuel ratio correction coefficient KLAf is renewed.

At the step S27, by a subroutine shown in FIG. 3, there are calculated a proportional term (P term) coefficient KP, an integral term (I term) coefficient KI, and a

differential term (D term) coefficient KD, the coefficients serving as feedback gains, and the thinning-out number NI.

In FIG. 3, first at a step S41, it is determined whether or not the engine is idling. If the answer to this question is affirmative (Yes), the thinning-out number NI and the coefficients KI, KP and KD are set to respective predetermined values NIIDL, KIIDL, KPIDL, and KDIDL (e.g. 4, 0.063, 0, 0, respectively) for idling at a step S42.

If the answer to the question is negative (No), i.e. if the engine is not idling, it is determined at a step S43 whether or not the present loop is executed immediately after fuel cut. Here, the expression "immediately after fuel cut" means "before a predetermined time period corresponding to a predetermined number of TDC signal pulses elapses after termination of fuel cut". If the answer to the question of the step S43 is affirmative (Yes), i.e. immediately after fuel cut, the thinning-out number NI and the coefficients KI, KP, KD are set to respective predetermined values NIAFC, KIAFC, KPAFC, KDAFC (e.g. 2, 0.6, 1.2, 0.8, respectively) to be applied immediately after fuel cut, at a step S44.

Here, the thinning-out number NIAFC to be applied immediately after fuel cut assumes a value smaller than those to be applied after the lapse of the predetermined time period after termination of fuel cut, and the PID coefficients KPAFC, KIAFC, KDAFC assume values larger than those applied after the lapse of the predetermined time period. This contemplates the fact that during fuel cut, the air-fuel ratio correction coefficient KLAf is held constant to interrupt the feedback control. By setting the thinning-out number NI and the coefficients NI, KI, KP, and KD in this manner, a rate (speed) increases immediately after termination of fuel cut, at which the supply air-fuel ratio is corrected in response to the difference $DKAF$ between the actual air-fuel ratio and the desired air-fuel ratio, which enables to make the supply air-fuel ratio rapidly follow the desired air-fuel ratio. As a result, it is possible to prevent degradation of exhaust emission characteristics and driveability which would otherwise occur immediately after termination of fuel cut.

If the answer to the question of the step S43 is negative (No), i.e. if the present loop is not one immediately after fuel cut, it is determined at a step S45 whether or not increased fuel supply for acceleration (i.e. supply of an increased amount of fuel when the engine is accelerating) is being carried out. If the answer to this question is affirmative (Yes), the thinning-out number NI and the coefficients KI, KP, KD are set to respective predetermined values NIACC, KIACC, KPACC, and KDACC (e.g. 4, 0.063, 0, 0, respectively) for increased fuel supply for acceleration at a step S46.

The thinning-out number NIACC for increased fuel supply for acceleration is set to a value larger than those applied when the engine is in any of the other operating conditions, and the PID coefficients KPACC, KIACC, and KDACC for increased fuel supply for acceleration are set to values smaller than those applied when the engine is in any of the other operating conditions. This contemplates the fact that while increased fuel supply is being carried out, the actual air-fuel ratio is deviated in an enriching direction due to another coefficient applied for increased fuel supply for acceleration, but if the air-fuel ratio correction coefficient KLAf is changed rapidly in response to this deviation, the supply air-fuel ratio is largely deviated in an leaning direction upon termination of increased fuel supply for accelera-

tion, i.e. excessive correction of the supply air-fuel ratio results. By setting the thinning-out number NI and the PID coefficients KI, KP, KD in this manner, the rate (speed) of correction of the supply air-fuel ratio is decreased, so that during increased fuel supply for acceleration, the supply air-fuel ratio relatively slowly follows the desired air-fuel ratio, which enables to prevent degradation of driveability immediately after termination of increased fuel supply for acceleration.

If all of the answers to the questions of the steps S41, S43, and S45 are negative (No), i.e. if the engine is not idling, and at the same time the present loop is neither one immediately after fuel cut nor one during increased fuel supply for acceleration, in the following steps S47 to S69, the thinning-out number NI and the PID coefficients KP, KI, and KD are set according to the engine rotational speed NE and the intake pipe absolute pressure PBA, as shown in FIG. 4. Specifically, these values NI, KP, KI, and KD are set according to the relationship in magnitude between an actual value of the engine rotational speed NE and predetermined values NENI1 to NENI3 (e.g. 1000, 2500, 4000 rpm, respectively) as well as the relationship in magnitude between an actual value of the intake pipe absolute pressure PBA and predetermined values PBNI1 and PBNI2 (e.g. 360, 560 mmHg, respectively). In this connection, in the present embodiment, the predetermined NE and PBA values NENI1 to NENI3, PBNI1 and PBNI2 used for determination of these relationships in magnitude (at steps S47, S48, S50, S53, S54, S56, S59, S60, S62, S65, and S67 in FIG. 3) are each provided with a hysteresis between the time the parameter value increases and the time it decreases.

(1) If $NE \leq NENI1$,

- (1-1) If $PBA < PBNI1$: NI = NI11 (e.g. 4), KI = KI11 (e.g. 0.25), KP = KP11 (e.g. 0), and KD = KD11 (e.g. 0).
 (1-2) If $PBNI1 \leq PBA < PBNI2$: NI = NI12 (e.g. 4), KI = KI12 (e.g. 0.6), KP = KP12 (e.g. 1.2), and KD = KD12 (e.g. 0.8).
 (1-3) If $PBNI2 \leq PBA$: NI = NI13 (e.g. 2), KI = KI13 (e.g. 0.6), KP = KP13 (e.g. 0.95), and KD = KD13 (e.g. 0.25).

(2) If $NENI1 < NE \leq NENI2$,

- (2-1) If $PBA < PBNI1$: NI = NI21 (e.g. 4), KI = KI21 (e.g. 0.3), KP = KP21 (e.g. 1.15), and KD = KD21 (e.g. 0.4).
 (2-2) If $PBNI1 \leq PBA < PBNI2$: NI = NI22 (e.g. 2), KI = KI22 (e.g. 0.3), KP = KP22 (e.g. 1.05), and KD = KD22 (e.g. 0.4).
 (2-3) If $PBNI2 \leq PBA$: NI = NI23 (e.g. 2), KI = KI23 (e.g. 0.35), KP = KP23 (e.g. 0.95), and KD = KD23 (e.g. 0.25).

(3) If $NENI2 < NE \leq NENI3$,

- (3-1) If $PBA < PBNI1$: NI = NI31 (e.g. 4), KI = KI31 (e.g. 0.3), KP = KP31 (e.g. 1.1), and KD = KD31 (e.g. 0.4).
 (3-2) If $PBNI1 \leq PBA < PBNI2$: NI = NI32 (e.g. 2), KI = KI32 (e.g. 0.35), KP = KP32 (e.g. 0.95), and KD = KD32 (e.g. 0.4).
 (3-3) If $PBNI2 \leq PBA$: NI = NI33 (e.g. 2), KI = KI33 (e.g. 0.4), KP = KP33 (e.g. 0.85), and KD = KD33 (e.g. 0.3).

(4) If $NE > NENI3$,

- (4-1) If $PBA < PBNI1$: NI = NI41 (e.g. 2), KI = KI41 (e.g. 0.35), KP = KP41 (e.g. 1.05), and KD = KD41 (e.g. 0.4).
 (4-2) If $PBNI1 \leq PBA < PBNI2$: NI = NI42 (e.g. 2), KI = KI42 (e.g. 0.35), KP = KP42 (e.g. 0.9), and KD = KD42 (e.g. 0.4).
 (4-3) If $PBNI2 \leq PBA$: NI = NI43 (e.g. 2), KI = KI43 (e.g. 0.4), KP = KP43 (e.g. 0.8), and KD = KD43

(e.g. 0.35).

5 Referring again to FIG. 2, at a step S28, it is determined whether or not the absolute value of the present value $DKAF_N$ of the difference calculated at the step S24 is larger than a predetermined value $DKPID$. If the answer to this question is negative (No), i.e. if $|DKAF_N| \leq DKPID$, the program jumps to a step S30, whereas if the answer is affirmative (Yes), i.e. if $|DKAF_N| > DKPID$, both the immediately preceding value $DKAF_{N-1}$ and the present value $DKAF_N$ of the difference are set to a value of 0 at a step S29, and then the program proceeds to the step S30, where the proportional term $KLAFP$, the integral term $KLAFI$, and the differential term $KLAFD$ are calculated according to the following equations (2) to (4):

$$20 \quad KLAFP = DKAF_N \times KP \quad (2)$$

$$KLAFI = KLAFI + DKAF_N \times KI \quad (3)$$

$$KLAFD = (DKAF_N - DKAF_{N-1}) \times KD \quad (4)$$

25 Therefore, if the answer to the question of the step S28 is affirmative (Yes), i.e. if $|DKAF_N| > DKPID$, it follows that $KLAFP = KLAFD = 0$, and $KLAFI = KLAFI$, since both the values $DKAF_N$ and $DKAF_{N-1}$ are set to 0 at the step S29. In other words, the feedback control by the proportional term and differential term is stopped, and the integral term is held at the immediately preceding value.

30 Thus, when the actual air-fuel ratio $KACT$ is violently fluctuated as at an early stage of acceleration or when misfire occurs, which leads to $|DKAF_N| > DKPID$, the feedback control by the proportional term and the differential term is stopped, and the integral term is held at the immediately preceding value, which enables to prevent large fluctuations in the air-fuel ratio, which lead to degradation in driveability and exhaust emission characteristics.

35 At steps S31 to S34, limit checking of the integral term $KLAFI$ calculated as above is carried out. More specifically, the calculated value of the integral term $KLAFI$ is compared with predetermined upper and lower limit values $LAFIH$ and $LAFIL$ at steps S31 and S32. If the integral term $KLAFI$ exceeds the upper limit value $LAFIH$, it is set to the upper limit value $LAFIH$, whereas if it is smaller than the lower limit value $LAFIL$, it is set to the lower limit value $LAFIL$.

40 At a step S35, the air-fuel ratio correction coefficient $KLAF$ is calculated by adding up the PID terms $KLAFP$, $KLAFI$, and $KLAFD$. Then, the immediately preceding value $DKAF_{N-1}$ of the aforementioned difference is set to the present value $DKAF_N$ of same at a step S36, and the thinning-out variable $NITDC$ is set to the thinning-out number NI calculated at the step S27 at the step S37, followed by terminating the present program.

What is claimed is:

60 1. An air-fuel ratio control method for an internal combustion engine having an exhaust passage, and an exhaust gas ingredient concentration sensor arranged in said exhaust passage for detecting the concentration of an ingredient in exhaust gases from said engine, wherein an amount of fuel to be supplied to said engine is calculated by the use of output from said exhaust gas ingredient concentration sensor to thereby feedback-control the air-fuel ratio of a mixture supplied to said engine to

a desired air-fuel ratio, and when said engine is in a predetermined accelerating condition, said amount of fuel to be supplied to said engine is increased, the method comprising the steps of:

- (1) determining whether or not said engine is in said predetermined accelerating condition; and
- (2) setting a rate of correction of the air-fuel ratio of said mixture by said feedback control to a smaller value when said engine is in said predetermined accelerating condition, than values to be set when said engine is in operating conditions other than said predetermined accelerating condition.

2. An air-fuel ratio control method according to claim 1, wherein said exhaust gas ingredient concentration sensor has output characteristics approximately proportionate to the concentration of said ingredient in said exhaust gases.

3. An air-fuel ratio control method according to claim 2, wherein said amount of fuel to be supplied to said engine is determined by multiplying a basic fuel amount by a desired air-fuel ratio coefficient representing said desired air-fuel ratio, and an air-fuel ratio correction coefficient calculated based on said desired air-fuel ratio coefficient and an equivalent ratio representing an actual air-fuel ratio which is commensurate with said output from said exhaust gas ingredient concentration sensor, said rate of correction of the air-fuel ratio of said mixture by said feedback control being determined by a rate of correction of said air-fuel ratio correction coefficient.

4. An air-fuel ratio control method according to claim 3, wherein said air-fuel ratio correction coefficient is obtained by adding up a proportional term, an integral term, and a differential term, said proportional, integral and differential terms being calculated by the use of respective predetermined coefficients and a difference between said desired air-fuel ratio coefficient and said equivalent ratio representing said actual air-fuel ratio, said rate of correction of said air-fuel ratio

correction coefficient being determined by said predetermined coefficients.

5. An air-fuel ratio control method according to claim 4, wherein said proportional, integral and differential terms are calculated by multiplying said respective predetermined coefficients by said difference between said desired air-fuel ratio coefficient and said equivalent ratio, said respective predetermined coefficients being set to smaller values when said engine is in said predetermined accelerating condition, than values to be set when said engine is in said operating conditions other than said predetermined accelerating condition.

6. An air-fuel ratio control method according to claim 5, wherein said desired air-fuel ratio coefficient having a value thereof assumed a second predetermined time period earlier than a present time is applied to said calculation of said proportional, integral and differential terms.

7. An air-fuel ratio control method according to claim 6, wherein said second predetermined time period is determined by a number of TDC signal pulses generated during a time period from the time fuel injection is effected to the time the resulting exhaust gases reach said exhaust gas ingredient concentration sensor.

8. An air-fuel ratio control method according to claim 4, wherein said air-fuel ratio correction coefficient is renewed whenever a predetermined number of TDC signal pulses are generated, said predetermined number of TDC signal pulses being dependent on operating conditions of said engine, said rate of correction of said air-fuel ratio correction coefficient being also determined by said predetermined number of TDC signal pulses.

9. An air-fuel ratio control method according to claim 8, wherein said predetermined number of TDC signal pulses is set to a larger value when said engine is in said predetermined accelerating condition, than values to be set when said engine is in said operating conditions other than said predetermined accelerating condition.

* * * * *

45

50

55

60

65