



US005393451A

United States Patent [19]

Koetzle

[11] Patent Number: **5,393,451**

[45] Date of Patent: * Feb. 28, 1995

[54] **HIGH TEMPERATURE FLASHPOINT, STABLE CLEANING COMPOSITION**

[76] Inventor: **A. Richard Koetzle**, 32 Lucinda La., Rochester, N.Y. 14626

[*] Notice: The portion of the term of this patent subsequent to May 12, 2009 has been disclaimed.

[21] Appl. No.: **243,734**

[22] Filed: **May 17, 1994**

Related U.S. Application Data

[63] Continuation of Ser. No. 881,251, May 11, 1992, abandoned, which is a continuation-in-part of Ser. No. 640,219, Jan. 11, 1991, Pat. No. 5,112,516.

[51] Int. Cl.⁶ **C11D 7/26; C11D 7/50; C23G 5/032**

[52] U.S. Cl. **252/170; 134/38; 134/39; 134/40; 252/153; 252/162; 252/171; 252/364; 252/542; 252/DIG. 8**

[58] Field of Search **252/153, 162, 170, 171, 252/364, 542, DIG. 8; 134/38, 39, 40**

[56] References Cited

U.S. PATENT DOCUMENTS

3,700,740	10/1972	Mourier	203/42
3,915,880	10/1975	Sepulveda	252/99
4,294,729	10/1981	Bakos et al.	252/171
4,336,024	6/1982	Denissenko	8/142
4,414,128	11/1983	Goffinet	252/111
4,469,848	9/1984	Hooper et al.	252/106
4,511,488	4/1985	Matta	252/162
4,576,728	3/1986	Stoddart	252/517

4,600,522	7/1986	Grzeskowiak, Jr.	252/170
4,735,626	4/1988	Smith et al.	8/137
4,767,563	8/1988	de Buzzaccarini	252/174.25
4,783,283	11/1988	Stoddart	252/173
4,797,231	1/1989	Schumann et al.	252/171
4,960,236	10/1990	Hedges et al.	228/180.1
4,983,224	1/1991	Mombrun et al.	252/170
5,102,566	4/1992	Fetterman, Jr. et al.	252/51.5 R
5,112,516	5/1992	Koetzle	252/162
5,156,760	10/1992	Marchese et al.	252/171

FOREIGN PATENT DOCUMENTS

0316726	5/1989	European Pat. Off.	.
0354027	2/1990	European Pat. Off.	.
2564105	11/1985	France	.
61-033129	2/1986	Japan	.
4130197	5/1992	Japan	.
4130199	5/1992	Japan	.

OTHER PUBLICATIONS

Merck's Chemical Index p. 8890, definition of Terpineol—No. 8886 1976.

Merck's Chemical Index p. 7248, definitions of Pinene—No. 7242, Pine Oil—No. 7243, 1976.

Primary Examiner—Linda Skaling
Attorney, Agent, or Firm—Joseph W. Berenato, III

[57] ABSTRACT


The present invention relates to an aqueous based micellar solution in the form of a microemulsion which is an effective all-purpose cleaner and which has a flashpoint in excess of its boiling point which is typically greater than 212 degrees Fahrenheit.

19 Claims, No Drawings

clude the class of mono- or sesquiterpenes and mixtures thereof and can be acyclic or monocyclic in structure. Acyclic terpene hydrocarbons useful in the present invention include 2-methyl-6-methylene-2, 7-octadiene and 2, 6-dimethyl-2, 4, 6-octadiene. Monocyclic terpene hydrocarbons include terpinene, terpinolene and limonene classes and dipentene. While the examples provided here employ naturally occurring mixtures of these compounds, it is understood that pure samples of these compounds could be employed as well. When refined samples of naturally occurring terpene hydrocarbons are employed care must be taken to insure that no significant amount of alpha or beta pinene are present, or that any alpha or beta pinene are removed by means of distillation or filtering.

Specifically excluded from the term "terpene hydrocarbon" are bicyclic terpenes which include alpha and beta pinene, and terpene alcohols.

The term "terpene alcohol" is understood for purposes of the present invention to encompass compounds of the formulae:



which are monocyclic, bicyclic and acyclic alcohols, respectively. Terpene alcohols are structurally similar to terpene hydrocarbons except that the structures also include some hydroxy functionality. They can be primary, secondary, or tertiary alcohol derivatives of monocyclic, bicyclic or acyclic terpenes as well as the above. Such tertiary alcohols include terpineol which is usually sold commercially as a mixture of alpha, beta, and gamma isomers. Linalool is also a commercially available tertiary terpene alcohol. Secondary alcohols include borneol, and primary terpene alcohols include geraniol. Terpene alcohols are generally available through commercial sources, however, one must take care in practicing this invention to insure that no significant amount of alpha pinene or beta pinene are present in the terpene alcohol source, or that care is taken to remove such pinenes.

As used herein, the term "no significant amount" of alpha pinene and beta pinene means a terpene hydrocarbon in which the quantity of alpha pinene or beta pinene present is insufficient to cause the flashpoint of the terpene hydrocarbon to be significantly below its boiling point. I estimate that the alpha pinene and beta pinene volume percentage in the raw alcohol should be less

than about 0.5%, because otherwise a sudden and significant decrease in the flashpoint will be experienced.

Examples of nonionic surfactants which are employed include propylene oxide or ethylene oxide condensation products of higher aliphatic alcohols, alkyl phenols, carboxylic acids, amides, amines and sulphonamides. These well-known surfactants include the sorbitan esters of fatty acids having 10 to 22 carbon atoms; polyoxyethylene sorbitan esters of C10 to C22 fatty acids having up to 95 percent propylene oxide; polyoxyethylene sorbitol esters of C10 to C22 fatty acids, polyoxyethylene derivatives of fatty phenols having 6 to 20 carbon atoms and up to 95 percent propylene oxide; fatty amino and amido betaines having 10 to 22 carbon atoms; polyoxyethylene condensates of C10 to C22 fatty acids or fatty alcohols having up to 95 percent propylene oxide. Polyoxyethylene and polyoxypropylene analogs of the above surfactants can be used in the present invention as long as care is taken to insure that polyoxyethylene polymers or polyoxypropylene polymers which have not been completely reacted with the fatty acid portion of the surfactant. Most importantly, volatile oligomeric fractions must be absent from the surfactants used in the present invention. A convenient way this goal can be accomplished is by using oxypropylene analogs of the above mentioned species of surfactants where feasible.

Ionic surfactants employed include surfactants such as the alkylaryl sulfonates of 6 to 20 carbons in the alkyl group; C10 to C22 fatty acid soaps; C10 to C22 fatty sulfates; C10 to C22 alkyl sulfonates; alkali metal salts of dialkyl sulfosuccinates; C10 to C22 fatty amine oxides; fatty imidazolines of C6 to C20 carbon atoms; fatty amido sulfobetaines having 10 to 22 carbon atoms; quaternary surfactants such as the fatty ammonium compounds having 10 to 22 carbon atoms; C10 to C22 fatty morpholine oxides; alkali metal salts of carboxylated ethoxylated C10 to C22 alcohols having up to 95 percent propylene oxide; propylene oxide condensates of C10 to C22 fatty acid monoesters of glycerins having up to 95 percent of propylene oxide; the mono- or diethanol amides of C10 to C22 fatty acids; and alkoxyated siloxane surfactants containing propylene oxide units and/or propylene oxide units; and phosphate esters, etc.

As is well-known in the field of surfactants, the counter ion in the case of anionic surfactants may be any of the alkali metals, ammonia, or substituted ammonias such as trimethylamine or triethanol amine. Usually ammonium, sodium and potassium are preferred. In the case of cationic surfactants, the counter ion is usually a halide, sulfate, or methosulfate, the chlorides being the most common industrially available compounds. The foregoing compounds have been described with particular reference to fatty derivatives. It is the fatty moiety usually forming the lipophilic moiety. A common fatty group is an alkyl group of natural or synthetic origin.

In most instances, the alkyl group may be replaced by the corresponding ethylenically saturated group having one or more ethylene linkages such as commonly occurs in nature. Common unsaturated groups are oleyl, linoleyl, decenyl, hexadecenyl, dodecenyl, etc. In appropriate cases, as known in the art, the alkyl group may be cyclic, i.e., cycloalkyls, or may be straight or branched chain. Other suitable surfactants include sorbitol monolaurate-propylene oxide condensates; sorbitol monomyristate-propylene oxide condensates; sorbitol monostearate-propylene oxide condensates; dodecylphenol-propylene oxide condensates; myristyl-

phenol-propylene oxide condensates; octylphenyl-propylene oxide condensates; nonylphenyl-propylene oxide condensates; stearylphenol-propylene oxide condensates; lauryl alcohol-propylene oxide condensates; stearyl alcohol-propylene oxide condensates; secondary alcohol-propylene oxide condensates such as C14-C15 secondary alcohols condensed with propylene oxide; decyl amino betaine; coco amido sulfobetaine; oleyl amido betaine; coco imidazoline; coco sulfoimidazoline; cetyl imidazoline; 1-hydroxyethyl-2-heptadecenyl imidazoline; 1-hydroxyethyl-2-mixed heptadecenyl heptadecadienyl imidazoline; n-coco morpholine oxide; decyl dimethyl amine oxide; coco amido dimethyl amine oxide; sorbitan tristearate condensed with propylene oxide; sorbitan trioleate condensed with propylene oxide; sorbitan trioleate; sodium or potassium dodecyl sulfate; sodium or potassium stearyl sulfate; sodium or potassium dodecyl benzene sulfonate; sodium or potassium stearyl sulfonate; triethanol amine salt of dodecyl sulfate; trimethyl dodecyl ammonium chloride; trimethyl stearyl ammonium methosulfate; sodium laurate; sodium or potassium myristate; and sodium or potassium stearate.

Optionally, the cleaning compositions of the present invention may also include a suitable solvent for specific cleaning purposes. Such solvents include n-methyl pyrrolidone, dipropylene glycol and ethylene glycol monobutyl ether.

All of the chemical components used in the present invention are commercially available.

EXAMPLES

The following examples illustrate certain aspects of the present invention. They are not intended to exemplify the full scope of the invention. In certain aspects they enable certain aspects of the invention.

Example 1

The following ingredients in the following proportions were combined and mixed:

Ingredient	Volume	Wt. %
H ₂ O	175	35.0
monoethanolamine	7.5	1.5
dodecylbenzene sulfonic acid	13.0	2.6
nonylphenoxy polyethoxy ethanol	38.5	7.7
dipropylene glycol	38.5	7.7
sodium xylene sulfonate	11.5	2.3
e.d.t.a.	4.0	0.8
terpeniol	62.0	12.4
assorted terpene alcohols	35.0	7.0
n-methyl pyrrolidone	115	23.0
		100.0%

The combination was clear and stable. When tested it exhibited a flashpoint in excess of 212 degrees Fahrenheit. In fact, it exhibited no flashpoint below the boiling point of the composition.

Example 2

A mixture of the following components:

Ingredient	Volume	Wt. %
H ₂ O	545	54.2

-continued

Ingredient	Volume	Wt. %
monoethanolamine	20	2.0
dodecylbenzene sulfonic acid	35.0	3.5
nonylphenoxy polyethoxy ethanol	100	10.0
terpeniol	93.0	9.3
assorted terpene alcohols	52.5	6.0
n-methyl pyrrolidone	150	15.0

The components formed a clear microemulsion with mixing. The composition had a flashpoint in excess of 212 degrees Fahrenheit.

Example 3

Ingredient	Volume	Wt. %
terpeniol	200	33.33
n-methyl pyrrolidone	200	33.33
dipropylene glycol	200	33.33

This clear mixture was clear, stable and had a flashpoint in excess of 212 degrees Fahrenheit.

Example 4

Another sample was made with the following composition:

Ingredient	Volume (ml)	Wt. %
H ₂ O	470	47.0
dodecyl benzene sulfonic acid	35.5	3.5
ethylene glycol monobutyl ether (EB)	100	10.0
Rexol 25/10	100	10.0
sodium xylene sulfonate	30	3.0
e.d.t.a.	10	1.0
terpeniol	250	25.0
1 N NaOH	4.5	0.5
		100.0%

The solution was adjusted to a pH between about 6 and 8. This solution was clear and stable. The solution did not flash below its boiling point.

Examples 5-7

Clear stable microemulsions of the following formulations were made, all of which displayed flashpoints in excess of 212 degrees Fahrenheit.

Example 5

Ingredient	Volume (ml)	Wt. %
H ₂ O	415	41.5
monoethanolamine	15	1.5
dodecylbenzene sulfonic acid	26	2.6
nonylphenoxy polyethoxy ethanol	77	7.7
dipropylene glycol	77	7.7
sodium xylene sulfonate	30	3.0
ethylene diamine	10	1.0
tetraacetic acid		
terpeniol	250	25.0
n-methyl pyrrolidone	100	10.0

Example 6

Ingredient	Volume (ml)	Wt. %
H ₂ O	545	54.5
monoethanolamine	15	1.5
dodecylbenzene sulfonic acid	26	2.6
sodium metasilicate	10	1.0
nonylphenoxy polyethoxy ethanol	77	7.7
dipropylene glycol	77	7.7
sodium xylene sulfonate	30	3.0
ethylene diamine	10	1.0
tetraacetic acid		
terpeniol	150	15.0
n-methyl pyrrolidone	50	5.0

Example 7

Ingredient	Volume (ml)	Wt. %
H ₂ O	495	49.5
monoethanolamine	15	1.5
dodecylbenzene sulfonic acid	26	2.6
sodium metasilicate	10	1.0
nonylphenoxy polyethoxy ethanol	77	7.7

Ingredient	Volume (ml)	Wt. %
dipropylene glycol	77	7.7
sodium xylene sulfonate	30	3.0
ethylene diamine	10	1.0
tetraacetic acid		
terpeniol	200	20.0
n-methyl pyrrolidone	50	5.0

The preceding Examples 1-7 were directed principally to aqueous based cleaning compositions. These compositions are environmentally improved over prior cleaning compositions because the terpene hydrocarbons are naturally occurring materials which are biodegradable. Particularly applications, however, may not be practical for use with an aqueous system and I have therefore developed a composition utilizing water miscible organic solvents in admixture with the terpene hydrocarbon.

I prefer that the organic solvents be water miscible in order to facilitate the cleaning of spills, and to minimize the possible contamination to ground water supplies in the event of a spill or leakage. Furthermore, because the solvents and the terpene hydrocarbon are water miscible, then the cleaning composition may be produced so as to be mixed with water by the user.

A preferred terpene hydrocarbon is produced by Technical Ltd. of Anacortes, Washington. The terpene alcohol had a product name of Terpene Alcohols 95%, and had the following analysis by gas liquid chromatography:

Alpha fenchone	2.1%
Terpinen-4-OL	1.0%
Cis-beta-terpineol	1.9%
Isoborneol	0.6%
Trans-beta terpineol	1.4%
Alpha terpineol	91.4%

-continued

Total terpene alcohols	98.8%
------------------------	-------

I have found that commercially available terpene alcohols actually are a mixture of various alcohols. The alcohol types and percentages may also be related to the starting composition from which the alcohol is produced. Many terpene alcohols are produced from wood waste and I have found, for example, that the terpene hydrocarbon produced from trees originating in Brazil have a lower concentration of the alpha and/or beta pinenes than those originating in Florida.

Formulation of the composition as set out in Example 1 with the above-identified Tecnal Ltd. material resulted in a cleaning composition with a flashpoint above the boiling point of 220° F. The flashpoint test was based upon the closed cup method recommended by the Department of Transportation at 49 Code of Federal Regulations, Chapter I, §173.115(d)(i)(A). Formulation into an organic composition as set forth below in Example 8 resulted in a composition with a flashpoint of 207° F. and a Kb value in excess of 500.

I have found that terpene alcohols containing 95% to 100% terpene alcohol, when substantially free of the alpha and beta pinenes or other impurities adversely affecting the flashpoint, can be formulated to produce a terpene based solvent as a microemulsion or an organic solvent blend having flashpoints in excess of 200° F. and with very low trace odor. The odor of prior terpene compositions was quite distinctive, required ventilation, and adversely impacted use of those formulations. The disclosed formulations exhibit little or none of the trace odor. In addition, because the flashpoint of the disclosed compositions exceed 200° F. then they may be safely transported and landfilled.

The purified terpene alcohols may be blended in any proportion with other solvents, diluents, and thinners to produce a non-aqueous solvent blend which has a flashpoint in excess of 200° F. and a faint low or trace terpene odor. Solvent blends may be developed with specific properties based upon specific applications. Suitable organic solvents include mineral based oil, tridecyl alcohol, ethylene glycol, propylene glycol, diethylene glycol, dipropylene glycol, triethylene glycol, tripolyethylene glycol, glycerine, monoethanolamine, monoisopropanolamine, diethanolamine, triethanolamine, di-tri-isopropanolamine, dibasic ester, glycol ether acetate DE, glycol ether acetate DB, isophorone, glycol ethers and n-methyl pyrrolidone.

Example 8

Ingredient	Volume %
N-methyl pyrrolidone	33.3%
Dipropylene glycol	33.3%
Terpene alcohol	33.3%

The composition of Example 8 had a flashpoint in excess of 207° F., and exhibited little of the distinctive terpene odor. The composition of Example 8 utilized the Tecnal Ltd. alcohol as the terpene alcohol.

Example 9

Ingredient	Volume %
n-methyl pyrrolidone	33.3%

-continued

Ingredient	Volume %
Dipropylene glycol	33.3%
Glidcol 95 (terpene hydrocarbon)	33.3%

5

Glidcol 95 is a commercially available terpene alcohol sold by Glidco Chemical. Glidcol 95 contains alpha terpinene, among other terpene hydrocarbons and terpene alcohols, and exhibits a flashpoint of between 180° F. and 195° F. depending upon the volatile impurities present. The flashpoint of Glidcol 95 may be increased to over 212° F. by increasing the temperature of the product to 200° F. for approximately five (5) minutes, sufficient time for the volatile impurities, including the alpha and beta pinenes, to be driven off. Example 9 was allowed to sit for more than six (6) months, and even then exhibited a flashpoint in excess of 212° F.

10

15

20

Commercially available terpene alcohols may contain a significant amount of terpene hydrocarbon impurities. The impurities include not only the alpha and beta pinenes, but also limonene, dipentene, terpinene, terpinolene, menthere, myrcene, sabinene, oneimene, thellandrene and mixtures thereof. The compositions of the invention require that the terpene hydrocarbon have no significant amount of these impurities, so that the flashpoint is high and there is little or no trace odor.

25

30

In the event a solvent formulation is used, such as Example 8, then I prefer that the solvents likewise have a relatively high flashpoint. According to the Condensed Chemical Dictionary, 1956 Edition, Reinhold Publishing Company, n-methyl pyrrolidone has a flashpoint of 204° F. and dipropylene glycol has a flashpoint of 280° F.

35

Those skilled in the art will recognize that the terpene alcohols may themselves be used to remove grease and other contaminants from various materials, such as steel. The terpene alcohol, without solvents and surfactants, may be contained within a tank into which the material to be cleaned is placed. Heating of the terpene alcohol may not be needed, depending upon the application, although because of the high flashpoint, heating may be useful. Should the terpene alcohol bath become too concentrated with dissolved grease, then the bath may be disposed of or the grease separated from the alcohol by various means, including membrane filtration.

40

45

While this invention has been described as having a preferred design, it is understood that it is capable of further modifications, uses and/or adaptations of the invention, following the general principle of the invention and including such departures from the present disclosure has come within known or customary practice in the art to which the invention pertains, and as may be applied to the central features hereinbefore set forth, and fall within the scope of the invention of the limits of the appended claims.

50

55

I claim:

1. A non-combustible solvent composition comprised of:

- a) at least a first solvent other than terpineol having a flashpoint in excess of 200° F; and
- b) admixed with said first solvent an effective amount for solvent purposes of terpineol containing no significant amount of alpha and beta pinene wherein the flashpoint of said terpineol is at least about 212° F.

60

65

2. The composition of claim 1 wherein:

a) said first solvent is miscible in water.

3. The composition of claim 1, wherein:

a) a second solvent other than terpineol or said first solvent having a flashpoint in excess of 200° F. is admixed with said terpineol.

4. The composition of claim 3 wherein:

a) each of said first and second solvents is soluble in water.

5. The composition of claim 3 wherein:

a) each of said first and second solvents is an organic material.

6. The composition of claim 5 wherein:

a) one of said solvents is n-methyl pyrrolidone and the other of said solvents is dipropylene glycol.

7. The composition of claim 3 wherein:

a) said first and second solvents and said terpineol are each present in the composition in equal volume percentages.

8. The composition of claim 1, wherein:

a) said terpineol has been devolatilized by heating to and being maintained for a sufficient time at a temperature sufficient to drive off any significant amount of alpha and beta pinene.

9. A non-combustible industrial solvent, comprising:

a) first and second organic solvents, other than terpineol each said organic solvent having a flashpoint in excess of 200° F.; and

b) an effective amount for solvent purposes of terpineol admixed with said solvents and containing no significant amount of alpha and beta pinenes so that the flashpoint of said terpineol is at least about 212° F.

10. An industrial solvent of claim 9, wherein:

a) each of said organic solvents is miscible in water.

11. An industrial solvent of claim 9, wherein:

a) there is an equal volume percentage of each of said organic solvents in the non-combustible industrial solvent.

12. An industrial solvent of claim 11, wherein:

a) each of said organic solvents are present in the non-combustible industrial solvent in a volume percentage equal to the volume percentage of said terpineol.

13. An industrial solvent of claim 9, wherein:

a) said terpineol contains from about 95% by volume to about 100% by volume of said terpineol.

14. An industrial solvent of claim 9, wherein:

a) said first solvent is n-methyl pyrrolidone and said second solvent is dipropylene glycol.

15. A high flashpoint water soluble composition, comprising:

a) a solvent system other than terpineol miscible in water and having a flashpoint in excess of 200° F.; and

b) an effective amount for solvent purposes of terpineol containing no significant amount of alpha and beta pinenes and having a flashpoint of at least about 212° F.

16. A water soluble composition of claim 15, wherein:

a) said solvent system comprises a blend of at least two organic solvents.

17. A water soluble composition of claim 16, wherein:

a) each of said solvents is present in a volume percentage equal to the volume percentage of said terpineol.

18. A water soluble composition of claim 17, wherein:

11

a) one of said solvents is n-methyl pyrrolidone and the other of said solvents is dipropylene glycol.

19. A method of removing grease and soluble contaminants from articles, comprising the steps of:

a) providing an article having a contaminant thereon; 5
and

b) removing the contaminant by applying to the con-

12

taminant a sufficient quantity of a terpineol which has no significant amount of alpha and beta pinene so that the flashpoint of said terpineol is at least about 212° F.

* * * * *

10

15

20

25

30

35

40

45

50

55

60

65