



US005564977A

# United States Patent [19]

[11] Patent Number: **5,564,977**

Algie

[45] Date of Patent: **Oct. 15, 1996**

[54] **INTEGRATED RACETRACK DISPLAY SYSTEM INCLUDING DISPLAY OF PERIODIC PARIMUTUEL DATA**

4,032,946	6/1977	Wakatsuki et al. ....	364/412
4,951,039	8/1990	Schwendeman et al. ....	273/86 R
5,212,636	5/1993	Nakazawa .....	364/412
5,275,400	1/1994	Weingardt et al. ....	273/274
5,411,258	5/1995	Wilson et al. ....	364/412
5,476,259	12/1995	Weingardt .....	273/138 A

[75] Inventor: **Robert Algie**, Allandale, Australia

[73] Assignee: **Trans-Lux Corporation**, Norwalk, Conn.

### FOREIGN PATENT DOCUMENTS

2028554	3/1980	United Kingdom .....	273/138 A
2229565	9/1990	United Kingdom .....	273/138 A

[21] Appl. No.: **295,983**

[22] Filed: **Aug. 25, 1994**

[51] Int. Cl.<sup>6</sup> ..... **G06G 7/48**

[52] U.S. Cl. .... **463/25; 463/30; 463/40; 463/41; 463/42**

[58] **Field of Search** ..... 273/138 R, 433, 273/434, 439, 138 A, 139, 274; 370/77; 364/412, 411; 340/323 R; 463/25, 30, 40-42

### OTHER PUBLICATIONS

IEEE Spectrum, Jul. 1994, "Higher Visibility for LEDs" picture, p. 33.

*Primary Examiner*—Jessica Harrison

*Assistant Examiner*—Mark A. Sager

*Attorney, Agent, or Firm*—Kane, Dalsimer, Sullivan, Kurucz, Levy, Eisele and Richard, LLP

### [56] References Cited


#### U.S. PATENT DOCUMENTS

2,081,822	5/1937	Kimbell .....	340/323 R
3,124,674	3/1964	Edwards et al. ....	364/412
3,327,292	6/1967	Eriksson et al. .	
3,505,646	4/1970	Affel, Jr. et al. ....	364/412
3,513,440	5/1970	Wells .....	340/323 R
3,594,762	7/1971	Gardberg et al. ....	340/323 R
3,697,698	10/1972	Oswald et al. .	
3,810,627	5/1974	Levy .....	273/138 A

### [57] ABSTRACT

The apparatus relates to a display apparatus for a betting parlor associated with a racetrack or Totalizator company, including a display of a large amount of racing and parimutuel data, particularly periodic parimutuel or odds data and the history thereof. Subsequent display portions display fluctuating odds then successively lock as the start of the race approaches.

**14 Claims, 6 Drawing Sheets**



COL1	COL2	COL3
99.3	78.5	25.00
3.5	1.7	2.80
19.2	10.8	12.10
4.2	4.2	





FIG. 1

28



SYD/RCE	RANDWICK
FINE/FAST	1600m
RACE 2	DUE: 12:55
RACE 2 ABANDONED	

FIG. 2

<u>CLOTH NO.</u>	<u>HORSE NAME</u>	<u>BARRIER NO.</u>
01	KINGSTON TOWN	(02)
02	PHARLAP	(12)
03	PLAY OR PAY	(18)

30




FIG. 3

	COL1	COL2	COL3
JOCKEY'S NAME	99.3	78.5	25.00
JOCKEY'S NAME	3.5	1.7	2.80
JOCKEY'S NAME	19.2	10.8	12.10
JOCKEY'S NAME	4.2	4.2	

FIG. 4

FIG. 5

1	12	HE'S NO FOOL	3.75	2.00
2	1	PHARLAP		12.00
3	5	KINGSTON TOWN		3.50
QUINELLA	1-12			49.20
TRIFECTA	12 - 1 - 5			307.50
EXACTA	12 - 1			100.10
SCRATCHINGS	2 - 7 - 9			

FIG. 6

1	12	3.75	2.00
2	1	12.00	
3	5	3.50	
QIN	1-12	49.20	
TRI	12 - 1 - 5	307.50	
XTA	12 - 1	100.10	
SCR	2 - 7 - 9		

38

FIG. 7

SYD/RCE			
RACE 2			
1	12	3.75	2.00
2	1	12.00	
3	5	3.50	
QIN		49.20	
TRI		307.50	
XTA		100.10	
SCR	2,5,9		

FIG. 8



SYD/RCE D/D	
RACES 5 & 6	29.50
SP/DIV	7.30
SYD/RCE X/D	
RACES 3&4	149.80
SP/DIV	25.00

42

FIG. 9




FIG. 10




FIG. 11



# INTEGRATED RACETRACK DISPLAY SYSTEM INCLUDING DISPLAY OF PERIODIC PARIMUTUEL DATA

## BACKGROUND OF THE INVENTION

### 1. Field of the Invention

The invention relates to a display apparatus for a racetrack or for a betting parlor associated with a racetrack or Total-  
5 10 15 20

### 2. Description of the Prior Art

In the prior art, it is well known to display racing and  
15 20

In its pure form, parimutuel betting allows those holding  
25 30 35 40 45

Moreover, the more information given to a bettor  
45 50 55

## OBJECTS AND SUMMARY OF THE INVENTION

It is therefore an object of this invention to provide a large  
60

It is therefore a further object of this invention to provide  
65

It is therefore a still further object of this invention to  
5 10 15 20

These and other objects are achieved by a system with a  
25 30 35 40 45

## BRIEF DESCRIPTION OF THE DRAWINGS

Further objects and advantages of the invention will  
45 50 55

FIG. 1 is a block diagram schematic of the hardware of the  
60 65

FIG. 2 is an example of the race book header display  
70 75

FIG. 3 is an example of the horses board section display  
80 85

FIG. 4 is an example of the jockeys/odds display board of  
90 95

FIG. 5 is an example of the jockeys/odds display board of  
100 105 110

FIG. 6 is an example of the large formals display board of  
115 120

FIG. 7 is an example of the small formals display board  
125 130

FIG. 8 is an example of the historic results display board  
135 140

FIG. 9 is an example of the doubles display board of the  
145 150

FIG. 10 is an example of the clock display board of the  
155 160

FIG. 11 is a schematic of an alternative embodiment using  
165 170

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring now to the drawings in detail wherein like  
175 180 185 190

The heart of the integrated display system 10 is central  
195 200 205 210 215 220 225 230 235 240 245 250



figuration. The CPU 11 typically loads programs from the hard disk drive 12 or floppy disk drive 14 into RAM for execution. These programs include an operating system, display application programs, and a program to organize the parimutuel data as received from a racetrack (alternately, for on-site racetrack locations, a program will be included to calculate the various odds periodically prior to a race). CPU 11 further should include a system clock to trigger the program module responsible for the separation of data for processing to the various display boards. Of course, some variations from a pure parimutuel system are envisioned. Similarly, variations and upgrades in storage devices due to technological advances are envisioned.

Video display terminal 16, typically a color VGA screen, keyboard 18, typically a standard 101-key keyboard, and printer 20 (via parallel port 55) communicate with CPU 11 in a conventional manner. Similarly, CPU 11 is provided with an uninterruptible power supply (UPS) 22 which senses a power outage or other transient via serial port 54.

Additionally, for applications off-site from the racetrack, CPU 11 communicates with modem 24 via serial port 53 and decoder 26 via serial port 52. Modem 24 typically must be capable of communicating over standard phone lines at 9600 baud. Modem 24 is used to download all race details at the start of the day and as an avenue to log-on to the system from a remote site for troubleshooting purposes. This also allows the upgrading of software via the telephone lines. Presently, a "Netcomm SmartModem V.32 bis E7" is recommended for this application. Of course, numerous technically equivalent substitutions are available. Alternately, for applications on-site with the racetrack, CPU 11 communicates with the central parimutuel computer system via serial port 53 either directly or through modem 24.

Decoder 26 is an interface between the broadcast data and the CPU 11. The broadcast data typically originates at the facility where the race is taking place, is encoded, and is transmitted to remote betting parlors (e.g., off-track betting parlors) where the data is decoded by decoder 26 and fed to CPU 11. Decoder 26 typically communicates with CPU 11 using RS232 ASCII protocol via serial port 52. In Australia, the information is carried on a sideband of Channel 7 and its regional network stations.

Header display board 28 is driven by CPU 11. Header display board 28 is typically a "DataWall" Display Panel as manufactured by the assignee of the present application (an application using CRT screens will be described hereinafter). A typical header display board 28 would be 24 characters wide, four lines deep and made of 2.1 inch character blocks comprised of light-emitting diodes (LEDs). As shown in FIG. 2, the top line of header display board 28 typically displays the race code and track location. The second line displays the weather, the track rating, and the track distance. The third line displays the race number and the current race start time. The fourth line is used to display relevant messages (e.g., that the race has been cancelled).

Horses display board 30 is driven by CPU 11. Horses display board 30 is typically a "DataWall" Display Panel as manufactured by the assignee of the present application. A typical horses display board 30 would be 24 characters wide, 24 lines deep and made of 1.2 inch character blocks comprised of light-emitting diodes (LEDs). As shown in FIG. 3, horses display board 30 typically displays the saddle cloth number, the horse's name, and the gate number (i.e., "start barrier number" in Australian parlance) drawn for each horse. The data displayed on horses display board 30 typically does not change prior to a race. However, one update

to the horses display board 30 may be if a horse enters the line-up late. Of course, this configuration is applicable to racing animals other than horses, such as greyhounds.

Jockeys/odds display board 32 is driven by CPU 11 and can display in one of two modes—jockeys mode or odds mode as shown in FIGS. 4 and 5, respectively. Jockeys/odds display board 32 is typically a "DataWall" Display Panel as manufactured by the assignee of the present application. A typical jockeys/odds display board 32 would be 16 characters wide, 24 lines deep and made of 1.2 inch character blocks comprised of light-emitting diodes (LEDs).

The jockeys/odds display board 32 is the most dynamic of all of the display boards in display system 10 and is calculated to produce the most excitement at the betting facility. As shown in FIG. 4, when the race to be displayed is first transmitted to the display system 10, jockeys/odds display board 32 displays the names of all of the jockeys that are assigned to the relevant mounts. If a mount does not have a jockey assigned at the time of display, it is shown as "NOT DECLARED". The jockeys/odds display board 32 displays the jockeys' names until the odds are due for display.

The timing of the display of the odds (i.e., the second mode of the jockeys/odds display board 32 as shown in FIG. 5) is controlled by two factors, one being the race type and the second being the time between races. For instance, in Australia, in thoroughbred racing, races are typically run every thirty minutes (weekdays) to forty minutes (weekends); in harness racing, races are typically run every twenty to thirty minutes; and in greyhound dog racing, races are typically run every fifteen to twenty minutes. This requires that the jockey/odds display board 32 display odds at varying rates for the different race types.

The odds columns are typically displayed in the following time segments before race start time:

Race Type	Col. 1	Col. 2	Col. 3
Thoroughbred Racing	20 min.	10 min.	5 min.
Harness Racing	18 min.	10 min.	5 min.
Greyhound Racing	14 min.	7 min.	4 min.

The odds are displayed in the following manner. At a predetermined time prior to the scheduled start of a race, the CPU 11 receives the current parimutuel data from the data stream received via the decoder 26, extracts the current odds and displays the odds data on jockeys/odds display board 32. It firstly removes the display of the jockeys' names from the jockeys/odds display board 32, then the first column of odds (see "Col. 1" above) is displayed. This first column is dynamically updated as data is received. The odds displayed in the first column will fluctuate until the time prior to the race for the second column (see "Col. 2" above) is reached. The odds display in the first column is locked (that is, the odds at the time prior to the race for the first column is continuously displayed) and the second column then starts to display the fluctuating odds until the time prior to the race as display for the third column (see "Col. 3" above) is reached. The odds display in the second column is then locked and the third column then starts to display the fluctuating odds until the start of the race. After the race has started, the decoder 26 receives collated data with final pools and odds which are then displayed and the header display board 28 is updated to read "FINAL ODDS" where the race start time is otherwise displayed. The final odds are typically displayed for two minutes after the race has finished, so that the bettors ("punters") can see what, if anything, they will be paid. The integrated display system 10 then displays the next race and the cycle starts again.



The formals display board can be either the large formals display board **34** as illustrated in FIG. **6** or the small formals display board **38** as illustrated in FIG. **7**. The large formals display board **34** as illustrated in FIG. **6** is typically thirty-two characters wide by twelve lines deep with 1.2 inch character blocks and is typically a "DataWall" Display Panel as manufactured by the assignee of the present application. The small formals display board **38** as illustrated in FIG. **7** is typically twenty-four characters wide by eight lines deep with 1.2 inch character blocks and is typically a "DataWall" Display Panel as manufactured by the assignee of the present application. The formals display board **34** or **38** receives data via the CPU **11** and is used to display race results as soon as the results are received by decoder **26**. The instantaneous display of the results lets the bettors ("punters") know that the establishment is ready to pay on the winning bets. The difference between the two formals display boards other than size is that the large display **34** (FIG. **6**) shows the horses' names in addition to the actual odds paid. The last three lines of the large formals display board **34** can be used for sponsors' advertisements if these lines are not required for the display of race results. These lines may be required, however, if the race result is a "dead-heat" or a tie and more than one winner is displayed. The small formals display board **38** of FIG. **7** has no additional lines for advertising purposes.

The historic results display board **40** as shown in FIG. **8** includes two top rows of nine characters of 2.1 inches each and eight bottom rows of sixteen characters of 1.2 inches. While this is a custom display board, it is typically a "MenuWall" Display Panel as manufactured by the assignee of the present application. The "MenuWall" Display Panel stores data in pages and displays one result per page starting with the first race then in turn all other races until all the results have been displayed and the cycle starts again.

The doubles display board **42** as shown in FIG. **9** includes twelve lines of sixteen characters of 1.2 inches each and is typically another "MenuWall" Display Panel as manufactured by the assignee of the present application. The doubles display board is used to display the "Daily" and "Extra Doubles" for each meeting being run and includes sufficient space to display other information, if necessary, as received via decoder **26**.

The clock display board **44** as shown in FIG. **10** is a time piece in the form of a 60 column display, typically an "InfoDataWall" Display Panel as manufactured by the assignee of the present application. The time is regularly updated by CPU **11**, but, as a security measure, the time is ultimately controlled by the data stream received-via decoder **26** wherein a time stamp is included with each message.

As shown in FIG. **1**, the header display board **28**, the horses display board **30**, the jockeys/odds display board **32**, the formals display board **34** or **38** and the clock display board **44** (the first four of which are "DataWalls" and the fifth of which is treated as a "DataWall") communicate with the CPU **11** via the first RS232 serial port **50** at 9600 Baud, typically with 8 data bits, 2 stop bits and no parity. Similarly, the historic results display board **40** and the doubles display board **42** (both of which are "MenuWalls") communicate with the CPU **11** via the second RS232 serial port **51** at 2400 Baud with **13** pages, typically with 8 data bits, 2 stop bits and no parity.

Alternately, as shown in FIG. **11**, particularly for off-site betting parlor applications, the integrated display system may substitute CRT displays **60**, **61**, **62**, **63** for the various

LED displays **28**, **30**, **32**, **34** (or **38**), **40**, **42** and **44**. Due to the large amount of data to be displayed and the requirement for high resolution, twenty-seven inch VGA screens are typically used instead of standard television screens. Typically, one screen is assigned to each racetrack at the off-site betting parlor so that the bettors ("punters") can be informed of the action at several racetracks, with a single line LED display **66**, **67**, **68** or **69** (driven by CPU **11** via serial port **50**) over each screen to label or display the track name associated with the given screen.

The opening of the screen for the upcoming race, the VGA data screens will display:

Subheader information:

TAB Code  
Race Number  
Race Track  
Due Start Time  
Track & Weather Conditions

Main Data Screen information

Saddle Cloth Number  
Full Horse Name  
Gate Number ("Barrier Draw" in Australian parlance)  
Jockey's Name  
Jockey's Weight

At given time spacings, such as 20, 15, 10 and 5 minutes (this example includes four time periods rather than the three time periods for the LED based display), prior to the race, the jockeys' names and weights are replaced with odds (i.e., "TAB approximate dividends" in Australian parlance). There are typically four columns of Win odds ("approximates") and one column of place odds ("approximates"). In this configuration, the CPU **11** is fitted with a six stack video driver board **65**, which allows upgrading from four racetrack system displays to six racetrack system displays without computer hardware upgrades. The software of CPU **11** allows complete automated operation with minimal clerk intervention throughout both day and night events.

In off-site operation, modem **24** and/or decoder **26** receives frequent and periodic parimutuel data from a central source. In on-site operation, data is typically directly transmitted to CPU **11**. This data is organized by the CPU **11** and broadcast to the various display boards or CRT screens **60**, **61**, **62**, **63**. Importantly, the frequent changes of the various odds due to the parimutuel system is transmitted to the jockeys/odds board **32** as described hereinabove for display.

Thus the several aforementioned objects and advantages are most effectively attained. Although a single preferred embodiment of the invention has been disclosed and described in detail herein, it should be understood that this invention is in no sense limited thereby and its scope is to be determined by that of the appended claims.

What is claimed is:

1. An apparatus comprising:

- means for receiving a parimutuel data stream derived from a succession of racing events;
- means for selecting selected portions of the parimutuel data stream; and
- a display means in communication with said means for selecting, said displays means including at least first, second and third alphanumeric displays for each of a plurality of bets, said first, second and third alphanumeric display corresponding to a first, second and third sequential time intervals prior to a racing event, respectively, wherein said first sequential time interval ends prior to said second sequential time interval, said



7

second sequential time interval ends prior to said third sequential time interval and said third sequential time interval ends prior to start of the racing event;

said display means displaying said selected portions of the parimutuel data stream from said means for selecting:

a. during said first sequential time interval, said first alphanumeric displays display fluctuating updated parimutuel data as received from said means for selecting selected portions of the parimutuel data stream;

b. at times subsequent to said first sequential time interval, said first alphanumeric displays display constant parimutuel data as received from said means for selecting selected portions of the parimutuel data stream at a time equal to an end of said first sequential time interval;

c. during said second sequential time interval, said second alphanumeric displays display fluctuating updated parimutuel data as received from said means for selecting selected portions of the parimutuel data stream;

d. at times subsequent to said second sequential time interval, said second alphanumeric displays display constant parimutuel data as received from said means for selecting selected portions of the parimutuel data stream at a time equal to an end of said second sequential time interval;

e. during said third sequential time interval, said third alphanumeric displays display fluctuating updated parimutuel data as received from said means for selecting selected portions of the parimutuel data stream.

2. The apparatus of claim 1 wherein said display means comprises a plurality of light-emitting-diode arrays.

3. The apparatus of claim 1 wherein said display means is at least one CRT display.

4. The apparatus of claim 1 wherein said means for receiving a parimutuel data stream includes a modem.

8

5. The apparatus of claim 1 wherein said means for receiving a parimutuel data stream includes a decoder receiving television signals.

6. The apparatus of claim 1 wherein said means for receiving a parimutuel data stream includes a decoder receiving a sideband of a television signal.

7. The apparatus of claim 2 wherein said display means includes a first light-emitting-diode array for displaying jockeys' names and weights prior to said first time period in place of said display portions.

8. The apparatus of claim 7 wherein said display means further includes a second light-emitting-diode array for displaying results of a most recent race.

9. The apparatus of claim 8 wherein said display means further includes a third light-emitting-diode array for displaying results of a plurality of recent races.

10. The apparatus of claim 9 wherein said display means further includes a fourth light-emitting-diode array for displaying supplementary betting information.

11. The apparatus of claim 10 wherein said display means further includes a fifth light-emitting-diode array for displaying a plurality of data chosen from a group including race code, track location, weather, track rating, track distance, race number, and current race start time.

12. The apparatus of claim 11 wherein said display means further includes a sixth light-emitting-diode array for displaying a plurality of data for each race participant chosen from a group including saddle cloth number, name and gate number.

13. The apparatus of claim 12 wherein said display means further includes a seventh light-emitting-diode array for displaying the time.

14. The apparatus of claim 13 wherein the time displayed on said seventh light-emitting-diode array is controlled by the parimutuel data stream wherein a time stamp is included in each message in said parimutuel data stream.

\* \* \* \* \*