



US005591155A

United States Patent [19]

[11] Patent Number: **5,591,155**

Nishikawa et al.

[45] Date of Patent: **Jan. 7, 1997**

[54] **DISPOSABLE TRAINING PANT HAVING IMPROVED STRETCHABLE SIDE PANELS**

[75] Inventors: **Masaharu Nishikawa, Akashi; Keith W. Rollag, Ashiya, both of Japan; David M. Sageser, Cincinnati, Ohio; Jiro Yamada, Kobeshi, Japan**

[73] Assignee: **The Procter & Gamble Company, Cincinnati, Ohio**

[21] Appl. No.: **597,552**

[22] Filed: **Feb. 2, 1996**

Related U.S. Application Data

[63] Continuation of Ser. No. 338,609, filed as PCT/JP93/04036, Apr. 29, 1993, abandoned.

[30] Foreign Application Priority Data

May 22, 1992 [JP] Japan 4-155637

[51] Int. Cl.⁶ **A61F 13/16**

[52] U.S. Cl. **604/393; 604/385.2**

[58] Field of Search 604/393, 385.1, 604/385.2, 373

[56] References Cited

U.S. PATENT DOCUMENTS

4,205,679	6/1980	Repke et al.	128/287
4,355,425	10/1982	Jones et al.	2/402
4,610,680	9/1986	La Fleur	604/385
4,610,681	9/1986	Strohbeen et al.	604/396
4,619,649	10/1986	Roberts	604/396
4,641,381	2/1987	Heran et al.	2/400
4,690,681	9/1987	Haunschild et al.	604/396
4,710,189	12/1987	Lash	604/385
4,743,239	5/1988	Cole	604/385
4,743,241	5/1988	Igaue et al.	604/385

4,834,741	5/1989	Sabee	604/385.2
4,940,464	7/1990	Van Gompel et al.	604/396
5,021,051	6/1991	Hiuke	604/385.2
5,151,092	9/1992	Buell et al.	604/385.2
5,236,430	8/1993	Bridges	604/396
5,246,433	9/1993	Hasse et al.	604/396
5,358,500	10/1994	LaVon et al.	604/385.2

FOREIGN PATENT DOCUMENTS

0323040	5/1989	European Pat. Off.	604/385.1
0320991	6/1989	European Pat. Off.	604/385.1
0638304A1	2/1995	European Pat. Off.	A61F 13/64
0641552A1	3/1995	European Pat. Off.	A61F 13/15
1144674	3/1969	United Kingdom	A41B 9/04
2244909	12/1991	United Kingdom	A61F 13/15
WO93/17648	9/1993	WIPO	A61F 13/15
WO93/24085	12/1993	WIPO	A61F 13/15
WO94/28845	12/1994	WIPO	A61F 13/15
WO95/03765	2/1995	WIPO	A61F 13/15
WO95/06451	3/1995	WIPO	A61F 13/15

OTHER PUBLICATIONS

Zuikou, Incomplete Translation of Hei3-176 053 published Jul. 1991 pp. 1-7.

Primary Examiner—Robert A. H. Clarke
Attorney, Agent, or Firm—Kevin C. Johnson; Steven W. Miller; Jacobus C. Rasser

[57] ABSTRACT

The present invention provides a disposable training pant having an improved elasticized side panel which gives improved fit and comfort. The disposable diaper has an absorbent core chassis (30) and a pair of elasticized side panels (50) connected to the longitudinal sides of the chassis, where each side panel is formed of two elasticized laminate members (10), joined by a side seam along a non-elasticized outboard edge (52) of each member.

1 Claim, 5 Drawing Sheets




FIGURE 1.




FIGURE 2.




FIGURE 3.




FIGURE 4.




FIGURE 5.





FIGURE 6.



DISPOSABLE TRAINING PANT HAVING IMPROVED STRETCHABLE SIDE PANELS

This is a continuation of application Ser. No. 08/338,609, filed as PCT/JP93/04036 on Apr. 29, 1993, now abandoned.

FIELD OF THE INVENTION

The present invention related to disposable absorbent articles, more particularly to disposable absorbent diapers and incontinent products, and most particularly to disposable training pants and pull-on diaper. The invention is directed particularly to such articles and products, especially training pants, which have an elasticized side panel that provides the training pant with improved fit and comfort. As used herein, "training pant" includes also pull-on diapers comprising an absorbent core.

DESCRIPTION OF RELATED ART

Training pants have become popular, especially for use on toilet-training children. In the past some training pants have been made elastically extensible using elastic elements disposed in the training pants such that the waist opening and leg openings are at least partially encircled with elasticized bands. This method of using elastic elements is shown in U.S. Pat. No. 4,205,679 to Repke, et al.; U.S. Pat. No. 4,610,680 to LaFleur; U.S. Pat. No. 4,610,681 to Strohsen, et al.; U.S. Pat. No. 4,641,381 to Heran, et al.; U.S. Pat. No. 4,909,804 to Douglas, Sr.; and U.S. Pat. No. 4,960,414 to Meyer.

Another method of elasticizing disposable training pants is shown in U.S. Pat. Nos. 4,490,464; 4,938,753; and 4,938,757 all of which issued to Van Gompel, et al. These patents disclose a pant-like garment formed by attaching discrete stretchable members to the side edges of the main body of the garment. The discrete stretchable members are described as being made by stretching an elastic or stretchable layer to a selected elongation, placing a nonstretchable layer, such as a nonwoven, on the stretched layer, bonding the layers together, and allowing the layers to relax so that the nonstretchable layer is gathered.

Other methods for making a stretchable member is described in U.S. Pat. No. 4,107,364, issued to Sisson on Aug. 15, 1978, U.S. Pat. No. 4,209,563 issued to Sisson on Jun. 24, 1980, U.S. Pat. No. 4,525,407 issued to Ness on Jun. 25, 1985, U.S. Pat. No. 4,834,741 issued to Sabee on May 30, 1989, European Patent Publication 409,315. The Procter & Gamble Company, published Jan. 23, 1991, all hereby incorporated by reference.

Still other methods for making a stretchable member is described in U.S. patent application Ser. Nos. 07/662536, 07/662537, and 07/662543, each filed Feb. 28, 1991 and assigned to The Procter & Gamble Company. These references describe making an elasticized laminate by mechanically stretching a zero-strain stretch laminate web to impart the elasticity thereto in the direction of stretching, at least up to the point of initial stretching. An elongatable, non-elastic nonwoven layer is first bonded to a liquid-impervious elastic layer while in its relaxed state to form the laminate web. The laminate web is then fed between a pair of opposed pressure applicators, preferably ones having three-dimensional surfaces which are complimentary to a varying degree with one another, and subjected to incremental mechanical stretching (or nonuniform or sequential mechanical stretching, as desired), whereby the elongatable nonwoven is permanently elongated in the direction of stretching. When the mechani-

cal stretching is removed, the elastic layer will enable the laminate to return substantially to its pre-stretch shape and dimensions, thereby rendering the non-elasticized laminate elastically extensible in the direction of initial stretching.

While the elasticized zero-strain stretch laminates described above are useful for making elasticized, stretchable side panels for training pants, they are not completely satisfactory. The elongatable non-elastic nonwoven layer of the laminate can be torn at least partially along lines oriented in the machine direction of the web, and perpendicular to the direction of stretch. The at least partial tearing of the nonwoven can diminish the contribution of the nonwoven to the tensile strength of the laminate. Furthermore, the elastic layer itself generally has low tensile strength and low tear propagation resistance. This property can be problematic when the elasticized laminate is used as a side stretch panel on a training pant to achieve stretch in the lateral (front-to-back) direction of the training pant while being worn, since the lines of at least partial tearing of the nonwoven of the laminate are then oriented in the longitudinal (machine) direction. Further, since the side seam is most preferably made in the longitudinal (machine) direction of the training pant (in order to optimize manufacturing speed and efficiency), the side seam can partially tear prematurely (for example, while the child is active) along the seam where the process for forming the side seam itself can further damage to some extent either the nonwoven or the elastic layer of the laminate. or both, along one or more of the lines of at least partial tearing of the nonwoven.

SUMMARY OF THE INVENTION

Though the problem may be solved by various means, none are completely satisfactory. For example, additional materials could be added to or between the front and the back edge portions of the side panels to make the seam stronger and to reduce damage to the elastic layer. However, the inventors have found that the problem can be solved by modifying the method for making the elasticized laminate used to form the elasticized side panels. During the making of the elasticized laminate, discrete and spaced apart regions of the laminate which is fed between the opposed pressure applicators are subjected to no or reduced mechanical stretching. After the laminate has been mechanically stretched, it is cut along its width (in the direction of feeding) in the middle of the regions where no or reduced mechanical stretching occurred (hereinafter referred to as "non-stretched region"). The widths of laminate are then cut to the appropriate lengths for front and back elasticized members. The non-stretched region is used as the respective outboard edge portions of the front and back elasticized members which are then joined to form the side seam. Thus, the present invention provides a side seam that has substantially improved strength and tear resistance, and provides a training pant with elasticized side panels having improved side seam integrity.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic view of a training pant according to the present invention.

FIG. 2 is an explanatory view showing an apparatus for preventing contraction of a web used in the present invention.

FIG. 3 is an explanatory view showing the matching condition of upper corrugated rolls 60 and lower corrugated rolls 61 in the apparatus shown in FIG. 2.

FIG. 4 is an explanatory view showing how the web is cut into two elasticized members with an angle.

FIG. 5 is an explanatory view showing how the seat is attached to the elasticized members with an angle.

FIG. 6 is an explanatory view showing how the elasticized members are attached between the backsheet and the cuff.

DETAILED DESCRIPTION OF THE INVENTION

Practice of the present invention involves the making of a training pant **1** (FIG. 1) comprising the steps of: making of the elasticized members having a non-mechanically stretched outboard edge portion, making of the absorbent chassis, attaching the elasticized members to the edges of the absorbent chassis, and forming the side seam between the non-elasticized outboard edge portions of the elasticized members to form the training pant with elasticized side panels.

The elasticized members are generally made by: laminating into a laminate web at least one elongatable, non-elastic nonwoven layer with an elastic layer while in its relaxed state; mechanically stretching portions along the width of the laminate web to impart elasticity thereto in the direction of stretching, at least up to the point of initial stretching, thereby leaving other regions of non-elasticized stretched laminate; and cutting the resultant elasticized laminate web along its width and its length to form the individual front waist area and back waist area elasticized members of the side panel.

The absorbent chassis is generally made by placing an absorbent core between a liquid-impervious backsheet and a liquid-pervious topsheet. The absorbent chassis of the present invention is generally of a rectangular shape, having side edges and end edges, and a front and a back waist area.

The elasticized members are then attached along the side edges in the front waist area and the back waist area of the chassis, so that a portion of the non-mechanically stretched region of the elasticized member is the outboard edge portion thereof.

Finally, the absorbent chassis with the elasticized members attached is folded at approximately the longitudinal center, bringing the body-side face (topsheet face) of the front waist area into proximity with the body-side face of the back waist area. The body side surfaces of the non-mechanically stretched edge portions of the opposed elasticized members attached to the front and back waist areas are then joined with a heat seal, thereby completing the training pant.

An elasticized member **10** is generally made by: laminating into a laminate web **11** at least one elongatable, non-elastic nonwoven layer **12** with at least one elastic layer **13** while both are in their relaxed state: mechanically stretching portions along the width of the laminate web **11** to impart elasticity thereto in the direction of stretching, at least up to the point of initial stretching, thereby leaving other regions of non-elasticized laminate: and cutting the resultant stretch laminate web **14** along its width and along its length, to form the individual front waist area and back elasticized members **10** of the side panel **5**.

A typical example of the elongatable, non-elastic nonwoven layer **12** comprises a hydrophobic, nonwoven carded web having a basis weight in the range of about 30–37 grams per square meter and comprised of approximately 1–5 denier fibers, available from Hercules, Inc., U.S.A.

The elastic layer **13** can be liquid pervious or liquid impervious, such as with a spunbonded polymeric non-

woven or a plastic film. A typical example of the elastic layer **13** comprises a polyurethane having a no-load caliper or thickness of approximately 0.045 mm (2 mil). An example includes DS-320C made by Japan Synthetic Rubber K.K.

The non-elastic nonwoven layer and the elastic layer are brought together and bonded to form the laminate **11**. The adhesive to bond the layers can be applied as a uniform continuous layer of adhesive, a patterned layer of adhesive, or an array of separate lines, spirals, or slots of adhesive. In a preferred embodiment, the adhesive selected is stretchable and the glue applicator comprises a melt blown application system, such as Model No. GM-50-2-1-GH available from J&M Laboratories of Gainesville, Ga., U.S.A. employing a nozzle having 8 orifices per linear centimeter (20 orifices per linear inch), as measured in the cross-machine direction, each orifice measuring about 0.5 mm (0.020 inches) in diameter. A preferred adhesive is HM-6515 Hot Melt Adhesive, available from H. B. Fuller Company of St. Paul, Minn., U.S.A. The adhesive is heated to a temperature of about 170 degrees centigrade and applied at a rate of about 0.75–1.25 milligrams per square centimeter. Heated compressed air at a temperature of about 220 degrees centigrade and a pressure of about 2500 mm Hg gauge is issued through the secondary orifices in the nozzle to assist in uniform distribution of the adhesive fibrils during the laydown operation.

As generally shown in FIG. 2, the laminate **11** web is then mechanically stretched to provide along the width of the web regions **15** of elasticized laminate and regions **20** of non-stretched, non-elasticized laminate. Typically, a web of approximately 1 meter in width *W* is fed through the stretching apparatus at a time. An apparatus for mechanical stretching the zero-strain stretch laminate **11** can consist of upper corrugated rolls **60** and lower corrugated rolls **61** which are matched so that the respective corrugations can mesh (as further shown in FIG. 3). The region **15** of the web which has passed through and between the upper and lower corrugated rolls is mechanically stretched in the areas between the grooves **62** of the upper corrugated roll **60** and the grooves **63** of the lower corrugated roll **61**. The regions **20** of the web which has passed between side-by-side upper corrugated rolls **60** do not receive any mechanical stretching.

It is preferred to use a means of clamping the web just outside the respective regions of mechanical stretching in order to prevent the web from contracting in a direction parallel to the direction of stretching as the web passes between the meshed rolls. A suitable means of preventing such contraction is shown in FIG. 2, where compressible disks **65** having a slightly larger diameter than the diameter of the upper corrugated rolls **60** are mounted adjacent each side of the grooves portions of line upper corrugated rolls. The compressible disks tightly grip line web and hold it securely against the coinciding non-grooved portions **64** of the lower corrugated roll **61**.

In the present invention, the regions **15** of mechanical stretching and the regions **20** of non-stretching will alternate along the width of the web. The width of the region **15** to be mechanically stretched (shown as *X*) is selected based on the desired waist opening of the training pant and the degree of elasticity of the stretch laminate, as well as on how the processed web **14** is cut after stretching into the individual side elasticized members **10**. For example, the processed web **14** can be cut, such as with knives, along its width at approximately the center of each of the regions **20** of non-mechanical stretching. Then as shown in FIG. 4, each individual width of processed laminate can further be cut into half substantially in the center of the region of mechani-

cal stretching, and cut into individual lengths L along the length of the web, to form sets of first side **10a** and second side **10b** elasticized members for attachment to the absorbent chassis and forming of the side seam. Depending on the size of the training pant to be made, the width X can be from 60–140 mm. For example, for a Large training pant intended for use by a child weighing from about 9–14 kg, the width X is about 70–100 mm, more preferably from 74–80 mm. In a particularly preferred embodiment, the width X is about 78 mm. Thus, after having cut the individual lengths of web in about the center of the region X, the width of the elasticized laminate portion **16** of an individual side elasticized member of this embodiment will be from about 30–70 mm. For the aforementioned Large training pant, the width X is from about 35–50 mm, more preferably from 37–40 mm, and particularly about 39 mm.

Preferably, the width of a region **20** of non-mechanical stretching of the web (shown as Y) will be from about 20–120 mm. For the aforementioned Large training pant, the width Y is about 20–60 mm, more preferably from 40–56 mm, and particularly about 50 mm. Since the web is cut in the center of the region Y in making the individual widths of web, the width of the non-mechanically stretched outboard edge portion **51** of the elasticized member is about 10–60 mm, and for the aforementioned Large training pant, Y is about 10–30 mm, more preferably from 20–28 mm, and particularly about 25 mm.

Preferable the length L of each elasticized member is from about 50–190 mm. As with the other dimensions of the elasticized members, the length L selected will depend on the size of the intended wearer, and fit and comfort considerations. For the aforementioned Large training pant, the length L is from about 80–170, more preferably from about 100–160 mm.

The absorbent chassis **30** is generally made by placing an absorbent core **31** between a liquid-impervious backsheet **32** and a liquid-pervious topsheet **33**. The absorbent chassis of the present invention is generally of a rectangular shape, having side edges **35a**, **35b** and end edges **36a**, **36b**, and a front waist area **40** and a back waist area **41**.

The absorbent core **31** can be any absorbent means which is generally compressible, conformable, non-irritating to the wearer's skin, and capable of absorbing and retaining liquids such as urine and other certain body exudates. The absorbent core has a garment surface, a body surface, side edges, and waist edges. The absorbent core may be manufactured in a wide variety of sizes and shapes (e.g., rectangular, hourglass, "T"-shaped, asymmetric, etc.) and from a wide variety of liquid-absorbent materials commonly used in disposable diapers and other absorbent articles such as comminuted wood pulp which is generally referred to as airfelt. Examples of other suitable absorbent materials include creped cellulose wadding, meltblown polymers including cross-linked cellulosic fibers, tissue including tissue wraps and tissue laminates, absorbent foams, absorbent sponges, superabsorbent polymers, absorbent gelling materials, or any equivalent material or combinations of materials. The configuration and construction of the absorbent core may also be varied (e.g., the absorbent core may have varying caliper zones, a hydrophilic gradient, a superabsorbent gradient, or lower average density and lower average basis weight acquisition zones; or may comprise one or more layers or structures). The total absorbent capacity of the absorbent core should, however, be compatible with the design loading and the intended use of the diaper. Further, the size and absorbent capacity of the absorbent core may be varied to accommodate wearers ranging from infants through adults.

In one embodiment of the present invention, the absorbent core **31** comprises two distinct webs or layers comprising an acquisition/distribution core and a storage core (neither shown). The acquisition/distribution core is positioned between the topsheet and the storage core, and the storage core is positioned between the acquisition/distribution core and the backsheet. The acquisition/distribution core has a top surface area which preferably is from 15%–170% of the top surface area of the storage core. The acquisition/distribution core is preferably positioned relative to the storage core so that none of its surface area extends beyond the boundaries of the storage core. The acquisition/distribution core preferably comprises a web of chemically stiffened cellulosic fibers, although binding means such as non-stiffened cellulosic fibers, synthetic fibers, chemical additives, and thermoplastic fibers can be added to increase the physical integrity of the web. The storage core preferably comprises an airlaid web of superabsorbent material and fiber material, preferably airfelt. Optionally, and most preferably, a pervious sheet (e.g., a tissue sheet) or other scrim may be positioned between the acquisition/distribution core and the storage core to increase the integrity of the absorbent core during processing and/or use.

The acquisition/distribution core serves to quickly collect discharged body fluids, to quickly transport the fluid from the point of initial contact to other parts of the acquisition/distribution core, and to temporarily hold such discharged body fluids until they can be absorbed by the storage core. The distribution function of the acquisition/distribution core is of particular importance in order to more fully utilize the capacity of the storage core. Thus, while the acquisition/distribution core may comprise a wide variety of absorbent materials, it preferably comprises fiber material that can rapidly transport fluid and not collapse upon being wetted so that the acquisition/distribution core can effectively acquire and distribute second and successive voids of fluid as well as utilize a minimal amount (<2%) of superabsorbent material (due to the slowness of their uptake and gel blocking).

The backsheet **32** is impervious to liquids (e.g., urine) and is preferably manufactured from a thin plastic film, although other flexible liquid impervious materials may also be used. As used herein, the term "flexible" refers to materials which are compliant and will readily conform to the general shape and contours of the human body. The backsheet prevents the exudates absorbed and contained in the absorbent core from wetting articles which contact the diaper such as bedsheets and undergarments. The backsheet may thus comprise a woven or nonwoven material, polymeric films such as thermoplastic films of polyethylene or polypropylene, or composite materials such as a film-coated nonwoven material. Preferably, the backsheet is a thermoplastic film having a thickness of from about 0.012 mm (0.5 mil) to about 0.051 mm (2.0 mils).

The backsheet **32** is positioned adjacent the garment surface of the absorbent core and is preferably joined thereto by attachment means such as those well known in the art. For example, the backsheet may be secured to the absorbent core by a uniform continuous layer of adhesive, a patterned layer of adhesive, or an array of separate lines, spirals, or spots of adhesive. Adhesives which have been found to be satisfactory are manufactured by Century Adhesives, Inc. of Columbus, Ohio and marketed as Century 5227; and by H. B. Fuller Company of St. Paul, Minn. and marketed as HL-1258. The attachment means will preferably comprise an open pattern network of filaments of adhesive as is disclosed in U.S. Pat. No. 4,573,986 entitled "Disposable Waste-Containment Garment", which issued to Minetola

and Tucker on Mar. 4, 1986, and which is incorporated herein by reference. An exemplary attachment means of an open pattern network of filaments comprises several lines of adhesive filaments swirled into a spiral pattern such as is illustrated by the apparatus and methods shown in U.S. Pat. No. 3,911,173 issued to Sprague, Jr. on Oct. 7, 1975; U.S. Pat. No. 4,785,996 issued to Ziecker, et al. on Nov. 22, 1978; and U.S. Pat. No. 4,842,666 issued to Werenicz on Jun. 27, 1989. Each of these patents are incorporated herein by reference. Alternatively, the attachment means may comprise heat bonds, pressure bonds, ultrasonic bonds, dynamic mechanical bonds, or any other suitable attachment means or combinations of these attachment means as are known in the art.

The topsheet **33** is compliant, soft feeling, and non-irritating to the wearer's skin. Further, the topsheet **33** is liquid pervious permitting liquids (e.g., urine) to readily penetrate through its thickness. A suitable topsheet can be manufactured from a wide range of materials, such as porous foams; reticulated foams; apertured plastic films; or woven or nonwoven webs of natural fibers (e.g., wood or cotton fibers), synthetic fibers (e.g., polyester or polypropylene fibers), or a combination of natural and synthetic fibers. Preferably, the topsheet is made of a hydrophilic or a surfactant-treated hydrophobic material.

The topsheet **33** is positioned adjacent the body surface of the absorbent core and is preferably joined thereto and to the backsheet **32** by attachment means (not shown) such as those well known in the art. Suitable attachment means are described with respect to joining the backsheet to the absorbent core. As used herein, the term "joined" encompasses configurations whereby an element is directly secured to the other element by affixing the element directly to the other element, and configurations whereby the element is indirectly secured to the other element by affixing the element to intermediate member(s) which in turn are affixed to the other element. In a preferred embodiment of the present invention, the topsheet and the backsheet are joined directly to each other in the diaper periphery and are indirectly joined together by directly joining them to the absorbent core by the attachment means.

The elasticized members **10** are then attached to the front waist area **40** and the back waist area **41** on each side edge **35a**, **35b** of the chassis, so that the non-mechanically stretched outboard edge portion **51** thereof is the distal edge. The inboard attachment edge **17** of the elasticized member **10** is preferably attached to the absorbent chassis **30** between the topsheet **33** and the backsheet **32** by means of an adhesive **18** applied to either surface, preferably both surfaces, of the inboard attachment edge **17**. The inboard attachment edge **17** of the elasticized member can alternatively be attached between the backsheet and other structures or layers of material in the chassis; for example, as shown in FIG. 6, between the backsheet and an inboard elasticized barrier leg cuff **55**. Generally, the width of the attachment edge **17** inserted and attached between the topsheet and backsheet is from about 5–20 mm, more preferably from about 10–15 mm. The adhesive can be applied in any effective means, such as continuously, intermittently, in either a straight or curved line, or in a swirl pattern.

Finally, the absorbent chassis **30** with the elasticized members **10** attached is mechanically folded at approximately the longitudinal center **42**, thereby bringing the body-side face **34** of the front waist area **40** into proximity with the body-side face of the back waist area **41**. The body-side facing surfaces of the outboard edge portions **51** of the opposed elasticized members **10** attached to the front

and back waist areas are then joined with a seal **52**, thereby forming an elasticized side panel **5** and completing the training pant. The seal **52** can be made parallel with the longitudinal side **35** of the absorbent chassis, or can be angled slightly, as shown in FIG. 5. The seal **52** is preferably made as thin as possible to minimize the width of the Side seam **50** formed. A preferred seal is a pressure bond seal which bonds together the elastic layers **13** of the respecting outboard edge portions **51** of the laminates. In a preferred method, the seal **52** is made by passing the outboard edge portions between a rotating anvil roll and a rotating pressure roll which typically exert about 1500–5000 kilograms force per square centimeter pressure on the laminae, thereby forming a line of seal **52** having a width generally from 1–10 mm, preferably from 2–5 mm. The bonding pattern can be continuous or intermittent, and straight, curved, or irregular. Preferably, a temperature below about 80 degrees centigrade is used. It is most preferred to operate the anvil and the pressure roll at their ambient temperature. A higher temperature can be used so long as it is well below the thermoplastic melting temperature of the material of the elastic layer and so long as the elastic layer itself is not damaged or weakened at such temperatures. Thus, the pressure, temperature, bond pattern and duration of application of the sealing means is selected to optimize the welding of the polymeric materials of the respective elasticized layer of the laminates without deteriorating the laminate or its components. The side seam **50** can also be made by other sealing means known in the art, including ultrasonic sealing, heat sealing, and combinations thereof.

After the side seam **50** is made, the excess material outside of the seal can be trim cut away along a line **53** outboard of the seal **52**. Further, portions of the side panels can be trim cut, particularly around the leg opening edge, to provide an improved fit and better comfort. The elasticized members **10** can be trim cut together immediately before or after seaming, or the front and back elasticized members can be trimmed separately prior to or after attachment to the absorbent chassis.

Optionally, the training pant of the present invention can comprise other features and structures commonly used in diapers and training pants. Such optional features include, but are not limited to: disposal tapes, elasticized waist and tummy panels in the back and front waist areas of the adsorbent chassis; elasticized outboard leg cuffs and elasticized inboard barrier leg cuffs, positioned generally along the sides of the absorbent chassis to partially surround and seal around the leg opening of the training pant; wetness indicators; and elasticized members in the crotch region of the absorbent chassis to provide better comfort, fit and containment of bodily exudates.

The effect of the present invention is to provide a training pant having elasticized side panels which have an improved side seam therein. The seam, such as one formed by a pressure sealing, is strong enough to remain sealed under ordinary use, yet can be easily torn by a person desiring to remove the training pant from the wearer, for example after the pant has been soiled.

We claim:

1. A disposable training pant comprising:

- 1) an absorbent chassis having side edges and a front and a back waist area, comprising:
 - a liquid-pervious topsheet,
 - a liquid-impervious backsheet, and
 - an absorbent core positioned between said topsheet and said backsheet; and

9

- 2) an elasticized side panel attached to and joining the front waist area and the back waist area along each longitudinal side of the absorbent chassis, said side panel being laterally stretchable, comprising:
a front elasticized member and a back elasticized member, each comprising:
(i) a non-elasticized laminate portion comprising at least one elongatable, non-elastic nonwoven layer

10

and at least one elastic layer, said non-elasticized laminate portion forming an outboard edge and (ii) an elasticized laminate portion; and
a side seam joining said outboard edges of said front elasticized member and said back elasticized member.

* * * * *