



US005771963A

United States Patent [19][11] **Patent Number:** **5,771,963****Blangetti et al.**[45] **Date of Patent:** **Jun. 30, 1998**[54] **CONVECTIVE COUNTERCURRENT HEAT EXCHANGER**

FOREIGN PATENT DOCUMENTS

[75] Inventors: **Francisco Blangetti; Vaclav Svoboda,**
both of Baden, Switzerland; **Harald**
Gerhard Fuchs, Lauchringen, Germany0080742 6/1983 European Pat. Off. .
1451270 1/1969 Germany .
3614180A1 11/1986 Germany .
4137946A1 5/1993 Germany .
1117803 6/1968 United Kingdom .[73] Assignee: **Asea Brown Boveri AG,** Baden,
Switzerland*Primary Examiner*—Allen J. Flanigan
Attorney, Agent, or Firm—Burns, Doane, Swecker &
Mathis, L.L.P.[21] Appl. No.: **746,937**[57] **ABSTRACT**[22] Filed: **Nov. 18, 1996**[30] **Foreign Application Priority Data**



Dec. 5, 1995 [DE] Germany 195 45 308.5

[51] **Int. Cl.⁶** **F28D 7/08**[52] **U.S. Cl.** **165/143; 165/157; 165/160;**
165/163[58] **Field of Search** 165/135, 143,
165/157, 160, 163[56] **References Cited**

U.S. PATENT DOCUMENTS

1,818,446 8/1931 Armacost 165/163 X
2,643,862 6/1953 Stelling 165/163 X
3,183,969 5/1965 Bell 165/163 X
3,651,789 3/1972 Giardina 122/32
3,749,160 7/1973 Vestre 165/143
4,899,814 2/1990 Price 165/163

A convective countercurrent heat exchanger comprises a nest of pipes (36) which is arranged in a cylindrical shell (35) and is equipped with ribbed pipes (37). The pipes through which a liquid flows are connected to a collector (33, 34). The shell is provided with a gas-inlet connection piece (31) and a gas-outlet connection piece (32). The nest of pipes (36), which is composed of a plurality of layered pipes, is mounted in a rectangular case (40). The pipes are provided in their straight parts (37) with welded-on ribs and are connected to one another by unribbed pipe bends (38). The pipe bends are accommodated in compartments (45) through which flow does not take place. The case (40) through which flow takes place opens on the outlet side (50) in a dome (51) which is delimited by the shell (35). The gas-outlet connection piece (32) is situated in the shell at that end of the annular chamber (44), enclosed by the shell and case, which is remote from the dome (51).

9 Claims, 4 Drawing Sheets




FIG. 1

FIG. 2




FIG. 3




FIG. 4





FIG. 5



CONVECTIVE COUNTERCURRENT HEAT EXCHANGER

BACKGROUND OF THE INVENTION

1. Field of the Invention

The invention relates to a convective countercurrent heat exchanger, essentially comprising a nest of pipes which is arranged in a cylindrical shell and is equipped with ribbed pipes, the pipes through which the liquid flows being connected on the inlet side and the outlet side by in each case one collector, which collectors penetrate the shell, and the shell being provided with in each case one gas-inlet connection piece and one gas-outlet connection piece.

2. Discussion of Background

The problems of convective heat exchange between a gas and a liquid are well known from the literature. The heat exchange process is decisively controlled by the gas phase, since this determines the thermal resistance of the chain. In order to counter this problem, structured surfaces, such as ribs, bumps or grooves, are used in the heat-exchange apparatuses on the side of the gas phase; such structured surfaces are known as extended surfaces.

Modern-day high-performance gas turbines operate with very high turbine inlet temperatures, which makes cooling of the combustion chamber, the rotors and the blades unavoidable. For this purpose, highly compressed air is generally drawn off at the compressor outlet. Since a very high proportion of the compressed air is used for the current conventional premixing combustion, on the one hand only a minimal amount of cooling air remains for cooling purposes. On the other hand, this air intended for cooling is, as a result of the compression, already very hot, for which reason preliminary cooling thereof is recommended. Cooling by means of water spraying (gas quenching) is known for this; with this method, however, the valuable heat of the cooling air, the proportion of which may be up to 20 MW in current machines, is only partially utilized. Consequently, it is recommended to use heat recuperators as part-flow coolers for the purpose of recooling, particularly if the gas turbine is operating in a combined gas/steam turbine process with waste-heat steam generation.

SUMMARY OF THE INVENTION

Accordingly, one object of the invention is to provide a novel convective countercurrent heat exchanger with a high level of thermodynamic utilization for high gas and liquid temperatures and high pressures. The specific thermohydraulic demands on this class of apparatuses are as follows: high gas inlet temperature between 300°–530° C., high pressure on the gas side between 20 and 35 bar, high pressure on the liquid side between 120 and 150 bar, low gas- and liquid-side pressure drops and relatively high heat-up range of the liquid of up to 200° C. for the purposes of heat recuperation.

According to the invention, this object is achieved by the fact

that the nest of pipes, which is composed of a plurality of layered pipes, has a rectangular cross section and is mounted in a rectangular case, which essentially comprises four outer case walls which are guided in the shell and form an annular chamber with the shell,

that the pipes between the two collectors form a closed coiled pipe and are provided in their straight parts with welded-on ribs,

that the pipe bends connecting the straight pipe parts are not provided with ribs and are accommodated on both sides

of the straight pipe parts in compartments through which the gas does not flow,

that the compartments are delimited in the longitudinal direction of the pipes by an outer and an inner case wall and extend over the entire height of the case through which flow takes place,

that the case through which flow takes place opens on the outlet side in a dome which is delimited by the shell,

and that the gas-outlet connection piece is arranged in the shell at that end of the annular chamber which is remote from the dome.

Using an apparatus of this kind, in which the concept of countercurrent guidance is realized, an optimum level of utilization of the operative temperature differences available is achieved. Depending on the performances required, which are expressed in heat-transfer surfaces of different sizes, a single-shell apparatus or a two-shell design in series arrangement may be used. This is particularly important in view of the fact that space requirement can play a decisive role when setting up and during maintenance.

In order to ensure good cooling of the shell, the new case design with inner closed flow conduction around the ribbed part of the pipes and with outer flow around the case by means of gas which has already been cooled is of major importance. The latter is also one of the important factors contributing to the operational reliability, which is to be regarded as high.

It is particularly beneficial if, in this connection, flow-diverting means are arranged in the annular chamber in the region of the case outlet. This measure makes it possible to prevent local overheating of the walls of the case around which gas flows.

When using an apparatus of this kind in a combined process, one of the advantages is to be regarded as the fact that valuable heat is completely retained for the process.

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete appreciation of the invention and many of the attendant advantages thereof will be readily obtained as the same becomes better understood by reference to the following detailed description when considered in connection with the accompanying drawings of an exemplary embodiment of the invention with reference to a combined gas/steam power station plant, wherein:

FIG. 1 shows a simplified circuit diagram of a combined gas/steam power station plant;

FIG. 2 shows a partial section through two coupled countercurrent heat exchangers in the transverse direction of the pipes;

FIG. 3 shows a partial section through a countercurrent heat exchanger in the longitudinal direction of the pipes;

FIG. 4 shows a cross section through an exchanger;

FIG. 5 shows a bottom view of the arrangement according to FIG. 2.

DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring now to the drawings, wherein like reference numerals designate identical or corresponding parts throughout the several views, only the elements which are essential for understanding the invention are shown and the direction of flow of the operating media is indicated by arrows, in FIG. 1, in the gas turbine circuit, fresh air drawn in from the atmosphere is compressed in a compressor 2 to

3

the operating pressure. The compressed air is heated strongly in a combustion chamber **3**, which is fired, for example, with natural gas, and the combustion gas formed in this way is expanded in an energy-producing manner in a gas turbine **4**. The energy obtained in the process is delivered to a generator **5** or the compressor **2**. The still hot exhaust gas of the gas turbine is fed from the output of the gas turbine, via a line **6**, to a waste-heat steam generation plant **7** and, from there, after giving up its heat, is discharged into the open via a stack (not shown).

A three-stage steam turbine **9, 10** and **11** is arranged in the steam turbine circuit on a common shaft with the gas turbine. The operating steam expanded in the low-pressure steam turbine **11** condenses in a condenser **13**. The condensate is conveyed by means of a condensate pump **14** directly into the steam generator **7**. The plant shown does not have a low-pressure preheater, generally heated by tapped steam, a feed-water container or a high-pressure preheater.

The waste-heat steam generation plant **7** is designed as an upright boiler and, in the present case, operates by a two-pressure steam process.

The low-pressure system is designed as a circulation system with drum, a forced-circulation system having been selected here. It comprises, in the flue-gas path of the boiler, the low-pressure preheater **15**, into which the condensate is introduced, the low-pressure evaporator **16** and the low-pressure superheater **19**. The low-pressure evaporator is connected to the drum **17** via a circulation pump. The superheated steam is transferred, via a low-pressure steam line **25**, into a suitable stage of the low-pressure steam turbine **11**.

The high-pressure system is designed as a once-through system and can thus be configured for both subcritical and also for supercritical parameters. It comprises, in the flue-gas path of the boiler, essentially the high-pressure preheater **21**, the high-pressure evaporator **22** and the high-pressure superheater **23**. The operating medium is fed to the high-pressure preheater **21** from the low-pressure drum **17** via a feed pump **20**. In this way, the previously customary feed-water container can be dispensed with. The superheated steam is transferred via a fresh-steam line **24** into the high-pressure part **9** of the steam turbine. Between the outlet of the latter and the inlet of the medium-pressure turbine **10**, the partly expanded steam is reheated in an intermediate superheater **26**.

For the air which is used for cooling purposes, an air line **27** branches off from the outlet of the compressor **2** to a part-flow cooler **28**, which in this example is of two-part design. From the air-outlet connection piece of this cooler, the cooled air passes via a cooling line **29** to the various consumers. On the water side, the part-flow cooler is connected via the lines **1** and **8** to the low-pressure drum **17** of the waste-heat steam generation plant **7**.

This part-flow cooler **28**—referred to below as counter-current heat exchanger and explained in more detail with reference to FIG. **2**—is a so-called duplex apparatus, which operates in series arrangement with the following internal connections: the gas-outlet connection piece **32** and the inlet-side liquid collector **33** of a first heat exchanger **30** are therefore connected to the gas-inlet connection piece **131** and the outlet-side liquid collector **134**, respectively, of a second heat exchanger **130**.

In the following text, the gas is referred to as air and the liquid as water. Accordingly, the air line **27** depicted in FIG. **1** leads to the air-inlet connection piece **31** of the first heat exchanger **30** and the cooling line **29** branches off from the

4

air-outlet connection piece **132** of the second heat exchanger **130**. Furthermore, the inlet-side water collector **133** of the second heat exchanger **30** is fed from the line **1** (by means of a circulation pump, not shown in FIG. **1**), and the heated water is conveyed back into the drum **17** from the outlet-side water collector **34** of the first heat exchanger **30** via the line **8**.

The countercurrent heat exchanger depicted in the right-hand half of FIG. **2** and in FIGS. **3** and **4** has a cylindrical shell **35** surrounding the transfer surfaces, which shell is in practice surrounded by an outer insulation (not shown). The shell is curved at its upper and its lower ends.

The nest of pipes **36** comprises a multiplicity of pipes arranged in layers next to one another, which pipes form closed coiled pipes. A coiled pipe of this kind comprises a number of straight pipes **37** which are arranged above one another in the direction of flow of the air and are welded to one another at their two ends by means of pipe bends **38**. Due to the fact that the pipes arranged in layers next to one another are all of the same length, the nest **36** has a rectangular cross-sectional shape. The number of pipes arranged in layers next to one another is advantageously matched to the pipe length such that an at least approximately square shape is produced, which can be inserted in the cylindrical shell in a favorable manner.

Collectors, to which the coiled pipes are welded at their two ends, are arranged above and below the nest. In the present case of an upright apparatus **30**, the water passes from the top to the bottom, i.e. from the inlet-side collector **33**, through the piping, to the outlet-side collector **34**. The two collectors penetrate the shell **35** in a suitable manner for the purpose of connection to the associated supply and discharge lines. In the respective plane of the collectors **33, 34**, the shell **35** is provided with access openings **55** which are welded closed by caps **54**. Since the supply temperature of the air can be very high, the lower, outlet-side water collector **35** is, moreover, heat-insulated by means of an annular shield **53**, at least in that region in which it is exposed to the flow field of the air.

The straight pipes **37** are ribbed pipes, in the case of which ribs, generally wound on in a helical manner, are continuously welded to the core pipe. At their two unribbed ends, they are provided with a weld seam preparation and lie in registers. Every two straight pipes **37** situated directly above one another are welded to one another on both sides by an unribbed pipe bend **38**. All the registers, arranged in storeys above one another, in which the straight pipes are mounted form a flow-limiting wall **39** in the longitudinal extent of the nest, which wall prevents the air from acting on the pipe bends **38**.

These flow-limiting walls **39** form the inner walls of a case **40**, which encloses the nest of pipes **36** over its entire length. The case is formed by two side case walls **41** running in the longitudinal direction of the pipes and two outer case walls **42** running transversely with respect thereto. The four walls **41, 42** are supported in the shell **35** by means of struts **43**. Together with the inner shell wall, the four case walls enclose an annular chamber **44**.

Compartments **45**, which extend over the entire height of the case, are thus formed between the two inner walls **39** and the associated outer walls **42**. The pipe bends **38** project into these compartments. The compartments are subdivided a number of times, over the height, by horizontal plates **49**, which are connected at regular intervals to the walls **39** and **42**. This measure prevents the development of a freely convective flow in the compartment, due to the consider-

ations that free convection changes into heat conduction with a sufficiently small enclosed cavity. The size of these cavities can therefore be defined by means of the number of plates **49**.

It can be seen that all the piping active for heat transfer is enclosed in the case. As a result, the countercurrent principle is ensured. Due to the fact that the unribbed bend part of the piping is situated in the side compartments, and moreover these compartments are subdivided by means of the plates, the flow bypasses, which could significantly impair the operation of the apparatus, are avoided.

At its lower curved end, the shell **35** has an opening for the air-inlet connection piece **31**. The latter is suspended in the shell via a thermal shield **46** (thermosleeve) and is connected to the air line **27** at its end projecting out of the apparatus. The transition from the circular inlet connection piece **31** to the rectangular nest cross section is made via a correspondingly configured adapter **47**. The latter is connected to the walls **39** and **41**, the insides of which limit the flow.

The nest of pipes **36** is subdivided in its longitudinal extent into a plurality of part-nests, which each have between them a pressure compensation chamber **48**. This modular construction with intermediate chambers additionally has several further advantages. In addition to the possibility of prefabricating part-nests, assembly is facilitated and space is present to desoot the piping, if this is necessary.

The case **40**, through which the air to be cooled flows from the bottom to the top, opens on the outlet side (**50**) in a dome **51** which is delimited by the shell **35**. In this dome, the now "cold" air is diverted and flows downward through the annular chamber **44**. In the process, it fulfills the extremely important function of cooling the shell. In order to make this measure still more effective, flow-diverting means **52**, in the form of simple deflector plates, may be arranged in the annular chamber **44** in the region of the case outlet. These plates are dimensioned and directed such that they impose a helical motion on the air flow, causing flow to take place around the whole shell wall. This air circulation is very important in order to prevent overheating of the externally insulated shell **35**, particularly in its lower part. During operation, the shell will assume at least approximately the temperature of the case walls, as a result of radiation and convection.

This also shows the importance of the case lining, as can be illustrated with reference to a numerical example. Assuming that the supply temperature of the air is about 500° C., the piping is designed, depending on the inflow temperature of the water, such that the air temperature at the case outlet **50** is about 240° C. The lining therefore also has the function, on the one hand, of reducing thermal radiation effects, which are of decisive importance at about 250° C., and, on the other hand, of reducing the convective heat transfer between case and shell. The shell will therefore approximately assume the temperature of the cooled air, i.e. about 240° C., which, with a corresponding configuration with favorable strength values—the assumed pressure of the air to be cooled is about 34 bar—, leads to a high operational reliability.

In view of these considerations, the air-outlet connection piece **32** is logically arranged in the shell **35** at that end of the annular chamber **44** which is remote from the dome **51**.

The duplex arrangement, shown in FIG. 2, of two apparatuses is based on the following consideration, for which it should be noted that the numerical values are given only by way of example, since they are dependent on all too numerous parameters:

In addition to the abovementioned inlet condition of the air to be cooled of 34 bar and 500° C., the amount of air is about 35 kg/sec. The water inlet temperature is about 155° C., the heat-up range of the water was set at 165° C., the water mass flow rate is 15.5 kg/sec. This requires, on the air side, a heat transfer surface of approximately 2000 m².

If the starting point is an apparatus whose shell diameter should not significantly exceed 2 m, and if an annular chamber **44** through which clear flow can take place is to be present, then the wall widths of the case are about 1200 mm.

If use is made of pipes having a 1" external diameter, a 1 3/4" rib diameter and 350 ribs/m, on the one hand the number of layered pipes in a bank of pipes can be obtained if the installation width of the pipes is taken into account. The number of banks of pipes to be staggered above one another can be obtained if the installation height of the banks of pipes, as well as that of the compensation chambers to be provided between the part-nests, is then taken into account. If the space required for the two curved shell ends and the water collectors is calculated in addition to this, it can easily be calculated that this produces an apparatus with a disproportionately great height.

This is where the idea of dividing the apparatus into two part-apparatuses connected in series comes in, the subdivision, for the reasons already stated, advantageously being carried out such that the air temperature at the interphase between the two part-apparatuses is about 240° C. This gives a water temperature of about 185° C. at the interphase of the apparatuses.

In design terms, then, the following solutions are recommended:

The air-outlet connection piece **32** of the first exchanger **30** and the air-inlet connection piece **131** of the second exchanger **130** are situated in a common plane, i.e. in this case at the same height. The cooled air thus flows through the annular chamber **144** of the second exchanger **130**, from the bottom to the top. It is diverted in the dome **151** and, via the case inlet **150** which is open at the top, flows through the second exchanger **130**, in countercurrent to the water. The operating medium leaves the apparatus, via the air-outlet connection piece **132**, as cooling air at a temperature of about 170° C. In the present case, the air is therefore cooled down by 330° C.

The inlet-side collector **33** of the first exchanger **30** and the outlet-side collector **134** of the second exchanger **130**, which are situated at the top at the same level, are designed as a single continuous component.

The inlet-side collector **133** of the second exchanger **130** is arranged at the same height as the outlet-side water collector **34** of the first exchanger **30**. In the case of upright apparatuses, the supply and discharge lines of the two collectors are preferably situated below the connection of the air-outlet connection piece **32** to the air-inlet connection piece **131**. As was already the case for the first part-apparatus, the shell **135** of the second exchanger is also equipped, in the region of the collectors **133** and **134**, with access openings **55** which are welded closed by caps **54**.

Since the water collectors **133** and **34** are situated at the same level, the associated feed **56** and the discharge **57** are expediently also placed in this plane. FIG. 5 shows a possible arrangement of these connections, which, despite the shell outer insulation (not shown), fit in between these shells.

Naturally, the invention is not limited to the exemplary embodiment shown and described. The novel apparatus design can in principle be used for all processes in which the

operating media involved are at high temperatures and even high pressures. They could even be used successfully as deheaters or as evaporators. Instead of the upright arrangement shown, the novel countercurrent heat exchanger could, of course, also be arranged horizontally.

Obviously, numerous modifications and variations of the present invention are possible in light of the above teachings. It is therefore to be understood that within the scope of the appended claims, the invention may be practiced otherwise than as specifically described herein.

What is claimed as new and desired to be secured by Letters Patent of the United States is:

1. A convective countercurrent heat exchanger, essentially comprising a nest of pipes (36) which is arranged in a cylindrical shell (35) and is equipped with ribbed pipes (37), the pipes through which the liquid flows being connected on the inlet side and the outlet side by in each case one collector (33, 34), which collectors penetrate the shell, and the shell being provided with in each case one gas-inlet connection piece (31) and one gas-outlet connection piece (32),

wherein the nest of pipes (36), which is composed of a plurality of layered pipes, has a rectangular cross section and is mounted in a rectangular case (40), which essentially comprises four outer case walls (41, 42) which are guided in the shell and form an annular chamber (44) with the shell,

wherein the pipes between the two collectors form a closed coiled pipe and are provided in their straight parts (37) with welded-on ribs,

wherein the pipe bends (38) connecting the straight pipe parts are not provided with ribs and are accommodated on both sides of the straight pipe parts in compartments (45) through which the gas does not flow,

wherein the compartments (45) are delimited in the longitudinal direction of the pipes by an outer (42) and an inner (39) case wall and extend over the entire height of the case (40) through which flow takes place,

wherein the case (40) through which flow takes place opens on the outlet side (50) in a dome (51) which is delimited by the shell (35),

and wherein the gas-outlet connection piece (32) is arranged in the shell at that end of the annular chamber (44) which is remote from the dome (51).

2. The countercurrent heat exchanger as claimed in claim 1, wherein the nest of pipes (36) is subdivided in its longitudinal extent into a plurality of part-nests which each have between them a pressure compensation chamber (48).

3. The countercurrent heat exchanger as claimed in claim 1, wherein the gas-inlet connection piece (31) is connected to the shell (35) via a thermal shield (46).

4. The countercurrent heat exchanger as claimed in claim 1, wherein the liquid-outlet collector (34), which is exposed to the hot gas flow, is surrounded by a thermal shield (53).

5. The countercurrent heat exchanger as claimed in claim 1, wherein flow-diverting means (52) are arranged in the annular chamber (44) in the region of the case outlet (50).

6. The countercurrent heat exchanger as claimed in claim 1, wherein the shell (35) is provided, in the planes of the collectors (33, 34), with access openings (55) which are welded closed by caps (54).

7. The countercurrent heat exchanger as claimed in claim 1 in series arrangement, in which the gas-outlet connection piece (32) and the inlet-side collector (33) of a first exchanger (30) are connected to the gas-inlet connection piece (131) and the outlet-side collector (134), respectively, of a second exchanger (130),

wherein the gas-outlet connection piece (32) of the first exchanger (30) and the gas-inlet connection piece (131) of the second exchanger (130) are situated in a common plane,

and wherein the inlet-side collector (33) of the first exchanger (30) and the outlet-side collector (134) of the second exchanger (130) are designed as a single continuous component.

8. The countercurrent heat exchanger as claimed in claim 7, wherein the feed (56) of the inlet-side collector (133) of the second exchanger (130) and the discharge (57) of the outlet-side collector (34) of the first exchanger (30) are situated between the shells (35, 135) of the two exchangers and are preferably arranged in a common plane, in the case of upright apparatuses preferably below the connection of the gas-outlet connection piece (32) of the first exchanger to the gas-inlet connection piece (131) of the second exchanger.

9. The use of a countercurrent heat exchanger as claimed in claim 1 in a combined gas/steam turbine process with waste-heat steam generation, the gas-inlet connection piece (31) being connected to the outlet of a gas-turbine compressor and the gas-outlet connection piece (132) being connected to a cooling air line (29), and the inlet-side and outlet-side collectors (133, 34) being connected to the steam-collecting drum (16) of a waste-heat steam generator (7).

* * * * *