



US005810306A

United States Patent [19]

[11] Patent Number: **5,810,306**

Hung et al.

[45] Date of Patent: **Sep. 22, 1998**

[54] SHAPE RETAINING FLEXIBLE CONNECTOR

[75] Inventors: **John Hung**, Quingpu, China; **Norman L. Matthew**, Highland Park; **Vince Alesi**, Bartlett, both of Ill.

[73] Assignee: **Custom Accessories, Inc.**, Niles, Ill.

[21] Appl. No.: **650,137**

[22] Filed: **May 17, 1996**

[51] Int. Cl.⁶ **F21M 3/18**

[52] U.S. Cl. **248/274.1; 248/160; 248/276.1; 362/419; 403/223**

[58] Field of Search **248/160, 104, 248/274.1, 276.1; 403/220, 223, 291; 362/285, 287, 419**

2,640,502	6/1953	Powers .	
2,723,426	11/1955	Pelley .	
2,759,765	8/1956	Pawley .	
3,168,274	2/1965	Street	248/160 X
3,266,059	8/1966	Stelle .	
3,534,389	10/1970	Bernard et al. .	
3,929,164	12/1975	Richter .	
4,238,816	12/1980	Merlo .	
4,305,560	12/1981	Ban .	
4,307,754	12/1981	Muratsubaki .	
4,367,967	1/1983	Albert, Jr. .	
4,393,728	7/1983	Larson et al.	248/160 X
4,463,779	8/1984	Wink et al. .	
4,692,850	9/1987	LeDoux .	
4,842,174	6/1989	Sheppard et al. .	
4,885,667	12/1989	Selden .	
4,912,612	3/1990	Giorgi .	
4,949,927	8/1990	Madocks et al.	248/276.1
5,263,646	11/1993	McCauley .	
5,442,528	8/1995	Vandenbelt .	
5,449,206	9/1995	Lockwood .	

[56] References Cited

U.S. PATENT DOCUMENTS

D. 282,011	12/1985	Fackert .	
314,440	3/1885	Eames .	
428,023	5/1890	Schoff .	
790,971	5/1905	Nicholls .	
809,977	1/1906	O'Brien .	
912,308	2/1909	Grimler	248/160
936,379	10/1909	Stevens	248/160
1,250,064	12/1917	Whims	248/160
1,255,577	2/1918	Berry .	
1,276,117	8/1918	Riebe .	
1,340,818	5/1920	Brinkman .	
1,731,322	10/1929	Riddle .	
1,783,278	12/1930	Brady .	
1,911,470	5/1933	Rosner .	
2,382,966	8/1945	Arens .	
2,510,198	6/1950	Tesmer	248/160 X

FOREIGN PATENT DOCUMENTS


921384	5/1947	France .	
854100	8/1952	Germany	248/160
2806037	8/1979	Germany	248/160
976640	12/1964	United Kingdom .	

Primary Examiner—Derek J. Berger
Attorney, Agent, or Firm—Dick and Harris

[57] ABSTRACT

A shape retaining flexible connector apparatus for supporting flashlights, lamps, etc., is provided. The shape retaining flexible connector apparatus includes a formable support member, one or more joint forming members associated with the support member and a cover member.

11 Claims, 1 Drawing Sheet






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

SHAPE RETAINING FLEXIBLE CONNECTOR

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to structures such as hoses, tubes, conduits, connectors and the like, which can be bent or formed into various shapes and which are configured to retain the bent shape until subsequently repositioned.

2. The Prior Art

Elongated conduit or tubular apparatus, having the characteristic of being bendable into a plurality of shapes and thereafter retaining the bent shape until subsequent repositioning, are known. Such apparatus are used for such diverse purposes as positioning a fluid conduit so that a flow of fluid exiting the conduit can be aimed in a particular direction, utilizing the flexible conduit as a support for other articles, such as lamps, mirrors, radios, fans, etc., so that the articles can be positioned in unusual or otherwise difficult locations. Such apparatus are often typically referred to as "goose neck" structures.

Some goose neck apparatus are formed through the provision of a helically wound metal tube, which may or may not include in combination, a helically wound coil. The construction of such a helically wound tube and/or coil permits a certain amount of flexibility and capacity for flexibly holding relatively large loads. Such structures are illustrated in LeDoux, U.S. Pat. No. 4,692,850 and Shepherd et al., U.S. Pat. No. 4,842,174. Such helically wound metal tube type structures can have the drawback that the amount of flexibility may be compromised in order to provide the requisite load carrying capacity.

Other types of goose neck structures are known which employ a succession of ball and socket joints. Such apparatus are can be used not only for the transport of fluids, but instead can also be used as support structures for lamps, fans, radios, magnifying lenses, etc. Examples of such ball and socket type goose neck supports may be found in Lockwood, U.S. Pat. No. 5,449,206.

However, such ball and socket type goose neck apparatus may have the drawback of being relatively complex and costly to manufacture and assemble. In addition, in certain ones of such ball and socket systems, such ball portions may pop out of their respective sockets if they are pivoted beyond a certain point.

It would be desirable to provide a flexible support having the capacity to retain its position when placed there until repositioned, yet is relatively easy and inexpensive to manufacture and assemble.

It would also be desirable to provide such a shape retaining flexible connector that is of relatively simple configuration. It would further be desirable to provide a shape retaining flexible connector that has both the capacity for substantial load bearing and high flexibility.

These and other objects of the invention will become apparent in light of the present specification and drawings.

SUMMARY OF THE INVENTION

The present invention comprises a shape retaining, flexible connector apparatus, operably configured to be positioned by a user into a plurality of positions for the facilitated support of one or more articles positioned thereon or proximate one or both of its ends thereby.

The shape retaining, flexible connector apparatus comprises an elongated, flexible, shape-retaining support mem-

ber. At least one joint forming member is disposed along the elongated, flexible, shape-retaining support member, for providing for the facilitated and controlled positioning of the support member. Means are provided for maintaining the at least one joint forming member in position along the support member. Means are also provided for attaching the one or more articles to the flexible connector apparatus.

In one embodiment of the invention, the flexible connector apparatus also comprises means for covering the support member and the at least one joint forming member, toward providing for the facilitated grasping and positioning of the support member. The covering means preferably comprises a flexible tube member.

In an embodiment of the invention, the at least one joint forming member comprises at least one substantially disk-shaped member, having an aperture extending therethrough, through which aperture the support member extends. The at least one substantially disk-shaped member preferably comprises a plurality of substantially disk-shaped members. The substantially disk-shaped members are positioned substantially adjacent one another along the support member. At least two adjacent ones of the plurality of substantially disk-shaped members have respective juxtaposed curved convex surfaces, configured so that upon flexing of the support member, the respective juxtaposed curved convex surfaces are capable of substantially engaging each other in relative rolling movement, to define a joint.

At least one of the substantially disk-shaped members is fabricated from a material which is softer than another material from which at least one other of the substantially disk-shaped members is fabricated.

The means for maintaining the joint forming members in position along the support member comprises a stop member, positioned at each end of the support member, for precluding the disk-shaped members from being removed from the support member.

The means for attaching the one or more articles to the flexible connector apparatus comprises at least one attachment member, affixed to at least one of the ends of the support member, and configured to engage at least one of the one or more articles.

The support member preferably comprises a metal wire.

The one or more articles is, in one embodiment of the invention, a lamp apparatus.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side elevation, partially in section, of the shape retaining flexible connector of the present invention.

FIG. 2 is an end elevation thereof.

FIG. 3 is a perspective view of a disk.

FIG. 4 is a side elevation thereof.

FIG. 5 is a perspective view of the end fitting for the shape retaining flexible connector.

DETAILED DESCRIPTION OF THE INVENTION

While this invention is susceptible of embodiment in many different forms, there is shown in the drawings and will be described in detail herein, a specific embodiment, with the understanding that the present invention is to be considered as an exemplification of the principles of the invention, and is not intended to limit the invention to the embodiment illustrated.

One embodiment of the flexible shape retaining coupler is illustrated in FIGS. 1-4. Shape retaining flexible coupler 10

includes a wire **13** which preferably in one embodiment of the invention is a heavy gauge wire fabricated from aluminum or copper or similar strong highly flexible and ductile metal, a wire fabricated from which can be repeatedly bent and straightened without failing from fatigue. Wire **13** preferably has a circular cross section, but may alternatively have a polygonal cross-section, or may have longitudinal grooves formed along its length. A fitting **16** is attached to each end of wire **13**. Any suitable manner of affixation of the wire **13** to fitting **16** may be employed. A preferred method is to affix each fitting **16** through the use of a nut **19** which is received within a recess **22** and configured to be threadably engaged with an end of wire **13**. Alternatively, the end **13A** of wire **13** can be enlarged or flattened by crimping or the like, so as to exceed the diameter of bore **37**. A corresponding method is likewise used proximate the other end of wire **13** to affix the other end of the wire **13** to a corresponding fitting **16**.

A plurality of spacer members **25**, **25'**, are positioned along wire **13**. Each spacer member **25** preferably is in the form of a disk (See FIG. **3** and FIG. **4**), having a substantially circular cross-section. However, other cross-sections, such as squares or polygons, may be used, if desired. Each disk **25** preferably has a substantially flat face **28** (as seen in side elevation) and a substantially rounded face **31**. Alternatively, the face opposite the flat face may be in the form of a shallow cone. In a still further alternative embodiment, one or both sides of each and every disk may be rounded or conical. Although each disk **25** may be formed as a completely solid article, in order to reduce weight and/or save material, each disk **25** may be molded, in at least a partially hollow manner, preferably from a plastic material, and having recesses **34**. Other materials may be used to form disks **25**, **25'**, including dense closed-cell foam, nylon, etc. Each disk **25** has a bore **37** extending completely there through. In the embodiment of FIGS. **1-4**, the disks **25** are arranged in alternating fashion along wire **13** so that successive pairs of disks have their flat faces **28** against one another. In a preferred embodiment of the invention, the pairs of disks **25** are positioned along wire **13** so that there is a minimum amount of free space between any given pair of disks. In an alternative embodiment, wire **13** is covered by one or more cylindrical foam members along the length of wire **13**, instead of disks **25** and **25'**.

A cover member **41**, preferably in the form of an outwardly ribbed or corrugated substantially cylindrical tube or bellows structure, and preferably fabricated from a durable yet flexible plastic material, is fitted over wire **13** and disks **25**, for covering the disks **25** and providing a cover over such internal components, a more uniform surface, and a more easily gripped surface. In an alternative embodiment, in which the disks have square or polygonal cross-sections, cover member **41** would similarly be preferably provided with a generally square or polygon cross-section. A portion of cover **41** has been shown in phantom in the illustration of FIG. **1** in order to more readily disclose the structure underneath. It is to be understood that in a preferred embodiment of the invention, cover **41** extends substantially the entire length of apparatus **10** from the fitting **16** at one end to the corresponding fitting **16** at the opposite end, although in other embodiments, the cover **41** may not extend the complete length of apparatus **10**, but instead may fall short of one or both of the ends. The pattern of ribs on cover member **41** is not limited to that illustrated, but should have a configuration which is simple to manufacture according to conventional plastic molding and/or extrusion techniques so as to provide a degree of substantially uniform flexibility

along its length, when apparatus **10** is either bent or straightened into a desired position. The material from which cover **41** is made should be a material having appropriate characteristics of suppleness, resilience and flexibility, such that when apparatus **10** is bent or straightened, creases (apart from those preformed corrugations), cracks, dimples and the like are substantially precluded, and the cover should be sized and configured so that it will not "creep" relative to the wire **13**.

Each fitting **16** comprises a shank **44** (preferably having a diameter which is approximately the same as that of threaded portion **50**) through which the wire **13** passes, a flange **47** (which may include tabs **48**) and a threaded portion **50**. Lengthwise, radially extending fins **45**, may be provided, as in the preferred embodiment of FIGS. **1-4**, extending from flange **47** to cup **26**, and extending radially outward a distance approximately the same as the radius of cup **26**, to provide strength to fitting **16** and/or to provide surfaces against which assembly tools may bear. As previously discussed, bore **22** is preferably formed in threaded portion **50** for receiving a nut to which wire **13** is threadably engaged, in the preferred embodiment. As stated, each fitting additionally includes a cup **26**, which has a concave surface which is configured substantially to nest conformably with the end most disk **25'**, at each end of apparatus **10**. At least one of the last two conjoining disks **25'** is preferably fabricated from a somewhat softer, preferably plastic, material than the remaining disks **25** which are interposed between the disks **25'**. This preferably softer material facilitates in the nesting and conforming of the cup **26** to the end most disk **25'**. This fitting occurs at a place of highest stress in the apparatus and accordingly some additional resiliency at the interconnection between the end most disk and the fitting **16** is believed to be advantageous, although not absolutely necessary for the functioning of the flexible connector.

Threaded portion **50** is provided to give a facilitated means of attachment of fitting **16** to an article **53** having a corresponding threaded portion **59** capable of securely receiving threaded portion **50**. Other forms of attachment, such as bayonet mounts, or snap-fit mounts, could also be used to attach fitting **16** to article **53**. Article **53** may be, for example, a flashlight unit, a fan, a radio, a television, a CD player, a mirror, a magnifying lens structure or any other device for which a flexible, yet shape-retaining, support may be desired. Moreover, the other end of coupler **10** may be similarly attached to a second such article **54** or a base.

The foregoing description and drawings merely serve to illustrate the invention and the invention is not limited thereto accept insofar as the appended claims are so limited, as those skilled in the art to have the disclosure before them will be able to make modifications and variations therein without departing from the scope of the invention.

We claim:

1. A shape retaining, flexible connector apparatus, operably configured to be positioned by a user into a plurality of positions for the facilitated support of one or more articles positioned thereon or proximate one or both of its ends thereby, the shape retaining, flexible connector apparatus comprising:

an elongated, flexible, shape-retaining support member, having a first and a second end and further having a longitudinal axis, a transverse axis and a vertical axis perpendicular thereto and configured for selectable flexible articulation into one of a plurality of positions between said longitudinal axis, said transverse axis and said vertical axis;

5

said support member being further configured for substantial maintenance of said one position, once positioned;

at least three joint forming members, disposed between said first and second ends of said shape-retaining support member along the longitudinal axis of the elongated, flexible, shape-retaining support member, for providing for the facilitated and controlled positioning of the support member;

means for maintaining the joint forming members in position along the support member; and

means for attaching the one or more articles to the flexible connector apparatus.

2. The flexible connector apparatus according to claim 1, further comprising means for covering the support member and the joint forming members for providing for facilitated grasping and positioning of the support member.

3. The flexible connector apparatus according to claim 2, wherein the covering means comprises a flexible tube member.

4. The flexible connector apparatus according to claim 1, wherein the joint forming members comprise substantially disk-shaped members, having aperture extending therethrough, through which apertures the support member extends.

5. The flexible connector apparatus according to claim 4, wherein the disk-shaped members of substantially are positioned substantially adjacent one another along the support member.

6. The flexible connector apparatus according to claim 5, wherein at least two adjacent ones of the substantially disk-shaped members have respective juxtaposed curved convex surfaces, configured so that upon flexing of the support member, the respective juxtaposed curved convex surfaces are capable of substantially engaging each other in relative rolling movement, to define a joint.

7. The flexible connector apparatus according to claim 4, wherein the means for maintaining the joint forming members in position along the support member comprises a stop member, positioned at each end of the support member, for precluding the disk-shaped members from being removed from the support member.

8. The flexible connector apparatus according to claim 1, wherein the means for attaching the one or more articles to the flexible connector apparatus comprises at least one attachment member, affixed to at least one of the ends of the support member, and configured to engage at least one of the one or more articles.

9. The flexible connector apparatus according to claim 1, wherein the support member comprises a metal wire.

6

10. A shape retaining, flexible connector apparatus, operably configured to be positioned by a user into a plurality of positions for the facilitated support of one or more articles positioned thereon or proximate one or both of its ends thereby, the shape retaining, flexible connector apparatus comprising:

an elongated, flexible shape-retaining support member; at least one joint forming member, disposed along the elongated, flexible, shape-retaining support member, for providing for the facilitated and controlled positioning of the support member;

means for maintaining the at least one joint forming member in position along the support member;

means for attaching the one or more articles to the flexible connector apparatus;

said at least one joint forming member comprising at least one substantially disk-shaped member, having an aperture extending therethrough, through which aperture the support member extends; and

the at least one substantially disk-shaped member is fabricated from a material which is softer than another material from which at least one other of the substantially disk-shaped members is fabricated.

11. A lamp apparatus, in combination with a shape retaining, flexible connector apparatus, operably configured to be positioned by a user into a plurality of positions for the facilitated support of one or more articles positioned thereon or proximate one or both of its ends thereby, wherein the shape retaining, flexible connector apparatus comprises:

an elongated, flexible, shape-retaining support member, having a longitudinal axis, a transverse axis and a vertical axis perpendicular thereto and configured for selectable flexible articulation into one of a plurality of positions between said longitudinal axis, said transverse axis and said vertical axis;

said support member being further configured for substantial maintenance of said one position, once positioned;

at least one joint forming member, disposed along the elongated, flexible, shape-retaining support member, for providing for the facilitated and controlled positioning of the support member;

means for maintaining the at least one joint forming member in position along the support member; and

means for attaching the one or more articles to the flexible connector apparatus.

* * * * *