



US005824961A

United States Patent [19]

[11] Patent Number: **5,824,961**

Burek et al.

[45] Date of Patent: **Oct. 20, 1998**

[54] **CENTRAL STRENGTH MEMBER ANCHOR FOR OPTICAL FIBER CABLES**

[75] Inventors: **Denis Edward Burek**, Cumming; **Marc Duane Jones**; **William H. Small**, both of Lithonia, all of Ga.

[73] Assignee: **Lucent Technologies Inc.**, Murray Hill, N.J.

[21] Appl. No.: **846,409**

[22] Filed: **Apr. 30, 1997**

[51] Int. Cl.⁶ **H01B 17/00**

[52] U.S. Cl. **174/135**; 174/92

[58] Field of Search 174/92, 93, 138 F, 174/135; 248/56, 65, 74.1, 74.4; 439/367, 465, 521, 687, 449; 138/158

[56] **References Cited**

U.S. PATENT DOCUMENTS

1,057,057	3/1913	Hoerr	248/65
3,779,494	12/1973	Nicholson et al.	248/56
3,875,325	4/1975	Anderson et al.	174/92
4,295,005	10/1981	Daugherty et al.	174/92
4,332,435	6/1982	Post	350/96.21
4,679,896	7/1987	Krafcik et al.	350/96.2
4,818,824	4/1989	Dixit et al.	174/92
5,097,529	3/1992	Cobb et al.	385/135
5,189,725	2/1993	Bensel, III et al.	385/135
5,370,345	12/1994	Condo	248/65
5,420,957	5/1995	Burek et al.	385/135
5,434,945	7/1995	Burek et al.	385/135
5,440,666	8/1995	Burek et al.	385/135

5,450,518	9/1995	Burek et al.	385/135
5,472,160	12/1995	Burek et al.	248/74.4
5,481,639	1/1996	Cobb et al.	385/135
5,519,804	5/1996	Burek et al.	385/135
5,679,927	10/1997	Hurkmans et al.	174/92

OTHER PUBLICATIONS

Simultaneous Voice and Data on the General Switch Telephone Network Using Framed QADM, IEEE Communications Magazine, Dec. 1996, By: Gordon Bremer, Paradyne Corp. and Ken Ko, Rockwell Semicon. Sys., pp. 58-63.


Primary Examiner—Kristine L. Kincaid

Assistant Examiner—Chau N. Nguyen

[57] **ABSTRACT**

A central strength member anchor for use, for example, in a splice closure, for anchoring the central strength member of a cable entrant into the closure has a planar member having at least one upstanding leg at one end thereof. The distal end of the leg has clamping a strength member receiving member having a bore into which the strength member is to be inserted. The receiving member has clamping arrangement, such as one or more set screws, for clamping the strength member in the bore. The height of the leg is such that the bore in the receiving member is substantially axially aligned with the cable strength member. The planar member has locating holes therein for locating the anchor in the closure, and side walls depending from the planar member have slots for mounting the anchor in the enclosure. The side walls also have at least one slit therein and the planar member is scored so that a portion of the anchor member may be broken off to shorten it.

23 Claims, 22 Drawing Sheets






FIG. 1




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 3A




FIG. 3B

FIG. 4A




FIG. 4B





FIG. 4E




FIG. 4C




FIG. 4D




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 5E




FIG. 6A




FIG. 6B




FIG. 6D




FIG. 6C




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 9A




FIG. 9B




FIG. 9C




FIG. 9D




FIG. 9E




FIG. 9F




FIG. 10A




FIG. 10B



FIG. 10C




FIG. 10D




FIG. 11




FIG. 12A




FIG. 12B




FIG. 12C




FIG. 12D




FIG. 13A




FIG. 13B




FIG. 13C




FIG. 13D




FIG. 14A




FIG. 14B



FIG. 14C




FIG. 14D




FIG. 14E




FIG. 15A




FIG. 15B




FIG. 15C




FIG. 16A




FIG. 16B




FIG. 16C



FIG. 16D




FIG. 16E




FIG. 17A




FIG. 17B




FIG. 17C



FIG. 18A




FIG. 18B




FIG. 19

CENTRAL STRENGTH MEMBER ANCHOR FOR OPTICAL FIBER CABLES

FIELD OF THE INVENTION

This invention relates to optical fiber cable splice closures and, more particularly, to a splice closure and components thereof which is capable of containing a large number of optical fiber splices and which is both low in cost and economical in installation and maintenance.

BACKGROUND OF THE INVENTION

Signal transmission through optical fibers has become, or is becoming, the dominant signal transmission mode. The bandwidth characteristics of optical fibers, as well as their relative immunity to certain types of interference and contaminants make them the desirable transmission medium in high capacity trunk lines as well as in lower capacity feeder and distribution lines.

No matter what the intended end use may be, individual optical fibers generally are combined in an optical fiber cable which contains a plurality of such fibers, each of which is protected by at least one layer of coating material. In one configuration, the fibers are assembled into groups which are held together by binder ribbons or tubes to form a cable core. This is generally enclosed in a metallic or plastic tube or jacket which, in the latter case, often contains a strength member. In another configuration, the fibers are arrayed in ribbon form and the core tube contains one or more stacked ribbons.

Regardless of the cable configuration, it is usually necessary that the lengths of fiber cable be spliced at their ends to the ends of other cables, which entails splicing each of the individual fibers in a cable to a corresponding individual fiber in the second cable. To this end, there is provided a splice closure which usually comprises a protective case which contains at least one splice tray which, in turn, has a plurality of splice holders mounted thereon, into which the encased individual fiber splices are inserted and held. The cables are entrant into the case and generally are clamped to each end thereof to reduce the effects of tensile forces on the cables and on the splices. Sufficient amounts of fiber slack must be provided for in the case, such as, for example, half a meter of fiber length so that the individual fibers can be pulled clear of the case to effect the splice. The slack also serves the important function of absorbing tensile forces, thereby isolating the splices from such forces. Because of the delicate and brittle nature of individual glass fibers, they cannot be crimped or bent too sharply, i.e., bent to too small a radius of curvature, which places restraints upon slack storage. Thus, there have been numerous arrangements in the prior art addressing the problem of fiber and slack storage, as exemplified by U.S. Pat. Nos. 5,097,529 of Cobb, et al.; 4,679,896 of Krafcik, et al.; and 4,332,435 of Post.

Inasmuch as, at the splice point, the cable itself is opened up and the base fibers are exposed, the only protection afforded the fibers is provided by the closure, which can provide only one or two layers of protection from the outside environment, the requirements therefor are more stringent than for the cable, which normally provides several layers of protection. The closure must anchor the cables stored therein, and it must be capable of withstanding torsional and axial loads transmitted by the cable to the closure so that the splices are protected from these loads. The closure must also seal the inner and outer sheaths of the cables and maintain the seal integrity under extreme environmental conditions. In addition, the closure must provide adequate fiber storage

for slack fiber without damaging the fibers and without increasing signal attenuation. The closure preferably should be capable of storing any type of splice, such as, for example, discrete mechanical, discrete fusion or mass mechanical, or other types while reducing forces that tend to damage the splices. Additionally, the closure should provide adequate grounding and anchoring for the metallic strength members of the cable. The closure should also be capable of accepting high fiber count cables as well as those of low fiber count.

Typically, prior art splice closures are somewhat complex, difficult to assemble, are necessarily bulky, and, in use, difficult to access. As a consequence, they are not economical when used for splicing relatively low count fiber cables, such as, for example, drop cables or CATV applications. Also, when used for low fiber count cables, the bulkiness of the closure makes it difficult to provide adequate storage room, without sacrificing accessibility. This problem of size has heretofore been addressed by simply using a large closure designed primarily for high capacity use, where feasible, or by designing special, smaller closures for low capacity use, which cannot carry or contain large numbers of fibers and splices.

In order to insure protection of the splices from moisture, it is current practice to form the closure out of two mating halves, with a grommet therebetween, and clamp them together. Cable entry is through openings in the grommet, which are usually supplied with inserts which seal the cable and in turn are sealed by the grommet. Such a grommet and insert arrangement is shown, for example, in U.S. Pat. No. 5,472,160 of Burek, et al. In that arrangement, the grommet, which is of a resilient material suitable for moisture sealing, has, at each end thereof, first and second seal members having bores therein for receiving grommet inserts, which, in turn have bores therein for receiving the cable. The seal members are preferably split longitudinally so that the grommet inserts, with cables extending therethrough, can be inserted in the seal members and be tightly embraced thereby. When the two halves of the housing are clamped together, the cable is tightly embraced, as are the seal members, so that a watertight seal is achieved.

In usage, it has been found that such a sealing arrangement can be vulnerable to a bending or flexing of the cable adjacent the entrance to or exit from the closure, which can, in some instances break the integrity of the seal. There have been various arrangements in the prior art for correcting this effect, one such arrangement being shown in U.S. Pat. No. 5,434,945 of Burek, et al. wherein the closure is encased in a protective shell which, after assembly, is filled with an encapsulant. Such an arrangement insures that the splice closure itself is virtually certain to be moisture proof. However, access to the splices is made more difficult by the presence of the encapsulant, which must be removed to permit such access. For high fiber count cables, limited access, while undesirable, does not necessarily pose too much of a problem. However, for low fiber count cables, where frequent access may often be required, such difficulty of access is undesirable.

Cables entrant into the enclosure are preferably, and in present day usage, almost always anchored to the splice enclosure itself, to guarantee a minimum of movement of the cable within the enclosure which could unduly stress the fibers and the fiber splices. One such anchoring means, in the form of a cable grip block, is shown in the aforementioned Burek, et al. U.S. Pat. No. 5,472,160. The grip block of that patent is capable of adapting to cables of different sizes, and also provides an anchor for the cable central strength mem-

ber which is a usual component of loose tube type cables. The anchoring arrangement for the central strength member requires that the strength member or members be cut to a specific length and bent upward into a slot within the grip member. The strength members are maintained within the slots against tensile forces because of their rigidity and because they are bent at a right angle. Thus, they function to help maintain the cable against shifting or movement. While this arrangement functions well, the necessity of cutting the strength members to specific lengths and of bending and threading them into the slots adds another increment of assembly time to the splice closure system.

Beyond the cable grip block, the cable is opened up, i.e., the cable jacket and/or sheaths are removed to free the individual fibers so that splicing can be effected, commonly referred to as fiber breakout. It is generally necessary, or at least desirable, that sufficient amounts of fiber slack be provided within the case, or enclosure as discussed hereinbefore, so that the individual fibers can be pulled clear of the closure for preparation of the ends for splicing and for effecting the splice. For a multifiber cable there should be, within the closure, some arrangement for positioning and storing the slack and for keeping the fibers arranged in an orderly manner. Prior art arrangements that address the problem of both splice and fiber slack storage and organization are shown in the aforementioned Cobb, et al. Krafcik, et al., U.S. Pat. No. 4,332,435 of Post, as well as in U.S. Pat. No. 5,420,957 of Burek, et al. As can be seen in these patents, a splice tray is used to hold and protect the splices themselves by means of a splice holder as well as providing space for the slack fibers to be contained without the necessity of too sharp bends. For example, a splice tray adapted to be mounted within the closure, as shown in the Burek, et al. U.S. Pat. No. 5,420,957, comprises an elongated substantially rectangular container having circular hubs at each end about which the fiber is to be wound, the radius of the hubs being greater than the critical bend radius, and a splice holder located between the hubs for containing and holding the splices. Such a tray has become a widely used component of present splice closures, and, where large members of splices are to be contained, various arrangements for stacking the trays may be provided as shown, for example, in U.S. Pat. No. 5,481,639 of Cobb, et al. In most of the aforementioned arrangements, the closure is designed to hold one or more splice trays having a specific configuration, and usually is not adaptable to accommodating splices for different kinds of fiber configurations, e.g., individual fibers or fiber ribbons. More particularly, it is generally economically unfeasible to modify a given closure to accept more than one type of tray.

Most of the prior art arrangements, as evident from the foregoing discussion, emphasize adequate storage capacity and fiber protection, with space and ease of access being secondary considerations. Certain ones of the aforementioned patents, such as the Cobb, et al. patent, make size, access, and cost important considerations, at least for some situations. However, even greater reductions in size, simplicity, and cost are needed, as well as a greater measure of versatility or adaptability coupled with a ready accessibility.

SUMMARY OF THE INVENTION

The present invention is a central strength member anchor for use in an enclosure, such as a splice closure, which has openings for ingress and egress of cables and gripping means within the closure for gripping the cable or cables. The closure supports the central strength member anchor

which is designed to grip and anchor the central strength member of, for example, a loose tube cable. The anchor of the invention has an elongated base portion and an elongated upstanding leg at one end. The leg has a distal end having a receiving member with a bore therethrough for receiving the cable strength member and means for anchoring the strength member in the bore. The anchor member also has means for locating it in the enclosure and means for mounting it thereto.

In greater detail, the anchor member may be used in a closure which comprises a plastic base member having a longitudinal axis and a cover member, preferably of suitable plastic material, both of which are substantially identical from being molded in the same molds, thereby eliminating a major cost of differing dies. The base and cover, both of which are flanged, have a racetrack grommet of, for example, polyurethane located between the flanges of the base and cover, which are clamped together by suitable means. When the base and cover are joined, they define a closure having a longitudinal axis and having openings at each end of the closure which are adapted to contain enlarged insert receiving members at the ends of the race-track grommet.

Within the closure are one or more grip blocks of, for example, the type shown in U.S. Pat. No. 5,440,666 of Burek, et al., which is mounted on studs in the base member. Between the studs is an upstanding projection over which is fitted the central strength member anchor of the invention which is held in place by the grip block, and which has an axial bore through which the strength member of an entrant cable, held in place by the grip block, is inserted. Gripping or set screws are adapted to hold the strength member firmly within the bore. The anchor member has a notched or scored base so that the spacing of the bore from the grip block can be any of two or more distances achieved by breaking the base at the desired notch or score. The bottom side of the base of the anchor member is slotted to enable the anchor member to be mounted on a projecting arm member extending between the studs. The breakout of the fibers occurs beyond the grip block, and, along the interior side walls of the base member are one or more cable tie retainers for holding bundled fibers or even cable neatly in place.

Mounted on the floor of the base member are first and second elongated upstanding pedestals having a circular cross section. The upstanding pedestals are spaced apart along the longitudinal axis and each has a diameter (or radius) greater than the critical bend radius of the fibers. Mounted on top of the pedestals is a rectangular shaped splice tray adapter plate. The configuration of the adapter plate permits the use of twice as many standard splice trays as are normally used in existing closure assemblies, whether stacked or not, and, additionally, makes use of existing splice trays without requiring modification thereof. On the other hand, when the discrete or mass splice trays of the invention are used, an increase in slack fiber storage space is realized.

It will be more apparent from the following detailed description, read in conjunction with the drawings, that the central strength member anchor provides a unique anchoring means for the central strength member of, for example, a loose tube cable. The inventive aspects of the central strength member anchor will be more readily understood from the following detailed description, read in conjunction with the following drawings.

DESCRIPTION OF THE DRAWINGS

In FIG. 1 an exploded perspective view of the splice closure of the invention and its component parts;

FIG. 2A is a perspective view of the splice closure base member;

FIG. 2B is a plan view of the base member of the splice closure;

FIG. 2C is a side elevation view of the base member of the splice closure;

FIG. 2D is an end elevation view of the base member of the splice closure;

FIGS. 3A and 3B are perspective views of the cover member of the splice closure;

FIGS. 4A and 4B are perspective views of the cable tie retainer of the invention;

FIG. 4C is a plan view of the cable tie retainer;

FIG. 4D is an elevation view of the cable tie retainer;

FIG. 4E is a cross-sectional view of the cable tie retainer along the line I—I of FIG. 4D

FIG. 5A is an elevation view of one of the pedestals of the invention;

FIG. 5B is an elevation view of one of the pedestals of the invention rotated 90° with respect to FIG. 5A;

FIG. 5C is a cross-sectional view of the pedestal along the line I—I of FIG. 5A;

FIGS. 5D and 5E are perspective views of the pedestal of FIG. 5A;

FIG. 6A is a plan view of the racetrack grommet of the invention;

FIG. 6B is an end elevation view of the racetrack grommet of FIG. 6A;

FIG. 6C is a side elevation view of the racetrack grommet of FIG. 6A;

FIG. 6D is a cross-sectional view of the insert receiving member of the racetrack grommet along the line I—I of FIG. 6A;

FIG. 7A is an elevation view of an insert for use with the grommet of FIG. 6A;

FIG. 7B is an end elevation view of the insert of FIG. 7A;

FIG. 7C is a cross-sectional view of the insert along the line I—I of FIG. 7B;

FIG. 8A is an elevation view of a port plug for use with the grommet of FIG. 6A;

FIG. 8B is an end elevation view of the port plug along the line I—I of FIG. 8A;

FIG. 8C is a cross-sectional view of the port plug of FIG. 8A

FIG. 9A is a perspective view of the central strength member (CSM) anchor of the present invention;

FIG. 9B is a plan view of the CSM anchor of FIG. 9A;

FIG. 9C is an end evaluation view of the CSM anchor of FIG. 9A;

FIG. 9D is a side evaluation view of the CSM anchor of FIG. 9A;

FIG. 9E is a plan view of an alternative configuration of the CSM anchor;

FIG. 9F is an end elevation view of the CSM anchor of FIG. 9E;

FIG. 10A is a perspective view of the splice tray adapter plate of the invention;

FIG. 10B is a plan view of one side of the splice tray adapter plate of FIG. 10A;

FIG. 10C is a side elevation view of the splice tray adapter of FIG. 10A;

FIG. 10D is an end elevation view of the splice tray adapter plate of FIG. 10A;

FIG. 11 is a perspective view of the splice tray adapter plate mounted on the pedestals, illustrating how one side thereof accommodates two standard (UCB) splice trays;

FIG. 12A is a plan view of a discrete splice tray for use with the invention;

FIG. 12B is a side elevation view of the discrete splice tray of FIG. 12A;

FIG. 12C is an end elevation view of the discrete splice tray of FIG. 12A;

FIG. 12D is a perspective view of the discrete splice tray of FIG. 12A;

FIG. 13A is a perspective view of the mass splice tray of the invention;

FIG. 13B is a plan view of the mass splice tray of FIG. 13A;

FIG. 13C is a side elevation view of the mass splice tray of FIG. 13A;

FIG. 13D is an end elevation view of the mass splice tray of FIG. 13A;

FIG. 14A is a perspective view of an insert for use with the mass splice tray of FIG. 13A, for holding one type of splice holder;

FIG. 14B is a plan view of the insert of FIG. 14A;

FIG. 14C is an end elevation view of the insert of FIG. 14A;

FIG. 14D is a side elevation view of the insert of FIG. 14A;

FIG. 14E is a detail of one of the locating members of the insert of FIG. 14A;

FIG. 15A is a perspective view of splice holders mounted in the insert of FIG. 14A;

FIG. 15B is a plan view of the splice holders mounted in the insert of FIG. 14A;

FIG. 15C is a side elevation view of the splice holders mounted in the insert of FIG. 14A;

FIG. 16A is a perspective view of another form of insert for use with the mass splice tray of FIG. 13A;

FIG. 16B is a plan view of the insert of FIG. 16A;

FIG. 16C is an end elevation view of the insert of FIG. 16A;

FIG. 16D is a side elevation view of the insert of FIG. 16A;

FIG. 16E is detail of one of the locating members of the insert of the insert of FIG. 16A;

FIG. 17A is a perspective view of a splice holder mounted in the insert of FIG. 16A;

FIG. 17B is a plan view of the holder and insert combination of FIG. 17A;

FIG. 17C is a side elevation view of the holder and insert combination of FIG. 17A;

FIG. 18A is a plan view of a cover member for the mass splice tray of FIG. 13A;

FIG. 18B is a side elevation view of the cover member of FIG. 18A; and

FIG. 19 is a perspective view of the mass splice tray of FIG. 13A showing at least a partial routing of the fiber ribbons therein relative to the splice holder.

DETAILED DESCRIPTION

In FIG. 1 there is shown an exploded view of the splice closure assembly 11 of the present invention, and the various

component parts thereof which, when assembled, make up a complete splice closure assembly.

Closure assembly **11** comprises a base member **12** and a cover member **13** which is designed to be bolted or otherwise clamped to base member **12** after the components have been assembled with the cables, optical fibers, and splices, none of which are shown, in their assigned positions. Both base member **12** and cover member **13** are preferably made of suitable plastic material having strength and rigidity sufficient to withstand external shocks without compromising the closure integrity, or without affecting the internal components of the assembly. As a cost saving measure, both base member **12** and cover member **13** are molded or otherwise formed in substantially identical molds or dies, and are, themselves, substantially identical to each other, as will be more apparent hereinafter.

Base member **12** has a deep trough-like configuration with first and second longitudinally extending flanges **14** and **16** leaving a plurality of bolt holes **17** which match corresponding bolt holes **18** in flanges **19** and **21** of cover member **13**. Bolts **22** and nuts (not shown) fit into the matching holes **17** and **18** for clamping the two members **12** and **13** together. It is, of course, to be understood that other types of external clamping means might readily be used in place of bolts **22**. Side by side end compartments **23,24** are formed at each end of base member **12** by means of walls or septa **26** and **27** which have semi-circular cut-outs therein for receiving the insert receiving members **28** and **29** of a race track grommet **31**, having bores therethrough for inserts **32** and **33**. Grommet **31**, which is made of a suitable flexible, compressible polyurethane material functions as a sealing gasket between the flanges **14** and **19** and **16** and **21** between base member **12** and cover member **13**. Each of the insert receiving members **28** and **29** has a pair of longitudinally spaced V-shaped grooves **34** in the bore thereof, only one of which is visible in FIG. 1. Each of the inserts **32** and **33**, both of which are preferably made of polyurethane, has a V-shaped ridge **36** around the circumference thereof which is adapted to fit within one of the grooves **34**. In order that insertion of inserts **32** and **33** into receiving members **28** and **29** might be more easily accomplished, each of the receiving members **28** and **29** is split longitudinally by slits **37**.

Each of the inserts **32** and **33** has a bore **38** extending therethrough for receiving the cable, not shown, which is to be spliced. As will be apparent hereinafter, each of the inserts **32** and **33** is split longitudinally by splits **39**, **41** to facilitate insertion of the cable therein, and, during assembly, the slits **41** in inserts **33** should be rotated by preferably 180° relative to the slits **39** in inserts **32** so that there is no straight through path for moisture to enter the closure from the outside. The use of two inserts arrayed end-to-end in butting relationship helps avoid breaking of the moisture seal or barrier as a result of flexing of the external portion of the cable. Even under severe flexing, which might cause inserts **33** to be displaced sufficiently to break the seal between the cable and the insert **33**, or between the insert **33** and receiving member **29**, the inner insert **32** is not affected, and the integrity of the seal, which results from the compressive forces on the grommet **31**, receiving members **29** and inserts **32** and **33** when base member **12** and cover member **13** are clamped together, is not affected. In a similar manner, the slits in both inserts **32** and **33** should be rotated relative to the slits **37** in receiving in receiving members **28** and **29**.

When only one cable is to be inserted into the closure assembly **11**, through, for example, receiving member **29** as shown in FIG. 1, a port plug **42** is inserted into receiving member **28** to create a moisture proof seal. Thus, both ends

of the closure assembly **11** will, upon assembly, have moisture proof seals, whether one or two cables are passed therethrough.

Within the closure assembly **11**, more particularly, within base member **12**, is mounted a grip block assembly **43** which preferably is the same as, or similar to, the grip block assembly shown, for example, in Burek et al. U.S. Pat. No. 5,440,666. Grip block **43** is shown aligned with insert receiving member **29** and insert **32** so that the cable entrant through insert **32** passes directly into grip block assembly **43**. The grip block is mounted on a pair of studs **44**, **46** which, in turn, are mounted in elongated bosses **47** and **48**. A grip block **43** is shown in FIG. 1 in its mounted position adjacent compartment **24** but separated therefrom by wall **27**. Grip block **43** performs the function of tightly gripping the cable entrant into the closure assembly in the manner shown and described in the aforementioned Burek et al. U.S. Pat. No. 5,440,666 so that the cable is immobilized. When the cable has a loose tube configuration having a central strength member, it is desirable that the central strength member, which is usually, but not always, a relatively stiff metallic wire member, be anchored. To this end, a central strength member anchor **49** is mounted below grip block assembly **43** and held in place thereby, and extends inwardly therefrom. Anchor **49**, which will be discussed in greater detail hereinafter, has a bore **51** substantially axially aligned with the cable held by grip block **43** for receiving the central strength member of the cable, and further has means for clamping the central strength member to immobilize it and the cable still further.

Along the interior side walls of base **12** are arrayed spaced built out slots **52**, only one of which is clearly shown in FIG. 1 into which cable tie retainers **53** are inserted. Cable tie retainer **53** make it possible to organize the interior of the closure assembly **11** by tying the cable or the fibers, in bunches, to the walls of the closure **11**, thereby making it possible to route the fibers or cable along the walls to prevent their becoming tangled or otherwise interfering with the other components.

On the interior floor of base member **12** are mounted first and second pedestals **54** and **56**, only pedestal **54** being completely shown. Pedestals **54** and **56**, which will be discussed more fully hereinafter, are substantially cylindrical in shape and have, at their distal ends resilient fingers **57**, **58** which are adapted to hold a splice tray adapter plate **59**, thereby affording a unique mounting arrangement for one or more splice trays **61**. The spaced pedestal arrangement makes it possible to store fiber slack by winding the fibers about the pedestals **54**, **56**, preferably in a figure eight (**8**) configuration, but many other configurations are possible. To this end, and to prevent too sharp bending of the fibers, the radius of the cylindrical pedestals **54**, **56** is greater than the critical bend radius of the fibers. In order that the fibers may be brought from the space below, past the splice tray adapter plate **59** up to the splice tray **61** mounted thereon, plate **59** has a rectangular shaped cutout **62** along one side, as shown, and splice tray **61** has a matching cut-out portion **63**. A recessed lid **64** is provided for splice tray **61** which becomes nested into the splice tray above it when the splice trays are stacked.

In order that the closure assembly **11** may be affixed to, for example, overhead cabling, or otherwise mounted to a support structure, flange member **14** has projecting mounting tabs **64**. These tabs **64**, which preferably are of the same material as other fastening hardware allowing the closure to be racked in a manhole or hung on an aerial strand.

Closure Base and Cover

FIGS. 2A through 2D are different views of base member **12**, and FIGS. 3A and 3B are two perspective views of cover

member 13, which, together, form the closure shell of the assembly 11. As can be seen from those figures, both base 12 and cover 13 are substantially identical in size, shape, and conformation, and generally comprise externally ribbed (for strength) shells of suitable plastic material. The same or similar dies may be used in molding members 12 and 13, however, base member 12 has additional elements not present in cover member 13. As can be seen in comparing FIGS. 2A and 3A, base member 12 has four elongated bosses 47 and 48 arrayed thereacross at each end adjacent wall 26 and 27 on the interior side thereof. Each pair of bosses 47 and 48 are joined by a cross shaped support member 66 which has a forward or inward projecting arm 67 and a rearward projecting arm 68. Arms 67 and 68 are best seen in FIG. 2B. For reasons which will be apparent hereinafter, arm 67 is longer than, and projects above, arm 68. The cross arms 71 and 72 between each of the bosses 47 and 48 likewise are shorter than arm 67. The innermost bosses 47 are joined by a septum or wall 73 which is spaced from wall 26 as best seen in FIG. 2B. The other end of base member 12 has the same configuration of bosses 47, 48, cross-shaped support members 66 and septum 73 as best seen in FIG. 2B. Studs 44 and 46, which are threaded, are preferably affixed in elongated bosses 47 and 48, respectively, during the molding process, to create a rigid connection of the studs to base member 12.

First and second spaced bosses 77 and 78 are located on the inner floor of member 12, and threaded studs 79 and 81 are affixed therein, preferably in the same manner as the studs 44 and 46. Bosses 77 and 78 and studs 79 and 81 are preferably aligned with the longitudinal centerline of member 12, and spaced as shown. It is important that none of the studs penetrate the wall of member 12, hence the method of placing them in position during the molding process is to be preferred.

At each end of member 12 are arrayed locating holes 74 which are designed to mate with bolt locations 76 on cover member 13, as best seen in FIG. 3A. In addition, bosses 75, having bores therein, are provided at each end to receive bolts 70 shown in FIG. 1, and cover member has bosses 80 having bolt holes extending therethrough. Bosses 75 prevent over compression of grommet 31 by bearing against bosses 80.

Built out slotted members 52 are formed along the two interior side walls of member 12, in spaced array, as shown. Members 52 are adapted to receive and retain cable tie retainers 53, the configuration of each of which is best seen in FIGS. 4A through 4E. Tie retainer 53 has a roughly T-shaped configuration with the cross piece 82 having elongated bores 83 and 84 at the distal ends thereof for receiving cable (or fiber) ties. The depending portion 86 also has a roughly T-shaped configuration designed to slip within the slot formed by member 52. The leg 87 of portion 86 is curved to facilitate insertion into the slot formed by member 52, and is provided with first and second barbs 88 and 89 which, when retainer 53 is inserted fully into slotted member 52 are designed to break off within the slot, thereby insuring that retainer 53 is firmly held within member 52. As was pointed out hereinbefore, cable tie retainer 53 is useful in organizing and routing cable and fiber. The ties can be wrapped around the fiber bunch, for example, and threaded through bores 83 and 84, thereby making it possible to snug the cable or fibers close to the side walls of base member 12.

First and second pedestals 54 and 56 are identical, and their configuration is shown in FIGS. 5A through 5E. Each of the pedestals 54 and 56 is designed to be mounted to one of the studs 79 and 81 by means of a threaded bore 91 in the

bottom 92 or by other suitable means, such as a nut; not shown. Each pedestal is aligned or oriented properly by means of an alignment hole 93 in the bottom 92 which mates with an alignment pin 94 on the bottom floor of member 12. Each pedestal which is of a suitable plastic material has a substantially hollow cylindrical shape, the radius of curvature of which is greater than the critical radius for the optical fibers, and has formed at the distal end thereof, by means of slits 96 and 97, resilient fingers 57 and 58 the distal ends 98 and 99 of which have formed thereon latch projections 101 and 102 designed to mate with splice tray adapter plate 58, as will be discussed more fully hereinafter. The use of pedestals 54 and 56 for holding the splice tray adapter plate 58, and hence, the splice tray or trays above the floor of member 12 provides a substantially empty space of large volumes defined by the side and end walls and the floor of member 12 for storing slack fiber. The fiber is wound in a FIG. 8 configuration or other chosen configurations previously discussed about the pedestals 54 and 56 and thus is prevented from becoming tangled or otherwise disorganized.

The cover member 13, shown in FIGS. 3A and 3B is, as has been discussed hereinbefore, adapted to fit, flange to flange with base member 12, with the racetrack grommet therebetween to provide a moisture and dirt proof seal.

The fiber closure assembly 11 including pedestals 54 and 56, splice tray adapter 59 and discrete splice tray 61 are the basis of U.S. patent application Ser. No. 08/847,214, filed concurrently herewith.

Racetrack Grommet and Inserts

Racetrack grommet 31, which is shown in detail in FIGS. 6A through 6D comprises a substantially rectangularly shaped member 103 of suitable flexible, resilient material, preferably polyurethane, having longitudinal sides 104 and 106 which are spaced apart a distance such that they fit between the flanges 14 and 16 on base 12 and 19 and 21 on cover member 13 and are substantially co-extensive therewith. Also, sides 104 and 106 have a plurality of bolt holes 107 which are spaced and located to be coincident with the holes 17 and 18 in the flanges of base member 12 and cover member 13. In some cases, bolts may not be the preferred way of clamping the base and cover member together, in which case the bolt holes 107 might not be needed. An alternative clamping arrangement is shown in U.S. Pat. No. 5,434,945 of Burek et al. At the ends of member or grommet 103 are transverse section 108 and 109, which are substantially identical, each of which comprises spaced cylindrical shaped insert receiving members 28 and 29 separated by a web 111. Web 111 has a bolt hole 112 extending therethrough which coincides with the holes in bosses 75 and 80 of base member 12 and cover member 13 respectively. The bolts 70 produce clamping along the centerline of the closure 11, thereby insuring a tight seal throughout, in conjunction with the bolts 22. Thus, any bowing or warping of either the base member 12 or cover 13 is prevented, or minimized. Each of the insert receiving members 28 and 29 has a bore 115 extending therethrough for receiving the grommet inserts 32 and 33 and a longitudinal slit 37 to facilitate insertion of the inserts therein for holding the inserts in place, as will be discussed hereinafter.

An insert 32 for a receiving member 28 or 29 which is preferably of the same material is shown in FIGS. 7A, 7B, and 7C and comprises a cylindrical body 113 having a cable receiving bore 38 extending therethrough. Within bore 38 are a plurality of flexible sealing flanges or fingers 114,

which are, as best seen in FIG. 7C, preferably sloped toward the cable entrance end of insert 32, and body 113 has a longitudinal slit 116 therein. In practice, when a cable is to be inserted into bore 38, the insert is spread apart at the slit 116 and the cable is forced into bore 38 past the sealing fingers 114. After cable insertion, and insertion of insert 32 into receiving member 28 or 29, the fingers 114 are compressed to produce a tight seal against the cable outer jacket. The outer surface of body 113 has a V-shaped circumferential ridge 36 which nests in V-shaped groove 34 in insert receiving member 28 or 29 to hold it in place longitudinally, and, incidentally, to form a moisture block. As was discussed hereinbefore, each of receiving members 28 and 29 is dimensioned and configured to hold two inserts 32 and 33 which are identical in butting or back to back relationship. Thus, the spacing between the V-shaped grooves 34 is approximately equal to the length of an insert 32 when the V-shaped ridges 36 are centrally located on insert 32, as shown. As pointed out hereinbefore, it is desirable that the slit 116 in one insert 32 be rotated, preferably 180°, to a different orientation than the slit 116 in abutting insert 33, thereby avoiding a direct moisture path into the interior of the closure assembly 11.

When assembly of the closure 11 is complete, the compression forces on the resilient grommet 31, receiving members 28 and 29, and inserts 32 and 33 insure that the slits 37 and 39 cannot open. However, if a cable passing through a pair of inserts 32, 33 undergoes external flexing or twisting closely adjacent to the closure 11, the forces on the outer insert 33 might be great enough to distort it thereby possibly opening it at the slit 39 or possibly unseating it within member 28 or 29, thereby destroying the integrity of its seal. The arrangement of the present invention wherein two inserts 32, 33 are used, allows the outer insert 33 to absorb any such external forces while the inner insert 32 is not subjected thereto, and hence, its seals remain unbroken.

In use, the assembly 11 may have only one cable entrant therein, or only one cable exiting, in which case one or more of the insert receiving members 28, 29 will not require the inserts 32, 33. However, the idle receiving member 28 or 29 must be sealed off to prevent the intrusion of moisture, dirt, or other contaminants into the closure interior. To this end, there are provided one or more port plugs 42, the configuration of which is shown in FIGS. 8A, 8B, and 8C. As can be seen in the figures, plug 42, which is preferably of the same material as base 12 and cover 13 and, is in the form of a hollow cylinder having a closure end wall 117 and a side wall 118 tapered in the interior of plug 42, as best seen in FIG. 8C. In addition, the exterior surface of plug 42, which is dimensioned to fit within a receiving member 28 or 29, has first and second V-shaped ridges 119 and 121 which are spaced to coincide with V-shaped grooves 34 in receiving member 28 or 29, and dimensioned to fit snugly therein. The tapered wall 118 which is thinner at the open end than at the closed end 117, facilitates insertion of the plug 42 into member 28 or 29, with the open end toward the interior of the closure 11, and end wall 117 facing the exterior. In this manner, unused receiving members 28, 29 are sealed so that the interior of closure 11 is not affected by ambient atmospheric conditions.

The combination of the racetrack grommet 31, inserts 32, 33, and port plugs 42 insure substantially complete sealing of the interior of closure 11.

The unique principles, construction and operation of the racetrack grommet, the inserts, and the port plugs are shown as used with a particular closure design. However, it will be clear to workers in the art that these features can readily be

adapted to other types of closures than the one shown. The racetrack grommet, inserts, and port plugs are the basis of U.S. patent application Ser. No. 08/848,788 of Burek et al filed concurrently herewith.

Central Strength Member Anchor

In FIGS. 9A through 9E there are shown various views of the central strength member (CSM) anchor 49, and of an alternative embodiment 142 thereof. As was pointed out hereinbefore, anchor 49 functions as an anchor for the central strength member of, for example, a loose tube cable, without requiring precise cutting or bending of the CSM.

Anchor 49, which is preferably of a hard plastic material, comprises an elongated base portion 123, an upstanding leg 124, and a CSM receiving member 126 having a bore 127 extending therethrough for receiving the CSM of the cable. Member 126 has first and second threaded bores 128 and 129 for receiving set screws 130 and 135 which clamp down on the CSM to hold it firmly in place within bore 127. Thus, the CSM is anchored firmly within the bore 127, which functions not only to contain the CSM but also add another point of resistance against tensile forces on the cable. Base portion 123 comprises a substantially rectangularly shaped planar member 131 from which depend side walls 132 and 133. Disposed along the center line of anchor 49 are first and second rectangular holes 134 and 136 which pass completely through member 131 and which are dimensioned to fit snugly over arm 67 of support member 66 which is shown in FIG. 2B. Each of the depending walls 132 and 133 has first and second slots 137 and 138 which are dimensioned to fit down over cross arms 71 and 72 when arm 67 penetrates one of the rectangular holes 134, 136 as explained in the foregoing. Each of the side walls 132 and 133 also has a slit 139 and member 131 is transversely scored at 141, the score 141 being aligned with slits 139. Slits 139 and score 141 allow the portion of base portion 123 to be broken off so that the slots 137 are to be fitted over cross arms 71 and 72 and rectangular hole 134 fits over arm 67. If, on the other hand, it is desired to have a greater length of the cable central strength member protruding from grip block 43, the member 123 is not broken, i.e., shortened, and slots 138 and rectangular hole 136 become functional in mounting anchor 49 to base member 12. Anchor 49 is, when the closure is assembled, located under grip block 43 and held in place thereby when block 43 is mounted to the base 12. The height of arm 124 is chosen such that when anchor 49 is mounted in place, the bore 127 will be approximately aligned with the axis of the cable held in grip block 43 so that it will not be necessary to bend the cable central strength member in order to anchor it. Further, the use of an elongated base portion 123 with the scoring 141 and the slits 139 in side walls 132 and 133 makes possible a wider range of CSM lengths, thereby minimizing the restraints on cutting the CSM to a proper length. The anchor 49, which is a separate entity from grip block 43, makes possible a simple and quick anchoring of the CSM.

FIGS. 9E and 9F depict a modification of the anchor member 49 which is capable of gripping two CSM's. For simplicity, like parts to those in FIGS. 9A, 9B, 9C, and 9D, bear the same reference numerals. The anchor member 142 comprises a base portion 123 which comprises a planar member 131 and depending side walls 132 and 133. However, one end of planar member 131 is bifurcated to form two arms 143 and 144, each one of which terminates in an upstanding leg 124 having a CSM receiving member 126 on the distal end thereof. Member 123 is shown with a third rectangular hole 146 and a second scoring 147 on the

surface of planar member **131**, thereby allowing greater flexibility in anchor length. Such an anchor member is especially useful in those closure assemblies where the grip block **43** or an equivalent cable gripping member is designed to accommodate two cables. The spacing of the two CSM receiving members **126** are chosen to be such that they are approximately aligned with the cable axes, thereby eliminating the necessity of precisely bending the cable CMS's.

The CSM anchor as shown and described herein greatly simplifies the assembly of the closure with cables entrant therein. Where, as is possible in the case of the assembly shown in FIG. 1, four cables are entrant into the closure, four CSM anchors **49** would be used. On the other hand, some closure configurations can accommodate greater numbers of cables, in which case, anchor **142** would be used, or, in some arrangements, a combination of anchors **49** and **142** can be used. The mounting arrangement for both anchors **49** and **142** are for the particular closure **11** as shown in FIG. 1. It will be apparent that other mounting arrangements for the anchor **49** and **142** might be used, depending upon the particular closure configuration.

Splice Tray Adapter Plate

In FIGS. 10A through 10D there is shown in greater detail the splice tray adapter plate **59** which mounts upon the tops or distal ends of the pedestals **54** and **56**. As was discussed in the foregoing, and as will be readily apparent hereinafter, adapter plate **59** can accommodate two standard splice trays of the type shown in the aforementioned Burek et al. U.S. Pat. No. 5,420,957, or more than two when the trays are stacked, as well as one or more stacked discrete splice trays **61** or mass splice trays.

Adapter plate **59** comprise a thin rectangular plate **147** of suitable material, preferably a hard plastic, which is preferably ribbed, as shown, for added stiffness and resistance to warping or bowing. First and second spaced openings **148** and **149**, substantially rectangular in shape but having curved ends are oriented as shown along the centerline of member **147**. The spacing between openings **148** and **149** corresponds or is equal to the spacing between pedestals **54** and **56**, and each opening **149** and **149** has, at each end thereof, a projecting lip **151** which is adapted to be engaged by one of the latch projections **101** or **102** on the distal ends of resilient fingers **57** or **58** of the pedestals **54** and **56**. In this manner, plate **59** can be mounted on and removably affixed to the pedestals **54** and **56**. At two of the corners **152** and **153** of the plate member **147** are pivot pin receiving bushings **154** and **156** which receive pivot pins on the splice tray **61** or other splice trays, as will be apparent hereinafter. Bushing **154** is, preferably, fixed in place at corner **152** while bushing **156** forms the end of a resilient finger **157** which extends from the side of plate member **147** toward corner **153**. Thus, in mounting a splice tray to adapter plate **59**, finger **157** can be flexed to permit easy insertion of a splice tray pivot pin therein. At each end of plate member **147** is a flange member **158** or **159**, and at each end of each flange member are pivot pins **161** and **162**, which are also used in mounting a splice tray on plate **59**. At the other two corners of rectangular plate **147** are latch holes **150** for latching a mounted splice tray, such as tray **61**, to adapter plate **59**.

Extending from flanges **158** and **159** and located substantially centrally between pins **161** and **162** are first and second L-shaped latch members **163** and **164**. As viewed in FIG. 10B and 10D, the legs **166**, **167** of members **163** and **164** extend across the thickness of flanges **158** and **159**, while the projecting arms **168** and **169** are aligned with the bottom

thereof. As will be apparent hereinafter, when either the discrete splice tray **61** or the mass splice tray for use with plate **59** is mounted, latch members **163** and **164** play no part in affixing such splice tray to adapter plate **59**. However, when standard or UCB splice trays are to be mounted, the adapter plate is inverted so that arms **168** and **169** are aligned with the top of flanges **158** and **159**, and latch members **163** and **164** act to latch the splice trays in place. This is illustrated in FIG. 11, which depicts adapter plate **59**, mounted on pedestals **54** and **56** in its inverted position where the L-shaped latch members **163** and **164** (only **163** being shown) are in their inverted position, with the arm **168** being at the top of the inverted L. First and second UCB type splice trays **171** and **172** are mounted on the pivot pins **161** and **162**, and resilient latches **173** and **174** on each splice tray engage the arms **168** and **169** of latch members **163** and **164**. Thus, adapter plate **59** can accommodate two splice trays **171** and **172** on a single level, and the splice trays may be stacked in accordance with present practice.

One elongated side **176** is provided with a cut-out portion **62** which forms passage for the fibers to be spliced from below the adapter plate **59** to the splice trays, as shown in FIG. 12D.

Plate **59** also has a centrally located bore **155** therein which is useful for mounting bolt or stud mounting splice trays thereto.

Discrete Splice Tray

The discrete fiber splice tray **61** for use with adapter plate **59** in closure **11** is shown in detail in FIGS. 12A through 12D. Tray **61** comprises a base member **177** of suitable rigid plastic material having a floor **178** along which are arrayed a plurality of splice holder regions **179** upon which splice holder **181**, shown diagrammatically in FIG. 12D are to be affixed, as by adhesive. The splice holders **181** as depicted in FIG. 12D are for illustrative purposes only, the actual splice holders having more slots for splices than are shown, and being configured for different types of splices. Extending upwardly from the peripheral edges of floor **178** are front, rear, and side walls **182**, **183**, and **184**, respectively. The designation "front" and "rear" are only applicable to the view of the splice tray shown in FIGS. 1 and 12D, there being no actual "front" and "rear". Extending from the top edges of walls **182**, **183**, and **184** are a plurality of protective tabs **186** which function to hold the fibers within the confines of the walls by preventing them from bulging or bending upward, as best seen in FIG. 12D. Tray **61** also has a recess opening **63** which, when tray **61** is mounted on adapter plate **59** on the obverse side thereof, coincides with opening **62** in plate **59** to allow fiber to be fed to the tray from below adapter plate **59**. First and second channels **187** and **188** are open to the recess opening **63** and function to route the fibers into the confines of the walls **182**, **183**, and **184**. Because the fiber slack is stored below the adapter plate, as discussed in the foregoing, it is not necessary that the splice tray **61** have hubs at each end, as is typical of the UCB tray and most other in the prior art. This represents a substantial savings in fabrication, since the dies or molds for the tray **61** are much simpler and correspondingly, less costly than those for prior art trays.

Located at the corners formed by side walls **184** and the walls **189** forming channels **187** and **188** are pivot pins **191** which are designed to fit within pivot pin bushings **154** and **156** on adapter plate **59**, thereby pivotally mounting splice tray **61** to plate **59**. As pivot pin bushing **192** formed on the distal end of a flexible finger **193** is located immediately

above the other pivot pin 191. Bushings 192 and 194 are adapted to receive the pivot pins of a second splice tray (not shown) in the event that it is necessary or desirable to stack several splice trays 61. Splice tray 61 is provided with a recessed cover 64, as shown in FIG. 1, which is used with every tray in a stack. At the other two corners of tray 61 are resilient latching fingers 190 whose distal ends have lipped latches 195 which are designed to mate with latch holes 150 in adapter plate 59 to hold tray 61 securely in place.

As can best be realized from FIG. 12D, the discrete splice tray 61 can contain a large number of discrete splices contained in holders 181, and only that portion of the fibers themselves contained therein is that required to accommodate the splices, without any additional slack storage.

Mass Splice Tray

The closure assembly 11, as pointed out in the foregoing, is, through its unique combination of pedestals 54 and 56 and adapter plate 59, capable of accommodating several different types of splice trays while providing large amounts of fiber storage space. In addition to its ability to organize optical fibers and fiber slack, it is also equally capable of organizing and storing or containing optical fiber ribbon structures and slack ribbon. Inasmuch as optical fiber ribbons contain large numbers, e.g., twelve, fibers therein, it is desirable that additional slack containment be provided to facilitate splicing of the fibers within the ribbon.

In FIGS. 13A through 13G there is depicted a mass splice tray 196, of suitable material such as thin, hard plastic, which is designed primarily to contain optical fiber ribbon splices of differing types while, at the same time, storing ribbon slack without creating two sharp bends in the ribbons.

As best seen in FIG. 13A, tray 196 comprises a planar floor member 197 of substantially rectangular shape having a front wall 198, a rear wall 199, and first and second end walls 201 and 202. It can be seen that the walls are substantially higher than the side and end walls of the discrete splice tray 61. The terms "front" and "rear" refer only to the positions of walls 198 and 199 as viewed in FIG. 13A. End walls 201 and 202 have extensions 203 and 204, respectively, from which project walls 206 and 207 which form channels 208 and 209 for routing the fiber ribbons from below the adapter plate 59 to the interior of tray 196, as defined by the walls thereof. Protective tabs 211 extend from the upper edges of the several walls to prevent the fibers or ribbons from bulging or bending upward, thereby maintaining them below the top edges of the walls of the tray 196. The top edge of front wall 198 has first and second spaced latch projection 212 and 213 which, as will be apparent hereinafter, function to hold a cover member in place. At the rear corners of extensions 203 and 204 are similar projections 215 which also function to hold the cover member in place. At either end of front wall 198, at the bottom thereof, is a resilient finger 214, the distal end of which has a projecting latch member 216 adapted to mate with the openings 150 in adapter plate 59 to affix the splice tray 196 into place on plate 59. At the intersections of end walls 201 and 202 with front wall 198 are first and second curved sections 217 and 218, which have extending flanges 219 and 221, each have a hole 222 at the corner thereof which is adapted to receive the latch members 216 on a second splice tray when the trays are stacked for additional capacity. At the lower corner of each of extensions 203 and 204 is a projecting pivot pin 223 which is designed to fit within one of the bushings 154 or 156 on adapter plate 59. On extension 204 is formed a resilient finger 224 which has, at its distal

end, a pivot pin bushing 226, located directly above pivot pin 223. Also, on extension 203 there is formed a pivot pin bushing 227. Bushings 226 and 227 are adapted to receive the pivot pins 223 of a second tray that is stacked upon the tray 196 so that it is pivotable with respect thereto, and pins 223 on tray 196 serve to mount it pivotably to adapter plate 59.

Extending from rear wall 199, and approximately centrally located with respect thereto is a splice holder support shelf 228 which is spaced from floor 197 and supported in part by a curved support member 229. Rear wall 199 has first and second slots 231 and 232 which are spaced apart a distance approximately the width of support shelf 228 and are aligned with the extending sides thereof, and which extend from the top edge of wall 199 approximately to the top surface of shelf 228, as best seen in FIG. 13A. Shelf 228 is designed to support any one of a number of types of splice holders, as will be apparent hereinafter, and slots 231 and 232 function to position the splice holders relative to the shelf 228.

The front wall 198 has depending therefrom spaced locating tabs 233 which are adapted to bear against the front edge of adapter plate 59, thereby locating tray 196 relative to the plate 59. End walls 201 and 202 each have a depending tab 234 which are adapted to fit within locating holes 236 in adapter plate 59, the further to assist in locating tray 196 on plate 59.

In FIGS. 14A through 14E there are shown several views of a splice holder insert 237 for mounting a splice holder with foam material for cushioning the splices, as shown in FIGS. 15A through 15C, onto mass splice tray 196. Insert 237, which is preferably made of a hard plastic material, comprises a floor member 239 having a front wall 241, an intermediate wall 242, and a rear wall 243, which is, as shown in the figures, wider than the floor 237 and walls, each of which is approximately as wide as the support shelf 228. Extending from the rear of wall 243 are first and second T-shaped locating members 244 and 246, with the legs of the T-shapes being spaced apart a distance equal to the spacing of the locating slots 231 and 232. The leg of member 244 is adapted to slip into slot 231, and the leg of member 246 into slot 246 so that insert 237 can be lowered onto shelf 229 and be held thereby members 244 and 246 in the slots 231 and 232 respectively. As shown in FIGS. 15A through 15C, two fusion splice holders 238 can be fitted onto insert 237, and held in place by, for example, suitable adhesive means, not shown, such as a double sided adhesive tape or a suitable cement. Each splice holder 238 is preferably made of a soft, resilient foam material and comprises a plurality of slots 247 separated by bands 248. The slots or grooves 247 are each adapted to hold an encased fusion splice therein and, because of the resilience of the holder material, to grip it firmly. As an example, each holder 238 may have six slots 247 so that twelve fusion splices may be contained on one insert. The inserts 237 may be stacked so long as there is room in slots 231 and 232 for the T-shaped members 244 and 246 of each insert, thereby greatly increasing the number of splices held. Inasmuch as a typical fiber ribbon contains twelve fibers, for example, two stacked inserts can contain two hundred and eight fiber splices.

In FIGS. 16A through 16E there is shown an insert 249 which is configured to hold a mechanical splice holder 251 as shown in FIGS. 17A through 17C. Insert 249 which, like insert 237 is preferably made of a suitable hard plastic material, comprises a floor 252, a front wall 253 and a rear wall 254. Insert 249, because of the configuration of splice holder 251, is wider than the shelf 228 of tray 196. On the

rear of wall **254** are first and second T-shaped locating and holding members **256** and **257** which function in the same manner as explained with reference to locating and holding members **244** and **246**. Insert **249** also has first and second shallow side walls **258** and **259** which assist in holding the splice holder **251** in place on insert **249**. As can be seen in FIGS. **17A** through **17C**, the mechanical splice holder **251** is depicted as mounted on insert **249** and comprises a plurality of off-set cavities **261** which are designed to hold the encased mechanical splices. Holder **261** is preferably made of a soft, resilient foam material that grips the encased mechanical splices. Fiber ribbon entrance into and exit from each of the cavities **261** is via slits **262** and **263** cut in the material of holder **251**. An advantage of such an arrangement is that the slits **262**, and **263** allow the holder to orient and hold the fiber ribbons leading to the splices and exiting therefrom.

In FIG. **18** there is depicted a cover member **264** for tray **196**. Cover member **264** which is preferably made of a transparent plastic material has first and second tabs **266** and **267** designed to hit against projections **212** and **213** on tray **196**, and act as a means of squeezing the cover so that it bends upward and shortens its width so that it can be easily removed from the splice tray and the rear edges **268** slip under projections **215** on tray **196**. Cover **264** also has a cut-out or recessed portion **269** to afford clearance for fiber ribbons being routed from below the adapter plate **59** to a second splice tray **196** stacked upon the first tray **196**.

FIG. **19** is a perspective view of the mass splice tray **196**, with a single fusion splice tray **238** and insert **237** mounted in place. A plurality of ribbon fibers (six in all) are shown leading into splices **271** (shown darkened for clarity and existing therefrom). A single fiber ribbon **272** is shown darkened for clarity, coming from the storage space below adapter plate **59** and entering channel **208**. Ribbon **272** emerges from channel **208** and passes within to curved end walls of tray **196**, then diagonally crosses over, as depicted by the arrow, passing under insert **237** and shelf **228** to circle around the opposite end as indicated by the arrow. Curved member **229** insures that the ribbon encounters no sharp edges. It then proceeds to the other end which it circles around, as indicated by the arrows, and then passes into the splice holder **238**. Such a routing of the ribbon is made possible by the placement of the splice holders on an elevated shelf, and provides a larger amount of allowable fiber slack. As pointed out hereinbefore, with ribbons it is desirable to have as much slack as can be accommodated.

The unique mass splice tray, **196** and the several components thereof as shown and described herein are the basis of U.S. patent application Ser. No. 081/851,102, filed concurrently herewith.

The foregoing description and the accompanying drawings have been for purposes of illustrating, in a preferred embodiment, the principles and features of the present invention. The splice closure of the present invention and the several novel components thereof is capable of handling a wide variety of optical fiber cable types without the necessity of customizing to accommodate particular cable types. Further, the closure affords ample storage for fiber slack, and can accommodate large numbers of fiber splices in a sealed enclosure having ready accessibility to the splices.

It should be noted that it will be obvious to those skilled in the art that many variations and modifications may be made to the preferred embodiment without substantial departure from the principles of the present invention. It is intended that all such variations and modifications be

included herein as being within the scope of the present invention. Further, in the claims hereinafter set forth, the corresponding structures, materials, acts, and equivalents thereof and of all means or step plus function elements are intended to include any structure, materials, or acts for performing the functions with other elements as specifically claimed.

We claim:

1. An anchor member for use in an enclosure having openings therein for passage of cables into and out of the enclosure and means within the enclosure for gripping cables passing through the openings, the enclosure further having support means for the anchor member, said anchor member comprising:

an elongated base portion having first and second ends; a first upstanding leg portion at one of said ends, said leg portion having a distal end;

a first receiving member having a bore therethrough for receiving a strength member of a cable at said distal end;

gripping means for releasably anchoring the strength member in said bore for resistance against tensile forces on the cable;

locating means for locating said anchor member in the enclosure; and

means for mounting said anchor member in the enclosure on the support means.

2. The anchor member as claimed in claim **1** wherein said leg portion is of a length sufficient to align substantially said bore with the axis of the cable passing through one of the openings in the enclosure when said anchor member is mounted in place.

3. An anchor member for use in an enclosure having openings therein for passage of cables into and out of the enclosure and means within the enclosure for gripping cables passing through the openings, the enclosure further having support means for the anchor member, said anchor member comprising:

an elongated base portion having first and second ends; a first upstanding leg portion at one of said ends, said leg portion having a distal end;

a first receiving member having a bore therethrough for receiving a strength member of a cable at said distal end;

said means for anchoring the strength member comprises at least one set screw in said receiving member;

means for locating said anchor member in the enclosure; and

means for mounting said anchor member in the enclosure on the support means.

4. An anchor member for use in an enclosure having openings therein for passage of cables into and out of the enclosure and means within the enclosure for gripping cables passing through the openings, the enclosure further having support means for the anchor member, said anchor member comprising:

an elongated base portion having first and second ends; a first upstanding leg portion at one of said ends, said leg portion having a distal end;

a first receiving member having a bore therethrough for receiving a strength member of a cable at said distal end;

means for anchoring the strength member in said bore;

means for locating said anchor member in the enclosure;

19

means for mounting said anchor member in the enclosure on the support means; and

said anchor member being made of a plastic material.

5 **5.** An anchor member for use in an enclosure having openings therein for passage of cables into and out of the enclosure and means within the enclosure for gripping cables passing through the openings, the enclosure further having support means for the anchor member, said anchor member comprising:

an elongated base portion having first and second ends comprising a substantially planar member having upper and lower surfaces and having first and second spaced side walls depending therefrom, each of said side walls having a lower edge;

a first upstanding leg portion at one of said ends, said leg portion having a distal end;

a first receiving member having a bore therethrough for receiving a strength member of a cable at said distal end;

means for anchoring the strength member in said bore; means for locating said anchor member in the enclosure; and

means for mounting said anchor member in the enclosure on the support means.

6. The anchor member as claimed in claim 5 wherein said means for locating comprises a first locating hole in said planar member.

7. The anchor member as claimed in claim 6 and further comprising a second locating hole in said planar member axially spaced from said first locating hole.

8. The anchor member as claimed in claim 7 wherein said first and second locating holes are rectangular in shape.

9. The anchor member as claimed in claim 5 wherein said means for mounting said anchor member in the enclosure comprises a first slot in each of said side walls extending from the lower edge of each of said side walls toward said lower surface of said planar member.

10. The anchor member as claimed in claim 9 wherein said first slots in each of said side walls are transversely aligned with each other.

11. The anchor member as claimed in claim 9 and further including a second slot in each of said side walls longitudinally spaced from said first slots and transversely aligned with each other.

12. The anchor member as claimed in claim 11 and further including a slit in each of said side walls extending from the lower edge of each of said side walls toward said lower surface of said planar member, said slits in said side walls being located between said first and second slots and spaced therefrom.

13. The anchor member as claimed in claim 12 wherein the slits in said side walls are transversely aligned with each other.

14. The anchor member as claimed in claim 13 and further including a transverse score in said upper surface of said

20

planar member, said score being aligned with said slits in said side walls.

15. An anchor member for use in an enclosure having openings therein for passage of cables into and out of the enclosure and means within the enclosure for gripping cables passing through the openings, the enclosure further having support means for the anchor member, said anchor member comprising:

an elongated base portion having first and second ends;

a first upstanding leg portion at one of said ends, said leg portion having a distal end;

a first receiving member having a bore therethrough for receiving a strength member of a first cable at said distal end;

means for anchoring the strength member in said bore;

means for locating said anchor member in the enclosure;

means for mounting said anchor member in the enclosure on the support means; and

a second upstanding leg portion at said one of said ends, said second leg portion being substantially parallel to said first leg portion and transversely spaced therefrom.

16. The anchor member as claimed in claim 15 wherein said second leg portion has a distal end, and a second receiving member at said distal end of said second leg portion having a bore therethrough for receiving a strength member of a second cable at said distal end of said second leg portion;

and means for anchoring the strength member of the second cable in said second receiving member.

17. The anchor member as claimed in claim 16 wherein said second upstanding leg portion is substantially the same length as said first upstanding leg portion.

18. The anchor member as claimed in claim 16 wherein said means for anchoring the cable strength member in said second receiving member comprises at least one set screw.

19. The anchor member as claimed in claim 18 wherein said elongated base portion comprises a substantially planar member having upper and lower surfaces and first and second spaced side walls depending therefrom, each of said side walls having a lower edge.

20. The anchor member as claimed in claim 19 wherein said means for locating comprises at least one locating hole in said planar member.

21. The anchor member as claimed in claim 19 wherein said means for mounting said anchor member in the enclosure comprises at least one slot in each of said side walls extending from the lower edge of each of said side walls toward said lower surface of said planar member.

22. The anchor member as claimed in claim 21 wherein said at least one slot in one of said side walls is transversely aligned with said at least one slot in the other of said side walls.

23. The anchor member as claimed in claim 15, wherein said anchor member is made of a hard plastic.

* * * * *