

US005835065A

United States Patent [19]


Wallace et al.


[11] **Patent Number:** **5,835,065**[45] **Date of Patent:** **Nov. 10, 1998**[54] **VARIABLE LENGTH WHIP WITH HELIX ANTENNA SYSTEM**[75] Inventors: **Raymond C. Wallace**, San Diego;
John K. M. Lee, Ramona; **Roger W. Martin**, San Diego, all of Calif.[73] Assignee: **Qualcomm Incorporated**, San Diego, Calif.[21] Appl. No.: **719,297**[22] Filed: **Sep. 19, 1996**[51] **Int. Cl.⁶** **H01Q 1/24**[52] **U.S. Cl.** **343/702; 343/895; 343/900**[58] **Field of Search** 343/702, 895,
343/900, 901; 455/89, 90; H01Q 1/24[56] **References Cited****U.S. PATENT DOCUMENTS**

5,594,457 1/1997 Wingo 343/895

Primary Examiner—Hoanganh T. Le*Attorney, Agent, or Firm*—Russell B. Miller; Roger W. Martin[57] **ABSTRACT**

An antenna system for a communication device. A whip antenna is surrounded by a helical antenna. A switch couples the helical antenna to the signal source when the whip antenna is in a retracted position. The whip antenna is comprised of an upper conductive portion, a lower conductive portion, and a dielectric portion which isolates the upper and lower conductive portions from each other. A conductive sleeve member surrounds the whip antenna and is slidably mounted thereon. In a first embodiment, when the whip antenna is extended, the conductive sleeve member slides over the dielectric portion, coupling the upper and lower conductive portions together. As the whip antenna is retracted, the helical antenna pushes the conductive sleeve member to the top end of the whip antenna, isolating the whip antenna from the helical antenna. In a second embodiment, the helical antenna is an integral part of the conductive sleeve member.

26 Claims, 4 Drawing Sheets






FIG. 2A






FIG. 2B






FIG. 4A




FIG. 4B

VARIABLE LENGTH WHIP WITH HELIX ANTENNA SYSTEM

BACKGROUND OF THE INVENTION

I. Field of the Invention

The present invention relates generally to antennas. More particularly, the present invention is directed to a novel and improved variable length whip and helix antenna system for use in a portable communication device.

II. Description of the Related Art

Portable communication devices, such as portable radiotelephones, typically employ a simple dipole whip antenna as the main antenna. This antenna is usually retractable to make the unit more compact when a call is not in progress. However, when the whip antenna is retracted within the portable radiotelephone housing, the efficiency of the antenna is substantially reduced due to the presence of conductive objects in the antenna pattern.

Several prior art antenna systems attempt to compensate for these object-induced nulls in the whip antenna pattern. For example, some prior art portable radiotelephones utilize a compact helical antenna as an auxiliary antenna, with the main whip antenna extending through the center of the helix. In these prior art portable radiotelephones, the helical antenna remains exposed while the main antenna is retracted within the radiotelephone housing. As such, the helical antenna is able to receive and transmit radio frequency (RF) signals even though the main antenna is retracted.

However, since the main whip antenna extends through the center of the helical antenna, there may be RF coupling between the helical antenna and the whip antenna when the helical antenna is in use, i.e. when the whip antenna is retracted. This coupling results in an undesirable loss of efficiency of the helical antenna. Some prior art antenna systems attempt to avoid this undesirable loss of efficiency due to coupling by fabricating a whip antenna in which a substantial length of the top portion of the whip antenna is constructed of a non-conductive material, such as plastic.

Such a prior art antenna system **100** is illustrated in FIGS. **1A** and **1B**. In FIG. **1A**, prior art antenna system **100** is seen to comprise a whip antenna **102** and a helical antenna **104**. Whip antenna **102** comprises a conductive portion **108** and a non-conductive portion **110**. Helical antenna **104** is typically encased in a dielectric housing **106** which is external to portable radiotelephone housing **150**. In FIG. **1A**, whip antenna **102** is fully extended, exposing conductive portion **108**. In this position, helical antenna **104** surrounds the bottom of conductive portion **108**.

In FIG. **1B**, whip antenna **102** is fully retracted, and helical antenna **104** receives and transmits RF signals. In this position, helical antenna **104** surrounds the non-conductive portion **110** of whip antenna **102**. Since the non-conductive portion **110** does not couple signal energy from helical antenna **104**, the undesirable loss in efficiency by parasitic coupling of whip antenna **102** described above is avoided.

However, a problem with the prior art solution described above is that when whip antenna **102** is in the extended position as shown in FIG. **1A**, helical antenna **104** has an unintended effect on the antenna pattern of whip antenna **102**. Some of the energy intended to be radiated through whip antenna **102** is coupled to helical antenna **104**. In many applications, this parasitic coupling by the helical antenna **104** is undesirable and inefficient in much the same way as the parasitic coupling by the whip antenna **102** as described above.

Another problem with the prior art solution as shown in FIGS. **1A** and **1B** is that the length of whip antenna **102** must be increased to incorporate non-conductive portion **110**. This results in an overall antenna length that is greater than is necessary for whip antenna **102** to perform efficiently. When whip antenna **102** is extended, the non-conductive portion **110** serves no functional purpose, increasing the physical antenna length without increasing the antenna electrical length. This extra length adds size, cost and weight to the portable radiotelephone **150**.

What is needed is a combination whip/helix antenna system which operates efficiently whether the whip antenna is extended or retracted, and in which the length of the whip antenna is independent of coupling considerations with the helical antenna.

SUMMARY OF THE INVENTION

The present invention is a novel and improved antenna system for a communication device. In the preferred embodiment, a whip antenna is surrounded by a helical antenna. The preferred embodiment of the antenna system further comprises a mechanical switch which couples the helical antenna to the signal source when the whip antenna is in a retracted position. The whip antenna is comprised of an upper conductive portion, a lower conductive portion, and an intermediate dielectric portion connected between the upper and lower conductive portions and isolating the upper and lower conductive portions from each other. A conductive sleeve member also surrounds the whip antenna and is slidably mounted thereon.

In a first embodiment, the helical antenna and the conductive sleeve member are two separate elements, with the helical antenna being fixedly mounted to the housing of the communication device. In this first embodiment, when the whip antenna is extended, the conductive sleeve member slides over the dielectric portion, coupling the upper and lower conductive portions together. As the whip antenna is retracted, the helical antenna pushes the conductive sleeve member to the top end of the whip antenna, isolating the whip antenna from the helical antenna. Furthermore, when the whip antenna is retracted, the mechanical switch couples the helical antenna to the signal source.

In a second embodiment, the helical antenna is an integral part of the conductive sleeve member. In this second embodiment, when the whip antenna is extended, the conductive sleeve member containing the helical antenna slides over the dielectric portion, coupling the upper and lower conductive portions together through the helical antenna element. The resulting antenna structure is a single radiating element having a lower whip-like conductive portion, an intermediate helical conductive portion, and an upper whip-like conductive portion. As the whip antenna is retracted, the housing of the communication device pushes the conductive sleeve member containing the helical antenna to the top end of the whip antenna, thereby isolating the whip antenna from the helical antenna. Furthermore, when the whip antenna is retracted, the mechanical switch couples the conductive sleeve member containing the helical antenna to the signal source.

In both of the above embodiments, since the conductive sleeve member couples the upper and lower conductive portions together when the whip antenna is extended, the physical length of the whip antenna is dictated only by the desired electrical length, and not by adverse RF coupling considerations. Furthermore, when the whip antenna is retracted, it does not adversely affect the antenna gain pattern of the helical antenna.

BRIEF DESCRIPTION OF THE DRAWINGS

The features, objects, and advantages of the present invention will become more apparent from the detailed description set forth below when taken in conjunction with the drawings in which like reference characters identify correspondingly throughout and wherein:

FIG. 1A is an illustration of a prior art antenna system in which the whip antenna is extended;

FIG. 1B is an illustration of the antenna system of FIG. 1A in which the whip antenna is retracted;

FIG. 2A is an illustration of a first embodiment of the antenna system of the present invention with the whip antenna extended and the sleeve member in cut-away view;

FIG. 2B is an illustration of the antenna system of FIG. 2A with the whip antenna retracted and the sleeve member in cut-away view;

FIG. 3A is an illustration of an exemplary portable radiotelephone, shown in partially cut-away view, employing the first embodiment of the antenna system of the present invention with the whip antenna extended;

FIG. 3B is an illustration of an exemplary portable radiotelephone of FIG. 3A with the whip antenna retracted;

FIG. 4A is an illustration of a second embodiment of the antenna system of the present invention with the whip antenna extended and the sleeve member in cut-away view; and

FIG. 4B is an illustration of the antenna system of FIG. 4A with the whip antenna retracted and the sleeve member in cut-away view.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

A first embodiment of the antenna system **200** of the present invention as shown in FIGS. 2A and 2B comprises a whip antenna **202** inserted longitudinally through the center of helical antenna **204**. Helical antenna **204** is preferably encased in a dielectric casing **206** such as plastic, and is mounted externally on portable radiotelephone housing **250** by means known in the art; for example, by a threaded insert (not shown). Whip antenna **202** may be extended as shown in FIG. 2A, or retracted within portable radiotelephone housing **250** as shown in FIG. 2B. In this first embodiment, regardless of whether whip antenna **202** is extended or retracted, helical antenna **204** remains mounted externally on housing **250**.

When whip antenna **202** is extended as shown in FIG. 2A, the helical antenna **204** is preferably not used, although it may be used to intentionally augment or alter the antenna gain pattern of whip antenna **202**. In order to switch out helical antenna **204** when whip antenna **202** is extended, a variety of electrical or mechanical switches may be used. For example, in FIGS. 2A and 2B, a feed point **220** of helical antenna **204** extends downwardly from the coils of helical antenna **204**. As can be seen from FIG. 2B, when whip antenna **202** is in a retracted position, feed point **220** is contacted by a spring arm **222** which provides signals to and from the radiotelephone's transceiver (not shown). Spring arm **222** is held securely against feed point **220** by a lateral spring force. However, when whip antenna **202** is in an extended position as shown in FIG. 2A, a widened portion **224** at the bottom of whip antenna **202** engages spring arm **222**, pushing spring arm laterally away from feed point **220** and electrically de-coupling spring arm **222** from helical antenna feed point **220**. By switching out helical antenna **204** when whip antenna **202** is extended, one may avoid

undesirable alterations or inefficiencies in the antenna gain pattern of whip antenna **202** when it is extended.

In another aspect of the first embodiment of the present invention, whip antenna **202** comprises an upper conductive portion **209**, a lower conductive portion **208**, and an intermediate dielectric portion **210**. A sliding sleeve member **211** surrounds whip antenna **202** and is slidably mounted thereon. In this first embodiment, sleeve member **211** is made of a conductive material, such as copper, steel or the like, and optionally may be outwardly encased in a protective dielectric material such as plastic (not shown). Also, although helical antenna **204** is illustrated in FIG. 2A and 2B as a proper helix, it may also be of other construction as is known in the art; for example a solid cylinder, a braided mesh, or a loop antenna. Likewise, whip antenna **202** may be of various constructions, such as telescopic or fixed length. Both upper and lower conductive portions **209**, **208** are constructed from metallic materials as are known in the art. Also, intermediate dielectric portion **210** is preferably constructed of a strong plastic, but may alternately be made of any non-conductive composite dielectric material as are known in the art.

When whip antenna **202** is extended from the portable radiotelephone housing **250** as shown in FIG. 2A, sleeve member **211** couples upper conductive portion **209** to lower conductive portion **208**, thus bypassing intermediate dielectric portion **210** and providing electrical continuity throughout the length of whip antenna **202**. In this extended position, whip antenna **202** conducts RF signals throughout its length. Current oscillates in whip antenna **202** through conductive portion **208**, sleeve member **211**, and upper conductive portion **209**, enabling whip antenna **202** to transmit and receive RF signals using its entire physical length.

As was previously mentioned, when whip antenna **202** is extended as shown in FIG. 2A, helical antenna **204** may be switched out by the engagement of widened portion **224** with spring arm **222**. In addition to switching out helical antenna **204**, spring arm **222** may also be used to couple whip antenna **202** to the radiotelephone's transceiver (not shown) if widened portion **224** is made of a conductive material, or is an integral part of lower conductive portion **208**. In such an embodiment, spring arm **222** would conduct RF signals to and from whip antenna **202** through widened portion **224** when whip antenna **202** is in the extended position shown in FIG. 2A, and would conduct RF signals to and from helical antenna **204** through feed point **220** otherwise, for example, when whip antenna **202** is in the retracted position shown in FIG. 2B.

In the first embodiment shown in FIGS. 2A and 2B, sleeve member **211** is a metallic cylinder having an inward turned "lip" or taper at each end for contacting the upper and lower conductive portions **209**, **208**. Alternatively, sleeve member **211** may be a "clip" arrangement which does not completely surround whip antenna **202**. Optionally, an upper lip of sleeve member **211** also engages sleeve stop **212**. Sleeve member **211** physically rests against sleeve stop **212** when whip antenna **202** is in the extended position illustrated in FIG. 2A. Sleeve stop **212** may be a "bump" on the upper conductive portion **209** as shown, or it may be a mere widening or flare of upper conductive portion **209**. Alternatively, sleeve stop **212** may be an integral part of lower conductive portion **208** as is shown in FIGS. 2A and 2B. Clearly, there are many different ways to physically suspend sleeve member **211** such that it bridges intermediate dielectric portion **210**, coupling upper conductive portion **209** to lower conductive portion **208**.

When whip antenna **202** is retracted substantially within portable radiotelephone housing **250** as shown in FIG. **2B**, sleeve member **211** is pushed to the top of whip antenna **202**, de-coupling upper conductive portion **209** from lower conductive portion **208**, and allowing intermediate dielectric portion to electrically isolate upper conductive portion **209** from lower conductive portion **208**. In this retracted position, helical antenna **204** is isolated from lower conductive portion **208** by the physical distance of intermediate dielectric portion **210**. As such, RF signals received and radiated by helical antenna **204** are not coupled to the entire length of whip antenna **202**, although there may be some negligible coupling to sleeve member **211** and upper conductive portion **209**.

In the first embodiment shown in FIG. **2B**, sleeve member **211** has an outer diameter smaller than the inner diameter of helical antenna **204**, and thus slides in between upper conductive portion **209** and helical antenna **204** when whip antenna **202** is in the retracted position. The sliding of sleeve member **211** as whip antenna **202** is moved from the extended position of FIG. **2A** to the retracted position of FIG. **2B** may be arrested by engaging a lower lip on sleeve stop **212**. Alternatively it may be arrested by engaging an upper lip on a widened upper end of upper conductive portion **209**. Based on the length of sleeve member **211** and the size and location of intermediate dielectric portion **210** along the length of whip antenna **202**, one may design many different schemes as are known in the art for limiting the travel of sleeve member **211** along the length of whip antenna **202**.

FIGS. **3A** and **3B** illustrate a partially cut-away view of the first embodiment of the antenna system **200** of the present invention employed by a portable radiotelephone **250** suitable for use with the present invention. When whip antenna **202** is in the extended position of FIG. **3A**, spring arm **222** engages widened portion **224**, switching out the helical antenna encased in dielectric housing **206**. Also, sleeve member **211** (here shown as a metallic cylinder with a lip at a top end) couples upper conductive portion **209** to lower conductive portion **208**, providing for full electrical continuity along the length of whip antenna **202**. When whip antenna **202** is in the retracted position of FIG. **3B**, spring arm **222** connects to the helical antenna encased in dielectric housing **206**. Also, sleeve member **211** slides to the top of upper conductive portion **209**, thus de-coupling upper conductive portion **209** from lower conductive portion **208**. In this position, the upper conductive portion **209** of whip antenna **202**, and the helical antenna encased in dielectric housing **206** are isolated from lower conductive portion **208** by intermediate dielectric portion **210**.

In this first embodiment of the present invention, spring arm **222** provides for the reduction of parasitic coupling by helical antenna **204** (see FIGS. **2A** and **2B**) when whip antenna **202** is extended, while sleeve member **211** provides for the reduction of parasitic coupling by whip antenna **202** when whip antenna **202** is retracted. Furthermore, sleeve member **211** allows the full physical length of whip antenna **202** to be used for receiving and radiating RF signals, without adding the additional length required in the prior art antenna system shown in FIGS. **1A** and **1B**. Thus, the physical length of whip antenna **202** in the present invention is independent of adverse coupling considerations found in the prior art antenna systems. Additionally, sleeve member **211** adds negligible size and weight to the phone, and may be compactly stored within helical antenna **204** when whip antenna **202** is retracted.

A second embodiment of the antenna system **200** of the present invention is illustrated in FIGS. **4A** and **4B**. This

second embodiment is similar to the first embodiment in that sleeve member **211** couples upper conductive portion **209** to lower conductive portion **208** when whip antenna **202** is in the extended position as shown in FIG. **4A**. However, in contrast to the first embodiment, helical antenna **204** is not fixedly mounted to the housing of portable radiotelephone **250**. In this second embodiment, helical antenna **204** is an integral part of sleeve member **211**, and current actually flows through helical antenna **204** when whip antenna **202** is in the extended position. Preferably, in this second embodiment, with the exception of helical antenna **204**, sliding sleeve member **211** is a non-conductive dielectric plastic material. Thus, when whip antenna **202** is extended, the resulting radiating element comprises a whip-like lower conductive portion **208**, the intermediate helical conductive portion of helical antenna **204** encased in sleeve member **211**, and the upper conductive portion **209**. When whip antenna **202** is in this extended position, helical antenna **204** behaves like a phasing coil, extending the electrical length of whip antenna **202**, while concentrating its radiating pattern along the horizontal plane. Alternatively, sleeve member **211** may still be a conductive material, however this would obviate the need for the helical antenna **204**, and the sleeve member **211** would merely act as a cylindrical radiator.

When whip antenna **202** is retracted as shown in FIG. **4B**, sleeve member **211** and integral helical antenna **204** are pushed to the top of whip antenna **202**, but remain exposed externally to portable radiotelephone housing **250**. However, feed point **220** of helical antenna **204** extends internally into portable radiotelephone housing **250** to make electrical contact with spring arm **222**. Thus, when whip antenna **202** is retracted, this second embodiment behaves similarly to the first embodiment of FIGS. **2A** and **2B** with helical antenna **204** acting as the primary radiator, while still isolating lower conductive portion **208** from whip antenna **202** by intermediate dielectric portion **210**. Alternatively, feed point **220** may be directly coupled to sleeve member **211** if sleeve member **211** is made from a conductive material. In such a case, the sleeve member **211** would act as a cylindrical radiator.

The previous description of the preferred embodiments is provided to enable any person skilled in the art to make or use the present invention. The various modifications to these embodiments will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other embodiments without the use of the inventive faculty. Thus, the present invention is not intended to be limited to the embodiments shown herein but is to be accorded the widest scope consistent with the principles and novel features disclosed herein.

We claim:

1. An antenna system comprising:

- a first antenna element having an extended position and a retracted position, said first antenna element comprising:
 - a first conductive portion;
 - a second conductive portion; and
 - a dielectric portion, disposed between said first and second conductive portions, for electrically isolating said first and second conductive portions when said first antenna element is in said retracted position;
- a second antenna element proximate said first antenna element; and
- a conductive sleeve member, for conductively coupling said first conductive portion to said second conductive

portion when said first antenna element is in said extended position.

2. The antenna system of claim 1 wherein said first antenna element is a whip antenna and said second antenna element is a helical antenna, said whip antenna extending longitudinally through a center of said helical antenna.

3. The antenna system of claim 2 wherein said conductive sleeve member is a conductive cylinder slidably mounted on, and substantially surrounding, said whip antenna.

4. The antenna system of claim 3 wherein said whip antenna further comprises means for preventing said conductive sleeve member from sliding beyond a predetermined location along said whip antenna.

5. The antenna system of claim 4 wherein said means for preventing comprises a stop mounted to said first conductive portion of said whip antenna.

6. The antenna system of claim 5 wherein an outer diameter of said conductive sleeve member is less than an inner diameter of said helical antenna, and wherein said conductive sleeve member is accommodated substantially within said center of said helical antenna when said whip antenna is in said retracted position.

7. The antenna system of claim 2 wherein said conductive sleeve member is a metallic clip slidably mounted on said whip antenna.

8. The antenna system of claim 7 wherein said whip antenna further comprises means for preventing said conductive sleeve member from sliding beyond a predetermined location along said whip antenna.

9. The antenna system of claim 8 wherein said means for preventing comprises a stop mounted to said first conductive portion of said whip antenna.

10. The antenna system of claim 9 wherein said conductive sleeve member is accommodated substantially within said center of said helical antenna when said whip antenna is in said retracted position.

11. An antenna system for use in a communication device having a housing, said antenna system comprising:

a first antenna element having an extended position wherein said first antenna element is substantially disposed externally to said housing and a retracted position wherein said first antenna element is substantially disposed internally to said housing, said first antenna element having a widened portion at a lower end said first antenna element further comprising:

a first conductive portion;

a second conductive portion; and

a dielectric portion, disposed between said first and second conductive portions, for electrically isolating said first and second conductive portions when said first antenna element is in said retracted position;

a second antenna element, disposed externally to said housing and surrounding said first antenna element;

a conductive sleeve member, for coupling said first conductive portion to said second conductive portion when said first antenna element is in said extended position; and

a spring arm for alternately coupling signals to and from said first and second antenna elements, said spring arm being disposed within said housing such that said widened portion of said first antenna element decouples said spring arm from said second antenna element when said first antenna element is in said extended position.

12. The antenna system of claim 11 wherein said first antenna element is a whip antenna and said second antenna element is a helical antenna, said whip antenna extending longitudinally through a center of said helical antenna.

13. The antenna system of claim 12 wherein said widened portion of said first antenna element is electrically conductive and wherein said spring arm couples signals to and from said first antenna element when said first antenna element is in said extended position.

14. The antenna system of claim 11 wherein said first antenna element is a whip antenna and said second antenna element is a helical antenna, said whip antenna extending longitudinally through a center of said helical antenna.

15. The antenna system of claim 14 wherein said conductive sleeve member is a conductive cylinder slidably mounted on, and substantially surrounding, said whip antenna.

16. The antenna system of claim 15 wherein said whip antenna further comprises means for preventing said conductive sleeve member from sliding beyond a predetermined location along said whip antenna.

17. The antenna system of claim 16 wherein said means for preventing comprises a stop mounted to said first conductive portion of said whip antenna.

18. The antenna system of claim 17 wherein an outer diameter of said conductive sleeve member is less than an inner diameter of said helical antenna, and wherein said conductive sleeve member is accommodated substantially within said center of said helical antenna when said whip antenna is in said retracted position.

19. The antenna system of claim 18 wherein said conductive sleeve member is a metallic clip slidably mounted on said whip antenna.

20. The antenna system of claim 19 wherein said whip antenna further comprises means for preventing said conductive sleeve member from sliding beyond a predetermined location along said whip antenna.

21. The antenna system of claim 20 wherein said means for preventing comprises a stop mounted to said first conductive portion of said whip antenna.

22. The antenna system of claim 21 wherein said conductive sleeve member is accommodated substantially within said center of said helical antenna when said whip antenna is in said retracted position.

23. An antenna system for use in a communication device having a housing, said antenna system comprising:

a first antenna element having an extended position wherein said first antenna element is substantially disposed externally to said housing and a retracted position wherein said first antenna element is substantially disposed internally to said housing, said first antenna element having a widened portion at a lower end, said first antenna element further comprising:

a first conductive portion;

a second conductive portion; and

a dielectric portion, disposed between said first and second conductive portions, for electrically isolating said first and second conductive portions when said first antenna element is in said retracted position; and

a spring arm for alternately coupling signals to and from said first and second antenna elements, said spring arm being disposed within said housing such that said widened portion of said first antenna element decouples said spring arm from said second antenna element when said first antenna element is in said extended position.

9

wherein said second antenna element couples said first
conductive portion to said second conductive portion
when said first antenna element is in said extended
position.

24. The antenna system of claim 23 wherein said first
antenna element is a whip antenna and said second antenna
element is a helical antenna, said whip antenna extending
longitudinally through a center of said helical antenna.

10

25. The antenna system of claim 24 wherein said whip
antenna further comprises means for preventing said second
antenna element from sliding beyond a predetermined loca-
tion along said whip antenna.

5 26. The antenna system of claim 25 wherein said means
for preventing comprises a stop mounted to said first con-
ductive portion of said whip antenna.

* * * * *