



US005839378A

# United States Patent [19]

[11] Patent Number: **5,839,378**

Stufflebeam et al.

[45] Date of Patent: **Nov. 24, 1998**

[54] **AGITATOR ASSEMBLY FOR A SEED METERING MECHANISM**

[75] Inventors: **John F. Stufflebeam**, Romeoville;  
**Thomas A. Olson**, Bolingbrook; **Lisle J. Dunham**, Downers Grove, all of Ill.

[73] Assignee: **Case Corporation**, Wis.

[21] Appl. No.: **700,217**

[22] Filed: **Aug. 20, 1996**

[51] Int. Cl.<sup>6</sup> ..... **A01C 7/00**

[52] U.S. Cl. .... **111/185; 111/181; 221/211; 221/273**

[58] Field of Search ..... **111/135, 170, 111/174, 177, 178, 179, 181, 184; 221/211, 278, 277, 203**

## [56] References Cited

### U.S. PATENT DOCUMENTS

1,591,637	7/1926	Matheson .....	221/203
1,651,605	12/1927	Kuhn et al. ....	221/203
2,880,906	4/1959	Probasco .....	221/203
3,820,666	6/1974	Nye et al. ....	221/211 X
3,990,606	11/1976	Gugenham .....	221/211
4,018,358	4/1977	Johnson et al. ....	221/211 X
4,029,235	6/1977	Grataloup et al. .	
4,047,638	9/1977	Harrer et al. .	
4,074,830	2/1978	Adams et al. .	
4,091,964	5/1978	Harrer .	
4,241,849	12/1980	Harrer .	
4,399,757	8/1983	Maury .	
4,450,979	5/1984	Deckler .	
4,469,244	9/1984	Maury .	
4,515,291	5/1985	Holmes .	
4,533,066	8/1985	Holmes et al. .	
4,589,433	5/1986	Abe .....	221/203 X
4,600,122	7/1986	Lundie et al. .	
4,601,372	7/1986	Swales et al. .	
4,613,056	9/1986	Olson .	
4,646,939	3/1987	Herriau .	
4,664,290	5/1987	Martin et al. .	
4,688,698	8/1987	Holland .....	221/211
4,697,721	10/1987	Johnson et al. ....	221/203 X
4,718,574	1/1988	Schoenmaekers .	

4,793,511	12/1988	Ankum et al. .	
4,799,291	1/1989	Ankum et al. .	
4,836,412	6/1989	Webber et al. .	
4,898,108	2/1990	McDermott .	
4,949,869	8/1990	Ribouleau .	
5,058,766	10/1991	Deckler .	
5,082,126	1/1992	Ribouleau .	
5,143,002	9/1992	Gaspardo .....	221/203 X
5,170,909	12/1992	Lundie et al. .	
5,325,800	7/1994	Wisor et al. .	
5,325,801	7/1994	Fiorido .	

### FOREIGN PATENT DOCUMENTS


0037775	B1	5/1984	European Pat. Off. .
0140701	A2	5/1985	European Pat. Off. .
0141638	A2	5/1985	European Pat. Off. .
0155688	A2	9/1985	European Pat. Off. .
0338883	A1	10/1989	European Pat. Off. .

*Primary Examiner*—Thomas B. Will  
*Assistant Examiner*—Victor Batson  
*Attorney, Agent, or Firm*—Richard A. Speer; Mayer Brown & Platt

## [57] ABSTRACT

A seed agitating assembly for a seed metering mechanism including a housing with a seed reservoir area wherein a mass of seeds are held and a rotatable seed disc internally carried by the housing. The seed disc is provide with a circular array of holes or throughopenings for captively transferring seeds from the seed reservoir to a seed discharge area on the seed metering mechanism. The seed discharge area is typically arranged in spaced relation from the seed reservoir. A rotary drive shaft extends endwise through the housing for imparting rotational movements to the seed disc. According to the present invention, a seed agitator assembly is provided for stirring or agitating the seeds in the seed reservoir. The seed agitating assembly includes a generally circular or plate-like member that is operably coupled to the drive shaft. The seed agitating assembly further includes a plurality of flexible arms carried by and radially extending beyond the periphery of the plate-like member for agitating the seeds in the seed reservoir as the plate-like member is rotatably propelled by the drive shaft.

**19 Claims, 18 Drawing Sheets**








FIG. 2





FIG. 3







FIG. 6




FIG. 7




FIG. 8






FIG. 9




FIG. 10




FIG. 11




FIG. 12






FIG. 13




FIG. 14




FIG. 16






FIG. 15



**FIG. 17**



**FIG. 18**



**FIG. 19**






FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 24A




FIG. 25




FIG. 26




FIG. 27




FIG. 28






FIG. 29





FIG. 30










FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 42






FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48




FIG. 49





FIG. 50





## AGITATOR ASSEMBLY FOR A SEED METERING MECHANISM

### FIELD OF THE INVENTION

The present invention generally relates to seed metering mechanisms and, more particularly, to an agitator assembly for agitating seeds in a seed reservoir area of the seed metering mechanism thereby preventing the seeds from becoming packed too tightly and maintaining the seeds in loose association relative to each other so that they will fill each hole in a revolving seed disc of the seed metering mechanism thus promoting accurate and consistent seed planting operations.

### BACKGROUND OF THE INVENTION

Seed meters of various designs have been used for some time to dispense seeds at a controlled rate into a seed furrow as the seed meter is advanced above and along the seed furrow. In a typical arrangement, a tractor is coupled to tow a tool bar to which are attached in a generally parallel, spaced apart relation a plurality of planting units with seed meter arrangement attached thereto. Each planting unit typically includes a seed hopper for containing and carrying a large quantity of seeds to be planted or a smaller container fed from a centralized bin or large hopper, a device for opening a furrow in the ground as the tractor drawn tool bar is advanced across the field over the ground, a seed meter is coupled to the seed hopper for dispensing individual seeds into the furrow at a controlled rate, and a further device for moving soil at the sides of the furrow to close the furrow over the seeds.

During a planting operation, the tractor typically moves across the field at speeds of about 4 to about 8 miles per hour. The spacing between adjacent individual seeds in each furrow can be as little as 0.5 inches or less or as much as 10 inches or more depending upon the particular seed being planted. The seed metering mechanism therefor must be capable of dispensing seeds at various rates in the order of 15 to 130 seeds per second or greater as well as at rates which are considerably less.

The many different types of seeds to be planted using a seed metering mechanism include corn, cotton, sorghum, sugar beets, soybeans and sunflowers to name a few. As will be appreciated, such seeds vary considerably in size, weight and shape. For example, peanut and edible bean seeds are among the largest seeds for planting and have elongated irregular shapes and outer surfaces. Soybean, and pelletized seeds are smaller and tend to be rounder and vary in shape and size. Sorghum and raw sugar beet seeds have a rounder almost spherical appearance. Sorghum seeds have a relatively smooth outer surface. On the other hand, raw sugar beet seeds have a very rough and irregular outer surface configuration. Cotton seed is small and shaped like some corn seed. On the other hand, corn seeds have a somewhat triangular shape with generally flat sides.

Despite these numerous differences in the size, shape and surfaces of such seeds, seed meters are expected and are required to handle all different types of seeds described above plus many more while requiring minimum effort regarding part changes and adjustments. At the same time, required spacing and depth standards of planting accuracy typically mandate a low error rate. A missed seed or doubling of seeds is undesirable and may be tolerated only very infrequently. Such requirements place considerable demands upon the accuracy of the seed metering mechanisms.

Some seed metering mechanisms used in planting operations of the type discussed above are of the mechanical type and include a vertical or horizontal seed plate or disc with mechanically actuated fingers or similarly operated mechanical devices for separating individual seeds from the seed disc and then dispense them into the furrow. While some mechanical seed meters are satisfactory for certain applications, they typically suffer from a number of limitations including the limited speed at which they can accurately dispense seeds, and inability to handle different type seeds without making cumbersome and extensive part changes, and an inherent design complexity which may typically add to the cost, wear and maintenance problems of the mechanically operated seed dispensing mechanisms.

Alternatively, a seed metering mechanism which utilizes an air pressure differential has been developed in an effort to overcome some of the problems of the mechanical seed meters. Air pressure differential seed meters, which are commonly known as air seed meters, are generally of two types. The first type being the positive pressure type and the second type relying upon negative pressure or vacuum.

In the positive pressure type of air seed metering mechanism, air is blown into the seed chamber and onto the surface of a rotating or otherwise movable and apertured member or disc in order to create the higher than atmospheric pressure in the chamber. This forces seeds from a seed mass onto the seed member or disc where they are retained for later release. The apertures or holes in the rotating member or disc are open to atmosphere where the individual seeds are held by the blowing air until the seeds are dispensed by interrupting the flow of air to the seeds.

While air seed meters of the positive pressure type offer certain advantages over mechanical seed meters, they have certain limitations of their own which may prove to be a significant disadvantage for various seeding applications. In an effort to fill each hole or opening with a seed as the seed disc rotates through the seed mass, a relatively high pressure differential is applied to the disc. Because the seeds are held in place on the rotating disc or other movable member by differential pressure resulting from positive pressure in the chamber, it is usually necessary that the air flow be directed through the seed mass to aid in the depositing of individual seeds onto the disc. The air flow has been found to interfere with the orderly delivery of seeds from the disc and, ultimately, to the ground. In positive pressure seed metering mechanisms, the seed hopper must be sealed to maintain pressure in the system. If for any reason the hopper lid comes off or the hopper otherwise becomes unsealed, the seed meter will not properly function.

Vacuum seed meters have been found to overcome some of the problems in the positive pressure seed meters and offer more control over the seed being transported by the seed disc. In vacuum seed meters, a vacuum source is typically coupled to a separate chamber on the opposite side of the seed disc from the seed mass with the vacuum communicating through the apertures in the seed disc to the seed mass. The vacuum is of sufficient magnitude such that it tends to draw seeds into the openings defined by the disc and hold the seeds thereto as the seeds are moved through the seed disc under the influence of the moving seed disc toward the seed discharge area of the seed metering mechanism. The openings between the outer surface of the seeds and the periphery of the openings in the disc allows air to pass therethrough thereby maintaining the seeds in operable association with the disc. Because the pressure differential at the seed disc comes from a vacuum source on the opposite side thereof and not from the flow of air at the same side



thereof as with positive pressure type seed metering mechanisms, the problem of having to direct an air flow through the seed mass and on to the seed disc are eliminated.

Regardless of which type of seed metering mechanism is used, whether it be a positive pressure type seed metering mechanism or a vacuum seed metering mechanism, there are instances when the seeds in the seed reservoir of the housing become compacted upon themselves. Seed compaction results from the row unit and the seed metering mechanism moving over bumpy fields. As a result of the vertical bumps of the seed metering mechanism housing, the seeds become compacted upon each other, As will be appreciated by those skilled in the art, the seed compaction problem is exacerbated in planting conditions during high humidity, dust and dirt carried in the environment, plus the weight of the seeds in the reservoir piled together.

As a result of seed compaction, it is difficult for the seeds to move into the recesses defined by the seed disc. Accordingly, it is common that not all of the holes or throughopenings in the seed disc have seeds locked or sucked into them. These spaces or openings between adjacent seeds can result in erratic seed plantings. That is, because seeds are not contained in each opening of the seed disc, due to compaction of seed mass in the seed reservoir, when the seeds are released in the discharge area of the seed metering mechanism there is erratic spacings and skips between adjacent seeds. Such erratic spacings typically result in poor planting conditions, low seed population and poor crop yield.

Thus, there is a need and a desire for a seed metering mechanism wherein the seeds in the seed reservoir area of the seed metering mechanism are inhibited from becoming compacted with each other and keeping the seeds stirred up and loose thus yielding a greater tendency for accurate seed plantings.

#### SUMMARY OF THE INVENTION

In view of the above, and in accordance with the present invention, there is provided a seed agitating assembly for a seed metering mechanism. As is well known, the seed metering mechanism typically includes a housing with a seed reservoir area wherein a mass of seeds are held and a rotatable seed disc internally carried by the housing. The seed disc is provided with a circular array of holes or throughopenings for captively transferring seeds from the seed reservoir to a seed discharge area on the seed metering mechanism. The seed discharge area is typically arranged in spaced relation from the seed reservoir. A rotary drive shaft extends endwise through the housing and preferably has a drive rotor at one end thereof for imparting rotational movements to the seed disc. According to the present invention, a seed agitator assembly is provided for stirring or agitating the seeds in the seed reservoir. The seed agitating assembly includes a generally circular or plate-like member that is operably coupled to the drive rotor. The seed agitating assembly further includes a plurality of flexible arms carried by and radially extending beyond the periphery of the plate-like member for agitating the seeds in the seed reservoir as the plate-like member is rotatably propelled by the drive shaft.

In a preferred form of the invention, each flexible arm of the seed agitator assembly has a flexible wire-like configuration. The flexible arm is preferably formed from a material such as nylon or a plastic-like material that offers both strength and flexibility during use. In a most preferred form of the invention, there are between four and eight flexible

wire-like arms extending radially beyond the periphery of the disc for imparting movement to the seeds in the seed reservoir of the seed metering mechanism. Regardless of their number, the plurality of flexible arms are preferably equidistantly arranged about the periphery of the plate-like member.

The plate-like member of the seed agitator assembly is drivingly coupled to the drive shaft to effect positive drive of the seed agitating assembly. In a preferred form, the plate-like member of the seed agitator assembly defines a multi-sided centralized throughbore that slidably fits over and about a complementarily shaped driver on the drive shaft.

The plate-like member of the seed agitator assembly has first and second major surfaces radially extending to the periphery thereof. One major surface of the plate-like member includes a plurality or series of receptacles. Each receptacle is configured to either have molded therein or removably accommodate one end of a flexible arm. The exterior surface of the receptacle is preferably configured to project outwardly in a fin or step-like fashion adding to the agitation of the seed mass in the seed reservoir as the plate-like member forcibly passes therethrough thus adding movements and stirring to the seed therein.

The opposite surface of the plate-like member of the seed agitating assembly has a generally planar configuration that preferably presses against a side surface of the seed disc. In a most preferred form of the invention, the plate-like member of the seed agitating assembly further comprises spring structure for constantly urging the agitating assembly away from the drive rotor and against the seed disc thus keeping it close to the seed disc to prevent seeds from inadvertently passing therebetween. In a preferred form of the invention, the spring structure is formed as an integral part of the plate-like member. Moreover, and to facilitate fabrication thereof, the plate-like member of the seed agitating assembly is formed from anon-metallic material.

The addition of a seed agitating assembly facilitates proper seed placement in each seed hole of the disc during a planting operation. That is, during a seed planting operation, the agitating assembly of the present invention continually moves through and stirs the seed mass thereby preventing compaction of the seeds therewithin. Thus, when a pressure differential is applied to the seed disc, the loosened seeds are readily drawn by vacuum pressure toward the openings in the disc thus adequately filling the array of openings in the disc. Forming the agitating assembly with flexible arms promotes the longevity of the seed agitating apparatus and allows longer periods before replacements are required. Moreover, forming the flexible arms from flexible wire material rather than projections extending from the back of the seed disc, enhances the usefulness of the agitator assembly as well as the seed disc. Furthermore, forming receptacles on the major side surface of the plate-like member furthermore adds to the movements imparted to the seeds as the plate-like member is propelled through the seed mass. Forming the spring structure as an integral part of the plate-like member reduces manufacturing costs and simplifies production of the agitating assembly. These and numerous other objects and advantages of the present invention will become readily apparent from the following detailed description, the appended claims, and the accompanying drawings.

#### DETAILED DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic right side elevational view of a planting unit with a seed metering mechanism in accordance with the present invention mounted thereon;



FIG. 2 is a rear perspective view looking forwardly of a seed hopper with a seed metering mechanism according to the present invention mounted thereon;

FIG. 3 is an enlarged right side elevational view of a seed metering mechanism with a fragmentary portion of a seed tube shown connected thereto;

FIG. 4 is a front elevational view of the seed metering mechanism of the present invention disassembled from the seed hopper;

FIG. 5 is a left side perspective view of the seed metering mechanism according to the present invention;

FIG. 6 is a sectional view taken along line 6—6 of FIG. 4;

FIG. 7 is an enlarged fragmentary view of the portion encircled by line 7—7 in FIG. 6;

FIG. 8 is an enlarged fragmentary view of the portion encircled by line 8—8 in FIG. 6;

FIG. 9 is an exploded perspective view of the seed metering mechanism of the present invention;

FIG. 10 is a right perspective view of a housing component forming part of the seed metering mechanism of the present invention;

FIG. 11 is an enlarged right side view of the housing component illustrated in FIG. 10;

FIG. 12 is a sectional view taken along line 12—12 of FIG. 3;

FIG. 13 is a sectional view taken along line 13—13 of FIG. 3;

FIG. 14 is a left side view of the housing component illustrated in FIG. 10;

FIG. 15 is an enlarged left side view of a portion of the housing illustrated in FIG. 14;

FIG. 16 is an enlarged left side view of the portion of the housing encircled in FIG. 15;

FIG. 17 is a right side view of a baffle used in combination with the housing of the present invention;

FIG. 18 is an end view of the baffle illustrated in FIG. 17;

FIG. 19 is a perspective view of a driven hub forming part of the seed metering mechanism of the present invention;

FIG. 20 is a perspective view of a drive hub forming part of a drive assembly of the seed metering mechanism of the present invention;

FIG. 21 is a right side view of the drive hub illustrated in FIG. 20;

FIG. 22 is a rear elevational view of the drive hub illustrated in FIGS. 20 and 21;

FIG. 23 is a perspective view of an agitator assembly used in combination with the seed metering mechanism of the present invention;

FIG. 24 is a right side view of the agitator assembly shown in FIG. 22;

FIG. 24A is a sectional view taken along line 24A—24A of FIG. 24;

FIG. 25 is an enlarged elevational view of a central portion of the agitator assembly showing a series of springs forming an integral part of the agitator assembly;

FIG. 26 is a sectional view taken along line 26—26 of FIG. 24;

FIG. 27 is a right side view of one form of seed metering plate to be used in combination with the seed-metering mechanism of the present invention;

FIG. 28 is an end view of the seed-metering plate shown in FIG. 26;

FIG. 29 is a right side view of a singulator apparatus arranged in combination with the seed-metering mechanism of the present invention;

FIG. 30 is an exploded perspective view of the singulator apparatus shown in FIG. 29;

FIG. 31 is a right side view of a base forming part of the seed singulator;

FIG. 32 is a sectional view taken along line 32—32 of FIG. 31;

FIG. 33 is a sectional view taken along line 33—33 of FIG. 31;

FIG. 34 is a perspective view of one form of singulator mount forming part of the singulator assembly;

FIG. 35 is a right side view of the singulator mount shown in FIG. 33;

FIG. 36 is a top elevational view, partly in section, of the singulator mount illustrated in FIG. 35;

FIG. 37 is a perspective view of another singulator mount forming part of the singulator apparatus shown in FIGS. 29 and 30;

FIG. 38 is a right side view of the singulator mount shown in FIG. 37;

FIG. 39 is a top plan view of the singulator mount shown in FIG. 38;

FIG. 40 is a perspective view of an actuator for the singulator apparatus;

FIG. 41 is a right side view of the actuator shown in FIG. 40;

FIG. 42 is an end view of the actuator shown in FIG. 40;

FIG. 43 is a side view of a cover forming part of the singulator apparatus of the present invention;

FIG. 44 is a sectional view taken along line 44—44 of the cover illustrated in FIG. 43;

FIG. 45 is a elevational view of a spool stud forming part of the singulator apparatus shown in FIGS. 29 and 30;

FIG. 46 is an end view of the spool stud shown in FIG. 45;

FIG. 47 is an elevational view of one form of singulator spool that can be used in combination with the singulator apparatus of the present invention;

FIG. 48 is a side view of the singulator spool illustrated in FIG. 47;

FIG. 49 is a partial sectional view taken along line 49—49 of FIG. 48; and

FIG. 50 is a partial sectional view taken along line 50—50 of FIG. 48.

#### DETAILED DESCRIPTION OF THE INVENTION

While the present invention is susceptible of embodiment in different forms, there is shown in the drawings and will hereinafter be described a preferred embodiment of the invention with the understanding that the present disclosure is to be considered as setting forth an exemplification of the present invention which is not intended to limit the invention to the specific embodiment illustrated.

Referring now to the drawings, wherein like reference numerals indicate like parts throughout the several views, an agricultural implement is schematically illustrated in FIG. 1 and is represented in its entirety by reference numeral 10. Implement 10 includes an elongated tool bar 12 which is supported for movement across and over fields by a plurality of wheels (not shown) and which is adapted to be towed in a given forward direction by a power source such as an



off-highway tractor or the like. Attached to the tool bar 12 are a plurality of planting units 14; with only one being illustrated and described in detail and from which a complete understanding of the present invention may be readily determined. As is well known in the art, the planting units 14 are mounted in side-by-side relation relative to each other along the length of the tool bar 12.

In the illustrated embodiment, each planting unit 14 preferably includes a conventional furrow opening apparatus generally indicated in FIG. 1 by reference numeral 18. As is known in the art, the furrow opening unit 18 preferably includes a pair of lateral spaced furrow opener discs 21, a furrow forming point, and an opener shoe 24. Alternatively, and without detracting or departing from the spirit and scope of the present invention, the planting unit 14 can be provided with a runner opener type for providing a furrow in the ground. The planting unit 14 further includes a pair of furrow closer discs 26 and a press wheel 28 arranged in fore-and-at relationship relative to each other.

A seed hopper 30 is likewise carried on each planting unit 14. The purpose of the seed hopper 30 is to provide storage for seed material that is to be gravitationally deposited to the ground as the planting unit moves over and across the field. It will be appreciated that a hopper container, smaller than that exemplified in the drawings, and connected to a centralized bin or large hopper would equally suffice without detracting or departing from the spirit and scope of the present invention. In the illustrated embodiment, a seed metering mechanism or apparatus 32 is arranged in seed receiving relation relative to the hopper 30 and, in the illustrated embodiment, forms part of the planting unit 14. The purpose of the seed metering apparatus or mechanism 32 is to uniformly release seeds received from the seed hopper 30 for deposit onto the ground. To facilitate delivery of seeds from the seed metering mechanism 32 to the ground, a vertically disposed seed tube 34 is mounted on the planting unit 14. The seed tube 34 is preferably of the type disclosed in co-pending and co-assigned patent application Ser. No. 08/581,444, filed Dec. 29, 1995, in the illustrated embodiment, a the full disclosure of which is incorporated herein by reference. Suffice it to say, the seed tube 34 defines a vertical passage 36 through which seeds are delivered to the ground.

As the power source or tractor pulls the tool bar 12 across and over the ground, the furrow opening apparatus 18 operates to open a furrow in the ground. Seeds from the hopper 30 flow into the seed metering mechanism 32 from whence seeds are introduced at a controlled rate into the seed tube 34 to uniformly move through the vertical passage 36 defined by tube 34 and are, ultimately, deposited onto the ground. The furrow closer 26 trails the furrow opening apparatus 18 and, as the implement 10 is drawn across the field, serves to close the furrow together and over the seed dispensed by the seed metering mechanism 32 into the furrow. The trailing press wheel 28 serves to compact the soil closed over the seeds.

In the illustrated embodiment, a pesticide hopper 38 is mounted toward a rear end of each planting unit 14. Hopper 38 preferably includes an insecticide and is provided with conventional dispensing means for applying controlled amounts of insecticide where desired in connection with the planting of seeds by each planting unit 14.

According to the present invention, the vacuum seed metering mechanism or apparatus 32 is mounted to and movable with the hopper 30 relative to frame structure 33 (FIG. 1) of the seed planting unit 14 and relative to the seed

tube 34. Moreover, the hopper 30 is mounted on and removable from the planting unit 14 in a conventional manner. As shown in FIG. 2, the seed metering mechanism 32 includes a split housing assembly 40 arranged toward the bottom of and in seed receiving relation relative to the seed hopper 30. The seed metering apparatus 32 mounted to each planting unit 14 (FIG. 1) is individually connected via a suitable flexible conduit 42 to a common vacuum source (not shown) suitably mounted for movement over and across the field.

As shown in FIGS. 2 through 5, the housing assembly 40 of the seed metering mechanism 32 has a generally cylindrical-like configuration measuring about 300 mm. in diameter. The housing assembly 40 is comprised of a housing or shell 44 that is rigidly secured to the seed hopper 30 and a cover or shell 46 releasably connected to shell 44. In the preferred form of the invention, the cover 46 is completely removable from the housing 44 when access to the interior of the seed metering mechanism 32 is desired or required. Preferably, a series of manually releasable fasteners 48 are equidistantly arranged about the periphery of the housing assembly 40 for releasably fastening the housing 44 and cover 46 in operable and substantially air tight relation relative to each other. In the illustrated embodiment, three fasteners 48 are provided for releasably securing the cover 46 to the housing 44.

The cover 46 of the split housing assembly 40 is preferably formed as a unitary or one-piece member that is formed with sealing surfaces and suitable cutoffs as an integral part thereof. As such, the seed metering mechanism of the present invention does not require additional parts to be added thereto to effect sealing such as rubber seals and the like. In the illustrated embodiment, the cover 46 is formed of a rigid nylon or thermoplastic material containing conventional antistat and/or other low friction agents such that no graphite, talc, or slick additives need to be used in combination with the seed metering mechanism of the present invention during operation thereof. Moreover, and as shown in FIG. 6, cover 46 of the split housing assembly 40 has an arcuate shaped chamber 50 extending about 270° and adjacent the periphery of the cover 46. As will be described in detail hereinafter, an exhaust or suction port 52 opens to the chamber 50 intermediate opposite ends thereof. As is conventional, the flexible conduit 42 is exteriorly connected to the exhaust port 52 such that a vacuum or negative pressure may be created in the chamber 50 when the cover 46 is fastened to the housing 44.

Chamber 50 in housing 46 is partially defined by a first annular or circular flat sealing face 54 formed integral with an inner surface 56 of the cover 46. Also arranged on the inner surface 56 of cover 46, in radially spaced congruent relation from the sealing face 54, is a second sealing face 58 that is likewise formed integral with the inner surface 56 of cover 46. Notably, the sealing faces 54 and 58 are arranged in generally planar relation relative to each other are formed integral with the cover 46 thus eliminating the need or requirement for additional separate rubber seals. Moreover, and as shown in FIG. 6, outwardly spaced from the sealing face 58, cover 46 defines a flat circular lip area 60 extending radially outwardly to the periphery of the cover 46. Notably, both the first and second seating faces 54 and 58 axially project from the inner surface 56 of the cover 44 beyond the circular lip area 60. Cover 46 furthermore defines a leg portion 62 that is generally coplanar with the flat lip area 60 and which extends tangentially away from one end of chamber 50.

As shown in FIG. 7, the inner and outer radially spaced sealing faces 54 and 58, respectively, are joined, at one end,



by a first radial web 64 that separates a leading end of vacuum chamber 50 from a seed discharge area of the seed metering mechanism 32 as will be discussed in detail below. In the illustrated form of the invention, the radial web 64 is preferably formed integrally with the cover 46 and has a flat sealing face 66 that is generally coplanar with the sealing faces 54 and 58 of cover 46.

As shown in FIG. 8, the opposite or trailing end of chamber 50 is defined by a second radial web 68 and elongate slot 69 defining a vacuum cutoff for the chamber 50. As shown, the radial web 68 is preferably formed integral with the cover 46 and likewise has a flat sealing face 70 formed planar with the sealing faces 54 and 58 of cover 46. Notably, cover 46 further defines an inclined ramp 72 radially extending through the chamber 50 and toward the vacuum cutoff 68 and elongate slot 69.

Turning now to FIG. 9, component assemblies of a preferred form of the seed metering mechanism 32 of the present invention are schematically illustrated in exploded perspective relative to each other. As shown, the seed metering mechanism 32 of the present invention preferably comprises the housing 44, a manually operated baffle assembly 100 that is operably adjusted from outside the housing assembly 40 of the seed metering mechanism 32, a drive assembly 200, an agitator assembly 300 for inhibiting seeds from compacting within the housing assembly 32, a seed disc or plate 400 that operably divides the interior of the housing assembly 32 into a seed chamber 74 (FIG. 4) between one side of the seed plate 400 and the interior of housing 44 and the vacuum chamber 50 between the opposite side of the seed plate or disc 400 and the cover 46, a singulator assembly 500 for inhibiting more than one seed from being advanced by the seed plate or disc 400 to the discharge area of the seed metering mechanism 32, a vibration mechanism 800 for facilitating the release of seeds from the disc 400 in the discharge area of the seed metering mechanism 32, and the cover 46 for closing the seed metering mechanism 32.

As shown in FIGS. 10 and 11, housing 44 of the seed metering mechanism 32 is preferably formed from a metal material and includes a generally planar back wall 76 having inner and outer surfaces 78 and 80, respectively. An annular hub 82 is formed at the center of the housing 44 and axially projects inwardly from the inner surface 78. The annular hub 82 defines a central bore 83 defining a longitudinal axis 84 for the seed metering mechanism 32. As shown in FIGS. 12 and 13, the drive assembly 200 axially extends through and is rotatably mounted within the hub 82 of housing 44. As shown in FIGS. 9 through 11, housing 44 defines a circumferential skirt or rim 85 that axially projects forwardly from the inner surface 78 in surrounding relation to a substantial portion of outer periphery of housing 44.

As shown in FIGS. 12 and 13, an annular portion of the edge of rim 85 cooperates and combines with the flat lip area 60 on the inner surface 56 of cover 46 to close the housing assembly 32. Notably, the area surrounded by rim 85 and between the seed plate or disc 400 and the inner surface 78 of the housing 44 defines a seed reservoir or chamber 86 wherein seeds are stored.

As shown in FIGS. 10 and 11, the annular rim or skirt 85 has arcuate areas 88 and 90 that are recessed from the remainder of edge. When the cover 46 is fastened to the housing 44, these recessed areas 88, 90 define circumferentially extending openings 89 (FIG. 4) and 91 (FIG. 13) allowing atmospheric air to enter the housing assembly 32 and maintain the seeds releasably attached to the disc 400 as

a function of the differential air pressures between the suction chamber 50 and the opposite side of the housing 32.

As shown in FIGS. 5, 10 and 14, the outer surface 80 of housing 44 defines a lug 92 which facilitates connection of the housing assembly 32 to the hopper 30. As shown, housing 44 further defines a chute 94 that allows and directs the gravitational flow of seed between the hopper 30 (FIG. 5) and the seed reservoir or chamber 86 (FIG. 12). In this regard, the back wall 76 of housing 44 defines an opening 96 (FIGS. 10 and 11) that allows seeds to pass from the chute 94 into the seed reservoir area or chamber 86 of the seed housing assembly 32.

Referring to FIGS. 10 and 11, housing 44 further defines a wall 97 spaced radially inwardly from rim 85 and axially projecting from the inner surface 76 of housing 44. The space or open area 95 between the rim 85 and wall 97 defines a seed exhaust area 98 for the seed metering mechanism 32. As shown, the exhaust area 98 opens at its lower end to the seed tube 34 (FIG. 1) and through which the seeds released from the seed plate 400 gravitationally move, ultimately, for deposit onto the ground. In this regard, the back wall 76 of housing 44 defines a series of vertically spaced openings 99 that allow atmospheric air to pass into the exhaust area 98 and facilitate the flow of seeds toward the seed tube 34 by eliminating or significantly reducing the air drawn upwardly into the seed discharge area 98 of the seed metering mechanism. In the preferred embodiment of the invention, and as shown in FIGS. 15 and 16, the openings 99 preferably have slotted or elongated configurations.

Returning to FIG. 3, when the cover 46 is releasably attached to the housing 44, a substantial portion of chamber 50 extends through the seed reservoir area 86 of housing 44. Moreover, the leading end of the vacuum chamber 50 is disposed proximate to but remains outside of the discharge chute 98 of the housing 44. At its other end, suction chamber 50 terminates toward the upper end of the discharge area or chute 98 such that seeds released from the seed plate 400 pass downwardly into the discharge chute 98 and pass gravitationally toward the seed tube 34. Moreover, with the cover 46 so arranged on the housing 44, leg portion 62 of the housing overlies and closes the open side of the discharge chute 98 defined by housing 44 to prevent seeds released from the seed plate from inadvertently escaping from the housing assembly 32.

The purpose of the seed baffle assembly 100 is to control the seed level in the seed reservoir 86 from outside of the housing assembly 40. With the present invention, and as mentioned above, the cover 46 is preferably removable from the housing 44. After the cover 46 is removed and the seed plate 400 is removed, the seeds in the reservoir 86 will tend to pour out to the ground. Moreover, if there is nothing to close the opening 96 at the bottom of the chute 94, the seeds in the supply hopper 30 will likewise tend to pour onto the ground. Accordingly, the present invention provides the seed baffle assembly 100 for selectively allowing the operator to choose the level of seed mass in the reservoir 86 from outside of the housing 44. That is, and unlike other seed metering mechanisms, the seed baffle assembly 100 is adjustable from the outside and does not require the operator to gain access to the interior of the seed metering mechanism 32 in order to close off the opening 96 leading from the hopper 30.

As shown in FIGS. 9, 17 and 18, the seed baffle assembly 100 comprises a seed baffle 102 having a general planar configuration. The seed baffle 102 defines a generally central throughbore 103 that allows the seed baffle 102 to be



mounted for rotation about the hub **82** of the housing **44** of housing assembly **40**. As shown in FIG. **12**, the seed baffle **102** is configured to mount in abutting and generally sealing relationship with the inner surface **78** of the housing **44**. Notably, the profile of the seed baffle **102** is such that the baffle **102**, when properly positioned relative to housing **44** of the housing assembly **40**, can completely close the opening **96** (FIG. **11**) at the bottom of the chute **94** through which seed is directed into the seed reservoir of housing **44**.

As shown in FIGS. **14** and **15**, the seed baffle assembly **100** further includes a linkage assembly **106** that is exteriorly manipulated from outside of housing **44** to effect the disposition of the seed baffle **102** and thereby control the operable size of the opening **96** in the housing **44**. Returning to FIG. **11**, the rear wall **76** of the housing **44** defines an arcuate slot **108** that extends through the wall **76** and has a radius concentric with the longitudinal axis **84** of the hub **82**. The exterior surface **80** of the rear wall **76** of housing **44** furthermore defines a pivot **110** (FIG. **15**).

In the illustrated embodiment of the invention, and as shown in FIGS. **14** and **15**, the linkage assembly **106** of the seed baffle assembly **100** preferably comprises a manually operated elongated lever **112** that extends parallel to the rear wall **76** of housing **44** and is pivotally connected intermediate its ends to a pivot **110** defined on the exterior **80** of housing wall **76**. A free end **113** of lever **112** extends beyond the periphery of the housing **44**. An elongated link section **114** of lever **112** extends parallel to an exterior side **80** of wall **76** and away from the pivot **110** of lever **112**. As will be appreciated, movement of lever **112** will result in pivotal movement of the link section **114**. A second elongated link **116**, arranged parallel to and extending adjacent the outer surface **80** of wall **76**, is articulately joined, at one end, to the free end of link section **114** of lever **112**. At its opposite end, link **116** is connected through the slot **108** to the seed baffle **102** (FIG. **17**). The connection between and the travel of link **116** of linkage assembly **106** is guided by the arcuate shape of the slot **108**. As will be appreciated, opposite ends of the slot **108** limit the travel of the linkage **106** and thereby the travel of the seed baffle **102** relative to the opening **96** in the rear wall **76** of the housing **44**.

As shown in FIGS. **10**, **14** and **15**, the exterior surface **80** of wall **76** on housing **44** defines a flange **118** preferably formed integral with the housing **44** and extending generally normal to the major exterior surface **80** of the housing **44**. The flange **118** defines a series of vertically spaced detents or notches **120**, **122**, **124** and **126**. Each notch or detent **120**, **122**, **124** and **126** opens to a common side of flange **118** to releasably accommodate the lever **112** therewithin.

In a preferred form of the invention, the lever **112** is sized such that the free end thereof extends radially past the flange **118** for easy and ready manual engagement. In a most preferred form of the invention, and to facilitate insertion of the lever **112** into the respective notch **120**, **122**, **124** or **126**, in the area where the lever **112** passes in proximity to the notches **120**, **122**, **124** and **126**, the lever **112** is configured with a generally circular cross-sectional configuration. The thickness of each notch or recess **120**, **122**, **124** and **126** defined on flange **118** closely proximates the diameter of the lever **112**. By such construction, the lever **112** can be manually and readily shifted from one notch to the other while the respective notches furthermore serve to releasably maintain the lever **112** in position selectively chosen by the operator during the functioning of the seed metering mechanism **32**. As will be appreciated, movement of the lever **112** likewise effects displacement of the seed baffle **102** relative to the opening **96** thereby regulating the flow of seeds through the opening and into the seed reservoir **86**.

In the illustrated form of the invention shown in FIG. **13**, the notches **120** and **126** define the extreme limits of movement of the seed baffle **102** relative to the opening **96** leading to the seed reservoir **86**. Moreover, it should be readily appreciated that less or more notches than that shown can be arranged on the housing **44** without detracting or departing from the spirit and scope of the present invention.

A schematic illustration of the drive mechanism **200** is provided in FIGS. **12** and **13**. As shown, the drive mechanism **200** comprises a driven shaft **202** that is rotatably mounted within the bore **83** defined in the housing **44** and coaxial with the longitudinal axis **84** of the seed meter assembly **32**. As shown, the driven shaft **202** has a center section **204** with reduced diameter sections **206** and **208** axially extending from opposite sides of the center section **204** and extending to respective free ends of the shaft **202**. Notably, the differences in diameter between the center section **204** and the reduced diameter section **208** results in the provision of a radial shoulder **210** therebetween. In the illustrated embodiment, the radial shoulder **210** on the shaft **202** abuts with an inward projection defined by the hub **82** on the rear wall **76** of housing **44** thereby limiting axial displacement of the driven shaft **202** to the left as shown in FIG. **6**.

The reduced diameter section **206** projects outwardly from the rear wall **76** of the housing **44** and has a driven coupler **214** carried at the free end thereof for releasably coupling the driven shaft **202** to a conventional drive coupler mechanism (not shown) that typically forms part of the planting unit **14**. As shown in FIGS. **12**, **13** and **19**, the driven coupler **214** has a mounting hub **216** that fits about and is releasably connected to the reduced diameter section **206** of the driven shaft **202** as with a suitable pin **218** or the like. The driven coupler **214** furthermore includes a driven lug **220** that axially extends generally parallel to but is disposed in radially spaced relation relative to the longitudinal axis **84** of the seed metering assembly **32**. As will be appreciated, movement imparted to the driven lug **220** will likewise be transferred to the mounting hub **216** and thereby to the driven shaft **202**. As is well known in the art, the driven lug **220** mates with a drive lug (not shown) provided on a conventional and well known drive coupler (not shown) that is disposed on the outside of the exterior surface **80** of the housing **44** and which conventionally forms part of the drive coupler mechanism. As will be appreciated by those skilled in the art, using only a single or one driven lug **220** on the drive mechanism **200** facilitates removal, when necessary, of the hopper **30** and the seed metering mechanism **32** from the planting unit **14**.

A drive rotor **230** is mounted at the opposite end of driven shaft **202** on the reduced diameter section **208**. As shown in FIGS. **20**, **21** and **22**, the drive rotor **230** comprises a mounting hub **232** that fits about and is releasably secured to the reduced diameter section **208** of the driven shaft **202** as with a suitable pin **234** (FIG. **22**) or the like. Notably, and as shown in FIGS. **12** and **13**, the mounting hub **232** has a greater diameter than the bore **83** defined in the hub **82** and through which the reduced diameter portion **208** axially extends. Accordingly, when the drive rotor **230** is fastened to the driven shaft **202**, the driven shaft **202** is prevented from moving to the right as shown in FIGS. **12** and **13** by the mounting hub **232** abutting with the hub **82** in the housing **44** of the seed metering housing assembly **32**.

Returning to FIGS. **20** through **22**, the drive rotor **230** further includes first and second driving sections **240** and **250**, respectively, that are arranged in centered relation about the longitudinal axis **84** of the seed metering mecha-



nism 32. As shown, the drive rotor 230 includes an enlarged disc-like member 236 defining a central bore 237 and having generally planar axially spaced and generally parallel major surfaces 238 and 239, respectively, radially extending outwardly to the periphery of the drive rotor 230. Projecting axially outwardly from the major surface 238 of the disc-like member 236 are the first and second driving sections 240 and 250, respectively.

The first driving section 240 comprises a multi-sided configuration wherein each of the sides of the driving section 240 are equal to each other but define a flat surface area 241 that is axially spaced from and is smaller than the major surface 238 of the disc-like member 236 such that surface 238 acts as a stop for the axial arrangement of subsequent members or pieces placed thereabout as will be described in detail hereinafter. In the illustrated embodiment, driving section 240 has a generally triangular configuration including side surfaces 242, 244 and 246 that axially project from the major surface 238 of the disc-like member 236 of drive rotor 230. It will be appreciated, however, that other configurations for the driving section 240 would equally suffice without detracting or departing from the spirit and scope of the present invention. For example, the first driving section 240 could be configured with four equal sides or five equal sides that axially project away from the planar surface 238 of the disc-like member 236.

The second driving section 250 of the drive rotor 230 likewise comprises a multi-sided configuration that axially extends beyond the first driving section 240. In the illustrated embodiment, the second drive section 250 comprises a plurality of equally spaced and axially elongated pins 252. Moreover, the pins 252 are all arranged in a common radial distance from the longitudinal axis 84 of the seed metering mechanism 32. In the illustrated embodiment, each pin 252 has a generally cylindrical like configuration between opposite ends thereof. It will be appreciated, however, that other pin configurations would equally suffice without detracting or departing from the spirit and scope of the present invention. Moreover, each pin 252 has a chamfered configuration 254 at the distal end thereof for promoting axial placement of the seed metering disc 400 thereover. In the illustrated embodiment, the pins 252 are integrally formed with the disc-like member 236. It will be appreciated, however, that the pins 252 could be formed separate from and then added to the disc-like member 236.

The agitator assembly 300 is arranged in driving relation relative to the drive rotor 230 of the drive assembly 200. As mentioned, the purpose of the agitator assembly is to inhibit seeds from compacting within the seed reservoir 86 of the housing assembly 32.

In the illustrated embodiment, and as shown in FIGS. 23 and 24, the agitator assembly 300 includes a disc shaped rotor 302 having a central hub 304 and a plurality of flexible and readily replaceable arms or fingers 306 radially extending from the rotor 302. In the illustrated embodiment, the central hub 304 is axially displaced from the remainder of the rotor 302 and has first and second generally parallel side surfaces 308 and 310, respectively. Notably, the axial distance separating the first and second surfaces 308, 310 of the central hub 304 of rotor 302 is generally equal to the axial distance the side surfaces 242, 244 and 246 project away from the major surface of the disc shaped member 236 of drive rotor 230 of the drive section 240.

The central hub 304 of agitator assembly 300 furthermore defines a centrally located through opening 312 that is

configured to substantially correspond to the cross-sectional configuration of the first driving section 240 of drive assembly 200. That is, in the illustrated embodiment, the opening 312 in the rotor 302 of the agitator assembly 300 has a generally triangular configuration that substantially corresponds to the triangular shape of the first driving section 240. It will be appreciated however, that changes in the configuration of the first driving section of drive assembly 200 will be equally reflected in the shape and size of the opening 312 in the rotor 302 of the agitator assembly 300. As such, when the rotor 302 of agitator assembly 300 is mounted on the first drive section of the drive rotor 230 of drive assembly 200, a drive connection is established between the drive rotor 230 of drive assembly 200 and the rotor 302 of agitator assembly 300.

The remaining portion of the disc shaped rotor 302 radially extending from the central hub 304 has generally parallel first and second side surfaces 318 and 320, respectively. Toward the periphery of the rotor 302 there are provided a series of equally disposed receptacles 322 for releasably accommodating one end of each finger 306. Each receptacle 322 has inclined surfaces 324 and 326 projecting angularly away from the side surface 318 of the rotor 302. Such receptacles 322 act as fins or step-like extrusions. As such, and upon rotation of the rotor 302, the seed mass in the seed reservoir 86 defined by the housing 44 of the housing assembly 32, is agitated by the receptacles 322 in a manner preventing the seed mass from compacting itself during operation of the seed metering mechanism 32. Similarly, the fingers 306 projecting radially or outwardly from each receptacle 322 tends to agitate the seed mass in the housing 44 upon rotation of the rotor 302.

In a preferred form of the invention, the fingers 306 projecting outwardly from the rotor 302 range in size from about 0.080 inches to about 0.095 inches in diameter and are preferably made from a nylon-like material or other suitable flexible material such as that used in grass trimming machines. Preferably, the fingers 306 radially extend outwardly for a distance equal to about 150 mm. Notably, the fingers 306 are disposed in a swept back configuration relative to the direction of rotation of the rotor 302. As such, should the fingers 306 engage an object along their path of travel, the fingers 306 merely tend to deflect around and out of the way of the obstruction without damaging either the obstruction or the finger 306. In a most preferred form of the invention, one end of each finger 306 is releasably accommodated within a hole or opening 330 defined by each receptacle 322 on the rotor 302. Accordingly, repair or replacement of the fingers 306 is readily and easily effected. It will be appreciated, however, that it is likewise within the spirit and scope of the present invention to form the fingers 306 as permanent cast or integral part of the rotor 302.

As shown in FIGS. 12 and 13, the rotor 302 of the agitator assembly 300 furthermore serves to axially urge the seed plate 400 in an axial direction and toward the cover 46 of the housing assembly 32. In this regard, and as best shown in FIG. 26, the rotor 302 of the agitator assembly 300 includes spring structure 350 for resiliently urging the seed plate 400 toward the cover 46 of the housing assembly 32 to maintain a sealing relationship between the seed disc 400 and the cover 46 throughout operation of the seed metering mechanism 32.

In the illustrated form of the invention, the spring structure 350 comprises a plurality of leaf springs 352 that are preferably formed integrally with the rotor 302. As shown in FIGS. 25 and 26, and in the area of the central hub 304, preferably adjacent and parallel to each side of opening 312,



the rotor **302** includes a plurality of fingers **352**. In the illustrated embodiment, each finger **352** has a cantilevered configuration. That is, each finger **352** is joined at one end to the rotor **302**. The free end of each finger **352**, however, axially projects beyond side surface **308** of the rotor **302** to resiliently engage the seed plate **400**.

During a seed planting operation, the tractor typically moves over the ground at a speed of about 4 to about 8 miles per hour. Seed spacings within the furrows can range between as little as 0.5 inches to as much as 10 inches between adjacent seeds. Accordingly, the rate of discharge from the vacuum seed metering mechanism **32** of the present invention can vary greatly from a very low discharge rate on the order of twenty seeds per second or less such as when the tractor is traveling at only about 4 miles per hour and up to 10 inch seed spacing is required to a very high rate on the order of about 130 seeds per second or greater where the tractor is traveling at a considerably faster speed and a seed spacing as little as 0.5 inches is required. It will be appreciated, therefore, that the seed metering mechanism **32** of the present invention must be capable of dispensing seeds at a rate which can vary considerably. To further complicate matters, the seed metering mechanism **32** of the present invention must be capable of handling different seeds of different sizes and surface characteristics. Ultimately, the important factor to be mastered relates to the ability to dispense seeds accurately.

In this regard, an advantageous feature of the present invention relates to the ability of quickly and easily change seed discs to accommodate the particular seed being planted. Another advantageous feature that is inherent with the design disclosed by the present invention relates to the ability to change seed discs without requiring the use of tools or other fasteners thereby significantly reducing the downtime incurred upon replacement or changing of the seed disc. Suffice it to say, and as shown in FIGS. **27** and **28**, the seed disc **400** is typically comprised of a metal material. It is also within the spirit and scope of the present invention to fabricate the seed disc **400** from a suitable plastic material. In either embodiment, the seed disc **400** measures about 300 mm. in diameter. The 300 mm. size of seed disc **400** is significantly greater than any seed discs currently known in the art and allows greater versatility in planting operations. Each seed disc **400** has a diameter greater than the diameter of the radially outermost sealing face **58** on the cover **46** of the housing assembly **40**.

The seed disc **400** has planar or flat first and second surfaces **402** and **404**, respectively, extending generally parallel to each other. The seed disc **400** furthermore has a plurality of apertures **410** therein arranged in a circumferential row adjacent but inside of a circular outer edge **412**. Each aperture **410** extends through the thickness of the seed disc **400** between the first and second surfaces **402** and **404**, respectively, of the disc **400**. As will be readily appreciated by those skilled in the art, and without departing or detracting from the spirit and scope of the present invention, the seed disc **400** can include additional rows of apertures (not shown) arranged closely adjacent and concentric to the first row of apertures **410**. Notably, the sides or surfaces **402** and **404** of the disc **400** in the area of each opening is substantially planar or flat with the remainder of the disc **400**. That is, the seed disc **400** is void of any recesses or voids arranged in surrounding relation to the openings **410**. The flat configuration of the plate or disc **400** across the entirety thereof and especially in the area of the openings **410** reduces frictional contact of the outer surface of the seeds when they are released from the disc in the discharge area **98** of the seed metering mechanism.

As shown in FIG. **27**, and toward the center thereof, each seed disc **400** includes a plurality of openings or drive sockets **420** that are equidistantly arranged relative to each other about a common diameter. Notably, the spacing between the openings **420** is equal to the spacing between the driving pins **252** of the second driving section **250** on the drive assembly **200**. Moreover, the shape and size of the apertures **420** in discs **400** correspond to the shape of the pins **252** of the second driving section **250** of drive rotor **230**. An important benefit is yielded by such construction. Because the disc **400** is mounted on the driving section **250** of drive rotor **230**, the disc **400** and the openings **410** provided therein turn about a fixed axis **84** of rotation. Accordingly, the openings **410** move along a predetermined path of travel as the disc **400** turns or rotates within the housing assembly **40**. Moreover, and as will be readily appreciated, different discs **400** are readily interchangeable within the seed metering mechanism **32** to accommodate different seed spacings and/or seeds having particular surface characteristics without the use of tools or fasteners. Notwithstanding the size of the seed disc **400**, the openings **410** thereon travel about a predetermined path of travel between the seed chamber **86** and the discharge area **98** of the seed metering mechanism.

As stressed throughout, an important aspect of seed metering mechanism **32** of the present invention relates to the ability to dispense the seeds to the ground with accuracy. This means that one seed and no more than one seed is planted at any desired location along the length of the furrow. As well known in the industry, dispensing or discharging more than one seed into the furrow at any single location, sometimes referred to as "doubling", is undesirable at the very least and is unacceptable for the majority of planting operations. The typical unavailability of suitable nutrients in the soil will simply not sustain or support the presence of two seeds at any single location.

For these and other reasons, and as shown in FIG. **29**, the seed metering mechanism **32** of the present invention furthermore includes a singulator assembly **500**. During operation of the seed metering mechanism **32** of the present invention, a suction is created in chamber **50** of housing **46**. As such, and as the apertures **410** on the seed disc **400** move through the seed mass in the seed reservoir **86** of housing **44**, one or more seed releasably attach themselves to the openings **410** in the seed disc under the influence of pressure differentials. As the seed disc **400** is drivingly rotated, the one or more seeds operably associated with each opening or aperture **410** moves with the seed disc toward the discharge area of the seed metering mechanism **32**. Intermediate the location where at the seeds operably attach themselves to the seed disc **400** and the seed discharge area of the seed dispensing mechanism from which the seeds gravitationally fall to the ground, the singulator assembly **500** of the present invention is provided to insure that one and only one seed is present in each opening or aperture **410** as the particular seed pocket or opening approaches the discharge area of the seed dispensing mechanism **32**. The seed singulator mechanism is indicated generally by reference numeral **500** in FIG. **29**. In the illustrated form of the invention, the singulator assembly **500** is shown attached to the backwall **78** of housing **44** of the housing assembly **40** as through a plurality of suitable fasteners **502** and **504** and is less sensitive to revolving speed of the seed disc **400** than are known seed singulator devices.

Turning to FIG. **30**, the singulator assembly **500** is shown in exploded perspective view. As shown, the singulator assembly comprises a base **510**, a pair of manually movable



brackets **530** and **550**, a manually operated adjustment mechanism **570**, and a cover **590**. Notably, one of the unique features of the present invention concerns the ability of the component parts of the singulator assembly **500** to be assembled and adjusted relative to each other without the use of screws or other fasteners. Accordingly, no tools are required for assembly or adjustment of the singulator assembly of the present invention thereby reducing downtime normally incurred during the planting operation when adjustment of the seed singulator is required or desired. Another salient aspect of the singular assembly **500** relates to the provision of at least three singulator spools **700** that are mounted in specifically spaced relation relative to the path of travel of the apertures **410** of the seed disc **400**.

Turning now to FIGS. **31** through **33**, the base **510** of the singulator assembly **500** includes a generally rectangular back wall **512** having a back side **513** and a front side **514**. Preferably, wall **512** of base **510** further includes a closed rim **515** extending about the peripheral edge of the back wall **512** and axially away from the front side **514** to define an enclosure or open cavity **516**. A pair of vertical disposed and horizontally spaced rails **518** and **520**, respectively, are provided within the enclosure **516**. As shown in FIG. **31**, the rails **518** and **520** are preferably integrally formed with the base **510**. It will be appreciated, however, that rails **518**, **520**, which are independently formed relative to the base **510**, would equally suffice. Apertured flanges **522** and **524** extend outwardly from the base **510** so as to allow releasable affixation of the base **510** to the housing **44** of the housing assembly as with suitable fasteners. Moreover, base **510** furthermore defines a central throughbore or opening **526** with radially elongated slots **527** and **528** that pass entirely through the base **510**. The slots **527** and **528** are arranged in diametrically opposed relation relative to each other and in generally concentric relationship relative to the bore or opening **526**.

Bracket **530** is shown in FIGS. **34** through **36**. As shown, bracket **530** includes a slidable member **532** that is preferably formed from hard plastic or nylon and is configured to slidably fit for vertical movement within the recess or opening **516** of base **510**. Bracket member **532** includes a top surface **534** and a bottom surface **536**. A pair of vertically disposed and horizontally spaced channels **538** and **540**, respectively, are provided and extend along the bottom surface **536** of the bracket member **532**. Notably, the size and spacing of the channels **538** and **540** are complementary to the size and spacing of the rails **518** and **520** on the base **510**. Bracket member **532** further defines a plurality of horizontally spaced and internally threaded recesses **542**, **544** and **546**. The threaded recesses **542**, **544** and **546** defined by bracket **532** are located in circumferentially spaced relation relative to each other on a common line of centers or a radius which is generally equal to the radius about which the holes or apertures **410** in the seed disc **400** are disposed. Bracket **532** further defines an elongated generally horizontal slot or opening **548** that passes between and opens to both the top and bottom surfaces **534** and **536**, respectively, of bracket member **532**.

Bracket **550** is shown in FIGS. **37** through **39**. As shown, bracket **550** includes a slidable member **552** that is preferably formed from hard plastic or nylon and is configured to slidably fit for vertical movement within the recess or opening **516** of base **510** in vertically disposed relation to bracket **530**. Bracket member **552** includes a top surface **554** and a bottom surface **556**. A pair of vertically disposed and horizontally spaced channels **558** and **560**, respectively, are provided and extend along the bottom surface **556** of the

bracket member **552**. Notably, the size and spacing of the channels **558** and **560** are complementary to the size and spacing of the rails **518** and **520** on the base **510**. Bracket member **552** further defines a plurality of horizontally spaced and internally threaded recesses **562**, **564** and **566**. The threaded recesses **562**, **564** and **566** defined by bracket **552** are likewise located on a common radius which is generally equal to the radius about which the holes or apertures **410** in the seed disc **400** are disposed. Bracket **552** further defines an elongated generally horizontal slot or opening **568** that passes between and opens to both the top and bottom surfaces **554** and **556**, respectively, of bracket member **552**.

The manually operated adjustment mechanism **570** for the singulator assembly is shown in FIGS. **40** through **42**. As shown, the adjustment mechanism **570** comprises an elongated lever **572**. The lower end of lever **572** is provided with a mounting pin **574** and a pair of actuating pins **576** and **578** disposed in equally spaced relation and on opposite sides of the mounting pin **574**. Notably, the mounting pin **574** is preferably formed integral with the lever **572** which is formed from plastic or nylon.

With the brackets **530** and **550** arranged in the enclosure **516** defined by base **510**, the lever **572** is arranged on the backside **513** of the base **510** and the mounting pin **574** is inserted endwise through the opening **526** in the base **510**. Notably, the diameter of the mounting pin **574** is substantially equal to the diameter of the hole or opening **526** in the base **510** such that the lever **572** is permitted to pivotally move and rock about an axis **575** defined by the mounting pin **574**. Similarly, the actuating pins **576** and **578** on the lever **572** project endwise through the arcuate slots **527** and **528**, respectively, of the base **510**. As such, the actuating pin **576** on lever **572** projects into the slot or opening **548** defined on bracket **530** while actuating pin **578** projects into the slot or opening **568** defined on bracket **550**. As will be appreciated by those skilled in the art, this arrangement allows the brackets to vertically move toward and away from each other along the rails **518** and **520** defined in the enclosure **516** of base **510** in response to manual pivotal or rocking movement of the lever **572** about the axis **575**. To facilitate movement of the lever **572**, the upper end of lever **570** is provided with a handle **580** that projects generally normal to the handle or lever **572** to readily allow manual manipulation of the handle or lever **570**.

The cover **590** for the singulator assembly **500** is schematically illustrated in FIGS. **43** and **44**. The cover **590** preferably includes a generally rectangular front wall **592** having a closed rim **594** extending about the peripheral edge thereof. Notably, the configuration of the front wall **592** and the rim **594** closely proximates if not corresponds to the configuration of the back wall **512** and closed rim **514** on base **510**. Cover **590** furthermore includes a central throughbore or opening **596** that is adapted to resiliently receive the free end of the mounting pin **574** of lever **572**. Preferably, the free end of the mounting pin **574** is configured to resiliently fit through the opening **596** in the front wall **592** of cover **590** in a manner securing the front wall **592** of cover **590** to the base **510** without use of further fasteners and yet allowing access to the interior of the singulator assembly when required.

Cover **590** further defines a plurality of vertically aligned and horizontally spaced pairs of openings **600**, **602** and **604**. Each vertically aligned pair of openings **600**, **602** and **604** comprises two vertically elongated slots **606** and **608**. As will be appreciated, the horizontal spacing between the pairs of openings **600**, **602** and **604** is equal to the horizontal



spacings between the threaded recesses 542, 544 and 546 of bracket 532 and the recesses 562, 564 and 566 of bracket 552. As will be appreciated, the elongated configuration of the openings 600, 602 and 604 allows for vertical displacement of the brackets 530 and 550 within the recess 516 of the base 510.

Cover 590 furthermore defines a generally vertical upstruck and arcuate bracket 620 that is generally coplanar with the top surface 622 of the cover 590. Notably, the bracket 620 has a relatively thin construction and thus a void or space 624 is provided on the rear side of the bracket 620. It is within this space or void 624 wherein the upper end of the lever 572 moves. Moreover, the bracket 620 is configured such that the handle 580 of lever 572 can extend thereover. Additionally, the top surface of the bracket 620 has indicia 630 thereon for readily providing a visual indication of the position of the lever 572.

The singulator assembly 500 further comprises a series of mounting studs 650 on which the singulator spools 700 are mounted. An exemplary form of stud 650 for mounting a single singulator spool 700 to the singulator assembly 500 is shown in FIGS. 45 and 46. As shown, each stud 650 comprises an elongated member 654 having a shank portion 655 with a shouldered and externally threaded end 656 and an enlarged head portion 658 at an opposite end thereof. Preferably, each stud member 654 is formed of metal. In the illustrated embodiment, each stud 650 is provided with a series of axially extending external splines 660 axially extending from the head portion 658 of each stud for about one-half the length thereof. Each stud 650 is provided with 4, 6, 8, 12 or more splines 660 as desired. Notably, the outside diameter of the stud member 654 is sized such that it is permitted to endwise pass through the vertically elongated slots 606 and 608 comprising each pair of openings 600, 602 and 604 in the cover 590 of the singulator assembly 500. Moreover, the external threading at end 656 of each stud member 654 corresponds to the internal threading or a metal insert (nut) within the recesses 542, 544 and 546 of bracket 530 (FIGS. 34 through 36) and within the recesses 562, 564 and 566 of bracket (FIGS. 37 through 39). Furthermore, it should be noted that the axial length of each spool member 702 is less than the axial distance separating the enlarged head portion 658 and the external threading 656 of each spool mounting stud 650.

An exemplary form of singulator spool 700 is schematically illustrated in FIGS. 47 through 50. As shown in FIG. 47, each singulator spool 700 comprises an elongated preferably metal tubular member 702 defining a longitudinal axis 704 which, when mounted to the seed metering mechanism, extends generally normal or perpendicular to the sides of the seed disc 400. In the illustrated embodiment, and at that end 706 of each spool disposed closely adjacent the seed disc 400 during operation of the seed metering mechanism, each spool member 702 preferably has a seed engaging portion projecting radially outwardly from the remainder of the spool. As shown, each spool member 702 preferably has a flared or frusto-conical seed engaging or surface configuration extending away from a planar bottom surface 707 defined by the spool member 702. As shown in FIGS. 47, 49 and 50, the flared profile at the free end 706 of each spool 700 increases in diameter toward end 706. Moreover, and as shown in FIGS. 47, 49 and 50, the bottom planar edge 707 of the spool 700 and the flared end 706 intersect with each other to define a relative sharp edge 709 extending about the periphery of the spool 700.

As shown in FIG. 48, the peripheral edge 710 of the free end 706 of spool member 702 has a changing or eccentric

profile relative to the longitudinal axis 704 of the spool member 702. That is, the seed engaging portion of each arcuate segment of the edge 710 of the enlarged free end of the spool member 702 is disposed at different radial distance from the longitudinal axis 704 of the spool member 702. The changing or eccentric profile allows or permits a changing circumferential surface area of the seed deflector portion of each spool 700 to be selectively positioned relative to the predetermined path of travel of the openings thereby changing the spacing of the seed deflector relative to the fixed path of travel of the openings 410 in the seed disc 400 and relative to each other. In this regard, and as shown in FIG. 47, the spool member 702 has a locating mark 703 thereon for providing a visual indication of the setting of the seed deflector 706 relative to the fixed path of travel of the seeds carried by the disc 400. In the illustrated embodiment, the locator or indicating mark 703 is provided adjacent or on the seed engaging surface portion of the seed deflector. It will be appreciated, however, that the locating or indicating mark can be provided elsewhere on the spool 700 without detracting or departing from the spirit and scope of the present invention.

As shown in FIGS. 49 and 50, each spool member 702 further defines an opening 712 extending axially through the spool member 704. As will be appreciated, rather than providing the peripheral edge 710 of the seed contacting surface eccentric relative to the axis 704 of the spool, it is also within the spirit and scope of the present invention to provide the opening 712 in eccentric relationship relative to the spool member.

At the flared end 706, the opening 712 in each spool member 704 has an enlarged counterbore portion 714 that is sized to accommodate the enlarged head portion 658 of the mounting stud 650 (FIGS. 45 and 46). The counterbore portion 714 of opening 712 is recessed or has a depth that allows the spool to be endwise moved without exposing the head portion 658 of the spool mounting 650 therebeyond. Because the enlarged counterbore portion 714 and the opening 712 are of different diameters, a radial wall or annular shoulder 713 is defined therebetween. Upon assembly, the enlarged head portion 658 engages with the annular shoulder 713 thereby limiting movement of the spool 700 relative to side of the seed disc 400. As mentioned, the overall length of the spool member 702 is less than the length of the mounting stud 650 thereby allowing axial or endwise displacement of the spool member 702 along the length of the stud 650. In this regard, a lengthwise portion of the opening 710 is provided with a series of internal splines 720 that are engagable with the external splines 660 on each mounting stud 650 for holding the seed engaging portion of the respective spool 700 in releasably fixed relation relative to the axis of rotation 704.

As mentioned above, the end 706 of each spool 700 has a flared or frusto-conical configuration. The slanted or angular configuration at the free end 706 of the spool 700 changes as a function of the angular orientation of the slanted surface relative to the longitudinal axis 704 of the spool 700. That is, the angular orientation of the flared end 706 of spool 700, in the area shown by lines 49—49 in FIG. 48, is equal to about a 45° angle relative to the planar bottom edge of the spool 700. In contrast, the angular orientation of the flared end 706 of spool 700, in the area shown by lines 50—50 in FIG. 48, may equal about 45° to 50° relative to the planar bottom edge 707 of the spool 700. As will be appreciated, the inclined surface configurations extending about the seed engaging portion of each spool defines an included angle ranging between about 35° and about 70°



between the inclined surface configuration and the adjacent face or side of the seed disc **400**. Accordingly, different effects or removal forces can be imparted to the seeds carried on the seed plate as a function of which angular orientation of the spool **700** is disposed relative to the seed pocket or opening **410** in the seed plate **400**.

As will be appreciated, the changing profile of the free edge **710** allows the disposition of the spool **700** to be manually changed relative to the path of movement of the openings **410** on the seed disc **400** moving therepast. The interaction of the external spline like configurations **660** on the stud **650** and the internal spline like configurations **720** on the spool **700** prevent the spool **700** from turning or rotating relative their respective stud **650**. Also, however, it is important to note that the interaction between the splines **660** and **720** allows the angular orientation of the spool **700** to be angularly adjusted as required to effect the necessary action relative to the seeds carried by the seed plate **400** toward the discharge area of the seed metering mechanism **32** of the present invention. It will be readily appreciated, of course, that the opening **710** in the spool **700** can be eccentric relative to the longitudinal axis **704** of the spool member **702** thereby effecting different adjustments of the spool **700** relative to the circular path of travel of the openings **410** in the seed disc **400**.

Returning to FIG. **30**, each spool **700** is mounted on a respective mounting stud **650** as shown. Notably, however, there is further provided a compression spring **760** or other form of resilient means for resiliently urging the spool axially outward and away from the cover **590** toward the seed disc **400**. As such, the planar bottom surface of the spool **700** is resiliently urged toward an adjacent relationship with the seed plate **400** and the edge of the spool serves to engage and orient the seeds traveling toward the discharge area of the seed metering mechanism **32**. The spring **760** furthermore allows the spool to be axially displaced against the action of the spring **760** until the cooperative instrumentalities, which in the illustrated embodiment includes the splines **660** on mounting member **650** and the splines **720** of the spool **700**, are released from each other thereby allowing rotation of the spool **700** about the axis **714** thereby adjusting the seed engaging surface relative to the predetermined path of the openings **410** on the seed disc **400**. As mentioned, the recessed bore **714** is sized to allow for axial displacement of the spool **700** relative to the mounting member **650** without exposing the head portion **658** thereof. After the seed engaging portion of the spool is properly positioned relative to the path of travel of the seed openings **410** in the disc **400**, the spool **700** is automatically returned to an operable position wherein the seed engaging portion is disposed adjacent the side of the disc **400** under the influence of the compression spring **760**. Thereafter, the cooperating instrumentalities on the mounting member **650** and spool releasably hold the seed engaging portion of the spool in fixed relation relative to the axis **714**.

With the present invention, a single singulator spool or up to six singulator spools can be used as part of the singulator assembly **500**. As shown in FIG. **29**, in a preferred form of the invention, normally two singulator spools **700** will be arranged to one side of the arcuate path of travel of the openings in the seed disc **400** while at least one singulator spool **700** will be arranged on the opposite side of the arcuate path of travel of the openings **410** in the seed disc **400**. As will be appreciated from an understanding of the present invention, the singulator assembly **500** offers several degrees of adjustment for orientating the seeds within the pockets or openings **410** of the disc **400** as well as for

disengaging surplus seeds from the plate **400**. First, the singulator spool **700** may be individually adjusted by turning or rotating the singulator spool **700** relative to its respective mounting stud **650**. Thus, different profiles on the singulator spool **700** can be properly orientated relative to the path of travel of the openings between adjacent spools **700**.

Alternatively, the singulator assembly **500** can be adjusted through use of the handle **570**, to move the brackets **530** and **550** that carry the singulator spools **700**. As will be appreciated, movement of the brackets **530** and **550** endwise within the cavity **516** defined by base **510** will move the singulator spools **700** carried by the brackets **530** and **550** relative to the arcuate path of travel of the openings **410** on the seed disc **400** thereby further effecting adjustment of the singulator apparatus **500**. To properly adjust the brackets **530** and **550** and the spools **700** carried thereon relative to the fixed path of travel of the openings **410** in the disc **400**, the indicia **630** provided on the cover **590** of the singulator apparatus **500** visually guides the operator to adjust the spools **700**.

Still another salient feature of the present invention relates to improving the release of the seeds from the seed disc **400** at the discharge area **98** of the seed metering mechanism **32**. Testing has revealed that imparting vibrations to the housing assembly **40** of the seed metering mechanism **32** facilitates the release of seeds from the seed plate **400** in the discharge area of the mechanism **32**. In this regard, and as shown in FIG. **11**, there is preferably provided a mechanism **800** for imparting vibrations to the housing assembly **40**. The vibration imparting mechanism **800** can take a myriad of shapes and sizes. Mechanism **800** can be driven in any suitable manner. Preferably, a mechanism that produces vibrations in the range of about 115 hz. to about 135 hz. appears to work well. In the illustrated form of the invention, an electrically operated vibration type mechanism including a housing **802** is securely fastened in and about the seed discharge area **98** of the seed metering mechanism and appears to operate satisfactorily. As will be appreciated, the vibration mechanism **800** can be mounted inside or outside of the housing **40** without departing or detracting from the spirit and scope of the present invention. Moreover, the vibrating mechanism **800** can be secured to the cover **46** to impart vibrations to the housing assembly **40**.

From the foregoing, it will be observed that numerous modifications and variations can be effected without departing from the true spirit and scope of the novel concept of the present invention. It will be appreciated that the present disclosure is intended as an exemplification of the invention, and is not intended to limit the invention to the specific embodiment illustrated. The disclosure is intended to cover by the appended claims all such modifications as fall within the scope of the claims.

What is claimed:

1. An agitator assembly for a vacuum seed metering mechanism including a housing divided into a seed reservoir and a vacuum chamber by a rotatable seed disc having a circular arrangement of throughholes provided therein to carry seeds under the influence of pressure differentials from the seed reservoir to a seed discharge area defined a spaced distance from said seed reservoir, a drive shaft being supported by and extending through said housing to rotate said seed disc, the agitator assembly comprising a plate-like member capable of being operably coupled to said drive shaft, the plate-like member having a generally circular periphery and first and second major surfaces, a series of flexible arms projecting outwardly beyond the periphery of said plate-like member to agitate the seeds in the seed



reservoir as the plate-like member is rotated with the arms sweeping through the seeds in the seed reservoir, and the second major surface having a series of outwardly-extending receptacles to further agitate the seeds in the seed reservoir as the plate-like member is rotated.

2. The agitator assembly according to claim 1 wherein the plate-like member is formed of a non-metallic material.

3. The agitator assembly according to claim 1 wherein the first major surface of said plate-like member has a generally planar configuration to mate against a face surface of said seed disc.

4. The agitator assembly according to claim 1 wherein said plate-like member defines a centrally located multi-sided throughbore for mating engagement with a complementarily shaped driver provided on said drive shaft to establish a drive connection therebetween.

5. The agitator assembly according to claim 1 further including spring structure to press the plate-like member against said seed disc in a predetermined axial direction.

6. The agitator assembly according to claim 1 wherein the arms are releasably connected to the plate-like member.

7. The agitator assembly according to claim 1 wherein the arms are formed integrally as part of the plate-like member.

8. The agitator assembly according to claim 1 wherein each arm is formed with a swept back configuration relative to the rotation of the plate-like member.

9. An agitator assembly for a seed metering mechanism including a housing having a seed reservoir wherein seeds are held, a rotatable seed disc having a circular array of throughholes to transfer seeds from the seed reservoir to a seed discharge area of the seed metering mechanism spaced from the seed reservoir, a rotary drive shaft defining an axis of rotation of said seed disc, said agitator assembly comprising a plate-like rotor member adapted to be driven by said drive shaft and a plurality of flexible arms extending outwardly from said rotor member beyond an outer periphery thereof to agitate seeds in the seed reservoir as the arms sweep through the seeds in the seed reservoir, each flexible arm being formed with a swept back configuration relative to the rotation of the rotor member.

10. The agitator assembly according to claim 9, wherein said rotor member defines a centrally located multi-sided throughbore for mating engagement with a complementarily shaped driver provided on said drive shaft to establish a drive connection therebetween.

11. The agitator assembly according to claim 9 wherein said rotor member has first and second major surfaces, one of said first and second major surfaces of said rotor member including a series of outwardly-extending receptacles to further agitate the seeds in the seed reservoir as the rotor member is rotated.

12. The agitator assembly according to claim 9 wherein the rotor member has first and second generally planar major surfaces, one of said first and second major surfaces of said rotor member having a generally planar configuration to mate against a face surface of said seed disc.

13. The agitator assembly according to claim 9 further including spring structure to urge said agitator assembly against said seed disc to maintain said agitator assembly and said seed disc in close relationship.

14. The agitator assembly according to claim 13 wherein said spring structure is formed as an integral part of said rotor member.

15. The agitator according to claim 9 wherein the arms are formed integrally as part of the rotor member.

16. A vacuum seed metering mechanism comprising a housing divided into a seed reservoir and a vacuum chamber by a rotatable seed disc having a circular array of throughholes provided therein to carry seeds under the influence of pressure differentials from the seed reservoir to a seed discharge area defined a spaced distance from said seed reservoir, a rotatable drive shaft supported by and extending through said housing to rotate said seed disc, and an agitator assembly including a plate-like member operably coupled to said drive shaft and having a generally circular periphery with first and second major surfaces, said agitator assembly further including a series of flexible arms projecting outwardly beyond the periphery of said plate-like member to agitate the seeds in the seed reservoir as the plate-like member is rotated and the arms sweep through the seeds in the seed reservoir each flexible arm being formed with a swept back configuration relative to the rotation of the seed disc.

17. The vacuum seed metering mechanism according to claim 16 wherein the drive rotor mounted on the drive shaft is provided with at least one axially extending pin and the seed disc includes a corresponding socket to receive each axially extending pin of the drive rotor respectively for driving engagement there between.

18. The vacuum seed metering mechanism according to claim 17 wherein the plate-like member defines a centrally located throughbore through which the at least one axially extending pin extends for receipt by the corresponding socket of the seed disc.

19. The vacuum seed metering mechanism according to claim 16 further including spring structure to press the plate-like member against the seed disc in a predetermined axial direction.

\* \* \* \* \*