



US005920752A

# United States Patent [19]

Karakama et al.

[11] Patent Number: **5,920,752**

[45] Date of Patent: **Jul. 6, 1999**

[54] **PROCESS CARTRIDGE INCLUDING A TONER FRAME SWINGABLY COUPLED WITH A DRUM FRAME FEATURE AND A GRIP FEATURE, AND AN APPARATUS USING THE SAME**

5,537,187	7/1996	Sekine .....	399/113
5,543,898	8/1996	Shishido et al. ....	399/111
5,638,161	6/1997	Numagami et al. ....	399/111

[75] Inventors: **Toshiyuki Karakama**, Tokyo; **Isao Ikemoto**, Kawasaki; **Yoshikazu Sasago**, Tokyo; **Haruhisa Oshida**, Hatogaya; **Shinya Noda**, Yokohama, all of Japan

### FOREIGN PATENT DOCUMENTS

0341667A3	11/1989	European Pat. Off. .
0501497A3	9/1992	European Pat. Off. .
0538479A1	4/1993	European Pat. Off. .
0586041A3	3/1994	European Pat. Off. .
0634707A2	1/1995	European Pat. Off. .
0708387A2	4/1996	European Pat. Off. .

[73] Assignee: **Canon Kabushiki Kaisha**, Tokyo, Japan

### OTHER PUBLICATIONS

European Search Report.

[21] Appl. No.: **08/637,264**

*Primary Examiner*—William J. Royer

[22] Filed: **Apr. 25, 1996**

*Attorney, Agent, or Firm*—Fitzpatrick, Cella, Harper & Scinto

### [30] Foreign Application Priority Data

Apr. 28, 1995 [JP] Japan ..... 7-104997

### [57] ABSTRACT

[51] **Int. Cl.<sup>6</sup>** ..... **G03G 21/18**

A process cartridge detachably mountable to a main assembly of an image forming apparatus includes a drum frame for supporting an electrophotographic photosensitive drum; a developing frame mounted to a developing roller for developing a latent image formed on the electrophotographic photosensitive drum; a toner frame having a toner accommodating portion for accommodating a toner to be used by the developing roller, wherein the toner frame is provided with a coupling member for swingably coupling with the drum frame, and is provided with a grip for gripping the process cartridge.

[52] **U.S. Cl.** ..... **399/111; 399/113**


[58] **Field of Search** ..... 399/110, 111, 399/113, 114

### [56] References Cited

#### U.S. PATENT DOCUMENTS

5,036,358	7/1991	Yoshida .....	399/64
5,223,893	6/1993	Ikemoto et al. ....	399/111
5,390,002	2/1995	Michlin .....	399/126
5,450,166	9/1995	Yashiro .....	399/111
5,500,714	3/1996	Yashiro et al. ....	399/111

**43 Claims, 21 Drawing Sheets**






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7






FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15






FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22

**PROCESS CARTRIDGE INCLUDING A  
TONER FRAME SWINGABLY COUPLED  
WITH A DRUM FRAME FEATURE AND A  
GRIP FEATURE, AND AN APPARATUS  
USING THE SAME**

FIELD OF THE INVENTION AND RELATED  
ART

The present invention relates to a process cartridge, a method for assembling a process cartridge, and an image forming apparatus.

The image forming apparatus in this specification includes an electrophotographic copying machine, an electrophotographic printer (for example, an LED printer or a laser beam printer), an electrophotographic facsimile, an electrophotographic word processor, and the like.

The process cartridge in this specification is a cartridge which is removably installable in the main assembly of an image forming apparatus, and in which a charging means, a developing means or a cleaning means, and an electrophotographic photosensitive member are integrally housed. It may integrally comprise an electrophotographic photosensitive member, and at least the charging means, the developing means, or the cleaning means, or may integrally comprise an electrophotographic photosensitive member, and at least the developing means. The charging means, the developing means, and the cleaning means are processing means which act on the electrophotographic photosensitive member.

A process cartridge system in which the aforementioned process cartridge is removably installed in the main assembly of an image forming apparatus, has been employed in an image forming apparatus based on the electrophotographic image formation process. According to this process cartridge system, users themselves can maintain the image forming apparatus; there is no need for service personnel. Therefore, this process cartridge system can remarkably improve the operational efficiency of the image forming apparatus. Consequently, the process cartridge system has been widely employed in the field of the image forming apparatus.

The present invention is a result of the further development of the aforementioned process cartridge.

SUMMARY OF THE INVENTION

It is a principal object of the present invention to provide a process cartridge and an image forming apparatus usable therewith wherein the load imparted to the process cartridge can be distributed.

It is another object of the present invention to provide a process cartridge and an image forming apparatus usable therewith wherein the load imparted to a coupling portion can be reduced.

It is a further object of the present invention to provide a process cartridge and an image forming apparatus usable therewith wherein productivity of the process cartridge is improved.

According to an aspect of the present invention, there is provided a process cartridge detachably mountable to a main assembly of an image forming apparatus, comprising: a drum frame for supporting an electrophotographic photosensitive drum; a developing frame mounted to a developing roller for developing a latent image formed on the electrophotographic photosensitive drum; a toner frame having a toner accommodating portion for accommodating the toner to be used by the developing roller, wherein the toner frame

is provided with a coupling member for swingably coupling with the drum frame, and is provided with a grip for gripping the process cartridge.

According to another aspect of the present invention, there is provided an electrophotographic image forming apparatus for forming an image on a recording material, wherein a process cartridge is detachably mountable to the image forming apparatus, comprising: a. mounting means for detachably mounting a process cartridge; the process cartridge including: a drum frame for supporting an electrophotographic photosensitive drum; a developing frame mounted to a developing roller for developing a latent image formed on the electrophotographic photosensitive drum; a toner frame having a toner accommodating portion for accommodating the toner to be used by the developing roller, wherein the toner frame is provided with a coupling member for swingably coupling with the drum frame, and is provided with a grip for gripping the process cartridge; the apparatus further comprising: b. feeding means for feeding the recording material.

These and other objects, features and advantages of the present invention will become more apparent upon a consideration of the following description of the preferred embodiments of the present invention, taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view depicting how a development frame and a cleaning frame are joined.

FIG. 2 is a sectional view depicting the internal structure of the joint between the development frame and the cleaning frame.

FIG. 3 is a partially cutaway plan view of the joint between the development frame and the cleaning frame.

FIG. 4 is a schematic section of an electrophotographic image forming apparatus, depicting the general structure thereof.

FIG. 5 is a cross-section of a process cartridge.

FIG. 6 is an external perspective view of the process cartridge.

FIG. 7 is an explanatory drawing depicting the structure of the right-hand guide for guiding the process cartridge during the insertion or removal thereof.

FIG. 8 is an explanatory drawing depicting the structure of the left-hand guide for guiding the process cartridge during the insertion or removal thereof.

FIG. 9 is a perspective view depicting how the process cartridge is installed into the image forming apparatus.

FIG. 10 is a sectional explanatory drawing depicting the state of the process cartridge having been partially inserted into the image forming apparatus.

FIG. 11 is a sectional drawing depicting the state of the process cartridge having been further inserted into the image forming apparatus.

FIG. 12 is a sectional view depicting the state of the process cartridge having been further inserted into the image forming apparatus.

FIG. 13 is a sectional view depicting the state of the process cartridge having been further inserted into the image forming apparatus.

FIG. 14 is a sectional view depicting the state of the process cartridge having been completely installed into the image forming apparatus.

FIG. 15 is a sectional drawing depicting the image forming apparatus, the lid of which is open, and in which the process cartridge has been completely installed.

FIG. 16 is an exploded perspective view of the cartridge frame.

FIG. 17 is a perspective view depicting how the toner seal is attached to the development frame.

FIG. 18 is an external perspective view of the process cartridge.

FIG. 19 is a perspective view of the process cartridge, depicting how a linking member is attached thereto.

FIG. 20 is a perspective drawing depicting how the process cartridge is held by a hand.

FIG. 21 is a perspective view of a toner accommodating container.

FIG. 22 is a perspective view thereof when the toner is filled.

### DESCRIPTION OF THE PREFERRED EMBODIMENTS

Hereinafter, the preferable embodiments of the present invention will be described in detail with reference to the drawings.

First, referring to FIGS. 1-14, a process cartridge in accordance with the present invention, and an electrophotographic image forming apparatus usable with such a process cartridge will be described in detail. As for the order in which descriptions are given, the general structures of the process cartridge and the image forming apparatus employing the process cartridge will be described at first, and then, cartridge installing means, the structure for opening or closing a drum shutter, the opening or closing movement of the drum shutter, and the structure of cartridge frames will follow. Thereafter, a method for joining the aforementioned two cartridge frames will be described.

#### {General Structure}

Referring to FIG. 4, in the electrophotographic image forming apparatus A (laser beam printer) in accordance with the present invention, a light beam which carries image data is projected from an optical system 1 onto an electrophotographic photosensitive member in the form of a drum to form a latent image thereon, and this latent image is developed into a toner image. The electrophotographic photosensitive member is charged by a charge roller 8 before it is irradiated with the image data carrying light beam. In synchronism with the formation of the toner image, recording mediums 2 disposed in a sheet feeder cassette 3a are separated and fed into the electrophotographic image forming apparatus one by one by a pickup roller 3b and a pressing member 3c placed in contact with the pickup roller 3b to apply a predetermined pressure. The recording medium 2 is further conveyed into the apparatus by a conveying means 3 comprising a conveyer roller pair 3d, a registration roller pair 3e, and the like. As a voltage is applied to a transfer roller 4 as a transferring means, the toner image formed on the electrophotographic photosensitive member integrally disposed in a process cartridge B is transferred onto the recording medium 2. The recording medium 2 having received the toner image is delivered to a fixing means 5 by a conveyer belt 3f. The fixing means 5 comprises a driving roller 5a, and a fixing roller 5d. The fixing roller 5d contains a heater 5b and is rotatively supported by a supporting member 5c. While the recording medium 2 is passed through the fixing means 5, heat and pressure are applied to the recording medium 2, whereby the toner image having been transferred onto the recording medium is fixed to the recording medium 2. The recording medium 2 with the fixed toner image is conveyed through a reversing passage and discharged into a sheet catcher portion 6, by discharge roller

pairs 3g and 3h. This image forming apparatus A also comprises a manual feeder tray 3i and a roller pair 3j so that the recording medium 2 can be manually fed.

The process cartridge B in accordance with the present invention comprises an electrophotographic photosensitive member and a minimum of one processing means. The processing means includes a charging means for charging the electrophotographic photosensitive member, a developing means for developing the latent image formed on the electrophotographic photosensitive member, a cleaning means for cleaning the toner remaining the surface of the electrophotographic photosensitive member, and the like. Referring to FIG. 5, in the process cartridge B, a photosensitive drum 7, which is an electrophotographic photosensitive member with a photosensitive layer, is rotated, and the surface of the rotating photosensitive drum 7 is uniformly charged by applying a voltage to the charge roller 8 which is the charging means. The surface of the photosensitive drum 7 is exposed to an optical image projected from the aforementioned optical system 1 through an opening 9, whereby a latent image is formed on the photosensitive drum 7. The latent image is developed by a developing means 10. As is evident from FIG. 5, the charge roller 8 is in contact with the photosensitive drum 7.

In the developing means 10, the toner contained in a toner holding portion 10a is sent out by a first rotary toner feeding member 10b1 and a second rotary toner feeding member 10b2, onto a development roller 10d, which is a developing member containing a fixed magnet 10c. As the development roller 10d is rotated, a layer of toner triboelectrically charged by the development blade 10e is formed on the surface of the development roller 10d. The toner particles in the toner layer are transferred onto the photosensitive drum 7 in correspondence to the aforementioned latent image, whereby the latent image is developed into a toner image, that is, a visible image.

After the toner image is transferred onto the recording medium 2 by applying to the transfer roller 4 a voltage with a polarity opposite to that of the toner image, the toner remaining on the photosensitive drum 7 is removed by a cleaning means 11 comprising a cleaning blade 11a for scraping off the residual toner, a reception sheet 11b for receiving the toner scraped from the photosensitive drum 7, and a waste toner collector 11c for collecting the waste toner. As is evident from FIG. 5, the cleaning blade 11a is in contact with the photosensitive drum 7.

The components such as the photosensitive drum 7 are integrally disposed within the frame of the process cartridge B, so that they can be removably installed within the apparatus main assembly 14. The cartridge frame is formed by joining a development frame 12 and a cleaning frame 13. The development frame 12 is formed by welding together a frame 12a, a development frame bottom portion 12b, and a development frame lid 12c.

#### {Cartridge Installing Means}

The process cartridge B is installed in the apparatus main assembly 14 by opening the lid 15 as shown in the drawing. Referring to FIGS. 7 and 8, the cartridge installing means comprises a pair of guide rails 16, which are exposed as the lid 15 is rotatively opened about an axis 15a (FIG. 4). The guide rails 16 are given an upward bowing curvature (in this embodiment, substantially arc-shaped), and symmetrically located in the respective lateral walls of the apparatus main assembly 14 across the cartridge accommodating space. Above the guide rails 16, a guide member 17 is attached. On the entrance side of the guide rails 16, a first slant surface 16a, and a second slant surface 16b are provided. The



second slant surface **16b** has a steeper angle than the first slant surface **16a**, and extends further downward from the bottom end of the first slanted surface **16a**.

On the other hand, the surfaces of the left and right longitudinal ends of the process cartridge B are provided with a guide portion, wherein the two guide portions symmetrically project in the longitudinal direction from the correspondent end surfaces of the process cartridge B, and are guided by the guide rails **16**. Referring to FIG. 6, the guide portion integrally comprises a boss portion **18** and a rib portion **19**. The boss portion **18** and the rib portion **19** are integrally formed with the cleaning frame **13** to which the photosensitive drum **7** is attached. The boss portion **18** is in line with the imaginary extension of the rotational axis of the photosensitive drum **7**, and the rib portion **19** extends backward, relative to the inserting direction of the process cartridge B, from the boss portion **18**, forming an upward bowing curvature (in this embodiment, substantially arc-shaped), which matches the configuration of the guide rails **16**.

Referring to FIGS. 10–15, when the process cartridge B is installed into the apparatus main assembly with the above described structure, the lid **15** is first opened, and the process cartridge B is inserted into the apparatus main assembly so that the leading end of the process cartridge B is caused to dive into the space below the optical means **1**. The guide rails **16** is arc-shaped, and the guide member **17** disposed above the guide rails **16** is given a configuration matching that of the guide member **17**. Further, the rib portion **19** also is given a configuration similar to that of the guide member **17**. Consequently, as the process cartridge B is inserted deeper, its orientation becomes substantially horizontal. As the cartridge B is pushed further inward, a bumping member **20** provided on the apparatus main assembly **14** comes in contact with a contact surface **21** provided on each longitudinal end of the leading end portion of the cleaning frame **13**, and then, the boss portion **18** of the process cartridge drops into a recess **16c** located at the deepest end of the guide rails **16**. As a result, a drum gear (unillustrated) fixed to one of the longitudinal ends of the photosensitive drum **7** is caused to engage with the driving gear **22** (FIG. 8) provided on the apparatus main assembly **14** side, enabling the driving force to be transmitted to the process cartridge B.

Next, referring to FIG. 12, as the lid **15** is closed, a pressing member **24**, which is axially supported on the lid **15**, and is under the pressure from a torsional coil spring, makes contact with the arm portion of the cleaning frame **13**, pressing it with a predetermined pressure generated from the torsional coil spring being torqued by the closing movement of the lid **15**. At the same time, the bumping member **20** provided on the apparatus main assembly **14** makes contact with the contact surface **21** of the process cartridge B, fixing the position of the process cartridge B.

Referring to FIG. 15, in order to take out the process cartridge B, the users open the lid **15**, whereby the pressure applied through the pressing member **24** is removed. In this state, the cartridge B is pulled upward so that the boss portion **18** comes out of the recess **16c**. Thereafter, the process cartridge B can be removed by pulling it as if rotating it in the counterclockwise direction of FIG. 12, with the rib portion **19** following the guide rails **16**.

The bottom portion of the cartridge frame is provided with an opening **O**, through which the photosensitive drum **7** comes in contact with the conveyed recording medium **2**. When the cartridge is not in use, the opening is covered by closing a drum shutter member **28** to protect the photosensitive drum **7**. Referring to FIG. 6, the drum shutter member

**28** is rotatively supported by a shutter arm **27** and a link member **29**. The shutter arm **27** is rotatively mounted on an axis **26** projecting outward from the longitudinal lateral wall of the development frame **12**, but the link member **29** is supported on the longitudinal lateral wall of the cartridge frame so that it can be rotated about the rotational center of an axis hole **36(a)**. As the process cartridge B is inserted along the guide rails **16** as described above, a projecting portion **29b** constituted of the bend portion of the link member **29** comes in contact with the first and second slant surfaces **16a** and **16b** of the guide rails **16**, causing the shutter member **28** to open (FIGS. 11 and 12). On the contrary, as the process cartridge B is taken out, the shutter member **28** is automatically closed by the pressure from the torsional coil spring **30** (FIG. 6) fitted around the axis **26**.

When the process cartridge B is inserted into or removed from the image forming apparatus A, the users pick up process cartridge B by the handhold portion **12c2** of the development frame **12**. The handhold portion **12c2** comprises the slanted upward facing surface of the cartridge lid **12c**. Referring to FIG. 6, this slanted portion, that is, the handhold portion **12c2**, is provided with minute ridges and valleys formed by numerous ribs **12c1** (extending in the direction perpendicular to the direction in which the process cartridge B is inserted into, or removed from, the apparatus main assembly). Referring to FIG. 5, the bottom portion of the cartridge frame is provided with an R portion which bulges downward, and this R portion is provided with several ribs **12a9** extending in the same direction as the aforementioned ribs **12a1**, constituting the handhold portion **12a10**. In order to install the process cartridge B into the image forming apparatus A, or remove it therefrom, the users pick up the process cartridge B by grasping it by the handhold portions **12c2** and **12a10** (ribs **12c1** and ribs **12a9**) as illustrated in FIG. 20, and then insert it into the apparatus main assembly, with the boss portion **18** and the rib portion **19** of the cleaning frame **13** following the guide rails **16**.

When the process cartridge B is pushed into the apparatus main assembly excessively fast, the process cartridge B is liable to be subjected to a large shock, which mostly acts on the pin **41** joining the development frame **12** and the cleaning frame **13**. However, the development frame **12** and the cleaning frame **13** are rotatable about the pin **41**; therefore, the aforementioned shock is distributed throughout the entire cartridge frame; the shock does not concentrate on a specific portion. In other words, the shock does not concentrate on the welded joint between the toner holding frame portion **12a** and the development frame bottom portion **12b**. Therefore, the strength with which the toner holding frame portion **12a** and the development frame bottom portion **12b** are welded has only to be enough to keep both frame portions **12a** and **12b** joined. Consequently, when welding the toner holding frame portion **12a** and the development frame bottom portion **12b**, it is unnecessary to specifically control the welding conditions, allowing the development frame **12** to be assembled without losing productivity.

Further, the means for positioning the development roller **10d**, and a mounting seat for the development blade **1e**, are provided on the toner holding frame portion **12a** as described in the foregoing. Therefore, in spite of the fact that the toner holding frame portion **12a** is provided with the arm portion **38**, the development roller **10d** and the development blade **10e** can be precisely positioned, so that their positional relationship with the photosensitive drum **7** mounted on the cleaning frame **13** can be maintained with sufficient precision.

{Structure for Opening or Closing Drum Shutter}

Referring to FIGS. 6, 18 and 19, the structure for opening or closing the aforementioned drum shutter will be described.

(Structure for Opening or Closing)

Referring to FIG. 6, one end of the shutter arm 27 is rotatively mounted on the axis 26 provided on the longitudinal end surface of the toner holding frame portion 12a, and to the other end, a ring portion 28a formed at one end of the shorter edge of the drum shutter member (protective cover) 28 is rotatively attached. The shutter member 28 is provided with a groove 28b, which runs adjacent to the longitudinal edge on the side opposite to the ring portion 28a, across the entire length of the edge. In this groove 28b, the shutter link member (supporting member) 29 formed by bending the metallic wire is rotatively anchored.

Referring to FIGS. 6 and 18, the end portion 29a of the link member 29 is rotatively supported by a link supporting member 36 and a gear cover 31. Referring to FIG. 19, the link supporting member 36 covers a toner filling opening 32 of the toner holding frame portion 12a. During the assembly process of the process cartridge B, toner is filled into the toner holding portion 10a through the toner filling opening 32, and the toner filling opening 32 is sealing with a cap 33. Thereafter, the link supporting member 36 is welded to the toner holding frame portion 12a, covering cap 33.

The link supporting member (link mount) 36 is provided with an axis hole 36a, which is located at a specific spot (after the welding of the link supporting member 36 to the toner holding frame portion 12a, it is located directly above the toner filling opening 32). The end portion 29a of the link member 29 is inserted into this axis hole 36a, whereby the link member 29 is rotatively supported at the end portion 29a.

Referring to FIG. 18, on the other side of the process cartridge B, a gear train comprising a drum gear 21a fixed to the longitudinal end of the photosensitive drum 7, and gears 21b-21g, are mounted on the longitudinal end surface of the toner holding frame portion 12a. This gear train transmits a driving force to the development roller 10d and the toner sending members 10b1 and 10b2. The aforementioned gear cover 31 is attached to cover this gear train. The other end 29a of the link member 29 is inserted into an axis hole 31a provided in the gear cover 31 to rotatively support the link member 29 at the other end 29a.

When seen from the direction indicated by an arrow mark in FIG. 6, the link member 29 forms an L-shape, and from its bend portion, a U-shaped projection 29b projects outward in the longitudinal direction of the process cartridge B. As this projection 29b is rotatively moved, the link member 29 is rotatively moved, whereby the shutter member 28 is caused to expose or cover the opening O.

The aforementioned axis 26 is provided with a torsional coil spring 30, one end of the spring 30 being anchored to the shutter arm 27 and the other end being anchored to the cleaning frame 13; therefore, the shutter member 28 remains under the constant pressure in the closing direction generated by the elasticity of the spring 30.

(Opening and Closing Movement)

Next, referring to FIGS. 10-15, the opening and closing movements of the drum shutter 28 will be described. First, referring to FIG. 11, as the process cartridge B is inserted into the image forming apparatus A as described before, the projection 29b of the link member 29 comes in contact with the first slanted surface 16a of the guide rails 16. At this moment of the contact, the angle  $\theta$  formed by the first slanted surface 16a and the link member 29 is an acute

angle. As a result, the link member 29 and the first slanted surface 16a do not prop against each other, allowing the shutter member 28 to be smoothly opened, and also allowing the smooth insertion of the process cartridge B.

Next, referring to FIG. 12, as the process cartridge B is further inserted, the shutter member 28 is gradually opened backward because the projection 29b remains in contact with the first slanted surface 16a. As the process cartridge B is inserted deeper, the projection 29b moves onto the second slanted surface 16a of the guide rails 16, ending the process cartridge B insertion process, as shown in FIGS. 13 and 14. This second slanted surface 16b is given a steeper angle than the first slanted surface 16a, allowing the shutter member 28 to remain open in the same open state even after the projection 29b of the link member 29 moves onto the second slanted surface 16b due to the further insertion of the process cartridge B; therefore, the shutter member 28 does not open too far, nor does it fail to open sufficiently.

As described above, the shutter member 28 opens or closes as the link member 29 is rotatively moved. But, because the link member 29 is supported by the link supporting member 36 which covers the toner filling opening 32, the rotational center of the link member 29 can be positioned right above the toner filling opening. Therefore, more latitude can be afforded for the positioning of the rotational center of the link member 29, which otherwise is more restricted since the shutter member 28 must follow a predetermined locus within the limited internal space of the image forming apparatus A; even when the size of the toner filling opening 32 must be designed to be large to increase the toner filling efficiency, more latitude can be afforded in determining the location of the mounting point for the link member 29.

{Structure of Cartridge Frame}

Next, the structure of the cartridge frame will be described. The cartridge frame is formed of polystyrol resin using injection molding. Referring to FIG. 16, the cartridge frame is formed by joining a first frame, which is the development frame 12, and a second frame, which is the cleaning frame 13 (drum frame). The development frame 12 is formed by welding the development frame bottom portion 12b (development roller supporting frame) to the toner holding frame portion 12a along their longitudinal edges, and then, welding the lid 12c to the top portion of the preceding two frame portions.

The toner holding frame portion 12a is provided with the toner supply opening 12a1 and the toner filling opening 12a2. The toner supply opening 12a1 extends in the longitudinal direction, and the toner filling opening 12a2 is located in one of the longitudinal end walls. Within the toner holding frame portion 12a, a number of supporting member 12a3 are provided. They stand upright, and are aligned in the longitudinal direction of the frame portion.

When the developing means is assembled, the first toner sending member 10b1 is first assembled into the toner holding frame portion 12a, and then, the lid member 12c is welded. Next, the toner supply opening 12a1 is sealed by welding a toner seal member (film) 5 to the seal attachment seat 12a5 formed around the toner supply opening 12a1. Then, after toner is filled into the toner holding portion 10a of the toner holding frame portion 12a, the cap 32 is placed over the toner filling opening 12a2 to seal the toner holding portion 10a. Referring to FIG. 17, the toner seal member S having sealed the toner supply opening 12a1 is folded back at one of the longitudinal ends of the toner supply opening 12a1, and its free end is caused to be exposed through a slit 12a8 of the toner holding frame portion 12a, so that the users

can remove the toner sealing member **5** by pulling the exposed free end when the process cartridge B is initially put to use.

Next, the development frame bottom portion **12b** is welded to the toner holding frame portion **12a** along the longitudinal edges, and the second toner sending member **10b2** is attached to the development frame bottom portion **12b**. Then, a seal **35** formed of foamed urethane, or the like is attached below a blade mounting seat **12a4**, and the development blade **10e** is screwed to the blade mounting seat **12a4**. Next, bearings **33a** and **33b**, a seal **34** formed of foamed urethane or the like, are attached, and the axis of the development roller **10d** is placed in the bearings **33a** and **33b**. The toner holding frame portion **12a** is provided with an arc-shaped portion **12a6**, which is a positioning means for fixing the bearings **33a** and **33b**; the bearings **33a** and **33b** are fixed to the arc-shaped portion **12a6** of the toner holding frame portion **12a**. Therefore, the development roller **10d**, the axis of which is supported by the bearings **33a** and **33b**, is attached to the toner holding frame portion **12a** with a preferable degree of precision.

The link support member **36** is attached at one of the longitudinal ends of the development frame **12**, covering the aforementioned cap **32**. On the other side of the development frame **12**, the gear train for transmitting the driving force to the photosensitive drum **7**, the development roller **10d**, and the like are mounted, and the gear cover **37** is attached to cover the gear train. The gear cover **37** is provided with a positioning axis **37a**; the gear cover **37** is fixed to the toner holding frame portion **12a** using engagement claws, screws, or the like after its position is fixed by inserting this positioning axis **37a** into the hole **33i** of the bearing **33a**, and the hole **12a7** of the toner holding frame portion **12a**.

One of the longitudinal ends of the toner holding frame portion **12a** is provided with an arm portion **38** as a joint portion, which is integrally formed with the toner holding frame portion **12a**. Also, the gear cover **37** attached to the other longitudinal end of the toner holding frame portion **12a** is provided with the arm portion **38** as the joint portion (FIG. 16).

The development frame **12**, into which various components constituting the aforementioned developing means have been assembled, and the cleaning frame **13**, into which the photosensitive drum **7**, the charge roller **8**, and various components constituting the cleaning means, have been assembled, are joined together at the arm portions **38**, completing the process cartridge B.

{Structure for Joining Development Frame and Cleaning Frame}

Next, referring to FIGS. 1–3, the structure for joining the development frame **12** and the cleaning frame **13** will be described. FIG. 1 is a perspective view of both frames **12** and **13**, depicting how they are joined. FIG. 2 depicts the internal structure of the joint, and FIG. 3 is a partially cutaway schematic plan view of the joint. The structures of the left and right joints at which the frames **12** and **13** are rotatively connected to each other with the arm portions **38** are the same; therefore, the structure on only one side will be described.

Referring to FIGS. 2 and 3, in order to give some elastic flexibility to the angle formed between the development frame **12** and the cleaning frame **13**, the process cartridge B is provided with a compression spring **40**, which is attached to a compression spring anchoring member **39** which integrally comprises a spring attachment portion **39a** and a cylindrical portion **39d**. The cylindrical portion **39d** has a

larger diameter than the diameter of the compression spring **40** attached to the spring attachment portion **39a**. The head portion of the cylindrical portion is provided with a rib **39b**, and the peripheral surface of the cylindrical portion **39d** is provided with two flanges **39c**.

The upward facing surface of the arm portion **38** of the development frame **12** is provided with a recess **38a** (receiving portion). The location of the recess **38a** is such that after the development frame **12** and the cleaning frame **13** are rotatively joined as will be described later, the recess **38a** is located right below the attachment hole **13a** of the cleaning frame **13**. Further, a through hole **38b** through which a pin **41** is put is provided at the tip portion of the arm portion **38**. The pin **41** will be described later.

On the other hand, the cleaning frame **13** is provided with an attachment hole **13a** into which the aforementioned spring anchoring member **39** is pressed. Referring to FIGS. 2 and 3, the attachment hole **13a** is constituted of a cylindrical hole portion **13a1** slightly larger than the flange **39c** or the cylindrical portion **39d** of the spring anchoring member **39**, and a cutaway portion **13a2**. The external wall **13b** of the cleaning frame **13** is provided with a hole **13c** through which the pin **41** is put, and the internal wall **13d** of the cleaning frame **13** is provided with a hole **13e** into which the pin **41** is pressed. The axial lines of the holes **13c** and **13e** coincide with each other, and are parallel to the axial lines of the holes **13c** and **13e** provided on the other side, relative to the longitudinal direction, of the cleaning frame **13**. Further, a rib **13f** is provided on the interior surface of the cleaning frame **13**, adjacent to the attachment hole **13a**.

Referring to FIGS. 2 and 3, when the development frame **12** and cleaning frame **13** are joined using the above structure, first, the arm portion **38** of the development frame **12** is inserted into the joining portion **13h** of the cleaning frame **13**. Next, the pin **41** is put through the hole **13c** of the cleaning frame **13**, and the through hole **38b** of the arm portion **38**, in this order, and then is pressed into the hole **13e**. As a result, the development frame **12** and cleaning frame **13** are joined in such a manner that they are rotatable about the pin **41**. At this stage of the process cartridge B assembly, no pressure is present to press the photosensitive drum **7** and development roller **10d** toward each other; therefore, assembly workers can easily examine the degree of the rotatability of both components.

Next, referring to FIG. 2, the spring anchoring member **39** to which the spring **40** has been attached is put through the attachment hole **13a**; the cutaway portion **13a2** of the attachment hole **13a**, and the flange **39c** of the spring anchoring member **39**, are aligned, with the tip of the spring **40** placed in contact with the bottom surface of the recess **38a**, and the spring anchoring member **39** is pressed straight down in the compressing direction of the spring **40** until the upper surface of the flange **39c** of the spring anchoring member **39** comes to be located below the rib **13f**, and the cylindrical portion **39d** comes to be guided by the cylindrical hole portion **13a1** of the attachment hole **13a**. In this state, the spring anchoring member **39** is rotated 90°, and is released. Consequently, the spring anchoring member **39** is pushed up, being guided by the cylindrical hole portion **13a1**, by the resiliency of the spring **40**, and is stopped at a point at which the flange **39c** strikes the bottom edge of the attachment hole **13a**.

As a result, the development roller **10d** mounted in the development frame **12** is pressed toward the photosensitive drum **7** mounted in the cleaning frame **13**, coming in contact with the ring members (unillustrated) as spacers mounted at the longitudinal ends of the development roller **10d**, and

thereby coming to be accurately positioned relative to the photosensitive drum 7. At the same time, the drum gear fixed to the longitudinal end of the photosensitive drum 7 becomes engaged with a roller gear fixed to the longitudinal end of the development roller 10d, enabling the driving force to be transmitted.

{Process Cartridge}

The aforementioned process cartridge B has the following structure. The process cartridge B removably installable in the main assembly of an image forming apparatus A comprises a drum frame 13 (cleaning frame), a development frame 12, a toner frame 12a. The drum frame 13 houses a electrophotographic photosensitive drum 7, a charging roller 8 for charging the electrophotographic photosensitive drum 7, a cleaning blade 11a for removing the toner remaining on the electrophotographic photosensitive drum 7, wherein the charging roller 8 is in contact with the electrophotographic photosensitive drum 7, and the cleaning block 113 is in contact with the electrophotographic photosensitive drum 7. The development frame 12 houses a development roller 10d for developing the latent image formed on the electrophotographic photosensitive drum 7, and the toner frame 12a comprises a toner holding portion 10a for holding the toner used for the aforementioned development. The toner frame 12a is joined with the development frame 12 along their longitudinal edges, and also supports an arm portion 38. The arm portion 38 is disposed at each longitudinal end of the toner frame 12a, and projects toward the drum frame 13 in the direction perpendicular to the longitudinal direction thereof, enabling the development frame 12 and the drum frame 13 to be joined so as to be oscillatable relative to each other. Also, the toner frame 12a comprises handhold portions 12a10 and 12c2 for holding the process cartridge B. They are located on the opposite side of the toner frame 12a relative to the drum frame 13. The handhold portions 12a10 and 12c2 are partially constituted of the lid 12c of the toner holding portion 10a of the toner frame 12a; therefore, they become the part of the toner frame 12a as the lid 12c is attached to the toner frame 12a. Further, the toner frame 12a is provided with a toner filling opening 12a2 through which the toner is filled, and a toner supply opening 12a1 for supplying to the development roller 10d the toner held in the toner holding portion 10a, and a toner seal mount 12a5 on which a toner seal 5 is attached. The toner filling opening 12a2 is located at one of the longitudinal ends of the toner frame 12a, and the toner supply opening 12a1 and the toner seal mount 12a5 extend in the longitudinal direction of the toner frame 12a. The toner seal 5 unsealably seals the toner supply opening 12a1. The toner frame 12a and the development frame 12 are joined by a pin 41 placed through a hole 38b of the arm portion 38, and holes 13c and 13e of the drum frame 13, wherein the development frame 12 joined with the toner frame 12a, and the drum frame 13, are rotatable about the pin 41.

In other words, in this embodiment, after the development frame 12 and cleaning frame 13 are rotatively joined, and the degree of the rotatability of the photosensitive drum 7 and development roller 10d is confirmed, the photosensitive drum 7 and the development roller 10d are pressed toward each other by the spring 40 anchored by the spring anchoring member 39; therefore, the possibility of the fluctuation of the pressure applied to the photosensitive drum 7 by the development roller 10d is eliminated. Further, the spring anchoring member 39 is attached so as to keep appropriately compressed the compression spring 40 attached to the spring anchoring member 39; therefore, the compression spring 40 is not liable to buckle. Further, the spring anchoring member

39 can be replaced without removing the spring cover. In other words, the spring anchoring member 39 can be replaced, the development and cleaning frames 12 and 13 remaining connected, enabling the spring anchoring member 39 to be exchanged with a spring anchoring member with a spring having a proper pressure, substantially regardless of the cartridge assembling order.

Consequently, the assembly efficiency for the process cartridge B is improved. In addition, when an image is formed using the process cartridge B described above, the pressure applied by the development roller 10d does not fluctuate as described above; therefore, a high quality image can be produced.

{Other Embodiment}

Next, various components of the process cartridge B and the image forming apparatus in accordance with the present invention will be described.

In the preceding embodiment, one of the arm portions 38 for connecting the development frame 12 and the cleaning frame 13 was disposed on the gear cover 37, and this gear cover 37 was fixed to one of the longitudinal ends of the development frame 12, but both arm portions 38 may be directly formed on the toner holding frame portion 12a. This arrangement can also effectively disperse the shock generated during the installation of the process cartridge B.

Further, in the preceding embodiment, the link supporting member 36 was welded to the cartridge frame, but the link supporting member 36 may be screwed to the cartridge frame, or may be glued to the cartridge frame with adhesive.

{Internal Structure of Toner Holding Frame}

Next, referring to FIGS. 21 and 22, the internal structure of the toner holding frame portion 12a will be described. As will be become clear from the following description, partition members 12a3 are provided within the toner holding frame portion 12a, wherein a gap is provided between the partition member 12a3 and the frame lid 12c. This arrangement is made so that even when the frame lid 12c is flexed as the users too firmly grasp the toner holding frame portion 12a (pcB), the flexed portion of the frame lid 12c can be supported by the top surface of the partition member 12a3.

A gap is also provided between the partition member 12a3 and the toner holding portion 10a. This arrangement is made so that the toner poured into the toner holding portion 10a through the toner filling opening 12a2 can be delivered with preferable efficiency into each of the spaces partitioned by the partition members 12a3 in spite of the presence of the partition members 12a3.

Referring to FIG. 16, the slant surface on the top of the frame lid 12c is provided with several parallel ribs 12c1, constituting a handhold portion 12c2. Further, referring to FIG. 21, the bottom portion of the toner holding frame portion 12a is provided with an R portion which bulges downward. The external surface of the R portion is also provided with several parallel ribs 12a5, constituting a handhold portion 12a10. The users can easily hold the process cartridge B by grasping the handhold portions 12a10 and 12c2, so that the process cartridge B can be smoothly installed into, or removed from, the image forming apparatus A (FIG. 9).

At this time, the relationship between the partition member 12a3 provided within the toner holding portion 10a, and the frame wall surface will be described. Referring to FIG. 5, a gap S1 is provided between the rear edge of the partition member 12a3 and the internal surface of the rear wall of the toner holding frame portion 12a ("rear" relative to the direction in which the toner within the toner holding portion 10a is supplied to the development roller 10d). Also, a

minute gap S2 is provided between the top end of the partition member 12a3 and the internal surface of the frame lid 12c.

The purpose of the partition member 12a3 is to minimize the deformation of the toner holding frame portion 12a and the frame lid 12c when excessive pressure is applied by the users who handle the process cartridge B by gripping the handhold portions 12c2 and 12a10. In other words, even if the users too firmly grasp the process cartridge B, and consequently, the toner holding frame portion 12a and/or the frame lid 12c become deformed, the top end of the partition member 12a3 and the internal surface of the frame lid 12c come in contact with each other, regulating the amount of the deformation.

With the presence of the partition members 12a3 within the toner holding portion 10a, unless the internal air of the toner holding portion 10a is properly released while the toner is filled, the toner cannot be filled with sufficiently high density.

Thus, in this embodiment, the gap S1 is provided between the partition member 12a3 and the internal surface of the rear wall of the toner holding frame portion 12a as described above. Consequently, when the toner is filled through the toner filling opening 12a2, the internal air of the toner holding portion 10a is allowed to flow through the gap S1 and out of the toner holding portion 10a as illustrated in FIG. 22 (a black arrow mark indicates the toner flow, and a white arrow mark indicates the air flow). As a result, the toner can be smoothly filled into the toner holding portion 10a, with a sufficient density.

It should be noted here that in order to provide a proper balance between the air releasing efficiency and the effectiveness in regulating the frame deformation, the gap S1 is preferred to be 5 mm–20 mm.

Also as described before, in this embodiment, the gap S2 is provided between the top end of the partition member 12a3 and the frame lid 12c; therefore, the generation of burr is prevented. More specifically, when the frame lid 12c is attached to the toner holding frame portion 12a without providing the gap S2, the top end of the partition member 12a3 and the internal surface of the frame lid 12c sometimes make contact due to manufacturing error. If the toner holding frame portion 12a and the frame lid 12c are welded together by ultrasonic welding when the partition member 12a3 and the frame lid 12c are in contact with each other, the burr may be generated between the top end of the partition member 12a3 and the internal wall of the frame lid 12c, and when generated, the burr is liable to drop into the toner holding portion 10a, and mix with the toner, forming a toner nucleus, during the transportation of the process cartridge B, or in the like situation. But, according to the present invention, the generation of the burr can be prevented.

On the other hand, when the gap S2 is too large, the internal pressure of the toner holding portion 10a is liable to increase. This is because when the handhold portion formed on the frame lid 12c welded to the toner holding frame portion 12a using ultrasonic welding is firmly gripped, the presence of an excessive gap is liable to allow both frame portions to deform. Thus, the size of the gap S2 is preferred to be set within a range of 0.0–0.5 mm so that when the handhold portions are firmly gripped, the deformation of the toner holding frame portion 12a and the frame lid 12c can be minimized. In this embodiment, the gap S2 is set at 0.2 mm.

As is evident from the above descriptions, not only does the provision of the gaps S1 and S2 between the partition member 12a3 and the internal surface of the frame allow the

toner to be filled with high density, but also, prevents the burr from mixing into the toner, and minimizes the frame deformation.

A process cartridge B is detachably mountable to a main assembly of an image forming apparatus, and comprises: a. an electrophotographic photosensitive drum 7; b. a developing roller 10d for developing a latent image formed on the electrophotographic photosensitive drum 7, the developing roller supplying toner to the electrophotographic photosensitive drum 7 by rotation thereof; c. a charging roller 8 for charging the electrophotographic photosensitive drum 7, the charging roller 8 being contacted to the electrophotographic photosensitive drum 7; d. a cleaning blade 11a for removing residual toner from the electrophotographic photosensitive drum 7; e. a toner accommodating container 12a, including: a toner accommodating portion 10a for accommodating toner usable for developing a latent image formed on the electrophotographic photosensitive drum 7, wherein the toner accommodating portion 10a is provided with a toner supply opening 12a1 for supplying the toner to the electrophotographic photosensitive drum 7 from the toner accommodating portion 10a; a partition wall 12a3 extending in the toner accommodating portion in a direction along a short side of the toner accommodating portion to define a plurality of space therein, wherein the toner accommodating portion has a bottom surface slanted down toward the toner supply opening, and the partition is provided on the slanted surface; a toner filling opening 12a2, at a longitudinal end of the toner accommodating portion, for permitting toner to be filled into the toner accommodating portion; and a through-passage S1 extending from one longitudinal end to the other longitudinal end along a length of the toner accommodating portion so as to permit the toner to be supplied into the spaces, the through-passage being formed between a wall surface of the toner accommodating portion and the partition wall, wherein the through-passage S1 is provided between a rear wall surface opposed to the toner supply opening and the partition wall.

Also, a process cartridge B is detachably mountable to a main assembly of an image forming apparatus, and comprises: a. an electrophotographic photosensitive drum 7; b. a developing roller 10d for developing a latent image formed on the electrophotographic photosensitive drum 7, the developing roller supplying toner to the electrophotographic photosensitive drum 7 by rotation thereof; c. a charging roller 8 for charging the electrophotographic photosensitive drum 7, the charging roller 8 being contacted to the electrophotographic photosensitive drum 7; d. a cleaning blade 11a for removing residual toner from the electrophotographic photosensitive drum 7; e. a toner accommodating container 12a, including: a toner accommodating portion 10a for accommodating toner usable for developing a latent image formed on the electrophotographic photosensitive drum 7, wherein the toner accommodating portion 10a is provided with a toner supply opening 12a1 for supplying the toner to the electrophotographic photosensitive drum 7 from the toner accommodating portion 10a; a cover member 12c for covering an opening other than the toner supply opening 12a1, wherein the cover member 12c covers the opening provided at an upper portion of the toner accommodating portion 10a, which portion takes an upper position when the process cartridge is mounted on the main assembly of the image forming apparatus; a handle portion 12c2 on the cover member 12c for facilitating handling of the toner accommodating container, wherein the handle 12c2 has a plurality of ribs 12c1. The outer surface of the toner accommodating container has a plurality of ribs 12a9. When the container

12a is handled, force is transferred to the rib of the cover and the rib of the container 10a.

In order to fill the toner into portion 10a, there are provided a toner filling opening 12a2 at one longitudinal end of the accommodating portion, the partition wall 12a3 for partitioning the inside space of the portion 10a. A gap S2 is formed between the cover member 12c and the partition wall 12a3. When the cover bends upon gripping the toner accommodating container, the partition wall 12a3 and the cover 12c are contactable. The gap S2 between the partition wall 12a3 and the cover 12c is not more than approx. 0.5 mm. The toner accommodating portion 10a and the cover 12c are welded.

Further, the aforementioned process cartridge B was of a type for forming a monochromatic image. However, not only is the present invention preferably applicable to the process cartridge which forms a monochromatic image, but also to a cartridge which comprises two or more developing means, and forms a multi-color image (for example, a two-color image, a three-color image, a full-color image, and the like).

As for the developing method, various known development methods such as the magnetic brush development method employing two component toner, the cascade development method, the touchdown development method, or cloud development method may be employed.

The electrophotographic photosensitive member is not limited to the photosensitive drum. For example, the following may be included.

First, as the photosensitive material, photoconductive material such as amorphous silicon, amorphous selenium, zinc oxide, titanium oxide, or organic photoconductor (OPC) may be included. As for the shape of the base member on which the photosensitive material is placed, a rotary member such as a drum or a member in the form of a sheet such as an endless belt, are included. Generally, a member in the form of a drum or a belt is employed. For example, a photosensitive drum comprises a cylinder of aluminum alloy or the like, and photoconductive material deposited or coated thereon.

The structure of the charging means described in the preceding embodiment was of the so-called contact type, but it is obvious that other conventional structures may be employed, for example, a structure in which a tungsten wire is surrounded on three sides by a shield of metallic material such as aluminum, and positive or negative ions generated by applying a high voltage to the tungsten wire are transferred onto the surface of the photosensitive drum to uniformly charge the drum surface.

As for the charging means, a charging means of the blade type (charging blade), the pad type, the block type, the rod type, the wire type, or the like may be employed in addition to the roller type charging means described in the preceding embodiment.

Regarding the method for cleaning the toner remaining on the photosensitive drum, the cleaning means may comprise a blade, a fur brush, a magnetic brush, or the like.

The process cartridge in accordance with the present invention comprises at least an electrophotographic photosensitive member and a developing means. Typically, a combination of a developing means, an electrophotographic photosensitive member, a charging means, and a cleaning means, a combination of a developing means, an electrophotographic photosensitive member, and a charging means or a cleaning means, a combination of a developing means and an electrophotographic photosensitive member, or the like combination is integrated in the form of a cartridge so that it can be removably installed into the main assembly of an apparatus.

Further, in the preceding embodiment, the image forming apparatus was represented by a laser beam printer, but the present invention is not limited by the preceding embodiment. Obviously, the present invention is also applicable to other image forming apparatuses such as an electrophotographic copying machine, a facsimile apparatus, or a word processor.

As described in the foregoing according to the present invention, the toner frame is provided with a grip and a coupling portion relative to the drum frame, wherein it is rotatable relative to the drum frame. Therefore, a coupling portion (welded portion) in the process cartridge constituted by a plurality of frames does not receive concentrated impact when it is mounted to the image forming apparatus. So, the strength of the coupling portion is enough without consideration to such an impact.

Thus, the coupling step during the manufacturing of the process cartridge is simplified, and therefore, the productivity is improved.

Accordingly, the manufacturing cost of the process cartridge is reduced, and therefore, the running cost of the apparatus is reduced.

While the invention has been described with reference to the structures disclosed herein, it is not confined to the details set forth, and this application is intended to cover such modifications or changes as may come within the purposes of the improvements or the scope of the following claims.

What is claimed is:

1. A process cartridge detachably mountable to a main assembly of an image forming apparatus, comprising:

a drum frame for support an electrophotographic photosensitive drum;

a developing frame to which a developing roller for developing a latent image formed on said electrophotographic photosensitive drum is mounted; a

a toner frame having a toner accommodating portion for accommodating a toner to be used by said developing roller, wherein said toner frame is provided with a coupling member for swingably coupling wit said drum frame, and is provided with a grip for gripping said process cartridge.

2. A cartridge according to claim 1, wherein said coupling member is provided at each of one longitudinal end and the other longitudinal end of said toner frame, and is projected toward a portion having said drum frame in a direction crossing with the longitudinal direction of said toner frame.

3. A cartridge according to claim 2, wherein said coupling member has a coupling member hole through which a pin is penetrated for swingably coupling between said toner frame and said drum frame, and wherein said toner frame and said drum frame are coupled by inserting said pin through said coupling member hole and a drum frame hole provided in said drum frame.

4. A cartridge according to claim 2, wherein said coupling member provided at one longitudinal end of said toner frame is integrally formed with said toner frame.

5. A cartridge according to claim 2, wherein said coupling member provided at the other longitudinal end of said toner frame is formed on a gear cover mounted to the other longitudinal end of said toner frame, wherein said gear cover functions to cover a gear train mounted on said toner frame.

6. A cartridge according to claim 2, wherein said coupling member is provided at each of the one longitudinal end and the other longitudinal end of said toner frame, and is projected toward a portion having said drum frame in a direction crossing with the longitudinal direction of said

toner frame, wherein said coupling member provided at the one longitudinal end of said toner frame is integrally formed with said toner frame, and wherein said coupling member provided at the other longitudinal end of said toner frame is formed on a gear cover mounted to the other longitudinal end of said toner frame, wherein said gear cover functions to cover a gear train mounted on said toner frame.

7. A cartridge according to claim 1, wherein a part of said grip is provided on a cover of said toner accommodating portion of said toner frame, and is mounted to said toner frame by mounting said cover to said toner frame, and another part of said grip is provided on an outer surface of said accommodating portion, wherein the outer surface faces said grip provided on said cover.

8. A cartridge according to claim 7, wherein said grip parts are provided with a plurality of ribs.

9. A cartridge according to claim 1, wherein said toner frame has a toner filling opening for filling said process cartridge with the toner, at one longitudinal end of said toner frame, and has a toner supply port for supplying the toner to said developing roller from said toner accommodating portion in the longitudinal direction of said toner frame, and a mounting portion for mounting a toner seal for openably sealing the toner supply port.

10. A cartridge according to claim 1, wherein said toner frame has a cap cover for covering a cap mounted to a toner filling opening for filling said process cartridge with the toner, at one longitudinal end of said toner frame, and has a gear cover for covering a gear train mounted to said toner frame at an other longitudinal end of said toner frame.

11. A cartridge according to claim 10, wherein said developing frame and said toner frame are welded together.

12. A process cartridge detachably mountable to a main assembly of an image forming apparatus, comprising:

a drum frame for supporting an electrophotographic photosensitive drum, a charging member for charging said electrophotographic photosensitive drum, and a cleaning member for removing residual toner from said electrophotographic photosensitive drum;

a developing frame to which a developing roller for developing a latent image formed on said electrophotographic photosensitive drum is mounted;

a toner frame having a toner accommodating portion for accommodating a toner to be used by said developing roller, wherein said toner frame is provided with a coupling member for swingably coupling with said drum frame, and is provided with a grip for gripping said process cartridge, wherein said toner frame is coupled with said developing frame in a longitudinal direction, wherein said coupling member has a coupling member hole through which a pin is penetrated for swingable coupling between said toner frame and said drum frame, and wherein said toner frame and said drum frame are coupled by inserting said pin through said coupling member hole and a drum frame hole provided in said drum frame, wherein said coupling member is provided at each of one longitudinal end of said toner frame and at an other longitudinal end of said toner frame, and is projected toward a portion having said drum frame in a direction crossing with the longitudinal direction of said toner frame, wherein said coupling member provided at the one longitudinal end of said toner frame is integrally formed with said toner frame, wherein said coupling member provided at the other longitudinal end of said toner frame is formed on a gear cover mounted to the other longitudinal end of said toner frame, wherein said gear cover functions to cover a gear train mounted on said toner frame.

13. A cartridge according to claim 12, wherein a part of said grip is provided on a cover of said toner accommodating portion of said toner frame, and is mounted to said toner frame by mounting said cover to said toner frame, and another part of said grip is provided on an outer surface of said accommodating portion, wherein the outer surface faces said grip provided on said cover.

14. A cartridge according to claim 13, wherein said grip parts are provided with a plurality of ribs.

15. A cartridge according to claim 12, wherein said toner frame has a toner filling opening for filling said process cartridge with the toner, at the one longitudinal end of said toner frame, and has a toner supply port for supplying the toner to said developing roller from said toner accommodating portion in the longitudinal direction of said toner frame, and a mounting portion for mounting a toner seal for openably sealing the toner supply port.

16. A cartridge according to claim 12, wherein said toner frame has a cap cover for covering a cap mounted to a toner filling opening for filling said process cartridge with the toner, at the one longitudinal end of said toner frame, and has a gear cover for covering a gear train mounted to said toner frame.

17. A cartridge according to claim 16, wherein said developing frame and said toner frame are welded together.

18. A process cartridge detachably mountable to a main assembly of an image forming apparatus, comprising:

a drum frame for supporting an electrophotographic photosensitive drum, a charging roller for charging said electrophotographic photosensitive drum, wherein said charging roller is contacted to said electrophotographic photosensitive drum, and a cleaning blade for removing a residual toner from said electrophotographic photosensitive drum, wherein said cleaning blade is contacted to said electrophotographic photosensitive drum;

a developing frame to which a developing roller for developing a latent image formed on said electrophotographic photosensitive drum is mounted;

a toner frame having a toner accommodating portion for accommodating a toner to be used by said developing roller, wherein said toner frame is provided with a coupling member for swingably coupling with said drum frame, and is provided with a grip for gripping said process cartridge, wherein said toner frame is coupled with said developing frame in a longitudinal direction, wherein said coupling member has a coupling member hole through which a pin is penetrated for swingable coupling between said toner frame and said drum frame, and wherein said toner frame and said drum frame are coupled by inserting said pin through said coupling member hole and a drum frame hole provided in said drum frame, wherein said coupling member is provided at each of one longitudinal end and at an other longitudinal end of said toner frame, and is projected toward a portion having said drum frame in a direction crossing with the longitudinal direction of said toner frame, wherein said coupling member provided at the one longitudinal end of said toner frame is integrally formed with said toner frame, wherein said coupling member provided at the other longitudinal end of said toner frame is formed on a gear cover mounted to the other longitudinal end of said toner frame, wherein said gear cover functions to cover a gear train mounted on said toner frame, wherein a part of said grip is provided on a cover of said toner accommodating portion of said toner frame, and is mounted to said toner frame by mounting said cover to said toner frame and another part of said

## 19

grip is provided on an outer surface of said accommodating portion, wherein the outer surface faces said grip provided on said cover, wherein said toner frame has a toner filling opening for filling said process cartridge with the toner, at the one longitudinal end of said toner frame, and has a toner supply port for supplying the toner to said developing roller from said toner accommodating portion in the longitudinal direction of said toner frame.

19. A cartridge according to claim 18, further comprising a mounting portion for mounting a toner seal for openably sealing the toner supply port.

20. A cartridge according to claim 18, wherein said developing frame and said toner frame are welded together.

21. An electrophotographic image forming apparatus for forming an image on a recording material, wherein a process cartridge is detachably mountable to said image forming apparatus, comprising:

a. mounting means for detachably mounting a process cartridge;

said process cartridge including:

a drum frame for supporting an electrophotographic photosensitive drum;

a developing frame mounted to a developing roller for developing a latent image formed on said electrophotographic photosensitive drum;

a toner frame having a toner accommodating portion for accommodating a toner to be used by said developing roller, wherein said toner frame is provided with a coupling member for swingably coupling with said drum frame, and is provided with a grip for gripping said process cartridge;

said apparatus further comprising:

b. feeding means for feeding the recording material.

22. An electrophotographic image forming apparatus for forming an image on a recording material, wherein a process cartridge is detachably mountable to said image forming apparatus, comprising:

a. mounting means for detachably mounting a process cartridge;

said process cartridge including:

a drum frame for supporting an electrophotographic photosensitive drum, a charging member for charging said electrophotographic photosensitive drum, a cleaning member for removing residual toner from said electrophotographic photosensitive drum;

a developing frame to which a developing roller for developing a latent image formed on said electrophotographic photosensitive drum is mounted;

a toner frame having a toner accommodating portion for accommodating a toner to be used by said developing roller, wherein said toner frame is provided with a coupling member for swingably coupling with said drum frame, and is provided with a grip for gripping said process edge, wherein said toner frame is coupled with said developing frame in a longitudinal direction, wherein said coupling member has a coupling member hole through which a pin is penetrated for swingable coupling between said toner frame and said drum frame, and wherein said toner frame and said drum frame are coupled by inserting said pin through said coupling member hole and a drum frame hole provided in said drum frame, wherein said coupling member is provided at each of one longitudinal end of said toner frame and at an

## 20

other longitudinal end of said toner frame, and is projected toward a portion having said drum frame in a direction crossing with the longitudinal direction of said toner frame, wherein said coupling member provided at the one longitudinal end of said toner frame is integrally formed with said toner frame, wherein said coupling member provided at the other longitudinal end of said toner frame is formed on a gear cover mounted to the other longitudinal end of said toner frame, wherein said gear cover functions to cover a gear train mounted on said toner frame;

said is further comprising:

b. feeding means for feeding the recording material.

23. An electrophotographic image forming apparatus for forming an image on a recording material, wherein a process cartridge is detachably mountable to said image forming apparatus, comprising:

a. mounting means for detachably mounting a process cartridge;

said process cartridge including:

a drum frame for supporting an electrophotographic photosensitive drum, a charging roller for charging said electrophotographic photosensitive drum, wherein said charging roller is contacted to said electrophotographic photosensitive drum, and a cleaning blade for removing a residual toner from said electrophotographic photosensitive drum, wherein said cleaning blade is contacted to said electrophotographic photosensitive drum;

a developing frame to which a developing roller for developing a latent image formed on said electrophotographic photosensitive drum is mounted;

a toner frame having a toner accommodating portion for accommodating a toner to be used by said developing roller, wherein said toner frame is provided with a coupling member for swingably coupling with said drum frame, and is provided with a grip for gripping said process cartridge, wherein said toner frame is coupled with said developing frame in a longitudinal direction, wherein said coupling member has a coupling member hole through which a pin is penetrated for swingable coupling between said toner frame and said drum frame, and wherein said toner frame and said drum frame are coupled by inserting said pin through said coupling member hole and a drum frame hole provided in said drum frame, wherein said coupling member is provided at each of one longitudinal end and an other longitudinal end of said toner frame, and is projected toward a portion having said drum frame in a direction crossing with the longitudinal direction of said toner frame, wherein said coupling member provided at one longitudinal end is integrally formed with said toner frame, wherein said coupling member provided at the other longitudinal end is formed on a gear cover mounted to the other longitudinal end of said toner frame, wherein said gear cover functions to cover a gear train mounted on said toner frame wherein a part of said grip is provided on a cover of said toner accommodating portion of said toner frame and is mounted to said toner frame by mounting said cover to said toner frame, and another part of said grip is provided on an outer surface of said accommodating portion, wherein the outer surface faces said grip provided



on said cover, wherein said toner frame has a toner filling opening for filling said process cartridge with the toner, at the one longitudinal end of said toner frame, and has a toner supply port for supplying the toner to said developing roller from said toner accommodating portion in the longitudinal direction of said toner frame;

said apparatus further comprising:

b. feeding means for feeding the recording material.

**24.** A process cartridge detachably mountable to a main assembly of an image forming apparatus, comprising:

a first frame for supporting an electrophotographic photosensitive member;

a second frame mounted to a developing member for developing a latent image formed on said electrophotographic photosensitive member;

a third frame having a toner accommodating portion for accommodating toner to be used by said developing member, wherein said third frame is provided with a coupling portion for swingably coupling with said first frame, and is provided with a grip for gripping said process cartridge, wherein said second frame and said third frame are coupled with each other.

**25.** A cartridge according to claim **24**, wherein said coupling portion is provided at each of one longitudinal end and an other longitudinal end of said third frame, and is projected toward a portion having said first frame in a direction crossing with the longitudinal direction of said third frame.

**26.** A cartridge according to claim **25**, wherein said coupling portion has a hole through which a pin is penetrated for swingably coupling between said first frame and said third frame, and wherein said first frame and said third frame are coupled by inserting said pin through said hole and a first frame hole provided in said first frame.

**27.** A cartridge according to claim **25** or **26**, wherein said coupling portion is integrally formed with said third frame and is provided at the one longitudinal end of said toner frame.

**28.** A cartridge according to claim **25**, wherein said coupling portion is formed on a gear cover which is a part of said third frame and which is mounted to the other longitudinal end of said third frame, wherein said gear cover functions to cover a gear train mounted on said third frame.

**29.** A cartridge according to claim **24** or **26**, wherein said coupling portion is provided at each of the one longitudinal end and at the other longitudinal end of said third frame, and is projected toward a portion having said first frame in a direction crossing with the longitudinal direction of said third frame, wherein said coupling portion provided at the one longitudinal end is integrally formed with said third frame, and wherein said coupling portion provided at the other longitudinal end is formed on a gear cover mounted to the other longitudinal end of said third frame, wherein said gear cover functions to cover a gear train mounted on said third frame.

**30.** A cartridge according to claim **24**, wherein a part of said grip is provided on a cover of said toner accommodating portion of said third frame, and is mounted to said third frame by mounting said cover to said third frame, and another part of said grip is provided on an outer surface of said accommodating portion, wherein the outer surface is faced to said grip is provided on said cover.

**31.** A cartridge according to claim **30**, which said grip parts are provided with a plurality of ribs.

**32.** A cartridge according to claim **24**, wherein said third frame has a toner filling opening for filling toner, at one

longitudinal end of said third frame, and has a toner supply port for supplying the toner to said developing member from said toner accommodating portion in the longitudinal direction of said third frame, and a mounting portion for mounting a toner seal for openably sealing the toner supply port.

**33.** A cartridge according to claim **24**, wherein said third frame has a cap cover for covering a cap mounted to a toner filling opening for filling the toner, at one longitudinal end of said third frame, and has a gear cover for covering a gear train mounted to said third frame, at an other longitudinal end of said third frame.

**34.** A cartridge according to claim **33**, wherein said second frame and said third frame are welded together.

**35.** A cartridge according to claim **24**, wherein said developing member is in the form of a developing roller, and said process cartridge further comprises a cleaning member and a charging member, which are supported on said first frame.

**36.** A process cartridge detachably mountable to a main assembly of an image forming apparatus, comprising:

a drum frame for supporting an electrophotographic photosensitive drum, a charging member for charging said electrophotographic photosensitive drum, and a cleaning member for removing residual toner from said electrophotographic photosensitive drum;

a developing frame for mounting a developing roller for developing a latent image formed on said electrophotographic photosensitive drum;

a toner frame having a toner accommodating portion for accommodating toner to be used by said developing roller, wherein said toner frame is provided with a coupling portion for swingably coupling with said drum frame, and is provided with a grip for gripping said process cartridge, wherein said toner frame is coupled with said developing frame in a longitudinal direction, wherein said coupling portion has a coupling hole through which a pin is penetrated for swingable coupling between said toner frame and said drum frame, and wherein said toner frame and said drum frame are coupled by inserting said pin through said coupling hole and a drum frame hole provided in said drum frame, wherein said coupling portion is provided at each of one longitudinal end and at an other longitudinal end of said toner frame, and is projected toward a portion having said drum frame in a direction crossing with the longitudinal direction of said toner frame, wherein said coupling portion provided at said one end is integrally formed with said toner frame, wherein said coupling portion provided at the other end is formed on a gear cover mounted to the other longitudinal end of said toner frame, wherein said gear cover functions to cover a gear train mounted on said toner frame.

**37.** A cartridge according to claim **36**, wherein a part of said grip is provided on a cover of said toner accommodating portion of said toner frame, and is mounted to said toner frame by mounting said cover to said toner frame, and another part of said grip is provided on an outer surface of said accommodating portion, wherein the outer surface, faces said grip provided on said cover.

**38.** A cartridge according to claim **37**, wherein a grip portion having said cover is provided with a rib.

**39.** A cartridge according to claim **36**, wherein said toner frame has a toner filling opening for filling the toner, at the one longitudinal end of said toner frame, and has a toner supply port for supplying the toner to said developing roller from said toner accommodating portion in the longitudinal direction of said toner frame, and a mounting portion for mounting a toner seal for openably sealing the toner supply port.

## 23

40. A cartridge according to claim 36, wherein said toner frame has a cap cover for covering a cap mounted to a toner filling opening for filling the toner, at the one longitudinal end of said toner frame, and has a gear cover for covering a gear train mounted to said toner frame, at the other longitudinal end of said toner frame. 5

41. A cartridge according to claim 36, wherein said developing frame and said toner frame are welded together.

42. An image forming apparatus for forming an image on a recording material, wherein a process cartridge is detachably mountable to a main assembly of an image forming apparatus, said apparatus comprising: 10

a. mounting means for detachably mounting said process cartridge;

said cartridge including: 15

a first frame for supporting an electrophotographic photosensitive member;

a second frame mounted to a developing member for developing a latent image formed on said electrophotographic photosensitive member; 20

a third frame having a toner accommodating portion for accommodating toner to be used by said developing member, wherein said third frame is provided with a coupling portion for swingably coupling with said first frame, and is provided with a grip for gripping said process cartridge, wherein said second frame and said third frame are coupled with each other; 25

said apparatus further comprising:

b. feeding means for feeding the recording material. 30

43. An image forming apparatus for forming an image on a recording material, wherein a process cartridge is detachably mountable to a main assembly of image forming apparatus, said apparatus comprising: 35

a. mounting means for detachably mounting said process cartridge;

said process cartridge including:

a drum frame for supporting an electrophotographic photosensitive drum, a charging member for

## 24

charging said electrophotographic photosensitive drum, and a cleaning member for removing residual toner from said electrophotographic photosensitive drum;

a developing frame for mounting a developing roller for developing a latent image formed on said electrophotographic photosensitive drum;

a toner frame having a loner accommodating portion for accommodating toner to be used by said developing roller, wherein said toner frame is provided with a coupling portion for swingably coupling with said drum frame, and is provided with a grip for gripping said process cartridge, wherein said toner frame is coupled with said developing frame in a longitudinal direction, wherein said coupling portion has a coupling hole through which a pin is penetrated for swingable coupling between said toner frame and said drum frame, and wherein said toner frame and said coupling drum frame are coupled by inserting said pin through said coupling hole and a drum frame bole provided in said drum frame, wherein said coupling portion is provided at each of one longitudinal end and an other longitudinal end of said toner frame, and is projected toward a portion having said drum frame in a direction crossing with the longitudinal direction of said toner frame, wherein said coupling portion provided at the one longitudinal end is integrally formed with said toner frame, wherein said coupling portion provided at the other longitudinal end is formed on a gear cover mounted to the other longitudinal end of said toner frame, wherein said gear cover functions to cover a gear train mounted on said toner frame;

said apparatus further comprising:

b. feeding means for feeding the recording material.

\* \* \* \* \*

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 5,920,752

DATED : July 6, 1999

INVENTOR(S): TOSHIYUKI KARAKAMA, ET AL.

Page 1 of 6

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

COVER PAGE:

Insert: [\*] -Notice: This patent issued on a continued prosecution application filed under 37 CFR 1.53(d), and is subject to the twenty year patent term provisions of 35 U.S.C. 1.54(a)(2).--.

COLUMN 2:

Line 58, "FIG. 3" should read --FIG. 13--.

COLUMN 5:

Line 17, "a" should read --an--.

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 5,920,752

DATED : July 6, 1999

INVENTOR(S): TOSHIYUKI KARAKAMA, ET AL.

Page 2 of 6

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

COLUMN 11:

Line 35, "12arerelative" should read --12a relative---.

Line 39, "tf12a" should read --toner frame 12a--.

COLUMN 12:

Line 6, "substantially" should read --substantially,--.

Line 33, "be" should be deleted.

COLUMN 16:

Line 8, "foregoing" should read --foregoing,--.

Line 32, "support" should read --supporting--.

Line 36, "a" should read --and--.

Line 40, "wit" should read --with--.

COLUMN 17:

Line 13, ", wherein the outer surface faces" should be changed to ---.

Line 14 should be deleted.

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 5,920,752

DATED : July 6, 1999

INVENTOR(S): TOSHIYUKI KARAKAMA, ET AL.

Page 3 of 6

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

COLUMN 17 (Cont.):

Line 30, "an other" should read --another--.

Line 48, "fame" should read --frame--.

Line 58, "an other" should read --another--.

COLUMN 18:

Line 4, "free," should read --frame,--.

Line 6, ", wherein the outer surface faces said" should be changed to ---.

Line 7 should be deleted.

Line 39, "franc" should read --frame--.

Line 50, "coup led" should read --coupled--.

Line 54, "an other" should read --another--.

COLUMN 19:

Line 2, "wherein the outer surface faces said grip" should be deleted.

Line 3, "provided on said cover," should be deleted.

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 5,920,752

DATED : July 6, 1999

INVENTOR(S): TOSHIYUKI KARAKAMA, ET AL.

Page 4 of 6

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

COLUMN 19 (Cont.):

Line 15, "for" (1<sup>st</sup> occurrence) should read --forming--.  
Line 37, "fob" should read --forming--.  
Line 67, "an" should read --another--.

COLUMN 20:

Line 1, "other" should be deleted.  
Line 12, "is" should read --apparatus--.  
Line 50, "an other" should read --another--.  
Line 67 should be deleted.

COLUMN 21:

Line 1, "on said cover," should be deleted.  
Line 26, "an other" should read --another--.

Line 62, ", wherein the outer surface is" should be changed to ---.

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 5,920,752

DATED : July 6, 1999

INVENTOR(S): TOSHIYUKI KARAKAMA, ET AL.

Page 5 of 6

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

COLUMN 21 (Cont.):

Line 63 should be deleted; and

COLUMN 22:

Line 10, "an other" should read --another--.

Line 43, "an other" should read --another--.

Line 45, "potion" should read --portion--.

Line 58, "portion, wherein the outer surface," should be changed to ---.

Line 59 should be deleted.

COLUMN 23:

Line 31, "apparats" should read --apparatus--.

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 5,920,752

DATED : July 6, 1999

INVENTOR(S): TOSHIYUKI KARAKAMA, ET AL.

Page 6 of 6

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

COLUMN 24:

Line 8, "loner" should read --toner--.

Line 21, "bole" should read --hole--.

Line 23, "an" should read --another--.

Line 24, delete "other".

Signed and Sealed this

Twenty-third Day of January, 2001

Attest:



Q. TODD DICKINSON

Attesting Officer

Commissioner of Patents and Trademarks