



US005924462A

United States Patent [19]

McKaughan

[11] Patent Number: 5,924,462
[45] Date of Patent: Jul. 20, 1999

[54] BEVERAGE FILLING MACHINE

[75] Inventor: Ted McKaughan, Forest Hill, Md.

[73] Assignee: Crown Simplimatic, Baltimore, Md.

[21] Appl. No.: 08/922,657

[22] Filed: Sep. 3, 1997

[51] Int. Cl.⁶ B65B 3/06

[52] U.S. Cl. 141/145; 141/39; 141/147

[58] Field of Search 141/144, 145,
141/146, 147, 39, 40, 44, 45, 47, 48, 49,
50

[56] References Cited

U.S. PATENT DOCUMENTS

2,676,742	4/1954	Day et al.	141/6
2,695,743	11/1954	Wetherby-Williams	141/9
2,728,511	12/1955	Breeback .	
3,825,043	7/1974	Fechheimer	141/147
3,946,770	3/1976	Trinne et al.	141/5
4,103,721	8/1978	Noguchi	141/6
4,442,873	4/1984	Yun .	
4,688,608	8/1987	Puskarz et al.	141/39
5,054,527	10/1991	Rozier	141/39
5,060,702	10/1991	LaWarre, Sr. et al.	141/39
5,150,740	9/1992	Yun .	
5,295,520	3/1994	Acker .	

Primary Examiner—Henry J. Recla


Assistant Examiner—Kerry S Culpepper


Attorney, Agent, or Firm—Howard & Howard


[57] ABSTRACT


A filling apparatus (10) for filling beverage containers (C) with carbonated liquid beverage (B) includes a rotating filling table (16) in which is supported a central tank (26). Beverage containers (C) are sequentially brought into registry with the filling table (16) where they undergo successive phases of vacuum, counter pressure, fill/vent, and snifling before they are released to a separate capping operation. A liquid supply (14) feeds liquid beverage (B) to the bottom of the central tank (26) and a CO₂ supply (32) feeds pressurized CO₂ into the top of the central tank (26). A plurality of valve housings (44) are spaced in generally equal radial and equal circumferential increments about the periphery of the filling table (16) and are associated with a beverage container (C) being filled. Liquid (36), gas (38) and vent (40) conduits extend between the central tank (26) and each valve housing (44). Each valve housing (44) includes a liquid chamber (54) having an outlet (52) for discharging liquid into the beverage container (C), and a vent chamber (60) isolated from the liquid chamber (54). A reciprocating valve (100) is linearly slidably disposed in each valve housing (44) for selective movement between a closed position sealing the outlet (52) and a fill position for passing liquid through the outlet (52) to the beverage container (C). The valves (100) each include a liquid section immersed in the liquid chamber (54), and a vent section disposed in the vent chamber (60). The durable reciprocating valves (100) can be retrofit on central tank filling units still in service, as well as used in new manufacture central tank filling machines.


11 Claims, 4 Drawing Sheets











BEVERAGE FILLING MACHINE

BACKGROUND OF THE INVENTION

1. Field of the Invention

The subject invention relates to a filling apparatus for filling beverage containers with carbonated liquid, and more specifically to an improved filler valve arrangement for such an apparatus having a centrally located carbonated beverage tank.

2. Description of Related Art

Filling apparatus for filling beverage containers with carbonated beverage, e.g., beer and carbonated soft drinks, are large high-speed machines which can continuously fill 800 or more beverage containers per hour. Such filling apparatus have in the past been constructed according to either of two tank types: central tank and annular (or torroidal) tank. Generally, the filler valve components of central tank type machines are not interchangeable with those of annular tank type machines, and vice versa. Traditionally, the central tank type filling apparatus have been used for beer, whereas the annular tank type machines have been used for soft drinks. Although more recently, the industry has seen increasing acceptance of the annular tank type units for filling both soft drink and beer containers.

In a central tank type filling apparatus, an array of remote valve housings are fed with beer and CO₂ via conduits from the pressurized central tank. The filler valves in the valve housings each comprise stacked disks or plates which are pressed tightly together and rotate between various positions to accommodate the vacuum/counter pressure/fill/snift operations. Examples of central tank type filling apparatus with the traditional disk valves are shown in U.S. Pat. No. 2,728,511 to Breeback, issued Dec. 27, 1955 and assigned to the assignee of the subject invention, and U.S. Pat. No. 5,295,520 to Acker, issued Mar. 22, 1994.

The inner valve bodies of the central tank-type disk valve have large surface areas which are pressed together in tight frictional contact to prevent leakage between the various openings. However, these compressed plates must rotate against each other. Rapid wear between the compressed plates of the disk valve is accentuated by the hard granular residue left by evaporated beer. Hence, a major disadvantage of the central tank type filling machines lay in its disk valves which characteristically exhibit poor pressure holding capabilities and require frequent maintenance due to rapid wear between the rotating inner valve body surfaces.

Annular tank filling machines, on the other hand, employ reciprocating filler valves which do not rely on large rotating surfaces to maintain pressure seals. Such reciprocating filler valves are located within the annular tank, having a lower section immersed in the liquid and a top section communicating directly with the pressurized CO₂ for the counter-pressure and venting phases of the filling operation. Therefore, reciprocating filler valves receive liquid beverage and CO₂ directly from, and vent directly back into, the annular tank. Reciprocating filler valves generally exhibit increased pressure holding capabilities and lower (more favorable) maintenance requirements. Examples of prior art reciprocating filler valves for annular tank-type machines may be found in U.S. Pat. No. 4,442,873 issued Apr. 17, 1984 and U.S. Pat. No. 5,150,740 issued Sep. 29, 1992, both in the name of Yun and both assigned to the assignee of the subject invention.

There are a great many central tank filling apparatus still in service. However, there is no know way to integrate the

more reliable reciprocating filler valves, which require immersion in the liquid beverage, with the central tank type units which feed the remote filler valves via conduits.

SUMMARY OF THE INVENTION

The subject invention comprises a central tank filling apparatus which employs reciprocating filler valves. The apparatus includes a base defining a generally vertical axis of rotation. A central tank is rotatably supported on the base about the axis and has a pressure containing interior region. A liquid supply communicates with the central tank for feeding liquid to the interior region. A plurality of receiving areas are spaced in generally equal radial and equal circumferential increments about the axis and are fixedly connected to the central tank for rotation therewith upon the base. A liquid conduit extends between the interior region of the central tank and each receiving area. A valve housing is supported on each receiving area and communicates with a corresponding one of the liquid conduits. Each valve housing includes an outlet for discharging liquid into a beverage container.

The improvement of the subject invention comprises a reciprocating filler valve which is linearly slidably disposed in each valve housing for selective movement between a closed position sealing the outlet and a fill position for passing liquid through the outlet to a beverage container. By using a reciprocating filler valve, as has been exclusively associated in the prior art with annular tanks, the subject invention overcomes the disadvantages and limitation of the prior art disk-type filler valves. The more popular and current manufacture reciprocating filler valves can now be retrofit on central tank filling units still in service. In this manner, both new manufacture and existing central tank filling machines can be outfitted/retrofitted with the more durable and pressure hardy reciprocating filler valves.

BRIEF DESCRIPTION OF THE DRAWINGS

Other advantages of the present invention will be readily appreciated as the same becomes better understood by reference to the following detailed description when considered in connection with the accompanying drawings wherein:

FIG. 1 is a partial cross-sectional view of a filling apparatus for filling beverage containers with carbonated liquid according to the subject invention;

FIG. 2 is a fragmentary cross-sectional view showing the improved filler valve and valve housing assembly attached to the receiving area of the filling apparatus and a beverage container positioned directly there below;

FIG. 3 is a cross-sectional view of the filler valve and valve housing, with the filler valve shown in its closed position for respective vacuum, counter-pressure, filling and snifting operations; and

FIG. 4 is cross-sectional view as in FIG. 3 showing the filler valve in its open position for simultaneous beverage filling and venting operations.

DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to the Figures, wherein like numerals indicate like or corresponding parts throughout the several views, a filling apparatus for filling beverage containers with carbonated liquid is generally shown at **10** in FIG. 1. The filling apparatus **10** comprises a base, generally indicated at **12**, which is fixed to a floor support and forms the non-moving

portion of the filling apparatus **10**. The base **12** includes a liquid supply conduit **14** which is centrally located coincident with a generally vertical axis of rotation A. The liquid supply conduit **14** is non-rotating and receives a pressurized flow of liquid beverage B from a pump and supply reservoir (not shown).

A filling table, generally indicated at **16** in FIG. 1, is rotatably supported upon the base **12** via bearing **18**. The filling table **16** includes a plurality of container platforms **20** spaced incrementally, i.e., uniformly, about the circumference of the table **16** for each supporting a beverage container C during the filling process. As is well known in the art, the platforms **20** are vertically indexable to bring containers C into and out of registry with an overhead filler valve assembly, as described in greater detail below. A large externally-toothed ring gear **22** is engaged by the pinion on a drive motor **24** to forcibly rotate the filling table **16** about the vertical axis A. In this manner, beverage containers C are placed on successive platforms **20** where they rotate with the filling table **16** throughout a portion of one complete revolution during the sequential vacuum/counter-pressure/fill/snift operations. The beverage containers C are then removed from the platforms and delivered promptly to a capping or other such closure operation. Although the drawing figures illustrate the beverage container C as a typical necked glass bottle, those skilled in the art will readily appreciate that the subject invention can be practiced with plastic bottles and can-type beverage containers.

A central tank **26** is fixed to the filling table **16** for rotation therewith over the base **12**. The central tank **26** is of the type having a pressure containing interior region **28** which is intersected by the central axis A. The liquid supply conduit **14** delivers liquid beverage B under pressure into the bottom of the interior region **28**. The liquid level **30** of the liquid beverage B is maintained at a preferred elevation in the interior region **28**. Pressurized CO₂ is delivered via a gas supply **32** into the top of the interior region **28** to occupy the space above the liquid level **30**.

The filling table **16** further includes a plurality of receiving areas **34** aligned substantially directly above each platform **20**, i.e., in radial and circumferential increments substantially equivalent to the platforms **20**. In this manner, the receiving areas **34** rotate about the vertical axis A together with the platforms **20** and the central tank **26**. A separate liquid conduit **36** extends from the bottom of the interior region **28** (i.e., below the liquid level **30**) to each receiving area **34**. Similarly, a gas conduit **38** extends from the top of the interior region **28** (i.e., above the liquid level **30**) to each receiving area **34** for conducting pressurized CO₂ thereto. Also, a vent conduit **40** extends between a segregated vent receptacle **42** in the interior region **28** of the central tank **26** to each receiving area **34**.

A valve housing, generally indicated at **44** in FIGS. 1-4, is attached to each receiving area **34** and preferably includes an upper body section **46**, a middle body section **48**, and a lower body section **50**. The valve housing **44** communicates with each corresponding liquid conduit **36**, gas conduit **38** and vent conduit **40** through respective openings in the middle body section **48**, as shown in FIG. 4. The valve housing **44** further includes an outlet **52** in the lower body section **50** for discharging liquid beverage B and CO₂ into a beverage container C. A centering bell **53** extends from the lower body section **50**, in alignment with the outlet **52**, for receiving the mouth of a beverage container C.

The valve housing **44** includes a liquid chamber **54** formed substantially within the middle body section **48** and

partially with the lower body section **50**. The liquid chamber **54** communicates directly with the outlet **52**, and is fed liquid beverage B from the liquid conduit **36** via a short liquid passage **56**. A seal **58** prevents leakage of the liquid beverage B, which is at an elevated pressure relative to atmospheric, into the interface between the middle **48** and lower **50** body sections.

The valve housing **44** also includes a vent chamber **60** formed substantially within the upper body section **46** but bounded along its bottom by the middle body section **48**. A stem bushing **62** is disposed in the middle body section **48**, between the vent chamber **60** and the liquid chamber **54**, for preventing liquid beverage B migration into the vent chamber **60**. In other words, the vent chamber **60** is isolated from the liquid chamber **54** in the valve housing **44** because the liquid level **30** in the interior region **28** of the central tank **26** may be maintained above vent chamber **60** elevation and would otherwise cause flooding of the vent chamber **60**.

A valve actuator, generally indicated at **64** in FIGS. 3 and 4, extends through an aperture in the upper body section **46** and into the vent chamber **60**. The valve actuator **64** includes a shaft **66** pivotally journaled in a bearing **68**, which is set in the upper body section **46**. The shaft **66** is thus supported for rotation about a generally horizontal axis, and includes an internal cam **70** on its interior end and a rotating external cam **72** on its exterior end. In the preferred embodiment, the internal cam **70** is generally cylindrical with a flat surface therein formed parallel to its horizontal axis of rotation. A bolt **74** or other such fastener may be used to secure the external cam **72** onto the exterior end of the shaft **66**.

Referring again to FIG. 1, a generally annular cam rail **76** is fixedly supported on stanchions **78** about the exterior of the rotating filling table **16**. As the filling table **16** rotates, the external cam **72** of each valve housing **44** engages a specially profiled cam (not shown) supported on the cam rail **76** to forcibly pivot the shaft **66** in either direction, thereby causing the internal cam **70** to rotate back and forth at predetermined intervals to open for filling/venting and close before sniffing operations.

Numerous passages are formed in the valve housing **44** to carry out the movement of the various gases during the vacuum, counter pressure, and snift operations. More specifically, and referring again to FIGS. 3 and 4, the valve housing **44** includes a pressurized gas (CO₂) passage **80** routing through the middle **48** and lower **50** body sections. The gas passage **80** connects to the gas conduit **38** and has a discharge **82** in the lower body section **50** just downstream of the outlet **52**. A normally closed flow control valve **84** is located in the middle body section **48**, upstream of the discharge **82**. The flow control valve **84** has a protruding push button which is depressed by a cam (not shown) supported on the cam rail **76**. In this manner, the flow control valve **84** is actuated along a predetermined arc of movement of the filling table **16** to cause pressurized CO₂ to flow from the gas conduit **38** and out the discharge **82** during the counter pressure phase.

The valve housing **44** also includes a vent passage **86** formed in both the middle **48** and upper **46** body sections. The vent passage **86** routes vented CO₂, still under pressure, from the vent chamber **60** to the vent conduit **40**. Furthermore, the valve housing **44** includes a vacuum passage **88** extending through all of the upper **46**, middle **48** and lower **50** body sections. The vacuum passage **88** has an inlet **90** in the lower body section **50** just downstream of the sealing surface in relative proximity to the discharge **82** for the gas passage **80**. A vacuum conduit **92** extending from a

vacuum generator, not shown, connects to the vacuum passage **88** for removing gases from a beverage container **C** during an initial vacuum operation, as described in detail below. A normally closed vacuum control valve **94** is operatively disposed on the middle body section **48**, and has a protruding push button which is depressed by a cam (not shown) supported on the cam rail **76**. In this manner, the vacuum control valve **94** is actuated along a predetermined arc of movement of the filling table **16** to cause gases present initially in an empty beverage container **C** to be sucked out through the inlet **90** during the vacuum phase.

Additionally, the valve housing **44** includes a snift aperture **96** downstream of the outlet **52**, also in proximity with the discharge **82** and inlet **90**. A normally closed snift control valve **98** is operatively associated with the snift aperture **96** for controlling depressurization of a filled beverage container **C**. The snift control valve **98** is attached to the lower body section **50** and also has a protruding push button which is depressed by a cam (not shown) supported on the cam rail **76** after completing the fill cycle. When the snift control valve **98** is depressed, the pressurized gas in the neck of the beverage container **C** is discharged, returning the interior of the beverage container **C** to atmospheric pressure prior to separation from the centering bell **53**.

A vent stem and valve assembly, generally indicated at **100** in FIGS. 2-4, is linearly slidably disposed in the valve housing **44** for selective reciprocating movement between a closed position (FIG. 3) sealing the outlet **52** and a fill position (FIG. 4) for passing liquid beverage **B** through the outlet **52** to a beverage container **C**. Preferably, only one valve assembly **100** is located in each valve housing **44** and serves only one beverage container **C** at a time. The valve assembly **100** includes an elongated stem **102** oriented vertically and slidably disposed within both the vent **60** and liquid **54** chambers by the stem bushing **62**. The stem **102** is hollow and forms a bypass through the liquid chamber **54** for venting pressurized gas from the beverage container **C** to the vent chamber **60** during the filling operation.

The upper end of the stem **102** comprises a vent section which is contained in the vent chamber **60**. A vent control valve **104** is telescopically supported over the upper end of the stem **102**. A synthetic abrasion-resistant cap **106** with attached sleeve **108** covers the control valve **104** and engages the internal cam **70** directly above. A compression spring **110** acts between the cap **106** and the stem bushing **62** to open the vent control valve **104** when the valve assembly **100** is in its fill position (FIG. 4) and close the vent control valve **104** when the valve assembly **100** is in its closed position (FIG. 3). Openings in the sides of the sleeve **108** allow CO₂ to vent when the valve assembly **100** is in its fill position.

The lower end of the stem **102** comprises a liquid section which is immersed in the liquid chamber **54**. A liquid flow seal **112** is carried on the lower end of the stem **102** for engaging the outlet **52** when the valve assembly **100** is in the closed position, as shown in FIG. 3. When the seal **112** is pressed against the outlet **52**, by the action of the internal cam **70**, liquid beverage **B** within the liquid chamber **54** is prevented from escaping. An annular mesh screen **114** is supported on the stem **102** just upstream of the seal **112**. An extension tube **115** extends from the lower end of the stem **102** to establish a fill level in the beverage container **C**. The extension tube **115** may or may not include a float-type valve.

A counterbalance spring **116** is housed within a stationary cage **118** disposed in the liquid chamber **54**. The cage **118**

includes numerous side openings so that liquid beverage **B** may freely permeate and fill its interior. A spool **120** within the cage **118** forms a stop for the lower end of the counterbalance spring **116**. The upper end of the counterbalance spring **116** bears against a flange **122** which in turn is fixedly connected to the stem **102**.

In operation, an empty beverage container **C** positioned on a platform **20** is lifted into registry with the centering bell **53** of a valve housing **44**, thereby establishing a pressure tight seal between the two. As the filling table **16** rotates, the vacuum control valve **94** is first depressed by a stationary cam on the cam rail **76**, thus drawing a vacuum on the beverage container **C**. Then, as the vacuum control valve **94** is returned to a closed condition, the flow control valve **84** is opened by a different stationary cam on the cam rail **76** to fill the beverage container **C** with CO₂ from the interior region **28** of the central tank **26**. Another stationary cam actuates the external cam **72** allowing the valve assembly **100** to raise to the fill position (FIG. 4) as soon as the internal pressure in the beverage container **C** approaches that in the central tank **26**. At this, the flow control valve **84** closes and the counterbalance spring **116** lifts the valve assembly **100** to the fill position, allowing liquid beverage **B** to flow gently under gravity into the beverage container **C**.

The (predominantly CO₂) gases within the beverage container **C** are displaced through the extension tube **115** and the stem **102** as liquid beverage **B** fills the beverage container **C**. Such displaced gases flow up past the open vent control valve **104** and into the vent chamber **60**. From the vent chamber **60**, the gases are pushed into the vent passage **86** and then through the vent conduit **40** back to the segregated vent chamber within the central tank **26**, as is well known in the art. The liquid beverage **B** stops flowing into the beverage container **C** when its level reaches the opening at the lower end of the extension tube **115**; at the same time the actuator **64** is rotated to its closed position (FIG. 3) thus depressing the cap **106** and forcing the stem **102** and attached seal **112** downwardly into engagement with the outlet **52**. Next, a stationary cam on the cam rail **76** depresses the snift control valve **98**, gently depressurizing the liquid and gas contents in the beverage container **C** and returning it to atmospheric pressure before separation from the centering bell **53**. Afterwards, the filled beverage container **C** together with its platform **20** lowers from the valve housing **44** and is then transferred to a suitable capping/closure operation.

The invention has been described in an illustrative manner, and it is to be understood that the terminology which has been used is intended to be in the nature of words of description rather than of limitation.

Obviously, many modifications and variations of the present invention are possible in light of the above teachings. It is, therefore, to be understood that within the scope of the appended claims, wherein reference numerals are merely for convenience and are not to be in any way limiting, the invention may be practiced otherwise than as specifically described.

What is claimed is:

1. A filling apparatus (**10**) for filling beverage containers (**C**) with carbonated liquid beverage (**B**), said apparatus (**10**) comprising: a base (**12**) defining a generally vertical axis of rotation (**A**); a central tank (**26**) rotatably supported on said base (**12**) about said axis (**A**) and having a pressure containing interior region (**28**); a liquid supply (**14**) communicating with said central tank (**26**) for feeding liquid beverage (**B**) to said interior region (**28**); a plurality of receiving areas (**34**) spaced in generally equal radial and equal circumfer-

ential increments about said axis (A) and fixedly connected to said central tank (26) for rotation therewith upon said base (12); a liquid conduit (36) extending between said interior region (28) of said central tank (26) and each said receiving area (34); a valve housing (44) supported on each said receiving area (34) and communicating with a corresponding one of said liquid conduits (36), each said valve housing (44) including a liquid chamber (54) having an outlet (52) for discharging liquid into the beverage container (C) and a vent chamber (60) communicating with said pressure contained interior region (28), said vent chamber (60) being totally isolated from said liquid chamber (54); a reciprocating vent stem and valve assembly (100) including a hollow vent stem (102) linearly slidably disposed in each said valve housing (44) and a valve (112) supported on and about said stem (102) for selective movement with said stem (102) between an open position and a closed position sealing said outlet (52) to the beverage container (C) as gases are vented through said hollow vent stem (102) into said vent chamber (60); and a valve actuator (64) extending through said vent chamber (60) of each valve housing (44) and having an internal cam (70) operatively engaging said vent stem (102) for moving said stem (102) and said valve (112) in unison.

2. An assembly as set forth in claim 1 wherein each said valve housing (44) includes a liquid chamber (54) communicating with said outlet (52), and each said vent stem (102) includes a liquid section immersed in said liquid chamber (54).

3. An assembly as set forth in claim 2 wherein each said valve housing (44) includes a vent chamber (60), and each said vent stem (102) includes a vent section disposed in the respective said vent chamber (60).

4. An assembly as set forth in claim 3 further including a gas supply (32) communicating with said central tank (26) for feeding pressurized gas to said interior region (28), and a gas conduit (38) conducting pressurized gas from said interior region (28) of said central tank (26) to each said valve housing (44).

5. An assembly as set forth in claim 4 wherein each said valve housing (44) includes a pressurized gas passage (80) having a discharge (82) downstream of said outlet (52) and a flow control valve (84) upstream of said discharge (82).

6. An assembly as set forth in claim 3 wherein each said stem (102) has a bypass formed therein for venting pressurized gas to said vent chamber (60), said bypass including a vent control valve (104).

7. An assembly as set forth in claim 6 wherein each said valve housing (44) includes a stem bushing (62) slidably supporting said vent stem (102) between said vent chamber (60) and said liquid chamber (54).

8. An assembly as set forth in claim 3 wherein each said valve housing (44) includes a centering bell (53) extending from said outlet (52) for receiving the mouth of a beverage container (C).

9. An assembly as set forth in claim 3 wherein each said valve housing (44) includes a snift aperture (96) downstream of said outlet (52), and a snift control valve (98) operatively associated with said snift aperture (96) for controlling depressurization of a filled beverage container (C).

10. An assembly as set forth in claim 1 wherein each said valve actuator (64) includes a shaft (66) pivotally journaled in said valve housing (44), said shaft (66) supporting said internal cam (70) on one end thereof and an external cam (72) on the other end thereof.

11. A filling apparatus (10) for filling beverage containers (C) with carbonated liquid beverage (B), said apparatus (10) comprising: a base (12) defining a generally vertical axis of rotation (A); a central tank (26) rotatably supported on said base (12) about said axis (A) and having a pressure containing interior region (28); a liquid supply (13) communicating with said central tank (26) for feeding liquid beverage (B) to said interior region (28); a plurality of receiving areas (34) spaced in generally equal radial and equal circumferential increments about said axis (A) and fixedly connected to said central tank (26) for rotation therewith upon said base (12); a liquid conduit (36) extending between said interior region (28) of said central tank (26) and each said receiving area (34); a valve housing (44) supported on each said receiving area (34) and communicating with a corresponding one of said liquid conduits (36), each said valve housing (44) including a liquid chamber (54) having an outlet (52) for discharging liquid into the beverage container (C) and a vent chamber (60) communicating with said pressure contained interior region (28), said vent chamber (60) being totally isolated from said liquid chamber (54); a reciprocating vent stem and valve assembly (100) including a hollow vent stem (102) linearly slidably disposed in each said valve housing (44) and a valve (112) supported on and about said stem (102) for selective movement with said stem (102) between an open position and a closed position sealing said outlet (52) to the beverage container (C) as gases are vented through said hollow vent stem (102) into said vent chamber (60); a vacuum generator; a vacuum conduit (92) extending from said vacuum generator and communicating from each said valve housing (44) for removing gases from a beverage container (C); and a vacuum control valve operatively disposed on the respective said valve housing (44).

* * * * *