



US006014327A

United States Patent [19] Banks

[11] Patent Number: **6,014,327**
[45] Date of Patent: **Jan. 11, 2000**

[54] MEMORY APPARATUS INCLUDING PROGRAMMABLE NON-VOLATILE MULTI-BIT MEMORY CELL, AND APPARATUS AND METHOD FOR DEMARCATING MEMORY STATES OF THE CELL

[75] Inventor: **Gerald J. Banks**, Fremont, Calif.

[73] Assignee: **BTG International Inc.**, Gulph Mills, Pa.

[21] Appl. No.: **09/311,748**

[22] Filed: **May 14, 1999**

Related U.S. Application Data

[60] Division of application No. 08/975,919, Nov. 21, 1997, which is a continuation-in-part of application No. 08/410,200, Feb. 27, 1995, Pat. No. 5,764,571, which is a division of application No. 08/071,816, Jun. 4, 1993, Pat. No. 5,394,362, which is a continuation of application No. 07/652,878, Feb. 8, 1991, Pat. No. 5,218,569.

[51] Int. Cl.⁷ **G11C 13/00**

[52] U.S. Cl. **365/185.03; 365/168**

[58] Field of Search **365/168, 189.01, 365/189.03, 45, 185.03**

[56] References Cited

U.S. PATENT DOCUMENTS

Re. 32,401 4/1987 Beilstein 365/168


Primary Examiner—Terrell W. Fears

Attorney, Agent, or Firm—Vorys, Sater, Seymour and Pease LLP

[57] ABSTRACT

Memory states of a multi-bit memory cell are demarcated by generating read reference signals having levels that constitute boundaries of the memory states. The read reference signals are dependent upon the levels of programming reference signals used for controlling the programming of the memory cell. The memory cell can thus be programmed without reading out its memory state during the programming process, with programming margins being assured by the dependence of the read reference signals on the programming reference signals. Both sets of reference signals may be generated by reference cells which track variations in the operating characteristics of the memory cell with changes in conditions, such as temperature and system voltages, to enhance the reliability of memory programming and readout.

33 Claims, 26 Drawing Sheets






FIG. 1




FIG. 2
PRIOR ART




FIG. 3




FIG. 4
PRIOR ART READ




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21A




FIG. 21B




FIG. 21C




FIG. 21D




FIG. 22




FIG. 23

**MEMORY APPARATUS INCLUDING
PROGRAMMABLE NON-VOLATILE MULTI-
BIT MEMORY CELL, AND APPARATUS AND
METHOD FOR DEMARCATING MEMORY
STATES OF THE CELL**

CROSS-REFERENCE TO RELATED
APPLICATIONS

This is a division of application Ser. No. 08/975,919 filed Nov. 21, 1997, which is a continuation-in-part of application Ser. No. 08/410,200 filed Feb. 27, 1995 (now U.S. Pat. No. 5,764,571), which is a division of application Ser. No. 08/071,816 filed Jun. 4, 1993 (now U.S. Pat. No. 5,394,362), which is a continuation of application Ser. No. 07/652,878 filed Feb. 8, 1991 (now U.S. Pat. No. 5,218,569).

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates to non-volatile memory devices and is more particularly concerned with certain apparatus and methods based on new concepts of memory state demarcation and programming reference signal generation for multi-bit electrically alterable non-volatile memory (EANVM) cells.

2. Related Background Art

In conventional single-bit per cell memory devices, the memory cell assumes one of two information storage states, either an "on" state or an "off" state. This combination of either "on" or "off" defines one bit of information. A memory device using such single-bit cells to store n bits of data (n being an integer greater than 0) thus requires n separate memory cells.

Increasing the number of bits which can be stored in a single-bit per cell memory device involves increasing the number of memory cells on a one-for-one basis with the number of bits of data to be stored. Methods for increasing the number of memory cells in a single memory device have relied upon advanced manufacturing techniques that produce larger chips containing more memory cells or that produce smaller memory cells (e.g., by high resolution lithography) to allow more memory cells to be placed in a given area on a single chip.

An alternative to the single-bit per cell approach involves storing multiple bits of data in a single memory cell. Previous approaches to implementing multiple-bit per cell non-volatile memory devices have typically involved mask-programmable read only memories (ROMs). In one of these approaches, the channel width and/or length of the memory cell is varied such that 2^n different conductivity values are obtained which correspond to 2^n different states, whereby n bits of data can be stored by a single memory cell. In another approach, the ion implant for the threshold voltage is varied such that the memory cell will have 2^n different voltage thresholds (V_t) corresponding to 2^n different conductivity levels corresponding to 2^n different states, whereby n bits of data can be stored by a single memory cell. Examples of memory devices of these types are described in U.S. Pat. No. 4,192,014 to Craycraft, U.S. Pat. No. 4,586,163 to Koike, U.S. Pat. No. 4,287,570 to Stark, U.S. Pat. No. 4,327,424 to Wu, and U.S. Pat. No. 4,847,808 to Kobatake.

Electrically alterable non-volatile memory (EANVM) devices capable of storing multiple bits of data per cell are also known. In these devices, the multiple memory states of the cell are demarcated by predetermined reference signal levels that define boundaries between adjacent memory

states. The memory cell is read out by comparing a signal from the cell with the reference signals to determine the relative levels of the cell signal and the reference signals. The comparison results indicate whether the cell signal level is above or below the respective memory state boundaries, and thus collectively indicate the programmed state of the cell corresponding to the stored data. The comparison results are encoded to reproduce the stored data and complete the cell readout operation. Generally speaking, the number of reference levels required to demarcate n memory states for storing n bits of data is $2^n - 1$. The number may be greater if, for example, the uppermost or lowermost memory state is to be bounded on both sides.

Previous approaches to programming multi-bit EANVM cells are based on a repeated cycle of programming and readout of the cell. The cell is programmed incrementally, by the application of programming pulses, and the programmed status of the cell is checked repeatedly during the programming process by reading out the memory state of the cell as described above to verify the attained level of programming. Programming is continued until the target memory state has been reached, as indicated by the readout of the cell.

In order to minimize the possibility of readout errors, the programming level of a multi-bit EANVM cell should be set with a margin relative to the reference signal level or levels that demarcate the target memory state. The programming margin should be sufficient to avoid readout errors that might occur due to variations in operating characteristics of the cell with changing conditions such as temperature, system voltages, or mere passage of time. More particularly, if the cell is programmed too close to a memory state boundary, slight variations in the operating characteristics could shift the cell signal level relative to the state boundary level, resulting in an error upon subsequent readout of the cell.

Program margining is not particularly problematical in single-bit per cell memory devices, since there are only two memory states, and thus no intermediate memory states. Because it is impossible to overshoot the target state by overprogramming the cell, the cell may simply be programmed to set the cell signal level as far as possible from the reference level bounding the two memory states.

By contrast, the presence of one or more intermediate memory states makes program margining a significant concern in the case of multi-bit per cell devices, because an intermediate memory state requires a programming margin that provides adequate separation from two boundary levels—that is, the boundaries of the intermediate memory state with both the state above and the state below. Programming the cell too close to either level can result in a readout error. Also, both overprogramming and under programming must be avoided to prevent overshooting and undershooting the target intermediate state.

Previous program margining techniques include techniques that, for programming purposes, shift the cell signal level or the reference signal levels relative to their values during normal memory readout. The effect in either case is that, for a given programming amount of the cell, the cell will read differently during programming than during a normal readout operation. The difference corresponds to the shift amount of cell signal or the reference signals and provides a programming margin. Examples of these techniques are found in U.S. Pat. No. 5,172,338 to Mehrotra et al. and in Beliker et al., "A Four-State EEPROM Using Floating-Gate Memory Cells," *IEEE Journal of Solid State Circuits*, Vol. SC-22, No. 3, June 1987, pp. 460-463.

Another margining technique involves the provision of additional reference signals having levels intermediate those of the state-demarcating reference levels. The intermediate reference levels define program margin ranges in conjunction with the state-demarcating levels. After the cell reaches the target memory state, as indicated by comparison with the state-demarcating signals, programming is continued based on further comparison of the cell signal with one or more intermediate reference signals to provide a programming margin. An example of this technique is found in U.S. Pat. No. 4,964,079 to Devin.

In the above-described approaches to programming multi-bit per cell EANVM devices, the programming speed (total time to program a cell to a target state) is substantially limited by the need for repeated readout of the memory cell during the programming process. Also, the aforementioned program margining techniques impose substantial complications on the overall circuit design due to the need to shift the cell signal level or the state-demarcating reference signal levels, or to provide intermediate reference levels for establishing program margin ranges in conjunction with the state-demarcating reference signal levels. Furthermore, these margining techniques do not assure an optimum programming margin throughout variations in operating characteristics of the cell, because they do not precisely track such variations with changing conditions that affect the operating characteristics.

SUMMARY OF THE INVENTION

The predecessor applications underlying the present application disclose a completely different approach to multi-bit per cell EANVM programming (the approach is also described in detail herein). According to this approach, the programming control scheme uses a programming reference signal corresponding to the target memory state to program the memory cell, and does not require reading out the memory state of the cell during programming.

The invention claimed in the present application is based on new concepts of memory state demarcation and programming reference signal generation that can be applied with great advantage to the aforementioned approach. According to a first of these concepts, a plurality of programming reference signals (or signals set in substantial correspondence therewith) are used to generate the state-demarcating reference signals. This is done in such a manner that each programming reference signal (or correspondingly set signal) has a level unique to its corresponding memory state. As will be more fully appreciated from the detailed description that follows, by generating the state-demarcating reference signals in this manner, it becomes possible to program a multi-bit EANVM cell without reading out the cell's memory state during the programming operation, while at the same time providing effective program margining without the complexities associated with the previous margining techniques described above.

According to one of its broader aspects, the present invention thus provides an apparatus for demarcating memory states of an EANVM cell having more than two memory states. The apparatus comprises a reference signal generating circuit which generates a plurality of signals corresponding to memory states of the cell, each signal having a level unique to its corresponding memory state and substantially the same as a programming reference level for controlling programming of the cell to the corresponding memory state. The reference signal generating circuit uses the plurality of signals to generate reference signals having levels that constitute boundaries of memory states of the cell.

The invention also provides a programmable multi-level memory apparatus, which comprises an EANVM cell having more than two memory states, a programming circuit for programming the EANVM cell, and a reference signal generating circuit as described above.

According to another of its broader aspects, the present invention provides an apparatus for demarcating memory states of an EANVM cell having more than two memory states, the apparatus comprising a reference signal generating circuit which generates reference signals having levels that constitute boundaries of memory states of the cell. The reference signals are generated dependent upon a plurality of signal levels that are set in substantial correspondence with programming reference levels for controlling programming of the cell, with each programming reference level being unique to a different memory state of the cell.

The invention also provides a programmable multi-level memory apparatus, which comprises an EANVM cell having more than two memory states, a programming circuit for programming the cell, and a reference signal generating circuit as just described.

In a preferred mode of the invention, the plurality of signals used to generate state-bounding the reference signals are themselves generated by reference cells that substantially track changes in operating characteristics of the EANVM cell with changes in conditions that affect the operating characteristics. The reference cells may have substantially the same construction as the EANVM cell, and be manufactured concurrently with the EANVM cell, by the same fabrication process, as elements of the same integrated circuit with the EANVM cell. Thus, the signals that are used to generate the state-bounding reference signals can track changes in the operating characteristics of the EANVM cell with high accuracy. This makes it possible to maintain optimum programming margins throughout variations in operating characteristics of the EANVM cell.

Another new concept of the present invention relates to programming reference signal generation, and in particular the use of reference cells for this purpose. According to this concept, which may (but need not be) applied in conjunction with the first concept discussed above, the programming reference signals are generated by corresponding reference cells which substantially track changes in operating characteristics of the EANVM cell with changes in conditions that affect the characteristics. This assures a stable relationship between the cell signal level and the programming reference signal levels and leads to better programming consistency.

Thus, in accordance with yet another of its broader aspects, the present invention provides a programmable multi-level memory apparatus which comprises an EANVM cell having more than two memory states, a programming reference signal generating circuit, and a programming circuit. The programming reference signal generating circuit includes a plurality of reference cells which substantially track changes in operating characteristics in the EANVM cell with changes in conditions that affect the operating characteristics. The reference cells include a corresponding reference cell for each memory state, with each reference cell being programmed such that the programming reference signal generating circuit generates a programming reference signal having a level unique to the corresponding memory state. The programming circuit selectively programs the EANVM cell in accordance with the level of each programming reference cell.

Still further aspects of the invention relate to the methodology of demarcating memory states of a multi-level EANVM cell based on the principles discussed above.

The principles of the present invention, as well as its various aspects, features, and advantages, will be more fully appreciated from the following detailed description taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a generic schematic representation of a non-volatile floating gate memory cell.

FIG. 2 is a block diagram of a prior art single-bit memory system.

FIG. 3 is a timing diagram of the voltage threshold of a prior art single-bit per cell EANVM system being programmed from an erased "1" state to a programmed "0" state.

FIG. 4 is a timing diagram of the bit line voltage of a prior single-bit per cell EANVM during a read operation. It illustrates VOLTAGE signals for both the programmed and erased conditions.

FIG. 5 is a block diagram of an M×N memory array implementing a multi-bit per cell EANVM system.

FIG. 6 is a block diagram of a circuit for reading a multi-bit EANVM cell.

FIG. 7 shows the bit line voltage as a function of time during a read cycle for a 2-bit per cell EANVM which has been programmed to one of four possible states, (0,0), (1,0), (0,1) and a fully erased condition (1,1). Four separate voltage levels are represented in this figure, each representing one of the four possible states. Only one of these would be present for any given read operation.

FIG. 8 is a block diagram of a multi-bit per cell system combining program/verify and read circuitry.

FIG. 9 is a timing diagram for the voltage threshold of a 2-bit EANVM cell being programmed from a fully erased (1,1) state to one of the other three possible states.

FIG. 10 is a timing diagram which illustrates the voltage threshold of a 2-bit EANVM cell being erased from a fully programmed (0,0) state to one of the other three possible states.

FIG. 11 is a timing diagram illustrating the voltage threshold of a 2-bit EANVM cell during a program/verify cycle using fixed width program pulses.

FIG. 12 is a timing diagram illustrating the bit line voltage of a 2-bit EANVM cell during a program/verify process which uses fixed width program pulses.

FIG. 13 is a timing diagram illustrating the voltage threshold of a 2-bit EANVM cell during a program/verify cycle using variable width program pulses.

FIG. 14 is a timing diagram illustrating the bit line voltage of a 2-bit EANVM cell during a program/verify process which uses variable width program pulses.

FIG. 15 is a simplified diagram of a circuit for generating read reference voltages for demarcating memory states in a 2-bit per cell EANVM in accordance with the present invention.

FIG. 16 is a diagram showing the relationship between the read and programming reference voltages in a memory system using the circuit of FIG. 15.

FIG. 17 illustrates a modification to the circuit of FIG. 15.

FIG. 18 illustrates another circuit for generating read reference voltages.

FIG. 19 is a more generalized diagram illustrating how the circuit of FIG. 16 can be applied to a 2-bit per cell EANVM array.

FIG. 20 is a simplified diagram of a circuit for generating programming reference voltages in accordance with the present invention. The circuit is shown coupled to a verify reference select circuit for selecting among the programming reference voltages.

FIGS. 21A–21D are timing diagrams of the bit line voltage during readout of a 2-bit EANVM cell programmed according to programming reference signals for each of the four possible memory states.

FIG. 22 is a simplified diagram illustrating a combined circuit for generating both read and programming reference voltages in accordance with the present invention.

FIG. 23 is a diagram similar to FIG. 22, but in which the reference cells are in the form of ROM cells.

DETAILED DESCRIPTION OF THE INVENTION

The invention will now be described in detail in relation to several preferred embodiments illustrated in the accompanying drawings. Of course, it will be understood that the illustrative embodiments are merely exemplary and that the scope of the present invention, as defined in the appended claims, encompasses a wide range of alternatives, modifications and equivalents, which may be implemented consistent with the basic principles described herein.

Generally speaking, the invention described herein allows multiple bits of information to be efficiently and reliably stored in and read from an electrically alterable non-volatile memory (EANVM). In the preferred practice of the invention, this is accomplished by electrically varying the conductivity of the channel of a floating gate FET to be within any one of K^n conductivity ranges, where "K" represents the base of the numbering system being employed (in a binary system, $K=2$) and n is the number of bits stored per cell ($n \geq 2$). The conductivity range is then sensed and encoded based on reference signal levels corresponding to boundaries of the conductivity ranges to read out the memory cell. The floating gate FET conductivity is electrically modified using programming hardware and algorithms which supply appropriate signals to the EANVM memory device in a program/verify control cycle which incrementally stores electrons on the floating gate until the desired conductivity level is achieved. For the purpose of illustration, the systems described herein will assume a binary system which stores 2-bits per memory cell.

I. Conventional Single-Bit EANVM Devices

Before considering the subject matter of the present invention in detail, it is appropriate, for purposes of perspective, to consider conventional single-bit per cell EANVM devices.

FIG. 1 is a generic schematic representation of a non-volatile floating gate FET memory cell 10.

The FET memory cell 10 includes a control gate 12 which is used either to select the memory cell for reading or is used to cause electrons to be injected onto a floating gate 14 during the programming process. Floating gate 14 is an electrically isolated structure which can indefinitely store electrons. A drain region 16 of the FET is coupled to a source region 18 by a channel region 19. The presence or absence of electrons on floating gate 14 alters the voltage threshold of the memory cell 10 and, as a result, alters the conductivity of its channel region. When the floating gate 14 is fully erased and the control gate 12 has been selected, the channel region 19 is in the fully "on", or high conductivity, state.

When the floating gate **14** is fully programmed, the channel region **19** is in the fully “off”, or low conductivity, state.

FIG. **2** is a block diagram of a conventional single-bit EANVM memory system **30**. The memory system **30** stores a single bit of information in an EANVM cell (FET) **32**. The cell **32**, which has the same construction as FET **10** in FIG. **1**, is selected for reading or writing when a row, or word, select signal is applied to a control gate terminal **34**. A source terminal **36** for the cell **32** is connected to a reference ground potential. A drain terminal **38** is connected through a pull-up device (resistor) **39** to a voltage $V_{\text{pull-up}}$ at a terminal **40**. Terminal **38** serves as the output terminal of the cell **32**. When the cell **32** stores a “0” bit, the channel of the FET is in a low conductivity, or high impedance, state so that the voltage at terminal **38** is pulled up to the voltage level $V_{\text{pull-up}}$ on terminal **40**. When the cell **32** stores a “1” bit, the channel of the FET is in a high conductivity, or low impedance, state so that the voltage at terminal **38** is pulled-down by the ground potential at terminal **36**.

For reading the value of the single bit stored in the cell **32**, a sense amplifier **42** compares the voltage at terminal **38** with a reference voltage Ref at terminal **43**. If a “0” is stored on the EANVM cell **32**, the cell is in a low conductivity state and, as a result, the voltage at terminal **38** is above the reference voltage at terminal **43**. The output terminal **44** of the sense amplifier **42** will be at a low voltage, which will be transmitted through an output buffer **46** to a terminal **48** and then coupled to an I/O terminal **50** as a logical “0”. If a “1” is stored in the EANVM cell **32**, the cell is in a high conductivity state and, as a result, the voltage at terminal **38** is below the reference voltage at terminal **43**. The output of the sense amplifier **42** will be a high voltage which will be transmitted to the I/O terminal **50** as a logical “1”.

For writing the value of an information bit in the cell **32**, it is assumed that the cell **32** is initially in the erased or fully “on” state, which corresponds to a logical “1”. The I/O terminal **50** is connected to the input terminal of an input latch/buffer **52**. The output of the input latch/buffer **52** is connected to an enable/disable terminal **54** of a program voltage switch **56**. The program voltage switch **56** provides a bit-line program voltage on a signal line **58** connected to terminal **38**. Another output from the program voltage switch **56** is the word line program voltage on a signal line **62**, which is connected to the control gate terminal **34** of the EANVM cell **32**. When a logical “0” is present at terminal **54** of the program voltage switch **56** from the output of input latch/buffer **52** and the program voltage switch **56** is activated by a program pulse on a signal line **64** from a program pulse generator **66**, activated by a PGM/Write (Program/Write) signal, the program voltage switch **56** provides the program voltage V_{pp} (typically 12 volts) from a terminal **68** to the control gate terminal **34** of the EANVM cell **32** via signal line **62**. The program voltage switch **56** also biases the drain of the EANVM cell **32** to a voltage somewhat less than V_{pp} , typically about 8 to 9 volts. Under these conditions, electrons are injected into the floating gate by a phenomenon known as hot electron injection. This programming procedure raises the voltage threshold of the EANVM cell, which increases its source-drain impedance. This continues until the FET memory cell **32** is effectively turned off, which corresponds to a “0” state. When a “1” is present on terminal **54** from the output of the input latch/buffer **52** and the PGM/Write signal is enabled, the signal line **58** is driven low and programming is inhibited so that the “1” or erased state is maintained.

FIG. **3** is a timing diagram showing the change in voltage threshold of the EANVM cell **32** under control of the word

line and bit line programming voltages as the memory cell is being programmed from the fully erased “1” state to the fully programmed “0” state. For simplicity, the word line and bit line programming voltages, which are controlled by the PGM/Write signal, are shown as a single pulse. For the duration of the PGM/Write pulse, the bit and word line program voltages are respectively applied to the drain of the memory cell **32** via the bit line terminal **38** and to the control gate via the control gate terminal **34** of the memory cell **32**. As electrons are injected onto the floating gate, the voltage threshold of the memory cell begins to increase. Once the voltage threshold has been increased beyond a specific threshold value indicated by the dashed horizontal line, the memory cell **32** is programmed to a “0” state.

Fowler-Nordheim tunneling can also be used instead of hot electron injection to place electrons on the floating gate. The multi-bit EANVM device described herein functions with either memory cell programming technique. The conventional programming algorithms and circuits for either type of programming are designed to program a single-bit cell with as much margin as possible in as short a time as possible. For a single-bit memory cell, margin is defined as the additional voltage threshold needed to insure that the programmed cell will retain its stored value over time.

FIG. **4** is a timing diagram showing the bit line voltage at terminal **38** as a function of time during a memory read operation. In this example, prior to time t_1 the bit line is charged to the $V_{\text{pull-up}}$ condition. Note that it is also possible that the bit line may start at any other voltage level prior to time t_1 . At time t_1 , the EANVM cell **32** is selected and, if the cell **32** is in the erased or “1” state, the cell **32** provides a low impedance path to ground. As a result, the bit line is pulled-down to near the ground potential provided at terminal **36** in FIG. **2**. If the EANVM cell **32** were in the “0” or fully programmed state, the bit line voltage would remain at the $V_{\text{pull-up}}$ voltage after time t_1 . The voltage on the bit-line terminal **38** and the reference voltage Ref at terminal **43** are compared by the sense amplifier **42**, whose buffered output drives I/O terminal **50**. When the reference voltage is greater than the bit line voltage, the output on I/O terminal **50** is a logical “1”. When the reference voltage is lower than the bit line voltage, the output on I/O terminal **50** is a logical “0”.

II. Memory Array for A Multi-Bit EANVM System

FIG. **5** is a block diagram of a multi-bit per cell EANVM system **100** in accordance with the present invention, which includes an $M \times N$ array of EANVM cells. The cells are shown as floating gate FET cells **102**, having the same construction as described in connection with FIG. **1**. The general arrangement of the system is similar to that used for conventional single-bit per cell memory devices, although on a detailed level there are significant differences related to the multi-bit per cell implementation as will be apparent later.

Each cell **102** in FIG. **5** belongs to a row and a column of the array and has its source connected to a ground reference potential and its drain connected to a corresponding column bit line **106**. The column bit lines are connected to corresponding pull-up devices indicated collectively by the block **105**. All control gates of a row of cells are connected to a corresponding row select, or word, line **104**. Rows are selected with a row select circuit **108** and columns are selected with a column select circuit **110** in the usual manner. Row and column address signals are provided over corresponding address busses **103A** and **103B**. Sense ampli-

fiers **112** are provided for each of the columns of the array. Decode/encode circuits **114** and n-bit input/output latches/buffers **116** are also provided (n=2 for a 2-bit per cell system). A PGM/Write signal is provided at an input terminal **118** for activating a mode control circuit **120** and a timing circuit **122**.

A significant advantage of this multi-bit per cell system **100** as compared to a single-bit per cell implementation is that the memory density is increased by a factor of n, where n is the number of bits which can be stored in an individual multi-bit memory cell.

III. Basic Read Mode/Circuitry For Multi-Bit Memory Cell

FIG. **6** shows a binary system **150** for reading the state of multi-bit floating gate memory cell **102**. For this example, the number of bits per cell (n) is assumed to be 2, so that one of four states of the memory cell must be detected, the four possible states being (0,0), (0,1), (1,0), and (1,1). To detect which state is programmed, a 4-level sense amplifier **152** is provided. This amplifier includes three sense amplifiers **154**, **156**, and **158**, each of which has its negative input terminal connected to the output terminal **138** of the memory cell **102**. Sense amplifier **154** has a reference voltage Ref3 connected to its positive input terminal, sense amplifier **156** has a reference voltage Ref2 connected to its positive input terminal, and sense amplifier **158** has a reference voltage Ref1 connected to its positive input terminal. These reference voltages demarcate the four memory states of the cell **102** and are set so as to satisfy the relationship $V_{pull-up} > Ref3 > Ref2 > Ref1$ (preferred techniques for generating these reference voltages will be described later). The respective output signals S3, S2, S1 of the three sense amplifiers drive an encode logic circuit **160**, which encodes the sensed signals S3, S2, S1 into an appropriate 2-bit data format. Bit 0 is provided at an I/O terminal **162**, and Bit 1 is provided at an I/O terminal **164**. A truth table for the encode logic circuit **160** is as follows:

S3	S2	S1	I/O 1	I/O 0	State
L	L	L	0	0	(0,0)
H	L	L	1	0	(1,0)
H	H	L	0	1	(0,1)
H	H	H	1	1	(1,1)

During a read operation of the multi-bit memory cell **102**, the levels of the respective output signals S3, S2, S1 of the sense amplifiers **154**, **156**, **158** are determined by the conductivity value to which the memory cell has been set during a programming operation (to be described later). When fully erased, EANVM cell **102** will be in its lowest threshold voltage state—that is, the highest conductivity state. Consequently, all of the reference voltages will be higher than the bit line voltage at terminal **138**, indicating a (1,1) state. When fully programmed, EANVM cell **102** will be in its highest threshold voltage state, that is, its lowest conductivity state. Consequently, all reference voltages will be lower than the bit line voltage at terminal **138**, indicating a (0,0) state. The intermediate threshold states are encoded as illustrated in the previous truth table for the logic circuit **160**.

FIG. **7** shows the bit line voltage at terminal **138** as a function of time during a read cycle for the memory cell **102**. For purposes of illustration, each of the four possible voltage signals corresponding to the four possible programmed states of the memory cell are shown. During a read cycle,

only the signal corresponding to the actual programmed state of the EANVM cell would occur. For example, assume the EANVM memory cell **102** has been programmed to a (1,0) state. Prior to time t1, because the EANVM cell **102** has not yet been selected or activated, the bit line **106** is pulled up to $V_{pull-up}$. At time t1, the EANVM cell is selected using standard memory address decoding techniques. Because the EANVM cell has been programmed to a specific conductivity level by the charge on the floating gate, the bit line is pulled down to a specific voltage level corresponding to the amount of current that the cell can sink at this specific conductivity level. When this point is reached at time t2, the bit line voltage stabilizes at a voltage level Vref3 between reference voltages Ref3 and Ref2 which bound the (1,0) state. When the EANVM cell **102** is de-selected, the bit line voltage will return to its pulled-up condition. Similarly, the bit-line voltage stabilizes at Vref2 for the (0,1) state or at 0 volts for the (1,1) state.

IV. Program and Read Circuitry for Multi-Bit EANVM Cell

FIG. **8** is a block diagram of circuitry **200** for programming and reading memory cell **102**. Although a binary 2-bit per cell system is shown for purposes of illustration, it is to be understood that the principles of the invention are similarly applicable to any system where the EANVM cell has more than two states. For example, in a non-binary system, the memory states can be three or some other multiple of a non-binary base.

The system **200** includes a memory cell **102** with a bit line output terminal **138**. For the read mode of operation, the 4-level sense amplifier **152**, supplied with read reference voltages Ref1, Ref2, and Ref3, and the encoder **160** are provided. Read data is provided at the Bit 0 I/O terminal **162** and at the Bit 1 I/O terminal **164**.

For the write mode of operation, a verify reference select circuit **222** provides an analog programming voltage reference level signal X to one input terminal of an analog comparator **202**. The programming reference voltages are chosen so that as soon as the bit line voltage on bit line **106** has reached the programming reference voltage level corresponding to a target memory state, the EANVM cell **102** is set to a proper threshold corresponding to the target memory state. The programming reference voltages Vref1, Vref2, Vref3, and Vref4 are set such that Vref4 is above Ref3, Vref3 is between Ref3 and Ref2, Vref2 is between Ref1 and Ref2, and Vref1 is below Ref1. During a normal read operation of either intermediate memory state, the bit line voltage will thus settle substantially midway between the read reference voltages demarcating the intermediate state to insure that the memory contents will be read accurately.

The verify reference select circuit **222** is controlled by the two output bits from a 2-bit input latch/buffer circuit **224**, which receives binary input bits from the I/O terminals **162** and **164**. The Y signal input terminal of the analog comparator **202** is connected to the bit line output terminal **138** of the multi-level memory cell **102**. The output signal from the analog comparator is provided on a signal line **204** as an enable/disable signal for a program voltage switch **220**.

An output signal line **206** from the program voltage switch **220** provides the word line program voltage to the control gate of the EANVM cell **102**. Another output signal line **106** provides the bit line programming voltage to the bit line terminal **138** of EANVM cell **102**.

After the program/verify timing circuit **208** is enabled by a PGM/Write signal provided on signal line **212** from a

PGM/Write terminal **214**, the timing circuit **208** provides a series of program/verify timing pulses to the program voltage switch **220** on a signal line **210**. The pulse widths are set to control the programming process so that the voltage threshold of the EANVM cell **102** is incrementally altered by controlling the injection of charge onto the floating gate of the EANVM cell. Each programming cycle changes the voltage threshold and, as a result, the conductivity of the memory cell **102**. After each internal program cycle is complete, as indicated by signal line **210** going "high", the program voltages provided by the program voltage switch **220** are removed, and a verify cycle begins. The voltage threshold of memory cell **102** is then determined by using the comparator **202** to compare the bit line voltage at terminal **138** with the selected programming reference voltage from the verify reference select circuit **222**. When the bit line voltage has reached the level of the programming reference voltage supplied by the verify reference select circuit **222**, the output signal from the comparator on line **204** will disable the program voltage switch **220**, ending the programming cycle.

For this embodiment of the invention, during a write operation, comparison of the current memory cell analog contents with the analog information to be programmed on the memory cell **102** is performed by the analog comparator **202**. The verify reference select circuit **222** analog output voltage X is determined by decoding the output of the 2-bit input latch/buffer **224**. The Y input signal to the analog comparator **202** is taken directly from the bit line terminal **138**. Note that the 4-level sense/encode circuits **152**, **160**, and verify reference select circuit **222** may be completely independent, as indicated in the drawing. Alternatively, they may be coupled together to alternately time share common circuit components. This is possible because the 4-level sense/encode circuits **152** and **160** are used in the read mode of operation while the verify reference select circuit **222** is used only in the write/verify mode of operation.

V. Basic Write Mode For Multi-Bit EANVM Cell

In the write mode, a binary multi-bit per cell EANVM system must be capable of electrically programming a memory cell to provide 2^n uniquely different threshold levels (n =the number of bits per cell). In the two-bit per cell implementation, if it is assumed that the cell starts from the erased (1,1) state, it is only necessary to program to three different thresholds which correspond to the three non-erased states. A first such threshold is determined so that, in the read mode, the bit line voltage will fall between Ref1 and Ref2. Another such threshold is determined so that, in the read mode, the bit line voltage will fall between Ref2 and Ref3. The third such threshold is determined so that, in the read mode, the bit line voltage will be greater than Ref3.

FIG. 9 illustrates the change in voltage threshold of a 4-level, or 2-bit, EANVM cell as the floating gate is being charged from an erased (1,1) threshold state to any one of the three other possible states (the charging being shown as continuous for simplicity). V_{t1} , V_{t2} , and V_{t3} in FIG. 9 are thresholds corresponding to the read reference levels Ref1, Ref2, and Ref3, respectively. The plots labeled (0,1), (1,0), and (0,0) correspond to the programming thresholds for those states, which are the three non-erased states. In prior art single-bit memory cells where there are only two states, the design objective is to provide enough charge to the floating gate to insure that the cell's voltage threshold is programmed as high as possible, as shown in FIG. 3. Because there is no upper threshold limit in a single-bit per cell system, overprogramming the cell will not cause incorrect data to be stored on the memory cell.

As will be appreciated from FIG. 9, in a multi-bit per cell system, the memory cell must be charged to a point so that the voltage threshold is within a specific voltage threshold range. For example, where the cell is being programmed to a (1,0) state, the proper threshold range is defined as being above a threshold level V_{t2} and as being below a threshold level V_{t3} . To accomplish this multi-level programming, the prior art EANVM circuitry is modified to the arrangement shown in FIG. 8. The comparator in FIG. 8, incidentally, is preferably analog as shown. However, a digital comparator could be used.

FIG. 10 illustrates the voltage threshold of a 4-level, or 2-bit, EANVM cell as the floating gate is being erased from a (0,0) state (the erasing being shown as continuous for simplicity). The EANVM programming operating procedure may call for a memory cell to be erased prior to being programmed. This erasure can be performed at the byte, block, or chip level and can be performed by electrical, UV, or other means. In this type of system, the cell would be completely erased to a (1,1) state prior to initiating a programming cycle. If a system has the capability to erase an individual memory cell, then it is not necessary to erase all of the cells of a group prior to initiating a programming operation. It is then possible to incrementally erase an individual memory cell as necessary to program the cell to the appropriate one of the voltage thresholds indicated by the plots labeled (1,0), (0,1), and (1,1).

FIG. 11 is a voltage threshold timing diagram which illustrates how the system of FIG. 8 programs the 2-bit EANVM cell **102** from an erased (1,1) state to a (1,0) state using the timing circuitry **208** to generate fixed-width timing pulses. A low logic level state of the PGM/Write signal on signal line **212** enables the timing circuit **208**. After being enabled at time t_1 , the timing circuit **208** provides an internal fixed-width low-level internal PGM timing pulse on signal line **210** to the program voltage switch **220**. This pulse is output following an initial verify cycle which will be discussed in connection with FIG. 12. For the duration of the low state of the internal PGM timing pulse, the bit line and word line program voltage outputs on lines **106** and **206** will be raised to their respective programming voltage levels as indicated in FIG. 11. During this programming process, charge is added to the floating gate of the memory cell **102**. When the internal PGM timing pulse from timing circuitry **208** switches to a high level, the programming voltages are removed and a verify cycle begins. For this example, verify reference voltage V_{ref3} is compared with the bit line voltage. This internally controlled program/verify cycle repeats itself until the bit line voltage on terminal **138** has reached V_{ref3} . At this time, t_2 , the EANVM cell **102** is verified to have been programmed to a (1,0) state, and programming is halted by the comparator **222** providing a disable signal on signal line **204** to the program voltage switch **220**.

FIG. 12 illustrates the bit line voltage of the 2-bit EANVM cell **102** as it is being programmed from the fully erased, or fully "on", state (1,1) to the partially "off" state (1,0) using fixed-width program pulses. When the externally applied PGM/Write pulse is applied at time t_1 , the program/verify timing circuit **208** first initiates a verify cycle to determine the current status of the memory cell **102**. This is indicated by the bit line voltage being pulled to a ground condition (corresponding to the erased state) from, in this example, $V_{pull-up}$, although prior to time t_1 , the bit line voltage could be pre-set to any voltage level. Once the cell has been determined to be in the erased state, the first program cycle is initiated. This is represented by the bit line voltage being pulled up to $V_{program}$. After the first fixed-

width programming pulse ends, a verify cycle begins. This is represented by the bit line voltage being pulled down to a point midway between ground potential and Ref1. During each successive verify cycle, the bit line voltage is observed to incrementally increase. This program/verify cycle continues until the bit line voltage has reached the selected programming reference voltage, in this case Vref3, which indicates a memory state of (1,0), at time t2.

FIG. 13 illustrates how the 2-bit EANVM cell 102 is programmed from the erased (1,1) state to the (1,0) state using a timing circuit 208 that generates variable-width programming pulses. The internal PGM pulses for this implementation start with a low state longer than for the fixed-width implementation of FIGS. 11 and 12. The low state pulse widths grow progressively shorter as the memory cell approaches the target voltage threshold. This approach requires more precise control than the fixed-width approach. However, programming times can be greatly reduced on average.

FIG. 14 illustrates the bit line voltage of cell 102 as it is being programmed from the fully erased, or fully "on", state (1,1) to the partially "off" state (1,0) using variable length program pulses. When the externally applied PGM/Write pulse goes to an active low level at time t1, the program/verify timing circuit 208 first initiates a verify cycle to determine the current status of the memory cell 102. This is indicated by the bit line voltage being pulled to a ground condition (corresponding to the erased state) from, in this example, Vpull-up, although prior to time t1, the bit line voltage could be preset to any voltage level. Once the cell has been determined to be in the erased state, the first program cycle is initiated. This is represented by the bit line voltage being pulled up to Vprogram. After the first variable length programming pulse is over, another verify cycle begins. This is represented by the bit line voltage being pulled down to a point midway between Ref1 and Ref2. During each successive verify cycle, the bit line voltage is observed to have increased. This program/verify cycle continues until the bit line voltage has reached the selected programming reference voltage, in this case Vref3, which indicates a memory state of (1,0), at time t2.

As explained above, the programming process for the multi-bit per cell EANVM uses program/verify cycles, to incrementally program the cell. The durations of these cycles are determined by the timing circuit 208. A key element of the system is to provide a programming scheme which provides for accurate programming of the memory cell 102. This is accomplished by matching the pulse widths of the timing pulses of the timing circuitry 208 to the program time of the EANVM cell being used. As seen from FIGS. 11 and 13, a desired voltage threshold actually falls within a range of threshold voltages. If the program pulses are too long, then too much charge may be added to the floating gate of the memory cell 102. This may result in an overshoot of the target voltage threshold, resulting in incorrect data being stored in the memory cell.

The programming pulse width is set such that if the voltage threshold of the cell 102 after the (N-1)th programming pulse is at a point just below the target voltage threshold, then the (N)th, or final, program pulse will not cause an overshoot resulting in an over programmed condition for a memory cell.

VI. Embodiments to Establish Reference Voltages for Programming and Memory State Demarcation

The program and read circuitry in FIG. 8 uses selectable programming reference voltage signals supplied to a bit line

comparator to control programming of the multi-bit memory cell. Programming is accomplished without reading out the cell. This allows for a significant reduction in programming time relative to previous systems that require repeated readout of the memory state of the cell during the programming process.

The following discussion addresses preferred modes of reference signal generation in accordance with the present invention. In principle, the system of FIG. 8 is not limited as to the manner in which the programming and read reference signals are established. The embodiments described in this section, however, implement important new concepts in memory state demarcation and programming control to enhance the reliability of the system.

The embodiments for memory state demarcation are based on a new concept whereby the read reference signals are generated using the programming reference signals, or signals set in substantial correspondence with the programming reference signals. The read reference signals are thus effectively dependent upon the programming reference signals. Because of this dependence, the system design can guarantee that the two sets of signals will closely conform with a predetermined relationship for program margining. For example, as will be seen in the illustrative embodiments, the programming reference voltages of two adjacent memory states may be subjected to voltage division to generate the intervening read reference voltage. The read reference voltage will then fall midway between the two programming reference voltages. As a result, the two programming reference voltages are equally marginate from the read reference voltage.

The embodiments related to programming control particularly address programming reference voltage generation. These embodiments employ reference cells which substantially track changes in operating characteristics of the memory cell (and thus its bit line signal) with changing conditions that affect the operating characteristics, such as temperature, system voltages, or mere passage of time. The use of such reference cells, which preferably have the same (or at least in large part the same) construction as the memory cell, assures a stable relationship between the programming reference voltages and the operating characteristics of the memory cell.

When the reference cells for program voltage generation are used to generate the read reference voltages as well, the read reference voltages will also closely track the changes in operating characteristics of the memory cell. This assures that data stored in the memory cell over a long period of time can be read out accurately. An alternative to using the programming reference cells for this purpose is to use a separate group of reference cells to generate voltages substantially the same as the programming reference voltages. Using the voltages from the separate group of cells to generate the read reference voltages would provide a similar tracking effect of the read reference voltages.

FIG. 15 is a simplified diagram illustrating a circuit for generating the read reference voltages Ref1, Ref2, and Ref3. In the form shown, the read reference voltages are generated by corresponding columns 1210, 1211, and 1212 of the circuit, each comprising a pair of reference cells connected in a voltage divider arrangement to generate the corresponding read reference signal. Column 1210 includes a first pair of reference cells 1203, 1204 for generating voltage Ref1. Column 1211 includes a second pair of reference cells 1205, 1206 for generating voltage Ref2. Column 1212 includes a third pair of reference cells 1207, 1208 for generating

voltage Ref3. Also shown in FIG. 15 is a bit line column 1209. The bit line column constitutes a portion of the main memory cell array and includes a memory cell 1202.

In order that the read reference voltages will precisely track changes in the memory cell bit line signal with changing conditions that affect the operating characteristics of the memory cells in the main array, reference cells 1203–1208 of the reference voltage generating circuit may, in one preferred mode, be of the same type and construction as their associated memory cells (e.g., cell 1202) of the main array. Thus, all of the cells 1202–1208 in FIG. 15 are assumed to be floating-gate-FET EANVM cells as previously described, all having the same construction. The reference cells, and indeed the reference columns, are preferably fabricated simultaneously with and by the same method as the columns of the main array, as part of the same integrated circuit with the array. Alternatively, the reference columns may be fabricated by way of the same method as the main memory cell array, but at a different time and/or as parts of a different integrated circuit.

Each of the reference cells 1203–1208 in FIG. 15 shares a common word (row select) line 1243 with the memory cell 1202. Each reference cell is also coupled, at its bit line, to a column pull-up voltage Vpull-up and the associated column output terminal via associated select transistors (FETS) 1201 and 1213, which may be NMOS or PMOS devices, for example. The select transistors 1201 are controlled via respective select lines 1214', and the select transistors 1213 are controlled via respective select lines 1215'. The bit lines of each pair of reference cells are connected together, as shown, to form the respective voltage divider arrangements. The memory cell 1202 is also coupled to a column pull-up voltage and the associated column bit line output via a pair of select transistors 1201, 1213 controlled respectively by select lines 1214, 1215.

The reference cells 1203–1208 are pre-programmed at the factory to voltage thresholds corresponding to the programming reference voltages Vref1–Vref4. Specifically, reference cells 1203 and 1204 are programmed respectively to voltage thresholds V1 and V2 to produce voltages equal to programming reference voltages Vref1 and Vref2 on their respective bit lines. Reference cells 1205 and 1206 are respectively programmed to voltage thresholds V2 and V3 to produce voltages equal to programming reference voltages Vref2 and Vref3. Reference cells 1207 and 1208 are respectively programmed to voltage thresholds V3 and V4 to produce voltages equal to programming references Vref3 and Vref4. The programming of the reference cells may be accomplished in any suitable manner. For example, the memory device may be provided with dedicated pins for external application of standard reference voltages to charge the cells. As another alternative, the memory device may incorporate an on-board set of ROM cells having implant dosages for providing bit line voltages corresponding to the desired programming reference voltages. The ROM bit line voltages would be used as programming reference voltages for initially programming the EANVM reference cells. The EANVM reference cells could be selectively coupled to the program verification comparator 202 (FIG. 8) to provide signal Y, and the ROM bit line voltages could be selectively applied to the comparator as signal X to program the EANVM reference cells by a programming operation as previously described. By using programming pulses of small width(s), the reference cells would be programmed with good accuracy. The ROM cells could also be used to reprogram the EANVM reference cells (under predetermined standard conditions) to restore the voltage thresholds of the reference cells to design values, if necessary.

By setting the successive programming reference voltages Vref1–Vref4 at equal intervals and correspondingly programming the voltage thresholds of the reference cells, the reference signal generating circuit shown in FIG. 15 establishes relationships between the programming reference voltages and the read reference voltages as shown in FIG. 16. It should be noted that the assignment of particular memory states to the programming reference voltages Vref1–Vref4 is not a critical matter, although good design practice dictates that the assignments should be consistent throughout the memory system. In a system employing error correction, it may be advantageous to assign the memory states out of binary sequence to facilitate optimization of error detection and correction algorithms. The present discussion assumes assignment of the memory states to the programming reference voltages in a non-binary sequence. Specifically, memory state (1,1) is assigned to the first (lowest) programming reference voltage Vref1, memory state (0,1) is assigned to the second programming reference voltage Vref2, memory state (1,0) is assigned to the third programming reference voltage Vref3, and memory state (0,0) is assigned to the fourth (highest) programming reference voltage Vref4.

As shown in FIG. 16, each read reference voltage is established so that the programming reference voltages for the memory states immediately above and below are equally margined relative to the read reference voltage. More particularly, the read reference voltages are defined as follows:

$$\text{Ref1}=(\text{Vref1}+\text{Vref2})/2$$

$$\text{Ref2}=(\text{Vref2}+\text{Vref3})/2$$

$$\text{Ref3}=(\text{Vref3}+\text{Vref4})/2$$

By virtue of the foregoing relationships, each read reference level will always be optimally margined relative to the adjacent programming reference levels at a position midway between the programming reference levels. Furthermore, because the operating characteristics of the reference cells track variations in the operating characteristics of the memory cell with changing conditions that affect the operating characteristics, the relationships shown in FIG. 16 are maintained throughout such variations. This ensures that data stored in the memory cell over a long period of time can be read out accurately despite differences in temperature, system voltages, etc. at the time of readout relative to the time of data storage. The curve shown in FIG. 16 indicates the bit line voltage of the memory cell during readout, assuming the cell is programmed to programming reference voltage Vref1.

In a practical application, it is possible that the voltages appearing at the outputs of the reference voltage columns 1210, 1211, 1212 will deviate slightly from the design values. Deviations may occur, for example, due to asymmetries in the physical arrangement of the circuit components, which are ordinarily laid out to maximize the compactness of the integrated circuit. Such asymmetries may result in differing line lengths and capacitance effects, for example, relative to the individual reference cells of a given pair. The deviations can be determined in advance by computer simulation of the circuit using standard computer simulation techniques. It is then possible to compensate for the deviations by adding appropriate signal pulling devices on the read reference lines to pull the divided outputs of the reference cells to the design values. Such devices may also be provided for similar reasons on the memory cell bit lines of the main array.

FIG. 17 shows a read-reference signal generating circuit as just described. The circuit is identical to that of FIG. 15,

except for the addition of the aforementioned signal pulling devices. These devices may be constituted by field effect transistors **1220–1223**, as shown, or by any other suitable type of device for this purpose, such as capacitor and resistor combinations, etc. The signal pulling devices are preferably connected as closely as possible to the points where the read reference signals (and memory bit line signals) feed into the multi-level sense amplifier for reading out the memory cell. Such an arrangement will optimize the accuracy of the voltage values supplied to the sense amplifier relative to the design values. This is, of course, desirable from the standpoint of high accuracy program margining and memory readout.

FIG. **18** is a simplified diagram showing another embodiment of a circuit **1200** for generating the read reference signals Ref1, Ref2, and Ref3. This circuit is based on the design of the circuit in FIG. **17**, but the higher-value reference cell and signal puller of each reference column are replaced by a corresponding single pull-up device **1321**, **1322**, or **1323** to provide the voltage divider arrangements, as shown. The pull-up devices on the individual read reference lines in FIG. **18** have their respective signal-pulling capacities set so that the read reference voltages will assume the same relationships relative to the programming reference voltages as shown in FIG. **16**. It should be noted that this embodiment is less preferred than the arrangement of FIG. **17** from the standpoint of tracking the memory cell, since the pull-up devices **1321**, **1322**, and **1323** on the read reference lines will not track the memory cell **1202** as closely as the reference cells with changing operating conditions.

FIG. **19** is a more generalized diagram illustrating how the reference signal generating circuit of FIG. **15** can be applied to a memory array. For convenience in FIG. **19**, the select line **1214** and select transistors **1201**, which are not required but may be desirable to reduce energy consumption, for example, have been replaced by a generic network of column pull-ups (so designated).

As shown in FIG. **19**, each row of memory cells in the array is provided with a corresponding set of reference cells **1203–1208** connected to form voltage divider arrangements as previously described. Each set (row) of reference cells would be selected individually for providing signals on the reference column bit lines for readout of a memory cell of the corresponding row of the main array. Although it is consistent with the principles of the present invention to use a single set of reference cells for all of the memory cells of the array (in which case the reference cells need not share the word line of any row of the array), the use of dedicated sets of reference cells for each row of the array is preferred for accuracy. More particularly, the use of dedicated reference cells allows for better symmetry in the arrangement of each set of reference cells relative to that of the corresponding row of memory cells within the overall memory circuit. For example, a reference cell for row M of the memory array in FIG. **20** will have the same number and type of components connected between its bit line terminal and the reference column output as does each corresponding memory cell **1202** between its bit line terminal and the column bit line output. Also, the line length from the bit line terminal of the reference cell to the reference column output can be made close to or the same as the line length from the bit line terminal of each corresponding memory cell to its associated column bit line output. Signal pulling devices may be added on the bit and read reference lines in a manner similar to FIG. **17**. In this case, the signal pulling capacity of each device would be determined by suitable calculation during the computer simulation process to provide the best overall accuracy of

the signal levels provided by the different cells within each column of the system.

FIG. **20** is a simplified diagram showing a circuit **1500** (above the dashed line) for generating programming references Vref1–Vref4 and an associated verify reference select circuit **222** (below the dashed line) for outputting the selected signal X for program verification. As shown in FIG. **20**, each row of the memory array is coupled with a set of reference cells **1503–1506** having the same construction as the memory cells. The reference cells need not be part of the same integrated circuit as the memory array, but they are preferably fabricated simultaneously with and by the same process as the array, as part of the same integrated circuit, for the reasons previously explained. The use of a dedicated set of programming reference cells for each row of the array is preferable for the same reasons as were discussed in connection with the arrangement of FIG. **20**. The reference cells for producing the programming reference signals Vref1–Vref4 are arranged in corresponding columns **1511–1514**, with their bit line terminals commonly connected to a corresponding bit line and a network of column pull-ups (so designated). Each set (row) of reference cells would be individually selected, via an associated word line **1543**, for providing signals on the corresponding column bit lines for programming verification of a memory cell of the corresponding row of the main memory array.

Each reference cell **1503** in column **1511** is pre-programmed at the factory (for example, as previously described in connection with FIG. **15**) to the voltage threshold **V1** to produce voltage Vref1 on the column bit line. Each reference cell **1504** in column **1512** is pre-programmed to the voltage threshold **V2** to produce voltage Vref2 on the column bit line. Each reference cell in column **1513** is pre-programmed to the voltage threshold **V3** to produce voltage Vref3 on the column bit line. Each reference cell in column **1514** is pre-programmed to the voltage threshold **V4** to produce voltage Vref4 on the column bit line. Signal pulling devices may be added on the column bit lines as previously explained if necessary to compensate for deviations of the column bit line voltages due to effects of layout asymmetries and the like.

The bit lines of columns **1511–1514** are coupled to corresponding select transistors (e.g., FETs) **271–274** of verify reference select circuit **222**. The select transistors, which may be NMOS or PMOS devices, for example, can be controlled by a simple logic circuit, such as the logic circuit LC shown in FIG. **20**. The circuit LC in FIG. **20** operates in accordance with the following truth table. Note that the signals I/O0 and I/O1 are provided as inputs from the input latch/buffer **224** (see FIG. **8**).

I/O0	I/O1	Vref1 Select	Vref2 Select	Vref3 Select	Vref4 Select
0	0	L	L	L	H
1	0	L	L	H	L
0	1	L	H	L	L
1	1	H	L	L	L

FIGS. **21A–21D** are readout timing diagrams showing the bit line voltage level of a selected memory cell in FIG. **20** after programming to each of the four memory states. In each diagram, at time t0, the bit line voltage is at its pre-charged value of Vpull-up, which is at or very near the value of Vref4. At time t1, the voltage level has dropped to the range indicated by the two closely spaced lines which are centered around the Vref level for the programmed state. The two lines indicate that there is a slight range of tolerance for

the bit line voltage level relative to the programming voltage reference level during read out of the memory cell. FIG. 21A illustrates the bit line voltage when the memory cell has been programmed to the voltage threshold V_1 corresponding to the programming reference level V_{ref1} . FIG. 21B illustrates the bit line voltage when the memory cell has been programmed to the voltage threshold V_2 corresponding to the programming reference level V_{ref2} . FIG. 21C illustrates the bit line voltage when the memory cell has been programmed to the voltage threshold V_3 corresponding to the programming reference level V_{ref3} . FIG. 21D illustrates the bit line voltage when the memory cell has been programmed to the voltage threshold V_4 corresponding to the programming reference level V_{ref4} .

While the read reference and programming reference generating circuits have been shown and described as separate circuits above, the circuits may readily be combined to share components as shown in FIG. 22. This is possible because the programming reference signals and the read reference signals need not be used at the same time. More particularly, the programming reference signals need only be used during the memory cell programming operation, whereas the read reference signals need only be used during the memory cell readout operation.

The circuit shown in FIG. 22 is a modification of the circuit of FIG. 19. In the circuit of FIG. 22, the bit line of reference cells 1203 is connected to provide programming reference voltage V_{ref1} , the bit line of reference cells 1204 is connected to provide programming reference voltage V_{ref2} , the bit line of reference cells 1207 is connected to provide programming reference voltage V_{ref3} , and the bit line of reference cells 1208 is connected to provide programming reference voltage V_{ref4} . Select transistors 271–274 correspond to the select transistors shown in FIG. 20.

FIG. 23 shows a modification of the circuit in FIG. 22, in which the EANVM reference cells 1203–1208 are replaced by ROM cells 2203–2208, respectively. The use of ROM cells as reference cells is advantageous because it avoids the initial programming requirement of EANVM reference cells, although the tracking effect of the reference signals relative to the EANVM cells of the main array may be reduced somewhat. To maximize the tracking effect, corresponding portions of the ROM cells and the EANVM cells can be fabricated by the same process steps. For example, the sources, drains, channel regions, and control gates of the EANVM cells and the ROM cells may be fabricated in this manner, with separate process steps being used to provide the EANVM floating gates and the ROM threshold implants.

As previously stated, the illustrative embodiments described herein are merely exemplary, and numerous changes and modifications can be made consistent with the principles of the invention. For example, although the invention has been explained in terms of voltage-based memory systems which utilize voltage signals from the memory and reference cells, the principles of the invention are equally applicable to current-based memory systems in which current levels rather than voltage levels are utilized.

The invention claimed:

1. For an electrically alterable non-volatile multi-level memory device including a plurality of non-volatile multi-level memory cells, each of the multi-level memory cells including a floating gate FET having a channel with electrically alterable voltage threshold value, the plurality of non-volatile multi-level memory cells being disposed in a matrix of rows and columns, channels of multi-level memory cells of a first group of the plurality of non-volatile

multi-level memory cells being coupled in parallel between a first bit line and a reference potential, channels of multi-level memory cells of a second group of the plurality of non-volatile multi-level memory cells being coupled in parallel between a second bit line and the reference potential, electrons being capable of being injected into the floating gate by a phenomenon of hot electron injection from the channel of each of the plurality of non-volatile multi-level memory cell, electric currents flowing through the channels of the multi-level memory cells of the first group and electric currents flowing through the channels of the multi-level memory cells of the second group being substantially flowing in a same direction, a method of operating the electrically alterable non-volatile multi-level memory device, comprising:

settling a parameter of at least one non-volatile multi-level memory cell of the plurality of non-volatile multi-level memory cells to one state selected from a plurality of states including at least a first state, a second state, a third state and a fourth state in response to information to be stored in the one non-volatile multi-level memory cell,

verifying whether the parameter of the one non-volatile multi-level memory cell has being settled to the one state selected from the plurality of states by comparing the parameter of the one non-volatile multi-level memory cell with a plurality of verifying reference parameters including at least a first verifying reference parameter, a second verifying reference parameter, a third verifying reference parameter and a fourth verifying reference parameter, and of repeating the operation for settling the parameter and the operation for verifying until it is verified by the operation for verifying that the parameter of the one non-volatile multi-level memory cell has being settled to the one state,

reading status of the one non-volatile multi-level memory cell by comparing the parameter with a plurality of reading reference parameters including at least a first reading reference parameter, a second reading reference parameter and a third reading reference parameter, wherein a conductivity value of the one non-volatile multi-level memory cell is decreased in order of the first state, the second state, the third state and the fourth state,

wherein the first reading reference parameter is allocated between the first state and the second state, the second reading reference parameter is allocated between the second state and the third state, and the third reading reference parameter is allocated between the third state and the fourth state,

wherein the first reading reference parameter, the second reading reference parameter and the third reading reference parameter are parameters for a normal read operation in which the information stored in the one non-volatile multi-level memory cell can be read out by output data of a plurality of bits,

wherein the normal read operation is carried out by parallel-comparing the parameter with the plurality of reading reference parameters by using a plurality of sense circuits including at least a first sense circuit, a second sense circuit and a third sense circuit, first input terminals of the first sense circuit, the second sense circuit and the third sense circuit are commonly supplied with the parameter from the one non-volatile multi-level memory cell, a second input terminal of the first sense circuit is supplied with the first reading

reference parameter, a second input terminal of the second sense circuit is supplied with the second reading reference parameter and a second input terminal of the third sense circuit is supplied with the third reading reference parameter, and

wherein the first verifying reference parameter is allocated below the first reading reference parameter, the second verifying reference parameter is allocated between the first reading reference parameter and the second reading reference parameter, the third verifying reference parameter is allocated between the second reading reference parameter and the third reading reference parameter and the fourth verifying reference parameter is allocated above the third reading reference parameter.

2. The method of operating the electrically alterable non-volatile multi-level memory according to claim 1, wherein the operation for settling the parameter includes an erasure operation in which non-volatile multi-level memory cells of one of a byte, a block and a chip level can be erased.

3. The method of operating the electrically alterable non-volatile multi-level memory according to claim 2, wherein the operation for settling the parameter includes a program operation in which electrons are injected into a floating gate of the one non-volatile multi-level memory cell.

4. For an electrically alterable non-volatile multi-level memory device including a plurality of non-volatile multi-level memory cells, each of the multi-level memory cells including a floating gate FET having a channel with electrically alterable voltage threshold value, the plurality of non-volatile multi-level memory cells being disposed in a matrix of rows and columns, channels of multi-level memory cells of a first group of the plurality of non-volatile multi-level memory cells being coupled in parallel between a first bit line and a reference potential, channels of multi-level memory cells of a second group of the plurality of non-volatile multi-level memory cells being coupled in parallel between a second bit line and the reference potential, electrons being capable of being injected into the floating gate by a phenomenon of hot electron injection from the channel of each of the plurality of non-volatile multi-level memory cell, electric currents flowing through the channels of the multi-level memory cells of the first group and electric currents flowing through the channels of the multi-level memory cells of the second group being substantially flowing in a same direction, a method of operating the electrically alterable non-volatile multi-level memory device, comprising:

controlling an electrical value of at least one non-volatile multi-level memory cell of the plurality of non-volatile multi-level memory cells to one state selected from a plurality of states including at least a first state, a second state, a third state and a fourth state in response to information to be stored in the one non-volatile multi-level memory cell,

verifying whether the electrical value of the one non-volatile multi-level memory cell has being controlled to the one state selected from the plurality of states by comparing the electrical value of the one non-volatile multi-level memory cell with a plurality of verifying reference electrical values including at least a first verifying reference electrical value, a second verifying reference electrical value, a third verifying reference electrical value and a fourth verifying reference electrical value, and of repeating the operation for controlling the electrical value and the operation for verifying

until it is verified by the operation for verifying that the electrical value of the one non-volatile multi-level memory cell has being controlled to the one state,

reading status of the one non-volatile multi-level memory cell by comparing the electrical value with a plurality of reading reference electrical values including at least a first reading reference electrical value, a second reading reference electrical value and a third reading reference electrical value,

wherein a conductivity value of the one non-volatile multi-level memory cell is decreased in order of the first state, the second state, the third state and the fourth state,

wherein the first reading reference electrical value is allocated between the first state and the second state, the second reading reference electrical value is allocated between the second state and the third state, and the third reading reference electrical value is allocated between the third state and the fourth state,

wherein the first reading reference electrical value, the second reading reference electrical value and the third reading reference electrical value are electrical values for a normal read operation in which the information stored in the one non-volatile multi-level memory cell can be read out by output data of a plurality of bits,

wherein the normal read operation is carried out by parallel-comparing the electrical value with the plurality of reading reference electrical values by using a plurality of sense circuits including at least a first sense circuit, a second sense circuit and a third sense circuit, first input terminals of the first sense circuit, the second sense circuit and the third sense circuit are commonly supplied with the electrical value from the one non-volatile multi-level memory cell, a second input terminal of the first sense circuit is supplied with the first reading reference electrical value, a second input terminal of the second sense circuit is supplied with the second reading reference electrical value and a second input terminal of the third sense circuit is supplied with the third reading reference electrical value, and

wherein the first verifying reference electrical value is allocated below the first reading reference electrical value, the second verifying reference electrical value is allocated between the first reading reference electrical value and the second reading reference electrical value, the third verifying reference electrical value is allocated between the second reading reference electrical value and the third reading reference electrical value and the fourth verifying reference electrical value is allocated above the third reading reference electrical value.

5. The method of operating the electrically alterable non-volatile multi-level memory according to claim 4, wherein the operation for controlling the electrical value includes an erasure operation in which non-volatile multi-level memory cells of one of a byte, a block and a chip level can be erased.

6. The method of operating the electrically alterable non-volatile multi-level memory according to claim 5, wherein the operation for controlling the electrical value includes a program operation in which electrons are injected into a floating gate of the one non-volatile multi-level memory cell.

7. For an electrically alterable non-volatile multi-level memory device including a plurality of non-volatile multi-level memory cells, each of the multi-level memory cells including a floating gate FET having a channel with elec-

trically alterable voltage threshold value, the plurality of non-volatile multi-level memory cells being disposed in a matrix of rows and columns, channels of multi-level memory cells of a first group of the plurality of non-volatile multi-level memory cells being coupled in parallel between a first bit line and a reference potential, channels of multi-level memory cells of a second group of the plurality of non-volatile multi-level memory cells being coupled in parallel between a second bit line and the reference potential, electrons being capable of being injected into the floating gate by a phenomenon of Fowler-Nordheim tunneling from the channel from the channel of each of the plurality of non-volatile multi-level memory cell, electric currents flowing through the channels of the multi-level memory cells of the first group and electric currents flowing through the channels of the multi-level memory cells of the second group being substantially flowing in a same direction, a method of operating the electrically alterable non-volatile multi-level memory device, comprising:

settling a parameter of at least one non-volatile multi-level memory cell of the plurality of non-volatile multi-level memory cells to one state selected from a plurality of states including at least a first state, a second state, a third state and a fourth state in response to information to be stored in the one non-volatile multi-level memory cell,

verifying whether the parameter of the one non-volatile multi-level memory cell has being settled to the one state selected from the plurality of states by comparing the parameter of the one non-volatile multi-level memory cell with a plurality of verifying reference parameters including at least a first verifying reference parameter, a second verifying reference parameter, a third verifying reference parameter and a fourth verifying reference parameter, and of repeating the operation for settling the parameter and the operation for verifying until it is verified by the operation for verifying that the parameter of the one non-volatile multi-level memory cell has being settled to the one state,

reading status of the one non-volatile multi-level memory cell by comparing the parameter with a plurality of reading reference parameters including at least a first reading reference parameter, a second reading reference parameter and a third reading reference parameter, wherein a conductivity value of the one non-volatile multi-level memory cell is decreased in order of the first state, the second state, the third state and the fourth state,

wherein the first reading reference parameter is allocated between the first state and the second state, the second reading reference parameter is allocated between the second state and the third state, and the third reading reference parameter is allocated between the third state and the fourth state,

wherein the first reading reference parameter, the second reading reference parameter and the third reading reference parameter are parameters for a normal read operation in which the information stored in the one non-volatile multi-level memory cell can be read out by output data of a plurality of bits,

wherein the normal read operation is carried out by parallel-comparing the parameter with the plurality of reading reference parameters by using a plurality of sense circuits including at least a first sense circuit, a second sense circuit and a third sense circuit, first input terminals of the first sense circuit, the second sense

circuit and the third sense circuit are commonly supplied with the parameter from the one non-volatile multi-level memory cell, a second input terminal of the first sense circuit is supplied with the first reading reference parameter, a second input terminal of the second sense circuit is supplied with the second reading reference parameter and a second input terminal of the third sense circuit is supplied with the third reading reference parameter, and

wherein the first verifying reference parameter is allocated below the first reading reference parameter, the second verifying reference parameter is allocated between the first reading reference parameter and the second reading reference parameter, the third verifying reference parameter is allocated between the second reading reference parameter and the third reading reference parameter and the fourth verifying reference parameter is allocated above the third reading reference parameter.

8. The method of operating the electrically alterable non-volatile multi-level memory according to claim 7, wherein the operation for settling the parameter includes an erasure operation in which non-volatile multi-level memory cells of one of a byte, a block and a chip level can be erased.

9. The method of operating the electrically alterable non-volatile multi-level memory according to claim 8, wherein the operation for settling the parameter includes a program operation in which electrons are injected into a floating gate of the one non-volatile multi-level memory cell.

10. For an electrically alterable non-volatile multi-level memory device including a plurality of non-volatile multi-level memory cells, each of the multi-level memory cells including a floating gate FET having a channel with electrically alterable voltage threshold value, the plurality of non-volatile multi-level memory cells being disposed in a matrix of rows and columns, channels of multi-level memory cells of a first group of the plurality of non-volatile multi-level memory cells being coupled in parallel between a first bit line and a reference potential, channels of multi-level memory cells of a second group of the plurality of non-volatile multi-level memory cells being coupled in parallel between a second bit line and the reference potential, electrons being capable of being injected into the floating gate by a phenomenon of Fowler-Nordheim tunneling from the channel from the channel of each of the plurality of non-volatile multi-level memory cell, electric currents flowing through the channels of the multi-level memory cells of the first group and electric currents flowing through the channels of the multi-level memory cells of the second group being substantially flowing in a same direction, a method of operating the electrically alterable non-volatile multi-level memory device, comprising:

controlling an electrical value of at least one non-volatile multi-level memory cell of the plurality of non-volatile multi-level memory cells to one state selected from a plurality of states including at least a first state, a second state, a third state and a fourth state in response to information to be stored in the one non-volatile multi-level memory cell,

verifying whether the electrical value of the one non-volatile multi-level memory cell has being controlled to the one state selected from the plurality of states by comparing the electrical value of the one non-volatile multi-level memory cell with a plurality of verifying reference electrical values including at least a first verifying reference electrical value, a second verifying

reference electrical value, a third verifying reference electrical value and a fourth verifying reference electrical value, and of repeating the operation for controlling the electrical value and the operation for verifying until it is verified by the operation for verifying that the electrical value of the one non-volatile multi-level memory cell has being controlled to the one state,

reading status of the one non-volatile multi-level memory cell by comparing the electrical value with a plurality of reading reference electrical values including at least a first reading reference electrical value, a second reading reference electrical value and a third reading reference electrical value,

wherein a conductivity value of the one non-volatile multi-level memory cell is decreased in order of the first state, the second state, the third state and the fourth state,

wherein the first reading reference electrical value is allocated between the first state and the second state, the second reading reference electrical value is allocated between the second state and the third state, and the third reading reference electrical value is allocated between the third state and the fourth state,

wherein the first reading reference electrical value, the second reading reference electrical value and the third reading reference electrical value are electrical values for a normal read operation in which the information stored in the one non-volatile multi-level memory cell can be read out by output data of a plurality of bits,

wherein the normal read operation is carried out by parallel-comparing the electrical value with the plurality of reading reference electrical values by using a plurality of sense circuits including at least a first sense circuit, a second sense circuit and a third sense circuit, first input terminals of the first sense circuit, the second sense circuit and the third sense circuit are commonly supplied with the electrical value from the one non-volatile multi-level memory cell, a second input terminal of the first sense circuit is supplied with the first reading reference electrical value, a second input terminal of the second sense circuit is supplied with the second reading reference electrical value and a second input terminal of the third sense circuit is supplied with the third reading reference electrical value, and

wherein the first verifying reference electrical value is allocated below the first reading reference electrical value, the second verifying reference electrical value is allocated between the first reading reference electrical value and the second reading reference electrical value, the third verifying reference electrical value is allocated between the second reading reference electrical value and the third reading reference electrical value and the fourth verifying reference electrical value is allocated above the third reading reference electrical value.

11. The method of operating the electrically alterable non-volatile multi-level memory according to claim **10**, wherein the operation for controlling the electrical value includes an erasure operation in which non-volatile multi-level memory cells of one of a byte, a block and a chip level can be erased.

12. The method of operating the electrically alterable non-volatile multi-level memory according to claim **11**, wherein the operation for controlling the electrical value includes a program operation in which electrons are injected into a floating gate of the one non-volatile multi-level memory cell.

13. An electrically alterable non-volatile multi-level memory device including a plurality of non-volatile multi-level memory cells, each of the multi-level memory cells including a floating gate FET having a channel with electrically alterable voltage threshold value, the plurality of non-volatile multi-level memory cells being disposed in a matrix of rows and columns, channels of multi-level memory cells of a first group of the plurality of non-volatile multi-level memory cells being coupled in parallel between a first bit line and a reference potential, channels of multi-level memory cells of a second group of the plurality of non-volatile multi-level memory cells being coupled in parallel between a second bit line and the reference potential, electrons being capable of being injected into the floating gate by a phenomenon of hot electron injection from the channel of each of the plurality of non-volatile multi-level memory cell, electric currents flowing through the channels of the multi-level memory cells of the first group and electric currents flowing through the channels of the multi-level memory cells of the second group being substantially flowing in a same direction:

wherein an operation for settling a parameter of at least one non-volatile multi-level memory cell of the plurality of non-volatile multi-level memory cells to one state selected from a plurality of states including at least a first state, a second state, a third state and a fourth state is carried out in response to information to be stored in the one non-volatile multi-level memory cell,

wherein an operation of verifying whether the parameter of the one non-volatile multi-level memory cell has being settled to the one state selected from the plurality of states is carried out by comparing the parameter of the one non-volatile multi-level memory cell with a plurality of verifying reference parameters including at least a first verifying reference parameter, a second verifying reference parameter, a third verifying reference parameter and a fourth verifying reference parameter is carried out, and repeating the operation for settling the parameter and the operation for verifying are carried out until it is verified by the operation for verifying that the parameter of the one non-volatile multi-level memory cell has being settled to the one state,

wherein an operation of reading status of the one non-volatile multi-level memory cell is carried out by comparing the parameter with a plurality of reading reference parameters including at least a first reading reference parameter, a second reading reference parameter and a third reading reference parameter,

wherein a conductivity value of the one non-volatile multi-level memory cell is decreased in order of the first state, the second state, the third state and the fourth state,

wherein the first reading reference parameter is allocated between the first state and the second state, the second reading reference parameter is allocated between the second state and the third state, and the third reading reference parameter is allocated between the third state and the fourth state,

wherein the first reading reference parameter, the second reading reference parameter and the third reading reference parameter are parameters for a normal read operation in which the information stored in the one non-volatile multi-level memory cell can be read out by output data of a plurality of bits,

wherein the normal read operation is carried out by parallel-comparing the parameter with the plurality of

reading reference parameters by using a plurality of sense circuits including at least a first sense circuit, a second sense circuit and a third sense circuit, first input terminals of the first sense circuit, the second sense circuit and the third sense circuit are commonly supplied with the parameter from the one non-volatile multi-level memory cell, a second input terminal of the first sense circuit is supplied with the first reading reference parameter, a second input terminal of the second sense circuit is supplied with the second reading reference parameter and a second input terminal of the third sense circuit is supplied with the third reading reference parameter, and

wherein the first verifying reference parameter is allocated below the first reading reference parameter, the second verifying reference parameter is allocated between the first reading reference parameter and the second reading reference parameter, the third verifying reference parameter is allocated between the second reading reference parameter and the third reading reference parameter and the fourth verifying reference parameter is allocated above the third reading reference parameter.

14. The electrically alterable non-volatile multi-level memory according to claim 13, wherein the operation for settling the parameter includes an erasure operation in which non-volatile multi-level memory cells of one of a byte, a block and a chip level can be erased.

15. The electrically alterable non-volatile multi-level memory according to claim 14, wherein the operation for settling the parameter includes a program operation in which electrons are injected into a floating gate of the one non-volatile multi-level memory cell.

16. The electrically alterable non-volatile multi-level memory according to claim 15, further comprising, a plurality of bit lines, including said first and said second bit line, each of which transfers information indicating data stored in a memory cell, wherein drain regions of said multi-level memory cells of said first group in said matrix are coupled to said first bit line of said plurality of bit lines, drain regions of said multi-level memory cells of said second group adjoining to said first group in said matrix are coupled to said second bit line adjoining to said first bit line in said plurality of bit lines and drain regions of multi-level memory cells of a third group adjoining to said second column in said matrix are coupled to a third bit line adjoining to said second bit line in said plurality of bit lines.

17. An electrically alterable non-volatile multi-level memory device including a plurality of non-volatile multi-level memory cells, each of the multi-level memory cells including a floating gate FET having a channel with electrically alterable voltage threshold value, the plurality of non-volatile multi-level memory cells being disposed in a matrix of rows and columns, channels of multi-level memory cells of a first group of the plurality of non-volatile multi-level memory cells being coupled in parallel between a first bit line and a reference potential, channels of multi-level memory cells of a second group of the plurality of non-volatile multi-level memory cells being coupled in parallel between a second bit line and the reference potential, electrons being capable of being injected into the floating gate by a phenomenon of hot electron injection from the channel of each of the plurality of non-volatile multi-level memory cell, electric currents flowing through the channels of the multi-level memory cells of the first group and electric currents flowing through the channels of the multi-level memory cells of the second group being substantially flowing in a same direction:

wherein an operation for controlling an electrical value of at least one non-volatile multi-level memory cell of the plurality of non-volatile multi-level memory cells to one state selected from a plurality of states including at least a first state, a second state, a third state and a fourth state is carried out in response to information to be stored in the one non-volatile multi-level memory cell,

wherein an operation for verifying whether the electrical value of the one non-volatile multi-level memory cell has being controlled to the one state selected from the plurality of states is carried out by comparing the electrical value of the one non-volatile multi-level memory cell with a plurality of verifying reference electrical values including at least a first verifying reference electrical value, a second verifying reference electrical value is carried out, a third verifying reference electrical value and a fourth verifying reference electrical value, and repeating the operation for controlling the electrical value and the operation for verifying are carried out until it is verified by the operation for verifying that the electrical value of the one non-volatile multi-level memory cell has being controlled to the one state,

wherein an operation for reading status of the one non-volatile multi-level memory cell is carried out by comparing the electrical value with a plurality of reading reference electrical values including at least a first reading reference electrical value, a second reading reference electrical value and a third reading reference electrical value,

wherein a conductivity value of the one non-volatile multi-level memory cell is decreased in order of the first state, the second state, the third state and the fourth state,

wherein the first reading reference electrical value is allocated between the first state and the second state, the second reading reference electrical value is allocated between the second state and the third state, and the third reading reference electrical value is allocated between the third state and the fourth state,

wherein the first reading reference electrical value, the second reading reference electrical value and the third reading reference electrical value are electrical values for a normal read operation in which the information stored in the one non-volatile multi-level memory cell can be read out by output data of a plurality of bits,

wherein the normal read operation is carried out by parallel-comparing the electrical value with the plurality of reading reference electrical values by using a plurality of sense circuits including at least a first sense circuit, a second sense circuit and a third sense circuit, first input terminals of the first sense circuit, the second sense circuit and the third sense circuit are commonly supplied with the electrical value from the one non-volatile multi-level memory cell, a second input terminal of the first sense circuit is supplied with the first reading reference electrical value, a second input terminal of the second sense circuit is supplied with the second reading reference electrical value and a second input terminal of the third sense circuit is supplied with the third reading reference electrical value, and

wherein the first verifying reference electrical value is allocated below the first reading reference electrical value, the second verifying reference electrical value is allocated between the first reading reference electrical

29

value and the second reading reference electrical value, the third verifying reference electrical value is allocated between the second reading reference electrical value and the third reading reference electrical value and the fourth verifying reference electrical value is allocated above the third reading reference electrical value.

18. The electrically alterable non-volatile multi-level memory according to claim 17, wherein the operation for controlling the electrical value includes an erasure operation in which non-volatile multi-level memory cells of one of a byte, a block and a chip level can be erased.

19. The electrically alterable non-volatile multi-level memory according to claim 18, wherein the operation for controlling the electrical value includes a program operation in which electrons are injected into a floating gate of the one non-volatile multi-level memory cell.

20. The electrically alterable non-volatile multi-level memory according to claim 19, further comprising, a plurality of bit lines, including said first and said second bit line, each of which transfers information indicating data stored in a memory cell, wherein drain regions of said multi-level memory cells of said first group in said matrix are coupled to said first bit line of said plurality of bit lines, drain regions of said multi-level memory cells of said second group adjoining to said first group in said matrix are coupled to said second bit line adjoining to said first bit line in said plurality of bit lines and drain regions of multi-level memory cells of a third group adjoining to said second column in said matrix are coupled to a third bit line adjoining to said second bit line in said plurality of bit lines.

21. An electrically alterable non-volatile multi-level memory device including a plurality of non-volatile multi-level memory cells, each of the multi-level memory cells including a floating gate FET having a channel with electrically alterable voltage threshold value, the plurality of non-volatile multi-level memory cells being disposed in a matrix of rows and columns, channels of multi-level memory cells of a first group of the plurality of non-volatile multi-level memory cells being coupled in parallel between a first bit line and a reference potential, channels of multi-level memory cells of a second group of the plurality of non-volatile multi-level memory cells being coupled in parallel between a second bit line and the reference potential, electrons being capable of being injected into the floating gate by a phenomenon of Fowler-Nordheim tunneling from the channel from the channel of each of the plurality of non-volatile multi-level memory cell, electric currents flowing through the channels of the multi-level memory cells of the first group and electric currents flowing through the channels of the multi-level memory cells of the second group being substantially flowing in a same direction:

wherein an operation for settling a parameter of at least one non-volatile multi-level memory cell of the plurality of non-volatile multi-level memory cells to one state selected from a plurality of states including at least a first state, a second state, a third state and a fourth state is carried out in response to information to be stored in the one non-volatile multi-level memory cell,

wherein an operation for verifying whether the parameter of the one non-volatile multi-level memory cell has being settled to the one state selected from the plurality of states is carried out by comparing the parameter of the one non-volatile multi-level memory cell with a plurality of verifying reference parameters including at least a first verifying reference parameter, a second verifying reference parameter, a third verifying refer-

30

ence parameter and a fourth verifying reference parameter is carried out, and repeating the operation for settling the parameter and the operation for verifying are carried out until it is verified by the operation for verifying that the parameter of the one non-volatile multi-level memory cell has being settled to the one state,

wherein an operation for reading status of the one non-volatile multi-level memory cell is carried out by comparing the parameter with a plurality of reading reference parameters including at least a first reading reference parameter, a second reading reference parameter and a third reading reference parameter,

wherein a conductivity value of the one non-volatile multi-level memory cell is decreased in order of the first state, the second state, the third state and the fourth state,

wherein the first reading reference parameter is allocated between the first state and the second state, the second reading reference parameter is allocated between the second state and the third state, and the third reading reference parameter is allocated between the third state and the fourth state,

wherein the first reading reference parameter, the second reading reference parameter and the third reading reference parameter are parameters for a normal read operation in which the information stored in the one non-volatile multi-level memory cell can be read out by output data of a plurality of bits,

wherein the normal read operation is carried out by parallel-comparing the parameter with the plurality of reading reference parameters by using a plurality of sense circuits including at least a first sense circuit, a second sense circuit and a third sense circuit, first input terminals of the first sense circuit, the second sense circuit and the third sense circuit are commonly supplied with the parameter from the one non-volatile multi-level memory cell, a second input terminal of the first sense circuit is supplied with the first reading reference parameter, a second input terminal of the second sense circuit is supplied with the second reading reference parameter and a second input terminal of the third sense circuit is supplied with the third reading reference parameter, and

wherein the first verifying reference parameter is allocated below the first reading reference parameter, the second verifying reference parameter is allocated between the first reading reference parameter and the second reading reference parameter, the third verifying reference parameter is allocated between the second reading reference parameter and the third reading reference parameter and the fourth verifying reference parameter is allocated above the third reading reference parameter.

22. The electrically alterable non-volatile multi-level memory according to claim 21, wherein the operation for settling the parameter includes an erasure operation in which non-volatile multi-level memory cells of one of a byte, a block and a chip level can be erased.

23. The electrically alterable non-volatile multi-level memory according to claim 22, wherein the operation for settling the parameter includes a program operation in which electrons are injected into a floating gate of the one non-volatile multi-level memory cell.

24. The electrically alterable non-volatile multi-level memory according to claim 23, further comprising, a plu-

rality of bit lines, including said first and said second bit line, each of which transfers information indicating data stored in a memory cell, wherein drain regions of said multi-level memory cells of said first group in said matrix are coupled to said first bit line of said plurality of bit lines, drain regions of said multi-level memory cells of said second group adjoining to said first group in said matrix are coupled to said second bit line adjoining to said first bit line in said plurality of bit lines and drain regions of multi-level memory cells of a third group adjoining to said second column in said matrix are coupled to a third bit line adjoining to said second bit line in said plurality of bit lines.

25. An electrically alterable non-volatile multi-level memory device including a plurality of non-volatile multi-level memory cells, each of the multi-level memory cells including a floating gate FET having a channel with electrically alterable voltage threshold value, the plurality of non-volatile multi-level memory cells being disposed in a matrix of rows and columns, channels of multi-level memory cells of a first group of the plurality of non-volatile multi-level memory cells being coupled in parallel between a first bit line and a reference potential, channels of multi-level memory cells of a second group of the plurality of non-volatile multi-level memory cells being coupled in parallel between a second bit line and reference potential, electrons being capable of being injected into the floating gate by a phenomenon of Fowler-Nordheim tunneling from the channel from the channel of each of the plurality of non-volatile multi-level memory cell, electric currents flowing through the channels of the multi-level memory cells of the first group and electric currents flowing through the channels of the multi-level memory cells of the second group being substantially flowing in a same direction:

wherein an operation for controlling an electrical value of at least one non-volatile multi-level memory cell of the plurality of non-volatile multi-level memory cells to one state selected from a plurality of states including at least a first state, a second state, a third state and a fourth state is carried out in response to information to be stored in the one non-volatile multi-level memory cell,

wherein an operation for verifying whether the electrical value of the one non-volatile multi-level memory cell has being controlled to the one state selected from the plurality of states is carried out by comparing the electrical value of the one non-volatile multi-level memory cell with a plurality of verifying reference electrical values including at least a first verifying reference electrical value, a second verifying reference electrical value, a third verifying reference electrical value and a fourth verifying reference electrical value is carried out, and repeating the operation for controlling the electrical value and the operation for verifying are carried out until it is verified by the operation for verifying that the electrical value of the one non-volatile multi-level memory cell has being controlled to the one state,

wherein an operation for reading status of the one non-volatile multi-level memory cell is carried out by comparing the electrical value with a plurality of reading reference electrical values including at least a first reading reference electrical value, a second reading reference electrical value and a third reading reference electrical value,

wherein a conductivity value of the one non-volatile multi-level memory cell is decreased in order of the first state, the second state, the third state and the fourth state,

wherein the first reading reference electrical value is allocated between the first state and the second state, the second reading reference electrical value is allocated between the second state and the third state, and the third reading reference electrical value is allocated between the third state and the fourth state,

wherein the first reading reference electrical value, the second reading reference electrical value and the third reading reference electrical value are electrical values for a normal read operation in which the information stored in the one non-volatile multi-level memory cell can be read out by output data of a plurality of bits,

wherein the normal read operation is carried out by parallel-comparing the electrical value with the plurality of reading reference electrical values by using a plurality of sense circuits including at least a first sense circuit, a second sense circuit and a third sense circuit, first input terminals of the first sense circuit, the second sense circuit and the third sense circuit are commonly supplied with the electrical value from the one non-volatile multi-level memory cell, a second input terminal of the first sense circuit is supplied with the first reading reference electrical value, a second input terminal of the second sense circuit is supplied with the second reading reference electrical value and a second input terminal of the third sense circuit is supplied with the third reading reference electrical value, and

wherein the first verifying reference electrical value is allocated below the first reading reference electrical value, the second verifying reference electrical value is allocated between the first reading reference electrical value and the second reading reference electrical value, the third verifying reference electrical value is allocated between the second reading reference electrical value and the third reading reference electrical value and the fourth verifying reference electrical value is allocated above the third reading reference electrical value.

26. The electrically alterable non-volatile multi-level memory according to claim **25**, wherein the operation for controlling the electrical value includes an erasure operation in which non-volatile multi-level memory cells of one of a byte, a block and a chip level can be erased.

27. The electrically alterable non-volatile multi-level memory according to claim **26**, wherein the operation for controlling the electrical value includes a program operation in which electrons are injected into a floating gate of the one non-volatile multi-level memory cell.

28. The electrically alterable non-volatile multi-level memory according to claim **27**, further comprising,

a plurality of bit lines, including said first and said second bit line, each of which transfers information indicating data stored in a memory cell, wherein drain regions of said multi-level memory cells of said first group in said matrix are coupled to said first bit line of said plurality of bit lines, drain regions of said multi-level memory cells of said second group adjoining to said first group in said matrix are coupled to said second bit line adjoining to said first bit line in said plurality of bit lines and drain regions of multi-level memory cells of a third group adjoining to said second column in said matrix are coupled to a third bit line adjoining to said second bit line in said plurality of bit lines.

29. An electrically non-volatile multi-level memory device comprising:

a plurality of memory cells disposed in matrix having rows and columns,

33

wherein each of said plurality of memory cells has a threshold voltage corresponding to data of two bits,
 wherein threshold voltages of said plurality of memory cells are allocated to one of a first, a second, a third and a fourth threshold range,
 wherein said first threshold range indicates an erase state, and said second, said third, said fourth threshold range indicate program states different from said erase state,
 wherein said second, said third and said fourth threshold range indicate mutually different programming states,
 wherein a threshold voltage of a memory cell selected from said plurality of memory cells is allocated in one of said first, said second and said third threshold range by hot electron injection, and
 wherein control gates of memory cells on the same row in said matrix are coupled to a word line of a plurality of word lines,
 a plurality of bit lines each of which transfers information indicating data stored in a memory cell, wherein drain regions of memory cells on a first column in said matrix are coupled to a first bit line of said plurality of bit lines, drain regions of memory cells on a second column adjoining to said first column in said matrix are coupled to a second bit line adjoining to said first bit line in said plurality of bit lines and drain regions of memory cells on a third column adjoining to said second column in said matrix are coupled to a third bit line adjoining to said second bit line in said plurality of bit lines,
 a programming circuit programming ones of said plurality of memory cells to said programming states by using verify reference parameters,
 a sense circuit which compares information indicating data stored in a memory cell with a first reference parameter, a second reference parameter and a third reference parameter in parallel, in a normal read operation,
 wherein said first threshold range is lower than said second threshold range, said second threshold range is lower than said third threshold range, and said third threshold range is lower than said fourth threshold range,

34

wherein said third reference parameter is higher than said second reference parameter, and said second reference parameter is higher than said first reference parameter, wherein said verify reference parameters have at least first and second verify reference parameters,
 wherein said first verify reference parameter is allocated between said second threshold range and said third threshold range, and said second verify reference parameter is allocated between said first threshold range and said second threshold range, and
 wherein said first verify reference parameter is settled between said second reference parameter and said third reference parameter, and said second verify reference parameter is settled between said first reference parameter and said second reference parameter.
30. An electrically non-volatile multi-level memory device according to claim **29**, wherein each of said plurality of memory cells has a floating gate, and a threshold voltage of a selected memory cell is allocated to one of said first, said second and said third threshold range from said fourth threshold range by being injected with hot electron to a floating gate of said selected memory cell.
31. An electrically non-volatile multi-level memory device according to claim **30**, further comprising,
 a column select circuit which receives column addresses, and which couples selected bit lines to said sense circuits.
32. An electrically non-volatile multi-level memory device according to claim **31**, wherein each of said sense circuits has a first comparator which receives said information and said first reference parameter, a second comparator which receives said information and said second reference parameter and a third comparator which receives said information and said third reference parameter.
33. An electrically non-volatile multi-level memory device according to claim **31**, wherein each of said plurality of memory cells has a source region to which is supplied with a reference potential in said read operation.

* * * * *