



US006041731A

United States Patent [19]

[11] Patent Number: **6,041,731**

Willis

[45] Date of Patent: **Mar. 28, 2000**

[54] **SELF-RIGHTING PLOW ANCHOR WITH FLOAT**

Attorney, Agent, or Firm—Coats & Bennett, P.L.L.C.

[76] Inventor: **John A. Willis**, 3104 White Oak Rd., Raleigh, N.C. 27609

[57] **ABSTRACT**

[21] Appl. No.: **09/300,126**

An anchor includes at least one plow-like fluke, a shank, and a float. The relative position of the float with respect to the center of gravity of the combined shank and fluke causes the anchor to assume a generally upright orientation quickly once the anchor is dropped in the water. One end of the shank is attached to the fluke and the float is attached to a rearward portion of the shank, with the float's center of buoyancy spaced away from the connection to the fluke. Upon being put in the water, the anchor quickly assumes a generally upright orientation, i.e., shank up and fluke tip down. Once in the generally upright orientation, the anchor may gently rock side to side with a pendulum-like action, with the tip of the fluke preferably being the lowest point of the anchor, during its descent to the bottom. When the anchor reaches a soft bottom, the tip of the fluke penetrates the bottom and the momentum of the anchor causes at least a portion of the fluke to bury into the bottom in a generally upright orientation. This setting of the anchor may be achieved in most or all situations without dragging the anchor along the bottom. The anchor is particularly adapted for watercraft where storage space is a concern and for shallow water watercraft.

[22] Filed: **Apr. 27, 1999**

[51] Int. Cl.⁷ **B63B 21/32**

[52] U.S. Cl. **114/301**

[58] Field of Search 114/301, 308, 114/294, 303, 304, 297, 295


[56] **References Cited**

U.S. PATENT DOCUMENTS

3,067,715	3/1962	Billups .
3,306,248	2/1967	Austin .
3,908,575	9/1975	Giolfo .
4,337,717	7/1982	Gregory .
4,834,015	5/1989	Alpert .
5,086,724	2/1992	Schreiber .
5,666,899	9/1997	Andersen .

Primary Examiner—S. Joseph Morano
Assistant Examiner—Patrick Craig Muldoon

25 Claims, 5 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

SELF-RIGHTING PLOW ANCHOR WITH FLOAT

FIELD OF THE INVENTION

The present invention relates to the field of anchors for watercraft, and more particularly to a self-righting plow anchor that includes a float on a shank thereof to enable the anchor to quickly assume an upright orientation upon entering the water.

BACKGROUND OF THE INVENTION

Anchors for watercraft should ideally become set quickly once the anchor is dropped in the water. Numerous anchor designs have been proposed that attempt to address this problem, such as the design shown in U.S. Pat. No. 4,337, 717. Many of these designs rely on some method of weighting the tip or tips of the anchor's fluke so as to promote a tip-first entry into the bottom. Other designs attempt to shape the fluke so that the anchor will right itself when the anchor is dragged along the bottom, and therefore properly dig into the bottom more quickly.

Applicant has discovered that quick setting of an anchor may be enhanced by causing the anchor to assume the proper orientation during descent, rather than relying on reorienting the anchor once it has landed. However, self-righting anchor designs proposed to date have proven inadequate, unduly complicated, or ill-suited for smaller anchors intended for use with smaller watercraft. In addition, the prior art designs are slow to assume the upright orientation and/or have proven unreliable. For instance, the modified Danforth type anchor of the patent to Austin, U.S. Pat. No. 3,306,248, is a complicated anchor having many parts. Likewise, the spade type anchors of the patents to Billups, U.S. Pat. No. 3,067, 715 and to Schrieber, U.S. Pat. No. 5,068,724, are unduly complicated. It is believed that none of these anchors have achieved commercial success.

In addition, it has been discovered that plow type anchors work well in situations where the bottom is soft, such as with sandy or muddy bottoms. Plow type anchors are characterized by a fluke that includes a plurality of side surfaces, at least two of which that are at an angle with respect to one another, and a pointed forward tip. For instance, the main part of the fluke in such anchors may be an inverted V cross-section with a taper from back to front so as to appear roughly triangular when viewed from the side. An example of this design is the anchor known as the Delta Fast Set sold by Simpson & Lawrence of England.

Despite the numerous anchor designs in the prior art, there remains a need for a self-righting anchor that can very quickly assume the proper orientation once dropped in the water from any orientation. And there is a particular need for plow type anchors having such a self-righting action.

SUMMARY OF THE INVENTION

The anchor of the present invention includes, inter alia, at least one plow-like fluke, a shank, and a float. The relative position of the float with respect to the center of gravity of the combined shank and fluke causes the anchor to assume a generally upright orientation quickly once the anchor is dropped in the water.

One end of the shank is connected to the fluke, preferably by direct attachment along a longitudinal axis of the fluke. The connection between the fluke and the shank is preferably not a rigid connection, but is instead a somewhat loose connection that allows for small lateral displacements of the

far end of the shank without the fluke being displaced. The float is attached to a rearward portion of the shank, with the float's center of buoyancy spaced away from the shank's connection to the fluke. Preferably, the float is shaped and sized to fit within the footprint of the fluke when viewed from above.

Upon being put in the water, the anchor of the present invention quickly assumes a generally upright orientation, i.e., shank up and fluke down. Thus, the anchor of the present invention is suitable for very shallow water situations. Once in the generally upright orientation, the anchor may gently rock side to side with a pendulum-like action, with the tip of the fluke preferably being the lowest point of the anchor, during its descent to the bottom. When the anchor reaches a soft bottom, the tip of the fluke penetrates the bottom and the momentum of the anchor causes at least a portion of the fluke to bury into the bottom in a generally upright orientation. This setting of the anchor may be achieved in most or all situations without dragging the anchor along the bottom.

Such an anchor is particularly adapted for shallow water operation, such as in a sound or the like, and the plow-like shape of the fluke is adapted for soft bottom applications. In addition, the anchor's simplicity of construction and effectiveness allows the anchor to be made economically in compact sizes while remaining effective. Thus, the present invention is particularly adapted for watercraft where storage space is a concern and for shallow water watercraft.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of one embodiment of an assembled anchor according to the present invention.

FIG. 2 is an exploded view of the anchor of FIG. 1 without the float.

FIG. 3 is a rear underside view of the anchor of FIG. 1.

FIG. 4 is a perspective view of another embodiment of an assembled anchor according to the present invention having two flukes.

FIG. 5 is a rear elevational view of the anchor of FIG. 4.

DETAILED DESCRIPTION

Referring to FIGS. 1-3, the anchor 10 of the present invention includes a fluke 20, a shank 40, and a float 60. The fluke 20 in FIG. 1 has a pointed front tip 22 and a broad tail 24. Running generally along the centerline of the fluke 20, from tail 24 to tip 22, is a longitudinal axis 25. The fluke 20 includes a pair of side surfaces 30, referred to herein as wings, joined by a third surface, referred to herein as a bridging surface 26. The wing surfaces 30 are generally triangular in shape with a generally straight lower edge 32 and a curved rear edge 34. The two wings 30 of FIG. 1 are of the same general shape, are disposed symmetrically about the longitudinal axis 25, and are canted with respect to one another. The wings 30 preferably meet at, and help form, the pointed tip 22 of the fluke 20. In contrast to many prior art anchors, in preferred embodiments of the fluke 20 there is no additional weighting at or near the tip 22, so as to lessen the overall weight of the anchor 10.

Between the two wings 30 is the optional bridging surface 26, which is also generally triangular in shape. Located in a middle portion of the bridging surface 26 are a plurality of mounting slots 28 that are preferably rectangular in shape. Also included on the bridging surface 26, near the rearmost mounting slot 28, are a plurality of holes for screws 72 that mount the lock plate 70 to the fluke 20 as described below.

The fluke **20** is preferably made from a single piece of metallic material, such as sheet steel, galvanized steel, stainless steel, aluminum, or other material suitable for aquatic environments. Alternatively, the fluke **20** may be formed from distinct pieces that are fastened or otherwise secured together, such as by welding.

The shank **40** is a generally elongate member preferably having three sections, a base **42**, a middle **50**, and a head **46**, as may easily be seen in FIG. 2. The base **42** includes a plurality of downwardly extending flanges **44** that are preferably L-shaped. The flanges **44** should be dimensioned so as to be able to be inserted through the mounting slots **28** on the fluke **20**. The head **46** is generally elongate and includes a slot **48** for connecting to an anchor line **80**. Between the head **46** and the base **42** is a middle section **50**. This middle section **50** includes a protrusion **52** that extends rearwardly away from the head **46** and that includes a circular mounting hole **54**. The shank **40** may be made from similar materials as the fluke **20**, but is preferably made from a less dense material so that the majority of the mass of the combined shank **40** and fluke **20** resides in the fluke **20**.

The float **60** may take a wide variety of shapes, but the float **60** is preferably generally cylindrical in shape with closed hemispherical ends **64**. The float **60** may be made from any suitably buoyant material, such as foamed plastic or the like. The material should be durable and resistant to UV damage. In some embodiments, the float **60** may be constructed from common heavy duty PVC piping materials. For instance, two end caps may be joined to a short section of PVC pipe to form a generally cylindrical body, with or without a center peripheral groove on the center portion of the outer surface **62**. Obviously, the interior portion of the float **60** should be water-tight for buoyancy. Further, it is plainly preferable that the corresponding portions of the float **60** and the mounting hole **54** of the shank **40** have the same shape.

To assemble the anchor **10**, the float **60** is joined to the shank **40**. If the float **60** is unitary, such as a compressible foam, the float **60** may be inserted into the mounting hole **54** in the middle section **50** of the shank **40**. The float **60** should be located so that it will provide approximately equal buoyancy to both left and right sides of the shank **40**. In one preferred embodiment, using the float **60** made from PVC pipe material, one end cap may be joined to a short section of PVC pipe using conventional means. The pipe section should be small enough to just fit within the mounting hole **54** and the end cap should have an outer diameter just larger than the mounting hole **54**. This partially assembled float **60** is then inserted into the mounting hole **54**, with the pipe section fitting through the mounting hole **54**. Thereafter, the other end cap may be added. With such a float **60**, the shank **40** will in effect bisect the outer surface **62** of the float **60** without penetrating the interior chamber of the float **60**.

The shank **40**, with the float **60** attached thereto, is then mated to the fluke **20**. To do so, the flanges **44** of the shank **40** are inserted through the mounting slots **28** on the fluke **20** and then the shank **40** is pulled forward such that the L-shaped flanges **44** engage the underside of the spaces between the mounting slots **28**. The shank **40** should be oriented generally along the longitudinal axis **25** of the fluke **20** with the head **46** of the shank **40** being closer to the tip **22** than the tail **24** of the fluke **20**. To hold the shank **40** in place, a lock plate arrangement may be used, as shown in FIG. 3. A lock plate **70** may be added to the underside of the fluke **20** so that a portion of the lock plate **70** extends into the space directly below one of the mounting slots **28** and up against a rear edge of a flange **44**. The lock plate **70** may then

be secured in place by suitable screws **72** passing through the fluke **20** and the lock plate **70**.

Of course, the sequence of assembly described above is but one of a variety of methods of making an anchor **10** according to the present invention. The sequence and inclusion of certain steps is for illustrative purposes only and is specifically not intended to be limiting as to the method of manufacture or the ultimate structure achieved.

With the shank **40** connected to the fluke **20**, the combined assembly will have a center of gravity. The float **60** should be rearward of this center of gravity, but forward of the tail **24** of the fluke **20**. Note, however, that the entire float **60** should preferably fit within the footprint of the fluke **20** when viewed from above.

To use the anchor **10**, a suitable anchor line or chain **80**, is attached to the anchor **10** via the slot **48** on the end of the shank **40**. Thereafter, the anchor **10** is dropped, tossed, hurled, or otherwise released into the water. Importantly, the anchor **10** of the present invention does not need to be in any particular orientation when introduced into the water. Once in the water, the anchor **10** will begin to sink through the water until it reaches the ground under the water. Because this ground may be sand, rock, mud, and may be under the sea, a lake, a river, a bay, or the like, the generic term "bottom" will be used for the balance of this description. While the bottom may be relatively hard, the present anchor **10** is particularly adapted for soft bottoms, such as sandy and/or muddy bottoms.

Upon being put in the water, the anchor **10** of the present invention quickly assumes a generally upright orientation, i.e., shank **40** up and fluke **22** down. This action is believed to be due to the location of the float **60** relative to the center of gravity of the anchor **10** and the tip **22** of the fluke **20**. By quickly, it is meant that the anchor **10** assumes the generally upright orientation within a vertical distance of five times the overall height of the anchor **10** or less, after being released at the surface of the water. Thus, the anchor **10** of the present invention is suitable for very shallow water situations. Once in the generally upright orientation, the anchor **10** will likely rock side to side in a pendulum-like action during its descent to the bottom. The point of rotation should be the center of buoyancy of the float **60**. The overall orientation is preferably such that the tip **22** of the fluke **20** is the lowest point of the anchor **10** during descent. This orientation may be achieved by placing the float **60** rearward and upward from the center of gravity of the anchor **10**, with the tip **22** on the opposite side of the center of gravity, as shown in FIG. 1.

When the anchor **10** reaches a soft bottom, the tip **22** of the fluke **20** will penetrate the bottom and the momentum of the anchor **10** will cause at least a portion of the fluke **20** to bury into the bottom. Preferably, the entire fluke **20** is buried, so that maximum resistance to movement may be achieved. When buried as described, the anchor **10** resists any forward force applied via the anchor line **80**. This setting of the anchor **10** may be achieved in most or all situations without dragging the anchor **10** along the bottom.

It should be noted that watercraft tend to move somewhat relative to the anchor **10** while anchored. In preferred embodiments, the present anchor **10** allows for small changes in the lateral angular relationship between the watercraft and the anchor **10** by allowing for small amounts of lateral movement at the connection between the shank **40** and the fluke **20**. That is, the shank **40** is preferably not rigidly attached to the fluke **20**, but is instead preferably connected through a joint having a small amount of built-in clearance.

To remove the anchor **10**, the user in the watercraft pulls in the anchor line **80** until the watercraft is approximately directly over the anchor **10**. By pulling on the anchor line **80** at this point, the end of the shank **40** will be pulled upwardly, thereby rotating the fluke **20** so that the tip **22** is no longer buried in the bottom, or at least pointed upwardly out of the bottom. The curved portions **34** of the wings **30** that help form the tail **24** of the fluke **20** should facilitate this rotational movement. Thereafter, the anchor **10** may simply be hauled aboard the watercraft in the customary fashion.

In the description above, the shank **40** was connected to the fluke **20** using an arrangement including a lock plate **70**. However, such an arrangement is not required. Indeed, the shank **40** may be joined to the fluke **20** in any manner known in the art, including by direct screwing, welding, or the like. Further, while not preferred due to the weight distribution aspects, the shank **40** may be formed integrally with the fluke **20**, such as by casting.

In addition, the fluke **20** above has been described as having two wings **30** and a central bridging surface **26**. However, such a fluke **20** is not required. Instead, the fluke **20** is only required to have two side surfaces **30**, one on each side of the longitudinal axis **25**, with the side surfaces **30** being disposed at an angle relative to one another.

An embodiment of the anchor **10** similar to that shown in FIG. 1 has been built. The fluke **20** was made from $\frac{1}{8}$ inch thick **304** stainless steel, had a tail **24** to tip **22** dimension of approximately $8\frac{1}{2}$ inches, a height at the tail **24** of approximately three inches, an overall width at the tail **24** of approximately six inches. The shank **40** was made from $\frac{1}{4}$ inch thick aluminum, had an overall length of approximately twelve inches, three L-shaped flanges **44** of approximately $\frac{1}{4}$ inch thickness (with the rearmost flange **44** having rearward facing portion of approximately $\frac{1}{4}$ inch to engage the lock plate **70**), and extended approximately normal to the bridging surface **26** of the fluke **20** when assembled. The float **60** was assembled from two inch diameter "SCH 40 PVC I" pipe available from Lasco, including two endcaps and a short pipe section. The float **60** was directly attached to the shank **40**, with the center of the float **60** located approximately $3\frac{1}{2}$ inches above the fluke **20**, and bisected by the shank **40**. The overall height of the anchor **10** was approximately $7\frac{1}{4}$ inches. Such an anchor **10** was tested and assumed a generally upright orientation within a vertical distance of approximately two and one half feet or less after being released at the surface of the water in an upside down orientation.

In other embodiments, the anchor **10** may include a plurality of flukes **20**. For example, the anchor **10** shown in FIG. 4 and FIG. 5 includes a pair of flukes **20**. These flukes **20** are interconnected by a generally U-shaped bracket **90**. The bracket **90** in turn mates with the shank **40**, preferably using a flange and lock plate arrangement similar to the joint between the shank **40** and fluke **20** of FIG. 1. As shown in FIGS. 4 and 5, the shank **40** is disposed between the two flukes **20** such that the buoyant center of the float **60** is both above the longitudinal axes **25** of the flukes **20** and located between the axes **25** when viewed from above. In fact, for the embodiment shown, the float **60** is located directly above the center of gravity of the combined fluke-shank assembly. Of course, the float **60** may be located elsewhere, but such a central position is believed to be most advantageous. Further, while only two flukes **20** are shown in FIG. 4, the anchor **10** may include more flukes **20**, preferably in a regular geometric configuration with all the lower edges **32** of the respective flukes **20** lying in a common plane.

The present invention may, of course, be carried out in other specific ways than those herein set forth without

departing from the spirit and essential characteristics of the invention. The present embodiments are, therefore, to be considered in all respects as illustrative and not restrictive, and all changes coming within the meaning and equivalency range of the appended claims are intended to be embraced therein.

What is claimed is:

1. An anchor, comprising:

- a) at least one fluke having at least a tip on a forward section thereof, a tail on a rearward section thereof, a longitudinal axis running from a central portion of said tail to a central portion of said tip, and at least first and second wing surfaces disposed on opposing sides of said longitudinal axis and canted with respect to each other;
- b) a shank connected to said fluke on a dorsal side thereof and extending away therefrom generally parallel to said longitudinal axis;
- c) a float attached to said shank at a position spaced away from said fluke and having a buoyant center, said buoyant center disposed above said longitudinal axis; and
- d) wherein said float causes the anchor to quickly assume a generally upright position when the anchor is descending through water after being released from any original starting orientation at the water's surface.

2. The anchor of claim 1 wherein the buoyant center of said float is disposed closer to said tail than said tip.

3. The anchor of claim 1 wherein said float does not extend laterally beyond said fluke when viewed from above.

4. The anchor of claim 1 wherein said float is directly attached to said shank.

5. The anchor of claim 1 wherein said float has an outer surface that is generally cylindrical in shape and generally bisected by said shank.

6. The anchor of claim 1 wherein said fluke further includes a third generally flat surface disposed between said first and second wing surfaces and wherein said shank connects to said fluke via said third surface.

7. The anchor of claim 1 wherein the anchor includes not more than one fluke.

8. The anchor of claim 1 wherein said fluke includes a single generally pointed front tip.

9. The anchor of claim 1 wherein said fluke is not additionally weighted proximate said tip other than by the weight of the material forming said fluke.

10. The anchor of claim 1 wherein said float remains in a fixed position relative to said shank and wherein said buoyant center of said float is disposed not farther forward than the center of gravity of said anchor.

11. The anchor of claim 1 wherein said float causes said anchor to remain generally upright, once righted, for the remaining duration of descent through said water.

12. The anchor of claim 1 wherein said fluke includes a generally pointed tip and wherein said tip automatically penetrates the ground under the water upon initial contact with said ground without having to be additionally displaced relative to said ground by pulling on said shank.

13. The anchor of claim 1 wherein said float causes said anchor, from any initial orientation, to assume a generally upright orientation within three feet of descent when dropped from a height of six feet or less above the water's surface.

14. The anchor of claim 1 wherein said shank includes a base proximate to said fluke and a head a distance from said fluke and wherein said shank is connected to said fluke via a loose connection wherein said head may move $\frac{1}{2}$ inch or

less laterally with respect to said longitudinal axis without causing said fluke to move laterally.

15. The anchor of claim 1 wherein said buoyant center of said float is disposed directly above said longitudinal axis.

16. The anchor of claim 1 further including a plurality of said flukes. 5

17. The anchor of claim 16 wherein said buoyant center of said float is further disposed between the said flukes when viewed from above.

18. A plow anchor, comprising: 10

a) at least one plow-like fluke having at least a generally pointed front tip, a tail, a longitudinal axis running from said tail to said tip, and at least first and second generally flat surfaces disposed on opposing sides of said longitudinal axis and angled with respect to each other, said fluke not additionally weighted proximate said tip other than by the weight of the material forming said fluke; 15

b) a shank connected to said fluke on a dorsal side thereof and extending away therefrom generally along said longitudinal axis; 20

c) a float attached to said shank at a position spaced away from said fluke and having a buoyant center, said buoyant center disposed above said longitudinal axis and closer to said tail than said tip; said float having an outer surface that is generally bisected by said shank; and 25

d) wherein said float causes the anchor to quickly assume a generally upright position when the anchor is descending through water after being released from any original starting orientation at the water's surface; and wherein said float causes said anchor to remain generally upright, once righted, for the remaining duration of descent through said water. 30

19. The anchor of claim 18 wherein said fluke includes a generally pointed tip and wherein said tip automatically penetrates the ground under the water upon initial contact with said ground without having to be additionally displaced relative to said ground by pulling on said shank. 35

20. The anchor of claim 19 wherein, when said ground is deep sand, the anchor may be pulled forward no more than twice the length of said fluke before the anchor becomes set.

21. The anchor of claim 18 wherein said float is directly attached to said shank. 40

22. A plow anchor, comprising:

a) at least one plow-like fluke having at least a generally pointed front tip, a tail, a longitudinal axis running from said tail to said tip, and at least first and second generally flat surfaces disposed on opposing sides of said longitudinal axis and angled with respect to each other; said fluke further including a third generally flat surface disposed between said first and second flat surfaces, said fluke not additionally weighted proximate said tip other than by weight of the material forming said fluke;

b) a shank connected to said fluke via said third surface on a dorsal side thereof and extending away therefrom generally along, but above, said longitudinal axis;

c) a float directly attached to said shank at a position spaced away from said fluke and having a buoyant center, said buoyant center disposed above said longitudinal axis and closer to said tail than said tip; said float having an outer surface that is generally bisected by said shank;

d) wherein said float does not extend laterally beyond said fluke when viewed from above; and

e) wherein said float causes the anchor to quickly assume a generally upright position when the anchor is descending through water after being released from any original starting orientation at the water's surface; and wherein said float causes said anchor to remain generally upright, once righted, for the remaining duration of descent through said water. 35

23. The anchor of claim 22 wherein, when said ground is deep sand, said anchor penetrates the ground under the water upon initial contact with said ground and wherein said anchor may be pulled forward not more than two feet before the anchor becomes set in said ground. 40

24. The anchor of claim 22 wherein, when said ground is deep sand, said tip automatically penetrates the ground under the water upon initial contact with said ground without having to be additionally displaced relative to said ground by pulling on said shank.

25. The anchor of claim 22 further including a plurality of said flukes connected to said shank and wherein said buoyant center of said float is further disposed between at least two of said flukes when viewed from above.

* * * * *