



US006053249A

United States Patent [19]

[11] Patent Number: **6,053,249**

Stevenson et al.

[45] Date of Patent: **Apr. 25, 2000**

[54] **METHOD AND APPARATUS FOR INJECTING GAS INTO A SUBTERRANEAN FORMATION**

5,431,228	7/1995	Weingarten et al.	166/357
5,450,901	9/1995	Ellwood	166/266
5,482,117	1/1996	Kolpak et al.	166/265
5,570,744	11/1996	Weingarten et al.	166/357
5,698,014	12/1997	Cadle et al.	96/157

[75] Inventors: **Mark D. Stevenson; Jerry L. Brady**, both of Anchorage, Ak.

OTHER PUBLICATIONS

[73] Assignee: **Atlantic Richfield Company**, Los Angeles, Calif.

“New Design for Compact Liquid-Gas Partial Separation”, J.S. Weingarten et al, SPE 30637, Dallas, TX Oct. 22-25, 1995. pp. 73-80.

[21] Appl. No.: **09/072,657**

Primary Examiner—David Bagnell
Assistant Examiner—Jennifer R. Dougherty
Attorney, Agent, or Firm—D. Faulconer

[22] Filed: **May 5, 1998**

[51] **Int. Cl.**⁷ **E21B 43/40; E21B 43/16**

[52] **U.S. Cl.** **166/305.1; 166/265; 405/128**

[58] **Field of Search** 166/90.1, 105.1, 166/265, 267, 268, 305.1; 405/53, 128

[57] ABSTRACT


[56] References Cited

U.S. PATENT DOCUMENTS

4,074,763	2/1978	Stevens	166/325
4,481,020	11/1984	Lee et al.	55/203
4,531,584	7/1985	Ward	166/265
4,632,601	12/1986	Kuwadd	405/128
5,343,945	9/1994	Weingarten et al.	166/305.1
5,421,408	6/1995	Stoisits et al.	166/274

A method and apparatus for injecting gas into a subterranean formation wherein the gas to be injected is mixed with a carrier fluid (e.g. water) at the surface to form a mixture which is then flowed down a wellbore. The mixture is flowed through a downhole separator to separate at least a portion of the gas from the mixture which is then injected into the formation. The carrier fluid and any unseparated gas are then returned to the surface to be separated whereby the carrier fluid can be recycled in the gas injection process.

18 Claims, 2 Drawing Sheets






FIG. 1




FIG. 2

METHOD AND APPARATUS FOR INJECTING GAS INTO A SUBTERRANEAN FORMATION

DESCRIPTION

1. Technical Field

The present invention relates to a method and apparatus for injecting gas into a subterranean formation and in one aspect relates to a method and apparatus for injecting gas into a formation wherein the gas is mixed with a carrier fluid at the surface which, in turn, is flowed down a well where at least a portion of the gas is separated and injected into the formation while the remaining gas and the carrier fluid is returned to the surface.

2. Background

It is well known that many hydrocarbon reservoirs produce extremely large volumes of gas along with crude oil and other liquids. In producing fields such as these, it is not unusual to experience gas-to-oil ratios (GOR) as high as 25,000 standard cubic feet per barrel (scf/bbl.) or greater. As a result, large volumes of gas must be separated out of the liquids before the liquids are transported to storage or for further processing. Where the production sites are near or convenient to large markets, this gas is considered a valuable asset when demands for gas are high. However, when demands are low or when the producing reservoir is located in a remote area, large volumes of produced gas can present major problems since production may have to shut-in or at least drastically reduced if the produced gas can not be timely and properly disposed of.

In areas where substantial volumes of the produced gas can not be marketed or otherwise utilized, it is common to "reinject" the gas into a suitable, subterranean formation. For example, it is well known to inject the gas back into a "gas cap" zone which usually overlies a production zone of a reservoir to maintain the pressure within the reservoir and thereby increase the ultimate liquid recovery therefrom. In other applications, the gas may be injected into a producing formation through an injection well to drive the hydrocarbons ahead of the gas towards a production well. Still further, the produced gas may be injected and "stored" in an appropriate, subterranean permeable formation from which it can be recovered when the situation dictates.

To reinject the gas, large and expensive separation and compression surface facilities must be built at or near the production site. A major economic consideration in such facilities is the relatively high costs of the gas compressor train which is needed to compress the large volumes of produced gas to the pressures required for injection. As will be understood in this art, significant cost savings can be achieved if the gas compressor requirements can be downsized or eliminated altogether. To achieve this, however, it is necessary to either raise the pressure at the surface by some means other than mechanical compression or else reduce the pressure required at the surface for injection of the gas downhole.

SUMMARY OF THE INVENTION

The present invention provides a method and apparatus for injecting gas into a subterranean formation in which the compressor horsepower required is substantially reduced or is eliminated altogether. Basically, the gas to be injected is mixed with a carrier fluid at the surface to form a mixture which is then flowed down a wellbore which extends into the subterranean formation. The mixture is flowed through a

downhole separator to separate at least a portion of the gas from the mixture which is then injected into the formation. The carrier fluid and any unseparated gas is then returned to the surface wherein it is further separated whereby the carrier fluid can be recycled for reuse in the operation.

More specifically, the gas to be injected is mixed with a dense, carrier fluid at the surface which, in turn, has been boosted to a relatively high pressure by a liquid pump or the like. The carrier fluid can be selected from a wide variety of liquids, e.g. water, brine, oil-based liquids, crude, etc. The mixture is flowed down either a string of tubing in the wellbore or through the annulus formed between the tubing and the wellbore and through a downhole separator; e.g. auger separator. Centrifugal force separates at least a portion of the gas (e.g. 75%) and the downhole pressures force the separated gas into the subterranean formation. The mixture of the carrier fluid and any unseparated gas flow upward from the separator to the surface through either the annulus or the tubing as the case may be.

The mixture of carrier fluid and unseparated gas is passed through a separator after it returns to the surface to separate the gas from the carrier fluid whereby the carrier fluid can be recycled. By forming a mixture with a dense, carrier fluid, the gas does not need to be compressed at the surface before it is injected down the wellbore. As will be appreciated, by reducing or eliminating the need for gas compressors, the costs involved in disposing of excess gas through injection are substantially reduced.

BRIEF DESCRIPTION OF THE DRAWINGS

The actual construction, operation, and apparent advantages of the present invention will be better understood by referring to the drawings which are not necessarily to scale and in which like numerals refer to like parts and in which:

FIG. 1 illustrates a well through which gas is being injected into a subterranean formation in accordance with the present invention by flowing a carrier liquid-gas mixture down the tubing and taking returns through the well annulus; and

FIG. 2 illustrates a well through which gas is being injected into a subterranean formation in accordance with the present invention by flowing a carrier liquid-gas mixture down the well annulus and taking returns through the tubing.

BEST KNOWN MODE FOR CARRYING OUT THE INVENTION

Referring more particularly to the drawings, FIG. 1 discloses an injection well **10** having a wellbore **11** which extends from the surface **12** into a permeable subterranean formation or injection zone **13**. As illustrated, wellbore **11** is cased with a string of casing **14** to a point slightly above formation **13**. A liner **15** or the like having openings **16** (e.g. perforations or slots) therein and closed at its lower end by cement plug **15a** or the like is suspended from the lower end of casing **14** and extends substantially through injection zone **13**. A packer **17** is provided near the top of liner **15** to block any substantial flow from around the outside of the liner into casing **14**. While this is one well-known way to complete a well, it will be recognized that other equally as well-known techniques can be used without departing from the present invention: e.g., wellbore **11** may be cased throughout its entire length and then perforated adjacent formation **13** or it may be completed "open-hole" adjacent formation **13**, etc.

A string of tubing **18** is positioned within casing **14** and extends from the surface substantially throughout the length

of casing **14** and terminates at a point substantially adjacent the top of injection zone **13**. Packer **19** is positioned near the lower end of tubing **18** to block any flow in the annulus **20** between tubing **18** and casing **14** at that point. Tubing has at least one opening **21** (a plurality shown but only some numbered) therethrough near its lower end to provide fluid communication between the tubing **18** and annulus **20** at a point above packer **19**.

A separator (e.g. auger separator **25**) is positioned within tubing **18** near the lower end thereof. Separator **25** can be affixed within tubing **18** and lowered therewith or, as will be understood, it can be lowered into the tubing on a wireline, coiled-tubing, or the like (not shown) and landed on a landing nipple or the like (not shown) within the tubing after the tubing **18** has been positioned within the wellbore. Auger separator **25**, as shown, is basically comprised of a housing **26** having a center conduit or tube **27** extending therethrough. Tube **27** is open at its lower end **28** and is closed at its upper end by a wireline connection **29** or the like which, in turn, can be used in positioning and/or removing separator **25** from tubing **18**, as will be understood in the art.

A spiral, auger-like blade **30** is affixed to the outer surface of tube **27** and extends along a substantial portion of its length within housing **26**. A seal **31** (O-ring or the like) is provided on housing **26** to effectively block flow between the housing and the tubing **18**. An inlet port **32** is provided in center tube **27** below the lower end of auger blade **30** for a purpose explained below. A tubing packer **33** or an X-nipple (not shown) or the like is provided on tube **27** below port **32** to block flow through housing **26** at that point. Auger separators of this type are known in the art and are disclosed and fully discussed in U.S. Pat. No. 5,431,228 which issued Jul. 11, 1995, which, in turn, is incorporated herein in its entirety by reference.

Also, for a further discussion of the construction and operation of such separators, see "New Design for Compact-Liquid Gas Partial Separation: Down Hole and Surface Installations for Artificial Lift Applications", Jean S. Weingarten et al, SPE 30637, Presented Oct. 22-25, 1995 at Dallas, Tex. As fully disclosed and explained in the above cited references, an auger separator (i.e. separator **25**) separates at least a portion of the gas from a flowing, mixed liquid-gas stream as it flows through the spiral path defined by auger blade **30**. The liquid in the stream is forced to the outside of the blade and against the wall of the housing **26** by centrifugal force while at least a portion of the gas is separated from the stream and remains near the wall of the center tube **27**. As the stream reaches the end of the auger, the separated gas will flow through an inlet port **32** and out the open bottom **28** of tube **27** while the liquid and remaining gas will continue to flow along the outside of tube **27**, through port(s) **21**, and back to the surface through well annulus **20**.

Auger separators have been proposed for separating a portion of the produced gas downhole for reinjecting it into a formation before the production stream reaches the surface; see co-pending and commonly-assigned U.S. patent application Ser. No. 08/757,857, now U.S. Pat. No. 5,794,697 filed Nov. 27, 1996; Ser. No. 08/982,993, filed Dec. 2, 1997; and Ser. No. 09/016,612, filed Jan. 30, 1998. In accordance with the present invention, an auger separator **25** is used downhole in a manner which significantly reduces or substantially eliminates the expensive, compressors which would otherwise be required for injecting gas from the surface into a subterranean injection zone **13**.

In accordance with the present invention, the effective density of the gas to be injected is increased at the surface

before it is fed down wellbore **11**. This is done by blending a dense, carrier fluid (e.g. liquid) with the gas at the surface to form a mixture having a bulk density between that of the carrier fluid and that of the gas. Dense carrier fluids which may include any fluids which will suspend the gas in the mixture but will allow separation of at least a part of the gas as the mixture passes through auger separator **25** which includes a wide variety of fluids. For example, such carrier liquids may include water; water-based liquids with added/dissolved densifying materials (e.g. produced water, seawater, drilling muds, "well-kill" brines, etc. with or without corrosion inhibitors); oil-based liquids such as drilling muds or the like; petrochemicals such as glycol; stabilized or volatile crude oils; or esoteric fluids such as a "heavy media", i.e. suspensions of fine particles of metal or the like such as a suspension of fine iron filings in water. The gas and the carrier liquid are mixed so that the density of the mixture when flowed under pressure (i.e. pumped) down wellbore **11** will overbalance the bottom-hole pressure within injection zone **13**, as will be more fully discussed below.

As shown in FIG. 1, gas is supplied to mixer **40** through line **41**. This is the gas which typically has been produced and then separated from a production stream (not shown) and is to be injected into subterranean zone **13**. Carrier liquid from surface separator **38** (to be discussed later) and/or from a separate source **39** is pumped under pressure by pump **42** through line **43** into mixing chamber **40** or other mixing device to form a carrier liquid-gas mixture. A foaming agent (e.g. low concentrations of sulphonates, polysulphonates, long-chain alcohols) may be added to the mixture (e.g. within mixer **40**) to prevent "slugging" as the mixture flows downward in tubing **18** as will be understood in the art.

This mixture (arrows **34**) flows down tubing **18** (FIG. 1) and through auger separator **25** where centrifugal force separates at least a portion of the gas from the mixture as explained above. The separated gas (arrows **35** in FIG. 1) passes through port(s) **32** in central tube **27** and exits into liner **15**. Packers **17**, **19**, and **33** block any substantially upward flow of gas so it can only flow through openings **16** and into zone **13** as the gas accumulates and the pressure increases in within liner **15**.

The dense carrier liquid plus any remaining gas mixture (arrows **36** in FIG. 1) flows along the outside of blade **30** of separator **25** and will pass through port(s) **21** in housing **26** as it reaches the bottom of blade **30**. The carrier liquid-unseparated gas mixture will flow to the surface through well annulus **20**, through outlet **37**, and into surface separator **38** where the remaining gas is separated from the carrier liquid. Any separated gas is taken from separator **38** through line **44** to be used as fuel or otherwise properly disposed of. The carrier liquid is taken from separator **38** and is preferably recycled to mixer **40** through pump **42** to be reused in the ongoing gas injection operation. It should be understood that carrier liquid may be added or removed from the circuit through line **39** as a particular situation may dictate.

In order to inject gas into zone **13**, the pressure of the separated gas in liner **15** has to be greater than the pressure within zone **13**. Accordingly, the pressure of the carrier liquid-gas mixture at the surface must be sufficient to overbalance the well pressure thereby allowing the mixture to flow down the wellbore **11**. This pressure is dictated by the pressure of the gas supply. Given that pumping liquid is easier than compressing gas, the pressure of the liquid in line **43** is substantially matched to the available gas pressure. The liquid pressure is generated at the surface primarily by pump

5

42 as it pumps the carrier-liquid to mixer 40. By generating the necessary injection pressure through the pumping of liquid, gas compression is substantially reduced or eliminated thereby significantly reducing the costs involved in the gas injection operation.

To further illustrate the present invention, an idealized example of a typical injection operation will now be set forth. Gas is to be injected into an injection zone 13 which has a formation pressure of approximately 3500 psia. Gas is fed to mixer 40 at a rate of 26.7 standard million cubic feet per day at a pressure of approximately 1950 psia while carrier liquid (e.g. water) is pumped into mixer 40 at a rate of 12000 bbls. per day at a pressure of approximately 1950 psia. A carrier-gas mixture having a density of about 21.6 lbs./cu.ft. leaves mixer 40 at a pressure of about 1950 psia and flows down wellbore 11. As the mixture flows through auger separator 25, approximately 75% of the gas will be separated from the mixture and will flow into liner 15 at a pressure of about 3730 psia. Since this pressure is greater than the formation pressure in zone 13, the gas will enter the zone, as is understood in the art. The differential in pressure between that of the mixture 36 as it enters the base of annulus 20 and the pressure at outlet 37 of annulus 20 causes the carrier liquid-unseparated gas mixture 36 to flow back to the surface. The unseparated gas expands as the mixture passes up annulus 20 thus assisting the lifting of the liquids.

FIG. 2 illustrates a further embodiment of the present invention wherein the flowpath is reversed. Well 10a is completed in the same manner as is well 10 in FIG. 1. The gas which is to be injected is mixed with a carrier liquid in mixer 40 in the same manner as described above. However, mixture 34a is now fed down well annulus 20 and through opening(s) 21 in tubing 18 to then flow upward through auger separator 25a. Again, at least a portion of the gas in mixture 34a will separate out of the mixture due to centrifugal force and will flow through opening(s) 32a which is now positioned above the top of blade 30 while the remainder 36a of mixture 34a flows to the surface through tubing 18 and out outlet 37a to separator 38. Separated gas 35a flows down center tube 27 and out the bottom thereof into liner 15 from which it passes through openings 16 into injection zone 13. Again, since the necessary injection pressure is effectively supplied by the supply gas and the pumped carrier liquid, the gas compression requirement at the surface is significantly reduced or eliminated.

What is claimed is:

1. A method for injecting a gas into a subterranean formation comprising:
 - mixing said gas with a carrier fluid at the surface to form a mixture therewith;
 - flowing said mixture down a wellbore which extends from the surface into said subterranean formation;
 - separating at least a portion of said gas from said mixture after said mixture has flowed down said wellbore;
 - injecting said separated portion of said gas into said subterranean formation; and
 - returning the mixture of said carrier fluid and any unseparated gas to said surface.
2. The method of claim 1 wherein said carrier fluid is comprised of water.
3. The method of claim 1 wherein said carrier fluid is comprised of brine.
4. The method of claim 1 wherein said carrier fluid is comprised of oil-based liquids.
5. The method of claim 1 wherein said carrier fluid is comprised of crude oil.

6

6. The method of claim 1 wherein said carrier fluid is comprised of a petrochemical liquid.

7. The method of claim 1 including;

separating said unseparated gas from carrier fluid after said mixture is returned to the surface; and

recycling said separated carrier fluid for mixing with said gas to be injected.

8. In a well having a wellbore extending from the surface into a subterranean formation and having a string of tubing extending within said wellbore with a downhole separator positioned within said tubing at a point substantially adjacent the top of said subterranean formation, a method of injecting gas into said subterranean formation comprising:

mixing said gas with a carrier fluid at the surface to form a mixture therewith;

flowing said mixture through said separator within said tubing to thereby separate at least a portion of said gas from said mixture;

injecting said separated portion of said gas into said subterranean formation; and

returning the mixture of said carrier fluid and any unseparated gas to said surface.

9. The method of claim 8 wherein said carrier liquid is selected from the group of water, brine, oil-based liquids, crudes, petrochemicals, and heavy media.

10. The method of claim 8 wherein said separator is an auger separator.

11. The method of claim 8 wherein said mixture is flowed down said tubing and through said separator and said mixture of said carrier fluid and any unseparated gas is returned to the surface through the annulus which is formed between said tubing and said wellbore.

12. The method of claim 8 wherein said mixture is flowed down said through the annulus which is formed between said tubing and said wellbore and up through said separator and said mixture of said carrier fluid and any unseparated gas is returned to the surface through said tubing.

13. The method of claim 8 including;

separating said unseparated gas from carrier fluid after said mixture is returned to the surface; and

recycling said separated carrier fluid for mixing with said gas to be injected.

14. Apparatus for injecting gas into a subterranean formation, said apparatus comprising:

a well having a wellbore extending from the surface into said subterranean formation;

a string of tubing positioned within said wellbore and extending from said surface to a point substantially adjacent said subterranean formation wherein an annulus is formed between said tubing and said wellbore;

a separator positioned with said tubing near the lower end thereof;

a mixer for mixing said gas with a carrier fluid at the surface to form a mixture thereof;

means for flowing said mixture down through said wellbore and through said separator to thereby separate at least a portion of said gas from said mixture;

means for flowing said separated portion of said gas from said separator into said subterranean formation; and

means for flowing the mixture of said carrier fluid and any unseparated gas back to the surface.

15. The apparatus of claim 14 wherein said separator is an auger separator.

7

16. The apparatus of claim 15 wherein said means for flowing said mixture down through said wellbore comprises: said string of tubing;

and wherein said means for flowing said mixture of said carrier and said any unseparated gas comprises: said annulus between said tubing and said wellbore.

17. The apparatus of claim 15 wherein said means for flowing said mixture down through said wellbore comprises: said annulus between said tubing and said wellbore;

8

and wherein said means for flowing said mixture of said carrier and said any unseparated gas comprises: said string of tubing.

18. The apparatus of claim 15 including:

a separator at the surface for separating said unseparated gas from said mixture of said carrier fluid and any unseparated gas after said mixture is returned to the surface.

* * * * *