



US006062252A

# United States Patent [19]

[11] Patent Number: **6,062,252**

Southern et al.

[45] Date of Patent: **May 16, 2000**

[54] **STABILIZER FOR GAS LINE METER**

[76] Inventors: **David J. Southern**, 919 Nutter Blvd., Billings, Mont. 59105; **Leslie H. Zuck**, 3306 Jack Burke La., Billings, Mont. 59106-1112

[21] Appl. No.: **09/030,656**

[22] Filed: **Feb. 25, 1998**

[51] Int. Cl.<sup>7</sup> ..... **F16L 5/00**

[52] U.S. Cl. .... **137/357**; 137/356; 137/343; 137/316; 137/236.1; 248/548; 248/75

[58] Field of Search ..... 137/343, 357, 137/356, 316, 236.1, 361; 248/75, 548

[56] **References Cited**

**U.S. PATENT DOCUMENTS**

713,974	11/1902	Foreman	.....	137/356
1,607,463	11/1926	Kent	.....	137/316
2,179,416	11/1939	Malear	.....	137/361
2,234,360	3/1941	Whitson	.....	248/548
2,761,286	9/1956	Billue et al.	.....	248/548
3,375,856	4/1968	Howard et al.	.....	137/236.1
4,174,822	11/1979	Larsson	.....	248/75
4,905,939	3/1990	Horn	.....	248/75
4,914,759	4/1990	Goff	.....	248/75


4,998,693	3/1991	Wiebe	.....	248/75
5,007,605	4/1991	Horvath	.....	248/75
5,067,679	11/1991	Courtney	.....	248/75
5,226,456	7/1993	Semak	.....	248/75
5,269,565	12/1993	Langner	.....	248/548
5,533,303	7/1996	Harvey	.....	137/357
5,738,313	4/1998	Rinke	.....	248/75
5,749,179	5/1998	Bohacik	.....	248/75
5,909,861	6/1999	Korson	.....	248/75

*Primary Examiner*—A. Michael Chambers  
*Assistant Examiner*—Thomas L. McShane  
*Attorney, Agent, or Firm*—Richard C. Conover

[57] **ABSTRACT**

An apparatus for preventing a gas meter from settling when fill dirt surrounding a plastic gas line settles with time including a rigid protective sleeve, positioned in surrounding relation to the plastic gas pipe line. A support rod is provided which has one end resting upon a footer of the building. The other end of the support rod is secured to an upper end of the protective sleeve. At the bottom of the protective sleeve, a break-away pipe support fixture is secured to the protective sleeve. The support fixture extends away from the protective sleeve and is positioned to releasably hold a looped slack portion of the plastic gas supply line before the supply line extends into the protective sleeve.

**3 Claims, 4 Drawing Sheets**









Fig. 1




**Fig. 2**




**Fig. 4**




**Fig. 3**



**Fig.7**



**Fig.5**



**Fig.6**




Fig.8

## STABILIZER FOR GAS LINE METER

### BACKGROUND OF THE INVENTION

This invention relates to a device for stabilizing a gas line meter connected to a gas line being led into a building and more specifically to a device that prevents the gas meter from settling as fill dirt surrounding the gas line settles.

When new buildings are built, dirt is removed to provide space for construction of a foundation or below ground floor. If gas is to be used in the building for heating, a gas line, taken from a feeder line, is installed across the space left by the removed dirt into a position adjacent to the foundation wall. An incoming gas supply line is usually made of plastic. Buildings codes generally require that any gas pipes above ground must be made of metal. A transition fitting is fitted to the end of the plastic gas supply line to provide a metal fitting having external threads. Conventional metal pipes can then be screwed to the external threads of the transition fitting. The gas line is then directed upwardly to gas meter above ground for easy access by a gas meter reader. The gas line runs from the meter to a gas line running into the building.

After the gas line is installed in the trench, the removed dirt is placed again in the space from which it was taken covering the gas line in the process. Problems develop when this fill dirt settles. The settling causes the gas line to settle with the dirt pulling the meter to which it is attached downwardly and away from the building. This presents an aesthetic as well as safety problems since the gas line and its connections are also disturbed.

It is an object of the present invention to provide apparatus for preventing a gas meter connected to a gas line from settling with the settling of the gas line.

### SUMMARY OF INVENTION

The present invention relates to an apparatus for preventing a gas meter from settling when fill dirt surrounding the gas line settles with time.

A rigid protective sleeve, preferably constructed of metal, is slipped over the plastic gas pipe line immediately below the transition fitting and extends generally downwardly for a distance into the ground. A support rod is positioned having one end resting upon the footer of the building. The other end of the rod is positioned adjacent the top end of the protective sleeve. A fastener secures the rod to the protective sleeve so the protective sleeve can not drop as the fill dirt settles.

At the bottom of the protective sleeve, a break-away pipe support fixture is secured to the protective sleeve. The support fixture extends away from the protective sleeve and is positioned to releasably hold a looped portion of the plastic gas supply line before the supply line extends into the protective sleeve.

When fill dirt is placed over the apparatus of the present invention, the gas supply line is supported by the support fixture. As the back fill dirt settles, the support fixture breaks away from the gas supply line and the movement of the gas line is accommodated by the loop of gas line held by the support fixture. The protective sleeve is supported by the support rod resting on the footer and will not settle with the gas line. Thus the meter connected to the protective sleeve is protected from settling as well.

### BRIEF DESCRIPTION OF DRAWINGS

In order that the invention may be clearly understood and readily carried into effect, a preferred embodiment of the

invention will now be described, by way of example only, with reference to the accompanying drawings wherein:

FIG. 1 is a schematic elevational view of a gas line meter stabilizer according to the present invention showed in operative relation with a conventional building foundation wall shown in cross-section;

FIG. 2 is an elevational view showing the transition between a protective sleeve and the above ground metal gas line pipe according to the present invention;

FIG. 3 is an elevational view, with parts broken away, of a rod socket connected to a protective sleeve according to the present invention;

FIG. 4 is a cross-sectional view taken along the line 4—4 in FIG. 3;

FIG. 5 is an elevational view with parts broken away, of a pipe support fixture according to the present invention;

FIG. 6 is a cross-sectional view taken along the line 6—6 in FIG. 5;

FIG. 7 is a top plan view of the pipe support fixture as shown in FIG. 5 with parts removed; and

FIG. 8 is a schematic elevational view of a gas line meter stabilizer of the present invention as it appears after fill dirt has settled.

### DESCRIPTION OF A PREFERRED EMBODIMENT

A preferred embodiment of a gas line meter stabilizer apparatus **10** is shown in FIG. 1. Conventionally, gas is supplied to a building through a plastic gas supply line **16** which is connected through a gas meter **12** to the building supply pipe **14**.

A widely used construction technique for erecting a building includes the digging of a trench in which a footer **20** is poured. A foundation wall **22** is then erected on top of footer **20**. Because footer **20** is poured in a trench, fill dirt **24** is back filled between wall **22** and undisturbed soil **26** upon completion of the foundation work.

When a gas supply line is to be installed, the plastic gas supply **16** is conventionally connected to a metal pipe **28** through a transition fitting **30**. The piping **28** is led through shut-off valve **18** and then to meter **12**. From meter **12**, the gas supply line is led through a wall of the building to the inside of the building.

As shown in FIG. 2 a protective sleeve **46** is fitted in surrounding relation to line **16** and is secured at one end to fitting **30** as by welding at **31**. In a preferred embodiment protective sleeve **46** is made of stainless steel.

Plastic gas supply line **16** is led through protective sleeve **46** and conventionally connected (not shown) to piping **28** through fitting **30**. As shown in FIG. 1, a support rod **54** is provided having one end positioned against and lying on top of footer **20**. The upper end of support rod **54** is secured to protective sleeve **46** with rod socket **52** as shown in FIG. 4 which is sized to accept an end of support rod **54**. Support rod socket **52** is securely clamped to protective sleeve **46** by pipe clamp **56**, which in a preferred embodiment is a conventional worm-gear pipe clamp.

A pipe support fixture **58** is secured to the bottom end of protective sleeve **46** as shown in FIG. 1. The fixture **58** in a preferred embodiment is a squared "U" channel member having a web portion **62** extending between parallel upright sidewalls **64**. A hole **66** is drilled in the web portion **62** and is sized to accept protective sleeve **46**. A hole **72** is drilled through web portion **62** and is sized to receive rod **54** as

shown in FIGS. 5 and 7. In a preferred embodiment the pipe support fixture 58 is constructed of metal and is secured to protective sleeve 46 as by welding.

As best seen in FIG. 5, a tubular support 74 is positioned on web 62 between walls 64 as shown in FIGS. 5 and 7. Biodegradable tape 76 is wrapped around a tubular support 74 and the support fixture 58 to secure tubular support 74 in this position. The tubular support 74 is bent as shown in FIG. 5. The plastic line 16 is positioned to have a slack loop 78 as shown in FIG. 1 and a portion of the slack loop is secured to the tubular support 74 with biodegradable tape 76 wrapped around both piping 16 and tubular support 74 to hold the two together.

In a preferred embodiment, biodegradable tape 76 is used to hold the line 16 to pipe support fixture 58 although any other type of break-away connection could also be used. When using biodegradable tape, the tape degrades with time allowing line 16 to break away from pipe support fixture 58.

With the present invention, the gas line 16 may be positioned in a trench during the construction of a building. A slack loop is formed in the gas line pipe and positioned against support 74. Tape or another break-away connector is used to temporarily hold line 16 against support 74 until dirt is back filled. Then as the fill dirt settles with time, line 16 will break-away from pipe support fixture 58. The loop of line 16 will accommodate the settling of line 16 in the fill dirt eliminating the tension on line 16 pulling on meter 12. Further, rod 54 resting on footer 20 which is secured to protective sleeve 46 positively supports meter 12 so that as gas line 16 moves downwardly, the meter 12 will not move with the gas line.

While the fundamental novel features of the invention have been shown and described, it should be understood that

various substitutions, modifications and variations may be made by those skilled in the art without departing from the spirit or scope of the invention. Accordingly, all such modifications or variations are included in the scope of the invention as defined by the following claims.

I claim:

1. A stabilizer for a gas line meter located above a ground surface of dirt and connected to a flexible gas supply line extending beneath the ground surface adjacent a foundation wall joined to a building footer located beneath the ground surface comprising:

a rigid protective sleeve surrounding the gas supply line and extending in a generally vertical direction beneath the ground surface and adjacent the foundation wall; and

a support rod also extending in a generally vertical direction adjacent the foundation wall having first and second ends with the first end resting on top of the footer beneath the ground surface and the second end secured to the protective sleeve at an upper end thereof; whereby when the gas supply line settles downwardly with the dirt, the gas meter is not pulled downwardly with the gas supply line.

2. The stabilizer according to claim 1, further including a pipe holder secured to the protective sleeve at a lower end thereof and a break-away connector for connecting the pipe holder to a portion of a slack loop of the flexible supply line.

3. The stabilizer according to claim 2 wherein the break-away connector comprises biodegradable tape.

\* \* \* \* \*