



US006166710A

# United States Patent [19] Havel

[11] Patent Number: **6,166,710**  
[45] Date of Patent: **Dec. 26, 2000**

[54] **VARIABLE COLOR DISPLAY SYSTEM FOR SEQUENTIALLY EXHIBITING DIGITAL VALUES**

3009416 3/1980 Germany .  
57-146112 9/1982 Japan .  
2158631A 10/1985 United Kingdom .

### OTHER PUBLICATIONS

[75] Inventor: **Karel Havel**, Bramalea, Canada

Wagner, B., "2-color LED+Driver=Versatile Visual Effects", EDN vol. 25, No. 19, Oct, 20, 1980.

[73] Assignee: **Texas Digital Systems, Inc.**

Smithline, L.M., "Dual light emitting diode synthesizes polychromatic light", Electronics, Aug. 16, 1979, p. 130.

[21] Appl. No.: **09/335,970**

Svestka, M. et al., "LEDs change color to indicate balance voltage", Electronic Engineering, vol. 48, No. 576, p. 19, Feb. 1976.

[22] Filed: **Jun. 18, 1999**

Saitoh, T. et al. "Multicolor light-emitting diodes with double junction structure". IEEE Transactions on Electron Devices, Feb. 1975, vol. ED-22, No. 2, pp. 29-32.

### Related U.S. Application Data

[62] Division of application No. 08/910,080, Aug. 12, 1997, Pat. No. 6,018,237, which is a division of application No. 08/571,246, Dec. 12, 1995, Pat. No. 5,656,935, which is a division of application No. 08/187,350, Jan. 27, 1994, Pat. No. 5,475,300, which is a division of application No. 07/865,460, Apr. 9, 1992, Pat. No. 5,283,517, which is a division of application No. 07/628,328, Dec. 14, 1990, Pat. No. 5,122,733, which is a division of application No. 07/197,322, May 23, 1988, abandoned, which is a division of application No. 06/819,111, Jan. 15, 1986, Pat. No. 4,794,383.

Yamaguchi, T. et al, "A High Brightness Gap Multicolor LED", IEEE Transactions on Electron Devices, vol. ED-28, No. 5, May 1981, p. 588-592.

[51] Int. Cl.<sup>7</sup> ..... **G09G 3/14**

Baker, M., "Chip changes the color of light-emitting diodes", Electronics, Apr. 7, 1981, p. 158-159.

[52] U.S. Cl. .... **345/46; 345/33; 345/34; 345/39**

Rao, V., Two LEDs blend and blink to indicate six states. Electronic Design, vol. 30, No. 16, p. 220, Aug. 5, 1982.

[58] Field of Search ..... **340/815.43, 815.44, 340/815.45, 815.56; 345/33, 34, 38, 30, 39, 40, 44, 46, 48**

Kojima, T. "Recent flat panel development in Japan", held in San Diego, CA, Apr. 29-May 1, 1980. SID 80 Digest, p. 22-23.

(List continued on next page.)

### [56] References Cited

#### U.S. PATENT DOCUMENTS

2,643,344 6/1953 McLaren et al. .  
2,648,015 8/1953 Greenfield et al. .  
2,682,000 6/1954 Clayton et al. .  
2,878,450 3/1959 Rabier .  
2,889,518 6/1959 Hudson et al. .

(List continued on next page.)

#### FOREIGN PATENT DOCUMENTS

220844A 1/1984 German Dem. Rep. .  
3037-500 10/1979 Germany .

Primary Examiner—Richard A. Hjerpe


Assistant Examiner—Kevin M. Nguyen

Attorney, Agent, or Firm—Winstead, Sechrest & Minick

### [57] ABSTRACT

A variable color display systems sequentially exhibits digital values in a color in accordance with the relation of the presently exhibited digital value to a past digital value. A memory, controlled by a timer, is provided for storing data representing the past digital value. A comparator compares the presently exhibited digital value with the data stored in the memory and develops a comparison signal accordingly, which is then used to control the color of the presently exhibited digital value.

24 Claims, 69 Drawing Sheets



## U.S. PATENT DOCUMENTS

3,516,724	6/1970	Ashton .....	350/96	4,720,709	1/1988	Imamura et al. .
3,595,991	7/1971	Diller .		4,725,828	2/1988	Cowlishaw .
3,719,849	3/1973	Steward .		4,740,818	4/1988	Tsilibes et al. .
3,740,570	6/1973	Kaelin et al. .		4,752,771	6/1988	Katogi et al. ....
3,760,174	9/1973	Boening et al. .		4,771,274	9/1988	Havel .
3,771,155	11/1973	Hayashi et al. .		4,831,326	5/1989	Havel .
3,840,873	10/1974	Usui .		5,003,298	3/1991	Havel .
3,873,979	3/1975	Craford et al. .				
3,911,418	10/1975	Takeda .				
3,924,227	12/1975	Stolov .....	340/336			
3,975,726	8/1976	Kawakami .				
4,044,546	8/1977	Koike .....	58/50 R			
4,086,514	4/1978	Havel .				
4,271,408	6/1981	Teshima et al. .				
4,295,127	10/1981	Sautter .....	340/373			
4,301,450	11/1981	Smoliar .				
4,360,804	11/1982	Ohura .				
4,488,149	12/1984	Givens, Jr. .				
4,559,480	12/1985	Nobs .				
4,581,612	4/1986	Jones .				
4,647,217	3/1987	Havel .				
4,689,613	8/1987	Ikeda .				
4,709,230	11/1987	Popowski et al. .				

## OTHER PUBLICATIONS

Niina, T. et al, "A multi-color GaP LED flat panel display device" New York, NY, USA, Apr. 28-30, 1981. 1981 SID International Symposium Digest of Papers, vol. XII (1981), p. 140-141.

Niina, T. et al, "A multi-color LED flat panel display device for colorful displays of letters and figures". Proceedings of the SID, vol. 23, No. 2, p. 73-76, 1982.

O'Mara, P.A. et al, "Microprocessor-controlled light-emitting diode dark adaptometer". Medical & Biological Engineering and Computing, vol. 20, No. 1, p. 70-76, 1982.

Landauer, R. W., "Electroluminescent Display", IBM Technical Disclosure Bulletin, vol. 8, No. 11, pp. 15-16, Apr. 11, 1966.

SenSym Solid State Barometers Catalog, p. 9-30, 1983.

PRIOR ART




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11






FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 26






FIG. 25




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36






FIG. 37






FIG. 39





ICI CHROMATICITY DIAGRAM

FIG. 40




FIG. 41





FIG. 42






FIG. 44




FIG. 45






FIG. 46





FIG. 47






FIG. 49







FIG. 50












FIG. 54




FIG. 55




FIG. 56





FIG. 57






FIG. 59




FIG. 60




FIG. 61







FIG. 62







FIG. 64






FIG. 66




FIG. 67




FIG. 68




FIG. 69




FIG. 70




FIG. 71






FIG. 72




FIG. 73




FIG. 74




FIG. 75





FIG. 76



RMS AND CREST FACTOR CHART

FIG. 77




FIG. 78




FIG. 79




FIG. 80




FIG. 81






FIG. 82




FIG. 83




FIG. 84




FIG. 85




FIG. 86




FIG. 87




FIG. 88





FIG. 89



**VARIABLE COLOR DISPLAY SYSTEM FOR  
SEQUENTIALLY EXHIBITING DIGITAL  
VALUES**

**CROSS-REFERENCE TO RELATED  
APPLICATIONS**

This is a division of my application Ser. No. 08/910,080, filed on Aug. 12, 1997, entitled Variable Color Display System, now U.S. Pat. No. 6,018,237 which is a division of my application Ser. No. 08/571,246, filed on Dec. 12, 1995, entitled Variable Color Display System, now U.S. Pat. No. 5,656,935 issued on Aug. 12, 1997, which is a division of my application Ser. No. 08/187,350, filed on Jan. 27, 1994, entitled Variable Color Digital Multimeter, now U.S. Pat. No. 5,475,300 issued on Dec. 12, 1995, which is a division of my application Ser. No. 07/865,460, filed on Apr. 9, 1992, entitled Variable Color Digital Multimeter, now U.S. Pat. No. 5,283,517 issued on Feb. 1, 1994, which is a division of my application Ser. No. 07/628,328, filed on Dec. 14, 1990, entitled Variable Color Digital Multimeter, now U.S. Pat. No. 5,122,733 issued on Jun. 16, 1992, which is a division of my application Ser. No. 07/197,322, filed on May 23, 1988, entitled Variable Color Digital Multimeter, now abandoned, which is a division of my application Ser. No. 06/819,111, filed on Jan. 15, 1986, entitled Variable Color Digital Multimeter, now U.S. Pat. No. 4,794,383 issued on Dec. 27, 1988.

Reference is also made to my related applications Ser. No. 06/817,114, filed on Jan. 8, 1986, entitled Variable Color Digital Timepiece, now U.S. Pat. No. 4,647,217 issued on Mar. 3, 1987, Ser. No. 06/919,425, filed on Oct. 16, 1986, entitled Electronic Timepiece with transducers, now U.S. Pat. No. 4,687,340 issued on Aug. 18, 1987, Ser. No. 06/926,511, filed on Nov. 3, 1986, entitled Electronic Timepiece with Physical Transducer, now U.S. Pat. No. 4,705,406 issued on Nov. 10, 1987, Ser. No. 07/150,913, filed on Feb. 1, 1988, entitled Variable Color Display Typewriter, now U.S. Pat. No. 4,824,269 issued on Apr. 25, 1989, Ser. No. 07/336,080, filed on Apr. 11, 1989, entitled Variable Color Display Typewriter, now U.S. Pat. No. 4,934,852 issued on Jun. 19, 1990, Serial No. 06/839,526, filed on Mar. 14, 1986, entitled Variable Color Display Telephone, now U.S. Pat. No. 4,726,059 issued on Feb. 16, 1988, Ser. No. 06/940/100, filed on Dec. 10, 1986, entitled Digital Voltmeter with Variable Color Background, now U.S. Pat. No. 4,831,326 issued on May 16, 1989, Ser. No. 06/922,847, filed on Oct. 24, 1986, entitled Continuously Variable Color Display Device, now U.S. Pat. No. 4,845,481 issued on Jul. 4, 1989, Ser. No. 07/322,341, filed on Mar. 13, 1989, entitled Continuously Variable Color Optical Device, now U.S. Pat. No. 4,965,561 issued on Oct. 23, 1990, Ser. No. 07/379,616, filed on Jul. 14, 1989, entitled Variable Color Digital Display for Emphasizing Position of Decimal Point, now U.S. Pat. No. 5,003,298 issued on Mar. 26, 1991, Ser. No. 06/920,740, filed on Oct. 20, 1986, entitled Step Variable Color Display Device, now abandoned, Ser. No. 06/931,626, filed on Nov. 17, 1986, entitled Variable Color Hybrid Display Device, now abandoned, Ser. No. 07/157,603, filed on Feb. 19, 1988, entitled Variable Color Multiplexed Display System, now abandoned, and Ser. No. 07/000,478, filed on Jan. 5, 1987, entitled Variable Color Digital Tachometer, now abandoned, which describe the devices employing a variable color display.

**BACKGROUND OF THE INVENTION**

1. Field of the Invention

This invention relates to display systems utilizing a variable color digital display.

2. Description of the Prior Art

A display device described in U.S. Pat. No. 3,740,570, issued on Jun. 19, 1973 to George R. Kaelin et al., uses special LEDs that exhibit different colors when subjected to different currents. The LEDs are biased by pulses of different amplitudes, to achieve different colors of the display, and by the length inversely proportional to the pulse amplitude, to compensate for variable brightness of the display caused by different amplitudes of the pulses.

A circuit employing a dual-color LED driven by a dual timer is described in the article by Bill Wagner entitled 2-color LED +driver = versatile visual effects, published on Oct. 2, 1980 in EDN volume 25, No. 19, page 164. Since dual-color LEDs are connected to conduct currents in opposite directions, it would be impossible to forwardly bias them simultaneously.

An electronic display having segments wherein each segment is capable of selectively illuminating two colors is disclosed in U.S. Pat. No. 4,488,149 issued on Dec. 11, 1984 to William A. Givens, Jr. Two AND gates are provided for biasing, in each display segment, either a first light emitting diode, for emitting a first color, or a second light emitting diode, for emitting a second color. It is not contemplated to illuminate both light emitting diodes in each segment simultaneously for blending the colors.

A multi-colour LED display for seven segment figures is disclosed in German Patent No. 3,009,416 issued on Sep. 17, 1981 to Klaus Gillessen. The LED circuit consists of seven group of diodes, each group made up of two diodes, one red and one green. The cathodes of all red diodes are terminated in a common connection, and the green ones likewise, the anodes of each pair of diodes being common for that pair. Two transistors connected in cascade are utilized for activating either all green LEDs, or all red LEDs, but not both simultaneously. When a low level signal is applied to the base of the first transistor, the first transistor is blocked, and the second transistor is turned ON to illuminate the second set of the diodes. When a high level signal is applied to the input of the first transistor, the first transistor is turned ON, while the second transistor is blocked, whereby the first set of the diodes is illuminated. Since the first transistor cannot be simultaneously turned ON and OFF, it would be impossible to illuminate the two sets of the diodes simultaneously. In another embodiment is shown a multi-colour LED display utilizing three sets of LEDs: red, green, and blue, which are respectively commonly connected and may be activated by manual switches. It is not contemplated that the three sets of LEDs be activated in selective combinations to blend the colors.

A digital electrooptical display with anti-parallel light emitting diodes is disclosed in East German Patent No. 220,844 issued on Apr. 10, 1985 to Thomas Hoffmann et al. Two light emitting diodes for emitting light of different colors are connected in each segment back-to-back. Since the light emitting diodes are connected to conduct currents in opposite directions, it would be impossible to illuminate them simultaneously, because the opposite currents attempting to pass through a single conductor would cancel.

A system for measuring radioactivity is described in U.S. Pat. No. 2,643,344, issued on Jun. 23, 1953 to Ian H. McLaren et al. Another systems for measuring radioactivity



are described in U.S. Pat. No. 2,648,015 issued on Aug. 4, 1953 to Alexander Greenfield et al., and in U.S. Pat. No. 2,682,000 issued on Jun. 22, 1954 to Joseph F. Clayton et al. Since these three patents are very similar, they are equally authoritative. The system for measuring radioactivity, disclosed in the three patents, includes an analog pointer indicator having three scales, with three associated colored light bulbs, for indicating which scale is applicable for the reading of the measured value. A mechanism for automatic range selection is provided, which is controlled by two solenoids, and which also controls the three associated colored light bulbs. In response to the range selection, one of the light bulbs illuminates the indicator face with a distinctive color to indicate which measurement scale is applicable.

The prior art variable color display systems do not contemplate that the indication of the presently exhibited digital value may be colored in accordance with its relation to a past digital value.

### SUMMARY OF THE INVENTION

In a broad sense, it is the principal object of this invention to provide an improved variable color digital display system.

It is another object of the invention to provide a variable color digital display system for sequentially exhibiting digital values.

It is still another object of the invention to provide a variable color digital display system with a memory for storing from time to time the exhibited values.

It is still another object of the invention to provide a variable color digital display system with a comparator for comparing the exhibited values with the values stored in the memory.

It is still another object of the invention to provide a variable color digital display system for controlling the color of the exhibited values in accordance with their relation to the values stored in a memory.

It is still another object of the invention to provide a variable color digital display system for controlling the color of the exhibited values in accordance with their relation to the values previously exhibited.

In summary, a variable color digital display system of the invention includes an a plurality of adjacent variable color light emitting diode digital display elements for sequentially providing a digital indication of a first digital value and of a second digital value, in a timing relationship determined by a timer.

The invention resides in the provision of a memory, for storing the previously exhibited value, of a comparator, for performing a comparison of the presently exhibited value with the value stored in the memory, and of a color control, for controlling the color of the digital indication in accordance with the result of the comparison.

### BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings in which are shown several possible embodiments of the invention,

FIG. 1 is a block diagram of a typical prior art monochromatic digital display system.

FIG. 2 is a generalized block diagram of a variable color digital display system for the practice of the present invention.

FIG. 3 is a block diagram of a step variable color display system.

FIG. 4 is a block diagram of a continuously variable color display system.

FIG. 5 is a block diagram of 2-primary color digital display.

FIG. 6 is a block diagram of 3-primary color digital display.

FIG. 7 is an enlarged detail of one digit of 2-primary color digital display.

FIG. 8 is an enlarged cross-sectional view of one display segment in FIG. 7, taken along the line 8—8.

FIG. 9 is an enlarged detail of one digit of 3-primary color digital display.

FIG. 10 is an enlarged cross-sectional view of one display segment in FIG. 9, taken along the line 10—10.

FIG. 11 is a schematic diagram of one digit of 2-primary color control circuit of this invention.

FIG. 12 is a schematic diagram of one digit of 3-primary color control circuit of this invention.

FIG. 13 is a block diagram of a color control logic circuit for controlling 2-primary color display.

FIG. 14 is a block diagram of a color control logic circuit for controlling 3-primary color display.

FIG. 15 is a schematic diagram of a color control logic circuit for controlling 2-primary color display.

FIG. 16 is a schematic diagram of a color control logic circuit for controlling 3-primary color display.

FIG. 17 is a simplified schematic diagram, similar to FIG. 11, showing how the number '7' can be displayed in three different colors.

FIG. 18 is a simplified schematic diagram, similar to FIG. 12, showing how the number '1' can be displayed in seven different colors.

FIG. 19 is a block diagram of 2-primary color 4-digit display.

FIG. 20 is a block diagram of 3-primary color 4-digit display.

FIG. 21 is a block diagram of a signal converter for 2-primary color display.

FIG. 22 is a block diagram of a signal converter for 3-primary color display.

FIG. 23 is a schematic diagram of a comparator circuit for 2-primary color display.

FIG. 24 is a graph showing the relationship between the inputs and outputs of the comparator circuit in FIG. 23.

FIG. 25 is a schematic diagram of a comparator circuit for 3-primary color display.

FIG. 26 is a graph showing the relationship between the inputs and outputs of the comparator circuit in FIG. 25.

FIG. 27 is a block diagram of a continuously variable color display system utilizing two primary colors.

FIG. 28 is a block diagram of a continuously variable color display system utilizing three primary colors.

FIG. 29 is an expanded block diagram of FIG. 27.

FIG. 30 is an expanded block diagram of FIG. 28.

FIG. 31 is a schematic diagram of a scaling circuit.

FIG. 32 is a schematic diagram of an A/D converter and memory combination of FIGS. 29 and 30.

FIG. 33 is a schematic diagram of a memory and color converter combination of FIG. 29.

FIG. 34 is a timing diagram of the circuit shown in FIG. 33.

FIG. 35 is a schematic diagram of a memory and color converter combination of FIG. 30.

FIG. 36 is a timing diagram of the circuit shown in FIG. 35.

FIG. 37 is a continuation of the timing diagram of FIG. 36.

FIG. 38 is a graphic representation of TABLE 1.

FIG. 39 is a graphic representation of TABLE 2.

FIG. 40 is a graph of the ICI chromaticity diagram.

FIG. 41 is a block diagram of a multimeter with variable color digital display.

FIG. 42 is a block diagram of a multimeter with multiplexed variable color digital display.

FIG. 43 is a block diagram of a digital multimeter with a display that can change color in accordance with external control.

FIG. 44 is a block diagram of a digital multimeter with a display that can change color in accordance with internal control.

FIG. 45 is a block diagram of a digital multimeter with a display that can change color in accordance with measurement quantity.

FIG. 46 is a block diagram of a digital multimeter with a display that can change color in accordance with measurement location.

FIG. 47 is a simplified schematic diagram of a variable color digital multimeter for measuring outputs of different transducers.

FIG. 48 is a simplified schematic diagram of a variable color digital multimeter for measuring signals from different locations.

FIG. 49 is a simplified schematic diagram of a variable color digital multimeter for measuring signals by different methods.

FIG. 50 is a simplified schematic diagram of a variable color digital thermometer.

FIG. 51 is a simplified schematic diagram of a digital amperimeter with variable color range indication.

FIG. 52 is a simplified schematic diagram of a digital voltmeter with variable color range indication.

FIG. 53 is a simplified schematic diagram of a digital ohmmeter with variable color range indication.

FIG. 54 is a detail of the multimeter shown in FIGS. 51, 52, and 53.

FIG. 55 is a simplified schematic diagram of a digital voltmeter for displaying positive and negative measurement results in respectively different colors.

FIG. 56 is a simplified schematic diagram of a variable color display system for displaying decimal numbers such that digits preceding and following the decimal point are displayed in respectively different colors.

FIG. 57 is a timing diagram of the circuit shown in FIG. 56.

FIG. 58 is a simplified schematic diagram of a variable color display system for displaying integers and decimal numbers in respectively different colors.

FIG. 59 is a block diagram of a variable color display device for selectively displaying output digital data from different digital devices in respectively different colors.

FIG. 60 is a simplified schematic diagram of a variable color digital barometer.

FIG. 61 is a simplified schematic diagram of a digital multimeter for displaying measurement results in accordance with time.

FIG. 62 is a block diagram of a variable color digital multimeter with comparator and memory.

FIG. 63 is a block diagram of a variable color digital multimeter with comparator and memory for high and low limits.

FIG. 64 is a block diagram of a variable color digital multimeter with comparator and memory for previous measurement values.

FIG. 65 is a block diagram of a variable color digital multimeter with memory for previous measurement errors.

FIG. 66 is a schematic diagram of a comparator with low and high measurement limits.

FIG. 67 is a schematic diagram of a comparator and error counter.

FIG. 68 is a detail of the comparator, error flip-flop, and color control combination.

FIG. 69 is a detail of the comparator, error memory, and color converter combination.

FIG. 70 is a detail of the low measurement limit memory and comparator combination.

FIG. 71 is a detail of the error counter and PROM combination.

FIG. 72 is a schematic diagram of a variable color digital multimeter with registered comparator for comparing instant measured values with previously stored ones.

FIG. 73 is a block diagram of a variable color digital multimeter with uniform color control for all display digits.

FIG. 74 is a block diagram of a variable color digital multimeter with independent color control for each display digit.

FIG. 75 is a block diagram of a dual digital voltmeter with single variable color digital display.

FIG. 76 is a block diagram of a variable color RMS digital voltmeter with variable color crest factor indication.

FIG. 77 is the RMS and crest factor chart.

FIG. 78 is an expanded block diagram of a crest factor converter with ratio producing circuit.

FIG. 79 is an expanded block diagram of a crest factor converter with precision divider.

FIG. 80 is a schematic diagram of an RMS-to-DC converter.

FIG. 81 is a schematic diagram of a peak detector.

FIG. 82 is an expanded block diagram of 2-primary color control for the crest factor converter.

FIG. 83 is an expanded block diagram of 3-primary color control for the crest factor converter.

FIG. 84 is an expanded block diagram of 2-primary color converter for the crest factor converter.

FIG. 85 is an expanded block diagram of 3-primary color converter for the crest factor converter.

FIG. 86 is a front view of a variable color digital multimeter of the present invention.

FIG. 87 is a block diagram of a variable color digital multimeter controlled by a microprocessor.

FIG. 88 is an expanded block diagram of a variable color digital multimeter for indicating front and rear measurements in different colors.

FIG. 89 is an expanded block diagram of a variable color digital multimeter for indicating DC, AC, and OHMS measurements in respectively different colors.

FIG. 90 is an expanded block diagram of a variable color digital multimeter for indicating measurements with filter and without filter in different colors.

Throughout the drawings, like characters indicate like parts.

#### BRIEF DESCRIPTION OF THE TABLES

In the tables which show examples of the relationship between an input voltage, memory contents, and resulting color in the color converter of the present invention, TABLE 1 shows the characteristic of a step variable 2-primary color converter.

TABLE 2 shows a rainbow-like characteristic of a continuously variable 3-primary color converter.

Throughout the tables, memory addresses and data are expressed in a well known hexadecimal notation.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now, more particularly, to the drawings, in FIG. 1 is shown a block diagram of a typical prior art digital display system which usually includes a device 10a for developing digital data, a suitable decoder 20 for converting the digital data into a displayable code, and a monochromatic digital display 30 for indicating the digital data visually.

As shown in FIG. 2, the present invention resides in the substitution of a commercially well known monochromatic digital display with a variable color digital display 40, and in the addition of a color control circuit 50 for controlling the color of display 40. The variable color digital display system of this invention can simultaneously indicate the values of two different quantities, from the outputs of respective devices 10b, 10c, by causing the value of the first quantity to be indicated on display 40 in digital format, and by controlling the color of display 40 in accordance with the value of the second quantity.

In FIG. 3 is shown a block diagram of another embodiment of a variable color digital display system of the present invention, characterized by a step variable color control circuit 51.

In FIG. 4 is shown a block diagram of still another embodiment of variable color digital display system, characterized by a continuously variable color control circuit 56.

In FIG. 5 is shown a block diagram of a 2-primary color display system including a commercially well known 7-segment display decoder driver 22, a variable color 7-segment display element 42, and a 2-primary color control logic circuit 52. The decoder driver 22 accepts a 4-bit BCD (binary coded decimal) code at its inputs A0, A1, A2, A3 and develops output drive signals at its outputs a, b, c, d, e, f, g, and DP (decimal point) to drive respective segments of 7-segment display element 42. The color control circuit 52 accepts color control logic signals at its inputs R (red), Y (yellow), and G (green) and develops at its outputs drive signals for red bus 5 and green bus 6, respectively, to illuminate display element 42 in a selected color.

In FIG. 6 is shown a block diagram of a 3-primary color display system including a 7-segment display decoder driver 22, variable color 7-segment display element 43, and a 3-primary color control logic circuit 53. The color control circuit 53 accepts color control logic signals at its inputs R (red), Y (yellow), G (green), BG (blue-green), B (blue), P (purple), and W (white) and develops at its outputs drive signals for red bus 5, green bus 6, and blue bus 7, respectively, to illuminate display element 43 in a selected color.

In FIG. 7, the 2-primary color display element includes seven elongated display segments a, b, c, d, e, f, and g,

arranged in a conventional pattern, which may be selectively energized in different combinations to display the desired digits. Each display segment includes a pair of LEDs (light emitting diodes): red LED 2 and green LED 3, which are closely adjacent such that the light signals emitted therefrom are substantially superimposed upon each other to mix the colors. To facilitate the illustration, the LEDs are designated by segment symbols, e.g., the red LED in the segment a is designated as 2a, etc.

In FIG. 8, red LED 2e and green LED 3e are placed on the base of a segment body 15a which is filled with a transparent light scattering material 16. When forwardly biased, LEDs 2e and 3e emit light signals of red and green colors, respectively, which are scattered within transparent material 16, thereby blending the red and green light signals into a composite light signal that emerges at the upper surface of segment body 15a. The color of the composite light signal may be controlled by varying the portions of the red and green light signals.

In FIG. 9, each display segment of the 3-primary color display element includes a triad of LEDs: red LED 2, green LED 3, and blue LED 4, which are closely adjacent such that the light signals emitted therefrom are substantially superimposed upon one another to mix the colors.

In FIG. 10, red LED 2e, green LED 3e, and blue LED 4e are placed on the base of a segment body 15b which is filled with a transparent light scattering material 16. Red LEDs are typically manufactured by diffusing a p-n junction into a GaAsP epitaxial layer on a GaAs substrate; green LEDs typically use a GaP epitaxial layer on a GaP substrate; blue LEDs are typically made from SiC material.

When forwardly biased, LEDs 2e, 3e, and 4e emit light signals of red, green, and blue colors, respectively, which are scattered within transparent material 16, thereby blending the red, green, and blue light signals into a composite light signal that emerges at the upper surface of segment body 15b. The color of the composite light signal may be controlled by varying the portions of the red, green, and blue light signals.

In FIG. 11 is shown a schematic diagram of a 2-primary color common cathodes 7-segment display element 42 which can selectively display various digital fonts in different colors on display segments a, b, c, d, e, f, g, and DP (Decimal Point). The anodes of all red and green LED pairs are interconnected in each display segment and are electrically connected to respective outputs of a commercially well known common-cathode 7-segment decoder driver 23. The cathodes of all red LEDs 2a, 2b, 2c, 2d, 2e, 2f, 2g, and 2i are interconnected to a common electric path referred to as a red bus 5. The cathodes of all green LEDs 3a, 3b, 3c, 3d, 3e, 3f, 3g, and 3i are interconnected to a like common electric path referred to as a green bus 6.

The red bus 5 is connected to the output of a tri-state inverting buffer 63a, capable of sinking sufficient current to forwardly bias all red LEDs 2a to 2i in display element 42. The green bus 6 is connected to the output of a like buffer 63b. The two buffers 63a, 63b can be simultaneously enabled by applying a low logic level signal to the input of inverter 64a, and disabled by applying a high logic level signal thereto. When buffers 63a, 63b are enabled, the conditions of red bus 5 and green bus 6 can be selectively controlled by applying suitable logic control signals to the bus control inputs RB (red bus) and GB (green bus), to illuminate display element 42 in a selected color. When the buffers 63a, 63b are disabled, both red bus 5 and green bus 6 are effectively disconnected to cause display element 42 to be completely extinguished.

In FIG. 12 is shown a schematic diagram of a 3-primary color common anodes 7-segment display element 43 which can selectively display digital fonts in different colors. The cathodes of all red, green, and blue LED triads in each display segment are interconnected and electrically connected to respective outputs of a commercially well known common anode 7-segment decoder driver 24. The anodes of all red LEDs 2a, 2b, 2c, 2d, 2e, 2f, and 2g are interconnected to form a common electric path referred to as a red bus 5. The anodes of all green LEDs 3a, 3b, 3c, 3d, 3e, 3f, and 3g are interconnected to form a like common electric path referred to as a green bus 6. The anodes of all blue LEDs 4a, 4b, 4c, 4d, 4e, 4f, and 4g are interconnected to form a like common electric path referred to as a blue bus 7.

The red bus 5 is connected to the output of a non-inverting tri-state buffer 62a, capable of sourcing sufficient current to illuminate all red LEDs 2a to 2g in display element 43. The green bus 6 is connected to the output of a like buffer 62b. The blue bus 7 is connected to the output of a like buffer 62c. The three buffers 62a, 62b, and 62c can be simultaneously enabled, by applying a low logic level signal to the input of inverter 64b, and disabled by applying a high logic level signal thereto. When buffers 62a, 62b, and 62c are enabled, the conditions of red bus 5, green bus 6, and blue bus 7 can be selectively controlled by applying valid combinations of logic level signals to the bus control inputs RB (red bus), GB (green bus), and BB (blue bus), to illuminate display element 43 in a selected color. When buffers 62a, 62b, and 62c are disabled, red bus 5, green bus 6, and blue bus 7 are effectively disconnected to cause display element 43 to be completely extinguished.

#### Step Variable Color Control

In FIG. 13 is shown a logic circuit 69a for developing drive signals for red bus 5 and green bus 6, to control the color of display element 42 shown in FIG. 11. Two voltage levels, referred to as logic high and low, are used throughout the description of the digital circuits. The color of display element 42 may be controlled by applying valid combinations of logic level signals to its color control inputs R (red), Y (yellow), and G (green). The logic circuit 69a combines the input signals in a logic fashion and develops output drive signals RB (red bus) and GB (green bus), for activating red bus 5 and green bus 6, respectively, of display element 42.

In FIG. 14 is shown a like logic circuit 69b for developing drive signals for red bus 5, green bus 6, and blue bus 7, to control the color of display element 43 shown in FIG. 12. The color of display element 43 may be controlled by applying valid combinations of logic level signals to its color control inputs B (blue), P (purple), BG (blue-green), G (green), Y (yellow), W (white), and R (red). The logic circuit 69b combines the input signals in a logic fashion and develops output drive signals RB (red bus), GB (green bus), and BB (blue bus), for activating red bus 5, green bus 6, and blue bus 7, respectively, of display element 43.

Exemplary schematic diagrams of the color control logic circuits shown in FIGS. 15 and 16 consider active high logic levels, which means that only the selected color control input is maintained at a high logic level, while all remaining color control inputs are maintained at a low logic level. The circuit in FIG. 15 is a detail of the color control logic circuit 69a employing 2-input logic OR gates 60a and 60b, interposed between the color control inputs R, Y, G and bus control outputs RB, GB, in a manner which will become more apparent from the description below. A like circuit in FIG. 16 is a detail of the color control logic circuit 69b

employing 4-input logic OR gates 61a, 61b, and 61c similarly interposed between the color control inputs B, P, BG, G, Y, W, R and bus control outputs RB, GB, BB. It will be obvious to those skilled in the art that other types of logic devices may be effectively used.

The operation of display element 42 shown in FIG. 11 will be now explained by the example of illuminating a digit '7' in three different colors. A simplified schematic diagram to facilitate the explanation is shown in FIG. 17. Any digit between 0 and 9 can be selectively displayed by applying the appropriate BCD code to the inputs A0, A1, A2, and A3 of common-cathode 7-segment decoder driver 23. The decoder driver 23 develops at its outputs a, b, c, d, e, f, g, and DP drive signals for energizing selected groups of the segments to thereby visually display the selected number, in a manner well known to those having ordinary skill in the art. To display decimal number '7', a BCD code 0111 is applied to the inputs A0, A1, A2, and A3. The decoder driver 23 develops high voltage levels at its outputs a, b, and c, to illuminate equally designated segments a, b, and c, and low voltage levels at all remaining outputs (not shown), to extinguish all remaining segments d, e, f, and g.

To illuminate display element 42 in red color, the color control input R is raised to a high logic level, and the color control inputs Y and G are maintained at a low logic level. As a result, the output of OR gate 60a rises to a high logic level, thereby causing the output of buffer 63a to drop to a low logic level. The current flows from the output a of decoder driver 23, via red LED 2a and red bus 5, to current sinking output of buffer 63a. Similarly, the current flows from the output b of decoder driver 23, via red LED 2b and red bus 5, to the output of buffer 63a. The current flows from the output c of decoder driver 23, via red LED 2c and red bus 5, to the output of buffer 63a. As a result, segments a, b, and c illuminate in red color, thereby causing a visual impression of a character '7'. The green LEDs 3a, 3b, 3c remain extinguished because the output of buffer 63b is at a high logic level, thereby disabling green bus 6.

To illuminate display element 42 in green color, the color control input G is raised to a high logic level, while the color control inputs R and Y are maintained at a low logic level. As a result, the output of OR gate 60b rises to a high logic level, thereby causing the output of buffer 63b to drop to a low logic level. The current flows from the output a of decoder driver 23, via green LED 3a and green bus 6, to current sinking output of buffer 63b. Similarly, the current flows from the output b of decoder driver 23, via green LED 3b and green bus 6, to the output of buffer 63b. The current flows from the output c of decoder driver 23, via green LED 3c and green bus 6, to the output of buffer 63b. As a result, segments a, b, and c illuminate in green color. The red LEDs 2a, 2b, and 2c remain extinguished because the output of buffer 63a is at a high logic level, thereby disabling red bus 5.

To illuminate display element 42 in yellow color, the color control input Y is raised to a high logic level, while the color control inputs R and G are maintained at a low logic level. As a result, the outputs of both OR gates 60a and 60b rise to a high logic level, thereby causing the outputs of both buffers 63a and 63b to drop to a low logic level. The current flows from the output a of decoder driver 23, via red LED 2a and red bus 5, to current sinking output of buffer 63a, and, via green LED 3a and green bus 6, to current sinking output of buffer 63b. Similarly, the current flows from the output b of decoder driver 23, via red LED 2b and red bus 5, to the output of buffer 63a, and, via green LED 3b and green bus 6, to the output of buffer 63b. The current flows from the

output c of decoder driver 23, via red LED 2c and red bus 5, to the output of buffer 63a, and, via green LED 3c and green bus 6, to the output of buffer 63b. As a result of blending light of red and green colors in each segment, segments a, b, and c illuminate in substantially yellow color.

The operation of display element 43 shown in FIG. 12 will be now explained by the example of illuminating a digit '1' in seven different colors. A simplified schematic diagram to facilitate the explanation is shown in FIG. 18. To display decimal number '1', a BCD code 0001 is applied to the inputs A0, A1, A2, and A3 of common anode 7-segment decoder driver 24. The decoder driver 24 develops low voltage levels at its outputs b and c, to illuminate equally designated segments b and c, and high voltage levels at all remaining outputs (not shown), to extinguish all remaining segments a, d, e, f, and g.

To illuminate display element 43 in red color, the color control input R is raised to a high logic level, while all remaining color control inputs are maintained at a low logic level. As a result, the output of OR gate 61a rises to a high logic level, thereby causing the output of buffer 62a to rise to a high logic level. The current flows from the output of buffer 62a, via red bus 5 and red LED 2b, to the output b of decoder driver 24, and, via red LED 2c, to the output c of decoder driver 24. As a result, segments b and c illuminate in red color, thereby causing a visual impression of a character '1'. The green LEDs 3b, 3c and blue LEDs 4b, 4c remain extinguished because green bus 6 and blue bus 7 are disabled.

To illuminate display element 43 in green color, the color control input G is raised to a high logic level, while all remaining color control inputs are maintained at a low logic level. As a result, the output of OR gate 61b rises to a high logic level, thereby causing the output of buffer 62b to rise to a high logic level. The current flows from the output of buffer 62b, via green bus 6 and green LED 3b, to the output b of decoder driver 24, and, via green LED 3c, to the output c of decoder driver 24. As a result, segments b and c illuminate in green color.

To illuminate display element 43 in blue color, the color control input B is raised to a high logic level, while all remaining color control inputs are maintained at a low logic level. As a result, the output of OR gate 61c rises to a high logic level, thereby causing the output of buffer 62c to rise to a high logic level. The current flows from the output of buffer 62c, via blue bus 7 and blue LED 4b, to the output b of decoder driver 24, and, via blue LED 4c, to the output c of decoder driver 24. As a result, segments b and c illuminate in blue color.

To illuminate display element 43 in yellow color, the color control input Y is raised to a high logic level, while all remaining color control inputs are maintained at a low logic level. As a result, the outputs of OR gates 61a and 61b rise to a high logic level, thereby causing the outputs of buffers 62a and 62b to rise to a high logic level. The current flows from the output of buffer 62a, via red bus 5 and red LED 2b, to the output b of decoder driver 24, and, via red LED 2c, to the output c of decoder driver 24. The current also flows from the output of buffer 62b, via green bus 6 and green LED 3b, to the output b of decoder driver 24, and, via green LED 3c, to the output c of decoder driver 24. As a result of blending light of red and green colors in each segment, the segments b and c illuminate in substantially yellow color.

To illuminate display element 43 in purple color, the color control input P is raised to a high logic level, while all remaining color control inputs are maintained at a low logic

level. As a result, the outputs of OR gates 61a and 61c rise to a high logic level, thereby causing the outputs of buffers 62a and 62c to rise to a high logic level. The current flows from the output of buffer 62a, via red bus 5 and red LED 2b, to the output b of decoder driver 24, and, via red LED 2c, to the output c of decoder driver 24. The current also flows from the output of buffer 62c, via blue bus 7 and blue LED 4b, to the output b of decoder driver 24, and, via blue LED 4c, to the output c of decoder driver 24. As a result of blending light of red and blue colors in each segment, segments b and c illuminate in substantially purple color.

To illuminate display element 43 in blue-green color, the color control input BG is raised to a high logic level, while all remaining color control inputs are maintained at a low logic level. As a result, the outputs of OR gates 61b and 61c rise to a high logic level, thereby causing the outputs of buffers 62b and 62c to rise to a high logic level. The current flows from the output of buffer 62b, via green bus 6 and green LED 3b, to the output b of decoder driver 24, and, via green LED 3c, to the output c of decoder driver 24. The current also flows from the output of buffer 62c, via blue bus 7 and blue LED 4b, to the output b of decoder driver 24, and, via blue LED 4c, to the output c of decoder driver 24. As a result of blending light of green and blue colors in each segment, segments b and c illuminate in substantially blue-green color.

To illuminate display element 43 in white color, the color control input W is raised to a high logic level, while all remaining color control inputs are maintained at a low logic level. As a result, the outputs of OR gates 61a, 61b, and 61c rise to a high logic level, thereby causing the outputs of respective buffers 62a, 62b, and 62c to rise to a high logic level. The current flows from the output of buffer 62a, via red bus 5 and red LED 2b, to the output b of decoder driver 24, and, via red LED 2c, to the output c of decoder driver 24. The current also flows from the output of buffer 62b, via green bus 6 and green LED 3b, to the output b of decoder driver 24, and, via green LED 3c, to the output c of decoder driver 24. The current also flows from the output of buffer 62c, via blue bus 7 and blue LED 4b, to the output b of decoder driver 24, and, via blue LED 4c, to the output c of decoder driver 24. As a result of blending light of red, green, and blue colors in each segment, segments b and c illuminate in substantially white color.

Since the outputs of decoder driver 24 may be overloaded by driving a triad of LEDs in parallel in display element 43, rather than a single LED in a monochromatic display, it would be obvious to employ suitable buffers to drive respective color display segments (not shown).

To illustrate how the present invention can be utilized in a multi-element variable color display configuration, in FIG. 19 is shown a detail of the interconnection in a 2-primary color 4-digit display having display segments 1a, 1b, 1c, and 1d arranged in a 7-segment font. The color control inputs R, Y, and G of color controls 52a, 52b, 52c, and 52d of all display elements 46a, 46b, 46c, and 46d are interconnected, respectively, and enable inputs E1, E2, E3, and E4 are used to control the conditions of respective display elements 46a, 46b, 46c, and 46d. A high logic level at the enable input E extinguishes the particular display element 46a, 46b, 46c, or 46d; a low logic level therein illuminates display element 46a, 46b, 46c, or 46d in a color determined by the instant conditions of the color control inputs R, Y, and G.

In FIG. 20 is shown a like detail of the interconnection in a 3-primary color 4-digit display having display segments 1a, 1b, 1c, and 1d arranged in a 7-segment font. Similarly,

the color control inputs B, P, BG, G, Y, W, and R of color controls **53a**, **53b**, **53c**, and **53d** of all display elements **47a**, **47b**, **47c**, and **47d** are interconnected, and the conditions of respective display elements **47a**, **47b**, **47c**, and **47d** are controlled by enable inputs E1, E2, E3, and E4. A high logic level at the enable input E extinguishes the particular display element **47a**, **47b**, **47c**, or **47d**; a low logic level therein illuminates display element **47a**, **47b**, **47c**, or **47d** in a color determined by the instant conditions of the color control inputs B, P, BG, G, Y, W, and R.

The exemplary color control circuits described herein will cooperate equally well with a multi-element variable color display constructed either in common cathodes or in common anodes configuration.

The enable inputs E1, E2, E3, E4 may be utilized to control the variable color multi-digit display in a multiplexed configuration, wherein the color codes for the display digits are presented in a sequence, one at a time, at a relatively fast rate, while the particular display digit is enabled.

In FIG. 21 is shown a block diagram of a signal converter for developing color control logic signals for 2-primary color display. The signal converter **85a** accepts at its input voltage from a variable analog voltage source **11** and develops at its outputs color control logic signals R, Y, G, having relation to the magnitude of instant input analog voltage, for controlling the color of variable color display element **42**, shown in FIGS. 11 and 15, in accordance with the magnitude of input voltage.

In FIG. 22 is shown a block diagram of a like signal converter for developing color control logic signals for 3-primary color display. The signal converter **85b** accepts at its inputs voltage from source **11** and develops output color control logic signals B, P, BG, G, Y, W, R, related to the magnitude of instant input analog voltage, for controlling the color of variable color display element **43**, shown in FIGS. 12 and 16, in accordance with the magnitude of input voltage.

In FIG. 23, the output voltage of variable analog voltage source **11** is applied to interconnected inputs of two analog comparators **82a**, **82b**, in a classic 'window' comparator configuration. When the voltage developed by source **11** is lower than the low voltage limit  $V_{lo}$ , set by a potentiometer **92a**, the output of comparator **82a** drops to a low logic level, thereby forcing the output of inverter **65a** to rise to a high logic level, to activate the color control logic input Y, to thereby illuminate display element **42**, shown in FIGS. 11 and 15, in yellow color.

When the voltage developed by source **11** is higher than the high voltage limit  $V_{hi}$ , set by a potentiometer **92b**, the output of comparator **82b** drops to a low logic level, thereby forcing the output of inverter **65b** to rise to a high logic level, to activate the color control logic input R, to thereby illuminate display element **42** in red color.

When the voltage developed by source **11** is between the low voltage limit  $V_{lo}$  and high voltage limit  $V_{hi}$ , the outputs of comparators **82a**, **82b** rise to a high logic level, thereby causing the output of AND gate **66** to rise to a high logic level, to activate the color control logic input G, to thereby illuminate display element **42** in green color.

FIG. 24 is a graph depicting the relationship between the input voltage of the comparator circuit shown in FIG. 23 and the color of the display element shown in FIG. 11. The display element illuminates in yellow color for the input voltage lower than the limit  $V_{lo}$ , in green color for the input voltage between the limits  $V_{lo}$  and  $V_{hi}$ , and in red color for the input voltage higher than the limit  $V_{hi}$ .

In FIG. 25, the output voltage of variable analog voltage source **11** is applied to interconnected '+' inputs of six analog comparators **82c**, **82d**, **82e**, **82f**, **82g**, **82h**, connected in a well known 'multiple aperture window' configuration. There are six progressively increasing voltage limits  $V_1$  to  $V_6$ , set by respective potentiometers **92c** to **92h**. The outputs of comparators **82c** to **82h** are respectively connected, via inverters **65c** to **65h**, to the inputs I1 to I7 of a priority encoder **67**. Each of the inputs I1 to I7 has assigned a certain priority (from I1 being the lowest priority progressively to I7 being the highest one). The priority encoder **67** develops at its outputs **00**, **01**, **02** a code identifying the highest priority input activated. The outputs of encoder **67** are respectively connected, via inverters **65j** to **65m**, to the inputs A0, A1, A2 of a 3-to-8 line decoder **68**, to decode the outputs of encoder **67** into seven mutually exclusive active logic low outputs Y1 to Y7. The outputs Y1 to Y7 are respectively connected, via inverters **65p** to **65v**, to the color control logic inputs B, P, BG, G, Y, W, R of display element **43** shown in FIGS. 12 and 16.

When the output voltage of source **11** is lower than the lowest voltage limit  $V_1$ , the output of comparator **82c** drops to a low logic level, thereby activating the input I1 of priority encoder **67**. The code **110** developed at the outputs **00**, **01**, **02** is inverted by inverters **65j** to **65m** to yield the code 001 which produces a low logic level at the output Y1, to force, via inverter **65p**, the color control input B to a high logic level for causing display element **43** to illuminate in blue color.

When the output voltage of the source **11** is between the adjacent voltage limits, e.g.,  $V_4$  and  $V_5$ , the output of comparator **82f** rises to a high logic level, thereby activating the input I5 of priority encoder **67**. The code 100 developed at the inputs of decoder **68** produces a high logic level at the color control logic input Y, and display element **43** illuminates in yellow color.

FIG. 26 is a graph depicting the relationship between the input voltage of the comparator circuit shown in FIG. 25 and the color of display element **42** shown in FIG. 12. The display element illuminates in blue color for the input voltage lower than the limit  $V_1$ , in purple color for the input voltage between the limits  $V_1$  and  $V_2$ , in blue-green color for the input voltage between the limits  $V_2$  and  $V_3$ , in green color for the input voltage between the limits  $V_3$  and  $V_4$ , in yellow color for the input voltage between the limits  $V_4$  and  $V_5$ , in white color for the input voltage between the limits  $V_5$  and  $V_6$ , and in red color for the input voltage higher than the limit  $V_6$ .

It would be obvious to those having ordinary skill in the art, in the view of this disclosure, that the color sequences could be readily changed by differently interconnecting the outputs of the comparator circuit with the color control logic inputs of display element **43**.

#### Continuously Variable Color Converter

FIG. 27 is a block diagram of a 2-LED continuously variable color display system, which includes a device **10** for developing electric signals and 2-LED color converter **57** for controlling red bus **5** and green bus **6**, respectively, of 2-LED variable color display element **42** in accordance with the electric signals.

FIG. 28 is a block diagram of a 3-LED continuously variable color display system which differs from the like system shown in FIG. 27 in that a 3-LED color converter circuit **58** is utilized to control red bus **5**, green bus **6**, and blue bus **7**, respectively, of 3-LED variable color display

element **43**, in accordance with the electric signals developed by device **10**.

The display system shown in FIG. **29** utilizes a scaling circuit **80a** which scales input analog voltage levels to a voltage range suitable for an A/D converter **74a**, which in turn develops at its outputs a digital code having relation to the value of the input analog voltage. The output lines of A/D converter **74a** are connected to the address inputs of a memory **76** having a plurality of addressable locations which contain data indicating the portions of red color for several different values of the input analog voltage. The output data of memory **76** are applied to the inputs of a color converter **57** which will develop control signals for red bus **5** and green bus **6**, respectively, of variable color display element **42**.

The display system shown in FIG. **30** utilizes a scaling circuit **80b** and an A/D converter **74b** for converting the instant value of an input analog voltage to a digital code. The outputs of A/D converter **74b** are connected, in parallel, to the address inputs of memory **76a**, which contains data indicating the portions of red color, to the address inputs of memory **76b**, which contains data indicating the portions of green color, and to the address inputs of memory **76c**, which contains data indicating the portions of blue color. The output data of memory **76a** are applied to red color converter **59a** which will develop control signals for red bus **5** of variable color display element **43**. The output data of memory **76b** are applied to green color converter **59b** which will develop control signals for green bus **6** of display element **43**. The output data of memory **76c** are applied to blue color converter **59c** which will develop control signals for blue bus **7** of display element **43**.

FIG. **31** is a schematic diagram of a scaling circuit capable of shifting and amplifying the input voltage levels. The circuit utilizes two operational amplifiers **81a** and **81b** in a standard inverting configuration. The amplifier **81a** is set for a unity gain by using resistors **90a** and **90b** of equal values; potentiometer **92a** is adjusted to set a desired offset voltage. The amplifier **81b** sets the gain by adjusting feedback potentiometer **92b** to a desired value with respect to resistor **90c**. As a result, an input voltage, which may vary between arbitrary limits  $V_{low}$  and  $V_{high}$ , may be scaled and shifted to the range between 0 Volts and 9.961 Volts, to facilitate the use of a commercially available A/D converter.

FIG. **32** is a schematic diagram of an A/D (analog-to-digital) converter **75** which is capable of converting input analog voltage, applied via resistor **90e** to its input  $V_{in}$ , to 8-bit digital data for addressing a memory **77**. The conversion may be initiated from time to time by applying a short positive pulse **99a** to the Blank and Convert input B&C. A/D converter **75** will thereafter perform a conversion of the instant input voltage to 8-bit data indicative of its value. When the conversion is completed, the Data Ready output DR drops to a low logic level, thereby indicating that the data are available at the outputs Bit **1** to Bit **8**, which are directly connected to respective address inputs **A0** to **A7** of memory **77**. When the DR output drops to a low logic level, the Chip Select input CS of memory **77** is activated, memory **77** is enabled, and the data, residing at the address selected by the instant output of A/D converter **75**, will appear at its data outputs **D0** to **D7**.

The description of the schematic diagram in FIG. **33** should be considered together with its accompanying timing diagram shown in FIG. **34**. A clock signal **99b** of a suitable frequency (e.g., 10 kHz), to provide a flicker-free display, is applied to the Clock Pulse inputs CP of 8-bit binary counters

**71e** and **71f** to step them down. At the end of each counter cycle, which takes 256 clock cycles to complete, the Terminal Count output TC of counter **71e** drops to a low logic level for one clock cycle, to thereby indicate that the lowest count was reached. The negative pulse **99c** at the TC output of counter **71e**, which is connected to the Parallel Load input PL of counter **71f**, causes the instant data at the outputs of memory **76** to be loaded into counter **71f**. The data at memory **76** represent the portion of red color; the portion of green color is complementary. The rising edge of the TC pulse **99c** triggers flip-flop **73** into its set condition wherein its output Q rises to a high logic level.

The counter **71f** will count down, from the loaded value, until it reaches zero count, at which moment its TC output drops to a low logic level. The negative pulse at the TC output of counter **71f**, which is connected to the Clear Direct input CD of flip-flop **73**, causes the latter to be reset and to remain in its reset condition until it is set again at the beginning of the next 256-count cycle. It is thus obvious that the Q output of flip-flop **73** is at a high logic level for a period of time proportional to the data initially loaded into counter **71f**. The complementary output  $\bar{Q}$  is at a high logic level for a complementary period of time.

The Q and  $\bar{Q}$  outputs of flip-flop **73** are connected to red bus **5** and green bus **6**, respectively, via suitable buffers **63a** and **63b**, shown in detail in FIG. **11**, to respectively energize red bus **5** and green bus **6** for variable time periods, depending on the data stored in memory **76**.

By referring now, more particularly, to the timing diagram shown in FIG. **34**, in which the waveforms are compressed to facilitate the illustration, the EXAMPLE 1 considers the memory data 'FD', in a standard hexadecimal notation, to generate light of substantially red color. At the beginning of the counter cycle, pulse **99c** loads data 'FD' into counter **71f**. Simultaneously, flip-flop **73** is set by the rising edge of pulse **99c**. The counter **71f** will be thereafter stepped down by clock pulses **99b**, until it reaches zero count, 2 clock cycles before the end of the counter cycle. At that instant a short negative pulse **99d** is produced at its output TC to reset flip-flop **73**, which will remain reset for 2 clock cycles and will be set again by pulse **99c** at the beginning of the next counter cycle, which will repeat the process. It is readily apparent that flip-flop **73** was set for 254 clock cycles, or about 99% of the time, and reset for 2 clock cycles, or about 1% of the time. Accordingly, red bus **5** of display element **42** is energized for about 99% of the time, and green bus **6** is energized for the remaining about 1% of the time. As a result, display element **42** illuminates in substantially red color.

The EXAMPLE 2 considers the memory data '02' (HEX) to generate light of substantially green color. At the beginning of the counter cycle, data '02' are loaded into counter **71f**, and, simultaneously, flip-flop **73** is set. The counter **71f** will count down and will reach zero count after 2 clock cycles. At that instant it produces at its output TC a negative pulse **99e** to reset flip-flop **73**. It is readily apparent that flip-flop **73** was set for 2 clock cycles, or about 1% of the time, and reset for 254 clock cycles, or about 99% of the time. Accordingly, red bus **5** of display element **42** is energized for about 1% of the time, and green bus **6** is energized for the remaining about 99% of the time. As a result, display element **42** illuminates in substantially green color.

The EXAMPLE 3 considers the memory data '80' (HEX) to generate light of substantially yellow color. At the beginning of the counter cycle, data '80' are loaded into counter

71f, and, simultaneously, flip-flop 73 is set. The counter 71f will count down and will reach zero count after 128 clock cycles. At that instant it produces at its output TC a negative pulse 99f to reset flip-flop 73. It is readily apparent that flip-flop 73 was set for 128 clock cycles, or about 50% of the time, and reset for 128 clock cycles, or about 50% of the time. Accordingly, red bus 5 of display element 42 is energized for about 50% of the time, and green bus 6 is energized for the remaining about 50% of the time. As a result of blending substantially equal portions of red and green colors, display element 42 illuminates in substantially yellow color.

The description of the schematic diagram of a 3-LED color converter in FIG. 19 should be considered together with its accompanying timing diagrams shown in FIGS. 20 and 21. A clock signal 99b is applied to the CP inputs of counters 71d, 71a, 71b, and 71c to step them down. Every 256 counts a negative pulse 99c is generated at the TC output of counter 71d, to load data into counters 71a, 71b, and 71c from respective memories 76a, 76b, and 76c, and to set flip-flops 73a, 73b, and 73c. The data in red memory 76a represent the portions of red color, the data in green memory 76b represent the portions of green color, and the data in blue memory 76c represent the portions of blue color to be blended.

The counters 71a, 71b, and 71c will count down, from the respective loaded values, until zero counts are reached. When the respective values of the loaded data are different, the length of time of the count-down is different for each counter 71a, 71b, and 71c. When a particular counter 71a, 71b, or 71c reaches zero count, its TC output momentarily drops to a low logic level, to reset its associated flip-flop (red counter 71a resets its red flip-flop 73a, green counter 71b resets its associated green flip-flop 73b, and blue counter 71c resets its associated blue flip-flop 73c). Eventually, all three flip-flops 73a, 73b, and 73c will be reset. The Q outputs of flip-flops 73a, 73b, and 73c are connected to red bus 5, green bus 6, and blue bus 7, respectively, via suitable buffers 62a, 62b, and 62c, as shown in FIG. 8, to respectively energize red bus 5, green bus 6, and blue bus 7 for variable periods of time.

By referring now more particularly to the timing diagram shown in FIGS. 20 and 21, the EXAMPLE 4 considers red memory data '80', green memory data '00', and blue memory data '80', all in hexadecimal notation, to generate light of substantially purple color. At the beginning of the counter cycle, pulse 99c simultaneously loads data '80' from red memory 76a into red counter 71a, data '00' from green memory 76b into green counter 71b, and data '80' from blue memory 76c into blue counter 71c. The counters 71a, 71b, and 71c will be thereafter stepped down. The red counter 71a will reach its zero count after 128 clock cycles; green counter 71b will reach its zero count immediately; blue counter 71c will reach its zero count after 128 clock cycles.

It is readily apparent that red flip-flop 73a was set for 128 clock cycles, or about 50% of the time, green flip-flop 73b was never set, and blue flip-flop 73c was set for 128 clock cycles, or about 50% of the time. Accordingly, red bus 5 of display element 43 is energized for about 50% of the time, green bus 6 is never energized, and blue bus 7 is energized for about 50% of the time. As a result of blending substantially equal portions of red and blue colors, display element 43 illuminates in substantially purple color.

The EXAMPLE 5 considers red memory data '00', green memory data '80', and blue memory data '80', to generate light of substantially blue-green color. At the beginning of

the counter cycle, data '00' are loaded into red counter 71a, data '80' are loaded into green counter 71b, and data '80' are loaded into blue counter 71c. The red counter 71a will reach its zero count immediately, green counter 71b will reach its zero count after 128 clock periods, and so will blue counter 71c.

The red flip-flop 73a was never set, green flip-flop 73b was set for 128 clock pulses, or about 50% of the time, and so was blue flip-flop 73c. Accordingly, green bus 6 of display element 43 is energized for about 50% of the time, and so is blue bus 7. As a result, display element 43 illuminates in substantially blue-green color.

The EXAMPLE 6 considers red memory data '40', green memory data '40', and blue memory data '80', to generate light of substantially cyan color. At the beginning of the counter cycle, the data '40' are loaded into red counter 71a, data '40' are loaded into green counter 71b, and data '80' are loaded into blue counter 71c. The red counter 71a will reach its zero count after 64 clock cycles, and so will green counter 71b. The blue counter 71c will reach its zero count after 128 clock cycles.

The red flip-flop 73a was set for 64 clock cycles, or about 25% of the time, and so was green flip-flop 73b. The blue flip-flop 73c was set for 128 clock cycles, or about 50% of the time. Accordingly, red bus 5 and green bus 6 of display element 43 are energized for about 25% of the time, and blue bus 7 is energized for about 50% of the time. As a result of blending about 50% of blue color, 25% of red color, and 25% of green color, display element 43 illuminates in substantially cyan color.

The EXAMPLE 7 considers red memory data '80', green memory data '40', and blue memory data '40', to generate light of substantially magenta color. At the beginning of the counter cycle, the data '80' are loaded into red counter 71a, data '40' are loaded into green counter 71b, and data '40' are loaded into blue counter 71c. The red counter 71a will reach its zero count after 128 clock cycles, green counter 71b will reach its zero count after 64 clock cycles, and so will blue counter 71c.

The red flip-flop 73a was set for 128 clock cycles, or about 50% of the time, green flip-flop 73b and blue flip-flop 73c were set for 64 clock cycles, or about 25% of the time. Accordingly, red bus 5 of display element 43 is energized for about 50% of the time, green bus 6 and blue bus 7 are energized for about 25% of the time. As a result, display element 43 illuminates in substantially magenta color.

By referring now more particularly to FIGS. 38 and 39, which are graphic representations of TABLES 1 and 2, respectively, the data at each memory address are digital representation of the portion of the particular primary color. All examples consider an 8-bit wide PROM (Programmable Read Only Memory). However, the principles of the invention could be applied to other types of memories.

In FIG. 38, RED PORTION indicates the portion of red primary color; GREEN PORTION indicates the portion of green primary color. The RED PORTION for a particular memory address was calculated by dividing the actual value of data residing at that address by the maximum possible data 'FF' (HEX). The GREEN PORTION for the same memory address is complementary; it was obtained by subtracting the calculated value of the RED PORTION from number 1.0.

In FIG. 38 is shown the characteristic of a 2-primary color converter, defined in TABLE 1, for developing color variable in steps: pure green for input voltages less than 0.625 V, substantially yellow for voltages between 1.25 V and



1.875 V, pure red for voltages between 2.5 V and 3.125 V, and of intermediate colors therebetween, this sequence being repeated three times over the voltage range.

In FIG. 39, RED PORTION indicates the portion of red primary color; GREEN PORTION indicates the portion of green primary color; BLUE PORTION indicates the portion of blue primary color. The RED PORTION for a particular memory address was calculated by dividing the value of red data residing at such address by the maximum possible data 'FF' (HEX). Similarly, the GREEN PORTION for that memory address was obtained by dividing the value of green data by 'FF' (HEX). The BLUE PORTION was obtained by dividing the value of blue data by 'FF' (HEX).

In FIG. 39 is shown the characteristic of 3-primary color converter, defined in TABLE 2, for developing color continuously variable from pure red, through substantially orange and yellow, pure green, pure blue, to substantially purple, in a rainbow-like fashion.

In the examples of the characteristics of color converters shown in TABLE 1 and TABLE 2, the data values stored in red memory 76a, green memory 76b, and blue memory 76c are so designed that the sums of the red data, green data, and blue data are constant for all memory addresses, to provide uniform light intensities for all colors. It is further contemplated that data stored in red memory 76a, green memory 76b, and blue memory 76c may be modified in order to compensate for different efficiencies of red, green, and blue LEDs. By way of an example, data values for a low efficiency LED may be proportionally incremented such that the time of energization is proportionally increased, to effectively provide equal luminances for LEDs of unequal efficiencies.

With reference to FIG. 40 there is shown the ICI (International Committee on Illumination) chromaticity diagram designed to specify a particular color in terms of x and y coordinates. Pure colors are located along the horseshoe-like periphery. Reference numbers along the periphery indicate wavelength in nanometers. When relative portions of three primary colors are known, the color of light produced by blending their emissions can be determined by examining the x and y values of ICI coordinates.

#### Digital Multimeter

FIG. 41 is a generalized block diagram of a multimeter with variable color digital display which includes a multimeter 101 for measuring values of a QUANTITY 1, digital decoder driver 21 for converting the output data of multimeter 101 to a displayable code, and variable color digital display 40 for indicating the measured values in digital format. The invention resides in the addition of a color converter circuit 55 for converting values of a QUANTITY 2 to color control signals for controlling the color of display 40. The display 40 thus simultaneously indicates values of the QUANTITY 1, in digital format, and values of the QUANTITY 2, in variable color.

FIG. 42 is a generalized block diagram of a like multimeter system with a multiplexed variable color digital display 41, which differs from the diagram shown in FIG. 41 in that the multimeter 102 develops at its outputs multiplexed signals to directly drive display 41.

A digital multimeter shown in a block diagram configuration in FIG. 43 is capable of selectively setting certain of its external controls by an external control selector 121a. The invention resides in the addition of associated color selector 121b for causing variable color digital display 40 to illuminate in a color corresponding to the selected external

control. The measurements performed with different external controls may be displayed in respectively different colors. The selectors 121a, 121b may include relays, mechanical switches, electronic and optical elements, devices for executing program of instructions, and the like. The association between the selectors 121a and 121b may be, in its simplest form, a direct coupling, whereby the selector 121b is always in the same position as the selector 121a, or a more sophisticated association in space, time, hardware, and software. The external controls may comprise measurement modes, such are local, remote, 2-wire, and 4-wire; measurement functions, such are DC voltage, AC voltage, DC current, AC current, resistance, capacitance, and inductance; measurement ranges for selectively scaling measured signals, and the like.

In FIG. 44 is shown a block diagram of a like digital multimeter capable of selectively setting certain of its internal measurement controls by an internal control selector 121a. The associated color selector 121b causes display 40 to illuminate in a color corresponding to the selected internal control, such that the measurements performed with different internal controls may be displayed in respectively different colors. The internal controls may comprise measurement modifiers, such are single, continuous, synchronous, and asynchronous triggering, sample rate, filter, offset, external reference, and scaling; measurement methods, units, and the like.

FIG. 45 is a block diagram of a digital multimeter with measurement quantity selection. By way of an example, when the quantity selector 121a is in its second position, thereby selecting the QUANTITY 2 to the input of digital multimeter 103, the associated color selector 121b is also in its second position, thereby applying the control voltage to the color control input C2, to cause the measured values of the QUANTITY 2 to be indicated on display 40 in the color C2. The measurements of different quantities may be indicated in respectively different colors.

FIG. 46 is a block diagram of a digital multimeter with input location selection. By way of an example, when the location selector 121a is in its third position, thereby selecting for the input of multimeter 103 signals from the LOCATION 3, the associated color selector 121b is also in its third position, thereby applying the control voltage to the color control input C3, to cause the measured values from the LOCATION 3 to be indicated on display 40 in the color C3. The measurements from different locations may be indicated in respectively different colors.

In FIG. 47 is shown an exemplary simplified schematic diagram of a digital multimeter for selectively measuring values of several different quantities from outputs of a temperature transducer 172, which converts temperature to voltage, pressure transducer 173, which converts atmospheric pressure to voltage, and physiological transducer 174, which converts physiological information to voltage. The term transducer, as used throughout the description of the invention, is used in its widest sense so as to include every type of a device for performing a conversion of one form of energy to another. The principles of the invention may be applied to various displacement, motion, force, pressure, sound, flow, temperature, humidity, weight, magnetic, and physiological transducers, and the like. When switch 123g is in its first position, thereby selecting temperature transducer 172, digital voltmeter 108 measures the output voltage of transducer 172, which is proportional to ambient temperature, and display 48 indicates the measured temperature in digital format. The associated switch 123h is also in its first position, thereby connecting the control

voltage +VCC to the color control input C1 of the color control circuit 42, to cause the display 48 to illuminate in the color C1. When switch 123g is in its second position, thereby selecting pressure transducer 173, display 48 indicates the measured atmospheric pressure in digital format and in the color C2. When switch 123g is in its last position, thereby selecting physiological transducer 174, display 48 indicates the measured physiological information, such as blood pressure, heart beat, and the like, in digital format and in the color Cn. Measured values of different quantities are thus displayed in respectively different colors.

In FIG. 48 is shown an exemplary simplified schematic diagram of a digital multimeter capable of measuring signals from seven different locations and of indicating the measured results in seven different colors, respectively. The outputs Q0, Q1, Q2 of a 4-bit binary counter 162b, which may be from time to time incremented by a clock pulse, are connected, in parallel, to the address inputs A, B, C of analog multiplexers 147a, 147b, respectively, to cause the multiplexer 147a to internally route signals from its selected input, e.g., Y1, to its output Y, and, simultaneously, to apply the control voltage +VCC from the terminal Y of multiplexer 147b, via its selected terminal, e.g., Y1, to one of the color control inputs B to R. The measured signals from the selected location are indicated on display 40 in digital format and in a color unique to the selected location. The indicated color sequences are merely exemplary; it would be obvious to devise other color sequences by differently interconnecting the terminals Y1 to Y7 of multiplexer 147b with the color control inputs.

In FIG. 49 is shown a simplified schematic diagram of an AC digital voltmeter for selectively measuring an RMS (Root Mean Square) or MAV (Mean Average Value) of a measured waveform. An RMS measurement provides a power content of the measured signal, as will be more fully explained later, for a waveform of any shape. Since the MAV measured value may differ from the RMS value for certain waveform shapes, it would be desirable to know which measurement method is employed. A switch 123i selects either the output of RMS converter 181 or the output of the precision rectifier circuit, consisting of an op amp 159a, resistors 124x, 124y, 124z and diodes 128a, 128b, to the input of digital voltmeter 108. An associated switch 123j selects one of the color control inputs C1, C2, in accordance with the selection of the measurement method. The display 48 indicates the magnitude of the measured AC waveform in digital format and in a color unique to the selected measurement method.

In FIG. 50 is shown a simplified schematic diagram of a digital thermometer which can selectively measure temperature in the Kelvin, Celsius, or Fahrenheit scale, by connecting the output of one of temperature transducers 177, 178, 179, via a switch 123m, to the input of digital voltmeter 108. An associated switch 123n applies the control voltage +VCC to one of the color control inputs C1, C2, C3, of the color control circuit 52, to thereby illuminate display 48 in a color unique to the selected temperature scale. The output voltage of Kelvin temperature transducer 177 is linearly proportional to temperature in the Kelvin scale. The output voltage of like Celsius temperature transducer 178 is linearly proportional to temperature in the Celsius scale. The output voltage of like Fahrenheit temperature transducer 179 is linearly proportional to temperature in the Fahrenheit scale.

In FIG. 51 is shown a simplified schematic diagram of a digital amperemeter with variable color range indication. The precision shunt resistors 126a, 126b, 126c, 126d, 126e, connected in series, convert measured current to voltage,

which is applied, via a resistor 125f of suitable value, to the input terminal of digital voltmeter 108. The current range is selectable by a rotary switch 123a, in a manner well known to those skilled in the art. The invention resides in the addition of a second rotary switch 123b, associated with the switch 123a such that both switches are always in the same position, to connect the reference voltage +VCC to the selected one of the color control inputs, in accordance with the selected current range. The remaining color control inputs are tied to ground via suitable pull down resistors 125a, 125b, 125c, 125d, 125e. By way of an example, display 40 may indicate measured current values on the 0.2 mA range in blue color, on 2 mA range in purple color, on 20 mA range in green color, on 200 mA range in yellow color, and on 2 A range in red color.

In FIG. 52 is shown a simplified schematic diagram of a digital voltmeter with variable color range indication. The precision voltage attenuating resistors 126f, 126g, 126h, 126i, 126j are connected in series, and the voltage range is selected by a rotary switch 123c, in a manner well understood by those skilled in the art. The invention resides in the addition of a second rotary switch 123d, associated with the switch 123c, to apply the reference voltage +VCC to the selected color control input. By way of an example, display 40 may indicate measured values on the 0.2 V range in white color, on 2 V range in yellow color, on 20 V range in green color, on 200 V range in blue-green color, and on 2000 V range in red color.

In FIG. 53 is shown a simplified schematic diagram of a digital ohmmeter with variable color range indication. The precision standard resistors 126k, 126m, 126n, 126p, 126r, selectable by a rotary range switch 123e, are connected such that the selected one of the standard resistors is in series with the measured resistance Rx, in a well known ratiometric arrangement. The invention resides in the addition of a second switch 123f, associated with the switch 123e, to connect the reference voltage +VCC to the selected one of the color control inputs, in accordance with the selected resistance range. By way of an example, display 40 may indicate measured resistance values on the 0.1 k range in yellow color, on 1 k range in green color, on 10 k range in blue color, on 100 k range in purple color, and on 1 M range in red color.

The examples of range and precision resistor values shown in FIGS. 51, 52, 53 should be considered merely as exemplary. Although the switches 123 are shown as rotary switches, they may, alternatively, be of any other type, such as pushbutton switches and relay contacts. Another modification envisions that only certain of the display digits may change color in accordance with the measurement range, while the remaining display digits may change color in accordance with a different quantity. It is readily apparent that the principles of the invention may be effectively applied to autoranging multimeters.

In FIG. 54 is shown a detail of the multimeter of FIGS. 51, 52, 53 which includes a DVM chip 108 capable of converting analog voltage applied to its inputs HI and LO into signals for directly driving respective segments of a 3½ digit 7-segment variable color display 48. The color control 50 causes display 48 to illuminate in a selected color, as described previously.

Commercially known digital multimeters are capable of indicating negative measured results, by displaying a small negative sign at the most significant digit, and positive measured results, usually by not displaying the minus sign. When a series of measurements is performed, it is difficult

to distinguish between the positive and negative measurement results displayed on a long character string, particularly when the measurements are performed at a relatively fast rate. In FIG. 55 is shown how this problem may be effectively solved by displaying positive and negative measurement results in respectively different colors on a 3½ digit common cathodes variable color display 48, which is capable of displaying a minus sign by illuminating the segment g in the most significant digit. The polarity output POL of digital voltmeter 108 is directly connected to the color control input R, and, via an inverter 151a, to the color control input G, of the color control circuit 52. When the POL output is at a low logic level, to indicate that the displayed number is positive, the minus sign is extinguished. A low logic level at the POL output forces the output of the inverter 151a to rise to a high logic level, to activate the color control input G, to thereby illuminate display 48 in green color. When the POL output rises to a high logic level, to indicate that the displayed number is negative, the minus sign is illuminated. A high logic level at the POL output activates the color control input R, to thereby illuminate display 48 in red color. It would be obvious, in the view of the present disclosure, to devise other color combinations.

The description of a variable color digital display system shown in FIG. 56, which is capable of emphasizing the position of a decimal point in a string of digits, should be considered together with its accompanying timing diagram shown in FIG. 57. The display system, which in its exemplary embodiment utilizes eight single-digit variable color displays 46a to 46h, which are only partially shown, is capable of detecting the position of decimal point in a string of displayed digits and of displaying all digits that precede the decimal point in a first color and all digits that follow the decimal point in a second color. The decimal point outputs DP of common-cathodes 7-segment decoders 23a to 23h, which may receive displayable data in a conventional manner (not shown), are continuously scanned in a sequence by a multiplexer 146 which is incremented by a counter 162d driven by clock 199j of a suitable frequency. When an active high DP output is detected on certain of the decoders 23a to 23h, the inverting output W of multiplexer 146, which is connected to the set direct input SD of DP flip-flop 138j, drops to a low logic level 199n, to force the latter to its set condition. The Q output of DP flip-flop 138j, which is connected to the D inputs of all flip-flops 138b to 138h, rises to a high logic level for the remaining time of the scanning cycle, to thereby indicate, as may be best observed in FIG. 57 in the line designated F—F 138j Q OUTPUT at waveform 199p, the position of the detected decimal point in reference to the scanning cycle. A decoder 166 is incremented synchronously with the multiplexer 146, and, as a result, its outputs Y0 to Y7 are sequentially driven to a low logic level, to trigger in a sequence flip-flops 138b to 138h to states determined by the conditions of their D inputs, respectively, at the time of triggering, as may be best observed in FIG. 57 in the lines designated DEC 166 OUTPUTS Y0 to Y7 at waveforms 199a to 199h. All flip-flops 138b to 138h, which were triggered before the decimal point was located during the scanning cycle, are triggered to their reset states, while all remaining flip-flops 138b to 138h, which were triggered after the decimal point was located, are triggered to their set states. The Y7 output of the decoder 166 is connected to the clear direct input CD of the DP flip-flop 138j, to force the latter to its reset condition at the end of each scanning cycle. The outputs Q and  $\bar{Q}$  of flip-flops 138b to 138h are respectively connected to color control inputs R and G of the color control circuits

52b to 52h, to thereby cause all display digits 46b to 46h that precede the instant decimal point to be illuminated in green color, and all remaining display digits that follow the decimal point to be illuminated in red color. It would be obvious that other color combinations may be devised.

The display system shown in FIG. 58 is capable of detecting the presence or absence of decimal point in the displayed digital string, and accordingly of displaying digital strings with decimal point (decimal numbers) in a first color, and digital strings without decimal point (integers) in a different color. The decimal point outputs DP of all common-cathode 7-segment decoders 23a to 23h are respectively connected to the inputs of an OR gate 154. When decimal point is present in the displayed digital string, the appropriate DP output rises to a high logic level, thereby forcing the non-inverting output of OR gate 154, which is connected to interconnected color control inputs R of all color control circuits 52a to 52h, to rise to a high logic level, to thereby cause all displays 46a to 46h to illuminate in red color. When no decimal point is detected in the displayed digital string, the inverting output of OR gate 154, which is connected to interconnected color control inputs G of all color control circuits 52a to 52h, rises to a high logic level, to thereby cause all displays 46a to 46h to illuminate in green color.

In FIG. 59 is shown a block diagram of a variable color digital display system for selectively indicating output values of seven digital devices 12a to 12g in digital format and in respectively different colors. The outputs of digital devices 12a to 12g are respectively connected to the inputs I1 to I7 of a digital multiplexer 146b, which is addressed by a counter 161c. Displayable digital data are routed from one of the multiplexer's inputs, selected by the instant output code of counter 161c, to its output Z and to variable color digital display element 43, to be displayed thereon in digital format. The counter 161c simultaneously addresses color decoder 165a, to activate one of seven color control inputs B, P, BG, G, Y, W, R of color control circuit 53, in accordance with the selected input of multiplexer 146b. By way of an example, when the counter's output code 010 (binary) is applied to the address inputs of multiplexer 146b, the input I2 is selected, and data from digital device 12b are indicated on display element 43 in digital format. Simultaneously, the counter's output code causes the output Y2 of decoder 165a to be active, thereby activating the color control input P, to cause display element 43 to illuminate in purple color. Digital devices 12a to 12g may include certain of those disclosed earlier.

In FIG. 60 is shown an expanded block diagram of a variable color digital barometer with memory, for indicating measured values of atmospheric pressure in digital format and in a color depending on previous measured values. A scaling circuit consisting of op amps 159c, 159d and resistors 124a, 124b, 124c, 124d, 124e shifts and scales output voltage of a pressure transducer 176, which is linearly proportional to atmospheric pressure, such that voltage at the input of digital voltmeter 107 directly corresponds to the atmospheric pressure, either in millibars or in mm Hg, depending on the values of resistor 124e and V REF voltage. The digital voltmeter 107 converts the instant analog voltage at its input to a digital code which is simultaneously applied to variable color digital display 40, to be indicated thereon in digital format, and to the data input of a combined memory and comparator 144, to be stored therein from time to time. The invention resides in the addition of a color control circuit 50 for illuminating display 40 in a color depending on the result of comparison between the instant

measured value of atmospheric pressure and previously stored one, to thereby indicate whether the atmospheric pressure is either rising, or falling, or remains unchanged. A three-decade counter **164**, or other suitable device for keeping time, is incremented in regular intervals by a clock, and its DIGITS outputs indicate the instant count. A decoder **165b** has its ADDRESS inputs connected, in a rather simplified manner, to the counter's DIGITS outputs and utilizes the counter's SELECT output as a strobe. As a result of continuous counting, at regular time intervals there will appear relatively short pulses  $99m$  at the selected decoder's output  $Y_n$ , which is connected to the LOAD input of memory and comparator **144**, to load the instant output data of digital voltmeter **107** into memory **144**. The comparator **144** effects a comparison of the data currently stored in its memory with the instant output data of digital voltmeter **107** and accordingly develops output signals LT (Less Than), EQ (Equal), and GT (Greater Than). The comparator's outputs LT, EQ, GT are respectively connected to the color control inputs R, Y, G of color control circuit **50**, to cause display **40** to illuminate in red color when the comparator's output LT is active (atmospheric pressure is falling), in yellow color when the output EQ is active (atmospheric pressure is unchanged), and in green color when the output GT is active (atmospheric pressure is rising). The above description may serve as a background for consideration of more sophisticated barometric systems capable of comparing the instant measured values with values obtained by virtue of arithmetic and logic operations, such as average or peak values of previous measurements, and of displaying measured values in a variety of colors depending on the rate of increase or decrease of measured values.

In FIG. **61** is shown a block diagram of a digital multimeter **103** for making series of measurements in combination with a clock **148** for keeping time. The time signals developed by the clock circuit **148** are decoded by a suitable time decoder **168** and converted to color control signals C1, C2 to Cn. The values measured by the multimeter **103** are indicated on display **40** in digital format and in a color having relation to time.

FIG. **62** is a block diagram of a multimeter which includes a memory **131**, containing a reference measured value, and a comparator **141**. Measured values of input signal, which is applied to an input conditioning circuit **120**, wherein it may be switched, scaled, attenuated, rectified, and filtered (not shown), are compared with the reference value stored in memory **131** and indicated on display **40** in digital format and in a color depending on the relationship between the measured value and the reference one. The memory **131** may include electronic storage elements, such as flip-flops, latches, RAMs, ROMs, and the like, and mechanical storage elements, such as binary switches or the like. When the instant measured value is less than the reference value, the output '<' of the comparator **141** is active, thereby activating the color control input C2 of the color control circuit **50**, to illuminate display **40** in the color C2. When the instant measured value is greater than the reference one, the comparator's output '>' is active, and the measured value is displayed in the color C1. Alternatively, the instant measured value may be displayed in a color indicating its deviation, absolute or relative, from the reference value.

FIG. **63** is a block diagram of a multimeter which includes a memory **131a** for storing a low measurement limit, memory **131b** for storing a high measurement limit, and comparators **141a**, **141b**. The measured values are compared with the high and low measurement limits and are indicated on display **40** in digital format and in a color depending on

the relationship between the measured value and the low and high measurement limits. When the measured value is lower than the low measurement limit, stored in memory **131a**, the output '<' of the comparator **141a** is active, thereby activating the color control input C3 of the color control circuit **50**, to illuminate display **40** in the color C3. When the measurement value is higher than the high measurement limit, stored in memory **131b**, the output '>' of comparator **141b** is active, thereby activating the color control input C1, to illuminate display **40** in the color C1. When the measured value is higher than the low measurement limit and lower than the high measurement limit, the active outputs '>' of the comparator **141a** and '<' of the comparator **141b** are combined in a logic fashion by a logic circuit **150**, thereby activating the color control input C2, to illuminate display **40** in the color C2.

FIG. **64** is a block diagram of a multimeter for making repeated measurements, which includes an A/D converter **106** and memory & comparator circuit **144**. The instant measured value of the input signal, converted to digital format by the A/D converter **106**, may be from time to time stored in memory **144**, so that subsequent measurements could be compared with the stored values. The instant measured value is displayed on display **40** in digital format and in a color depending on the result of comparison with the value stored in the memory. When the instant measured value is less than that stored in the memory, the output LT (Less Than) of comparator **144** is active, thereby activating the color control input C3 of color control circuit **50**, to display the measured value in the color C3. When the instant measured value is equal to that stored in the memory, the comparator output EQ (Equal) is active, thereby activating the color control input C2, to display the measured value in the color C2. When the instant measured value is greater than that stored in the memory, the comparator output GT (Greater Than) is active, thereby activating the color control input C1, to display the measured value in the color C1.

FIG. **65** is a block diagram of a multimeter for making a series of measurements and for comparing each measured value, by comparators **141a**, **141b**, with low and high measurement limits stored in memories **131a**, **131b**, respectively. An additional error memory **131c**, which may include an error counter, and logic circuit **150a** are provided for storing the number of measurement errors. The instant measured value is indicated on display **40** in digital format and in a color depending, firstly, on its relationship with the applicable low and high measurement limits, and, secondly, on the number of previous measurement errors. Various kinds of decisions may be made, by a logic circuit **150b**, based on the contents of the error memory. The decisions may be as simple as merely to display the measurement results in the color C1 for no previous measurement errors and in the color C2 for some previous errors, or may involve sophisticated color selections based on the number of previous errors and total number of measurements, arrived at by virtue of arithmetic and logic operations.

In FIG. **66** is shown an exemplary simplified schematic diagram of the limit memory and limit comparator combination, generally shown in FIG. **65**, for 8-bit measurement data (two BCD digits). The 8-bit data stored in a memory **132a**, symbolizing the low measurement limit, are applied to respective inputs B0 to B7 of a digital comparator **143a**; the 8-bit data stored in a like memory **132b**, symbolizing the high measurement limit, are applied to respective inputs B0 to B7 of a comparator **143b**. The 8-bit measurement data, having relation to the instant measured value, are applied to respective inputs A0 to A7 of both comparators

143a, 143b, interconnected in parallel. The comparators 143a, 143b effect a comparison between the measurement data and the instant low and high measurement limits and accordingly develop their output signals '<', '=', '>'. When the instant measurement data are less than the low measurement limit, the '<' output of the comparator 143a rises to a high logic level. When the instant measurement data are greater than the high measurement limit, the '>' output of the comparator 143b rises to a high logic level. When the instant measurement data are between the low and high measurement limits, one of the inputs of each OR gate 152a, 152b rises to a high logic level, thereby forcing both inputs of AND gate 155a to rise to a high logic level, which in turn forces the output of the latter to rise to a high logic level. The outputs PASS, FAIL LOW LIMIT, and FAIL HIGH LIMIT may be connected to respective inputs C1, C2, and C3 of the color control 50. By way of an example, display 40 may illuminate in green color for pass, in yellow color for fail on the low limit, and in red color for fail on the high limit.

In FIG. 67 is shown a simplified schematic diagram of the limit memory, limit comparator, and error memory combination, in a digital multimeter for making a series of measurements. A memory 132c contains data symbolizing low measurement limits for each measurement step. A like memory 132d contains data symbolizing high measurement limits for each measurement step. An 8-bit counter 161, which is incremented for each measurement step by a suitable clock pulse, is used to simultaneously address both memories 132c, 132d. When addressed for a particular measurement step, the memories 132c, 132d present the data residing at such address to the inputs B0 to B7 of comparators 143c, 143d, respectively, as the instant low and high measurement limits. The comparison of the instant measurement data with the instant measurement limits is performed by comparators 143c, 143d at each measurement step. When the measurement passes, the PASS output rises to a high logic level. When the measurement fails, either on the low or high measurement limit, the FAIL output of OR gate 152e rises to a high logic level, and error memory 135a is incremented by the next clock pulse. Thus the error memory 135a contains data representing the total number of measurement errors. A logic circuit 150b converts the instant error memory data to color control signals C2 to Cn, whereby the instant measured value is displayed in the color C1 on pass, and in a certain of the colors C2 to Cn on fail, depending on the total number of previous measurement errors, as will be more fully explained later.

In FIG. 68 is shown a detail of the comparator, error flip-flop, and color control combination generally shown in FIG. 65. When a measurement error occurs, either on the low or high measurement limit, the output of an OR gate 152f, which is connected to the D input of error flip-flop 138a, rises to a high logic level, and the error flip-flop will be set by the next clock pulse, to indicate that there was a measurement error. The error flip-flop may be suitably reset (not shown), e.g., at the beginning of each measurement series. Results of the measurements are indicated on display 40 in digital format and in a color depending on the result of comparison with the instant low and high measurement limits and on the condition of the error flip-flop. By way of an example, the measurements may be displayed in green color on pass, in yellow color on fail with no previous measurement errors, and in red color on fail with previous measurement errors.

FIG. 69 is another exemplary detail of the comparator, error memory, and color converter combination generally shown in FIG. 67. When a measurement error occurs, the

output of an OR gate 152g, which is connected to the DATA input of the error memory 135b, rises to a high logic level, and the error memory contents will be incremented by the next clock pulse. The error memory 135b thus contains data indicating the total number of previous measurement errors. The outputs of error memory 135b are applied to interconnected inputs of red color converter 59a, green color converter 59b, and blue color converter 59c, which develop drive signals for energizing red bus 5, green bus 6, and blue bus 7 of display 40 to illuminate it in a color related to the total number of previous errors.

FIG. 70 is a detail of the low limit memory and comparator combination shown in FIG. 66. An 8-bit latch 134 stores data representing the instant low measurement limit, which may be from time to time entered via its inputs D0 to D7 (not shown). Two 4-bit digital comparators 142a, 142b are cascaded to form an 8-bit digital comparator, in a manner well understood by those skilled in the art.

FIG. 71 is an exemplary detail of the error counter and PROM combination shown in FIG. 69. An 8-bit counter 163, which contains the count indicating the total number of previous measurement errors, is employed to address, via its outputs Q0 to Q7, a PROM 77 containing the color conversion data which may be used to develop drive signals for red bus 5, green bus 6, and blue bus 7, as previously shown in FIG. 35, to thereby illuminate display 40 in a color depending on the total number of previous measurement errors.

The schematic diagram shown in FIG. 72 includes a digital multimeter 103 for making repeated measurements of input signals and for developing at its outputs a 4-digit BCD code having relation to the magnitude of the instant input signal, and two cascaded registered comparators 145a, 145b for comparing the instant measured value with the value previously stored. From time to time, a short positive pulse 99n may be applied to interconnected Load inputs S0, S1, to cause the instant data at the inputs I0 to I7 of both registered comparators 145a, 145b to be loaded therein. The subsequent measured values will be compared with the reference value currently loaded in the register, and interconnected outputs LT (Less Than), EQ (Equal), GT (Greater Than), which are tied to the supply voltage via suitable pull-up resistors 124f, 124g, 124h, will indicate the result of each comparison. The comparator outputs are respectively connected to the color control inputs C1, C2, C3 of the color control circuit 50, to control the color of display 40, shown in FIG. 62, in accordance with the result of the comparison. The display 40 indicates the instant measured value in digital format and in a color depending on the result of comparison with the reference value currently stored in the register. By way of an example, display 40 may illuminate in green color when the instant measured value is equal to the reference value, in yellow color when it is less than the reference value, and in red color when it is larger than the reference value.

In FIG. 73 is shown a simplified schematic diagram of a digital voltmeter with 3½ digit variable color display. The digital voltmeter 107 is configured, by having its initialize conversion input INIT connected to a high logic level, to continuously convert input analog voltage, applied to its input terminal via a resistor 124a, to 3½ digit BCD code corresponding to the magnitude of instant input voltage. The BCD codes for the respective digits are converted, by 7-segment decoders 22a, 22b, 22c, 22d, to signals for directly energizing the segments of the variable color display digits 42a, 42b, 42c, 42d, respectively, in a manner well understood by those skilled in the art. The color control circuit 50 causes all four display digits to illuminate uniformly in a selected color, as previously described.

A like block diagram shown in FIG. 74 differs in that four color control circuits **50a**, **50b**, **50c**, **50d** are employed to independently control the colors of respective display digits **42a**, **42b**, **42c**, **42d**.

In FIG. 75 is shown, in a block diagram configuration, a multimeter utilizing two digital voltmeters **109a** and **109b** for measuring respective INPUT SIGNALS **1** and **2**. The measured values of both input signals are simultaneously indicated on a single 8-digit variable color display element **42** such that the four most significant display digits **D1** to **D4** indicate the output of digital voltmeter **109a**, and the four least significant display digits **D5** to **D8** indicate the output of digital voltmeter **109b**. In order to clearly distinguish between the two measured values, without the need for a visual gap therebetween, the color control circuit **52a** is adapted, by having its color control input **G** connected to a high logic level, to illuminate the four most significant display digits **D1** to **D4** in green color, and like color control circuit **52b** is adapted, by having its color control input **R** connected to a high logic level, to illuminate the four least significant digits **D5** to **D8** in red color.

FIG. 76 is a block diagram of an RMS digital voltmeter with variable color crest factor indication. The RMS (Root Mean Square) value of the measured waveform is its heating value when applied to a resistor; it indicates the magnitude of the measured waveform regardless of its shape. The Crest Factor is the peak signal value divided by the RMS value; it indicates what type of a waveform it is.

The digital voltmeter includes an RMS converter **181** for converting an input measured signal to a DC value representative of the energy content of the measured signal. The DC value from the RMS converter **181** is applied to the HI input terminal of a digital voltmeter **105** which develops at its outputs signals to directly drive variable color digital display **40**, to thereby indicate the measured RMS value in digital format, in a manner well known to those having ordinary skill in the art.

The invention resides in the addition of a crest factor converter **183** for computing the crest factor value of the measured waveform, and of a color converter **55** for controlling the color of display **40** in accordance with the crest factor value. The RMS digital voltmeter of the present invention will simultaneously indicate the RMS value of the measured waveform in digital format and in a color indicative of the crest factor value of the measured waveform, to thereby simultaneously indicate its magnitude and shape.

FIG. 77 is a comparison chart of RMS and crest factor values for several exemplary waveforms. It is readily apparent that the crest factor value is a good indication of the waveform shape. The unity value of the crest factor indicates that the measured signal is either a symmetrical waveform or a DC signal. Small values of the crest factor (less than 2) usually indicate either a sine wave, triangle wave, or a low duty cycle pulse train. High values of the crest factor (greater than 4) usually indicate a noise signal or a pulse train with a high duty cycle.

As illustrated in FIG. 78, the crest factor converter **183** includes a ratio producing circuit **187** that develops at its output **RATIO A:B** a signal representative of the ratio of signals applied to its inputs **A** and **B**. The peak signal value, obtained from the output of the peak detector **185**, is applied to the input **A**. The RMS signal value, obtained from the output of the RMS-to-DC converter **181**, is applied to the input **B**. The computed ratio of the peak signal value to the RMS signal value, developed at the output **RATIO A:B**, is by definition a crest factor value of the measured signal.

In a simplified exemplary schematic diagram of a ratio producing circuit, shown in FIG. 79, the output DC voltage of the RMS-to-DC converter **181** is applied to the **X1** input of a precision divider **188**, while the output DC voltage of the peak detector **185** is applied to its input **Z2**. The precision divider **188** develops at its output suitably scaled DC voltage representing the ratio of the signals **Z2** to **X1**.

In an exemplary detail of the RMS converter circuit, shown in FIG. 80, the measured signal is applied, via suitable potentiometer **127c**, to the input of an RMS-to-DC converter **182**, which develops at its output a DC voltage corresponding to RMS value of the measured signal. The potentiometer **127b** and resistors **124p**, **124r** are used to adjust offset voltage; the capacitor **129p** is selected to set a suitable averaging time constant.

FIG. 81 is an exemplary detail of the peak detector circuit, in which a measured signal is applied, via a suitable resistor **124u**, to the input of a peak detector **186**, which develops at its output a DC voltage, retained on the hold capacitor **129r**, representing the maximum value of the input signal. The present peak value may be from time to time reset, by applying a relatively short positive pulse **99p** to interconnected inputs **DET** and **RESET**. When pulse **99p** returns to a low logic level, new peak of the input signal may be measured.

As shown in FIG. 82 in a block diagram form, the output voltage of the crest factor converter, which indicates the instant measured value of the crest factor, may be applied to input of a suitable comparator **141a**, such as the one shown in FIG. 23, to develop color control logic signals **R**, **Y**, **G** for the color control circuit **52**, to illuminate display element **42** in one of three colors, in accordance with the value of the crest factor. By way of an example, the comparator **141a** may be set to develop active color control signal **G** for values of the crest factor less than 1.5, to illuminate display element **42** in green color, active color control signal **Y** for values of the crest factor between 1.5 and 2.5, to illuminate display element **42** in yellow color, and active color control signal **R** for values of the crest factor greater than 2.5, to illuminate display element **42** in red color.

A similar block diagram shown in FIG. 83 differs in that a comparator **141b**, such as the one shown in FIG. 25, and color control circuit **53** are used to illuminate display element **43** in one of seven colors, in accordance with the value of the crest factor. By way of an example, the comparator **141b** may develop active color control signal **B** for values of the crest factor less than 1.1, to illuminate display element **43** in blue color, active color control signal **P** for values of the crest factor between 1.1 and 1.4, to illuminate display element **43** in purple color, active color control signal **BG** for crest factor values between 1.4 and 1.7, to illuminate display element **43** in blue-green color, active color control signal **G** for crest factor values between 1.7 and 2.0, to illuminate display element **43** in green color, active color control signal **Y** for crest factor values between 2.0 and 2.5, to illuminate display element **43** in yellow color, active color control signal **W** for crest factor values between 2.5 and 3.0, to illuminate display element **43** in white color, active color control signal **R** for crest factor values greater than 3.0, to illuminate display element **43** in red color.

As shown in FIG. 84, the output voltage of the crest factor converter **183** is applied to the input of a scaling circuit **80a**, such as the one shown in FIG. 31, to be scaled and shifted to a voltage range suitable for the continuous 2-primary color converter **57**, which will develop drive signals for controlling red bus **5** and green bus **6**, respectively, of

display 42, to illuminate it in a color related to the instant measured value of the crest factor.

A like block diagram shown in FIG. 85 differs in that 3-primary color converter 58 is used to develop drive signals for red bus 5, green bus 6, and blue bus 7, respectively, of display element 43, to illuminate it in a color related to the measured value of the crest factor. The relationship between the crest factor values and the color of display element 43 may be defined at will, e.g., by programming suitable data into PROMs contained in color converter 58, as previously described.

In FIG. 86 is shown a front view of a digital multimeter which includes a 6½ digit variable color digital display 49, keyboard 117, and suitable terminals 116 for attaching thereto the measuring cords. The keyboard 117 includes a DC V key 118a for setting the multimeter to its DC voltage mode, AC V key 118b for setting the multimeter to its AC voltage mode, OHMS key 118c for setting the multimeter to its OHMS mode, RANGE keys 118d, 118e, 118f, 118g, 118h, 118i for setting the multimeter to a selected range, LOCAL key 118j for setting the multimeter to its local mode, FRONT key 118k for selecting front measurement terminals, FILTER key 118m for setting the multimeter to its filter mode, AUTO key 118n for setting the multimeter to its autoranging mode, OFFS key 118p, '%' key 118r, and LAH key 118s for setting the multimeter to certain of its mathematical modes. The HI INPUT terminal 116a and LO INPUT terminal 116b may be used for voltage measurements; the like HI OHM terminal 116c and LO OHM terminal 116d may be used for resistance measurements.

In FIG. 87 is shown a block diagram of a variable color digital multimeter controlled by a microprocessor or micro-computer 168, which can be influenced either locally, by entering commands via the keyboard 117, or remotely, by sending commands over a bus via the remote control circuit 169. When properly commanded, the microprocessor 168 can control the input conditioning section 120, AC section 112, and OHMS section 113, to selectively switch, scale, attenuate, rectify, and filter the measured signals, before being applied to the input of an A/D converter 106, which repeatedly performs analog-to-digital conversions and develops output data indicative of the magnitude of the instant measured signal. The microprocessor 168 can from time to time read output data of the converter 106 and send same to display controller 167, which causes the data to be indicated on display 40 in digital format. The invention resides in the addition of a color memory 136, wherein data symbolizing a selected color may be stored, and color control 50 for illuminating display 40 in the selected color. It is contemplated that the color of display 40 may be controlled in accordance with certain of the following operating modes:

a. Local/remote mode: The multimeter may be set either to its local mode, e.g., by actuating the LOCAL key 118j on the front panel, wherein all commands are entered via the keyboard 117, and the remote control 169 is disabled, or to its remote mode wherein all commands are sent via the remote control 169, and the keyboard 117 is disabled. When in its local mode, microprocessor 168 will send data to the color memory 136 commanding color control 50 to illuminate display 40 in a first color (e.g., green); when in its remote mode, microprocessor 168 will send different data to color memory 136 commanding that display 40 be illuminated in a second color (e.g., red), so that an operator may readily distinguish the two modes.

b. Normal/offset mode: The multimeter may be set to its offset mode, e.g., by actuating the OFFS key 118p on the

front panel, wherein a numeric constant (an offset) is stored in the microprocessor's memory, to calculate and display the difference between a measured value and the offset; when in its normal mode, the multimeter displays true measured values. To indicate in which mode the multimeter currently operates, the microprocessor 168 will send data to the color memory 136 commanding that display 40 be illuminated in a first color when in its normal mode and in a second color when in its offset mode.

c. Standard/percent mode: The multimeter may be set to its percent mode, e.g., by actuating the '%' key 118r on the front panel, wherein a percent deviation of a measured value from a value stored in the microprocessor's memory (reference value) is calculated and displayed; when in its standard mode, true measured values are displayed. To indicate in which mode the multimeter currently operates, microprocessor 168 will send data to color memory 136 commanding that display 40 be illuminated in a first color for the standard mode and in a second color for the percent mode.

d. LAH/standard mode: The multimeter may be set to its LAH (Low, Average, High) mode, e.g., by actuating the LAH key 118s on the front panel, wherein the multimeter will store the most positive and most negative measured values, calculate the average measured value, and count the number of measurements during the LAH cycle; when in its standard mode, true measured values are displayed. To indicate whether the multimeter currently operates in the standard or LAH mode, the microprocessor 168 will send data to the color memory 136 commanding that display 40 be illuminated in a first color for the standard mode and in a second color for the LAH mode.

In FIG. 88 is shown an expanded block diagram of a digital multimeter with a DC section 111 for processing DC signals, AC section 112 for processing AC signals, and OHMS section 113 for performing resistance measurements, as will be more fully explained later. The multimeter includes input terminals HI INPUT 116a, LO INPUT 116b, HI OHM 116c, LO OHM 116d on the front panel shown in FIG. 86, and like input terminals on the rear panel (not shown), which may be selectively connected to the input of a digital voltmeter 105. To select between the front and rear measurements, the FRONT key 118k may be actuated, which toggles a front/rear relay 191 between its energized and disenergized conditions. To facilitate the illustration, a convention was adopted that a particular relay is designated in the drawings by a certain numeral, and its associated contacts are designated by same numeral with character 'a', 'b', etc., appended. By way of an example, relay 191 has contacts 191a, 191b, 191c, 191d, 191e. When relay 191 is not energized, its contacts 191a to 191e are in the positions as illustrated, thereby making available the front input terminals for connection to the input of digital voltmeter 105. When relay 191 is energized, its contacts 191a to 191e switch to their other positions, respectively, thereby making available the rear input terminals for connection to the input of the digital voltmeter 105. The invention resides in the addition of relay contact 191e, associated with contacts 191a to 191d, such that the front and rear measurements are indicated in a digital format and in respectively different colors. When the measurements via the front input terminals are performed, as illustrated, relay contact 191e is open, and the color control input C1 is pulled to a low logic level by a suitable pull-down resistor 124v, thereby forcing, via an inverter 151e, the color control input C2 to rise to a high logic level, to thereby cause display 40 to be illuminated in the color C2 (e.g., red). When the measurements via the rear

input terminals are performed, by causing relay 191 to be energized to switch its contacts 191a to 191e to their other positions, respectively, contact 191e is closed to apply a high logic level from the source +VCC to the color control input C1, and to simultaneously force, via inverter 151e, the color control input C2 to a low logic level, to thereby cause display 40 to be illuminated in the color C1 (e.g., green).

In FIG. 89 is shown a like block diagram of a digital multimeter for selectively performing DC, AC, and OHMS measurements and for indicating measured values in digital format and in respectively different colors. To perform DC measurements, the DC relay 192 is energized, e.g., by actuating the DC V key 118a on the front panel of the, to connect the HI INPUT terminal, via contact 191a and closed contact 192a, and via the DC section 111, to the HI input of digital voltmeter 105. Simultaneously, the LO relay 195 is energized to connect the LO INPUT terminal, via contact 191b and closed contact 195a, to the LO input of digital voltmeter 105. Measured DC values of the input signal are indicated on display 40 in digital format, in a manner well understood by those skilled in the art. The invention resides in the provision of a relay contact 192b, associated with contact 192a, to apply a high logic level to the color control input C1, to cause display 40 to illuminate in the color C1 (e.g., red).

To perform AC measurements, the AC relay 193 is energized, e.g., by actuating the AC V key 118b on the multimeter's front panel, to connect the HI INPUT terminal, via contact 191a and closed contact 193a, and via the AC section 112, to the HI input of digital voltmeter 105. Simultaneously, LO relay 195 is energized to connect the LO INPUT terminal to the LO input of the digital voltmeter 105. Measured AC values of the input signal are indicated on display 40 in digital format, in a manner well understood. The relay contact 193b, associated with contact 193a, closes when relay 193 is energized, to apply a high logic level to the color control input C2, to cause display 40 to illuminate in the color C2 (e.g., yellow).

To perform OHMS measurements, the OHMS relay 124 is energized, e.g., by actuating the OHMS key 118c on the multimeter's front panel, to connect the HI OHM terminal, via closed contact 194a, and via OHMS section 113, to the HI input of digital voltmeter 105. The LO OHM terminal is connected, via closed contact 194b, to the LO input of digital voltmeter 105. Measured resistance values are indicated on display 40 in digital format, in a manner well known. The relay contact 194c, associated with contacts 194a, 194b, closes when relay 194 is energized, to apply a high logic level to the color control input C3, to cause display 40 to illuminate in the color C3 (e.g., green).

The digital voltmeter shown in FIG. 90 may be set to its filter mode wherein the measured signal is filtered to remove high frequency noise. The invention resides in the addition of a filter flip-flop 138b for activating color control circuit 50 to illuminate display 40 in the color C1 for the filter mode turned on and in the color C2 for the filter mode turned off. The filter mode may be turned on and off by actuating the FILTER key 118m, to toggle filter flip-flop 138b. When key 118m is actuated, its associated keyswitch 119m momentarily closes, to connect a low logic level to the trigger input TRG of a timer 158, which is normally tied to a high logic level via its pull-up resistor 124i, to produce at the timer's output OUT a relatively short positive going pulse 99s, to trigger filter flip-flop 138b to its opposite state. The width of pulse 99s may be set by selecting suitable values of resistor 124z and capacitor 129s, to eliminate the problem of possible bouncing of keyswitch 119m. When flip-flop 138b is in

its set condition, its output Q, which is connected to the input of a relay driver 157, rises to a high logic level, to activate the latter, to energize filter relay 196. The associated relay contact 196a closes to connect filter circuit 149 to the input of digital voltmeter 105. The outputs Q and  $\bar{Q}$  of flip-flop 138b are connected to the color control inputs C1, C2, respectively, to cause display 40 to illuminate in a color in accordance with the condition of flip-flop 138b.

In brief summary, the invention describes a variable color digital display system which comprises a plurality of adjacent variable color light emitting diode digital display elements for sequentially providing a digital indication of a first digital value and of a second digital value, in accordance with a first timing signal and a second timing signal, respectively, developed by a timing device. A memory is provided for storing the data corresponding to the first digital value, in accordance with the first timing signal. A comparator is also provided for comparing the second digital value, in accordance with the second timing signal, with the data stored in the memory and for developing a first comparison signal when the second digital value is larger than the data stored in the memory and a second comparison signal when the second digital value is less than the data stored in the memory. A color control is also provided for uniformly controlling the color of the digital indication, in accordance with the second timing signal, for illuminating the digital indication in a first color in response to the first comparison signal and in a second color in response to the second comparison signal.

It would be obvious, in the view of the present disclosure, that the hardware design of the present invention may be also implemented by software. It would be further obvious that persons skilled in the art may resort to modifications in the construction of the preferred embodiment described herein, without departing from the spirit and scope of the invention as defined in the appended claims. It is contemplated that the principles of the invention are also applicable to numerous diverse types of display devices, such as luminescent devices, liquid crystal display devices, plasma display devices, cathode ray tube display devices, and the like.

#### Correlation Table

This is a correlation table of reference characters used in the drawings herein, their descriptions, and examples of commercially available parts.

#	DESCRIPTION	EXAMPLE
1	display segment	
2	red LED	
3	green LED	
4	blue LED	
5	red bus	
6	green bus	
7	blue bus	
10	device developing electric signals	
11	analog voltage source	
12	digital device	
15	segment body	
16	light scattering material	
20	decoder	
21	digital decoder driver	
22	7-segment display decoder driver	
23	common cathode 7-segment decoder driver	74LS49
24	common anode 7-segment decoder driver	74LS47
30	monochromatic digital display	
40	variable color digital display	



-continued

#	DESCRIPTION	EXAMPLE
41	multiplexed variable color display	
42	variable color 7-segment display element (2 LEDs)	
43	variable color 7-segment display element (3 LEDs)	
46	variable color display element (2 LEDs)	
47	variable color display element (3 LEDs)	
48	3 1/2 digit variable color display	
49	6 1/2 digit variable color 7-segment display	
50	color control	
51	step variable color control	
52	color control (2 LEDs)	
53	color control (3 LEDs)	
55	color converter	
56	continuously variable color converter	
57	2-primary color converter	
58	3-primary color converter	
59	single color converter	
60	2-input OR gate	74HC32
61	4-input OR gate	4072
62	non-inverting buffer	74LS244
63	inverting buffer	74LS240
64	inverter	part of 74LS240,4
65	inverter	74HC04
66	2-input AND gate	74HC08
67	priority encoder	74HC147
68	3-to-8 line decoder	74HC138
69	logic circuit	
71	8-bit counter	74E579
73	D type flip-flop	74HC74
74	A/D converter	
75	8-bit A/D converter	AD570
76	memory	
77	2k x 8 bit PROM	2716
80	scaling circuit	
81	op amp	LM741
82	analog comparator	LM339
85	signal converter	
90	resistor	
91	resistor	
92	potentiometer	
93	capacitor	
99	pulse	
101	multimeter	
102	multimeter with multiplexed outputs	
103	digital multimeter	
105	digital voltmeter	
106	A/D converter	
107	Teledyne DVM chip	TSC8750
108	Teledyne DVM chip	TSC7107
109	Intersil DVM chip	ILS7107
111	DC section	
112	AC section	
113	OHMS section	
115	control section	
116	measuring terminal	
117	keyboard	
118	key	
119	keyswitch	
120	input conditioning	
121	selector	
123	rotary switch	
124	resistor	
125	resistor	
126	precision resistor	
127	potentiometer	
128	signal diode	1N4148
129	capacitor	
131	memory	
132	8-bit wide memory	
134	8-bit latch	74HC273
135	error memory	
136	color memory	
138	D-type flip-flop	74HC74
141	comparator	
142	4-bit digital comparator	74HC85
143	8-bit digital comparator	

-continued

#	DESCRIPTION	EXAMPLE
5	144 memory & comparator	
	145 registered comparator	74F524
	146 8-channel digital multiplexer	74HC151
	147 analog multiplexer	4051
	148 clock	
	149 filter	
10	150 logic circuit	
	151 inverter	74HC04
	152 2-input OR gate	74HC32
	154 8-input OR/NOR gate	74HC4078
	155 2-input AND gate	74HC08
	156 3-input AND gate	74HC11
15	157 relay driver	1416
	158 timer	NE555
	159 op amp	LM741
	161 counter	
	162 4-bit binary counter	74HC161
	163 8-bit binary counter	74F579
20	164 3-decade counter	14553
	165 decoder	
	166 1-to-8 lines decoder	74HC138
	167 display controller	ICM721A
	168 microprocessor	8085
	169 remote control	
	172 temperature transducer	
25	173 pressure transducer	
	174 physiological transducer	
	176 SenSym pressure transducer	LX1802AN
	177 Kelvin temperature transducer	
	178 Celsius temperature transducer	LM35
	179 Fahrenheit temperature transducer	LM34
30	181 RMS to DC converter	
	182 RMS converter chip	AD536A
	183 crest factor converter	
	185 peak detector	
	186 peak detector chip	PKD-01
	187 ratio producing circuit	
35	188 precision divider chip	FAD535
	191 front/rear relay	JDT21
	192 DC section relay	JDT7
	193 AC section relay	JDT7
	194 OHMS section relay	JDT15
	195 LO input relay	JWD-107
40	196 filter relay	JWD-107
	199 pulse	

The examples of commercially available components should be considered as merely illustrative. It will be appreciated that other components may be readily and effectively used. The integrated circuits used in the description of the invention are manufactured by several well known companies, such as Analog Devices, Inc., Fairchild Camera and Instrument Corporation, Intel Corporation, Intersil, Inc., Motorola Semiconductor Products Inc., National Semiconductor Incorporated, Precision Monolithics Incorporated, Teledyne Semiconductor, Texas Instruments Inc., etc.

TABLE 1

	DATA PORTIONS				
	Input Voltage (Volts)	PROM Address (Hex)	'Red' PROM (Hex)	red	green
60	0.0	00	00	0.0	1.0
	0.039	01	00	0.0	1.0
	0.078	02	00	0.0	1.0
	0.117	03	00	0.0	1.0
	0.156	04	00	0.0	1.0
	0.195	05	00	0.0	1.0
65	0.234	06	00	0.0	1.0
	0.273	07	00	0.0	1.0

TABLE 1-continued

DATA PORTIONS					5
Input Voltage (Volts)	PROM Address (Hex)	'Red' PROM (Hex)	red	green	
0.312	08	00	0.0	1.0	
0.352	09	00	0.0	1.0	
0.391	0A	00	0.0	1.0	10
0.430	0B	00	0.0	1.0	
0.469	0C	00	0.0	1.0	
0.508	0D	00	0.0	1.0	
0.547	0E	00	0.0	1.0	
0.586	0F	00	0.0	1.0	
0.625	10	40	0.25	0.75	15
0.664	11	40	0.25	0.75	
0.703	12	40	0.25	0.75	
0.742	13	40	0.25	0.75	
0.781	14	40	0.25	0.75	
0.820	15	40	0.25	0.75	
0.859	16	40	0.25	0.75	20
0.898	17	40	0.25	0.75	
0.937	18	40	0.25	0.75	
0.977	19	40	0.25	0.75	
1.016	1A	40	0.25	0.75	
1.055	1B	40	0.25	0.75	
1.094	1C	40	0.25	0.75	
1.133	1D	40	0.25	0.75	25
1.172	1E	40	0.25	0.75	
1.211	1F	40	0.25	0.75	
1.250	20	80	0.5	0.5	
1.289	21	80	0.5	0.5	
1.328	22	80	0.5	0.5	
1.367	23	80	0.5	0.5	30
1.406	24	80	0.5	0.5	
1.445	25	80	0.5	0.5	
1.484	26	80	0.5	0.5	
1.523	27	80	0.5	0.5	
1.562	28	80	0.5	0.5	
1.602	29	80	0.5	0.5	35
1.641	2A	80	0.5	0.5	
1.680	2B	80	0.5	0.5	
1.719	2C	80	0.5	0.5	
1.758	2D	80	0.5	0.5	
1.797	2E	80	0.5	0.5	
1.836	2F	80	0.5	0.5	40
1.875	30	C0	0.75	0.25	
1.914	31	C0	0.75	0.25	
1.953	32	C0	0.75	0.25	
1.992	33	C0	0.75	0.25	
2.031	34	C0	0.75	0.25	
2.070	35	C0	0.75	0.25	45
2.109	36	C0	0.75	0.25	
2.148	37	C0	0.75	0.25	
2.187	38	C0	0.75	0.25	
2.227	39	C0	0.75	0.25	
2.266	3A	C0	0.75	0.25	
2.305	3B	C0	0.75	0.25	
2.344	3C	C0	0.75	0.25	50
2.389	3D	C0	0.75	0.25	
2.422	3E	C0	0.75	0.25	
2.461	3F	C0	0.75	0.25	
2.500	40	FF	1.0	0.0	
2.539	41	FF	1.0	0.0	
2.578	42	FF	1.0	0.0	55
2.617	43	FF	1.0	0.0	
2.656	44	FF	1.0	0.0	
2.695	45	FF	1.0	0.0	
2.734	46	FF	1.0	0.0	
2.773	47	FF	1.0	0.0	
2.812	48	FF	1.0	0.0	60
2.852	49	FF	1.0	0.0	
2.891	4A	FF	1.0	0.0	
2.930	4B	FF	1.0	0.0	
2.969	4C	FF	1.0	0.0	
3.008	4D	FF	1.0	0.0	
3.047	4E	FF	1.0	0.0	
3.086	4F	FF	1.0	0.0	65
3.125	50	00	0.0	1.0	

TABLE 1-continued

DATA PORTIONS				
Input Voltage (Volts)	PROM Address (Hex)	'Red' PROM (Hex)	red	green
3.164	51	00	0.0	1.0
3.203	52	00	0.0	1.0
3.242	53	00	0.0	1.0
3.281	54	00	0.0	1.0
3.320	55	00	0.0	1.0
3.359	56	00	0.0	1.0
3.398	57	00	0.0	1.0
3.437	58	00	0.0	1.0
3.477	59	00	0.0	1.0
3.516	5A	00	0.0	1.0
3.555	5B	00	0.0	1.0
3.594	5C	00	0.0	1.0
3.633	5D	00	0.0	1.0
3.672	5E	00	0.0	1.0
3.711	5F	00	0.0	1.0
3.750	60	40	0.25	0.75
3.789	61	40	0.25	0.75
3.828	62	40	0.25	0.75
3.867	63	40	0.25	0.75
3.906	64	40	0.25	0.75
3.945	65	40	0.25	0.75
3.984	66	40	0.25	0.75
4.023	67	40	0.25	0.75
4.062	68	40	0.25	0.75
4.102	69	40	0.25	0.75
4.141	6A	40	0.25	0.75
4.178	6B	40	0.25	0.75
4.219	6C	40	0.25	0.75
4.258	6D	40	0.25	0.75
4.299	6E	40	0.25	0.75
4.336	6F	40	0.25	0.75
4.375	70	80	0.5	0.5
4.414	71	80	0.5	0.5
4.453	72	80	0.5	0.5
4.492	73	80	0.5	0.5
4.531	74	80	0.5	0.5
4.570	75	80	0.5	0.5
4.609	76	80	0.5	0.5
4.648	77	80	0.5	0.5
4.687	78	80	0.5	0.5
4.727	79	80	0.5	0.5
4.766	7A	80	0.5	0.5
4.805	7B	80	0.5	0.5
4.844	7C	80	0.5	0.5
4.883	7D	80	0.5	0.5
4.922	7E	80	0.5	0.5
4.961	7F	80	0.5	0.5
5.000	80	C0	0.75	0.25
5.039	81	C0	0.75	0.25
5.078	82	C0	0.75	0.25
5.117	83	C0	0.75	0.25
5.156	84	C0	0.75	0.25
5.195	85	C0	0.75	0.25
5.234	86	C0	0.75	0.25
5.273	87	C0	0.75	0.25
5.312	88	C0	0.75	0.25
5.352	89	C0	0.75	0.25
5.391	8A	C0	0.75	0.25
5.430	8B	C0	0.75	0.25
5.469	8C	C0	0.75	0.25
5.508	8D	C0	0.75	0.25
5.547	8E	C0	0.75	0.25
5.586	8F	C0	0.75	0.25
5.625	90	FF	1.0	0.0
5.664	91	FF	1.0	0.0
5.703	92	FF	1.0	0.0
5.742	93	FF	1.0	0.0
5.781	94	FF	1.0	0.0
5.820	95	FF	1.0	0.0
5.859	96	FF	1.0	0.0
5.898	97	FF	1.0	0.0
5.937	98	FF	1.0	0.0
5.977	99	FF	1.0	0.0

TABLE 1-continued

DATA PORTIONS				
Input Voltage (Volts)	PROM Address (Hex)	'Red' PROM (Hex)	red	green
6.016	9A	FF	1.0	0.0
6.055	9B	FF	1.0	0.0
6.094	9C	FF	1.0	0.0
6.133	9D	FF	1.0	0.0
6.172	9E	FF	1.0	0.0
6.211	9F	FF	1.0	0.0
6.250	A0	00	0.0	1.0
6.289	A1	00	0.0	1.0
6.328	A2	00	0.0	1.0
6.367	A3	00	0.0	1.0
6.406	A4	00	0.0	1.0
6.445	A5	00	0.0	1.0
6.484	A6	00	0.0	1.0
6.524	A7	00	0.0	1.0
6.562	A8	00	0.0	1.0
6.602	A9	00	0.0	1.0
6.641	AA	00	0.0	1.0
6.680	AB	00	0.0	1.0
6.719	AC	00	0.0	1.0
6.758	AD	00	0.0	1.0
6.797	AE	00	0.0	1.0
6.836	AF	00	0.0	1.0
6.875	B0	40	0.25	0.75
6.914	B1	40	0.25	0.75
6.953	B2	40	0.25	0.75
6.992	B3	40	0.25	0.75
7.031	B4	40	0.25	0.75
7.070	B5	40	0.25	0.75
7.109	B6	40	0.25	0.75
7.148	B7	40	0.25	0.75
7.187	B8	40	0.25	0.75
7.227	B9	40	0.25	0.75
7.266	BA	40	0.25	0.75
7.305	BB	40	0.25	0.75
7.344	BC	40	0.25	0.75
7.383	BD	40	0.25	0.75
7.422	BE	40	0.25	0.75
7.461	BF	40	0.25	0.75
7.500	C0	80	0.5	0.5
7.539	C1	80	0.5	0.5
7.587	C2	80	0.5	0.5
7.617	C3	80	0.5	0.5
7.656	C4	80	0.5	0.5
7.695	C5	80	0.5	0.5
7.734	C6	80	0.5	0.5
7.773	C7	80	0.5	0.5
7.812	C8	80	0.5	0.5
7.852	C9	80	0.5	0.5
7.891	CA	80	0.5	0.5
7.930	CB	80	0.5	0.5
7.969	CC	80	0.5	0.5
8.008	CD	80	0.5	0.5
8.047	CE	80	0.5	0.5
8.086	CF	80	0.5	0.5
8.125	D0	C0	0.75	0.25
8.164	D1	C0	0.75	0.25
8.203	D2	C0	0.75	0.25
8.242	D3	C0	0.75	0.25
8.281	D4	C0	0.75	0.25
8.320	D5	C0	0.75	0.25
8.359	D6	C0	0.75	0.25
8.398	D7	C0	0.75	0.25
8.437	D8	C0	0.75	0.25
8.477	D9	C0	0.75	0.25
8.516	DA	C0	0.75	0.25
8.555	DB	C0	0.75	0.25
8.594	DC	C0	0.75	0.25
8.633	DD	C0	0.75	0.25
8.672	DE	C0	0.75	0.25
8.711	DF	C0	0.75	0.25
8.750	E0	FF	1.0	0.0
8.789	E1	FF	1.0	0.0
8.828	E2	FF	1.0	0.0

TABLE 1-continued

DATA PORTIONS				
Input Voltage (Volts)	PROM Address (Hex)	'Red' PROM (Hex)	red	green
8.867	E3	FF	1.0	0.0
8.906	E4	FF	1.0	0.0
8.945	E5	FF	1.0	0.0
8.984	E6	FF	1.0	0.0
9.023	E7	FF	1.0	0.0
9.062	E8	FF	1.0	0.0
9.102	E9	FF	1.0	0.0
9.141	EA	FF	1.0	0.0
9.180	EB	FF	1.0	0.0
9.219	EC	FF	1.0	0.0
9.258	ED	FF	1.0	0.0
9.299	EE	FF	1.0	0.0
9.336	EF	FF	1.0	0.0
9.375	F0	00	0.0	1.0
9.414	F1	00	0.0	1.0
9.453	F2	00	0.0	1.0
9.492	F3	00	0.0	1.0
9.531	F4	00	0.0	1.0
9.570	F5	00	0.0	1.0
9.609	F6	00	0.0	1.0
9.648	F7	00	0.0	1.0
9.687	F8	00	0.0	1.0
9.727	F9	00	0.0	1.0
9.766	FA	00	0.0	1.0
9.805	FB	00	0.0	1.0
9.844	FC	00	0.0	1.0
9.883	FD	00	0.0	1.0
9.922	FE	00	0.0	1.0
9.961	FF	00	0.0	1.0

TABLE 2

DATA PORTIONS								
Input Voltage (Volts)	PROM Address (Hex)	'Red' PROM (Hex)	'Green' PROM (Hex)	'Blue' PROM (Hex)	red	green	blue	
0.0	00	FF	00	00	1.0	0.0	0.0	
0.039	01	FE	02	00	0.992	0.008	0.0	
0.078	02	FC	04	00	0.984	0.016	0.0	
0.117	03	FA	06	00	0.976	0.024	0.0	
0.156	04	F8	08	00	0.969	0.031	0.0	
0.195	05	F6	0A	00	0.961	0.039	0.0	
0.234	06	F4	0C	00	0.953	0.047	0.0	
0.273	07	F2	0E	00	0.945	0.055	0.0	
0.312	08	F0	10	00	0.937	0.063	0.0	
0.352	09	EE	12	00	0.930	0.070	0.0	
0.391	0A	EC	14	00	0.922	0.078	0.0	
0.430	0B	EA	16	00	0.914	0.086	0.0	
0.469	0C	E8	18	00	0.906	0.094	0.0	
0.508	0D	E6	1A	00	0.899	0.101	0.0	
0.547	0E	E4	1C	00	0.891	0.109	0.0	
0.586	0F	E2	1E	00	0.883	0.117	0.0	
0.625	10	E0	20	00	0.875	0.125	0.0	
0.664	11	DE	22	00	0.867	0.133	0.0	
0.703	12	DC	24	00	0.859	0.141	0.0	
0.742	13	DA	26	00	0.851	0.149	0.0	
0.781	14	D8	28	00	0.844	0.156	0.0	
0.820	15	D6	2A	00	0.836	0.164	0.0	
0.859	16	D4	2C	00	0.828	0.172	0.0	
0.898	17	D2	2E	00	0.820	0.180	0.0	
0.937	18	D0	30	00	0.812	0.188	0.0	
0.977	19	CE	32	00	0.804	0.196	0.0	
1.016	1A	CC	34	00	0.796	0.204	0.0	
1.055	1B	CA	36	00	0.788	0.212	0.0	
1.094	1C	C8	38	00	0.781	0.219	0.0	
1.133	1D	C6	3A	00	0.773	0.227	0.0	
1.172	1E	C4	3C	00	0.766	0.234	0.0	
1.211	1F	C2	3E	00	0.758	0.242	0.0	

TABLE 2-continued

DATA PORTIONS							
Input Voltage (Volts)	PROM Address (Hex)	'Red' PROM (Hex)	'Green' PROM (Hex)	'Blue' PROM (Hex)	red	green	blue
1.250	20	C0	40	00	0.75	0.25	0.0
1.289	21	BE	42	00	0.742	0.258	0.0
1.328	22	BC	44	00	0.734	0.266	0.0
1.367	23	BA	46	00	0.726	0.274	0.0
1.406	24	B8	48	00	0.719	0.281	0.0
1.445	25	B6	4A	00	0.711	0.289	0.0
1.484	26	B4	4C	00	0.703	0.297	0.0
1.523	27	B2	4E	00	0.695	0.305	0.0
1.562	28	B0	50	00	0.687	0.313	0.0
1.602	29	AE	52	00	0.680	0.320	0.0
1.641	2A	AC	54	00	0.672	0.328	0.0
1.680	2B	AA	56	00	0.664	0.336	0.0
1.719	2C	A8	58	00	0.656	0.344	0.0
1.758	2D	A6	5A	00	0.648	0.352	0.0
1.797	2E	A4	5C	00	0.641	0.359	0.0
1.836	2F	A2	5E	00	0.633	0.367	0.0
1.875	30	A0	60	00	0.625	0.375	0.0
1.914	31	9E	62	00	0.613	0.383	0.0
1.953	32	9C	64	00	0.609	0.391	0.0
1.992	33	9A	66	00	0.602	0.398	0.0
2.031	34	98	68	00	0.594	0.406	0.0
2.070	35	96	6A	00	0.586	0.414	0.0
2.109	36	94	6C	00	0.578	0.422	0.0
2.148	37	92	6E	00	0.570	0.430	0.0
2.187	38	90	70	00	0.562	0.438	0.0
2.227	39	8E	72	00	0.554	0.446	0.0
2.266	3A	8C	74	00	0.547	0.453	0.0
2.305	3B	8A	76	00	0.539	0.461	0.0
2.344	3C	88	78	00	0.531	0.469	0.0
2.389	3D	86	7A	00	0.524	0.476	0.0
2.422	3E	84	7C	00	0.516	0.484	0.0
2.461	3F	82	7E	00	0.508	0.492	0.0
2.500	40	80	80	00	0.5	0.5	0.0
2.539	41	7C	84	00	0.484	0.516	0.0
2.578	42	78	88	00	0.469	0.531	0.0
2.617	43	74	8C	00	0.453	0.547	0.0
2.656	44	70	90	00	0.437	0.563	0.0
2.695	45	6C	94	00	0.422	0.578	0.0
2.734	46	68	98	00	0.406	0.594	0.0
2.773	47	64	9C	00	0.391	0.609	0.0
2.812	48	60	A0	00	0.375	0.625	0.0
2.852	49	5C	A4	00	0.359	0.641	0.0
2.891	4A	58	A8	00	0.344	0.656	0.0
2.930	4B	54	AC	00	0.328	0.672	0.0
2.969	4C	50	B0	00	0.312	0.688	0.0
3.008	4D	4C	B4	00	0.297	0.703	0.0
3.047	4E	48	B8	00	0.281	0.719	0.0
3.086	4F	44	BC	00	0.266	0.734	0.0
3.125	50	40	C0	00	0.25	0.75	0.0
3.164	51	3C	C4	00	0.234	0.766	0.0
3.203	52	38	C8	00	0.219	0.781	0.0
3.242	53	34	CC	00	0.203	0.797	0.0
3.281	54	30	D0	00	0.187	0.813	0.0
3.320	55	2C	D4	00	0.172	0.828	0.0
3.359	56	28	D8	00	0.156	0.844	0.0
3.398	57	24	DC	00	0.141	0.859	0.0
3.437	58	20	E0	00	0.125	0.875	0.0
3.477	59	1C	E4	00	0.109	0.891	0.0
3.516	5A	18	E8	00	0.094	0.906	0.0
3.555	5B	14	EC	00	0.078	0.922	0.0
3.594	5C	10	F0	00	0.062	0.938	0.0
3.633	5D	0C	F4	00	0.047	0.953	0.0
3.672	5E	08	F8	00	0.031	0.967	0.0
3.711	5F	04	FC	00	0.016	0.984	0.0
3.750	60	00	FF	00	0.0	1.0	0.0
3.789	61	00	F8	08	0.0	0.969	0.031
3.828	62	00	F0	10	0.0	0.937	0.063
3.867	63	00	E8	18	0.0	0.906	0.094
3.906	64	00	E0	20	0.0	0.875	0.125
3.945	65	00	D8	28	0.0	0.844	0.156
3.984	66	00	D0	30	0.0	0.812	0.188
4.023	67	00	C8	38	0.0	0.781	0.219
4.062	68	00	C0	40	0.0	0.75	0.25

TABLE 2-continued

DATA PORTIONS							
Input Voltage (Volts)	PROM Address (Hex)	'Red' PROM (Hex)	'Green' PROM (Hex)	'Blue' PROM (Hex)	red	green	blue
4.102	69	00	B8	48	0.0	0.719	0.281
4.141	6A	00	B0	50	0.0	0.687	0.313
4.178	6B	00	A8	58	0.0	0.656	0.344
4.219	6C	00	A0	60	0.0	0.625	0.375
4.258	6D	00	98	68	0.0	0.594	0.406
4.299	6E	00	90	70	0.0	0.562	0.438
4.336	6F	00	88	78	0.0	0.531	0.469
4.375	70	00	80	80	0.0	0.5	0.5
4.414	71	00	78	88	0.0	0.469	0.531
4.453	72	00	70	90	0.0	0.437	0.563
4.492	73	00	68	98	0.0	0.406	0.594
4.531	74	00	60	A0	0.0	0.375	0.625
4.570	75	00	58	A8	0.0	0.344	0.656
4.609	76	00	50	B0	0.0	0.312	0.688
4.648	77	00	48	B8	0.0	0.281	0.719
4.687	78	00	40	C0	0.0	0.25	0.75
4.727	79	00	38	C8	0.0	0.219	0.781
4.766	7A	00	30	D0	0.0	0.187	0.813
4.805	7B	00	28	D8	0.0	0.156	0.844
4.844	7C	00	20	E0	0.0	0.125	0.875
4.883	7D	00	18	E8	0.0	0.094	0.906
4.922	7E	00	10	F0	0.0	0.062	0.938
4.961	7F	00	08	F8	0.0	0.031	0.967
5.000	80	00	00	FF	0.0	0.0	1.0
5.039	81	04	00	FC	0.016	0.0	0.984
5.078	82	08	00	F8	0.031	0.0	0.969
5.117	83	0C	00	F4	0.047	0.0	0.953
5.156	84	10	00	F0	0.063	0.0	0.937
5.195	85	14	00	EC	0.078	0.0	0.922
5.234	86	18	00	E8	0.094	0.0	0.906
5.273	87	1C	00	E4	0.109	0.0	0.891
5.312	88	20	00	E0	0.125	0.0	0.875
5.352	89	24	00	DC	0.141	0.0	0.859
5.391	8A	28	00	D8	0.156	0.0	0.844
5.430	8B	2C	00	D4	0.172	0.0	0.828
5.469	8C	30	00	D0	0.188	0.0	0.812
5.508	8D	34	00	CC	0.2	0.0	0.8
5.547	8E	38	00	C8	0.219	0.0	0.781
5.586	8F	3C	00	C4	0.234	0.0	0.766
5.625	90	40	00	C0	0.25	0.0	0.75
5.664	91	44	00	BC	0.266	0.0	0.734
5.703	92	48	00	B8	0.281	0.0	0.719
5.742	93	4C	00	B4	0.297	0.0	0.703
5.781	94	50	00	B0	0.313	0.0	0.687
5.820	95	54	00	AC	0.328	0.0	0.672
5.859	96	58	00	A8	0.344	0.0	0.656
5.898	97	5C	00	A4	0.359	0.0	0.641
5.937	98	60	00	A0	0.375	0.0	0.625
5.977	99	64	00	9C	0.391	0.0	0.609
6.016	9A	68	00	98	0.406	0.0	0.594
6.055	9B	6C	00	94	0.422	0.0	0.578
6.094	9C	70	00	90	0.438	0.0	0.562
6.133	9D	74	00	8C	0.453	0.0	0.547
6.172	9E	78	00	88	0.469	0.0	0.531
6.211	9F	7C	00	84	0.484	0.0	0.516
6.250	A0	80	00	80	0.5	0.0	0.5
6.289	A1	84	00	7C	0.516	0.0	0.484
6.328	A2	88	00	78	0.531	0.0	0.469
6.367	A3	8C	00	74	0.547	0.0	0.453
6.406	A4	90	00	70	0.563	0.0	0.437
6.445	A5	94	00	6C	0.578	0.0	0.422
6.484	A6	98	00	68	0.594	0.0	0.406
6.524	A7	9C	00	64	0.609	0.0	0.391
6.562	A8	A0	00	60	0.625	0.0	0.375
6.602	A9	A4	00	5C	0.641	0.0	0.359
6.641	AA	A8	00	58	0.656	0.0	0.344
6.680	AB	AC	00	54	0.672	0.0	0.328
6.719	AC	B0	00	50	0.688	0.0	0.312
6.758	AD	B4	00	4C	0.703	0.0	0.297
6.797	AE	B8	00	48	0.719	0.0	0.281
6.836	AF	BC	00	44	0.734	0.0	0.266
6.875	B0	C0	00	40	0.75	0.0	0.25
6.914	B1	C4	00	3C	0.766	0.0	0.234

TABLE 2-continued

Input Voltage (Volts)	PROM Address (Hex)	DATA PORTIONS			red	green	blue
		'Red' PROM (Hex)	'Green' PROM (Hex)	'Blue' PROM (Hex)			
6.953	B2	C8	00	38	0.781	0.0	0.219
6.992	B3	CC	00	34	0.797	0.0	0.203
7.031	B4	D8	00	30	0.813	0.0	0.187
7.070	B5	D4	00	2C	0.828	0.0	0.172
7.109	B6	D8	00	28	8.844	0.0	0.156
7.148	B7	DC	00	24	0.859	0.0	0.141
7.187	B8	E0	00	20	0.875	0.0	0.125
7.227	B9	E4	00	1C	0.891	0.0	0.109
7.266	BA	E8	00	18	0.906	0.0	0.094
7.305	BB	EC	00	14	0.922	0.0	0.078
7.344	BC	F0	00	10	0.938	0.0	0.062
7.383	BD	F4	00	0C	0.953	0.0	0.047
7.422	BE	F8	00	08	0.967	0.0	0.031
7.461	BF	FC	00	04	0.984	0.0	0.016

What I claim is:

**1. A variable color digital display system comprising:**

a plurality of adjacent variable color light emitting diode digital display elements for exhibiting a digital value; timing means for developing sequential timing signals; means for sequentially providing a digital indication, on said display elements, of a plurality of digital values, in accordance with said timing signals;

a memory for sequentially storing data corresponding to said digital values, in accordance with said timing signals;

a comparator for comparing the exhibited digital value with the data stored in said memory and for developing a first comparison signal when the exhibited digital value is equal to the data stored in said memory and a second comparison signal when the exhibited digital value is not equal to the data stored in said memory;

a color control for illuminating said digital indication in a first color in response to said first comparison signal and in a second color in response to said second comparison signal.

**2. A variable color digital display system comprising:**

a plurality of adjacent variable color light emitting diode digital display elements for exhibiting a digital value; timing means for developing sequential timing signals; means for sequentially providing a digital indication, on said display elements, of a plurality of digital values, in accordance with said timing signals;

a memory for sequentially storing data corresponding to said digital values, in accordance with said timing signals;

a comparator for comparing the exhibited digital value with the data stored in said memory and for developing a first comparison signal when the exhibited digital value is larger than the data stored in said memory, a second comparison signal when the exhibited digital value is less than the data stored in said memory, and a third comparison signal when the exhibited digital value is equal to the data stored in said memory;

a color control for illuminating said digital indication in a first color in response to said first comparison signal, in a second color in response to said second comparison signal, and in a third color in response to said third comparison signal.

**3. A variable color digital display system comprising:**

a plurality of adjacent variable color light emitting diode digital display elements for exhibiting a digital value; timing means for developing a first timing signal and a second timing signal;

means for sequentially providing a digital indication, on said display elements, of a first digital value, in accordance with said first timing signal, and of a second digital value, in accordance with said second timing signal;

a memory for storing data corresponding to said first digital value, in accordance with said first timing signal;

means for comparing, in accordance with said second timing signal, said second digital value with the data stored in said memory and for developing a first comparison signal when said second digital value is equal to the data stored in said memory and a second comparison signal when said second digital value is not equal to the data stored in said memory;

a color control for controlling the color of said digital indication, in accordance with said second timing signal, for illuminating said digital indication in a first color in response to said first comparison signal and in a second color in response to said second comparison signal.

**4. A variable color digital display system comprising:**

a plurality of adjacent variable color light emitting diode digital display elements for exhibiting a digital value; timing means for developing a first timing signal and a second timing signal;

means for sequentially providing a digital indication, on said display elements, of a first digital value, in accordance with said first timing signal, and of a second digital value, in accordance with said second timing signal;

a memory for storing data corresponding to said first digital value, in accordance with said first timing signal;

means for comparing, in accordance with said second timing signal, said second digital value with the data stored in said memory and for developing a first comparison signal when said second digital value is larger than the data stored in said memory, a second comparison signal when said second digital value is less than the data stored in said memory, and a third comparison signal when said second digital value is equal to the data stored in said memory;

a color control for controlling the color of said digital indication, in accordance with said second timing signal, for illuminating said digital indication in a first color in response to said first comparison signal, in a second color in response to said second comparison signal, and in a third color in response to said third comparison signal.

**5. A variable color digital display system comprising:**

a plurality of adjacent variable color light emitting diode digital display elements for exhibiting a digital value, each said display element including a color control input for controlling its color, the color control inputs of each of said display elements being interconnected for controlling the color of said display elements uniformly;

timing means for developing a first timing signal and a second timing signal;

means for sequentially exhibiting on said display elements a first digital value, in accordance with said first timing signal, and a second digital value, in accordance with said second timing signal;

a memory for storing data corresponding to said first digital value, in accordance with said first timing signal;

a comparator for comparing, in accordance with said second timing signal, said second digital value with the data stored in said memory, said comparator having a comparator output for developing a first comparison signal when said second digital value is equal to the data stored in said memory and a second comparison signal when said second digital value is not equal to the data stored in said memory, said comparator output being connected to the interconnected color control inputs of said display elements for controlling the color of the exhibited second digital value in accordance with its relation to the first digital value.

6. A variable color digital display system comprising:

a plurality of adjacent variable color light emitting diode digital display elements for exhibiting a digital value, each said display element including a first color control input, for illuminating said display element in a first color, and a second color control input, for illuminating said display element in a second color, the first color control inputs of each of said display elements being interconnected, and the second color control inputs of each of said display elements being interconnected, for controlling the color of said display elements uniformly;

timing means for developing a first timing signal and a second timing signal;

means for sequentially exhibiting on said display elements a first digital value, in accordance with said first timing signal, and a second digital value, in accordance with said second timing signal;

a memory for storing data corresponding to said first digital value, in accordance with said first timing signal;

a comparator for comparing, in accordance with said second timing signal, said second digital value with the data stored in said memory, said comparator having a first comparator output, for developing a comparison signal when said second digital value is equal to the data stored in said memory, and a second comparator output, for developing a comparison signal when said second digital value is not equal to the data stored in said memory, said first comparator output being connected to the interconnected first color control inputs of said display elements, and said second comparator output being connected to the interconnected second color control inputs of said display elements, for controlling the color of the exhibited second digital value in accordance with its relation to the first digital value.

7. A variable color digital display system comprising:

a plurality of adjacent variable color light emitting diode digital display elements for exhibiting a digital value, each said display element including a first color control input, for illuminating said display element in a first color, a second color control input, for illuminating said display element in a second color, and a third color control input, for illuminating said display element in a third color, the first color control inputs of each of said display elements being interconnected, the second color control inputs of each of said display elements

being interconnected, and said third color control inputs of each of said display elements being interconnected, for controlling the color of said display elements uniformly;

timing means for developing a first timing signal and a second timing signal;

means for sequentially exhibiting on said display elements a first digital value, in accordance with said first timing signal, and a second digital value, in accordance with said second timing signal;

a memory for storing data corresponding to said first digital value, in accordance with said first timing signal;

a comparator for comparing, in accordance with said second timing signal, said second digital value with the data stored in said memory, said comparator having a first comparator output, for developing a comparison signal when said second digital value is larger than the data stored in said memory, a second comparator output, for developing a comparison signal when said second digital value is less than the data stored in said memory, and a third comparator output, for developing a comparison signal when said second digital value is equal to the data stored in said memory, said first comparator output being connected to the interconnected first color control inputs of said display elements, said second comparator output being connected to the interconnected second color control inputs of said display elements, and said third comparator output being connected to the interconnected third color control inputs of said display elements, for controlling the color of the exhibited second digital value in accordance with its relation to the first digital value.

8. A variable color digital display system comprising:

a plurality of adjacent variable color light emitting diode digital display elements for exhibiting a digital value, each said display element including a color control input for controlling its color;

timing means for developing a first timing signal and a second timing signal;

means for sequentially exhibiting on said display elements a first digital value, in accordance with said first timing signal, and a second digital value, in accordance with said second timing signal;

a memory for storing data corresponding to said first digital value, in accordance with said first timing signal;

means for comparing, in accordance with said second timing signal, said second digital value with the data stored in said memory and for developing a first comparison signal when said second digital value is equal to the data stored in said memory and a second comparison signal when said second digital value is not equal to the data stored in said memory;

a color control for applying said first comparison signal and said second comparison signal to said color control inputs for uniformly controlling the color of the exhibited second digital value in accordance with its relation to the first digital value.

9. A variable color digital display system comprising:

a plurality of adjacent variable color light emitting diode digital display elements for exhibiting a digital value, each said display element including a plurality of color control inputs for controlling its color;

timing means for developing a first timing signal and a second timing signal;

means for sequentially exhibiting on said display elements a first digital value, in accordance with said first timing signal, and a second digital value, in accordance with said second timing signal;

a memory for storing data corresponding to said first digital value, in accordance with said first timing signal;

means for comparing, in accordance with said second timing signal, said second digital value with the data stored in said memory and for developing a first comparison signal when said second digital value is larger than the data stored in said memory, a second comparison signal when said second digital value is less than the data stored in said memory, and a third comparison signal when said second digital value is equal to the data stored in said memory;

a color control for applying said first comparison signal, said second comparison signal, and said third comparison signal to said color control inputs for uniformly controlling the color of the exhibited second digital value in accordance with its relation to the first digital value.

**10.** A variable color digital display system comprising:

a plurality of adjacent variable color light emitting diode digital display elements for exhibiting a digital value, each said display element including a color control input for controlling its color;

timing means for developing a first timing signal and a second timing signal;

means for sequentially exhibiting on said display elements a first digital value, in accordance with said first timing signal, and a second digital value, in accordance with said second timing signal;

a registered comparator for storing data corresponding to said first digital value, in accordance with said first timing signal, for comparing, in accordance with said second timing signal, said second digital value with said data, and for developing a first comparison signal when said second digital value is equal to said data and a second comparison signal when said second digital value is not equal to said data;

a color control for applying said first comparison signal and said second comparison signal to said color control inputs for uniformly controlling the color of the exhibited second digital value in accordance with its relation to the first digital value.

**11.** A variable color digital display system comprising:

a plurality of adjacent variable color light emitting diode digital display elements for exhibiting a digital value, each said display element including a plurality of color control inputs for controlling its color;

timing means for developing a first timing signal and a second timing signal;

means for sequentially exhibiting on said display elements a first digital value, in accordance with said first timing signal, and a second digital value, in accordance with said second timing signal;

a registered comparator for storing data corresponding to said first digital value, in accordance with said first timing signal, for comparing, in accordance with said second timing signal, said second digital value with said data, and for developing a first comparison signal when said second digital value is larger than said data, a second comparison signal when said second digital value is less than said data, and a third comparison signal when said second digital value is equal to said data;

a color control for applying said first comparison signal, said second comparison signal, and said third comparison signal to said color control inputs for uniformly controlling the exhibited second digital value in accordance with its relation to the first digital value.

**12.** A variable color digital display system comprising:

a plurality of adjacent variable color light emitting diode digital display elements for exhibiting a digital value, each said display element including a first color control input, for illuminating said display element in a first color, and a second color control input, for illuminating said display element in a second color, the first color control inputs of each of said display elements being interconnected, and the second color control inputs of each of said display elements being interconnected, for controlling the color of said display elements uniformly;

timing means for developing a first timing signal and a second timing signal;

a memory for storing data corresponding to a first digital value, in accordance with said first timing signal;

means for exhibiting on said display elements a second digital value, in accordance with said second timing signal;

means for comparing, in accordance with said second timing signal, said second digital value with the data stored in said memory, said comparator having a first comparator output, for developing a comparison signal when said second digital value is equal to the data stored in said memory, and a second comparator output, for developing a comparison signal when said second digital value is not equal to the data stored in said memory, said first comparator output being connected to the interconnected first color control inputs of said display elements, and said second comparator output being connected to the interconnected second color control inputs of said display elements, for controlling their color accordingly.

**13.** A variable color digital display system comprising:

a plurality of adjacent variable color light emitting diode digital display elements for exhibiting a digital value, each said display element including a first color control input, for illuminating said display element in a first color, a second color control input, for illuminating said display element in a second color, and a third color control input, for illuminating said display element in a third color, the first color control inputs of each of said display elements being interconnected, the second color control inputs of each of said display elements being interconnected, and said third color control inputs of each of said display elements being interconnected, for controlling the color of said display elements uniformly;

timing means for developing a first timing signal and a second timing signal;

a memory for storing data corresponding to a first digital value, in accordance with said first timing signal;

means for sequentially exhibiting on said display elements a second digital value, in accordance with said second timing signal;

means for comparing, in accordance with said second timing signal, said second digital value with the data stored in said memory, said comparator having a first comparator output, for developing a comparison signal when said second digital value is larger than the data

stored in said memory, a second comparator output, for developing a comparison signal when said second digital value is less than the data stored in said memory, and a third comparator output, for developing a comparison signal when said second digital value is equal to the data stored in said memory, said first comparator output being connected to the interconnected first color control inputs of said display elements, said second comparator output being connected to the interconnected second color control inputs of said display elements, and said third comparator output being connected to the interconnected third color control inputs of said display elements, for controlling their color accordingly.

- 14.** A variable color digital display system comprising:  
 a plurality of adjacent variable color light emitting diode digital display elements for exhibiting a digital value, each said display element including a color control input for controlling its color;  
 timing means for developing a first timing signal and a second timing signal;  
 a memory for storing data corresponding to a first digital value, in accordance with said first timing signal;  
 means for sequentially exhibiting on said display elements a second digital value, in accordance with said second timing signal;  
 means for comparing, in accordance with said second timing signal, said second digital value with the data stored in said memory and for developing a first comparison signal when said second digital value is equal to the data stored in said memory and a second comparison signal when said second digital value is not equal to the data stored in said memory;  
 a color control for applying said first comparison signal and said second comparison signal to said color control inputs for uniformly controlling the color of the exhibited second digital value in accordance with its relation to the first digital value.

- 15.** A variable color digital display system comprising:  
 a plurality of adjacent variable color light emitting diode digital display elements for exhibiting a digital value, each said display element including a plurality of color control inputs for controlling its color;  
 timing means for developing a first timing signal and a second timing signal;  
 a memory for storing data corresponding to a first digital value, in accordance with said first timing signal;  
 means for sequentially exhibiting on said display elements a second digital value, in accordance with said second timing signal;  
 means for comparing, in accordance with said second timing signal, said second digital value with the data stored in said memory and for developing a first comparison signal when said second digital value is larger than the data stored in said memory, a second comparison signal when said second digital value is less than the data stored in said memory, and a third comparison signal when said second digital value is equal to the data stored in said memory;  
 a color control for applying said first comparison signal, said second comparison signal, and said third comparison signal to said color control inputs for uniformly controlling the color of the exhibited second digital value in accordance with its relation to the first digital value.

- 16.** A variable color digital display system comprising:  
 a single variable color light emitting diode digital display element for exhibiting a digital value, said display element including a color control input for controlling its color;  
 a counter for developing a first timing signal and a second timing signal;  
 a memory for storing data corresponding to a first digital value, in accordance with said first timing signal;  
 a decoder for providing a digital indication, on said display element, of a second digital value, in accordance with said second timing signal;  
 a comparator for comparing, in accordance with said second timing signal, said second digital value with the data stored in said memory, said comparator including a comparator output for developing a first comparison signal when said second digital value is equal to the data stored in said memory and a second comparison signal when said second digital value is not equal to the data stored in said memory;  
 a color control for applying said comparator output to said color control input, for illuminating said digital indication in a first color in response to said first comparison signal and in a second color in response to said second comparison signal.
- 17.** A variable color digital display system comprising:  
 a single variable color light emitting diode digital display element for exhibiting a digital value, said display element including a first color control input for illuminating, upon activation of said first color control input, said display element in a first color and a second color control input for illuminating, upon activation of said second color control input, said display element in a second color;  
 a counter for developing a first timing signal and a second timing signal;  
 a memory for storing data corresponding to a first digital value, in accordance with said first timing signal;  
 a decoder for providing a digital indication, on said display element, of a second digital value, in accordance with said second timing signal;  
 a comparator for comparing, in accordance with said second timing signal, said second digital value with the data stored in said memory, said comparator including a first comparator output for developing a comparison signal when said second digital value is equal to the data stored in said memory and a second comparator output for developing a comparison signal when said second digital value is not equal to the data stored in said memory;  
 a color control for applying said first comparator output to said first color control input, for illuminating said digital indication in a first color in response to the comparison signal developed on said first comparator output, and for applying said second comparator output to said second color control input, for illuminating said digital indication in a second color in response to the comparison signal developed on said second comparator output.
- 18.** A variable color digital display system comprising:  
 a single variable color light emitting diode digital display element for exhibiting a digital value, said display element including a first color control input for illuminating, upon activation of said first color control input, said display element in a first color, a second



## 51

color control input for illuminating, upon activation of said second color control input, said display element in a second color, and a third color control input for illuminating, upon activation of said third color control input, said display element in a third color;

a counter for developing a first timing signal and a second timing signal;

a memory for storing data corresponding to a first digital value, in accordance with said first timing signal;

a decoder for providing a digital indication, on said display element, of a second digital value, in accordance with said second timing signal;

a comparator for comparing, in accordance with said second timing signal, said second digital value with the data stored in said memory, said comparator including a first comparator output for developing a comparison signal when said second digital value is larger than the data stored in said memory, a second comparator output for developing a comparison signal when said second digital value is less than the data stored in said memory, and a third comparator output when said digital value is equal to the data stored in said memory;

a color control for applying said first comparator output to said first color control input, for illuminating said digital indication in a first color in response to the comparison signal developed on said first comparator output, for applying said second comparator output to said second color control input, for illuminating said digital indication in a second color in response to the comparison signal developed on said second comparator output, and for applying said third comparator output to said third color control input, for illuminating said digital indication in a third color in response to the comparison signal developed on said third comparator output.

**19.** A variable color display device comprising:  
a variable color light emitting diode display element for exhibiting a digital value;  
timing means for developing sequential timing signals;  
means for sequentially providing a digital indication, on said display element, of a plurality of digital values, in accordance with said timing signals;  
memory means for storing data corresponding to said digital values, in accordance with said timing signals;  
means for comparing the value of the exhibited digital indication with the data stored in said memory means, and for developing a comparison signal accordingly;  
and  
means for controlling the color of said digital indication in accordance with said comparison signal.

**20.** A variable color display device comprising:  
a variable color light emitting diode display element for exhibiting a digital value;  
timing means for sequentially developing a first timing signal and a second timing signal;  
memory means for storing data corresponding to a first digital value, in accordance with said first timing signal;  
means for providing a digital indication, on said display element, of a second digital value, in accordance with said second timing signal;  
means for comparing the value of said second digital indication with the data stored in said memory means, and for developing a comparison signal accordingly;  
and

## 52

means for controlling the color of said digital indication in accordance with said comparison signal.

**21.** A variable color display device comprising:  
a variable color light emitting diode display element for exhibiting a digital value;  
timing means for sequentially developing a first timing signal and a second timing signal;  
memory means for storing data corresponding to a first digital value, in accordance with said first timing signal;  
means for providing a digital indication, on said display element, of a second digital value, in accordance with said second timing signal;  
means for comparing the value of said second digital indication with the data stored in said memory means, and for developing a first comparison signal when the value of said second digital indication is larger than said data, and a second comparison signal when the value of said second digital indication is less than said data; and  
means for illuminating said digital indication in a first color in response to said first comparison signal, and in a second color in response to said second comparison signal.

**22.** A variable color display device comprising:  
a variable color light emitting diode display element for exhibiting a digital value;  
timing means for sequentially developing a first timing signal and a second timing signal;  
memory means for storing data corresponding to a first digital value, in accordance with said first timing signal;  
means for providing a digital indication, on said display element, of a second digital value, in accordance with said second timing signal;  
means for comparing the value of said second digital indication with the data stored in said memory means, and for developing a first comparison signal when the value of said second digital indication is larger than said data, a second comparison signal when the value of said second digital indication is less than said data, and a third comparison signal when the value of said second digital indication is equal to said data; and  
means for illuminating said digital indication in a first color in response to said first comparison signal, in a second color in response to said second comparison signal, and in a third color in response to said third comparison signal.

**23.** A variable color display device comprising:  
a variable color light emitting diode display element for exhibiting a digital value and including a first color control input for illuminating, in response to an active color control signal, said digital value in a first color, and a second color control input for illuminating, in response to an active color control signal, said digital value in a second color;  
timing means for sequentially developing a first timing signal and a second timing signal;  
memory means for storing data corresponding to a first digital value, in accordance with said first timing signal;  
means for providing a digital indication, on said display element, of a second digital value, in accordance with said second timing signal;

**53**

means for comparing the value of said second digital indication with the data stored in said memory means, said means for comparing including a first comparator output for developing a comparison signal when the value of said second digital indication is larger than said data, and a second comparator output for developing a comparison signal when the value of said second digital indication is less than said data; and

means for coupling said first comparator output to said first color control input and said second comparator output to said second color control input.

**24.** A variable color display device comprising:

a variable color light emitting diode display element for exhibiting a digital value:

timing means for sequentially developing a first timing signal and a second timing signal;

**54**

memory means for storing data corresponding to a first digital value, in accordance with said first timing signal, and including a memory output indicative of the stored data;

means for providing a digital indication, on said display element, of a second digital value, in accordance with said second timing signal;

means for comparing, including a first input responsive to said memory output and a second input responsive to the value of said second digital indication, for developing a comparison signal in accordance with the relation of the value of said digital indication to said stored data; and

means for controlling the color of said digital indication in accordance with said comparison signal.

\* \* \* \* \*