



US006179426B1

(12) **United States Patent**
Rodriguez, Jr. et al.

(10) **Patent No.:** **US 6,179,426 B1**
(45) **Date of Patent:** **Jan. 30, 2001**

(54) **INTEGRATED FRONT PROJECTION SYSTEM**

(75) Inventors: **Ernesto M. Rodriguez, Jr.; Dennis F. Vanderwerf**, both of Austin, TX (US)

(73) Assignee: **3M Innovative Properties Company**, Saint Paul, MN (US)

(*) Notice: Under 35 U.S.C. 154(b), the term of this patent shall be extended for 0 days.

(21) Appl. No.: **09/261,715**

(22) Filed: **Mar. 3, 1999**

(51) **Int. Cl.**⁷ **G03B 21/14**

(52) **U.S. Cl.** **353/69; 353/79; 353/119**

(58) **Field of Search** **353/79, 39, 69, 353/70, 119, 122; 248/917, 918, 919, 920**

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,979,921	*	11/1934	Wier	353/79
3,940,209	*	2/1976	Portner et al.	353/79
3,951,534	*	4/1976	Altman	353/70
4,012,115		3/1977	Brown	350/128
4,092,064	*	5/1978	Puel	353/79
4,130,352	*	12/1978	Overman et al.	353/79
4,156,561		5/1979	Lucas	353/38
4,298,246		11/1981	Iwamura	350/122
4,565,430		1/1986	Grunwald	353/61
4,756,615	*	7/1988	Hildebrand	353/74
4,787,737	*	11/1988	Ogawa et al.	353/57
4,911,529	*	3/1990	Van DeVen	
5,096,278	*	3/1992	Yoshioka et al.	359/459
5,210,641		5/1993	Lewis	359/448
5,278,596	*	1/1994	Machtig	353/122

5,349,400	*	9/1994	Kaplan et al.	353/119
5,624,173	*	4/1997	Davidson	353/119
5,663,817		9/1997	Frapin et al.	349/5
5,694,245		12/1997	Goto et al.	359/460
6,023,369		2/2000	Goto	359/443

FOREIGN PATENT DOCUMENTS

1226687A		8/1999	(CN)	G03B/21/56
197 12 244					
A1		10/1998	(DE)	G03B/21/10
0 837 351 A2		4/1998	(EP)	G02B/27/28
0 837 351 A3		12/1998	(EP)	G02B/27/28
05297465		11/1993	(JP)	G03B/21/60

* cited by examiner


Primary Examiner—William Dowling

(74) *Attorney, Agent, or Firm*—Nester F. Ho

(57) **ABSTRACT**

A front projection display system that integrates an optical engine, having control and power supply electronics, and a dedicated projection screen to provide a compact video display device. The projection engine is coupled to a high gain projection screen, having an optimized reflection pattern to give optimum optical performance in ambient light and viewing angle sensitive environments. Components of the projection engine are modularly placed in a retractable arm, pivotally connected to the screen. The arm offers precise registration to the screen apparatus and thus repeatedly precisely aligns optically and mechanically to the screen. The projection wall system has an open projection position and a closed storage position. Use of a radically offset projection head having matching keystone correction features allows the arm to protrude above the head of the presenter and offer a sharp and unobtrusive projection zone.

35 Claims, 18 Drawing Sheets






FIG. 1





FIG. 2






FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16







FIG. 17



INTEGRATED FRONT PROJECTION SYSTEM

BACKGROUND OF THE INVENTION

The present invention relates to an integrated front projection display system. In particular, the present invention relates to a low-profile integrated front projection system that coordinates specialized projection optics and an integral screen optimized to work in conjunction with the optics to create the best viewing performance and produce the necessary keystone correction.

Electronic or video display systems are devices capable of presenting video or electronically generated images. Whether for use in home-entertainment, advertising, videoconferencing, computing, data-conferencing or group presentations, the demand exists for an appropriate video display device.

Image quality remains a very important factor in choosing a video display device. However, as the need increases for display devices offering a larger picture, factors such as cost and device size and weight are becoming vital considerations. Larger display systems are preferable for group or interactive presentations. The size of the display system cabinet has proven an important factor, particularly for home or office use, where space to place a large housing or cabinet may not be available. Weight of the display system also is an important consideration, especially for portable or wall-mounted presentations.

Currently, the most common video display device is the typical CRT monitor, usually recognized as a television set. CRT devices are relatively inexpensive for applications requiring small to medium size images (image size traditionally is measured along the diagonal dimension of a rectangular screen). However, as image size increases, the massive proportions and weight of large CRT monitors become cumbersome and severely restrict the use and placement of the monitors. Also, screen curvature issues appear as the screen size increases. Finally, large CRT monitors consume a substantial amount of electrical power and produce electromagnetic radiation.

One alternative to conventional CRT monitors is rear projection television. Rear projection television generally comprises a projection mechanism or engine contained within a large housing for projection upon the rear of a screen. Back-projection screens are designed so that the projection mechanism and the viewer are on opposite sides of the screen. The screen has light transmitting properties to direct the transmitted image to the viewer.

By their very nature, rear projection systems require space behind the screen to accommodate the projection volume needed for expansion of the image beam. As background and ambient reflected light may seriously degrade a rear projected image, a housing or cabinet generally encloses the projection volume. The housing may contain a mirror or mirrors so as to fold the optical path and reduce the depth of

the housing. The need for "behind-the-screen" space precludes the placing of a rear projection display on a wall.

A new category of video presentation systems includes so-called thin Plasma displays. Much attention has been given to the ability of plasma displays to provide a relatively thin (about 75–100 mm) cabinet, which may be placed on a wall as a picture display in an integrated compact package. However, at the present time, plasma displays are costly and suffer from the disadvantages of low intensity (approx. 200–400 cd/m² range) and difficulty in making repairs. Plasma display panels are heavy (~80–100 lbs., ~36–45 kg.), and walls on which they are placed may require structural strengthening.

A traditional type of video presentation device that has not received the same degree of attention for newer applications is front-projection systems. A front-projection system is one that has the projection mechanism and the viewer are on the same side of the screen. Front projection systems present many different optical and arrangement challenges not present in rear projection systems, as the image is reflected back to the audience, rather than transmitted. An example of front projection systems is the use of portable front projectors and a front projection screen, for use in meeting room settings or in locations such as an airplane cabin.

One of the advantages of front projectors is the size of the projection engine. Electronic front projectors traditionally have been designed for the smallest possible "footprint", a term used to describe the area occupied on a table or bench, by the projector. Portable front projectors have been devised having a weight of about 10–20 lbs. (~4.5–9 kg.).

Nevertheless, front projection systems have traditionally not been considered attractive for newer interactive applications because of factors such as blocking of the image by the projector or the presenter, poor image brightness, image distortion and setup difficulties.

Traditional electronic front projectors typically require a room that may afford the projection volume necessary for image expansion without any physical obstructions. Although images may be projected upon a large clear flat surface, such as a wall, better image quality is achieved by the use of a separate screen. FIGS. 1 and 2 illustrate a traditional front projection system. A projector **10** is placed on a table or other elevated surface to project an image upon a screen or projection surface **20**. Those familiar with the use of electronic projectors will appreciate that tilting the projector below the normal axis of the screen produces a shape distortion of the image, known as a keystone effect. Most new electronic projectors offer a limited degree of keystone correction. However, as may be appreciated in FIG. 2, the placement of the projector may still interfere with the line of sight of the audience.

Of greater significance is the fact that to achieve a suitable image size, and also due to focus limitations, the projector **10** requires a certain "projection zone" in front of the screen **20**. Table A lists the published specifications for some common electronic projectors currently in the market.

TABLE A

Projector Type	Lens Focal Length	Imager Diagonal	Smallest Screen Diagonal	Shortest Throw Distance	Throw Ratio	Maximum Keystone Correction
CTX Opto EzPro 580	*	163 mm Transmissive LCD	1.0 m	1.1 m	1.1	20° offset/optical
InFocus	*	18 mm	1.3 m	1.5 m	1.2	18°

TABLE A-continued

Projector Type	Lens Focal Length	Imager Diagonal	Smallest Screen Diagonal	Shortest Throw Distance	Throw Ratio	Maximum Keystone Correction
LP425		Reflective DMD				offset
Chisholm Dakota X800	43–58.5 mm	23 mm Reflective LCD	0.55 m	1.2 m	2.2	15° electronic
Epson Powerlite 7300	55–72 mm	33.5 mm Transmissive LCD	0.58 m	1.1 m	1.9	*
Proxima Impression A2	45–59 mm	23 mm Transmissive LCD	0.5 m	1.0 m	2.0	12° offset
3M MP8620	167 mm	163 mm Transmissive LCD	1.0 m	1.2 m	1.2	16° offset/optical

*Not given in published specifications

Throw distance is defined as the distance from the projection lens to the projection screen. Throw ratio usually is defined as the ratio of throw distance to screen diagonal. The shortest throw distance available for the listed projectors is one meter. To achieve a larger image, between 40 to 60 inches (~1 to 1.5 meters), most projectors must be positioned even farther away, at least 8 to 12 feet (approximately 2.5 to 3.7 meters) away from the wall or screen.

The existence of this “projection zone” in front of the screen prevents the viewer from interacting closely with the projected image. If the presenter, for example, wishes to approach the image, the presenter will block the projection and cast a shadow on the screen.

Traditional integrated projectors require optical adjustment, such as focusing every time the projector is repositioned, as well as mechanical adjustment, such as raising of front support feet. Electronic connections, such as those to a laptop computer, generally are made directly to the projector, thus necessitating that the projector be readily accessible to the presenter or that the presenter runs the necessary wiring in advance.

Another problem with front projectors is the interference by ambient light. In a traditional front projector a significant portion of the projected light is scattered and is not reflected back to the audience. The loss of the light results in diminished image brightness. Accordingly, a highly reflective screen is desirable. However, the more reflective the screen, the larger the possible degradation of the projected image by ambient light sources. The present solution, when viewing high quality projection systems such as 35 mm photographic color slide presentation systems, is to attempt to extinguish all ambient lights. In some very critical viewing situations, an attempt has been made even to control the re-reflection of light originating from the projector itself.

Some screen designers have attempted to address the ambient light problem with “mono-directional reflection” screens, that is, a projection screen attempts to absorb light not originating from the projector, while maximizing the reflection of incident light originating from the direction of the projector. Nevertheless, since portable projectors are, in fact, portable and are used at various throw distances and projection angles, it has proven very difficult to optimize a screen for all possible projector positions and optical characteristics.

An alternative is to design a dedicated projection facility. Such a design necessitates a dedicated conference room, in

20

which the projector and screen position, as well as the projector’s optical characteristics, are rigorously controlled and calibrated. Structural elements may be used to suspend the selected projector from the ceiling. Once calibrated, such system would be permanently stationed. Such a facility may suffer from high costs and lack of portability.

Another issue that prevents optimal performance by front projectors is the keystone effect. If projectors are placed off-center from the screen, keystoneing will occur. Keystoneing is a particular image distortion where the projection of a rectangular or square image results in a screen image that resembles a keystone, that is a quadrilateral having parallel upper and lower sides, but said sides being of different lengths.

Methods for the reduction of keystoneing again are dependent upon the position of the projector with respect to the screen. Keystone correction may be achieved by optical and by electronic methods. For large keystone correction in LCD imagers, optical methods are presently preferable, as electronic methods may suffer from pixelation distortion, as pixels become misaligned. Presently, to the applicants’ knowledge, the available optical keystone correction in commercially available portable electronic front projectors is between 10° to 20°.

The need remains for a large screen video presentation system that offers efficient space utilization, lower weight and attractive pricing. Such a system should preferably yield bright, high-quality images in room light conditions.

SUMMARY OF THE INVENTION

An embodiment of the present invention comprises a front projection display system that integrates an optical engine, having control and power supply electronics, and a dedicated projection screen to provide a compact video display device. The projection engine is coupled to a high gain projection screen, having an optimized reflection pattern to give optimum optical performance in ambient light and viewing angle sensitive environments. Components of the projection engine are modularly placed in a retractable arm, pivotally connected to the screen. The arm offers precise registration to the screen apparatus and thus repeatably precisely aligns optically and mechanically to the screen. The projection wall system has an open projection position and a closed storage position. The architecture is very flat and light, having depth of less than three inches (~7.5 cm.) and a weight of less than 25 pounds (11 kilograms). Use of

65

a radically offset projection head having matching keystone correction features allows the arm to protrude above the head of the presenter and offer a sharp and unobtrusive projection zone.

An exemplary integrated front projection display in accordance with the present invention includes a front projection screen, a pivoting arm coupled to the flat projection screen, the arm having a storage position and a projection position; and a front projection head coupled to the arm. When the arm is in the projection position, the front projection head is at a predetermined position with respect to the front projection screen.

The projection head includes projection optics having mechanical off-axis keystone correction compensation greater than or approximately equal to 22° , a throw distance of at most 800 mm, a throw-to-screen diagonal ratio of at most 1.

The front projection screen may have a vertically graduated reflection distribution, wherein light rays emanating from the projection position generally are reflected by the projection screen in a preselected direction, normal to the vertical axis of the screen. In the horizontal direction, the screen has a horizontal distribution, wherein the light rays generally are reflected along a predetermined illumination spread with respect to the horizontal axis.

The front projection display further may include modular and separate electronic and imaging modules. The imaging module may be placed inside the projection head and the electronic module is placed in the swiveling arm.

The electronic module may be enclosed by a honeycomb structure. A cooling fan produces a cooling air current and the honeycomb structure directs the cooling current to flow through the length of the hollow structure. The honeycomb acts as a heat exchanger and the heat generated by the projector is dissipated by convection by the cooling current. The honeycomb structure also acts as an EMI/RFI shield. The cell size, material thickness and orientation of the honeycomb structure are tuned to attenuate undesirable high electromagnetic frequencies.

In an alternative embodiment, the front projection display may include a light source remotely placed from the imaging components and a flexible illumination waveguide. The illumination waveguide then optically couples the light source to the imaging components in the projection head. Also in alternative embodiments, the front projection display system may include a CPU placed within the frame and digital annotation components.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a traditional projection device and screen arrangement.

FIG. 2 is an elevation side view of the arrangement illustrated in FIG. 1.

FIG. 3 is a perspective view of an integrated front projection system in accordance with the present invention in the use or projection position.

FIG. 4 is a perspective view of the integrated front projection system illustrated in FIG. 3 in the closed or storage position.

FIG. 5 is a side elevation view of the integrated front projection system illustrated in FIG. 3 in the use or projection position.

FIG. 6 is a schematic cut-away side elevation view of a first embodiment of the arm and projection head of the integrated front projection system illustrated in FIG. 3.

FIG. 7 is a schematic cut-away side elevation view of a second embodiment of the arm and projection head of the integrated front projection system illustrated in FIG. 3.

FIG. 8 is a side elevation view of a third embodiment of an integrated front projection system in accordance with the present invention in the use or projection position.

FIG. 9 is a schematic cut-away side elevation view of a fourth embodiment of the arm and projection head of an integrated front projection system in accordance with the present invention.

FIG. 10 is a schematic cut-away side elevation view of a fifth embodiment of the arm and projection head of an integrated front projection system in accordance with the present invention.

FIG. 11 is a top plan view of the integrated front projection system illustrated in FIG. 10.

FIG. 12 is a perspective view of a sixth embodiment of an integrated front projection system in accordance with the present invention.

FIG. 13 is a perspective view of a seventh embodiment of an integrated front projection system in accordance with the present invention.

FIG. 14 is a side elevation view of the vertical reflection pattern of a controlled light distribution front projection screen in accordance with the present invention.

FIG. 15 is a plan view of the horizontal reflection pattern of the front projection system illustrated in FIG. 14.

FIG. 16 is a vertical cross-sectional view of a controlled light distribution front projection screen in accordance with the present invention.

FIG. 17 is a horizontal cross-sectional view of the front projection screen illustrated in FIG. 16.

FIG. 18 is a perspective view of a portion of the honeycomb structure of the integrated front projection system illustrated in FIG. 3.

FIG. 19 is a detail plan view of the portion of the honeycomb structure illustrated in FIG. 18.

DETAILED DESCRIPTION OF THE INVENTION

A preferred embodiment of the present invention comprises a front projection system that integrates an optical engine, having modular control and power supply electronics, and a dedicated projection screen to provide a compact and light video display device. FIGS. 3–6 illustrate a first exemplary embodiment of an integrated front projection system **100** in accordance with the present invention.

The front projection system **100** includes a dedicated high gain projection screen **102** mounted on a frame **104**. A projection head **106** is pivotally mounted by an arm **108** to a center top portion of the frame **104** at a hinge unit **110**. The arm **108** may be rotated out 90° allowing the projection head **106** to pivot from a closed or storage position to an opened or projection position.

The screen **102** is optically coupled to the projection head. The screen **102** may be a flexible material extended over frame **104** or may be a rigid component. In an alternative embodiment, both the screen and the frame are made of an integral sheet of material. The screen **102** may include multiple-layers or special coatings, such as to allow its use as an erasable whiteboard.

The frame **104** contains and supports other components of the system. The frame **104** may house additional components such, as integrated speakers **112**, input and output

jacks **113**, and a control panel **114**. In the present exemplary embodiment, the mechanical infrastructure of the projection system **100**, the arm **108** and the frame **104**, include lightweight materials such as aluminum, magnesium, or plastic composites. The entire projection system, accordingly, is relatively light (20–25 pounds, 9–11 kilograms).

In the present exemplary embodiment, the arm **108** is rigid and hollow. The arm **108** comprises die cast aluminum or magnesium, or other suitable materials, surrounded by a hard plastic shell. At the top and center of the frame **104**, the hinge unit **10** allows the projection arm **108** and head **106** to pivot between a closed (storage) position and an open (use) position. FIG. 4 illustrates the projection system **100** in a closed or storage position. When not in use, the arm **108** may be kept in the closed position as to be substantially parallel with the frame **104**, and thus present no obstruction to objects that may be moving in the space in front of the frame **104**. Although the arm is shown folded back to an audience left position, the system may be adaptable to allow storage of the arm and projection head to an audience right position. An ability to select storage position may be valuable in avoiding obstacles present in the projection area prior to the installation of the system. The ability of the arm **108** to rotate contributes to the projection system's minimal thickness, approximately 2–3 inches (5–7.5 cm.), in the storage position.

The system **100** allows for the projection head **106** to be placed in an exact pivotal registration in the operating or projection mode in relation to the optical screen **102**. In system **100**, use position is at a normal arm angle with respect to the screen and generally above the screen. However, other embodiments may be designed around other predetermined positions. Movement between the two positions may be assisted manually or may be motor-driven.

In the present embodiment, an electrical motor **116** residing within the hinge unit **110** controls the movement of the arm **108**. The motor **116** may be AC, DC, manually driven by detentes, over-center-cam (spring loaded) or any other suitable type that provides reliable repeatable positioning. The motor **116** is a precision guided gear drive motor having two limit sensor switches to accurately position the arm **108**, and accordingly, the projection head **106**, in precise and repeatable closed and open positions.

The movement of the arm **108** and the functions of the projector system **100** may be controlled through the control panel **114**, a remote control (not shown), or other control mechanism. While the arm **108** of the projection system **100** is pivotally fixed at a single point, those skilled in the art will readily appreciate that a variety of different linkage and/or pivoting mechanisms may be implemented within the spirit of the present invention. In alternative embodiments, the head and arm may include additional hinge or telescopic movement and the arm may be coupled to other portions of the frame or to a wall or post.

As explained in more detail in relation to FIGS. 14–17, the system **100** optimizes the coupling of the projection engine with the exact positioning of the head **106** in relation to the screen **102** to yield high contrast, brightest enhancement, image uniformity, optimal image position, and sharp focus. Since the optical parameters of the projection engine are known and selected for compatibility and the exact position of the projector head **106** in the use position is known and predetermined, the exemplary screen **102** may be designed and optimized to provide maximum illumination for the audience while reducing interference by ambient light.

When active, the projection system **100** generates a beam of light having a plurality of light rays **162**. In relation to a coordinate system wherein the screen defines a z-plane, each light ray **162** includes components along both the horizontal x-plane and the vertical y-plane. The angle of incidence of each light beam **162** upon the screen **102** depends on the optical characteristics of the projector, such as F/#, and the position of the projection head **106** in relation to the screen **102**.

FIG. 14 is a side elevation of a vertical axis ray diagram, illustrating the reflection of light beams **162** emitted by projection system **100**. Point **60** is the known precise location of the ideal point source for projection lens **140** (illustrated in FIG. 6) when the projection head **106** is in the “USE” position. The angles of incidence of the light beams **162** on the screen increase along the positive x-direction (see directional axis in FIG. 14).

In a traditional screen, the light rays **162** would each be reflected in accordance with their angle of incidence. Especially at the sharp projection angle of system **100**, the resulting light pattern would be scattered, with only a portion of the light rays reaching the audience. To compensate for the graduated increase in incidence angles, the screen **102** includes a vertically graduated reflection pattern oriented to receive the projected light rays **162** at the expected incidence angle for each point on the screen **102** and to reflect the rays approximately at normal angle along the vertical plane. The light beams **162** are reflected in a direction vertically close to normal because that corresponds to the expected location of the audience. In alternative embodiments where the audience is expected to be in a different position, a different reflection pattern may be implemented.

FIG. 15 illustrates a top plan view of the horizontal distribution of the light emanating from point **60**. As the audience is expected to be horizontally distributed, the horizontal reflection pattern of the screen is arranged to provide a wider illumination spread in the horizontal direction.

FIG. 16 illustrates an expanded view of a vertical cross-section of the projection screen **104**. FIG. 17 illustrates an expanded plan view of a horizontal cross section of the screen. The projection screen comprises a multi-layer material. The screen **104** includes a first linear Fresnel lens element **170**, a second linear Fresnel element **172**, and a reflective component **174**. First and second spacer elements **171** and **173** may be placed between the Fresnel elements **170** and **172** and between the second Fresnel element **172** and the reflective element **174** respectively. The linear Fresnel lens elements **170** and **172** include a planar side, **176** and **178** respectively, and a prismatic side, **180** and **182** respectively. The first Fresnel element **170** includes a thin isotropic diffusing layer **184** on its planar side **176**. The diffusing layer **184** functions as an image-receiving surface. The prismatic side **180** includes a plurality of linear grooves **186** running horizontally in a graduated pattern. The grooves **186** are designed to control the vertical light spread. The lens center is positioned near the top of the projection screen.

The prismatic side **182** of the second linear Fresnel lens element **172** includes a plurality of vertical grooves **188** (FIG. 17) facing the plurality of grooves **186** of the first Fresnel lens element **170**. The second linear Fresnel lens element **172** has a lens center positioned on a vertical line extending through the center of the screen. The planar surface **178** of second Fresnel element **172** faces a back reflector **174**, having a vertical linear structure reflecting the

light back in the direction of the audience. The grooves of the structure back reflector **174** preferably have a cylindrical shape, such as a lenticular structure, or may be a repeating groove pattern of micro facets that approximate a cylindrical shape. An incident surface **175** of the back reflector **174** may be specular or diffuse reflecting, metallic, or white coated, depending on the amount of screen gain and type of screen appearance desired. Second linear Fresnel element **172**, in conjunction with the structured back reflector **174**, provides control light of distribution spreading in the horizontal direction to accommodate viewers who are positioned horizontally in front of the screen. Alternatively, the reflector structure **174** may be embossed into the planar surface **178**, reducing the number of screen elements.

Alternative embodiments of the screen may comprise 3M multi-layer film technology.

As may be appreciated in FIG. 5, the projection system **100** places the projection head **106** at an extreme angle and close distance to the screen **102**, thus minimizing the possibility of the presenter's interference. Placement of the optical head **106** at the end of a radically offset projection arm **108** presented unique mechanical and optical challenges. Even the lightest and most compact conventional portable projectors at about 7 lb. (3.2 kg.), may have leveraged unbalanced strain upon the structure components. Optically, the throw distance necessary to even focus the image would have necessitated a long arm, further creating lever amplified stresses on the structure. Even if structurally sound, the system would have projected a severely keystone distorted and relatively small image.

An electronic optical engine includes imaging and electronic components. As better illustrated in FIG. 6, in projection system **100** the arm **108** is a rigid hollow structure surrounded by an outer plastic shell **118**. The structure of arm **108** defines an arm chamber **122** and allows for the modular and separate placement of a control and power electronics module **118** and an imaging module **120**. The control and power electronics module **118** includes control boards, ballast, and other electronic components. The electronic elements are internally connected through an array of internal power and data connections. The imaging module **120** includes a light source, projection optics, color wheel and imager. By distributing components of the projection system along the arm and the frame, a lesser load is placed on the hinge and the arm. Also, a smaller projector head size becomes possible. Those skilled in the art will recognize that a variety of different modular arrangements may be possible within alternative embodiments of the present invention. For example, alternatively, components of the electronics module may be placed inside of frame **104**.

A considerable amount of EMI/RFI shielding is required in traditional projector designs to reduce EM crosstalk between the lamp and the electronic components and to have radio frequency containment. The separate placement of electronic components within the arm **108** naturally reduces EMI/RFI interference. Furthermore, in the exemplary system **100**, the power supply and control electronics module **118** is enclosed by a honeycomb structure **124** including a plurality of hexagonal cells **125**. The honeycomb structure surrounds the power supply and electronics module **118** and provides both EMI/RFI shielding and thermal management characteristics. FIGS. 18 and 19 illustrate details of the honeycomb structure **124**. As described in co-pending and co-assigned U.S. patent application Ser. No. 08/883,446, entitled, "Honeycomb Light and Heat Trap for Projector", which is hereby incorporated by reference, the shape, orientation, thickness and size of the hexagonal cells may be

tuned to attenuate specific electromagnetic frequencies. In the present exemplary embodiment, the hexagonal cells **125** are aligned generally longitudinally along the arm **108** and are oriented at a predetermined specific angle ϕ to attenuate high electromagnetic frequencies. The honeycomb structure **124** is an aluminum hexagonal core having 0.25–0.0625 inch (0.635–0.159 cm.) cell size S, 0.002 inch (~0.005 cm.) foil thickness T, and a corrosion resistant coating. The physical separation of the electronic components and the honeycomb structure **124** provide sufficient attenuation to reduce the need for other traditional coatings or shields.

The present arrangement also offers an efficient thermal management system. An air intake **126** is located in the housing of the hinge unit **110**. A fan **130**, located in the projection head **106**, draws air through the air intake **126**, through the interior of the hollow projection arm **108**, cooling the electronic and power supply components **118** located therein. The air exits the projection head **106** through an air outlet **127**. Air also may be drawn through the projection head **106**. The flow of cooling air also may be used to cool components located in the projector head **106** or a separate cooling air flow or heat management elements may be employed.

The orientation of the honeycomb structure **124** also is designed to act as a convection heat sink to absorb the thermal energy generated by the electronic module **118** and transfers the heat by convection into the flow of cooling air drawn by the fan **130**. The honeycomb structure is oriented to direct air flow over sensitive components. Different portions of the honeycomb structure **124** may have different inclination angles ϕ to direct air flow to different components. The chamber **122** may also include exterior or interior fins, **127** and **128** respectively, to act as high efficient heat exchangers for both lamp and electronics cooling. The ability to direct the flow of cooling air with the honeycomb structure **124** into the interior fins **128** allows for better convection cooling, thus enabling the use of a low CFM fan **130** or even the use of naturally created convection. The cooling arrangement offered by the arm and the honeycomb structure also allows for very low overall power consumption and low audible noise.

Commercially available electronic front projectors are designed to project a specified screen diagonal (D) at a specified throw distance (TD). The throw ratio (TR) of a projector is defined as the ratio of throw distance to screen diagonal. Magnification is measured as screen diagonal/imager diagonal. Optically, the unobtrusive arrangement of the projection head **106** of projection system **100** requires that the image simultaneously accommodate three very demanding requirements: (1) short-throw distance, (2) high magnification, and (3) large keystone correction. To minimize image shadowing, in the present exemplary embodiment, the projector head **106** is located at a projection angle $>22^\circ$ and the arm measures about 36 in. (~91.4 cms). The screen **102** has a screen diagonal between 42 to 60 inches (~107–152 cms.). Accordingly, the design goals for the exemplary display system **100** included (1) a throw distance ≤ 800 mm; (2) a magnification $\geq 50\times$; and (3) keystone correction for a projection angle ≥ 220 .

Referring to FIG. 6, the projection head **106** includes a lamp unit **132**, an imager or light valve **134**, condensing optics **136**, a color wheel **138**, a condensing mirror **139** and a projection lens **140**. The projection head may also include polarization converters (for polarization rotating imagers), infrared and ultraviolet absorption or reflection filters, an alternative light source possibly coupled with a lamp changing mechanism, reflector mirrors, and other optical compo-

nents (not shown). The lamp unit **132** includes a reflector **131** and a lamp **133**. The reflector **131** focuses the light produced by the lamp **133** through the color wheel **138**. The beam of light then is condensed by the condensing optics **136** and the condensing mirror **139**. The now condensed beam of light is reflected off the condensing mirror and is directed towards the reflective imager **134**, which in turn reflects the light onto the projection lenses **140**.

The lamp unit **132** includes an elliptic reflector **131** and a high intensity arc discharge lamp **133**, such as the Philips UHP type, from Philips, Eindhoven, The Netherlands, or the OSRAM VIP-270 from Osram, Berlin, Germany. Other suitable bulbs and lamp arrangements may be used, such as metal halide or tungsten halogen lamps.

In the present exemplary embodiment, the imager **134** comprises a single XGA digital micromirror device (DMD) having about a 22 mm diagonal, such as those manufactured by Texas Instruments, Inc., Dallas, Tex. The color wheel **138** is a spinning red/green/blue (RGB) color sequential disc producing 16.7 million colors in the projected image. In alternative embodiments, the color wheel and the imager **134** may be replaced by different suitable configurations, such as a liquid crystal RGB color sequential shutter and a reflective or transmissive liquid crystal display (LCD) imager. Those skilled in the art will readily recognize that other optical components and arrangements may be possible in accordance with the spirit of the present invention.

The imager **134** and the lamp **132** may be cooled by the airflow generated by the fan **130**. A further thermal advantage of the arrangement of the present embodiment is that the warmer components, such as the lamp, are located at an end portion of the cooling air flow path, thus preventing the intense heat from the lamp from affecting delicate electronic components.

Traditional projector lenses proved unsuitable to accomplish the simultaneous requirements of the display system **100**. Accordingly, the present invention addresses this problem by the innovative conversion of 35 mm camera lenses having a small f-number and a large field of view into projection lenses. The projection lens **140** has a focal length about 14 to 20 mm, and a speed of f/2.8 or less. Suitable lenses include Nikon 18 mm. f/2.8 D Nikkor from Nikon, Japan, or Canon Photo EF 14 mm. f/2.8 L USM from Canon, Japan. The focus of the lens **140** is preset for optimal resolution on screen **102**.

To provide 22° keystone correction, the light valve center is shifted from the projection lens center by an amount equal to the projection angle. Such a large degree of keystone correction is possible because the projection angle is known and is repeatable. At projection angles exceeding 22°, the projection lens is selected to have a full field coverage angle exceeding 90°. In alternative embodiments, even larger keystone correction are possible, thus enabling the use of even a shorter projection arm. The keystone correction features need not be limited only to the optics. Keystone corrected optics, electronic keystone correction means, and screen inclination may be combined to achieve a suitable image. In an alternative embodiment, the screen may be motor driven, to reach an inclined projection position at the time that the arm is placed in the open position.

FIG. 7 illustrates a second exemplary embodiment of the present invention. The same last two digits in the reference numerals designate similar elements in all exemplary embodiments. To decrease the size of the light engine even further and to reduce the size and weight of projector head **206** and arm **208**, lamp **232** and fan **230** are placed within

hinge unit **210** or within frame **204**. Power supply and electronic components **218** are located inside frame **204** and behind screen **202**. A sequential color wheel **238**, a projection lens **240**, and condensing optics **236**, including a condensing mirror **239**, remain within the projector head **206**. A flexible illumination waveguide **242** is channeled through the projection arm **208** and couples the illumination from the lamp or light source **232** to the condensing optics **236**. The lamp **232** focuses light into an entrance aperture **244** of the illumination waveguide **242**. The light is transmitted by the illumination waveguide **242** up to an exit aperture **245**, where the light is then directed through the color wheel **138** to the condensing optics **236** and **239**. In the present embodiment, the illumination waveguide **242** is a solid large core plastic optical fiber, such as Spotlight type LF90FB from Sumitomo 3M Company, Ltd., Japan, or Stay-Flex type SEL 400 from Lumenyte International Corp., of Irvine, Calif.

Cooling in system **200** is performed in a reverse direction than in system **100**. The cooling mechanism or fan **230** draws air from the air intake **226** located in the projection head **206** and exhausts air through the air exhaust **227** located on the hinge unit **210**.

FIG. 8 illustrates a third exemplary embodiment of a projection system **300** in accordance with the present invention. The projection system **300** includes a projection head **306** mounted along the mid-span of a pivoting arm **308**. The projection head **306** is substantially similar to the projection head **106** in system **100**. The image projected by a projection lens **340** of the projection head **306** is reflected off a mirror or reflective surface **346** onto a screen **302**. The arrangement of optical system **300** allows for an increased throw distance and magnification while maintaining the same arm length or for the same throw distance and magnification with a shorter pivoting arm.

FIG. 9 illustrates a fourth exemplary embodiment of a projection system **400** in accordance with the present invention, having a screen **402**, a frame **404**, a projection head **406**, and an arm **408**. The projection head **406** of the projection system **400** includes a lamp **432** optically aligned with a transmissive color wheel **438** and condensing optics **436**. After passing through the color wheel **438** and the condensing optics **436**, a light beam is focused upon a reflective imager **434**, which, in turn, directs the light beam towards a retrofocus projection lens **440**. The projector system **400** includes modular power supply and system electronics **418** and a separate modular driver board **448** for the imager **434**.

FIG. 10 illustrates a fifth exemplary embodiment of a projection system **500** in accordance with the present invention. In the projection system **500**, the power supply electronics **519** are positioned inside of a frame **504**. A hinge **510** couples an arm **508** holding a projector head **506** to the frame **504**. Electronic control boards **550** are positioned within the arm **508**. The projection head **506** includes a lamp unit **532**, a polarizer **535**, optics **536**, a transmissive LCD imager **534**, and projection lens **540**, all aligned in a straight optical path. A fan **530** provides ventilation. As illustrated in FIG. 11, the arm **508** may be rotated a $\pm 90^\circ$ for storage on the right or the left side.

FIGS. 12 and 13 illustrate the versatility of the projection system of the present invention. FIG. 12 illustrates a digital whiteboard system **601** including a projection system **600** in accordance with the present invention and an input device, such as a stylus, **653**. The projection system **600** includes integrated electronics for an annotation system **652**, as well

as UV IR, laser or other type of sensors 654. The sensors 654 are calibrated to track the movement of the stylus 653 on the surface of the screen. The stylus 653 similarly may include transmitters and/or sensors to aid in tracking and to coordinate timing or control signals with electronics 652. The screen 602 may be coated to allow for erasable whiteboard use. The integrated electronics 652 may include a CPU.

FIG. 13 illustrates a videoconferencing and/or dataconferencing system 701, including a projection system 700 in accordance with the present invention. A camera 756, such as a CMOS or CCD camera, is mounted on the projection head 706 or on the frame 704. The camera 756 may pivot to capture a presenter or to capture documents placed on the screen 702. Alternatively, additional cameras may be directed to the presenter and to the screen. Again, the screen may be coated to act as an erasable whiteboard. The camera 756 is directly coupled to a CPU 758 integrally placed within the frame 704. A microphone 760 also is placed within the frame 704. Additional electronic modules, such as a tuner, network card, sound card, video card, communication devices, and others may be placed within the frame 704.

Those skilled in the art will readily appreciate that elements of the present invention may be combined, separately or in one system, to provide videoconferencing, dataconferencing, and electronic whiteboard functions, as well as any other function where a light and compact display system may be useful.

As the system of the present invention is designed to optimize the projection image at the predetermined projection position, no set-up adjustments are necessary to the optics, mechanics, or electronics and optimal on-screen performance is consistently offered. The integral structure of the system 100 allows for easier storage and portability and avoids cabling and positioning associated with the use of traditional projectors.

Those skilled in the art will appreciate that the present invention may be used with a variety of different optical components. While the present invention has been described with a reference to exemplary preferred embodiments, the invention may be embodied in other specific forms without departing from the spirit of the invention. Accordingly, it should be understood that the embodiments described and illustrated herein are only exemplary and should not be considered as limiting the scope of the present invention. Other variations and modifications may be made in accordance with the spirit and scope of the present invention.

What is claimed is:

1. An integrated front projection display comprising:

- a) a front projection screen;
- b) a movable arm coupled to the flat projection screen, the arm having a storage position and a projection position; and
- c) a front projection head coupled to the arm, wherein when the arm is in the projection position, the front projection head is at a predetermined position with respect to the front projection screen

wherein the projection head includes projection optics having:

- a mechanical off-axis keystone correction compensation greater or approximately equal to 22°,
- a throw distance of at most 800 mm, and
- a throw-to-screen diagonal ratio of at most 1.

2. The front projection display of claim 1,

- a) wherein the front projection screen has a generally flat surface, the generally flat surface defining a horizontal axis and a vertical axis,

- b) the front projection screen having a vertically graduated reflection distribution, wherein light rays emanating from the projection position generally are reflected by the projection screen in a preselected direction.

3. The front projection display of claim 2, wherein the light rays generally are reflected in a normal direction with respect to the vertical axis.

4. The front projection display of claim 2, wherein the light rays generally are reflected along an illumination spread with respect to the horizontal axis.

5. The front projection display of claim 1, further comprising an electronic module and an imaging module, wherein the imaging module is modularly placed separately from the electronic modules.

6. An integrated front projection display comprising:

- c) a front projection screen;
- d) a movable arm coupled to the flat projection screen, the arm having a storage position and a projection position; and
- e) a front projection head coupled to the arm, wherein when the arm is in the projection position, the front projection head is at a predetermined position with respect to the front projection screen;
- f) an electronic module and an imaging module, wherein the imaging module is modularly placed separately from the electronic module, and wherein the imaging module is placed inside the projection head and the electronic module is placed in the movable arm.

7. The front projection display of claim 1, further comprising a light source and a flexible illumination waveguide, wherein the projection head includes imaging components optically coupled to the light source by the flexible illumination waveguide.

8. An integrated front projection display comprising:

- a) a front projection screen;
- b) a movable arm coupled to the flat projection screen, the arm having a storage position and a projection position; and
- c) a front projection head coupled to the arm, wherein when the arm is in the projection position, the front projection head is at a predetermined position with respect to the front projection screen;
- d) an electronic module enclosed by a honeycomb structure;
- e) further comprising a cooling fan producing a cooling current, wherein the movable arm has an elongated hollow structure, and the honeycomb structure directs the cooling current to flow through the length of the hollow structure.

9. The front projection display of claim 8, wherein the honeycomb is a heat exchanger and the heat generated by the projector is dissipated by convection by the cooling current.

10. An integrated front projection display comprising:

- b) a controlled light distribution front projection screen;
- b) a front projection head integrally coupled to the projection screen, wherein the front projection head has a predetermined projection position with respect to the screen, and the screen is optically tuned to receive and reflect light rays emanating from the projection head at the projection position;
- c) a swiveling arm coupling the front projection screen to the front projection head;
- d) an electronic module and an imaging module, wherein the electronic module is enclosed by a honeycomb structure; and

15

- e) a cooling fan producing a cooling current, wherein the swiveling arm has an elongated hollow structure, and the honeycomb structure directs the cooling current to flow through the length of the hollow structure.
- 11.** An integrated front projection display comprising:
- a front projection screen;
 - a movable arm coupled to the flat projection screen, the arm having a storage position and a projection position; and
 - a front projection head coupled to the arm, wherein when the arm is in the projection position, the front projection head is at a predetermined position with respect to the front projection screen;
 - an electronic module enclosed by a honeycomb structure;
 - wherein the honeycomb structure includes a plurality of cells and wherein the size, orientation, and wall thickness of the cells are tuned to attenuate specific electromagnetic wavelengths.
- 12.** An integrated front projection display system comprising:
- a planar projection screen formed on a front surface of a frame,
 - a movable arm hingedly connected at a first end to the frame, the arm being movable between a storage position and a projection position, and
 - a projection head mounted on a second end of the movable arm such that it does not substantially obstruct the view of the projection screen when the arm is in the projection position, the projection head including a keystone correction mechanism for projecting a corrected image onto the projection screen when the arm is in the projection position.
- 13.** A digital annotation system including the front projection display of claim **12**.
- 14.** A video-conferencing system including the front projection display of claim **12**.
- 15.** The front projection display of claim **12**, further including a CPU.
- 16.** The integrated front projection display of claim **1**, further comprising:
- a controlled light distribution front projection screen; and
 - a front projection head integrally coupled to the projection screen, wherein the front projection head has a predetermined projection position with respect to the screen, and the screen is optically tuned to receive and reflect light rays emanating from the projection head at the projection position.
- 17.** The front projection display of claim **16**,
- wherein the screen has a generally flat surface, the generally flat surface defining a horizontal axis and a vertical axis,
 - the front projection screen having a vertically graduated reflection distribution, wherein the light rays emanating from the projection head generally are reflected by the projection screen in a preselected direction.
- 18.** The front projection display of claim **17**, wherein the light rays generally are reflected in a normal direction with respect to the vertical axis.
- 19.** The front projection display of claim **17**, wherein the light rays generally are reflected along an illumination spread with respect to the horizontal axis.
- 20.** The front projection display of claim **16**, further comprising a swiveling arm coupling the front projection screen to the front projection head.

16

- 21.** The front projection display of claim **20**, further comprising an electronic module and an imaging module, wherein the imaging module is modularly placed separately from the electronic module.
- 22.** An integrated front projection display comprising:
- a controlled light distribution front projection screen;
 - a front projection head integrally coupled to the projection screen, wherein the front projection head has a predetermined projection position with respect to the screen, and the screen is optically tuned to receive and reflect light rays emanating from the projection head at the projection position;
 - a swiveling arm coupling the front projection screen to the front projection head; and
 - an electronic module and an imaging module, wherein the imaging module is modularly placed separately from the electronic module wherein the imaging module is placed inside the projection head and the electronic module is placed in the swiveling arm.
- 23.** The front projection display of claim **22**, wherein the electronic components are enclosed by a honeycomb structure.
- 24.** A front projection system comprising:
- power supply and control electronic components, the electronic components radiating electromagnetic waves;
 - optical components, wherein the electronic components are modularly separated from the optical components; and
 - a honeycombed structure enclosing the electronic components, the honeycomb structure having a plurality of hexagonal cells oriented to collect the electromagnetic waves and having a size less than the expected wavelength of the electromagnetic waves.
- 25.** An integrated front projection display comprising:
- a controlled light distribution front projection screen;
 - a front projection head integrally coupled to the projection screen, wherein the front projection head has a predetermined projection position with respect to the screen, and the screen is optically tuned to receive and reflect light rays emanating from the projection head at the projection position;
 - a swiveling arm coupling the front projection screen to the front projection head;
 - an electronic module and an imaging module, wherein the electronic module is enclosed by a honeycomb structure; and
 - wherein the honeycomb is a heat exchanger and the heat generated by the projector is dissipated by convection by the cooling current.
- 26.** The front projection display of claim **25**, further comprising a light source and a flexible illumination waveguide, wherein the projection head includes imaging components optically coupled to the light source by the flexible illumination waveguide.
- 27.** An integrated front projection display comprising:
- a controlled light distribution front projection screen;
 - a front projection head integrally coupled to the projection screen, wherein the front projection head has a predetermined projection position with respect to the screen, and the screen is optically tuned to receive and reflect light rays emanating from the projection head at the projection position;
 - wherein the projection head includes a projection optics having:

- i) a mechanical off-axis keystone correction compensation greater or approximately equal to 22°,
- ii) a throw distance of at most 800 mm,
- iii) a throw-to-screen diagonal ratio of at most 1.

28. A digital annotation system including the front projection display of claim 27. 5

29. A video-conferencing system including the front projection display of claim 27.

30. A front projection system comprising:

- a) a front projection screen; and 10
- b) a front projector device integrally coupled to the projection screen, the projector device having:
 - i) a mechanical off-axis keystone correction compensation greater or approximately equal to 22°, 15
 - ii) a throw distance of at most 800 mm,
 - iii) a throw-to-screen diagonal ratio of at most one.

31. The front projection display system of claim 12,

- a) the projection head having, in the projection position, a predetermined source point location for projected light rays; 20
- b) the front projector screen defining a horizontal axis and a vertical axis, the front projector screen comprising a plurality of optical elements distributed across the projector screen, wherein each of the optical elements is optically aligned with the source point location to receive the projected light rays at an expected angle of incidence and to reflect the projected light rays at a predetermined desired angle of reflection. 25

32. The front projection display system of claim 31, wherein the projection screen further comprises 30

- a) a multi-layer material construction having a first linear Fresnel element layer,
- b) a second linear Fresnel element layer and
- c) a reflector, the first linear Fresnel, the second linear Fresnel and the reflector arranged sequentially; 35
- d) wherein the first linear Fresnel layer includes a plurality of horizontal grooves having a vertically graduated pattern corresponding to the vertical component of the

expected angle of incidence of the projected light rays at each horizontal groove and the vertical component of the angle of incidence of the desired angle of reflection, each horizontal groove corresponding to a row of the optical elements.

33. The front display system of claim 32,

- a) wherein the second linear Fresnel element includes a plurality of vertical grooves having a horizontal pattern corresponding to the horizontal component of the expected angle of incidence of the projected light rays at each vertical groove and the horizontal component of the angle of incidence of the desired angle of reflection, each vertical groove corresponding to a column of the optical elements.

34. The front display of claim 33, wherein the reflector includes a reflection pattern.

35. An integrated front projection display system comprising:

- a) a planar projection screen formed on a front surface of a rigid frame, the screen including means for reflecting light from the screen in a preselected spatial distribution;
- b) a movable arm hingedly connected at a first end to the rigid frame, the arm being movable between a storage position and a projection position, the arm further comprising means for moving the arm between said storage and projection positions and for retaining the arm at each of said positions; and
- c) a projection head mounted on a second end of the movable arm such that it does not substantially obstruct the view of the projection screen when the arm is in the projection position, the projection head including means for providing an image to be displayed, means for focusing the image onto the projection screen, and means for correcting the keystone effect in the projected image when the arm is in the projection position.

* * * * *