



US006185092B1

(12) **United States Patent**
Landrum et al.

(10) **Patent No.:** **US 6,185,092 B1**
(45) **Date of Patent:** **Feb. 6, 2001**

(54) **COMPUTER SYSTEM WITH IN-LINE SWITCHBOX MOUNTING**

5,801,921 * 9/1998 Miller 361/686
6,022,087 * 2/2000 Gibert 312/194

(75) Inventors: **Gary Landrum**, Montgomery; **Michael Owens**, Tomball, both of TX (US)

* cited by examiner

(73) Assignee: **Compaq Computer Corporation**

(*) Notice: Under 35 U.S.C. 154(b), the term of this patent shall be extended for 0 days.

Primary Examiner—Leo P. Picard

Assistant Examiner—Tung Minh Bui

(74) *Attorney, Agent, or Firm*—Williams, Morgan & Amerson, P.C.

(21) Appl. No.: **09/390,233**

(22) Filed: **Sep. 3, 1999**

(57) **ABSTRACT**

(51) **Int. Cl.**⁷ **H05K 5/00**; H05K 7/00

(52) **U.S. Cl.** **361/683**; 361/681; 361/686; 361/724; 361/727; 312/223.1; 312/223.2

(58) **Field of Search** 361/686, 683, 361/681, 724, 727; 312/223.1, 223.2; 364/705.01, 708.1


An apparatus includes a cabinet, a keyboard assembly, and a switchbox. The cabinet has mounting rails. The keyboard assembly includes a keyboard tray and a keyboard slide. The keyboard slide has fixed and moveable portions. The fixed portion is mounted to the mounting rails, and the moveable portion is mounted to the keyboard tray. A switchbox is mounted to the fixed portion of the keyboard slide.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,388,032 * 2/1995 Gill et al. 364/146

10 Claims, 6 Drawing Sheets







FIG. 1






FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8

COMPUTER SYSTEM WITH IN-LINE SWITCHBOX MOUNTING

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates generally to mounting systems for computer systems, and, more particularly, to a computer system with an in-line switchbox mounting.

2. Description of the Related Art

Computer systems typically employ a monitoring system, such as a video display. Certain computer systems use a rack in which multiple devices, such as servers, peripheral devices, etc., are mounted. Often multiple servers are housed in the same rack, and are monitored by selectively coupling a video display, keyboard, and a mouse (or trackball) to one of the servers through a multiplexing unit. The multiplexing unit, commonly referred to as a switchbox, is typically installed in one of the slots in the rack.

One technique for providing the monitoring capability involves mounting a conventional monitor on a shelf in the rack unit. Such an arrangement uses a large amount of available rack space, and is thus inefficient if a large number of components are required to be mounted in the rack.

With the introduction of flat panel display technology, it is possible to reduce the depth required for a monitor. Currently, monitoring systems available for use in a rack system involve mounting a pivotable flat panel monitor and keyboard in a common tray (i.e., referred to as a monitoring tray) in the rack. One such arrangement is shown in U.S. Pat. No. 5,388,032. The monitor is pivotably mounted to the monitoring tray at its lower edge to allow the monitor to be raised for use while the monitoring tray is extended. When not in use the monitor is rotated to a horizontal position and the monitoring tray is inserted back into the rack. Such an arrangement has several disadvantages. First, because the monitor and keyboard are contained in a common tray, there is a practical limit on the number of positions in the rack that the monitoring tray can be located. Generally, the monitoring tray is mounted near waist level to allow a standing user to access the keyboard. Such a position has ergonomic disadvantages due to the proximity of the keyboard to the monitor, as the monitor may be difficult to view.

Another disadvantage of the common monitor and keyboard arrangement is that the monitoring tray must be essentially fully extended to allow access to the monitor. Some rack systems include doors that must also remain in an open position if the monitoring tray is to be left extended. In some cases, such as system installation, maintenance, or troubleshooting, it may be desirable to leave the monitor in a viewable position for an extended period of time. The extended position of the monitoring tray can be annoying to users that must maneuver around various racks with extended monitoring trays and/or doors. Open doors may also prevent effective monitoring of adjacent rack mounted equipment.

The present invention is directed to overcoming, or at least reducing the effects of, one or more of the problems set forth above.

SUMMARY OF THE INVENTION

An aspect of the present invention is seen in an apparatus including a cabinet, a keyboard assembly, and a switchbox. The cabinet has mounting rails. The keyboard assembly includes a keyboard tray and a keyboard slide. The keyboard slide has fixed and moveable portions. The fixed portion is

mounted to the mounting rails, and the moveable portion is mounted to the keyboard tray. A switchbox is mounted to the fixed portion of the keyboard slide.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention may be understood by reference to the following description taken in conjunction with the accompanying drawings, in which like reference numerals identify like elements, and in which:

FIG. 1 is a simplified isometric view of a computer system in accordance with the present invention;

FIG. 2 is a simplified isometric view of the computer system shown with a keyboard assembly and a pivotable display assembly in their extended positions;

FIGS. 3 and 4 are isometric views of the pivotable display assembly and the cabinet of FIG. 2;

FIG. 5 is a rear isometric view of the pivotable display assembly with the display detached;

FIG. 6 is an isometric view of the pivotable display assembly with the display in a pivoted position;

FIG. 7 is a cut-away isometric view of the computer system showing the keyboard assembly and a switchbox; and

FIG. 8 is a simplified block diagram illustrating the interconnection between the keyboard, display, switchbox, and servers.

While the invention is susceptible to various modifications and alternative forms, specific embodiments thereof have been shown by way of example in the drawings and are herein described in detail. It should be understood, however, that the description herein of specific embodiments is not intended to limit the invention to the particular forms disclosed, but on the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the invention as defined by the appended claims.

DETAILED DESCRIPTION OF SPECIFIC EMBODIMENTS

Illustrative embodiments of the invention are described below. In the interest of clarity, not all features of an actual implementation are described in this specification. It will of course be appreciated that in the development of any such actual embodiment, numerous implementation-specific decisions must be made to achieve the developers' specific goals, such as compliance with system-related and business-related constraints, which will vary from one implementation to another. Moreover, it will be appreciated that such a development effort might be complex and time-consuming, but would nevertheless be a routine undertaking for those of ordinary skill in the art having the benefit of this disclosure.

Referring now the figures, and particularly, to FIG. 1, a simplified isometric view of a computer system **10** is provided. The computer system **10** includes a cabinet **15** with a door **20** and a plurality of devices **25**. The particular devices **25** employed in the computer system **10** depend on the specific application. These devices **25** may include servers, storage devices, power management devices, or other equipment. Generally, the height of the devices **25** is measured in increments of 1.75", where 1.75" is referred to as 1 U. The total height capacity of the cabinet **15** may vary. Commonly available cabinets **15** have capacities of 22, 36 or 42 U, for example.

In the illustrated embodiment, two servers **30**, **35**, a keyboard assembly **40**, a storage system **45** (i.e., having

multiple hard disk drives), a pivotable display assembly **50**, and a tape backup system **52** are installed in the cabinet **15**. This mix of equipment is provided for illustrative purposes. It is contemplated that many other combinations may be used. The keyboard assembly **40** and pivotable display assembly **50** are described in greater detail herein.

Turning now to FIG. **2**, a simplified isometric view of the computer system **10** is shown with the keyboard assembly **40** and the pivotable display assembly **50** in their extended positions. The pivotable display assembly **50** is oriented such that sufficient clearance exists to allow the door **20** to be closed with the pivotable display assembly **50** in its extended position, albeit the keyboard assembly **40** must be inserted before the door **20** may be closed. The keyboard assembly **40** is discussed in greater detail in U.S. patent application Ser. No. 09/390,257, entitled, "METHOD AND APPARATUS FOR RETAINING AN ELECTRICAL CONNECTOR" in the name of Gary Landrum and Michael Owens, and incorporated herein by reference in its entirety.

FIGS. **3** and **4** illustrate isometric views of the pivotable display assembly **50** and the cabinet **15** (shown in a cut away view). The pivotable display assembly **50** includes a tray **55** to which a display **60** (e.g., a flat panel display) is pivotably mounted. The cabinet **15** includes mounting rails **65** to which a pair of conventional slides **70** are disposed along opposite sides **75**, **80** of the tray **55**. The slides **70** generally include a moveable and fixed portion **85**, **90**. The fixed portions **90** are attached to mounting rails **65**, while the moveable portions **85** are attached to the opposite sides **75**, **80** of the tray **55**. The moveable and fixed portions **85**, **90** engage one another such that a sliding movement therebetween is provided. The slides **70** allow the tray **55** to translate linearly out of the cabinet **15** for easy access by a computer user, and into the cabinet **15** for storage.

A cable **95** coupled to the display **50** extends through a hole **100** defined in the tray **55**. Typically, video signals are transmitted through the cable **95** to the display **50**. A cable management arm **105** is provided to inhibit tangling of the cable **95** during lateral movement of the tray **55**. Movement of the tray **55** necessarily produces similar movement of the pivotable display assembly **50**.

Turning now to FIG. **5**, a rear isometric view of the pivotable display assembly **50** with the display **60** detached is shown. A back plate **105** is pivotably mounted to the tray **55** by hinges **110**. The back plate **105** is in turn mounted (e.g., by screws or other suitable fasteners) to the display **60** proximate the front edge **120** of the tray **55**. Accordingly, as the display **60** pivots, as shown in FIG. **6**, it remains oriented proximate the front edge **120**.

As seen in FIG. **6**, a bezel **125** is mounted to the display **60** for functional and aesthetic purposes. First, the bezel **125** provides physical protection to the display **60** to prevent damage from a user inadvertently bumping or striking the display **60**. The end portion **130** of the bezel **125** obscures the tray **55**, back plate **105**, and electrical cords (not shown) when the pivotable display assembly **50** is in its stored position (as seen in FIG. **4**) to provide a uniform, clean look.

Turning now to FIG. **7**, a cut-away isometric view of the computer system **10** showing the keyboard assembly **40** is provided. A keyboard **135** is contained in a keyboard tray **140** as described in the above-referenced U.S. patent application Ser. No. 09/390,257. A switchbox **140** is mounted to fixed mounting brackets **145**. The fixed mounting brackets **145** also serve as fixed portions for slides (not shown) on the keyboard assembly **40**. The switchbox is coupled to the keyboard **135** and the display **60** to route signals to a

selected server **30**, **35** through cables (not shown) connected to connectors **150** on the rear **150** of the switchbox **140**. Coupling the switchbox **140** to the fixed mounting brackets **145** frees up space in the cabinet **15** for other components.

Referring to FIG. **8**, a simplified block diagram illustrating the interconnection between the keyboard **135**, display **60**, switchbox **140**, and servers **30**, **35** is provided. The keyboard **135** and display **60** are coupled to the switchbox **140** by the display cable **95** and a keyboard cable **155**. Server cables **160** are coupled to each of the servers **30**, **35**. The switchbox **140** selectively couples one of the server cables **160** to the display cable **95** and the keyboard cable **155** to allow the keyboard **135** to control the selected server **30**, **35** and the display information from the server **30**, **35** to be displayed on the display **60**.

The mounting configurations of the keyboard assembly **40**, pivotable display assembly **50**, and switchbox **140** described herein provide numerous advantages. First, the proximity of the display **60** to the front edge **120** of the tray **55** of the pivotable display assembly **50** allows the display to be left in a viewable position without extending outwardly from the cabinet **15** or interfering with the door **20**. Also, because the keyboard assembly **40** and the pivotable display assembly **50** are independently mounted to the cabinet **15**, they may be oriented in any number of positions. This provides ergonomic advantages for the user of the computer system **10**. Also, because the switchbox **140** is mounted in-line with the keyboard assembly **40**, no additional space is required for the independent orientations. For example, if the keyboard **135** and display **60** were mounted in a common tray (not shown), the switchbox **140** would still have to be mounted in the cabinet, taking at least 1 U of space. Mounting the switchbox **140** is in-line with the keyboard assembly **40** allows independent positioning of the keyboard **135** and the display **60** without sacrificing additional space.

The particular embodiments disclosed above are illustrative only, as the invention may be modified and practiced in different but equivalent manners apparent to those skilled in the art having the benefit of the teachings herein. Furthermore, no limitations are intended to the details of construction or design herein shown, other than as described in the claims below. It is therefore evident that the particular embodiments disclosed above may be altered or modified and all such variations are considered within the scope and spirit of the invention. Accordingly, the protection sought herein is as set forth in the claims below.

What is claimed:

1. An apparatus, comprising:

a cabinet, having mounting rails;

a keyboard assembly, the keyboard assembly, including:

a keyboard tray; and

a keyboard slide having fixed and moveable portions, the fixed portion being mounted to the mounting rails, and the moveable portion being mounted to the keyboard tray; and

a switchbox mounted to the fixed portion of the keyboard slide.

2. The apparatus of claim 1, further comprising a display mounted in the cabinet, wherein the display includes a display cable, the keyboard tray includes a keyboard having a keyboard cable, and the switchbox is coupled to the display cable and the keyboard cable.

3. The method of claim 1, further comprising:

mounting a display in the cabinet, the display including a display cable;

providing a keyboard in the keyboard tray, the keyboard having a keyboard cable; and

5

coupling the display cable and the keyboard cable to the switchbox.

4. The apparatus of claim 2, further comprising a plurality of servers mounted in the cabinet, wherein the switchbox is adapted to couple a selected one of the servers to the display cable and the keyboard cable.

5. The apparatus of claim 2, wherein the keyboard assembly and the display assembly are mounted to the cabinet in different vertical positions.

6. The method of claim 3, further comprising:

mounting a plurality of servers in the cabinet; and

selectively coupling a selected one of the servers to the display cable and the keyboard cable through the switchbox.

7. The method of claim 3, wherein mounting the keyboard assembly and mounting the display assembly include mounting the keyboard assembly and the display assembly to the cabinet in different vertical positions.

6

8. A method for assembling a computer system, comprising:

providing a cabinet, having mounting rails;

mounting a keyboard assembly to the mounting rails; and

mounting a switchbox to the mounting rails in-line with the keyboard assembly.

9. The method of claim 8, wherein the keyboard assembly includes a keyboard tray and a keyboard slide having fixed and moveable portions, and the method further comprises mounting the fixed portion to the mounting rails and mounting the moveable portion to the keyboard tray.

10. The method of claim 8, wherein mounting the switchbox comprises mounting the switchbox to the fixed portion of the keyboard slide.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,185,092 B1
DATED : February 6, 2001
INVENTOR(S) : Gary Landrum et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 4,
Line 63, delete "1" and insert thereof -- 8 --.

Signed and Sealed this

Eleventh Day of December, 2001

Attest:

Nicholas P. Godici

Attesting Officer

NICHOLAS P. GODICI
Acting Director of the United States Patent and Trademark Office