



US006220516B1

(12) **United States Patent**
Tuttle et al.

(10) **Patent No.:** **US 6,220,516 B1**
(45) **Date of Patent:** ***Apr. 24, 2001**

(54) **METHOD OF MANUFACTURING AN ENCLOSED TRANSCEIVER**

(75) Inventors: **Mark E. Tuttle; John R. Tuttle**, both of Boise; **Rickie C. Lake**, Eagle, all of ID (US)

(73) Assignee: **Micron Technology, Inc.**, Boise, ID (US)

(*) Notice: This patent issued on a continued prosecution application filed under 37 CFR 1.53(d), and is subject to the twenty year patent term provisions of 35 U.S.C. 154(a)(2).

Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/008,215**

(22) Filed: **Jan. 16, 1998**

Related U.S. Application Data

(62) Division of application No. 08/781,107, filed on Jan. 9, 1997, now Pat. No. 5,776,278, which is a continuation of application No. 08/602,686, filed on Feb. 16, 1996, now abandoned, which is a continuation of application No. 08/137,677, filed on Oct. 14, 1993, now abandoned, which is a continuation-in-part of application No. 07/899,777, filed on Jun. 17, 1992, now abandoned.

(51) **Int. Cl.⁷** **G06K 19/06**
(52) **U.S. Cl.** **235/492; 235/380**
(58) **Field of Search** **235/380, 382.5, 235/492**

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,706,094	12/1972	Cole et al.	342/44
3,750,167	7/1973	Gehman et al.	342/44
3,780,368	12/1973	Northeved et al.	342/44

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

4120265	1/1992	(DE)
1567784	5/1980	(GB)
404075191 *	3/1992	(JP)

OTHER PUBLICATIONS

The New IEEE Standard Dictionary of Electrical and Electronics Terms, 5th Ed., 1993, p. 662.

merriam-Webster Collegiate Dictionary, 1993, p. 563.

U.S. Patent Application Ser. No. 08/422,007, Filed Apr. 11, 1995.

U.S. Patent Application Ser. No. 08/071,463, Filed Jun. 2, 1993.

U.S. Patent Application Ser. No. 08/515,128, Filed Aug. 15, 1995.

U.S. Patent Application Ser. No. 08/410,889, Filed Mar. 27, 1995.

U.S. Patent Application Ser. No. 08/530,747, Filed Sep. 19, 1995.

U.S. Patent Application Ser. No. 08/588,559, Filed Jan. 18, 1996.

(List continued on next page.)


Primary Examiner—Mark Tremblay

(74) *Attorney, Agent, or Firm*—Wells, St. John, Roberts, Gregory & Matkin P.S.

(57) **ABSTRACT**

The present invention teaches a method of manufacturing an enclosed transceiver, such as a radio frequency identification (“RFID”) tag. Structurally, in one embodiment, the tag comprises an integrated circuit (IC) chip, and an RF antenna mounted on a thin film substrate powered by a thin film battery. A variety of antenna geometries are compatible with the above tag construction. These include monopole antennas, dipole antennas, dual dipole antennas, a combination of dipole and loop antennas. Further, in another embodiment, the antennas are positioned either within the plane of the thin film battery or superjacent to the thin film battery.

30 Claims, 12 Drawing Sheets



U.S. PATENT DOCUMENTS

3,832,530	8/1974	Reitboeck et al.	342/44
3,849,633	11/1974	Reitboeck et al.	235/487
4,049,969	9/1977	Salonimer et al.	356/5
4,075,632	2/1978	Baldwin et al.	343/6.8
4,226,361	10/1980	Taylor	235/380
4,331,957	5/1982	Enander et al.	342/22
4,399,441	8/1983	Vaughn et al.	342/50
4,418,411	11/1983	Strietzel	340/870.16
4,453,074	6/1984	Weinstein	235/380
4,484,355	11/1984	Henke et al.	455/76
4,649,233	3/1987	Bass et al.	380/21
4,680,724	7/1987	Sugiyama et al.	364/708
4,724,427	2/1988	Carroll	340/572
4,727,560	2/1988	Van Zanten et al.	377/60
4,746,618	5/1988	Nath et al.	437/2
4,746,830	5/1988	Holland	310/313 D
4,756,717	7/1988	Sturgis et al.	427/290
4,777,563	10/1988	Teraoka et al.	361/395
4,783,646	11/1988	Matsuzaki	340/572
4,827,110	5/1989	Rossi et al.	235/376
4,827,395	5/1989	Anders et al.	364/138
4,854,328	8/1989	Pollack	128/736
4,882,294	11/1989	Christenson	437/90
4,908,502	3/1990	Jackson	235/437
4,911,217	3/1990	Dunn et al.	152/152.1
4,918,631	4/1990	Hara et al.	364/708
4,926,182	5/1990	Ohta et al.	342/44
4,942,327	7/1990	Wantanabe et al.	310/313
4,956,645 *	9/1990	Guena et al.	342/361
4,960,983	10/1990	Inouc	235/449
4,962,415	10/1990	Yamamoto et al.	357/74
5,008,776	4/1991	Queyssac	361/392
5,023,573	6/1991	Adam	333/17.2
5,068,894	11/1991	Hoppe	380/23
5,095,240	3/1992	Nyson et al.	342/44
5,144,314	9/1992	Malmberg et al.	342/44
5,148,504	9/1992	Levi et al.	385/14
5,153,710	10/1992	McCain	357/75
5,166,502	11/1992	Rendleman et al.	235/492
5,200,362 *	4/1993	Lin et al.	29/841
5,214,410	5/1993	Verster	340/572
5,274,221	12/1993	Matsubara	235/492
5,302,954	4/1994	Brooks et al.	342/44
5,313,211	5/1994	Tokuda et al.	342/50
5,326,652	7/1994	Lake	429/127
5,337,063	8/1994	Takahira	343/741

5,340,968 *	8/1994	Watanabe et al.	235/380
5,350,645	9/1994	Lake et al.	429/124
5,414,427	5/1995	Gunnarsson	342/51
5,416,423	5/1995	De Borde	324/677
5,432,027	7/1995	Tuttle et al.	429/127
5,434,397	7/1995	Diehl et al.	235/380
5,448,110	9/1995	Tuttle et al.	257/723
5,480,462	1/1996	Tuttle	29/623.5
5,486,431	1/1996	Tuttle et al.	429/66
5,494,495	2/1996	Tuttle	29/623.2
5,497,140	3/1996	Tuttle	342/51
5,510,074	4/1996	Rose	264/261
5,619,066 *	4/1997	Curry et al.	257/679
5,621,412	4/1997	Sharpe et al.	342/51
5,649,296	7/1997	MacLellan et al.	455/38.2

OTHER PUBLICATIONS

U.S. Patent Application Ser. No. 08/205,590, Filed Mar. 2, 1994.

U.S. Patent Application Ser. No. 08/147,495, Filed Nov. 5, 1993.

U.S. Patent Application Ser. No. 08/538,826, Filed Oct. 5, 1995.

U.S. Patent Application Ser. No. 08/585,428, Filed Jan. 11, 1996.

U.S. Patent Application Ser. No. 08/610,236, Filed Mar. 4, 1996.

U.S. Patent Application Ser. No. 08/584,788, Filed Jan. 9, 1996.

U.S. Patent Application Ser. No. 08/489,185, Filed Jun. 9, 1995.

U.S. Patent Application Ser. no. 08/602,686, Filed Feb. 16, 1996.

K. Casson et al., "High Temperature Packaging: Flip Chip on Flexible Laminate", Jan. 1992, Surface Mount Technology, pp. 19–20.

R.W. Johnson, "Polymer Thick Films: Technology and Materials", Jul. 1982, Circuits Manufacturing (reprint).

K. Gilleo, "Using SM Devices On Flexale Circuitry", Mar. 1986, Electri-onics, pp. 20–23.

M.G. Kanarzibis "Conductive Polymers", Dec. 3, 1990, Chemical and Engineering News—American Chemical Society, pp. 36–54.

* cited by examiner




FIG.1A






FIG.1B








FIG. 4A



FIG. 4B




FIG. 4C




FIG. 4D




FIG. 5A

FIG. 5B





FIG. 6A




FIG. 6B







FIG. 6C






FIG. 8




FIG. 9






FIG. 10






FIG. 13A




FIG. 13B

METHOD OF MANUFACTURING AN ENCLOSED TRANSCEIVER

CROSS REFERENCE TO RELATED APPLICATION

This is a division of U.S. patent application Ser. No. 08/781,107, filed Jan. 9, 1997, and titled "Method of Manufacturing an Enclosed Transceiver," now U.S. Pat. No. 5,776,278, which in turn is a continuation of U.S. patent application Ser. No. 08/602,686, filed on Feb. 16, 1996, now abandoned, which is a file wrapper continuation of U.S. patent application Ser. No. 08/137,677, filed Oct. 14, 1993, now abandoned, which is a continuation-in-part of U.S. patent application Ser. No. 07/899,777, filed Jun. 17, 1992 (now abandoned).

TECHNICAL FIELD

The present invention relates generally to a process for manufacturing an enclosed transceiver, such as a radio frequency identification ("RFID") tag.

BACKGROUND

In the field of radio frequency identification ("RFID"), communication systems have been developed utilizing relatively large packages whose size is on the order of that of a cigarette package or a substantial fraction thereof, and generally speaking, have been fabricated using hybrid circuit fabrication techniques. These relatively large electronic packages have been affixed, for example, to railroad cars to reflect RF signals in order to monitor the location and movement of such cars.

With respect to an enclosed electronic apparatus, a system for handling baggage in an airport terminal is a typical application. Such a system incorporates radio frequency identification (RFID) between interrogators and transceivers. Further, each baggage tag is an enclosed, battery operated transceiver.

Other smaller passive RFID packages have been developed for applications in the field of transportation, including the tracking of automobiles. These packages include reflective systems of the type produced by Amtech Inc. of Dallas, Tex. However, these reflective passive RFID packages which operate by modulating the impedance of an antenna are inefficient in operation, require large amounts of power to operate, and have a limited data handling capability.

In still other applications of article location and tracking, such as in the postal service or in the field of airline baggage handling and transport, it has not been practical or feasible to use the above relatively large and expensive RFID hybrid packages on smaller articles of transport such as letters, boxed mail shipments or airline luggage. Accordingly, in these latter areas of transport monitoring, as well as many other areas such as inventory control of stored articles, article location and tracking methods have traditionally employed bar code identification and optical character recognition (OCR) techniques which are well known in the art.

Bar code identification and OCR techniques are labor intensive and may, for example, require several airline employees or postal workers to physically manipulate the article and/or the bar code readers to read these bar codes before the transported article reaches its final destination. In addition, the cost of bar code readers and optical character readers is high, limiting the number of locations at which these readers can be used. Furthermore, both bar code readers and optical character readers tend to be highly unreliable.

In yet further and somewhat unrelated fields of: (1) animal tracking and (2) plant tracking, other types of passive RFID tags have been developed by Hughes/IDI/DeStrom of Irvine, Calif. These tags utilize a coil wrapped around a ferrite core.

Such passive RFID tags have a very limited range, on the order of nine (9) inches, have a very limited data handling capability, and are not field programmable. In addition, these tags are limited in data storage capacity and are slow in operation.

In view of the problems described above and related problems that consequently become apparent to those skilled in the applicable arts, the need remains for enclosed electronic apparatus including transceivers wherein the enclosure is inexpensive, readily manufactured in high volume, appropriate in size for use as a stamp, label, or tag, and, in the case of transceivers, operable over distances of several hundred feet without regard for the spacial orientation of the enclosure.

SUMMARY

The general purpose and principal object of the present invention is to provide a novel alternative approach to all of the above prior art RFID, OCR, and bar code type location tracking and data storage systems. This new approach as described and claimed herein represents a fundamental breakthrough in the field of article transport control in a wide variety of fields, of which the fields of airline baggage transport, delivery of parcels and mail, and inventory control are only three examples.

To accomplish this purpose and object, we have invented and developed a new and improved radio frequency identification device, an associated electrical system, and a method for communicating with a remote RFID device from a local interrogator and controller. The size of this new device will typically be on the order of one inch square and 0.03 inches thick, or only slightly larger and slightly thicker than a postage stamp. This device includes, in combination, an integrated circuit (IC) which is mounted in an approximately one inch square package and is encapsulated, for example laminated, in a flexible or rigid thin film material. This material may also include a suitable adhesive backing for reliably securing the package to an outer surface or printed label of an article of interest. The IC includes therein a receiver section for driving suitable control logic and memory for decoding and storing input information such as an identification number, the baggage owner's name, point of origin, weight, size, route, destination, and the like. This memory includes, but is not limited to, PROMs, EPROMs, EEPROMs, SRAMs, DRAMs, and ferroelectric memory devices. The IC also includes a transmitter section therein operative for transmitting this information to an interrogator upon subsequent IC interrogation. An RF antenna is placed in a desired geometrical configuration (for example, monopole, dipole, loop, bow-tie, or dual-dipole) and incorporated within or on the thin film material and adjacent to the IC in an essentially two dimensional structure, neglecting the approximately 30 mil thickness dimension of the completed structure.

Advantageously, a thin battery is connected to the IC for providing power to the IC. The IC also incorporates circuitry to allow for operation in a sleep mode during transit and in storage in order to conserve power. Thus, at shipment points of origin, destination, and locations in transit, an operator may encode data into the IC or interrogate the IC by signaling the IC from a remote location to thereby "wake up" the IC without engaging in any hands-on operation.

In a preferred embodiment of the invention, the integrated circuit receiver and transmitter are operated in a spread spectrum mode and in the frequency range of 200 Mhz to 10 GHz, with the range of 800 MHz to 8 GHz being the range of most importance. This operation has the effect of avoiding errors or improper operation due to extraneous signal sources and other sources of interference, multipathing, and reflected radiation from the surrounding environment.

Accordingly, it is a further object of this invention to provide an RFID electronic device of the type described and method of fabricating such device.

Another object of this invention is to provide an RFID system and method of operation of the type described which utilizes RF transmitting and receiving sections on a single IC. Such a system has applications for tracking people or articles in both storage and transit.

Another object of this invention is to provide an electronic device of the type described which does not include bulky hybrid circuits, use modulation techniques described above for passive RFID tags, nor require scanning of bar codes, bar code readers, optical character readers, or especially clean operating environments.

Another object of this invention is to provide an electronic device of the type described which may be manufactured using integrated circuit fabrication and packaging processes.

Another object of this invention is to provide an electronic device of the type described which may be reliably and economically manufactured at high yields and at a high performance to price figure of merit.

Another object of this invention is to provide an RFID device of the type described which is field writable and has a transmission range greater than five (5) feet.

Another object of this invention is to provide a novel assembly process for manufacturing the RFID electronic device described herein.

Another object is to provide a manufacturing process of the type described which is conducive to high speed automation.

Another object is to provide an enclosed electronic device of the type described which is further conducive to high speed product usage, since these RFID devices may be supplied to the customer in a tape and reel format, a fan fold format, or a sheet format.

Another object of this invention is to provide an RFID device of the type described which may be powered with the use of an RF coil and capacitor and without the use of a battery. Such device is also referred to herein as the "passive" device embodiment. However, the term "passive" refers only to the fact that no battery is used, whereas the electrical circuitry on the IC is indeed active while being powered by the RF coil and capacitor combination.

Another object of this invention is to provide a non-contact method of object and person detection and location which can serve as a replacement for metal-to-metal contact in smart card applications and as a replacement for magnetic strip, bar code, and other types of contact-powered electronics. This novel method of object detection and location represents a significant saving of time and manual effort. For example, consider the time and effort involved when a person must first remove a smart card from a pocket or billfold and then insert the card in a card reader device before being allowed entry into a secured area within a building.

Another object of this invention is to provide an electronic device, system, and communication method of the type

described which represents, in novel combination, a fundamental breakthrough in many diverse fields of article shipment, including the parcel post and postal fields, the airline industry, inventory control for many manufacturing industries, security, waste management, personnel, and the like.

Accordingly, an enclosed electrical assembly of the present invention includes: a rigid or flexible thin film support member having an integrated circuit (IC) disposed thereon and an antenna incorporated within the IC or positioned adjacent to the IC within a predetermined area of the thin support member; means on the IC for receiving and encoding data relating to the article being stored or shipped; and means on the IC for reading the stored data and transmitting this data to an operator at a remote location.

According to a first aspect of such an assembly, a base member and a cover member each having conductive patterns developed thereon connect the IC in series with two thin film batteries. By arranging two batteries with the IC, no substantial current flows through a laminated or folded portion of the assembly. Smaller signal levels, lower power operation, and longer useful life of the assembly results.

According to another aspect, antenna coupling is also provided to the IC without current flow through a laminated or folded portion of the assembly. Greater sensitivity in receiving and lower losses in transmitting result.

According to another aspect of the present invention, an RFID device has two modes of operation are provided with a wake-up circuit. The wake-up circuit senses in-band energy and switches from a sleep mode to an operating (waked) mode. The sleep mode being useful during transit and storage of the RFID device to conserve battery power.

According to another aspect of such an RFID device, the IC includes receiver and transmitter sections characterized by spread spectrum modulation. Use of spread spectrum modulation reduces data transmission and reception errors, reduces the possibility of improper operation in response to extraneous signal sources, reflected radiation from a surrounding noisy environment, and other interference. Battery power is thereby conserved.

According to another aspect of the present invention, the enclosure includes an adhesive on an outer surface thereof. The adhesive permits reliable and convenient securing of a device of the present invention to an article being transported or stored.

According to yet another aspect of the present invention, by enclosing a transceiver in film, an extremely light weight, durable, and thin package results. Such a package is appropriate for use in replacement of or in conjunction with the conventional handwritten label, conventional hand-cancelled or postage-metered stamp, and the conventional baggage tag.

According to another aspect of the present invention, the frequencies of radio communication, modulation scheme, geometry of the antenna, capacity of the battery, and electrical properties of the enclosure cooperate for omnidirectional communication between an enclosed transceiver of the present invention and a distant interrogator. No manual manipulation of the interrogator or transceiver is required for area-wide communication such as confirming the contents of a delivery vehicle or verifying inventory in place, to name a few examples.

According to an aspect of another embodiment of the present invention, a plurality of transceivers are enclosed and laminated between a pair of films. One side of one of the films has adhesive capability. The transceivers are separated

5

and arranged on a backing. A roll or tape of the backing having transceivers removably attached thereto is enclosed in an RF tight dispenser. The dispenser provides convenient access to unprogrammed transceivers for use on articles to be shipped. When removed from the dispenser, a transceiver communicates with an interrogator in the area for establishing transceiver identity, shipping authorization, destination or storage criteria, date of issue, and similar information. By shielding transceivers within the dispenser from wake-up signals, battery power is conserved.

These and other embodiments, aspects, advantages, and features of the present invention will be set forth in part in the description which follows, and in part will become apparent to those skilled in the art by reference to the following description of the invention and referenced drawings or by practice of the invention. The aspects, advantages, and features of the invention are realized and attained by means of the instrumentalities, procedures, and combinations particularly pointed out in the appended claims.

DESCRIPTION OF THE DRAWINGS

FIG. 1A and FIG. 1B are functional block diagrams of enclosed transceivers of the present invention.

FIG. 2 is a perspective view of an enclosed transceiver as shown in FIG. 1A.

FIG. 3 is a plan view showing the conductive patterns on the base and cover members used in FIG. 2, including dotted line outlines of the locations for the IC and batteries.

FIG. 4A through FIG. 4D are cross sectional views taken along lines 4—4 of FIG. 3 showing four processing steps used in constructing the enclosed transceiver shown in FIG. 3.

FIG. 5A is a perspective view of an alternate embodiment of the invention wherein the IC is mounted on a parallel plate capacitor which in turn is mounted on a battery.

FIG. 5B is an enlarged portion of FIG. 5A.

FIG. 6A through FIG. 6E are cross sectional views taken along lines 6—6 of FIG. 5 showing five processing steps used in constructing the embodiment shown in FIG. 5.

FIG. 7 is a cross-sectional view showing an arrangement of battery and capacitor alternate to the embodiment shown in FIG. 5.

FIG. 8 is a perspective view of another alternate embodiment of the present invention having battery surfaces defining and performing the function of a bow-tie antenna.

FIG. 9 shows an alternate, passive device embodiment of the present invention in partially cut-away perspective view wherein the battery has been altogether eliminated and further wherein a capacitor is periodically charged from an external source in a manner described below to provide operating power to the IC.

FIG. 10 is a top view of a web of enclosed transceivers of the present invention.

FIG. 11 is an exploded perspective view of the top and bottom films used to construct one of the enclosed transceivers shown in FIG. 10.

FIG. 12 is a cross-sectional view taken along lines 12—12 of FIG. 11 showing a portion of the web shown in FIG. 10 and illustrating electrical coupling to and between the films.

FIG. 13A is a process flow diagram showing the steps of the present invention used to manufacture an enclosed transceiver.

FIG. 13B is a process flow diagram showing the steps of the present invention used to manufacture another enclosed transceiver.

6

In each functional block diagram, a single line between functional blocks represents one or more signals. A person of ordinary skill in the art will recognize that portions of the perspective views and cross-sectional views are enlarged for clarity.

DESCRIPTION

FIG. 1A and FIG. 1B are functional block diagrams of enclosed transceivers of the present invention. Enclosed transceiver 1 includes a pair of batteries 2 and 3, a dipole antenna 4 and 5, and an integrated circuit (IC) 11. Batteries 2 and 3 are in series connection through line 6 and cooperate as powering means for supplying power to IC 11 through lines 8 and 9. As will be discussed below, the series connection of two batteries simplifies conductor patterns in the enclosure. IC 11 is a four terminal device operating as communicating means for transmitting and receiving radio signals. Dipole antenna 4 and 5 couples radio signals between IC 11 and the communications medium which separates enclosed transceiver 11 from an interrogator, not shown. The interrogator is located up to 400 feet from enclosed transceiver 11.

Integrated circuit 11 is a transceiver including wake-up circuit 12, receiver 13, transmitter 14, control logic 15, and memory 16. Each of these functional circuits receives power signals VCC and GND on lines 8 and 9. When a received signal has substantial in-band energy as detected by wake-up circuit 12, control logic 15 enables receiver 13 for receiving and decoding a radio signal on antenna 4 and 5. Received data is provided by receiver 13 to control logic 15. Control logic 15 writes received data into memory 16. Control logic 15 also processes (i.e. decodes, tests, or edits) the received data with data stored in memory 16 and determines whether a response transmission is appropriate and the content of such a response. If a response is appropriate, control logic 15 reads transmit data from memory 16 and enables transmitter 14 for sending the transmit data as a second radio signal on antenna 4 and 5. Control logic 15 operates as a controller for reading data from and writing data to memory 16. Antenna 4 and 5 matches the medium to the receiver and to the transmitter for improved receiver sensitivity, and reduced transmission losses. Dipole antenna 4 and 5 has a toroidal antenna pattern with a null along the axis of the toroid.

FIG. 1B is a functional block diagram of an alternate enclosed transceiver of the present invention. Like numbered elements correspond to elements already described with reference to FIG. 1A. Enclosed transceiver 18 includes loop antenna 19, battery 20, and integrated circuit 21. Loop antenna 19 provides near omnidirectional communication capability as will be discussed with reference to FIG. 11.

Battery 20 is connected to antenna line 22 to reduce the number of terminals required to connect integrated circuit 21 into enclosed transceiver 18 and to improve the omnidirectional nature of the antenna pattern. A novel enclosure implements this connection to be discussed below. Integrated circuit 21 is a three terminal device providing the same functions as integrated circuit 11 already described with reference to FIG. 1A.

As an example of a data call-up operation, consider the events surrounding checking baggage or mailing a package. When an enclosed transceiver of the present invention is placed on the outside surface of a piece of luggage by the airlines or on a package for shipment by the postal service, an airline agent or postal worker operates an interrogator. The interrogator transmits information to receiver 13 via an RF communication link concerning data such as the owner's

name, an ID number, point of origin, weight, size, route, destination, amount of postage prepaid, billing information for debit, postage, handling, or storage costs due, time stamp, and the like. This received data is coupled to control logic 15 for processing, encoding, and storage in memory 16. Stored data is made available for call up by an interrogator at one or more points along the shipment route.

For example, upon reaching a point of shipment destination, an interrogator calls up stored data and uses it at the point of destination for insuring that the item of luggage or shipment is most assuredly and efficiently put in the hands of the desired receiver at the earliest possible time. Specifically, an interrogator at the destination point sends interrogation signals to the enclosed transceiver 1 where they are received by antenna 4 and 5 and first processed by sleep/wake up circuit 12. Wake-up circuit 12 operates to bring integrated circuit 11 out of a "sleep" mode into a "waked" mode wherein receiver 13 receives and decodes signals to provide received data to control logic 15.

With integrated circuit 11 now in "waked" mode, memory 16 is read by control logic 15 to call-up transmit data, i.e. the above six pieces of information relating to the shipped article. Control logic 15 then couples the transmit data to transmitter 14 and enables transmitter 14 for sending transmit data to the interrogator.

Receiver 13 and transmitter 14 preferably employ one of the well known spread spectrum modulation techniques including for example: (1) direct sequencing, (2) frequency hopping, (3) pulsed FM or chirped modulation, (4) time hopping, or (5) time-frequency hopping used with pulse amplitude modulation, simple amplitude modulation or binary phase shift keying.

The communication circuitry of an interrogator (not shown) is designed to conform to the modulation technique, message encoding, and modes of operation described for the enclosed transceivers of the present invention. Interrogator design is understood by those skilled in the art and, therefore, is not described herein.

FIG. 2 is a perspective view of an enclosed transceiver as shown in FIG. 1A. Enclosed transceiver 1 includes a base support layer 30 upon which an integrated circuit 32 is disposed on the near end of layer 30 and connected to a dipole antenna consisting of a pair of conductive strips 34 and 36 extending laterally from IC 32. These conductive strips 34 and 36 will typically be screen printed on the upper surface of base support layer 30.

A pair of rectangularly shaped batteries 38 and 40 are positioned as shown adjacent to IC 32 and are also disposed on the upper surface of base support member 30. Rectangular batteries 38 and 40 are electrically connected in series to power IC 32 in a manner more particularly described below. Assembly of enclosed transceiver 1 is completed by the folding over of an outer or upper cover member 42 which is sealed to the exposed edge surface portions of the base member 30 to thereby provide an hermetically sealed and completed package. When cover member 42 is folded over onto base member 30, conductive strip 50 is attached to batteries 38 and 40 using conductive epoxy. Conductive strip 50 provides means for coupling a pole of battery 38 to a pole of battery 40; thus accomplishing the series electrical connection of batteries 38 and 40. Integrated circuit 32 has transmitter, memory, control logic, and receiver stages therein and is powered by batteries 38 and 40 during the transmission and reception of data to and from an interrogator to provide the interrogator with the various above information and identification parameters concerning the article, animal or person to which the enclosed transceiver is attached.

FIG. 3 is a plan view showing the conductive patterns on the base and cover members used in FIG. 2, including dotted line outlines of the locations for the IC and batteries. During the initial manufacturing stage for the enclosed transceiver, base 30 and cover 42 are joined at an intersecting line 44. Dipole antenna strips 34 and 36 are shown positioned on each side of IC 32. Two conductive strips 46 and 48 serve to connect the bottoms of batteries 38 and 40 to IC 32. Conductive strip 50 is provided on the upwardly facing inside surface of top cover 42, so that, when cover 42 is folded at intersecting line 44, the outer boundary 52 of cover 42 is ready to be sealed with the outer boundary 54 of base support member 30. Simultaneously, conductive strip 50 bonded by the conductive epoxy to batteries 38 and 40, completes the series electrical connection used to connect batteries 38 and 40 in series with each other and further in series circuit with integrated circuit 32 through conductive strips 46 and 48.

FIG. 4A through FIG. 4D are cross sectional views taken along lines 4—4 of FIG. 3 showing four processing steps used in constructing the enclosed transceiver shown in FIG. 3. FIG. 4A shows in cross sectional view IC 32 bonded to base support member 30 by means of a spot or button of conductive epoxy material 56. Conductive strip 48 is shown in cross section on the upper surface of base support member 30.

In FIG. 4B, battery 40 is aligned in place as indicated earlier in FIG. 2 and has the right hand end thereof bonded and connected to the upper surface of conductive strip 48 by means of a spot of conductive epoxy applied to the upper surface of conductive strip 48, but not numbered in this figure.

In FIG. 4C, a stiffener material 58 is applied as shown over the upper and side surfaces of IC 32. The stiffener material will preferably be an insulating material such as "glob-top" epoxy to provide a desired degree of stiffness to the package as completed. Next, a spot of conductive epoxy is applied to each end of conductive strip 50, and then cover layer material 42 with the conductive epoxy thereon is folded over onto batteries 38 and 40 and base member 30 to cure and heat seal and, thus, complete and seal the package in the configuration shown in FIG. 4D.

FIG. 5A is a perspective view of an alternate embodiment of the invention wherein the IC is mounted on a parallel plate capacitor which in turn is mounted on a battery. FIG. 5B is an enlarged portion of FIG. 5A. The enclosed transceiver shown includes the combination of battery 60, capacitor 62, and IC 64. When inrush current requirements for IC 64 exceed the capability of battery 60 to supply surge current, for example, due to inductive coupling or battery structure, inrush current is supplied by capacitor 62. The structure of battery 60 is in direct contact with the upper surface 66 of a base support member 68. The structure of parallel plate capacitor 62 is positioned intermediate to the upper surface of the structure of battery 60 and the bottom surface of IC 64. In order to facilitate making electrical contacts to capacitor 62 and battery 60, respectively, an exposed capacitor bottom plate area 65 is provided on the left hand side of this structure and an exposed battery bottom plate area 67 is provided on the right hand side of the battery-capacitor-chip structure. A plurality of antenna lines 70, 72, 74, and 76 form two dipole antennas connected to opposite corners of IC 64 in a generally X-shaped configuration and extend as shown from IC 64 to the four corners of the package. Upper polymer cover 77 is sealed in place as shown to hermetically seal all of the previously identified elements of the package between base support member 68 and polymer cover 77.

FIG. 6A through FIG. 6E are cross sectional views taken along lines 6—6 of FIG. 5 showing five processing steps used in constructing the embodiment shown in FIG. 5. Base starting material includes a first or base polymer layer 78, such as polyester or polyethylene, which is laminated with a relatively impermeable material such as metal film, PVDC, or silicon nitride. Base layer 78 is coated on the bottom surface thereof with a suitable adhesive film 80 which will be used for the device adhesion during device usage. If the adhesive is sufficiently impermeable, the impermeable coating may be omitted. The battery connection and attachment are made on the upper surface of base layer 78 using a spot of conductive epoxy. Conductive epoxy is also used at interface 94 between battery 60 and capacitor 62 and interface 98 between capacitor 62 and IC 64.

Referring now to FIG. 6B, a thin film battery consisting of parallel plates 84 and 86 is placed on base layer 78. Next, a capacitor comprising parallel plates 90 and 92 is attached onto battery layer 84 using a conductive epoxy. Bottom plate 92 of capacitor 62 is somewhat larger in lateral extent than top capacitor plate 90 in order to facilitate the necessary electrical connection of battery 60 and capacitor 62 to integrated circuit 96. IC 96 corresponds to IC 64 in FIGS. 5A and 5B. IC 96 is then attached to top capacitor plate 90 with a conductive epoxy at interface 98, thereby providing an electrical connection. The bottom surface of IC 96 is metallized to facilitate this connection. In an alternate and equivalent fabrication process, an epoxy cure heat step or metallization anneal step is used to enhance the sealing between the various above stacked elements.

Referring now to FIG. 6C, prefabricated insulating layer 100 is now laid over the battery/capacitor/IC stack in the geometry shown. Layer 100 includes openings 102, 104, 110, and 112 therein for receiving a conductive polymer material as will be described below in the following stage of the process. Prefabricated holes 102, 104, 110, and 112 in layer 100 are aligned, respectively, to the battery contact, to the capacitor contact, and to the contacts on the top of IC 96. Layer 100 is then sealed to base polymer layer 78 using, for example, a conventional heating or adhesive step.

Referring now to FIG. 6D, a conductive polymer material 108 is deposited in openings 102 and 104 in the lower regions of layer 100 and extended up into the upper openings 110 and 112 of layer 100 to make electrical contact as indicated on the upper surface of IC 96. The shaped conductive epoxy material 108 may also be preformed utilizing a stamping tool or silk screening techniques and is applied as shown over the upper surface of layer 100. Conductive epoxy material 108 forms the innermost region of the antenna structure extending from IC 96 out in the dual dipole geometry as previously described with reference to FIGS. 5A and 5B. However, the complete antenna geometry shown in FIG. 5A is outside the lateral bounds of the fragmented cross sectional views shown in FIGS. 6A through 6E. At this point in the process, an epoxy cure heat step is optional.

Referring now to FIG. 6E, polymer insulating layer 114 is formed on the upper surface of layer 100 in the geometry shown and further extends over the exposed upper surfaces of the conductive epoxy polymer antenna material 108. Layer 114 is then sealed to layer 100 using either heat or adhesive sealing. Layer 114 provides a final hermetic seal for the completed device shown in cross section in FIG. 6E.

FIG. 7 is a cross-sectional view showing an arrangement of battery and capacitor alternate to the embodiment shown in FIG. 5. As shown in FIG. 7, the battery and capacitor are mounted side-by-side under the IC. The electrical connec-

tion for battery 118 and capacitor 120 to integrated circuit 96 is provided by positioning the battery 118 and capacitor 120 in the co-planar configuration shown on the surface of base polymer layer 78. The bottom plate of battery 118 is connected through conductive epoxy layer 128 to the top surface of IC 96. The bottom plate of parallel plate capacitor 120 is connected through conductive epoxy layer 128 to the top surface of the IC 96. A small space 126 is provided as shown to electrically isolate battery 118 and capacitor 120. In addition, in this embodiment of the invention, conductive material 128 is extended as shown between the left side opening 130 in the layer 100 and a lower opening 132 in layer 100. In a manner similar to that described above with reference to FIGS. 6A through 6E, layer 114 is then extended over the top surface of layer 100 in the geometry shown. Conductive polymer material 128 extends to connect the crossed antenna structure of FIG. 5 to IC 96 shown in FIG. 7.

FIG. 8 is a perspective view of another alternate embodiment of the present invention having battery surfaces defining and performing the function of a bow-tie antenna. IC 138 is centrally positioned as shown on the upper surface of base support member 140 and is electrically connected to two triangularly shaped batteries 142 and 144, also disposed on the upper surface of base support member 140. Batteries 142 and 144 are connected in series with IC 138 when protective cover member 146 is sealed over the top surfaces of the two batteries 142 and 144 and the IC 138 using processing steps previously described.

In the embodiment of the invention shown in FIG. 8, the entire outer surfaces of the two batteries 142 and 144 serve as a “bow tie” antenna structure for the enclosed transceiver. At communication wavelengths, the top and bottom surfaces of batteries 142 and 144 are coupled together. Batteries 142 and 144 are connected in series with the IC 138 to provide DC operating power therefor in a manner previously described. Moreover, the dual use of the batteries as power supplies and antenna structures minimizes the number of terminals required to connect IC 138 into an enclosed transceiver.

FIG. 9 shows an alternate, passive device embodiment of the present invention in partially cut-away perspective view wherein the battery has been altogether eliminated and further wherein a capacitor is periodically charged from an external source in a manner described below to provide operating power to the IC. This embodiment is known as the passive or battery-less device embodiment, since it contains no battery therein. Instead, operating power is provided by a capacitor structure identified as component 148 located beneath IC 150. A charge on capacitor 148 is maintained by conventional RF charging circuits (not shown) on IC 150 which are energized from a remote source.

The enclosed transceiver shown in FIG. 9 includes a first loop antenna 152 for receiving RF charging signals for capacitor 148 and a dipole antenna formed of conductive strips 154 and 156 for receiving and transmitting data to and from IC 150. As in previous embodiments, capacitor 148 and IC 150 are positioned and hermetically sealed between a base cover member 157 and a top cover member 158.

FIG. 10 is a top view of a web of enclosed transceivers of the present invention. Laminated sheet 200 includes 36 enclosed transceivers 210 simultaneously manufactured in a plurality of cavities as already described. Sheet 200 in a preferred embodiment includes 252 enclosed transceivers, each approximately 1.5 inches square. Alternatively, sheet 200 includes one folded film as illustrated in FIGS. 2, 3, and

4; three coextensive films **114**, **100**, and **78** as illustrated in FIGS. **6** and **7**; or two coextensive films as is apparent from FIGS. **8** and **9**, and FIGS. **11** and **12** to be discussed below. Sheet **200**, in one embodiment is sectioned to obtain individual enclosed transceivers by interstitial cutting, perforation and tearing, or sheering; sectioning being simultaneous with or following the step of sealing each enclosed cavity by lamination, embossing, hot stamping or the like. Alternatively enclosed transceivers are manufactured in a continuous strip, for example, one enclosure.

After manufacturing has been completed, a large number of finished devices, or webs are stored on a take-up reel (not shown) supporting a corresponding large plurality of the devices. Advantageously, storage on a take-up reel not only makes the present process conducive to high speed automated manufacturing, but in addition makes the process compatible to high speed manual or automated product dispensing and use. Large numbers of enclosed transceivers may be supplied easily to a user in a conventional tape and reel format. The user can readily detach one device at a time for immediate attaching to an article. Alternatively, enclosed transceivers are manufactured and shipped in sheets and later sectioned by the customer.

In yet another embodiment, devices are cut from the tape or sheet from which they were manufactured and then removably mounted on a backing. The backing in one embodiment is in tape format and in another equivalent embodiment is in sheet format. When mounted to a backing, enclosed transceivers are more effectively stored in a cache for dispensing individually. The cache, not shown, includes means for dispensing (i.e. separately providing a transceiver on demand) and shielding means for preventing signal reception by enclosed transceivers within the cache. If shielding were not included, a supply of transceivers located within communicating range of an interrogator would soon expend battery capacity by processing signals including, for example, wake-up signals. Means for dispensing includes, for example, mechanical devices for feeding a tape or sheet through an opening and mechanical devices for separating shielding materials from a tape or sheet. The former dispensing means, in one embodiment of the cache, cooperates with shielding across the opening including conductive rollers, separating brushes, separating fingers, and the like. The latter dispensing means, in another embodiment of the cache, cooperates with conductive backing material, or conductive foam as a backing or cover layer arranged to shield the exposed edges of a roll containing transceivers.

FIG. **11** is an exploded perspective view of the top and bottom films used to construct one of the enclosed transceivers shown in FIG. **10**. The embodiment shown corresponds to enclosed transceiver **18** shown in FIG. **1B**. Top film **214** includes area **222** for lamination onto the top surface (pole) of battery **20**; strip **218** for loop antenna **19**; and, contact area **226**. Each of these three features, in a preferred embodiment, is formed of conductive ink. In an alternate and equivalent embodiment, these three features are formed of conductive epoxy. Bottom film **230** includes area **238** for lamination onto the bottom surface (pole) of battery **20**; strip **234** for loop antenna **19**; contact area **254**; and contact points **242**, **246**, and **250** for connecting integrated circuit **21** to the battery and antenna. Each of these six features, in a preferred embodiment, is formed of conductive ink, though conductive epoxy is equivalent.

Contact **246** is intentionally misaligned with respect to area **222** to prevent shorting battery **20**. However, strips **218** and **234** are aligned to coincide, as are contact areas **226** and **254**, respectively. These strips and contact areas when joined

by lamination cooperate as means for coupling power from battery **20** to IC **21** and, simultaneously, for electrically matching IC **21** to the communications medium by forming loop antenna **19**. Thus, contacts **242**, **246**, and **250** correspond respectively to lines **24**, **23**, and **22** shown in FIG. **1B**.

Unlike the antenna pattern of the dipole antenna shown in FIGS. **1A**, **2**, **3**, and **9**, there is no null in the antenna pattern for loop antenna **19**, due in part to the conductive structure of battery **20** being connected to one side of loop antenna **19**. The combined loop antenna and battery structure is also preferred over the dipole in that the combination provides an antenna pattern that is less subject to variation over a broad range of frequencies.

FIG. **12** is a cross-sectional view taken along lines **12—12** of FIG. **11** showing a portion of the web shown in FIG. **10** and illustrating electrical coupling to and between the films. The completed assembly includes similarly numbered elements already discussed with reference to FIG. **11**. IC **290** is prepared for assembly by forming conductive bumps **306** and **314** to terminals on its lower surface. In a preferred embodiment, bumps are formed of conductive epoxy. In an alternate embodiment, metallic bumps, such as gold, are formed by conventional integrated circuit processes. IC **290** as shown is in a “flip chip” packaging orientation having substantially all circuitry formed on the surface facing film **230**. Prior to assembly, a puddle of conductive epoxy is applied to contacts **250** and **242**. IC **290** is then located atop contacts **250** and **242** so that bumps **306** and **314** are surrounded within puddles **302** and **310**. The film is then heated to set all conductive epoxy including puddles **302** and **310**, as well as strips and areas including the antenna and contact areas **226** and **254**, formed of conductive epoxy. Finally, top film **214** is aligned over bottom film **230** so that contact areas **226** and **254** are pressed together.

FIG. **13A** is a process flow diagram showing the steps of the present invention used to manufacture an enclosed transceiver of the type shown in FIGS. **10—12**. The manufacturing process begins with a polyester film used for the bottom and for the top. Material for the bottom in a first embodiment is identical to the top and includes film with dimensional stability, for example, polyester film that has been heat stabilized or pre-shrunk. These materials, though inexpensive, are porous to substances that degrade the life and functions of the battery and integrated circuit. This disadvantage is resolved in a preferred embodiment by coating the outer surfaces of the material used for the top and bottom film with a barrier material.

In the first step **410**, barrier material, such as a silicon nitride deposit, is formed on the outer surface by sputtering, or by chemical vapor deposition (CVD), preferably plasma enhanced CVD. The deposit provides a hermetic barrier to prevent water vapor and other contaminants from affecting (e.g. oxidizing) battery and transceiver components. In a first embodiment the resulting thickness of the deposit is from 400 to 10,000 angstroms. In another embodiment, where thin deposits are desirable, coating on both sides of the film prevents pin holes in each deposit from aligning in a way that defeats hermeticity. The thickness of the deposit and the manner of formation are design choices based on the selection of materials for the film and the deposit, as well as the system requirements for hermeticity over time. For example an alternate and equivalent embodiment uses other barrier materials including silicon oxide and silicon nitride deposited at a thickness of 100 to 400 angstroms. The barrier material is formed in such an embodiment using one of the processes including evaporation, deposition, chemical vapor deposition, and plasma enhanced chemical vapor deposition.

In another embodiment of the present invention, a nitride film is sputtered on the outside portion of a top and bottom base support layer. Each base support layer preferably comprises a polymer material such as a polyester film that is laminated with a barrier layer material such as polyethylene and/or polyvinylidenechloride (PVDC). Formation of the barrier material deposit can be deferred until the enclosed transceiver is encapsulated, provided that environmental concerns such as contamination, over heating, and changes in pressure are addressed.

In step **420**, a laminate adhesive is applied to the inner surfaces of the top and bottom films. The laminate adhesive is activated in a later manufacturing step to cause the top and bottom layers to adhere. Preferably, the adhesive is tack free. at room temperature and selected to match laminating equipment heat and pressure capabilities. In a preferred embodiment, butyl acrylate is extruded onto the films to cover the entire inside surface of each film. In another embodiment, the adhesive is screen printed for economy.

In step **430**, conductors are screen printed onto the films. In a preferred embodiment, the conductors are formed on top of laminate adhesive. Areas such as grid conductors **222** and **238** shown in FIG. **11** for contacting the battery are, consequently, interspersed with areas of exposed laminate adhesive to provide a more durable enclosure. In this embodiment, a polymer thick film ink is employed. High conductivity is provided by such inks that include copper or silver constituents. The ink preferably provides a stable surface for electrical butt contact formations. A low oxidation rate at storage temperature is desirable, though oxidation could be minimal in a controlled manufacturing environment.

Printed circuits on the top layer are arranged to perform multiple functions when the top and bottom layers are joined. First, a conductor on the top layer completes series or parallel circuits for devices having contacts in two planes. Conductor **50** in FIG. **2** is one example. Second, a conductor on the top layer completes an antenna structure for the transceiver integrated circuit, as illustrated in FIG. **8**. Third, a single conductor in the top layer accomplishes both the first and second functions. See, for example, the conductor in FIG. **11** identified as areas **226**, **222**, and **216**.

In an alternate embodiment, conductors are formed in a subtractive process, for example, chemical etching. By using a positive screen print process, energy and material are conserved. Printed circuit technology is applied in another embodiment wherein the step of attaching the integrated circuit and the battery to a base material includes soldering and brazing. The base material in such an embodiment is one of a wide variety of printed circuit materials including polyimide and glass-epoxy materials.

In step **440**, the top and bottom base support layers are cut from the roll or web to form sheets as illustrated in FIG. **10** to facilitate use of automated component placement machinery. Each sheet is attached, in step **450**, to a carrier panel for compatibility with conveyor based manufacturing facilities. At step **460**, a carrier with sheet attached is loaded into a magazine or placed onto a conveyor for automated manufacturing. Steps **440–460**, in an alternate embodiment of the manufacturing process of the present invention, are omitted. as unnecessary when continuous manufacturing from roll stock is desirable.

In step **470**, those portions of conductors that are to make electrical contact with the integrated circuit are prepared with a coating or puddle of conductive epoxy. In a preferred embodiment, silver filled epoxy is employed that remains

wet at room temperature until thermally cured. Application of the epoxy is by screen printing. In an alternate embodiment, epoxy is applied by dispensing.

In step **480**, integrated circuit die are placed so that epoxy bumps previously formed on the integrated circuit enter the puddles formed in step seven. The arrangement of the integrated circuit face down on the bottom film is commonly referred to as “flip-chip” orientation. In an alternate and equivalent embodiment, integrated circuits are also placed in contact puddles formed on the top, i.e. cover layer. All die on the sheet are placed and aligned in this step **480** prior to proceeding with subsequent cure.

In step **490**, a batch of panels is heated to set the epoxy applied in step **470**. In an alternate embodiment, a conveyor based oven supports continuous curing. Curing temperature and duration are design choices that match the epoxy curing requirements. In a preferred embodiment, curing is performed at 150 degrees Celsius for 3 to 5 minutes. The cure is selected so as not to interfere with the characteristics of the laminate adhesive applied in step **420**.

In step **500**, an encapsulation material, commonly called “glob top epoxy” is applied over the integrated circuit. Suitable nonconductive materials include those providing a stiffening property to protect the integrated circuit and the electrical connections thereto from mechanical damage.

In step **510**, the encapsulating material is cured. In a preferred embodiment, the encapsulating material is cured with ultraviolet radiation. An alternate and equivalent embodiment, employs a thermal curing process. The ultraviolet cure is preferred for rapid manufacturing. However, use of a thermal cure in step **510** may permit use of a partial thermal cure in step **490**, later perfected by additional thermal cure duration provided in step **510**.

In step **520**, the battery or batteries are aligned and placed on the base support film. In an embodiment including stacked battery cells, connection is made using conductive tape having adhesive on both sides of the tape. Such tape commonly includes conductive particles in the adhesive.

In step **530**, the top or cover film is aligned over the bottom or base film. In an embodiment including a folded film, the top film is folded over the base film. In an alternate embodiment employing continuous manufacturing from roll stock, the base film and top film are aligned for continuous lamination.

In step **540**, the top cover film is pressed onto the bottom base film and heat is applied to activate the adhesive applied in step **420**. For butyl acrylate adhesive a temperature of from 95 to 110 degrees Celsius is preferred.

In applications where the transceiver is to be used in harsh environments, the seal provided by automated lamination equipment may be incomplete or have weaknesses caused, for example, by insufficient heat or pressure at a point in an area to be sealed. Enclosing components of varying thicknesses can result in air pockets surrounding such components that, if too near the periphery, can also lead to weaknesses and voids. In such applications, the preferred process includes step **550** wherein the periphery of each transceiver on a sheet is subject to a second application of heat and pressure for activating laminate adhesive applied in step **420**. The additional heat and pressure in such a localized periphery can deform the films to form minute bosses. Thus, the step is called embossing. The aspect of the effective application of heat and pressure is more important than the extent of consequential deformation.

In an alternate embodiment, each enclosure is evacuated. Lamination for such an embodiment is conducted in an

evacuated environment. Embossing in yet another embodiment is also conducted in an evacuated environment.

After step 540, the circuitry of the battery powered transceiver is active by virtue of the completed circuits formed when the top cover layer is aligned and butt contacts are formed with components and the base layer. Functional tests of multiple or individual transceivers are now feasible.

In step 560, transceivers are functionally tested. To prevent interference between tests of individual transceivers, a pair of grounded plates with surface features are placed on both sides of a sheet of enclosed transceivers so that each transceiver operates inside a shielded cavity. The wavelength used for testing is selected such that leakage through the thickness of the embossed seal is negligible. Plates similar to the embossing die used in step 550 are used in one embodiment. Each cavity includes an antenna for transmitting stimulus signals and for receiving response signals for measuring the quality of each transceiver. Measurements include, for example, receiver sensitivity, transmitted spectrum, message handling capability, self-testing, and response timing.

In step 570, the sheet of tested transceivers is sheered in two dimensions to singulate or separate the transceivers from one another. In an alternate and equivalent embodiment, a backing material is applied to one side of the sheet prior to singulation. Singulation for this embodiment is accomplished by kiss cutting through the top and base films leaving the transceivers attached to the backing material. Transceivers, whether attached to the backing or loose are then sorted based on the results of functional testing performed in step 560 and additional testing as needed.

FIG. 13B is a process flow diagram showing the steps of the present invention used to manufacture another enclosed transceiver of the types shown in FIGS. 2–9. This embodiment of the method of the present invention includes nine (9) processing steps or fabrication stages which are used in the overall manufacturing process and in the construction of an enclosed transceiver.

In one embodiment the nine steps are performed sequentially as follows. In step 610, a circuit pattern is initially formed on a base layer material. This base layer material is preferably a polymer such as a polyester film that is laminated with a barrier layer material such as polyethylene and/or polyvinylidenechloride (PVDC). In step 612, the circuit pattern is cured and a conductive epoxy material is applied. In step 614 an integrated circuit chip is aligned onto the base layer. In step 616, two (2) batteries are aligned onto the base layer. In an alternate enclosed transceiver, the batteries are stacked vertically in either a series or parallel electrical connection. In step 618, the epoxy applied in step 612 is cured. In step 620, a stiffener material is applied. In step 622 epoxy is applied to the top surface of the battery and then the top half of the base layer is folded over the bottom half so that the top half forms the top cover. In step 624, the epoxy material applied in step 622 is cured. Finally, in step 626, the package is sealed to complete manufacturing of the package.

Various modifications may be made in and to the above described embodiments without departing from the spirit and scope of this invention. For example, various modifications and changes may be made in the antenna configurations, battery arrangements (such as battery stacking), device materials, device fabrication steps, and the functional block diagrams without departing from the scope of this invention. The various off-chip components such as the antenna, battery, and capacitor are manufactured on-chip

in alternate and equivalent embodiments. As a second example, the antenna in another alternate and equivalent embodiment is formed on the outer surface or within the outer film. In such an arrangement, coupling to the antenna is through the capacitance of the outer film as a dielectric. When formed on the exterior, the material comprising the antenna also provides hermeticity to the film for protecting the enclosed transceiver. Accordingly, these and equivalent structural modifications are within the scope of the following appended claims.

As previously suggested, an enclosed transceiver used as an RFID device has utility directed to a wide variety of applications including, but not limited to, airline baggage (luggage, freight, and mail); parcel post (Federal Express and United Parcel Service); U.S. Mail; manufacturing; inventory; personnel security.

While the particular invention has been described with reference to illustrative embodiments, this description is not meant to be construed in a limiting sense. It is understood that although the present invention has been described in a preferred embodiment, various modifications of the illustrative embodiments, as well as additional embodiments of the invention, will be apparent to persons skilled in the art, upon reference to this description without departing from the spirit of the invention, as recited in the claims appended hereto. It is therefore contemplated that the appended claims will cover any such modifications or embodiments as fall within the true scope of the invention.

The words and phrases used in the claims are intended to be broadly construed. A “sticker” refers generally to a label, tag, marker, stamp, identifier, packing slip, invoice, package seal, tape, band, clasp, medallion, emblem, shield, and escutcheon regardless of printed or handwritten material thereon. Mechanical coupling of a “sticker” so defined to an article, person, plant, or animal is not restricted to adhesive but is intended to broadly include all forms of fastening, tying, and securing.

What is claimed is:

1. A data storing device comprising:
 - a housing including first and second opposed major portions that are connected together;
 - an integrated circuit mounted to the first portion of the housing, the integrated circuit including a microprocessor and a random access memory, the random access memory being configured to store data;
 - a battery supported by the first portion of the housing and having first and second terminals, the first terminal being coupled to the integrated circuit; and
 - connection circuitry coupling the second terminal of the battery to the integrated circuit to complete a circuit, the connection circuitry including a conductor supported by the second portion of the housing and movable with the second portion of the housing.
2. A data storing device in accordance with claim 1 wherein the battery is a thin film battery.
3. A data storing device comprising:
 - a housing defined by first and second housing portions, the second housing portion being movable relative to the first housing portion between mated and open positions;
 - a random access memory configured to store data, the random access memory being supported by the first housing portion;
 - a battery in the housing; and
 - a conductor supported by and movable with the second housing portion, the conductor connecting the battery

17

to the random access memory when the second housing portion is in the mated position.

4. A data storing device in accordance with claim 3 wherein the random access memory comprises a static random access memory.

5. A data storing device in accordance with claim 3 and further comprising an integrated circuit including the memory, and a microprocessor, and wherein the conductor connects the battery to the integrated circuit.

6. A data storing device in accordance with claim 3 and further comprising an integrated circuit including the memory, and including a microprocessor, wherein the memory is a static random access memory, and wherein the conductor connects the battery to the integrated circuit so that the integrated circuit is powered by the battery, thereby resulting in the static random access memory being powered by the battery.

7. A data storing device in accordance with claim 3 wherein the battery comprises a thin film battery.

8. A data storing device in accordance with claim 3 wherein the housing has a thickness of about 0.03 inches.

9. A data storing device in accordance with claim 3 and further comprising an integrated circuit including the memory, including an RF transmitter, and including a microprocessor, wherein the memory is a static random access memory, and wherein the conductor connects the battery to the integrated circuit so that the integrated circuit is powered by the battery, thereby resulting in the static random access memory being powered by the battery.

10. A data storing device in accordance with claim 3 and further comprising an integrated circuit including the memory, including a microwave transmitter, including a microwave receiver, and including a microprocessor, wherein the memory is a static random access memory, and wherein the conductor connects the battery to the integrated circuit so that the integrated circuit is powered by the battery, thereby resulting in the static random access memory being powered by the battery.

11. A data storing device in accordance with claim 3 and further comprising conductive epoxy coupling the battery to the random access memory.

12. A portable data storing device comprising:

a housing defined by first and second housing portions; an integrated circuit including a random access memory random access memory for storing the data, the integrated circuit being supported by the first housing portion;

a battery in the housing; and

a conductor supported by and movable with the second housing portion and coupling the battery to the integrated circuit.

13. A portable data storing device in accordance with claim 12 wherein the battery comprises a thin film battery.

14. A portable data storing device in accordance with claim 12 wherein the housing has a thickness of about 0.03 inches.

15. A portable data storing device in accordance with claim 12 wherein the integrated circuit comprises a microprocessor, and an RF transmitter controlled by the microprocessor.

16. A portable data storing device method in accordance with claim 12 wherein the integrated circuit comprises a microprocessor, a spread spectrum radio frequency trans-

18

mitter controlled by the microprocessor, a receiver controlled by the microprocessor, and the random access memory, and wherein the random access memory is a static random access memory.

17. A portable data storing device method in accordance with claim 12 and further comprising conductive epoxy electrically coupling the integrated circuit to the battery.

18. A portable data storing device comprising:

a housing defined by first and second housing portions each including planar surfaces;

an integrated circuit supported from the first housing portion, the integrated circuit including a microprocessor, including a spread spectrum RF transmitter controlled by the microprocessor, including an RF receiver controlled by the microprocessor, and including a static random access memory configured to store the data;

a thin film battery in the housing; and

a conductor supported by and movable with the second housing portion, the conductor connecting the battery to the integrated circuit so that the integrated circuit is powered by the battery, thereby resulting in the static random access memory being powered by the battery.

19. A portable data storing device in accordance with claim 18 wherein the housing has a thickness of about 0.03 inches.

20. A portable data storing device in accordance with claim 18 and further comprising conductive epoxy electrically connecting the battery to the microprocessor.

21. A data storing device according to claim 1, wherein the conductor completes a circuit and supplies electrical power to the memory when the first and second portions of the housing are hermetically sealed together and does not complete the circuit or supply electrical power to the memory when the first and second portions are not hermetically sealed together.

22. A data storing device according to claim 1, wherein the conductor completes a circuit and supplies electrical power to the memory when the first and second portions of the housing are sealed together and does not complete the circuit or supply electrical power to the memory when the first and second portions are not sealed together.

23. A data storing device according to claim 1, wherein the first and second portions of the housing hermetically seal the integrated circuit and the battery.

24. A data storing device according to claim 1, wherein the first and second portions of the housing hermetically seal the integrated circuit and the battery when the first and second portions of the housing are mated together, and wherein the conductor completes a circuit and supplies electrical power to the memory when the first and second portions of the housing are mated together and does not complete the circuit or supply electrical power to the memory when the first and second portions are not mated together.

25. A data storing device according to claim 3, wherein the first and second housing portions enclose and hermetically seal the integrated circuit and the battery when the first and second housing portions are in the mated position.

26. A data storing device according to claim 3, wherein the conductor does not supply electrical power to the memory when the first and second housing portions are not in the mated position.

27. A data storing device according to claim 3, wherein the conductor completes a circuit and supplies electrical

19

power to the memory when the first and second portions of the housing are sealed together and does not complete the circuit or supply electrical power to the memory when the first and second portions are not sealed together.

28. A data storing device according to claim 12, wherein the first and second housing portions are configured to be mated and to enclose and hermetically seal the integrated circuit and the battery when the first and second housing portions are mated. 5

29. A data storing device according to claim 28, wherein the conductor couples the battery to the integrated circuit when the first and second housing portions are mated and does not couple the battery to the integrated circuit when the first and second housing portions are not mated. 10

30. A portable data storage device comprising: 15
a first housing member;
an antenna formed on the first housing member;
a second housing member configured to be mated to the first housing member;
a first battery disposed between the first and second housing members, a first electrode of the first battery contacting a first power conductor on the first housing member; 20

20

a second battery disposed between the first and second housing members, a first electrode of the second battery contacting a second power conductor on the first housing member;

an integrated circuit disposed on a side of the first housing member configured to be mated to the second housing member, the integrated circuit including a microprocessor, a RF transmitter controlled by the microprocessor, an RF receiver controlled by the microprocessor and a static random access memory coupled to the microprocessor and configured to store the data, the RF transmitter and RF receiver being operatively coupled to the antenna; and

a conductor formed on the second housing member, the conductor coupling the first and second batteries in series and supplying electrical power to the integrated circuit when the second housing member is mated to the first housing member and not coupling the first and second batteries in series or supplying electrical power to the integrated circuit when the second housing member is not mated to the first housing member.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,220,516 B1
DATED : April 24, 2001
INVENTOR(S) : Mark E. Tuttle; John R. Tuttle; and Rickie C. Lake.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 14,

Line 6, delete "step seven" and insert -- step 470 --.

Signed and Sealed this

Eighteenth Day of December, 2001

Attest:

A handwritten signature in black ink, appearing to read "James E. Rogan", with a horizontal line drawn underneath it.

Attesting Officer

JAMES E. ROGAN
Director of the United States Patent and Trademark Office