



US006223713B1

(12) **United States Patent**
Moorman et al.

(10) **Patent No.:** **US 6,223,713 B1**
(45) **Date of Patent:** **May 1, 2001**

(54) **OVERHEAD CAM ENGINE WITH CAST-IN VALVE SEATS**

1,799,271	4/1931	Woolson .	
1,845,136	2/1932	Dieter .	
1,910,375	5/1933	Woolson .	
2,000,714	5/1935	Nutt	184/6
2,235,160	3/1941	Ljungstrom	123/192
2,306,554	12/1942	Morehouse	184/6

(75) Inventors: **James W. Moorman**, Kiel; **Erik J. Christiansen**, Cedarburg, both of WI (US); **Roberto Molina**, Turin (IT); **Gar M. Adams**, Elkhart Lake, WI (US)

(List continued on next page.)

(73) Assignee: **Tecumseh Products Company**, Tecumseh, MI (US)

FOREIGN PATENT DOCUMENTS

63-147906 6/1988 (JP) .

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

Primary Examiner—John Kwon
(74) *Attorney, Agent, or Firm*—Baker & Daniels

(57) **ABSTRACT**

(21) Appl. No.: **09/494,867**

(22) Filed: **Jan. 31, 2000**

A single cylinder, internal combustion engine with a dry sump lubrication system. The engine includes an engine housing in which the overhead camshaft and crankshaft are rotatably supported, and the housing includes an integrally formed cylinder and head. A timing belt disposed externally of the engine housing interconnects the crankshaft and camshaft, and a piston connected to the crankshaft reciprocates within an internal bore provided in the engine housing cylinder. The cylinder wall around the internal bore is of a generally uniform thickness and circumscribed by cooling fins such that the cylinder resists bore distortion during operation. Dry sump lubrication is obtained by an external oil reservoir connected to a pump which supplies pressurized oil to the bearing journals of the camshaft. A portion of the oil at the camshaft bearing journals flows through passages provided within the cylinder to lubricate the bearing journals of the crankshaft. The reciprocating motion of the valve assemblies controlling intake and exhaust of the combustion chamber pumps the oil which lubricated the camshaft back to the external reservoir. The reciprocating motion of the piston similarly effects a high pressure within the crankcase cavity to pump oil which has lubricated the crankshaft back to the external reservoir. The inventive engine further provides for the mounting of flywheels within the crankcase cavity in conjunction with an external, light-weight fan for engine housing cooling, as well as employs a cast in valve seat for the overhead valve assemblies.

Related U.S. Application Data

(62) Division of application No. 09/286,636, filed on Apr. 2, 1999, now Pat. No. 6,032,635, which is a continuation of application No. 09/047,246, filed on Mar. 24, 1998, now Pat. No. 5,979,392, which is a division of application No. 08/673,100, filed on Jul. 1, 1996, now Pat. No. 5,755,194.

(51) **Int. Cl.**⁷ **F01M 1/00**

(52) **U.S. Cl.** **123/196 R; 123/196 W; 123/195 HC**


(58) **Field of Search** 123/188.8, 196 R, 123/196 W, 195 HC; 29/888.453, 888.4, 888.44

(56) **References Cited**

U.S. PATENT DOCUMENTS

Re. 21,031	3/1939	Schenk .
Re. 32,620	3/1988	Iwai .
1,024,727	4/1912	Huff .
1,112,536	10/1914	Huff .
1,191,246	7/1916	Tillotson .
1,291,839	1/1919	Gorham .
1,339,497	5/1920	Church .
1,384,873	7/1921	Strickland .
1,470,769	10/1923	Shaw .
1,575,359	3/1926	Nutt .

6 Claims, 7 Drawing Sheets



U.S. PATENT DOCUMENTS

2,324,373	6/1943	Dusevoir	74/598	4,773,884	9/1988	Matsumoto	440/88
2,346,207	4/1944	Brown	123/65	4,805,565	2/1989	Ssato	123/90.6
2,458,051	1/1949	Bosma	123/196	4,881,510	11/1989	Etoh	123/572
2,496,434	2/1950	Bosma	184/6	4,903,654	2/1990	Sato	123/196
2,700,964	2/1955	Nallinger	123/41.77	4,911,119	3/1990	Ohno	123/196
2,752,213	6/1956	Swart	309/10	4,936,270 *	6/1990	Ushio et al.	123/188.8
2,857,903	10/1958	Watkins	123/196	4,982,705	1/1991	Hudson	123/41.65
3,037,582	6/1962	Egloff	184/6	4,984,539	1/1991	Shinoda	123/41.42
3,042,146	6/1962	Shimanckas	184/6	5,020,490 *	6/1991	Seko	123/188.8
3,044,238	7/1962	Harkness	56/25.4	5,090,375	2/1992	Hudson	123/196
3,144,095	8/1964	Trapp	184/6	5,143,033	9/1992	Catterson	123/195
3,195,526	7/1965	Jordan	123/73	5,176,116	1/1993	Imagawa	123/196
3,331,364	7/1967	Chariatte	123/196	5,193,500	3/1993	Haft	123/196 CP
3,416,295	12/1968	Kaufman	56/25.4	5,213,074	5/1993	Imagawa	123/196
3,418,993	12/1968	Scheiterlein	123/195	5,241,932	9/1993	Everts	123/195
3,523,592	8/1970	Fenton	184/6	5,243,937	9/1993	Imagawa	123/195
3,669,082	6/1972	Hatz	123/41.65	5,293,847	3/1994	Hoffman	123/90.6
3,687,231	8/1972	Scheiterlein	184/6.5	5,320,795	6/1994	Mitchell	264/318
3,691,914	9/1972	Reisacher	92/169	5,347,967	9/1994	Todero	123/317
3,983,852	10/1976	Chatourel	123/41.69	5,421,298 *	6/1995	Ming et al.	123/193.5
4,372,258	2/1983	Iwai	123/73	5,447,127	9/1995	Luck et al.	123/90.33
4,433,655	2/1984	Villella	123/196	5,524,581	6/1996	Rush, II et al.	123/196 M
4,446,828	5/1984	Bauder	123/196	5,551,393 *	9/1996	Amano et al.	123/193.5
4,466,409	8/1984	Asak	123/433	5,606,943	3/1997	Tamba et al.	123/196 W
4,475,488	10/1984	Odashima	123/73	5,687,685 *	11/1997	Amano et al.	123/188.8
4,493,661	1/1985	Iwai	440/77	5,687,688	11/1997	Tsunoda et al.	123/196 W
4,523,556	6/1985	Suzuki	123/196	5,706,769 *	1/1998	Shimizu	123/195 HC
4,570,586	2/1986	Roe	123/192	5,755,194	5/1998	Moorman et al.	123/196 W
4,570,587 *	2/1986	Watanabe et al.	123/195 HC	5,765,520 *	6/1998	Adachi et al.	123/188.8
4,579,093	4/1986	Eanes	123/65	5,778,848	7/1998	Takahashi et al.	123/196 W
4,606,304	8/1986	Kruger	123/90.27	5,960,760 *	10/1999	Wang et al.	123/188.8
4,641,546	2/1987	Mettler	74/598	5,988,135 *	11/1999	Moormann et al.	123/195 HC
4,727,834	3/1988	Isaka	123/196	B1 4,570,584	2/1986	Uetsuji	123/179
4,766,859	8/1988	Mijaki	123/196				

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 7







FIG. 4








FIG. 9




FIG. 10




FIG. 11A

FIG. 11 B

OVERHEAD CAM ENGINE WITH CAST-IN VALVE SEATS

This is a division of application Ser. No. 09/286,636, filed Apr. 2, 1999 U.S. Pat. No. 6,032,635, which is a continuation of application Ser. No. 09/047,246 U.S. Pat. No. 5,979,392, filed Mar. 24, 1998, which is a divisional of application Ser. No. 08/673,100 U.S. Pat. No. 5,755,194, filed Jul. 1, 1996.

BACKGROUND OF THE INVENTION

The present invention pertains to a portable engine, and, in particular, to a single cylinder internal combustion engine of the size and type adapted for use in power equipment such as that used in lawn and garden, general utility and snow removal operations. Such equipment includes but is not limited to lawnmowers, snow throwers, generators, string trimmers, leaf blowers, ice augers, earth movers, etc.

A variety of portable engines which are relatively lightweight have been employed with outdoor or lawn and garden power equipment such as lawnmowers, string trimmers and the like. While both four cycle and two cycle engine designs have previously been utilized, four cycle engines have generally emerged as the preferred design from the standpoint of reducing exhaust and noise emissions. In particular, recent legislation has reduced allowable exhaust emission levels to a point where the engine must be carefully designed to comply with promulgated emission levels, and four cycle engines typically burn cleaner than two cycle engines.

One shortcoming of some commercially available four cycle engines that undesirably leads to higher emissions relates to their propensity to distort in shape. As the engine heats up during usage, the thermal expansion of the engine cylinder block components may produce bore distortions which allow leakage, such as lubricating oil, to pass the piston rings and pollute the engine exhaust. In particular, due to weight and space restrictions inherent in the utilization of these portable engines, and in order to accommodate other mechanical workings of the engines such as drive components for an overhead camshaft, the cylinder bore wall thickness may vary markedly around the bore perimeter. In addition, the walls may be less rigid than optimal because a thin inner wall must be provided to separate multiple internal chambers. In addition, reinforcing ribbing may be withheld due to spacing requirements. These wall thickness variations and lack of rigidity may result in a non-uniform expansion or distorting of the cylinder bore during combustion pressure and thermal cycling, and consequently an unclean engine combustion may occur. A further consequence of such distortion producing leakage is to form oil-based deposits in the combustion chamber. It is well known that these deposits are an important source of the emission of volatile organic compounds, a critical constituent in the control of exhaust emissions. Build-up of these deposits over time is the main contributor to the deterioration of the control of exhaust emissions over the useful life of an engine.

Another potential source of cylinder bore distortion stems from the use of a separate head and cylinder. When a cylinder head is fastened to the cylinder block, the point loading around the cylinder bore which occurs with head bolt torquing may create sufficient bore distortion to compromise the seal with the piston. The head gasket normally introduced between the cylinder and head creates additional bore distortion concerns. For example, because the head gasket serves as a heat transfer barrier and thereby does not uniformly distribute the heat energy over the cooling surfaces of the engine, distortion potential of the cylinder bore associated with thermal expansion may be exacerbated.

Another shortcoming of some existing single cylinder engines relates to their lubrication system. Many engines depend on a continual splashing of the lubricant collected in the sump to lubricate the moving engine components. This splashing technique is not entirely satisfactory as it tends to be less reliable in thoroughness than pressurized lubrication. Further, because splash-type lubrication demands that the engine remain in a designed-for orientation to ensure the oil splashes extend into the collected lubricant, the orientations at which the engine can operate may be limited, thereby hindering engine applications. In other systems, a pump immersed in the lubricant collected in the crankcase sump distributes that lubricant around the engine. In addition to having a limited range of engine orientations at which a given pump will function, this configuration has several disadvantages. For example, a separate pump is required which may increase the engine weight, engine cost and be inconvenient to access for servicing. In addition, the amount of oil is limited by the crankcase volume. Still other engines which use a dry sump lubrication system require an additional pump mechanism to pump the sump contents to a reservoir, and this additional pump adds undesirable weight and cost.

The need for flywheels introduces other problems in portable engines. Due to space constraints, flywheels are typically mounted on the crankshaft at a position external of the engine housing and in a cantilevered fashion. To support this cantilevered flywheel mass without failure, the crankshaft must be formed with a stronger shaft than would be required without an external flywheel. Regardless of whether this stronger shaft is obtained by using a stronger material or by providing a larger diameter shaft, the overall weight of the engine is likely to be increased, and the ease of portability of the engine is thereby diminished. In addition, flywheels are frequently formed separately from the crankshaft and then rotatably fixed together via keying. Unfortunately, during aggressive or emergency stopping which can occur by accident or by use of braking devices, the inertia of the flywheel can lead to breakage of the key between the crankshaft and the flywheel, which renders the engine nonoperational.

Thus, it is desirable to provide a small internal combustion engine which overcomes these and other disadvantages of prior art engines.

SUMMARY OF THE INVENTION

The present invention provides a single cylinder, four cycle overhead cam engine designed to satisfy existing emission standards while still providing a lightweight construction convenient for applications such as lawnmowers and handheld devices. The uniform wall thickness and reinforcing ribs incorporated into the engine cylinder block reduces bore distortions which precipitate an unclean operation. The dry sump lubrication system employed eliminates the need for an extra pump, which would undesirably add weight to the engine, to lift oil used to lubricate the engine parts back to a reservoir for recirculation. This unique means of providing "free" lift pumps saves both weight and cost. By mounting the engine flywheels internally of the engine housing and introducing a lightweight fan on the crankshaft externally of the housing, the inventive engine can be formed with a lighter crankshaft but still be provided with a cooling air flow over the engine housing.

The invention, in one form thereof, is a single cylinder, four stroke cycle, overhead cam engine having an engine block that includes an integrally formed cylinder and cylinder head and having a crankshaft cavity and a crankcase cavity, an interconnected crankshaft, connecting rod and piston disposed in the crankcase cavity, and a camshaft and belt assembly disposed in said camshaft cavity.

A pair of valve stem bores extend through the block between the camshaft and crankcase cavities, the valve assembly including valve stems disposed in the stem bores. There are no further internal passages in the block extending between the camshaft and crankcase cavities. Along the axial segment of the cylinder wall in which the piston reciprocates, the wall has a substantially uniform thickness around substantially all of the wall circumference. A pair of valve seats are cast in the cylinder block and are separate from the head.

One advantage of the engine of the present invention is that the substantially uniform wall thickness of the cylinder reduces the possibility of bore distortion likely to cause undesirable emissions.

Another advantage of the present invention is that cooling fins completely encircling the cylinder increase the rigidity of the cylinder and thereby reduce the possibility of bore distortion.

Another advantage of the present invention is that the integral cylinder and cylinder head eliminates the need for a head gasket as well as elimination of distortion producing fasteners between the cylinder head and cylinder block.

An advantage of the present invention is that the overhead valve seat can be cast in place during cylinder block casting, thereby eliminating the need to machine the cylinder head for receipt of the valve seat. This reduces cost as well as eliminating a common reliability problem caused by pressed-in seats falling out during operation.

BRIEF DESCRIPTION OF THE DRAWINGS

The above mentioned and other advantages and objects of this invention, and the manner of attaining them, will become more apparent and the invention itself will be better understood by reference to the following description of embodiments of the invention taken in conjunction with the accompanying drawings, wherein:

FIG. 1 is a diagrammatic vertical view in partial cross-section of an internal combustion engine configured according to the principles of the present invention;

FIG. 2 is a diagrammatic plan view of the engine of FIG. 1, wherein portions have been removed to better illustrate the interconnection of the camshaft and crankshaft externally of the cylinder block via the timing belt;

FIG. 3 is an exploded view of selected portions of the engine of FIG. 1, namely the cam cover, cylinder block, crankcase cover, camshaft, crankshaft, and timing belt;

FIG. 4 is a cross-sectional view, taken along line 4—4 of FIG. 1, showing the generally uniform wall thickness of the cylinder;

FIG. 5 is a perspective view of the one-piece camshaft of the engine of FIG. 1;

FIG. 6 is an abstract perspective view of one embodiment of a crankshaft in a disassembled condition;

FIG. 7 is a perspective view of the crankshaft mounted fan of the engine of FIG. 1;

FIG. 8 is an enlarged view of that portion of the lubrication system shown in FIG. 1 utilized to lubricate the camshaft region of the engine;

FIG. 9 is an enlarged view of that portion of the lubrication system shown in FIG. 1 utilized to lubricate the crankshaft region of the engine;

FIG. 10 is a diagrammatic view of the overall configuration and operation of one embodiment of the dry sump, pressurized lubrication system of the present invention; and

FIGS. 11A and 11B are enlarged diagrammatic views of the valve assemblies and the driving camshaft at two sequential stages of operation during which the alternating

reciprocating motion of the valve assemblies pumps the oil introduced around the valve assemblies back to the external oil reservoir.

Corresponding reference characters indicate corresponding parts throughout the several views. Although the drawings represent embodiments of the invention, the drawings are not necessarily to scale and certain features may be exaggerated in order to better illustrate and explain the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

The embodiments disclosed below are not intended to be exhaustive or limit the invention to the precise forms disclosed in the following detailed description.

Referring to FIG. 1, there is diagrammatically shown a vertical crankshaft type internal combustion engine, generally designated 20, configured in accordance with the present invention. While the shown vertical crankshaft orientation finds beneficial application in a variety of devices including lawnmowers, engine 20 could be otherwise arranged and oriented, for example with a horizontally oriented crankshaft or any angle inbetween, within the scope of the invention.

As shown in FIG. 1, and with additional reference to the perspective view of FIG. 3, the housing of engine 20 is formed in part by a cylinder block including a central cylinder 22 integrally formed with both cylinder head 24 and an upper crankcase skirt 26. The cylinder block is a one-piece die casting which is cast from a lightweight material, such as aluminum, and then machined to a final shape. The engine housing also includes die cast cam cover 28 and crankcase cover 30 respectively secured to cylinder head 24 and crankcase skirt 26 with suitable fasteners such as bolts (not shown). Cylinder head 24 and cam cover 28 include cooperating journal bearings 32, 33, 34 and 35 upon which an overhead camshaft, generally designated 40, is rotatably supported. At their interface, crankcase skirt 26 and crankcase cover 30 similarly include cooperating journal bearings 36, 37 and 38, 39 for the crankshaft, generally designated 42. Journal bearings 32—39 may be integrally formed with their respective engine housings as shown, or could be otherwise provided within the scope of the invention.

Cylinder 22 is provided with a cylindrical axial bore 44 in which a die cast elliptical barrel-faced piston 46 with associated rings translates in a reciprocating fashion during operation. The volume within bore 44 between piston 46 and cylinder head 24 serves as a combustion chamber for engine 20. Along at least the axial segment of the cylinder bore 44 in which piston 46 slides during reciprocating strokes, cylinder 22 is substantially symmetrical about the axis of the piston stroke. This symmetry advantageously results in a more uniform thermal expansion of cylinder 22 in the radial direction during use that reduces cylinder bore distortion. For example, as shown in FIG. 4, which is a transverse cross-section taken along line 4—4 of FIG. 1, cylinder 22 is formed of a single, generally ring-shaped wall 48 having an inner radial periphery 50 defining bore 44. The outer radial periphery 52 of wall 48 is exposed to allow passing air to draw off heat generated during combustion within bore 44. Except for two radially projecting bosses 54, 55 spaced 180° apart and through which pass symmetrical axially-extending lubrication conduits 56, 57 drilled therethrough, wall 48 is exactly ring-shaped. Wall 48 has a substantially uniform thickness in the range of 0.180" to 0.250", and preferably a thickness of about 0.180". As best shown in FIG. 4, circumscribing cylinder 22 and radially projecting therefrom are a series of axially spaced, annular cooling fins 59. Fins 59 are uniformly shaped along the length of cylinder 22. In addition

to providing an increased surface area for dissipating heat, cooling fins **59** act as stiffening ribs for cylinder **22** that add rigidity which further hinders bore distortion.

With direction in reference to the stroke of piston **46** relative to crankshaft **42**, at the top of cylinder bore **44** is a one-piece valve seat **61** provided within cylinder head **24**. Valve seat **61** seats the valve heads **64**, **65** of exhaust and inlet poppet valve assemblies **67**, **68**. Valve seat **61** is a net shape insert, preferably preformed from a powdered metal composition such as Zenith sintered product no. F0008-30, which is cast in cylinder head **24**. In particular, after valve seat **61** is inserted into the cylinder block die, the die is closed and the casting of the block occurs. Raised plateau sections **62** that laterally and upwardly project from opposite side edges of valve seat **61** permit the molten aluminum injected into the closed die to mold around the raised sections **62** to maintain valve seat **61** in position. It will be recognized that no machining is required to insert valve seat **61** into the cylinder block with this cast-in insertion technique. Alternately shaped and arranged modules, including recesses provided within valve seat **61**, that provide similar securing functions as raised plateau sections **62** could naturally be substituted within the scope of the invention.

Valve assemblies **67**, **68**, which control flow communication between the combustion chamber **44** and the inlet port **70** (See FIG. 3) and the exhaust port (not shown) in the cylinder block, or vice versa, may be of traditional design and are selectively engaged during the four stroke engine cycle by overhead camshaft **40**. Suitable seals (not shown) prevent lubricant introduced within the camshaft cavity region from reaching bore **44**. As further shown in FIG. 5, camshaft **40** includes a cam sprocket **72** such as a notched pulley at one axial end, a gerotor pump inner rotor **74** with pilot **75** at the opposite axial end, intermediate journal sections **76**, **77** that rotate within bearings **32**–**35**, and cam lobes **79**, **80** that directly actuate separate valve assemblies **67**, **68**. Camshaft **40** is preferably formed in one-piece from a lightweight thermoset or thermoplastic material, such as Fiberite FM-4017 F. This plastic material tends to produce less noise during engagement with valve assemblies **67**, **68** and bearings **32**–**35** than do standard metal materials. This material further allows ready provision of precisely designed shapes requiring little or no machining while achieving a low weight. Alternative camshaft constructions, including an assembly of component parts made from various materials, may also be employed.

Aligned parallel to camshaft **40** is crankshaft **42**, which is diagrammatically shown in FIG. 1. Crankshaft **42** is formed from cast ferrous material such as ductile iron and includes a lower shaft portion including a journal section **83** and a stub shaft **84** which outwardly extends from the engine housing for power take off to drive, for example, a lawnmower blade. The upper shaft portion of crankshaft **42** includes journal section **86**, a shaft segment **87**, and an upper stub shaft **88** (see FIG. 3). A sintered metal drive sprocket **90** such as a pulley with a notched outer periphery is axially inserted over shaft segment **87** and is attached for rotation therewith via a tapered key (not shown). Between bearing journals **83**, **86** and housed within the crankcase cavity **91** defined by crankcase cover **30** and crankcase skirt **26**, crankshaft **42** includes a pair of counterweight/flywheel members **94**, **95**. Members **94**, **95** are preferably integrally formed with journal sections **83**, **86**, respectively, and are interconnected by a spanning crank pin **93**. A two-piece extruded or cast connecting rod **92** is pivotally attached to piston **46** with a wrist pin (not shown) and is rotatably supported on crank pin **93**. In an alternative embodiment the connecting rod may be of one piece construction. The wrist pin can be secured with conventional retainers or alternatively with plastic inserts at either end of the axially floating

wrist pin which engage the cylinder bore wall and the opposite ends of the wrist pin.

As best shown in FIG. 3, counterweight/flywheel members **94**, **95** include disc-shaped flywheel portions **97**, **98** axially centered on crankshaft **42**. Flywheel portions **97**, **98** function as a conventional flywheel to provide all the rotational inertia to crankshaft **42** necessary to even out crankshaft rotation during the four cycle operation and to maintain crankshaft rotation during the piston strokes other than the power stroke. Counterweight/flywheel members **94**, **95** further include counterweight portions **99**, **100** at the same axial locations along crankshaft **42** as flywheel portions **97**, **98**. While in the shown configuration part of the flywheel portions **97**, **98** and counterweight portions **99**, **100** are merged together, the portions could have an alternative arrangement, such as an axially stacked arrangement within cavity **91**. The placement of flywheel portions **97**, **98** within cavity **91** and in close proximity to the journal bearings **36**–**39** avoids the use of a large cantilevered mass outside the engine housing which cannot be perfectly balanced and thus creates unwanted torsional forces on the crankshaft. In addition, bending and shear stresses are also imparted to the crankshaft.

As represented in the abstract perspective view of FIG. 6, crankshaft **42** can be fashioned by forming counterweight/flywheel members **94**, **95** integral with the upper and lower shaft portions respectively. Crankshaft **42** is completed by providing a crank pin **93** having cylindrical plugs **93a**, **93b** insertable into cooperatively shaped recesses **101**, **102** provided in members **94**, **95**. An alternative to the shown configuration of a stepped crank pin would be a straight pin.

Referring again to FIG. 1, drive sprocket **90** and cam sprocket **72** are preferably interconnected by an endless loop driver, such as a chain or timing belt, mounted externally of the engine housing. Timing belt **105** shown effects the transmission of rotational motion from crankshaft **42** to camshaft **40** and achieves the timed relation therebetween necessary for proper engine operation. Flexible timing belt **105**, which includes notches on its inner or outer surface oriented perpendicular to the direction of belt travel, also passes over idler pulley **106**, which is abstractly shown in FIG. 2. Idler pulley **106** is a non-spring loaded, adjustable sealed ball bearing mounted on an eccentric, but may also be of other conventional constructions, including spring loaded for automatic adjustment. A governor (not shown) of a suitable construction may be axially mounted on idler pulley **106** or cam sprocket **72** to regulate the engine speed. By mounting a governor at such a location, the governor can be positioned in close proximity to the carburetor, and also need not be associated with leak-prone sealed rods projecting from the crankcase. The governor may also be of a commonly known air vane type.

Mounted to upper stub shaft **88** is a lightweight centrifugal-type fan **108** utilized to force cooling air over the housing of engine **20**. Fan **108** may be constructed with minimal mass as it is not intended to provide the rotational inertia already provided by flywheel portions **97**, **98**. As a result, the moment produced on the crankshaft is relatively minor. As further shown in the perspective view of FIG. 7, fan **108** includes a disc-shaped body **109** molded from thermoset or UV modified thermoplastic with blades **111** for air circulation. Body **109** includes a raised spoke **113** having an outer radial periphery into which ignition magnets **115**, **116** are molded. Magnets **115**, **116** cooperate with engine ignition system **128** mounted to the engine housing **22** to generate sparking within the combustion chamber that initiates internal combustion. Fan body **109** further includes counterweight **118** which balances the weight of magnets **115**, **116** and spoke **113**, and counterweight **118** may include a metal insert molded therein. Molded into the center of

body **109** is a relatively sturdy, multi-lobed aluminum insert **120** which functions in the shown embodiment as both a mounting hub for fan **108** and a starter cup. In particular, mounting hub/starter cup insert **120** includes axial bore **121** which receives stub shaft **88** and is attached for rotation therewith via a tapered key (not shown). In outer surface **123**, mounting hub/starter cup **120** includes recesses **124** structured for engagement with the pawls (not shown) of recoil starter **129** which descend when starter **129** is utilized. Radial lobes **125**, **126** shown in FIG. 7 define angular gaps therebetween filled with molded plastic to prevent insert **120** from separating from fan body **109** during starting. As the precise construction of ignition system **128** and recoil starter **129** are not material to the present invention and can be one of a variety of well known types, further explanation is not provided herein. In situations where an electric starter accompanies or replaces recoil starter **129**, a grooved ring (not shown) preferably integrally formed in the bottom surface of fan body **109** may be utilized for engaging a starter pinion. Although plastic is preferred from a weight standpoint, other materials including aluminum may be used to form fan body **109**. In an alternative embodiment (not shown) using commonly known alternative ignition means, the fan **108** may be of a simpler construction with additional cooling blades replacing spoke **113**, magnets **115**, **116** and counterweight **118**. This simpler, lighter, more efficient fan would be fastened to a stub shaft (not shown) with simpler fasteners, such as integrally molded clips or simple rivets. In this alternative the recoil starter hub may be separately attached or integrally molded to the fan.

Referring again to FIG. 1, engine **20** is preferably kept lubricated with a dry sump pressurized lubrication system that allows for multi-positional operation. The system includes an oil reservoir **135** mounted externally of and to the engine housing. Although shown at an elevation below the engine housing, reservoir **135** could be positioned above the balance of engine **20** without compromising the lubrication system operation. Oil reservoir **135** may be formed of a durable transparent plastic material such as nylon 6.6 thermoplastic, and with appropriate indicia to allow a visual determination of oil level. A first oil return conduit **138** formed of flexible tubing with a 0.125"-0.500" internal diameter extends between a crankcase outlet **140**, namely a housing bore opening into crankcase cavity **91**, and a reservoir inlet **141** opening into oil reservoir **135** above the collected lubricant. A second similarly constructed oil return conduit **143** with a 0.125"-0.500" internal diameter communicates with an outlet **145** and reservoir inlet **147**. Outlet **145** is a bore, drilled through cylinder head **24**, which opens into the head cavity **180**, shown in FIG. 8, in which the biasing components of valve assembly **67** are housed. Return conduits **138** and **143** circulate the oil delivered to crankshaft **42** and overhead camshaft **40** respectively as described further below.

An abstractly shown breather/filler cap **150** securely fits over an inlet **152** through which replacement oil can be poured into reservoir **135**. Breather **150** is a conventional filter-type assembly that includes check valve **149** allows one-way air flow out of reservoir **135**, while preventing oil passage. Breather **150** includes an air exhaust port **151** which may be connected in flow communication with air intake port **70** on the carburetor air filter (not shown) or with the carburetor (not shown). The particular construction of breather **150** is not material to the invention and may be one of many suitable designs known in the art. Rather than being formed into the inlet cap, breather **150** could instead be integrated into a wall of reservoir **135** removed from inlet **152**. Oil pick-up **155** includes an oil filter submerged within the volume of oil maintained in reservoir **135** and connects to a 0.125"-0.500" internal diameter supply conduit **159** leading to the lubrication system pump mechanism used to

pressurize the oil introduced into engine **20**. Oil pick-up **155** may be constructed of flexible tubing with a weighted inlet end to cause it to remain submerged within the reservoir fluid when the engine is tilted from a standard orientation. Check valve **157** is of a standard construction and is located within conduit **159** to permit one way flow of oil from reservoir **135**. Oil reservoir **135** may also be mounted directly to oil pump **161** in certain orientations (not shown) which precludes the need for supply conduit **159** and check valve **157**.

The configuration of the pressurized lubrication system will be further explained with reference to FIGS. 8 and 9, which respectively show enlarged views of the engine parts used to lubricate camshaft **40** and crankshaft **42**. The preferred pump mechanism fed by supply conduit **159** is a gerotor type pump which operates in a known manner. In the shown embodiment, the pump is generally designated **161** and utilizes the rotation of camshaft **40** to perform the pumping operations. Alternate types of pumps, including those which are separate from the remaining working components of engine **20**, may be used to drive the lubrication system within the scope of the invention. The pump **161** includes a thermoset plastic cover plate **162**, attached to the engine housing with bolts and an O-ring seal (not shown). A pressed metal or plastic outer rotor **165**, which is retained by plate **162** and cooperatively shaped with inner rotor **74** of camshaft **40** to effect fluid pressurization is also included. Camshaft hub **75** is provided with bearing surfaces **166** in cover plate **162**. Pump inlet port **163** communicates with the downstream end of oil supply conduit **159**. Pressurized oil that is outlet at port **164** is forced into bore **167** within cam cover **28**. A pressure relief valve **168** returns high pressure oil from port **164** to inlet port **163** to prevent excessive pressure. Cross bores **169**, **170** distribute oil within bore **167** to annular grooves **172**, **173** which are provided in bearings **32**, **34** and **33**, **35** respectively and which ring journals **76**, **77**. At their upstream ends, oil conduits **56**, **57** open into grooves **172**, **173** to allow oil communication therebetween. Conduits **56**, **57** extend through cylinder head **24** and cylinder **22** toward crankshaft **42**. Conduits **56**, **57** are shown being parallel to bore **44**, and consequently bosses **54**, **55** radially project a uniform distance along the axial length of cylinder **22**.

Referring now to FIG. 9, at its downstream end, oil conduit **56** terminates at bearing surface **36** to effect lubrication of crankshaft journal **83**. For the vertical type crankshaft arrangement shown, journal **83** is further lubricated by the quantity of oil which falls to the bottom of cavity **91**. Oil conduit **57** terminates at annular groove **175** formed in journal bearings **37**, **39**. Lubrication bore **177** drilled through counterweight/flywheel member **95** and journal **86** extends between annular groove **175** and the bearing surface between connecting rod **92** and crank pin **93**. Annular groove **175** continuously communicates with bore **177** during crankshaft **42** rotation to provide uninterrupted pressurized lubrication for the bearing surface of connecting rod **92** throughout operation. Although not shown, an axial bore extending between the connecting rod bearing surface and the wrist pin for piston **46** may be provided to provide pressure lubrication for the wrist pin.

The structure of the lubrication system of the present invention will be further understood in view of the following general explanation of its operation. This explanation refers to FIG. 10, which schematically shows an alternate orientation of the invention shown in FIG. 1 in that the crankshaft is horizontally disposed. It will be appreciated that still further modifications to the lubrication system can be performed within the scope of the invention. Lubricant **136** such as oil within external reservoir **135** is drawn through supply conduit **159** by pump **161** and introduced at high

pressure into camshaft **40**. Cross bores in camshaft **40** direct the oil to the journal bearings, such as bearings **32**, **33** shown. The high oil pressure causes an overflow portion of the oil from both journal bearings to migrate axially inwardly and thereby lubricate the camshaft lobes **79**, **80**. Due to camshaft **40** rotation, the lubricating oil is also slung off camshaft **40** to splash lubricate the remainder of the surfaces and components within the cavity between cam cover **28** and cylinder head **24**, including the portions of the valve assemblies represented at **67**, **68** exposed within cavities **180**, **181**.

The remainder of the oil introduced at the journal bearings within grooves **172**, **173** (See FIG. **8**) is forced under positive pressure axially through conduits **56**, **57** toward crankshaft **42**. The oil is maintained cool during this travel time by the transfer of heat to the bosses **54**, **55** which are exposed to passing cooling air. At its downstream end, conduit **56** includes an opening through which the conveyed oil is outlet to pressure lubricate shaft journal **83**. Oil from conduit **57** outlets to lubricate shaft journal **86** as well as to fill annular groove **175** (See FIG. **9**), and lubrication bore **177** routes pressurized oil from groove **175** to lubricate the connecting rod bearing surfaces. The overflow oil displaced from the pressure lubricated bearing surfaces by the arrival of additional oil is slung off crankshaft **42** to splash lubricate the moving components within crankcase cavity **91**, such as piston **46**, the piston rings, the wrist pin, the wrist pin bearings and the cylinder wall.

The circulation of the oil within engine **20** back to the external reservoir **135** is effected by positive displacement and/or pressure fluctuations caused by the reciprocating motion of the valve assemblies and piston. With additional reference to FIGS. **11A** and **11B**, which are enlarged, abstract views of the valve assemblies and the camshaft at sequential stages of engine operation, the oil which lubricates camshaft **40** and its associated valve assemblies **67**, **68** accumulates in cavities **180**, **181** provided in cylinder head **24**. The spring-biased cam followers **183**, **184**, which in the shown embodiment are bucket-shaped tappets but could be otherwise configured, as well as the top of their associated valve stems **186**, **187** reside within cavities **180**, **181**. Cam followers **183**, **184** are tightly toleranced to the dimensions of cavities **180**, **181** to act as pistons to facilitate the following pumping operations. As camshaft **40** rotates, as shown in FIG. **11A**, cam lobe **80** drives bucket tappet **184** downwardly, thereby reducing the effective volume of cavity **181** and creating a high positive pressure therein. This positive pressure forces the oil accumulated within cavity **181** to pass through slot **189** formed in valve head **24** between cavities **181**, **180**. Rather than an open-ended slot proximate camshaft **40**, a bore or aperture could be substituted within the portion of cylinder head **24** between the cavities. As shown in FIG. **11B**, as camshaft **40** continues to rotate cam follower **184** returns to its unengaged position and cam lobe **79** subsequently drives cam follower **183** downward to pressurize cavity **180**. Outlet bore **145** in cylinder head **24** is provided with a larger cross-sectional area than slot **189** such that the path of least resistance for the oil accumulated within pressurized cavity **180** is through bore **145**. Consequently, the positive pressure created within valve cavity **180** by the piston-like pumping action of valve assembly **67** forces the oil toward return conduit **143**.

The oil in return conduit **143** is propelled in a step-wise fashion therethrough to oil reservoir **135**. In particular, when a quantity of oil and air within valve assembly cavity **180** is forced into supply conduit **143**, oil and air within the segment of conduit tubing adjacent inlet **147** is displaced and empties in a spurt into oil reservoir **135**. The oil pumped into return conduit **143** for a particular valve assembly pumping stroke empties into oil reservoir **135** only after

multiple additional pumping strokes have occurred, and the multiple is dependent in part upon the length of return conduit **143**. Breather **150** allows air to be exhausted from within reservoir **135** such that a high pressure does not build up within reservoir **135** which would prevent oil pumping. Oil does not return into cavity **180** on the upstroke of valve assembly **67** because inlet **147** is above the oil level thus allowing only air to be drawn back out of reservoir **135**. Thus, step-wise return of the oil to the oil return conduit and thus to the oil reservoir is effected by the positive pressure created by the pumping action of the valve assemblies.

Oil is returned from crankcase cavity **91** by exploiting the pumping action of piston **46**. As piston **46** is driven downwardly within cylinder bore **44**, the pressure in crankcase cavity **91** increases. This positive pressure forces a quantity of the lubricating oil and entrapped air within cavity **91** completely through oil return conduit **138** and into oil reservoir **135**. Breather **150** achieves air venting of the volume of air which is blown through tubing **138** to prevent a pressure build-up. As piston **46** is driven upwardly within bore **44** to create a vacuum within crankcase cavity **91**, air flows through breather **150**, through the oil return conduit **138**, and into crankcase cavity **91**. Because port **141** is above the fluid level, the only oil reintroduced through conduit **138** into cavity **91** during the piston upstroke is any small quantity of oil in conduit **138** which failed to reach reservoir **135** during the piston downstroke.

While this invention has been described as having a preferred design, the present invention may be further modified within the spirit and scope of this disclosure. This application is therefore intended to cover any variations, uses, or adaptations of the invention using its general principles. Further, this application is intended to cover such departures from the present disclosure as come within known or customary practice in the art to which this invention pertains.

What is claimed is:

1. An overhead camshaft internal combustion engine comprising:

- an engine housing including a cylinder block casting having an integrally formed cylinder and cylinder head, said cylinder comprising an internal bore;
- a crankshaft disposed within said engine housing and extending externally thereof;
- a piston connected to said crankshaft and mounted for reciprocation within said cylinder internal bore;
- at least one overhead valve for regulating inlet to and exhaust from said cylinder internal bore;
- a camshaft disposed in said head and driven by said crankshaft, said camshaft comprising at least one cam for operating said at least one overhead valve; and
- a cast-in valve seat for said at least one overhead valve formed separately from said cylinder block casting and captured in said cylinder head during cylinder block casting formation.

2. The internal combustion engine of claim **1** wherein said cast-in valve seat comprises a powdered metal construction.

3. The internal combustion engine of claim **1** further comprising a dry sump lubrication system, said lubrication system including a lubricant reservoir external of said engine housing, means including a pump for supplying lubricant from said reservoir to said camshaft, and means for returning lubricant used to lubricate said camshaft from within said engine housing back to said external reservoir.

4. The internal combustion engine of claim **1** wherein said camshaft includes a camshaft sprocket located external of said engine housing, said crankshaft includes a drive sprocket located external of said engine housing, said engine

11

comprises an endless loop drive member interconnecting said drive sprocket and said camshaft sprocket for transmitting rotational motion therebetween, and wherein said drive member is located externally of said engine housing.

5 **5.** The internal combustion engine of claim **1** further comprising first and second lubricant passages extending through said cylinder head and cylinder, said first passage including an upstream end for inletting lubricant disposed at a first camshaft bearing, said first passage including a downstream end for outletting lubricant to a first crankshaft bearing, a second passage including an upstream end for

12

inletting lubricant disposed at a second camshaft bearing, and said second passage including a downstream end for outletting lubricant to a second crankshaft bearing.

6. The internal combustion engine of claim **5** wherein said first and second lubricant passages extend through bosses provided in said cylinder that radially protrude from a cylindrical periphery of said cylinder, said bosses externally exposed to permit cooling of lubricant passing therethrough.

* * * * *