



US006242741B1

(12) **United States Patent**  
**Miller et al.**

(10) **Patent No.: US 6,242,741 B1**  
(45) **Date of Patent: Jun. 5, 2001**

(54) **RADIATION DETECTION APPARATUS**

4,932,412 6/1990 Goldenberg .  
4,959,547 9/1990 Carroll et al. .

(75) Inventors: **Eric Miller**, Fairfield; **Richard Scott Rader**, Guilford; **Timothy N. Wells**, Ridgefield, all of CT (US); **Paul Stoppel**, Wayland, MA (US)

(List continued on next page.)

**FOREIGN PATENT DOCUMENTS**

2 117 900 10/1983 (GB) .

(73) Assignee: **United States Surgical Corporation**, Norwalk, CT (US)

**OTHER PUBLICATIONS**

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

Richard D. Baxter, "Miniature Hybrid Preamplifier for CdTe Detectors", pp. 493-497, IEEE Transactions on Nuclear Science, vol. NS-23, No. 1, Feb. 1976.

C.L. Colton and J.G. Hardy, "Evaluation of a Sterilizable Radiation Probe as an Aid to the Surgical Treatment of Osteoid-Osteoma", pp. 1019-1021, J. Bone and Joint Surg., vol. 65-A No. 7, Sep. 1983.

E.P. Szypryt, J.G. Hardy, & C.L. Colton, "An Improved Technique Of Intra-Operative Bone Scanning", pp. 643-646, J. Bone and Joint Surg., vol. 68-B, No. 4, Aug. 1986.

(21) Appl. No.: **09/177,636**

(22) Filed: **Oct. 23, 1998**

(51) **Int. Cl.**<sup>7</sup> ..... **A61B 6/00**

(52) **U.S. Cl.** ..... **250/363.02; 250/363.1; 600/436**

(58) **Field of Search** ..... **250/363.02, 363.1; 600/436**

(List continued on next page.)

(56) **References Cited**

**U.S. PATENT DOCUMENTS**


3,427,454	2/1969	Webb .
3,598,109	8/1971	Kobayashi et al. .
3,665,916	5/1972	Kobayashi et al. .
3,669,095	6/1972	Kobayashi et al. .
3,670,719	6/1972	Kobayashi et al. .
3,863,623	2/1975	Trueblood et al. .
4,015,592	4/1977	Bradley-Moore .
4,092,980	6/1978	Frank et al. .
4,243,884	1/1981	Avera, Jr. .
4,255,659	3/1981	Kaufman et al. .
4,301,367	11/1981	Hsu .
4,338,521	7/1982	Shaw et al. .
4,545,375	10/1985	Cline .
4,649,276	3/1987	Suzuki .
4,682,604	7/1987	Fymat et al. .
4,688,569	8/1987	Rabinowitz .
4,782,840	11/1988	Martin, Jr. et al. .
4,801,803	1/1989	Denen et al. .
4,889,991	12/1989	Ramsey et al. .
4,893,013	1/1990	Denen et al. .

Primary Examiner—Constantine Hannaher

(57) **ABSTRACT**

A radiation detection apparatus includes a hand-held probe with a switch assembly removably mounted thereon. The switch assembly having first and second switches, one to initiate transmission of electrical signals representing scintillations detected over a set time period to a remotely located control unit for counting and averaging, and the other to direct the control unit to download and preferably record the counted and averaged scintillation values for further use. The switch assembly has an insulating member for electrically insulating the switches from the probe, and spaced gripping members that releasably grip the probe. A movable stand is provided preferably with a holder for holding the probe. The probe can have a protective cover thereon with a switch assembly mounted onto the probe over the cover.

**8 Claims, 5 Drawing Sheets**



## U.S. PATENT DOCUMENTS

5,008,546	4/1991	Mazziotta et al. .
5,036,201	7/1991	Carroll et al. .
5,057,690	10/1991	Morgan et al. .
5,070,878	12/1991	Denen .
5,140,040	8/1992	DeBernardis .
5,148,040	9/1992	Wise Jr., et al. .
5,151,598	9/1992	Denen .
5,158,086	10/1992	Brown et al. .
5,166,073	11/1992	Lefkowitz et al. .
5,170,055	12/1992	Carroll et al. .
5,246,005	9/1993	Carroll et al. .
5,304,763	4/1994	Ellman et al. .
5,428,223	6/1995	Jatteau et al. .
5,429,133	7/1995	Thurston et al. .
5,441,050	8/1995	Thurston et al. .
5,456,260	10/1995	Kollias et al. .
5,475,219	12/1995	Olson .
5,495,111	2/1996	Thurston et al. .
5,635,717	6/1997	Popescu .
5,682,888	11/1997	Olson et al. .

## OTHER PUBLICATIONS

Radiation Monitoring Devices, Inc., “*Gamma Guidance System from RMD*”, 2 pages, (a Product Bulletin Published by RMD Inc., in Oct. 1997).

Radiation Monitoring Devices, Inc., “*Nuclear Instruments by RMD*”, 2 pages, (a Product Bulletin Published by RMD Inc., in 1981). NOTE: the month need not be specified as 1981 is much earlier than the US filing date of Oct. 23, 1998.

Radiation Monitoring Devices, Inc., “*Technetium, 14MM Surgical Probe System from RMD*”, 1 page, (a Product Bulletin Published by RMD Inc., in 1996). NOTE: the month need not be specified as 1996 is much earlier than the US filing date of Oct. 23, 1998.

Rik Pijpers et al., “*Sentinel Node Biopsy in Melanoma Patients: Dynamic Lymphoscintigraphy Followed by Intra-operative Gamma Probe and Vital Dye Guidance*.” pp. 788–792, *World J. Surg.*, Oct. 21, 1997. NOTE: The attached copy (pp. 1–13) is of the original article, submitted to the *World J. Surg.*

“Build a Personal Radiation Monitor,” *Popular Electronics*, by John Steidley, Martin Nakashian and Gerald Entine, Jan. 1980, pp. 39–46.

“Use of a Cadmium Telluride Detector in a New Tiny Personal Radiation Chirper” by Michael A. Wolf, C. John Umbarger and Gerald Entine, *IEEE Transactions on Nuclear Science*, vol. NS–26, No. 1, Feb. 1979.


“Radiation Detector Probes for Tumor Localization Using Tumor–Seeking Radioactive Tracers” by J. M. Woolfenden H. B. Barber, *American Journal Roentgenology* article (153:35–39) Dept. of Radiology, University of Arizona, Tucson 85724, Jul. 1989.

“Performance Comparison of Surgical Gamma Probes.” A. van Lingen, et al, from the *Journal of Nuclear Medicine Abstract Book Supplement*, vol. 38, p 208p–209p, May 1997.

“New Product Release, Nuclear Surgical Probe” by Radiation Monitoring Devices, Inc., one page, Jan. 1985.

“A Surgical Imaging Probe for Tumor Detection.” N. E. Hartsough, et al, From the *Journal of Nuclear Medicine*, vol. 30, #5, p 891, May 1989.

Cover page of brochure entitled 83rd annual Clinical Congress with handwriting at the bottom, which indicates that the Radiation Monitoring Device, Inc. (RMD) Gamma Guidance System featured in the RMD booth #501 was shown at the 83rd annual Clinical Congress on Oct. 12–17, 1997.






FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10

**RADIATION DETECTION APPARATUS****BACKGROUND OF THE INVENTION**

## 1. Field of the Invention

The present invention relates to a radiation detection apparatus. More particularly, the present invention relates to an apparatus for detecting, quantizing and mapping radiation emitted from a scintillation fluid having gamma-emitting isotopes. The apparatus is battery operated and has a hand-held probe for detecting radiation, and for transmitting electrical signals that represent the detected radiation to a remote unit to process the signals into information. The hand-held probe is a scintillation detector that has a switch assembly removably mounted on the probe for initiating remotely electrical signals to a control unit.

The switch assembly has preferably two finger-operated triggers. One trigger initiates the count, and the other trigger directs the remote unit to download, and preferably record, the counted scintillations or averaged scintillation values for further use.

## 2. Description of the Prior Art

Procedures for detecting, quantizing and localizing or mapping carcinomas in living beings are known. A radiation-emitting substance is passed through a patient's body. Either a radiation detector device is secured to the patient's body, or a hand-held probe is held adjacent a series of sites surrounding a suspected tumor. One procedure involves injecting a scintillation fluid containing, for example, technetium <sup>99</sup>, in quadrants of the capillary system located about a site to determine whether cancer has spread to the lymphatic system. Since fluid drains from the injected area through the lymphatic system, the scintillation detector allows identification and location of the sentinel node, the first lymph node draining the most scintillation fluid and emitting the highest number of scintillations in the lymphatic drainage path from the tumor.

Heretofore, each radiation detecting, quantizing and mapping apparatus has been connected by hardwire to an electrical receptacle or has a battery that discharges during use. One conventional apparatus has a foot pedal connected to a remote unit to initiate counts. The foot pedal does not activate a downloading of counts, let alone during a preset time period. A second conventional apparatus has a built-in rechargeable battery. This is disadvantageous since an extended time, usually four to six hours, is required to recharge the battery. Since recharging cannot occur during operation of the apparatus, should the battery require recharging during a procedure, the procedure must be stopped.

In addition, the apparatus has a hand-held probe and a remotely located control unit. The probe was merely used for detecting emitted radiation from the patient's body and transmitting electric signals representing the detected radiation to the control unit for processing. The control unit has the controls for controlling various functions including taking counts, setting the time period for taking timed counts, and initiating the taking of counts. These controls had to be activated solely at the control unit. This is disadvantageous because to conduct the counting procedure, the operator must hold and use the hand-held radiation detection probe with one hand. With the other hand, the operator needed to reach the control unit and manipulate the controls. It is difficult to conduct both the detection and control manipulation simultaneously. Also, to do so results in difficulties in taking counts and, perhaps, inaccuracies in the counts. For example, while taking a scintillation count,

the probe must be precisely positioned over a selected site for a set period of time. It is difficult to maintain that precise position while reaching to depress a count start button on the control unit. Movement of the probe during counting can create an inaccurate count. Since counting is repeated at different probe angle positions over the same site and over different body sites, the difficulties and inaccuracies can be compounded. Therefore, it is desired to have an improved radiation detection apparatus that obviates or reduces such difficulties, inaccuracies and inefficiencies.

It is known to employ switches removably mounted on a handpiece. U.S. Pat. No. 5,304,763 discloses two or more finger-operated switches removably mounted to a hand-held electrosurgical device. The switches control the application, e.g., initiation and termination, of electrical energy provided to the device. For example, one switch controls the application of energy to energize an electrode of the device for cutting body tissue. The other switch energizes a suction portion of the device to remove cut tissue from the body.

Heretofore, hand-held radiation detection probes and their cables have had to be sterilized to be re-usable because they become contaminated during use. Sterilizing such hand-held detection devices prior to each use is expensive, time consuming and may require maintaining a larger than necessary inventory of the probes and cables. It is desired to have an apparatus that obviates the need for sterilizing hand-held devices or probes prior to their re-use. It would also be desired to have an apparatus that allows for the use of hand-operated switches mounted on the hand-held device or probe during use, but permits removal from it during sterilization of the device or probe.

**SUMMARY OF THE INVENTION**

It is an object of the present invention to provide an improved radiation detection apparatus that includes a hand-held radiation detection probe with at least one switch removably mounted thereon.

It is another object of the present invention to provide such a radiation detection apparatus in which the one switch has a first trigger or button that remotely enables a counter in a control unit to accumulate electrical signals representing radiation scintillation detected over a set time period, and a second button that remotely directs the control unit to output data regarding the counted scintillations.

It is still another object of the present invention to provide such a radiation detection apparatus that allows the operator to operate a hand-held probe, while simultaneously using the switches mounted on the probe to control a remote control unit.

It is yet another object of the present invention to provide such a radiation detection apparatus in which the control unit is battery operated to provide total mobility of the control unit.

It is a further object of the present invention to provide such a radiation detection apparatus that has a removable, rechargeable battery as its power source.

It is still a further object of the present invention to provide such an improved radiation detection apparatus that enables a hand-held radiation detection probe to be reused without prior sterilization.

It is yet a further object of the present invention to provide such a hand-held radiation detection probe with a cover to protect the probe from contamination during use, and to isolate electrically the switch from the hand-held probe.

It is still yet a further object of the present invention to provide such an improved radiation detection apparatus that is removably mounted on a movable stand.



These and other objects of the present invention are achieved by a radiation detection apparatus comprising: means for counting a scintillation count value; means for outputting a scintillation count value to a utilization device; a hand-held probe including a scintillation detector; means for connecting the probe to the count means; first means removably positioned on the probe for, in a first state, causing the count means to accumulate a scintillation count over a first period, and in a second state, causing the count means to accumulate a scintillation count over a second period, the second period being longer than the first period; and second means removably positioned on the probe for causing, upon activation, the output means to manifest an accumulated scintillation count from the count means.

The radiation detection apparatus can include means for displaying a count value of the count means. The display means responds to activation to the second state of the first means, by displaying a count value accumulated over the second period for a preset time period.

Preferably, activation of the second means is operative, only during the preset time period, to cause the output means to manifest a scintillation count accumulated during the second period from the counter means. Activation of the second means, at times other than during the preset time period, causes activation of any selected other function of the control unit.

The radiation detection apparatus can include a movable stand having a holder for releasably mounting the probe on the stand.

The present invention also includes a hand-held radiation detection probe having a flexible removable protective covering thereover to protect the probe from contamination during storage or use, and permit the probe to be re-used without prior sterilization. Preferably, the covering is a sheath.

The present invention may further include a hand-held radiation detection probe having a switch assembly removably mounted thereon. The switch assembly has at least one switch, an insulating member for electrically insulating said switch from said probe which is a saddle formed by a spaced, opposed pair of cooperative depending gripping members adapted to releasably grip said probe therebetween.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic representation of the radiation detection apparatus of the present invention;

FIG. 2 is a top plan view, with portions broken away, of a preferred embodiment of the probe shown in FIG. 1;

FIG. 3 is a top plan view, with portions broken away, of the probe shown in FIG. 2 without a switch mounted thereon and covered by a sheath;

FIG. 4 is a top plan view, with portions broken away, of the probe shown in FIG. 2 covered by a sheath and having a switch assembly mounted thereon;

FIG. 5 is a top plan view, with portions broken away, of the probe shown in FIG. 2 covered by a drape and with a switch assembly shown optionally mounted thereon;

FIG. 6 is a perspective view of the removable switch assembly that is mounted on the probe shown in FIG. 2;

FIG. 7 is an exploded perspective view of the switch assembly shown in FIG. 6;

FIG. 8 is a front view of the housing of the control unit of the present invention;

FIG. 9 is a front perspective view of a movable stand for mounting the control unit of the radiation detection apparatus of FIG. 1; and

FIG. 10 is a rear perspective view, with portions broken away, of the control unit and stand shown in FIG. 9.

#### DETAILED DESCRIPTION OF THE INVENTION

Referring to the drawings and, in particular, FIG. 1, there is a schematic of a preferred embodiment of the radiation detection apparatus of the present invention, generally represented by reference number 10. Apparatus 10 includes a hand-held radiation detection device or probe 50, and a control unit 100 connected to probe 50 by a suitable connection, such as a flexible cable 12. Probe 50 includes a radiation detector 52, a handle 54, and a shaft 56 that connects detector 52 to handle 54. Detector 52 includes a crystal, such as a cadmium telluride crystal, for detecting radiation, such as gamma protons, emitted from a radiation source in a patient's body. The radiation source is a scintillation fluid preferably containing technetium 99.

Probe 50 converts the detected scintillation radiation into electrical pulses that are amplified and transmitted through cable 12 to control unit 100. Removably mounted to probe 50 is a switch assembly 70. Assembly 70 preferably has two switches 72, 74. Switches 72, 74 are preferably push button switches.

Activation of switch 72 enables a count accumulator module 158, described below, to accumulate a scintillation count over a preset time period, such as ten seconds. Otherwise, scintillation counts are accumulated over succeeding one second periods. The scintillation pulses detected by probe 50 pass from the probe through cable 12 to a pulse shaping circuit 150 where the scintillation pulses are shaped. The shaped pulses are fed to a discriminator 152 which passes pulses that fall within an energy window that has been preset for technetium 99 by an energy window set 154. The pulses passed by discriminator 152 are fed to an audio unit 156 where they are broadcast to aid the probe operator in positioning probe 50.

Pulses from discriminator 152 are also fed to a counter, for example a count accumulator module 158. Module 158 counts the scintillation pulses and averages them, in the normal operational mode, over succeeding one second periods, or over a preset period, such as a ten second period, if selected by the probe operator's activation of switch 72 instead of pressing button 108 on control unit 100. The accumulated and averaged count value is passed from count accumulator module 158 to a display unit 160 that displays the averaged count value for each one second period, or for the preset 10 second period.

Upon activation of switch 74 on probe 50, the accumulated and averaged count value is also passed from module 158 through a download control 162 and output to a terminal, here shown as output terminal 164. Output terminal 164 can be connected to a utilization device, such as a recorder 166. Output terminal 164 may also be connected, directly or remotely, to a computer 168. Computer 168 can be, for example, a personal computer, laptop, or other computing device, for storage and manipulation of the output data.

The electronic signals sent by control unit 100 to computer 168 represents the ten second count frozen and shown on display 160. Signals received by computer 168 will be received by its software which will record the signals, for example, to keep patient records of how control unit 100 was used (settings, duration, etc.). The software can be tailored to individual preferences or to established clinical protocols. However, control unit 100 and probe 50 must be kept

electrically isolated from computer **168**, and the computer must not be able to control, program or otherwise affect the performance of the control unit or the probe. Thus, a unidirectional (control unit **100** to computer **168**) isolated interface, e.g. optical coupler (represented by the heavy dashed line II) is employed should the computer be connected to output terminal **164**.

After a patient has been injected with a radiation emitting substance, for example, a scintillation liquid containing technetium **99**, hand-held probe **50** is held stationary in position over a radiation detection site on the patient's body. A count is taken of the scintillation detected at that site for a given time period. This process is repeated at one or more different sites, or for different angular positions of the probe on the same site, and a comparison is made of the counts obtained at each site. With switch **72** in a deactivated position, scintillations are detected or sampled over a series of first count sampling periods. Each sample period is, for example, preferably of one second duration. The signals or pulses transmitted from probe **50** during each one second period cause count accumulator module **158** to accumulate a scintillation count that is an average of the scintillation pulses over the one second period.

Control unit **100** is set such that activation of switch **72** initiates a ten second count sampling period, followed by a three second freeze period of the average count taken for the ten second period. During the ten second sampling period, module **158** accumulates and averages the scintillation counts taken over the ten second period. The average count is displayed on display **160** for the three second freeze period. During the sampling period, a sampling light (not shown) on control unit **100** will flash. At the end of the sampling period, the sampling light goes off and a single audible beep is emitted. If, during the three second freeze period, switch **74** is activated by the operator, the frozen count is downloaded from module **158** to output terminal **164** which sends the frozen count to a utilization device.

When switch **74** is activated during the three second period, two audible beeps are emitted. If switch **74** is not activated during the freeze period, no downloading of the frozen count occurs. Switch **74** can be activated during or at the end of any one second count sampling period or, as stated above, during the three second freeze period. Thus, activation of switch **74** downloads the ten second count value to output terminal **164**, and an audible signal indicates that the download has occurred. If switch **74** is not activated during the three second freeze period, module **158** returns to its normal mode of accumulating and averaging sampled counts per second and displaying the counts per second on display **160**.

Control unit **100** is powered by a removable, rechargeable battery. The preferred battery is a lead-acid rechargeable battery capable of four hours of continuous operation. When a predetermined set period of time of power battery life remains, such as, for example, fifteen minutes, a warning indicator, such as a light, will flash or indicate the commencement of that set period. Accordingly, the user can simply insert a second battery in the control unit **100** to operate the control unit, and the first battery can simply be recharged when desired.

As shown in FIG. 2, switch assembly **70** is removably mounted on handle **54** of probe **50**. Switch assembly **70** preferably has two finger-operated push button switches **72**, **74**.

Referring to FIG. 3, probe **50** may have a removable protective cover **60** placed thereover. The protective cover

**60** preferably is a sheath that substantially fully encompasses probe **50** to protect it from being soiled or contaminated during storage and use. Sheath **60** permits probe **50** to be re-used without prior sterilization. Sheath **60** has a closed end **62** that covers detector **52**, and an opposite open end **64** that can be at any desired location beyond handle **54**. Preferably, sheath **60** is long enough to the entire length of cable **12**, as shown in FIG. 2.

Sheath **60** can have any suitable size, shape and configuration. Thus, it can fit loosely, tightly or form-fitted or even shrunk onto probe **50**. As shown in FIG. 4, sheath **60** preferably fits sufficiently tightly onto probe **50**, especially about detector **52**, to minimize interference with its function. Sheath **60** preferably also fits tightly about the portion of handle **54** onto which switch assembly **70** is to be mounted, to enable the switch assembly to remain tightly and securely mounted onto the handle. Sheath **60** can be made of any suitable material or materials, and can be single or multiple layered. Preferably, sheath **60** is made from a flexible film or sheet. The preferred material for sheath **60** is a single layer of polyurethane.

Although sheath **60** is the preferred cover, any suitable cover can be employed that permits switch assembly **70** to be effectively mounted onto probe **50**. The sheath **60** is removable and preferably disposable and easily replaceable. Thus, as shown in FIG. 5, a drape **66** of flexible film can be placed over and secured to probe **50**. As shown in FIG. 5, a continuous portion of drape **66** can be placed over detector **52**, tied around shaft **56** by a tie **68**, and gathered and secured about handle **54** or about cable **12** (not shown) by any suitable member, such as by a clip **69**. Switch assembly **70** (dashed line) can be mounted on probe **50** while the switch assembly is covered by drape **66**.

Referring to FIG. 6, switch assembly **70** preferably has a saddle **76** formed by a curved undersurface **78** and a pair of spaced opposed cooperative depending gripping members **80** that are adapted to releasably grip probe **50** (not shown) between them. Gripping members **80** are arcuately shaped and sized to fit tightly about handle **54** of probe **50**. Gripping members **80** are rigid enough to hold probe **50** between them, but resilient enough to allow the switch assembly **70** to be removed from the probe.

As shown in FIG. 7, the preferred switch assembly **70** also has a cover **82**, button switches **72**, **74**, a carrier in the form of a mounting member **84** having saddle **76**, a recessed panel **86**, and an insulating member **88** that fits into recessed panel **86** and insulates the switches and any electrical wiring and connections (not shown) from probe **50** (not shown). In a preferred embodiment, there are two switches **72**, **74**. However, it is possible that these switches may be combined into a single switch or that a third or more switches may be added to control remotely other functions of control unit **100**.

Referring to FIG. 8, housing **212** of control unit **100** has a power button **102**, a plurality of holes **104**, preferably three, for operatively receiving a three prong plug of cable **12**, a receiver **106** for operatively receiving a plug connected to probe **50**, and a digital display **130**. Housing **212** also has a button **108**, which is preferably a push button, that initiates the ten second count time period, a light **110** that lights during the ten second period, a calibration indicator **112**, and a battery charge indicator light **114**. Housing **212** also has a volume control knob **116**, a plurality of volume indicators **118**, preferably light indicators, a knob to deactivate an internal threshold and window pre-set for technetium **99** to permit setting a wider window, a light indicator **122** for the

internal threshold, and an audio range knob **124** to change the audio range from among the three values indicated by lights **126**, **128** and **130**. Referring to FIGS. **6** and **8**, when switch **72** of switch assembly **70** is activated, button **108** is activated and, thus, light **110** is activated. When switch **74** is activated to download or record a count, an audible signal is provided.

FIGS. **9** and **10** show a movable stand **200** suitable for use with radiation detection apparatus **10** of the present invention. Stand **200** has an upper vertical shaft **202** telescopically seated with a lower vertical shaft **204**. Shaft **204** is mounted at its bottom end onto the hub of a plurality of radially outwardly extending legs **206** supported on rotatable wheels **208**. Shaft **202** is held at a desired height by an adjustable restrainer **205** on the top end of shaft **204**. The upper end of shaft **202** has an adjustable fastener **210** mounted thereon. Fastener **210** has a horizontal shaft (not shown) onto which the lower end **211** of a bracket **214** is rotatably mounted. A housing **212** of control unit **100** is secured to bracket **214**. Bracket **214** and housing **212** can be tilted up and down to a desired angle about the shaft of fastener **210** and held at the desired angle by tightening threaded bolt **215**.

Lower shaft **204** preferably has a pair of holders **220** mounted thereon. Each holder **220** has a pair of spaced, vertically disposed opposed holding members **222** adapted, e.g. shaped, to receive and releasably hold probe **50**. Each holder **220** is positioned within a protective box **224** having a cover **226**. Lower shaft **204** preferably has a support **228** for supporting cable **12** for probe **50**. Onto the rear of lower shaft **204**, there is preferably fixedly mounted the lower end of an elongated bracket **230**. Bracket **230** has a platform **232** welded or otherwise fixed thereto. Platform **232** preferably is for supporting an auxiliary component such as a computer (not shown). The side of housing **212** has an angularly disposed rectangular cavity at **234** for holding and accessing the replaceable rechargeable battery (not shown) to supply power to control unit **100**.

The present invention having been thus described with particular reference to the preferred forms thereof, it will be obvious that various changes and modifications may be made therein without departing from the spirit and scope of the present invention as defined in the appended claims.

What is claimed is:

1. A radiation detection apparatus comprising:

means for counting a scintillation count value;

means for outputting a scintillation count value to a utilization device;

a hand-held probe including a scintillation detector; means for connecting said probe to said counting means;

first means positioned on said probe for, in a first state, remotely causing said counting means to accumulate a first scintillation count over a first period and, in a second state, remotely causing said counting means to accumulate a second scintillation count over a second period, said second period being longer than said first period;

a display, which, in response to said second state of said first means, operates to display said second scintillation count for a preset period; and

second means positioned on said probe for causing, upon activation, said output means to manifest an accumulated scintillation count from said counting means, wherein an activation of said second means during said preset time period causes said output means to manifest said second scintillation count, and a lack of activation of said second means during said preset time period causes said counting means to accumulate a scintillation count over said first period.

2. The radiation detection apparatus as recited in claim 1, wherein said first and second means are mounted on a carrier that is removably positioned on and that electrically isolates said first and said second means from said probe.

3. The radiation detection apparatus as recited in claim 1, wherein said second period is about ten seconds.

4. The radiation detection apparatus as recited in claim 1, wherein said first period is about one second.

5. The radiation detection apparatus as recited in claim 1, wherein said activation of said second means is operative, at times other than during said preset time period, to cause said count means to accumulate scintillation counts for differing time periods.

6. The radiation apparatus as recited in claim 1, wherein said preset time period is about three seconds.

7. The radiation detection apparatus as recited in claim 1, wherein said radiation detection apparatus is adapted to receive an exchangeable, rechargeable battery.

8. The radiation detection apparatus as recited in claim 1, wherein said output means downloads to a utilization device through an electrically isolating interface that precludes reverse signal transfer from said utilization device.

\* \* \* \* \*