



US006243234B1

(12) **United States Patent**
Haddock et al.

(10) **Patent No.:** **US 6,243,234 B1**
(45) **Date of Patent:** ***Jun. 5, 2001**

(54) **DISK DRIVE INCLUDING SLIDER WITH CONTACT EDGE AND RECESSED READ TRANSDUCER**

(75) Inventors: **Quinn Haddock**, Longmont; **Patrick R. Wacker**, Louisville, both of CO (US)

(73) Assignee: **Maxtor Corporation**, Longmont, CO (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

5,418,667	5/1995	Best et al.	360/103
5,455,730	10/1995	Dovek et al.	360/113
5,499,149	3/1996	Dovek	360/103
5,535,073	7/1996	Brezoczky et al.	360/105
5,650,892	7/1997	Dorius et al.	360/103
5,673,156	9/1997	Chen et al.	360/97.01
5,734,519	3/1998	Fontana, Jr. et al.	360/97.01
5,768,055	6/1998	Tian et al.	360/103
5,771,570	6/1998	Chhabra et al.	29/603.06
5,822,153	10/1998	Lairson et al.	360/104
5,872,685	2/1999	Park et al.	360/103
5,898,542	4/1999	Koshikawa et al.	360/103
5,909,340	6/1999	Lairson et al.	360/104
5,982,583	11/1999	Strom	360/103
5,991,119	11/1999	Boutaghou et al.	360/103
5,995,324	* 11/1999	Haddock et al.	360/103
6,128,163	* 10/2000	Haddock et al.	360/237.1

FOREIGN PATENT DOCUMENTS

11-066518	* 3/1999	(JP) .
11-273035	* 10/1999	(JP) .

* cited by examiner

Primary Examiner—William Klimowicz
(74) *Attorney, Agent, or Firm*—David M. Sigmond

(57) **ABSTRACT**

A method of design of a magnetic recording slider and sensor geometry is disclosed which allows a magneto-resistive recording element to achieve a significantly reduced physical and magnetic spacing with a rigid magnetic recording disk in a disk drive, without resulting in thermal transients caused by sensor/disk contacts. The method utilizes pseudo-contact slider technology with an intentionally recessed MR sensor pole tip and alumina region. The reduced spacing achieved by pseudo-contact recording is significant compared to the spacing loss incurred by the proposed precision of the MR recording element, resulting in a net reduction in head medium magnetic spacing.

76 Claims, 3 Drawing Sheets

Related U.S. Application Data

(63) Continuation of application No. 09/350,491, filed on Jul. 9, 1999, now Pat. No. 6,128,163, which is a continuation of application No. 09/083,700, filed on May 21, 1998, now Pat. No. 5,995,324.

(51) **Int. Cl.**⁷ **G11B 21/21**; G11B 17/32; G11B 5/60


(52) **U.S. Cl.** **360/237.1**

(58) **Field of Search** 360/234.3, 234.7, 360/235.4, 235.7, 236.5, 237.1, 313

References Cited

U.S. PATENT DOCUMENTS

4,669,011	5/1987	Lemke	360/103
5,041,932	8/1991	Hamilton	360/104
5,253,232	10/1993	Akagi et al.	369/13
5,255,141	10/1993	Valstyn et al.	360/126
5,267,104	11/1993	Albrecht et al.	360/97.02






Fig. 1




Fig. 2




Fig. 3A




Fig. 3B




Fig. 3C

Fig. 4A




Fig. 4B





Fig. 4C



DISK DRIVE INCLUDING SLIDER WITH CONTACT EDGE AND RECESSED READ TRANSDUCER

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. application Ser. No. 09/350,491, filed Jul. 9, 1999 (U.S. Pat. No. 6,128,163), which is a continuation of U.S. application Ser. No. 09/083,700, filed May 21, 1998 (U.S. Pat. No. 5,995,324).

This invention relates to pseudo-contact recording, tribology and magneto-resistive heads. More particularly, to the thermal asperity effects of the disk-slider interface and the designs and methods for improving the use of magneto-resistive heads in near-contact and in-contact recording systems through intentional pole-tip rescission.

BACKGROUND OF THE INVENTION

In a conventional magnetic recording system, the rotation of the rigid magnetic disk causes a transducer or magnetic recording head to be hydrodynamically lifted above the surface of the recording medium. The hydrodynamic lifting phenomena results from the flow of air produced by the rotating magnetic disk. This airflow causes the head to "fly" above the disk surface. Of course, when the rotation of the magnetic disk stops or slows, the head element is deprived of its aerodynamic buoyancy and lands on the surface of the disk.

Magnetic heads typically comprise a rectangular slider body onto which is attached a transducer device along one portion of the slider body. Normally, sliders are made of various ceramic materials. For instance, a composition of alumina and titanium-carbide is one of the more common slider materials in use today due to its relative wear resistance. A variety of other materials have also been used as well. There are typically two types of transducers for magnetic recording, thin film or magneto-resistive (MR). Thin-film transducers can read or write. An MR transducer can only read. Hence a second thin film transducer must be used in combination with an MR transducer for full read/write capabilities.

A primary goal of hard disk drives is to provide maximum recording density in the hard disk. It has been found that the recording density that can be achieved using a magnetic recording transducer depends, in part, on the distance between the recording medium of the hard disk and the magnetic recording transducer. A related goal is to increase reading efficiency or reduce read errors, while increasing recording density. Problems associated with attaining these goals may vary depending upon whether the drive utilizes a thin film transducer for both reading and writing, or a magneto-resistive transducer for reading and a thin film head for writing.

From a writing or recording density standpoint, the transducer is ideally maintained in direct contact with the recording medium of a hard disk. Recording density decreases as the write transducer is elevated above the disk surface. By providing zero separation distance between the magnetic recording transducer of the slider and the disk, high magnetic recording densities are achieved. However, the hard disk typically spins at about or in excess of 4,000 r.p.m. and continuous direct contact between the slider and the transducer, on the one hand, and the recording medium, on the other hand, can cause unacceptable wear in both the recording medium, the slider and the transducer. Wear occurring in the recording medium can result in a loss of

data. Wear occurring in the transducer can result in complete failure of the recording transducer requiring replacement of the slider housing the transducer, as well as loss of data.

A common approach to protecting the head/disk interface from excessive wear has been to coat the surface of the disk with a liquid lubricant. However, this can create an accumulation of debris on the head, including the lubricant and dust or dirt from the surrounding environment. Accumulation of such debris around the contact surface of the head leads to signal modulation caused by particle induced fluctuations in the heads. Accumulation of debris and other particulate matter can also create a dramatic increase in the wear rate as the debris is captured in the friction zone between the slider and the disk. The presence of any liquid lubricant in the zone can magnify this effect dramatically.

To prevent undue wear of the recording medium, slider and/or transducer while still maintaining acceptable recording density, the bottom surface of the slider is typically configured as an air bearing surface (ABS). High speed rotation of the disk causes a stream of air to flow along the surface of the disk. The ABS of the slider interacts with the flow of the air causing the slider to float about the hard disk surface. Hence, while the disk is spinning and the slider is positioned adjacent to the disk, the slider floats slightly above the disk, thereby substantially eliminating wear to either the disk or to the slider.

Although the conventional ABS slider design has been effective in preventing wear of the slider and/or transducer and the recording medium, optimum recording densities have been lost due to separation between the recording medium and the magnetic recording transducer of the slider.

From the standpoint of reading data from a magnetic disk, and similar to recording, reading efficiency decreases the farther the read element is from the disk. Because the signal to noise ratio decreases with increasing distance between the transducer and the disk, moving the transducer closer to the disk increases data storage bit density. Moreover, because MR transducers are more sensitive than thin film read elements, an MR transducer will read more efficiently, with less errors, than a thin film head at the same distance above the disk.

Conventional magneto-resistive elements disposed on sliders are designed with air bearing surfaces to fly above the surface of a rigid rotating magnetic recorded disk. Current disk drives with MR heads operate at an average head disk physical spacing of approximately 40 nanometers, with distribution ranging up to 75 nanometers. This range of spacing is required to account for slider and disk drive manufacturing tolerances, such as in the actuator and disk/spindle interface, and environmental conditions such as altitude and temperature, which would cause the slider to fly too low and make contact with the rigid disk. Contact of the magneto-resistive MR sensor with the disk surface has proven to cause an undesirable thermal transient due to friction, commonly referred to as thermal asperity. Thus, unlike inductive heads which are able to tolerate disk contacts without generating signal transients, use of MR heads has required the MR heads to fly above the disk surface resulting in less efficient recording density.

Based on the foregoing, a desirable solution would be to utilize a flying MR head transducer with as little spacing as possible between the disk surface and the transducer. With flying heads, however, the height is influenced in large part by the quality of the manufacturing process. Manufacturing tolerance includes the manufacturability of components such as the crown, camber, twist, etch depths of the slider,

head-gimble interface, assembly tolerances and the very process of stacking and swaging parts together. If a precise suspension and alignment mechanism is required, such as with the transducer spaced only a few nanometers above the disk surface, the overall mechanical tolerances of various components must be correspondingly more precise. Such precision would be not only mechanically difficult, but exceedingly expensive.

The present invention removes sensitivities due to manufacturability by placing the slider in contact with the disk but recessing the MR transducer pole-tip. In this manner, precisely controlled mechanical flying is not necessary and increased recording and reading efficiencies due to head/disk proximities are achieved.

OBJECTS OF THE INVENTION

It is an object of the present invention to utilize pseudo-contact slider technology with MR sensor technology, to achieve reduced magnetic spacing without generating detrimental thermal asperities.

SUMMARY OF THE INVENTION

In one embodiment of the present invention, the intentional recession of the MR sensor pole-tip and surrounding alumina matrix are recessed from the plane of the air bearing surface on the order of 5–15 nanometers. This recession can be produced with conventional slider lapping and cleaning techniques. The recession of the pole-tip and the surrounding alumina will cause the slider contact point, which, is in contact with a recording medium, to move forward of the MR sensor. Because the sensor area will not be in contact with the disk surface, thermal transients will be eliminated or significantly reduced. Thermal transients and variations are insulated from the MR sensor by the slider body material or other insulating materials deposited on the slider in front of the MR sensor. Slider pitch angle, dynamic pitch response and slider crown are designed such that the slider contact point remains in front of the MR sensor on the slider body material under all tolerance conditions. In this manner, reading errors will decrease and reading efficiency will increase, without incorporating expensive mechanical design and manufacturing solutions.

Another embodiment of the present invention is to recess only the sensor region, leaving the alumina region planar with the air bearing surface. The contact point can be on the alumina at the extreme trailing edge.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a bottom surface view of a slider of the present invention.

FIG. 2 is a side view of a slider of the present invention which is in contact with a recording medium.

FIG. 3A is a perspective view of a slider of the present invention having a relatively flat shaped configuration.

FIG. 3B is a perspective view of a slider of the present invention having a relatively semicylindrical-shaped configuration.

FIG. 3C is a perspective view of a slider of the present invention having a relatively bowl-shaped configuration.

FIG. 4A is a bottom view of a slider of the present invention having a relatively flat shaped configuration.

FIG. 4B is a bottom view of a slider of the present invention having a relatively semicylindrical-shaped configuration.

FIG. 4C is a bottom view of a slider of the present invention having a relatively bowl-shaped configuration.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The present invention provides a method and apparatus for improving the use of magnetic-resistive heads in pseudo-contact and in-contact recording systems through intentional transducer recession. The present invention is particularly useful in a hard disk drive system which uses a magneto-resistive head to read information from a magnetic disk.

The present invention will be described with regard to the accompanying drawings in FIGS. 1–4C which assist in illustrating various features of the invention. In one embodiment of the present invention, a slider **10** for positioning a transducer **14** relative to a recording medium **18** is provided. The slider **10** comprises an air-bearing surface (ABS) **22** having a recessed portion **42** adjacent to a trailing edge **30**, a contact portion **46** disposed in front of the recessed portion **42**, a leading edge **26** located opposite the trailing edge **30**, and a magneto-resistive transducer **14** which is disposed within the recessed portion **42**. The magneto-resistive transducer **14** is disposed at the recessed portion **42** such that when the contact portion **46** is in contact with the recording medium **18**, and the magneto-resistive transducer **14** is spaced above the recording medium **18**. The recessed portion **42**, facing a rotating recording medium **18**, can be intentionally produced using any of the known methods including conventional slider lapping and cleaning techniques, polishing and sputter etching.

The slider **10** is made of a various ceramic materials. A composition of alumina and titanium-carbide is one of the more common slider materials in use today due to its relative wear resistance. This wear resistance property of alumina and titanium-carbide ceramic material can be used in the air-bearing surface of the slider **10** having a contact portion **46**; however, this wear-resistance property also makes it more difficult to produce a recessed portion **42** in the ABS of the slider **10**. One can achieve having both wear-resistance property in a contact portion **46** and the ability to relatively easily introduce a recessed portion **42** by having the slider **10** that is composed of at least two different materials. For example, the contact portion **46** of the slider **10** can be composed of a wear-resistant ceramic composition such as alumina-titanium-carbide, silicon carbide or a deposited film of carbon. Whereas, the portion of the ABS **22** which ultimately forms the recessed portion **42** can comprise ceramic composition which can be selectively removed, for example, alumina.

The slider is designed such that the contact portion **46** remains in front of the transducer **14** on the slider. To prevent excessive wear caused by the constant contact between the contact portion **46** and the recording medium **18**, the contact portion **46** is composed of a wear-resistant material as discussed above. In addition, the recording medium **18** can be coated with a lubricant to reduce the friction.

Positioning the transducer **14** at a recessed portion **42** allows the transducer (e.g., a magneto-resistive (MR) recording element) to achieve a predictable and significantly reduced physical and magnetic spacing with a rigid recording medium without resulting in thermal asperities. Preferably the recessed portion **42** is from about 5 nm to about 15 nm. This spacing prevents the transducer **14** from physically coming in contact with the recording medium **18**. In addition, because the invention utilizes a contact or pseudo-contact slider, the spacing is achieved without having to

employ expensive manufacturing and assembly techniques. Moreover, the present invention eliminates or reduces manufacturing tolerances.

The spacing between the transducer **14** and the recording medium **18** is determined by many factors such as a slider pitch angle, a dynamic pitch response, and a slider crown. Any of these factors can be adjusted to achieve a desired spacing between the recording medium **18** and the transducer **14**.

A slider pitch angle refers to the angle formed between the recording medium **18** and the slider **10**. A steep slider pitch angle requires a relatively deeper recession to avoid having the transducer **14** coming in contact with the recording medium **18**, whereas a small slider pitch angle requires smaller recession. A typical slider pitch angle is from about 100 microradians to about 400 microradians, more preferably from about 150 microradians to about 200 microradians, and most preferably from about 150 microradians to about 160 microradians. In a particularly useful embodiment, the slider pitch angle is about 150 microradians.

The ABS **22** of the slider **10** can be of any shape. Exemplary shapes of the ABS **22** of the slider **10** which are useful for the present invention are shown in FIGS. **3A-3C**, and they include a relatively flat, semicylindrical-shaped, and bowl-shaped configurations, respectively. Preferably the ABS is bowl-shaped or semicylindrical-shaped. When the ABS **22** is bowl-shaped or semicylindrical-shaped, the leading edge **26** of the slider **10** is raised above the plane of the recording medium when the slider **10** is at rest. This height **50** is called a "slider crown". (See for example, FIGS. **3B** and **3C**). Preferably the slider crown **50** is from about 50 nm to about 75 nm, for a 50% form factor slider. And the slider crown **50** is from about 30 nm to about 50 nm for a 30% form factor slider. A form factor slider refers to de facto industry standard slider configuration having a dimension of 0.159 inch (length) \times 0.125 inch (width) \times 0.034 inch (height).

Since the recording mechanism of the present invention does not involve a direct contact between the transducer **14** and the recording medium **18**, thermal transients are eliminated, or significantly reduced to the extent that thermal variations are insulated from the transducer by the slider body material, or other insulating materials which can be deposited before the transducer **14**. Useful insulating materials include alumina.

Unlike other currently available pole-tip recessed sliders, the slider **10** of the present invention is not designed to "fly" above the recording medium **18** when the recording medium is rotated by a spin motor means. But rather the contact portion **46** of the slider **10** is designed to be in a pseudo-contact with the recording medium **18**, i.e., the slider **10** actually contacts the recording medium **18** for a significant amount of time even when the recording medium **18** is spinning. It will be appreciated that this contact can be continuous or it can be intermittent due to a various factors such as the surface texture of the recording medium **18**. This contact between the slider **10** and the recording medium **18** results in a significant reduction of height variation between the transducer **14** and the recording medium **18** compared to a flying head recording mechanisms. The height variation between the slider **10** and the recording medium **18** in the present invention is reduced by at least about 50% compared to a non-contact recording head, more preferably at least about 60%, and most preferably at least about 75%. Alternatively, the height between the slider **10** and the recording medium is preferably about 0.6 microinches (μ in),

more preferably about 0.4 μ in, and most preferably about 0.2 μ in. And because the slider **10** does not fly above the recording medium **18**, the recording system of the present invention is significantly less sensitive to gram load, altitude, and static attitude compared to flying head recording mechanisms.

The spinning recording medium **18** creates an air movement around the slider **10** which can cause the slider to be lifted above the recording medium **18**. To prevent this "flying" of the slider **10**, the slider contact force is kept at a level such that a significant amount of contact is maintained between the slider **10** and the recording medium **18** during the normal operation of the recording system. For a recording system having the recording medium spinning at about 5400 rpm, the slider contact force is from about 100 mg to about 500 mg, more preferably from about 100 mg to about 300 mg, and most preferably from about 100 mg to about 200 mg.

The amount of friction between the contact point **46** of the slider **10** and the recording medium **18** can affect the amount of heat that is generated which can cause loss of data in the recording medium **18**. In addition, high friction between the contact point **46** and the recording medium **18** results in more power consumption by the recording system. The amount of friction generated by sliding the contact point **46** across the surface of the recording medium **18** is a function of a coefficient of friction. Preferably the coefficient of friction is from about 0.3 to about 1.0, more preferably from about 0.3 to about 0.6, and most preferably from about 0.3 to about 0.4.

The slider **10** can have one or more side rails **34** that extend substantially from the leading edge **26** to the trailing edge **30**. Although the side rails **34** are represented in FIG. **1** as being a straight edge, it can be any variety of shape such as a curve or a zig-zag shape.

The slider **10** can also have a center rail **52** that extends substantially from the leading edge **26** to the trailing edge **30**. The design of the air-bearing surface is selected such that the air-bearing surface does not generate an excess amount of lift when the recording medium **18** is spinning. This helps maintain pseudo-contact of the slider with the recording medium **18**. In a particularly useful embodiment of the present invention the slider **10** has two side rails **34** and a center rail **52**.

By reducing the effective distance between the MR head and the recording medium, the present invention provides a recording system that has a high signal to noise ratio.

The slider **10** can also have a thin film transducer (e.g., an inductive head) to allow writing of magnetic information on the recording medium **18**. Presence of both MR-head and a thin film transducer provides a magnetic recording system which can read and write desired information on the recording medium.

The foregoing description of the present invention has been presented for purposes of illustration and description. Furthermore, the description is not intended to limit the invention to the form disclosed herein. Consequently, variations and modifications commensurate with the above teachings, and the skill or knowledge of the relevant art, are within the scope of the present invention. The embodiment described hereinabove is further intended to explain the best mode known for practicing the invention and to enable others skilled in the art to utilize the invention in such, or other, embodiments and with various modifications required by the particular applications or uses of the present invention. It is intended that the appended claims be construed to include alternative embodiments to the extent permitted by the prior art.

What is claimed is:

1. A disk drive, comprising:
a recording medium; and
a slider that includes a leading edge, a trailing edge opposite said leading edge, an air bearing surface between said leading and trailing edges, a recess that faces said recording medium and is contiguous with said trailing edge, a contact portion, and a read transducer disposed within said recess, wherein said contact portion consists essentially of a contact edge of said slider, said contact portion maintains a significant amount of contact with said recording medium and is the only portion of said slider that contacts said recording medium during read and write operations associated with said recording medium, and said read transducer is spaced from said recording medium during read and write operations associated with said recording medium.
2. The disk drive of claim 1, wherein said contact portion is devoid of a write transducer.
3. The disk drive of claim 1, wherein said slider includes a write transducer and said contact portion excludes said write transducer.
4. The disk drive of claim 1, wherein said contact between said contact portion and said recording medium is intermittent.
5. The disk drive of claim 1, wherein said contact between said contact portion and said recording medium is continuous.
6. The disk drive of claim 1, wherein said contact between said contact portion and said recording medium occurs for a significant amount of time during read and write operations associated with said recording medium.
7. The disk drive of claim 1, wherein said contact between said contact portion and said recording medium occurs during read and write operations associated with said recording medium.
8. The disk drive of claim 1, wherein said slider does not fly above said recording medium during read and write operations associated with said recording medium.
9. The disk drive of claim 1, wherein said recess has a flat upper surface contiguous with said trailing edge.
10. The disk drive of claim 1, wherein said air bearing surface is semicylindrical-shaped.
11. The disk drive of claim 1, wherein said air bearing surface is bowl-shaped.
12. The disk drive of claim 1, wherein said air bearing surface includes first and second side rails with trailing portions spaced from said trailing edge that provide at least part of said contact portion.
13. The disk drive of claim 1, wherein said air bearing surface includes a center rail with a trailing portion spaced from said trailing edge that provides at least part of said contact portion.
14. The disk drive of claim 1, wherein said air bearing surface includes first and second side rails and a center rail each with trailing portions spaced from and parallel to said trailing edge that provide said contact portion.
15. The disk drive of claim 1, wherein said recess extends across all of said contact portion and all of said trailing edge.
16. The disk drive of claim 1, wherein said recess extends between and is contiguous with said leading and trailing edges.
17. The disk drive of claim 1, wherein said recess has a flat upper surface that faces said recording medium and said read transducer is embedded in and aligned with and contiguous with said flat upper surface.

18. The disk drive of claim 1, wherein said recess is formed by slider lapping and cleaning.
19. The disk drive of claim 1, wherein said recess is formed by polishing.
20. The disk drive of claim 1, wherein said recess is formed by sputter etching.
21. A disk drive, comprising:
a recording medium;
a spin motor for rotating said recording medium; and
a slider that includes a leading edge, a trailing edge opposite said leading edge, an air bearing surface between said leading and trailing edges, a recess that faces said recording medium and is contiguous with said trailing edge, a contact portion contiguous with said recess, and a read transducer disposed within said recess, wherein said contact portion consists essentially of a contact edge of said slider that is substantially traverse to a direction of motion of said recording medium that is proximate thereto, said contact portion is the only portion of said slider that contacts said recording medium during read and write operations of said disk drive, said contact portion does not fly above said recording medium during read and write operations of said disk drive, and said read transducer is spaced from said recording medium during read and write operations associated with said recording medium.
22. The disk drive of claim 21, wherein said contact portion maintains a significant amount of contact with said recording medium during read and write operations associated with said recording medium.
23. The disk drive of claim 21, wherein said contact portion contacts said recording medium a significant amount of time during read and write operations associated with said recording medium.
24. The disk drive of claim 21, wherein said contact portion intermittently contacts said recording medium during read and write operations associated with said recording medium.
25. The disk drive of claim 21, wherein said contact portion continually contacts said recording medium during read and write operations associated with said recording medium.
26. A disk drive, comprising:
a disk for storing information;
a spin motor for rotating said disk; and
a slider that includes a leading edge, a trailing edge opposite said leading edge, side edges between said leading and trailing edges, an air bearing surface between said leading and trailing edges and between said side edges, a recess that faces said disk and is contiguous with said trailing edge, a contact portion between said side edges that consists essentially of a contact edge substantially parallel to said trailing edge and contiguous with said recess, and a read transducer disposed within said recess, wherein said contact portion is the only portion of said slider in contact or pseudo-contact with said disk and said read transducer is spaced from said disk as said read transducer reads information from said disk while said disk is rotating during read and write operations associated with said disk.
27. The disk drive of claim 26, wherein said contact portion maintains a significant amount of contact with said disk as said read transducer reads information from said disk while said disk is rotating during read and write operations associated with said disk.

28. The disk drive of claim 26, wherein said contact portion contacts said disk a significant amount of time as said read transducer reads information from said disk while said disk is rotating during read and write operations associated with said disk.

29. The disk drive of claim 26, wherein said contact portion intermittently contacts said disk as said read transducer reads information from said disk while said disk is rotating during read and write operations associated with said disk.

30. The disk drive of claim 26, wherein said contact portion continually contacts said disk as said read transducer reads information from said disk while said disk is rotating during read and write operations associated with said disk.

31. A disk drive, comprising:

a recording medium;

a pseudo-contact slider, including

an air bearing surface directed to face said recording medium;

a leading edge;

a trailing edge located opposite said leading edge;

a recess contiguous with said trailing edge;

a contact edge such that a significant amount of contact is maintained between said contact edge and said recording medium without significant contact between any other portion of said slider and said recording medium during read and write operations associated with said recording medium; and

a read transducer disposed in said recess such that when said contact edge is in contact with said recording medium, said read transducer is spaced above said recording medium.

32. The disk drive of claim 31, wherein said read transducer is spaced from about 5 nm to about 15 nm above said recording medium when said recording medium is spinning in operation.

33. The disk drive of claim 31, wherein said slider further comprises two side edges and two side rails along said air bearing surface disposed substantially near each of said two side edges.

34. The disk drive of claim 31, wherein said slider further comprises a center rail that extends along said air bearing surface from essentially said leading edge along the length of said slider.

35. The disk drive of claim 31, wherein said recess has a flat upper surface that extends across all surface area of said recess.

36. The disk drive of claim 31, wherein said slider further comprises an insulation contiguous with said read transducer.

37. A hard disk drive, comprising:

a recording medium;

a spin motor for rotating said recording medium; and

a pseudo-contact slider that includes a leading edge, a trailing edge, an air bearing surface, a contact portion, a read transducer, a write transducer, and a recess contiguous with the trailing edge, wherein said read transducer is disposed in the recess, said contact portion excludes said read transducer and said write transducer, and a contact edge of said contact portion and no other portion of said slider maintains a significant amount of contact with said recording medium during reading and writing operations associated with said recording medium, and said read transducer is spaced above said recording medium during said reading and writing operations.

38. The disk drive of claim 37, wherein said contact portion is disposed in front of said recessed portion.

39. The disk drive of claim 37, wherein said slider further comprises a center rail and two side rails extending on both sides of said center rail substantially from said leading edge of said slider to said trailing edge of said slider.

40. The disk drive of claim 37, wherein said slider is constructed from a first material, said read transducer is disposed in a matrix of a second material at said trailing edge of said slider, and said first and second materials have different characteristics.

41. The disk drive of claim 40, wherein said first material is selected from the group consisting of alumina-titanium carbide, and silicon carbide.

42. The disk drive of claim 40, wherein said second material is selected from the group consisting of alumina, carbon and a mixture thereof.

43. The disk drive of claim 37, wherein said read transducer is spaced from about 5 nm to about 15 nm from the plane of said air bearing surface of said slider.

44. The disk drive of claim 37, wherein said contact between said contact edge and said recording medium is substantially continuous.

45. The disk drive of claim 37, wherein said slider does not fly above said recording medium when said recording medium is spinning.

46. A disk drive, comprising:

a recording medium; and

a slider that includes a leading edge, a trailing edge opposite said leading edge, an air bearing surface between said leading and trailing edges, a recess that faces said recording medium and is contiguous with said trailing edge, a contact edge contiguous with said recess, a read transducer disposed within said recess, and a write transducer, wherein said contact edge maintains a significant amount of contact with said recording medium and no other portion of said slider maintains a significant amount of contact with said recording medium, and said read and write transducers are spaced from said recording medium when said recording medium is spinning during read and write operations associated with said recording medium.

47. The disk drive of claim 46, wherein said contact edge is a front edge of said recess opposite said trailing edge.

48. The disk drive of claim 46, wherein said contact edge is said trailing edge.

49. The disk drive of claim 46, wherein said contact edge is a single continuous edge.

50. The disk drive of claim 49, wherein said single continuous edge is substantially perpendicular to a direction of motion of said recording medium where said contact edge contacts said recording medium.

51. The disk drive of claim 46, wherein said contact edge includes at least two spaced edges.

52. The disk drive of claim 51, wherein said spaced edges are substantially perpendicular to a direction of motion of said recording medium where said contact edge contacts said recording medium.

53. The disk drive of claim 46, wherein said contact between said contact edge and said recording medium is intermittent.

54. The disk drive of claim 46, wherein said contact between said contact edge and said recording medium is substantially continuous.

55. The disk drive of claim 46, wherein said contact between said contact edge and said recording medium occurs for a significant amount of time when said recording medium is spinning.

11

56. The disk drive of claim 46, wherein said slider does not fly above said recording medium when said recording medium is spinning.

57. The disk drive of claim 46, wherein said recess has a flat upper surface contiguous with said trailing edge. 5

58. The disk drive of claim 46, wherein said air bearing surface is semicylindrical-shaped.

59. The disk drive of claim 46, wherein said air bearing surface is bowl-shaped.

60. The disk drive of claim 46, wherein said air bearing surface includes first and second side rails with trailing portions spaced from said trailing edge, and said contact edge includes said trailing portions. 10

61. The disk drive of claim 46, wherein said air bearing surface includes a center rail with a trailing portion spaced from said trailing edge, and said contact edge includes said trailing portion. 15

62. The disk drive of claim 61, wherein said contact edge is said trailing portion.

63. The disk drive of claim 46, wherein said air bearing surface includes first and second side rails and a center rail each with trailing portions spaced from and parallel to said trailing edge, and said contact edge includes said trailing portions. 20

64. The disk drive of claim 63, wherein said contact edge is said trailing portions. 25

65. The disk drive of claim 46, wherein said recess extends across all of said contact and trailing edges.

66. The disk drive of claim 46, wherein said recess extends between and is contiguous with said leading and trailing edges. 30

67. The disk drive of claim 46, wherein a slider pitch angle between said slider and said recording medium when said recording medium is spinning during said read and write operations is from about 100 microradians to about 400 microradians. 35

68. The disk drive of claim 67, wherein said slider pitch angle is from about 150 microradians to about 200 microradians.

69. The disk drive of claim 68, wherein said slider pitch angle is from about 150 microradians to about 160 microradians. 40

70. The disk drive of claim 69, wherein said slider pitch angle is about 150 microradians.

71. A disk drive, comprising: 45

a disk for storing data;

a spin motor for rotating said disk; and

12

a slider that includes a leading edge, a trailing edge opposite said leading edge, an air bearing surface between said leading and trailing edges, a recess that faces said disk and is contiguous with said trailing edge, a contact portion that consists essentially of a contact edge contiguous with said recess and is devoid of a write transducer, and a read transducer disposed within said recess for reading information from said disk, wherein said contact portion maintains a significant amount of contact with said disk and no other portion of said slider maintains a significant amount of contact with said disk and said read transducer is spaced from said disk during read operations from said disk.

72. The disk drive of claim 71, wherein said contact portion consists of said contact edge.

73. The disk drive of claim 71, wherein said air bearing surface includes first and second side rails and a center rail each with trailing portions spaced from and parallel to said trailing edge, and said contact edge consists of said trailing portions.

74. The disk drive of claim 71, wherein said significant amount of contact is substantially continuous contact.

75. The disk drive of claim 71, wherein a slider pitch angle between said slider and said disk when said disk is rotating during said read operations is from about 100 microradians to about 400 microradians.

76. A disk drive, comprising:

a disk for storing data;

a spin motor for rotating said disk; and

a slider that includes a leading edge, a trailing edge opposite said leading edge, an air bearing surface between said leading and trailing edges, a recess that faces said disk and is contiguous with said trailing edge, a contact portion that consists of a contact edge contiguous with said recess and is devoid of a write transducer, and a read transducer disposed within said recess for reading information from said disk, wherein said contact portion maintains substantially continuous contact with said disk and no other portion of said slider maintains substantially continuous contact with said disk and said read transducer is spaced from said disk as said disk rotates and said read transducer reads data from said disk.

* * * * *