



US006250706B1

(12) **United States Patent**
Davis, Jr. et al.

(10) **Patent No.:** **US 6,250,706 B1**
(45) **Date of Patent:** **Jun. 26, 2001**

(54) **INTEGRATED FLAT CABLE CONNECTOR**

(75) Inventors: **Joseph J. Davis, Jr.**, Ortonville; **David A. Hein**, Sterling Heights, both of MI (US)

(73) Assignee: **Lear Corporation**, Southfield, MI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/518,994**

(22) Filed: **Mar. 3, 2000**

Related U.S. Application Data

(60) Provisional application No. 60/149,323, filed on Aug. 17, 1999.

(51) **Int. Cl.**⁷ **H01R 11/05; B62D 25/14**

(52) **U.S. Cl.** **296/70; 174/72 A**

(58) **Field of Search** **296/70; 174/72 A, 174/72 TR; 439/34**

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,416,497	11/1983	Brandsness et al.	339/17 F
4,522,114	6/1985	Matsuno	98/2.09
4,650,925	3/1987	Coldren	174/135
4,815,984	3/1989	Sugiyama et al.	439/211
5,297,334 *	3/1994	Johnson	29/861
5,309,634 *	5/1994	Van Order et al.	29/863
5,324,203	6/1994	Sano et al.	439/34
5,460,530	10/1995	Toba et al.	439/34
5,549,344	8/1996	Nishijima et al.	296/70
5,709,358 *	1/1998	Kubota	248/27.1
5,735,041	4/1998	Zaguskin et al.	29/857

5,841,070 *	11/1998	Takiguchi et al.	174/72 A
5,846,091 *	12/1998	Nishijima et al.	439/34
5,856,908	1/1999	Takiguchi et al.	361/690
5,877,936	3/1999	Nishitani et al.	361/600
5,883,777 *	3/1999	Nishitani et al.	361/647
5,931,682 *	8/1999	Takiguchi et al.	439/34
6,048,020 *	4/2000	Gronowicz et al.	396/70
6,095,272 *	8/2000	Takiguchi et al.	180/90

FOREIGN PATENT DOCUMENTS

195 21 887
A1 12/1996 (DE) .

OTHER PUBLICATIONS

International Search Report, Dec. 20, 2000.

* cited by examiner

Primary Examiner—D. Glenn Dayoan


Assistant Examiner—Paul Chenevert

(74) *Attorney, Agent, or Firm*—Brooks & Kushman P.C.

(57) **ABSTRACT**

A cross-car beam for providing structural support for an instrument panel. The cross-car beam includes a primary wire harness for carrying electrical power to a plurality of electrical components housed within the instrument panel, a secondary wire harness having a secondary connector block connected thereto, and a primary connector block affixed to the cross-car beam adjacent the primary wire harness for mating with the secondary connector block. In this manner the secondary wire harness is electrically connected to the primary wire harness. Additionally, the secondary connector block has a plurality of electrical terminals for electrically contacting a plurality of conductors disposed on the primary wire harness.

14 Claims, 4 Drawing Sheets






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6

INTEGRATED FLAT CABLE CONNECTOR**CROSS-REFERENCE TO RELATED APPLICATION**

This application claims the benefit of U.S. Provisional Application Ser. No. 60/149,323, filed Aug. 17, 1999.

TECHNICAL FIELD

The present invention relates to flat copper cables, and to connectors for communicating electrical signals to a plurality of electrical devices.

BACKGROUND ART

Typically, instrument panels house a plurality of electrical components, such as engine gauges, air conditioning controls, radios, lighters, glove box lights and the like. These electrical devices must provide power by a wire harness packaged within the instrument panel. Generally, a wire harness is made with a plurality of pigtailed having an electrical connector disposed at one end for connecting to an electrical device, such as one referenced above.

As the electrical devices increase in the instrument panel so does the complexity of the wire harness. More complex wire harnesses are generally larger leading to larger assembly costs, weight, and more difficult to package. Typically, the same wire harness is used over a similar series of vehicles. Therefore, a vehicle having only a few of the myriad of options available may contain a complex wire harness which is under utilized.

Accordingly, a need exists for a new improved means for connecting electrical devices to a flat copper cable wire harness. The new and improved means must eliminate unutilized wire harness cable while provide a quick and easy means to connect additional cable to the wire harness.

DISCLOSURE OF INVENTION

Accordingly, an object of the present invention is to provide an instrument panel having a wire harness connector affixed thereto for connecting a secondary wire harness to a primary wire harness.

In accordance with this and other objects, the present invention provides a new and improved instrument panel for use in an automobile. The instrument panel has a cross-car beam which provides structural support for the instrument panel, a primary wire harness for carrying electrical power to a plurality of electrical components housed within the instrument panel, a secondary wire harness having a secondary connector block connected thereto, a primary connector block affixed to the cross-car beam adjacent the primary wire harness for mating with the secondary connector block. In this manner, the secondary wire harness is electrically connected to the primary wire harness. The secondary connector block has a plurality of electrical terminals for electrically contacting a plurality of conductors disposed on the primary wire harness. The present invention provides a means to easily electrically connect a secondary wire harness to a primary wire harness.

In accordance with another aspect of the present invention the primary and secondary wire harnesses are preferably a flat copper cable.

In accordance with still another aspect of the present invention the primary connector block is integrally molded to the cross-car beam.

In accordance with still another aspect of the present invention the cross-car beam further comprises a front panel and a back panel.

In accordance with still another aspect of the present invention the primary connector block is integrally molded to the front panel of the instrument panel.

In accordance with still another aspect of the present invention the primary connector block is a male connector end.

In accordance with still another aspect of the present invention the secondary connector block is a female connector end.

In accordance with yet another aspect of the present invention a cross-car beam for providing structural support for an instrument panel is provided. The cross-car beam includes a primary wire harness for carrying electrical power to a plurality of electrical components housed within the instrument panel, a secondary wire harness having a secondary connector block connected thereto, and a primary connector block affixed to the cross-car beam and adjacent the primary wire harness for mating with the secondary connector block. In this manner, the secondary wire harness is electrically connected to the primary wire harness. Additionally, the secondary connector block has a plurality of electrical terminals for electrically contacting a plurality of conductors disposed on the primary wire harness.

The above features, benefits and advantages and other features, benefits and advantages of the present invention are readily apparent from the following detailed description of the best mode for carrying out the invention when taken together with the accompanying drawings.

BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is a perspective view of an instrument panel configured to attach to an interior of an automobile and having a primary wire harness for communicating electrical signals to a plurality of electrical components packaged within the instrument panel, in accordance with the present invention;

FIG. 2 is a perspective view of an instrument panel configured to attach to an interior of an automobile and having a primary wire harness, and a secondary wire harness connected thereto for communicating electrical signals to a plurality of electrical components packaged within the instrument panel, in accordance with the present invention;

FIG. 3 is an enlarged view of the primary connector block, as shown in FIG. 2, affixed to the cross-car beam and further depicting the secondary connector block attached to the secondary wire harness, in accordance with the present invention;

FIG. 4 is a cross sectional view of FIG. 3 illustrating the engagement of the primary connector block with the secondary connector block and the contact between the terminals of the secondary connector block and the conductors on the primary wire harness, in accordance with the present invention;

FIG. 5 is a perspective view of an integrated connector, in accordance with another aspect of the present invention; and

FIG. 6 is a cross-sectional view of the integrated connector at a location indicated in FIG. 5, in accordance with the present invention.

BEST MODE FOR CARRYING OUT THE INVENTION

Referring now to FIG. 1, an instrument panel assembly is generally indicated by reference numeral 10. Instrument panel 10 includes a top panel 12, a cross-car beam 14, a front panel 16, and a center stack 18. Top panel 12 is configured

to attach to cross-car beam **14** and front panel **16** to enclose the myriad of electronic devices housed within the instrument panel **12**. Center stack **18** typically holds a stereo and may include an ashtray **11** and lighter **13**. Center stack **18** is configured to meet with the top panel **12** and front panel **16** in order to provide a unified instrument panel appearance.

To provide electrical power, as well as a medium for transmitting control signals to and from the myriad of electronic devices contained within the instrument panel a wire harness **20** is provided. Wire harness **20** is preferably a flat copper cable comprised of copper on Mylar. Wire harness **20** generally runs longitudinally across the cross-car beam **14** from a driver's end **22** to a passenger end **24** of the instrument panel **10**.

Preferably, a connector block **26** is integrally molded to the cross-car beam **14** and provides one half of an electrical connector for communicating power and electrical signals from wire harness **20** to a particular electrical device housed within the instrument panel **10**.

Referring now to FIG. 2, instrument panel **10** is shown with wire harness **20** attached to the cross-car beam **14**, and having a plurality of wire harness pigtailed in electrical communication therewith, in accordance with the present invention. As illustrated, wire harness pigtailed **30** generally comprise connector ends **32** and **34**. Connector ends **32** and **34** are disposed at either end of a flat copper cable. Wire harness pigtailed **30** preferably are comprised of copper conductors on a Mylar sheet material. Wire harness pigtailed **30** at their female connector ends **32** make electrical contact with wire harness **20** by contacting copper traces or conductors on wire harness **20**. The details of this connection will be disclosed in more detail below.

Referring now to FIG. 3, male connector end **26** integrally molded with cross-car beam **14** is illustrated, in accordance with the present invention. Wire harness **20** as shown is disposed or lays over top of male connector **26** and is prevented from moving transversely by end posts **40** and **42**. In operation, female connector **32** is positioned between the end posts **40** and **42** and is pushed onto male connector **26** sandwiching wire harness **20** therebetween. A plurality of connector terminals **44** of female connector **28** make electrical contact with the plurality of copper traces or conductors **50** on wire harness **20** thereby electrically connecting a secondary wire harness with the primary wire harness. Of course other electrical connections for connecting similar secondary wire harnesses to the primary wire harness can be made anywhere along the primary wire harness. Thus, the present invention provides a wire harness assembly which is extremely flexible. Moreover, the wire harness of the present invention may be configured in numerous ways as dictated by instrument panel design and electrical component content.

Referring now to FIG. 4, female connector **28** is shown mated with male connector **26**, in accordance with the present invention. When female connector **28** has engaged male connector **26** proper alignment of terminals **44** on conductors **50** is achieved by the guidance of female connector **28** provided by posts **40** and **42**. More specifically, wire harness **20** is prevented from moving transversely with respect to male connector **26** and accordingly female connector **28** is prevented from moving transversely with respect to male connector **26** by the contact of a connector surface of female connector **28** with posts **40** and **42**. After female connector **28** is fully engaged with male connector **26** the wire harness pigtail **30** is able to communicate electrical signals to an electrical component attached to the

instrument panel. As mentioned above, integrally formed male connectors **26** may be positioned anywhere along the cross-car beam to provide quick and easy connection of an electrical component to the primary wire harness.

In accordance with another aspect of the invention, an integrated connector **60** is illustrated in FIGS. 5 and 6. FIG. 5 is a side elevation of connector **60** and FIG. 6 is a cross-sectional view through connector **60** at the location indicated on FIG. 5. Integrated connector **60** has a female connector portion **62** which snaps and locks onto a male connector portion **64**. Female connector portion is integrally molded to back panel **66** of cross-car beam **14** and male connector portion **64** is integrally molded to front panel **68** of the cross-car beam **14**. This is done so that back panel **66** may be made out of ABS with poly-carbonate or similar material to form a living hinge **70**, while front panel **68** may be made out of a less expensive material or a material having different material properties. Female connector portion **62** is shown in an open position as indicated by reference letter A and in a closed position as indicated by reference letter B.

In operation wire harness **20** is loaded onto male connector portion **64**. Female connector portion **62** having electrical connector terminal and a secondary wire harness (not shown) connected thereto is then rotated about living hinge **70** and positioned over top off male connector portion **64**. Female connector portion **62** further includes a clasp **72** which cooperates with a tab **74** to removably secure the female connector portion **62** to the male connector portion **64**. When female connector portion **62** snaps down onto male connector portion **64** and clasp **72** engages tab **74** wire harness **20** is in electrical communication with the secondary wire harness.

As indicated in FIG. 6 a flap **78** is integrally formed with female connector portion **62** to protect wire harness **20**. Flap **78** may be as long as desired covering only a portion of wire harness **20** or the entire length of wire harness **20**.

Accordingly, it is readily apparent from the above disclosure that the present invention offers many advantages and benefits over the prior art. For example, the present invention eliminates additional parts by integrating a male connector end into a cross-car beam. Moreover, the present invention reduces wire harness complexity by providing a quick and easy means to electrically connect to a wire harness. Further, the present invention allows vehicle designers to use one wire harness design for a variety of vehicles containing different accessory options.

While embodiments of the invention have been illustrated and described, it is not intended that these embodiments illustrate and describe all possible forms of the invention. Rather, the words used in the specification are words of description rather than limitation, and it is understood that various changes may be made without departing from the spirit and scope of the invention.

What is claimed is:

1. An instrument panel for use in a vehicle, comprising:
 - a cross-car beam for providing structural support for the instrument panel;
 - a primary wire harness for carrying electrical power to a plurality of electrical components housed within the instrument panel;
 - a secondary wire harness having a secondary connector block connected thereto, wherein the secondary connector block has a plurality of electrical terminals for electrically contacting a plurality of conductors disposed on the primary wire harness; and
 - a primary connector block integrally molded to the cross-car beam and adjacent the primary wire harness for

5

directly mechanically mating with the secondary connector block to electrically connect the primary wire harness to the secondary wire harness.

2. The instrument panel of claim 1, wherein the primary wire harness is a flat copper cable.

3. The instrument panel of claim 1, wherein the secondary wire harness is a flat copper cable.

4. The instrument panel of claim 1, wherein the cross-car beam further comprises a front panel and a back panel.

5. The instrument panel of claim 4, wherein the primary connector block is integrally molded to the front panel.

6. The instrument panel of claim 1, wherein the primary connector block is a male connector end.

7. The instrument panel of claim 1, wherein the secondary connector block is a female connector end.

8. A cross-car beam for providing structural support for an instrument panel, comprising:

a primary wire harness for carrying electrical power to a plurality of electrical components housed within the instrument panel;

a secondary wire harness having a secondary connector block connected thereto, wherein the secondary con-

6

connector block has a plurality of electrical terminals for electrically contacting a plurality of conductors on the primary wire harness; and

a primary connector block integrally molded to the cross car beam and adjacent the primary wire harness for directly mechanically mating with the secondary connector block to electrically connect the primary wire harness to the secondary wire harness.

9. The cross-car beam of claim 8, wherein the primary wire harness is a flat copper cable.

10. The cross-car beam of claim 8, wherein the secondary wire harness is a flat copper cable.

11. The cross-car beam of claim 8, wherein the primary connector block is integrally molded to the cross car beam.

12. The cross-car beam of claim 8, wherein the cross car beam further comprises a front panel and a back panel.

13. The cross-car beam of claim 8, wherein the primary connector block is a male connector end.

14. The cross-car beam of claim 8, wherein the secondary connector block is a female connector end.

* * * * *